THE AUGMENTED IMAGE PRIOR: DISTILLING 1000 CLASSES BY EXTRAPOLATING FROM A SINGLE IMAGE

Figure 1: **Extrapolating from one image.** Strongly augmented patches from a single image are used to train a student (S) to distinguish semantic classes, such as those in ImageNet. The student neural network is initialized randomly and learns from a pretrained teacher (T) via KL-divergence. Although almost none of target categories are present in the image, we find student performances of $>66\%$ for classifying ImageNet's 1000 classes. In this paper, we develop this single datum learning framework and investigate it across datasets and domains.

ABSTRACT

What can neural networks learn about the visual world when provided with only a single image as input? While any image obviously cannot contain the multitudes of all existing objects, scenes and lighting conditions – within the space of all $256^{3 \cdot 224 \cdot 224}$ possible 224-sized square images, it might still provide a strong prior for natural images. To analyze this "augmented image prior" hypothesis, we develop a simple framework for training neural networks from scratch using a single image and augmentations using knowledge distillation from a supervised pretrained teacher. With this, we find the answer to the above question to be: 'surprisingly, a lot'. In quantitative terms, we find accuracies of $94\%/74\%$ on CIFAR-10/100, 69% on ImageNet, and by extending this method to video and audio, 51% on Kinetics-400 and 84% on SpeechCommands. In extensive analyses spanning 13 datasets, we disentangle the effect of augmentations, choice of data and network architectures and also provide qualitative evaluations that include lucid "panda neurons" in networks that have never even seen one.

1 INTRODUCTION

Deep learning has both relied and improved significantly with the increase in dataset sizes. In turn, there are many works that show the benefits of dataset scale in terms of data points and modalities used. Within computer vision, these models trained on ever larger datasets, such as Instagram-1B (Mahajan et al., 2018) or JFT-3B (Dosovitskiy et al., 2021), have been shown to successfully distinguish between semantic categories at high accuracies. In stark contrast to this, there is little research on understanding neural networks trained on *very small* datasets. Why would this be of any interest? While smaller dataset sizes allow for better understanding and control of what the model is being trained with, we are most interested in its ability to provide insights into fundamental aspects of learning: For example, it is an open question as to what exactly is required for arriving at semantic visual representations from random weights, and also of how well neural networks can extrapolate from their training distribution.

While for visual models it has been established that few or no real images are required for arriving at basic features, like edges and color-contrasts (Asano et al., 2020; Kataoka et al., 2020; Bruna & Mallat, 2013; Olshausen & Field, 1996), we go far beyond these and instead ask what the minimal data requirements are for neural networks to learn *semantic categories*, such as those of ImageNet.

This approach is also motivated by studies that investigate the early visual development in infants, which have shown how little visual diversity babies are exposed to in the first few months whilst developing generalizeable visual systems (Orhan et al., 2020; Bambach et al., 2018). In this paper, we study this question in its purest form, by analyzing whether neural networks can learn to extrapolate from a single datum.

However, addressing this question naïvely runs into the difficulties of i) current deep learning methods, such as SGD or BatchNorm being tailored to large datasets and not working with a single datum and ii) extrapolating to semantic categories requiring information about the space of natural images beyond the single datum. In this paper, we address these issues by developing a simple framework that recombines *augmentations* and *knowledge distillation*.

First, augmentations can be used to generate a large number of variations from a single image. This can effectively address issue i) and allow for evaluating the research question on standard architectures and datasets. This use of data augmentations to generate variety is drastically different to their usual use-case in which transformations are generated to implicitly encode desirable invariances during training.

Second, to tackle the difficulty of providing information about semantic categories in the single datum setting, we opt to use the outputs of a supervisedly trained model in a knowledge distillation (KD) fashion. While KD (Hinton et al., 2015) is originally proposed for improving small models' performance by leveraging what larger models have learned, we re-purpose this as a simple way to provide a supervisory signal about semantic classes into the training process.

We combine the above two ideas and provide both student and teacher only with augmented versions of a single datum, and train the student to match the teacher's imagined class-predictions of classes – almost all of which are not contained in the single datum, see Fig. 1. While practical applications do result from our method – for example we provide results on single image dataset based model compression in the Appendix – our goal in this paper is analyzing *the fundamental question* of how well neural networks trained from a single datum can extrapolate to semantic classes, like those of CIFAR, SpeechCommands, ImageNet or even Kinetics.

What we find is that despite the fact that the resulting model has only seen a single datum plus augmentations, surprisingly high quantitative performances are achieved: *e.g.* 74% on CIFAR-100, 84% on SpeechCommands and 66% top-1, single-crop accuracy on ImageNet-12. We further make the novel observations that our method benefits from high-capacity student and low-capacity teacher models, and that the source datum's characteristics matter – random noise or less dense images yield much lower performances than dense pictures like the one shown in Figure 1.

In summary, in this paper we make these four main contributions:

1. A minimal framework for training neural networks with a single datum using distillation.
2. Extensive ablations of the proposed method, such as the dependency on the source image, augmentations and network architectures.
3. Large scale empirical evidence of neural networks' ability to extrapolate on > 12 vision and audio datasets.
4. Qualitative insights on what and how neural networks trained with a single image learn.

2 RELATED WORK

The work presented builds on top of insights from the topics of knowledge distillation and single- and no-image training of visual representations and yields insights into neural networks' ability to extrapolate.

Distillation. In the original formulation of knowledge distillation (KD), the goal is to train a typically lower capacity ("student") model from a pretrained ("teacher") model in order to surpass the performance of solely training with a label-supervised objective. KD has also been explored extensively to train more performant and, or compressed student models from the soft-target predictions of teacher models (Ba & Caruana, 2014; Hinton et al., 2015; Gou et al., 2021; Furlanello et al., 2018; Czarnecki et al., 2017). Similarly, other approaches have also been developed to improve transfer from teacher to student, including sharing intermediate layers' features (Romero et al., 2014), spatial attention transfer (Zagoruyko & Komodakis, 2016b), similarity preservation between activations of

the networks (Tung & Mori, 2019), and contrastive distillation (Tian et al., 2020a). KD has also been shown to be an effective approach for learning from noisy labels (Li et al., 2017). More recently, Beyer et al. (2022) conducted a comprehensive empirical investigation to identify important design choices for successful distillation from large-scale vision models. In particular, they show that long training schedules, paired with consistent augmentations (including *MixUp*) for both student and teacher, result in better performances.

Without the training data. Distilling knowledge without access to the original training dataset was originally proposed in 2017 (Lopes et al., 2017) and first experiments of leaving out single MNIST classes from the training data were shown in (Hinton et al., 2015). Yet, this paradigm is gaining importance as many recent advancements have been made possible due to extremely large proprietary datasets that are kept private. This has lead to either the sole release of trained models (Radford et al., 2021; Ghadiyaram et al., 2019; Mahajan et al., 2018) or even more restricted access to only the model outputs via APIs (Brown et al., 2020). While the original work (Lopes et al., 2017), still required activation statistics from the training dataset of the network, more recent works do not require this "meta-data". These approaches are typically generation based (Chen et al., 2019; Ye et al., 2020; Micaelli & Storkey, 2019; Yin et al., 2020) and *e.g.* yield datasets of synthetic images that maximally activate neurons in the final layer of teacher. Related to this, there are works which conduct "dataset" distillation, where the objective is to distill large-scale datasets into much smaller ones, such that models trained on it reach similar levels of performance as on the original data. These methods generate synthetic images (Wang et al., 2018; Radosavovic et al., 2018; Liu et al., 2019; Zhao & Bilen, 2021; Cai et al., 2020), labels (Bohdal et al., 2020), or both (Nguyen et al., 2021), but due to their meta-learning nature have only been successfully applied to small-scale datasets. In contrast to GAN- and inversion-based methods, as well as to dataset distillation, our approach does not require the knowledge of the weights and architecture of the teacher model, and instead works with black-box "API"-style teacher models and much smaller "datasets" of just a single datum plus augmentations. This paper follows a radically different goal: We are interested in *analysing* the potential of extrapolating from a single image to the manifold of natural images, for which we choose KD as a well-suited and simple tool.

Prior knowledge in deep learning. Finally, this work is related to several works which have analysed the infusion of prior knowledge to the training process. For example the prior knowledge contained in neural network architectures (Ulyanov et al., 2018) or image augmentations (Xiao et al., 2020). In this work, we instead view a single image as a "prior" for all other natural images, which to the best of our knowledge has not been explored.

3 METHOD

We believe that simplicity is the key to demonstrating and analysing the question of how far a single image can take us. We are inspired by recent work of Asano et al. (2020), which "patchifies" a single-image using augmentations, and the knowledge distillation method presented by Beyer et al. (2022) and our technical contribution lies in unifying them to develop a *single-image distillation* framework.

i. Dataset generation. In (Asano et al., 2020), a single "source" image is augmented many times to generate a static dataset of fixed size. This is done by applying the following augmentations in sequence: cropping, rotation and shearing, and color jittering. For this, we follow their official implementation[1], and do not change any hyperparameters. We do however analyze the choice of source images more thoroughly by additionally including a random noise, and a Hubble-telescope image to our analysis. In addition, we also conduct experiments on audio classification. For generating a dataset of augmented audio-clips, we apply the set of audio-augmentations from (Bitton & Papakipos, 2021), which consist of operations, such as random volume increasing, background noise addition and pitch shifting to yield log-Mel spectrograms from raw waveforms (see Appendix for complete details).

ii. Knowledge distillation. The knowledge distillation objective is proposed in (Hinton et al., 2015) to transfer the knowledge of a pretrained teacher to a lower capacity student model. In this

---

[1] https://github.com/yukimasano/single_img_pretraining

Table 1: **Distilling dataset.** 1 image + augmentations $\approx$ almost 50K in-domain CIFAR-10/100 images. Here, both teacher and student are WideR40-4 networks.

	Distillation dataset			Accuracy	
Name	# Images	# Pixels	Size (MB)	C10	C100
CIFAR-10	50K	51M	145	95.26	76.29
CIFAR-100	50K	51M	145	94.51	78.06
CIFAR-10	10K	10M	29	94.58	72.95
Ours	1	2.8M	0.27	94.14	73.80

Table 2: **Comparison to other datasets.** Teacher model is WideR40-2 and student is WideR40-1 as in (Micaelli & Storkey, 2019).

Data	**C10**
CIFAR-10	92.61
Fractals	33.26
StyleGAN	83.42
ZeroSKD	86.60
Ours	89.27

case, the optimization objective for the student network is a weighted combination of dual losses: a standard supervised cross-entropy loss and a "distribution-matching" objective that aims to mimic the teacher's output. However, in our case there are no class-labels for the patches generated from a single image, so we solely use the second objective formulated as a Kullback–Leibler (KL) divergence between the student output p^s and the teacher's output p^t:

$$\mathcal{L}_{\text{KL}} = \sum_{c \in \mathcal{C}} -p_c^t \log p_c^s + p_c^t \log p_c^t \tag{1}$$

where c are the teachers' classes and the outputs of both student and teacher are temperature τ flattened probabilities, $p = \texttt{softmax}(l/\tau)$, that are generated from logits l.

For training, we follow (Beyer et al., 2022) in employing a function matching strategy, where the teacher and student models are fed consistently augmented instances, that include heavy augmentations, such as *MixUp* (Zhang et al., 2018) or *CutMix* (Yun et al., 2019). However, in contrast to (Beyer et al., 2022), we neither have access to TPUs nor can train 10K epochs on ImageNet-sized datasets. While both of these would likely improve the quantitative results, we believe that this handicap is actually blessing in disguise: This means that the results we show in this paper are not specific to heavy-compute, or extremely large batch-sizes, but instead are fundamental.

4 EXPERIMENTS

4.1 IMPLEMENTATION DETAILS

Source data. For the source data, we utilize the single images of (Asano et al., 2020), except for one image, which we replace by a similar one as we could not retrieve its licence. These images are of sizes up to 2,560x1,920 (the "City" image of Fig. 1). For the audio experiments, we use two short audio-clips from Youtube, a 5mins BBC newsclip, as well as a 5mins clip showing 11 Germanic languages. Images and audio visualizations, sources and licences are provided in Appendix A.

Tasks. For simplicity, we focus on classification tasks here and provide results on a sample application of single-image based model compression in Appendix B.9. For our ablations and small-scale experiments we focus on CIFAR-10/100 (Krizhevsky et al., 2009). For larger-scale experiments using 224×224 sized images we evaluate our method on datasets with varying number of classes (see Table 7) an additionally conduct experiments in the audio domain (see Table 5) and video (see Table 6). Further implementation details are provided in Appendix C.

4.2 ABLATIONS

1-image vs full training set. We first examine the capability to extrapolate from one image to small-scale datasets, such as CIFAR-10 and CIFAR-100. In Table 1, we compare various datasets for distilling a teacher model into a student. We find that while distillation using the source dataset always works best (95.26% and 78.06%) on CIFAR-10/100, using a single image can yield models which almost reach this upper bar (94.1% and 73.8%). Moreover, we find that one image distillation even outperforms using 10K images of CIFAR-10 when teaching CIFAR-100 classes even though these two datasets are remarkably similar. To better understand why using a single image works, we next disentangle the various components used in the training procedure: (a) the source image, (b)

Table 3: **Ablations of single image distillation.** We analyze key components in our experimental setup. We report top-1 accuracies for CIFAR-10/100. For the teacher we use WideR40-4 and for the student a WideR16-4 and train for 1K epochs.

Distillation dataset		Accuracy	
Image	# Pixels	C10	C100
"Noise"	4.9M	69.30	19.50
"Universe"	4.8M	88.18	39.68
"Bridge"	1.1M	92.24	57.87
"City"	4.9M	93.13	64.85
"Animals"	2.8M	93.28	66.12

(a) **Distilling image.** Content of source image matters.

	Accuracy	
Signal	C10	C100
Full	93.32	68.69
Top-5	92.98	64.72
Argmax	91.89	60.75

(b) **Teacher signal.** Even with only top-5, or hard distillation, performance only slightly degrades.

Augmentations				Accuracy	
Hflip.	RCrop.	MixUp	CutMix	C10	C100
✓	✓			89.34	55.05
✓		✓		91.03	58.24
✓			✓	92.86	64.26
✓	✓	✓		92.41	63.50
✓	✓		✓	93.32	68.69

(c) **Varying Augmentation.** More helps, CutMix is important.

Figure 2: **CIFAR-100 accuracies for varying source images.** Setting as in 3a.

the generated image dataset size and (c) the augmentations used during distillation, corresponding to Tables 3a and 3c.

Choice of single image. From Table 3a, we find that the choice of source image content is crucial: Random noise or sparser images perform significantly worse compared to the denser "City" and "Animals" pictures. We compare 23 further images in Fig. 2 and find that distillation quality roughly correlates with the density in images and JPEG sizes. This is in contrast to self-supervised pretraining of (Asano et al., 2020), suggesting that the underlying mechanisms are different.

Varying loss functions. In Table 3b, we show that the student can learn even with much degraded learning signals. For example even if it receives only the top-5 predictions or solely the argmax prediction (*i.e.* a hard label) of the teacher without any confidence value, the student is still able to extrapolate at a significant level ($> 91\%/60\%$ for CIFAR-10/100). Even at ImageNet scale, the performance remains at a high 43.8% top-1 accuracy (see Appendix B.3). This also suggests that copying models solely from API outputs is possible, similar to (Orekondy et al., 2019). We also evaluated L1 and L2 distillation functions (see Table 9 for details) and found that these perform slightly worse. This echoes the finding of (Tian et al., 2020a) that standard KD loss of Eq. (1) is actually a strong baseline hence use this in the rest of our experimental analysis.

Augmentations. In Table 3c, we ablate the augmentation we use during knowledge distillation. Besides observing the general trend of "more augmentations are better", we find that *CutMix* performs better than MixUp on our single-image distillation task. This might be because in our case the model is tasked with learning how to extrapolate towards real datapoints, while MixUp is derived and therefore might be more useful for interpolating *between* (real) data samples (Zhang et al., 2018; Beyer et al., 2022).

Comparison to synthetic datasets. In Table 2, we find that there is something unique about using a single image, as our method outperforms several synthetic datasets, such as FractalDB Kataoka et al. (2020), randomly initialized StyleGAN Baradad et al. (2021), as well as the GAN-based approach of (Micaelli & Storkey, 2019). This is despite the fact that these synthetic datasets contain ~ 50K images. We provide insights on the characteristics of this 1-image dataset in Section 4.4.

Table 4: **Distilling various architectures** on CIFAR-10/100. We compare student accuracy when distilling with full training set vs our 1-image dataset

	Teacher	Acc.	Student	Acc.	Distillation Full	Ours	$\Delta < 5\%$
CIFAR10	VGG-19	93.28	VGG-16	92.42	92.84	92.14	✓
	ResNet-56	93.77	ResNet-20	92.52	92.29	90.70	✓
	WideR40-4	95.42	WideR40-4	95.42	94.36	94.14	✓
	WideR16-4	95.20	WideR40-4	95.42	94.30	94.02	✓
CIFAR100	VGG-19	70.79	VGG-16	73.26	71.19	58.66	✗
	ResNet-56	70.99	ResNet-20	65.74	67.04	52.43	✗
	WideR40-4	78.14	WideR40-4	78.14	75.54	73.80	✓
	WideR16-4	78.14	WideR40-4	75.56	76.29	74.08	✓

Table 5: **Distilling audio representations.** 1 audio clip $+$ augmentations provide stronger supervisory signal for the student to distill teacher's knowledge.

			Distillation		
Dataset	Categories (#Classes)	Teacher	Full	Ours$_A$	Ours$_B$
MUSAN (Snyder et al., 2015)	Generic sounds (3)	98.76	96.78	89.85	96.28
Voxforge (MacLean, 2018)	Languages (6)	91.13	89.04	72.85	78.47
Speech Commands (Warden, 2018)	Keywords (12)	95.15	94.86	82.90	84.19
LibriSpeech (Panayotov et al., 2015)	Speakers (100)	99.89	99.54	78.67	84.12

Next, using the insights gained in this section, we scale the experiments towards other network architectures, dataset domains and dataset sizes.

4.3 GENERALISATION

Architectures   In Table 4, we experiment with different common architectures on CIFAR-10 and CIFAR-100. On CIFAR-10, we find that almost all architectures perform similarly well, except for the case of ResNet-56 to ResNet-20 which could be attributed to the lower capacity of the student model. We find that the distillation performance of WideR40-4 to WideR40-4 on CIFAR-10 is very close to distilling from original source data; achieving accuracy of 94.14% and only around one-percentage point lower than supervised training. This analysis shows that our method generalizes to other architectures hints that larger capacity student models might be important for high performances.

Extension to audio.   So far, our proposed approach has shown success in distilling useful knowledge for images. To further test the generalizability of our approach on other modalities, we conduct experiments on several audio recognition tasks of varying difficulty. We perform distillation via 50K randomly generated short audio clips from two (*i.e.* Ours$_A$ and Ours$_B$), 5mins YouTube videos (see Appendix A for more details). In Table 5, we compare the results against the performance of the teacher model and distilling directly using source dataset. We find that even for audio, distilling with merely a single audio clip's data provides enough supervisory signal to train the student model to reach above 80% accuracy in the majority of the cases. In particular, we see significant improvement in distillation performance when a single audio has a wide variety of sounds to boost accuracy on challenging Voxforge dataset from 72.8% to 78.4%. Our results on audio recognition tasks demonstrate the modality agnostic nature of our approach and further highlight the capability to perform knowledge distillation in the absence of large amount of data.

Extension to video.   We conduct further experiments on video action recognition tasks. As distillation data, we generate simple pseudo-videos of 12 frames that show a linear interpolation of two crop locations at taken at the beginning and end for the City image and use X3D video architectures (Feichtenhofer, 2020) as teachers and students, see Appendix B.1 for further details. In Table 6, we find that our approach indeed generalizes well to distilling video models with performances of 75.2% and 51.8% on UCF-101 (Soomro et al., 2012) and K400 (Carreira & Zisserman, 2017)–despite the fact that the source data is not even a real video.

Table 6: **Scaling to video.** Student models are trained from scratch. Top-1 accuracy is shown with 10-temporal center-cropped clips per video. Details in Appendix B.1

Dataset	Teacher	**Distill**
UCF-101	90.4	75.2
K400	67.8	51.8

Figure 3: **Output confidence scores.** Temperature-scaled softmax scores of the predicted classes for 5K patches and the 5K CIFAR-10 validation set images.

Table 7: **Larger scale datasets.** Teacher is ResNet-18 and student is varied between ResNet-50 and ResNet-50x2. Students are trained from scratch. Gap to teacher in brackets for ResNet-50x2.

			1-Image-Distill	
Dataset	**Categories (#Classes)**	**Teacher (R18)**	→R18	→R50x2
STL-10 (Coates et al., 2011)	Generic objects (10)	96.3	93.9	95.0 (-1.3)
ImageNet-100 (Tian et al., 2020b)	Objects (100)	89.6	84.4	88.5 (-1.1)
Flowers (Nilsback & Zisserman, 2006)	Flower types (102)	87.9	81.5	83.8 (-4.1)
Places (Zhou et al., 2017)	Scenes (365)	54.0	50.3	53.1 (-0.9)
ImageNet (Deng et al., 2009)	Objects (1000)	69.5	66.2	69.0 (-0.5)

4.4 SCALABILITY TO LARGE-SCALE DATASETS AND MODELS

From this section on, we scale our experiments to larger models utilizing 224×224-sized images, and evaluate these on various vision datasets.

Varying datasets. In Table 7 we find that, overall, a single image is not enough to fully recover the performance on more difficult datasets. This might be because of the fine-grained nature of these datasets, *e.g.* ImageNet includes more than 120 kinds of dogs and Flowers contains 102 types of flowers. Nevertheless, we find a surprisingly high accuracy of 66% on ImageNet's validation set, even though this dataset comprises 1000 classes, and the student only having seen heavily augmented crops of a single image. In Table 8, we conduct further analyses on distilling ImageNet models.

Patchification vs more data. At the top part of the Table 8, we analyse the effect of using original vs patchified (p) random images from the training set of ImageNet. We find that while for 10 and 100 source images, patchification improves performance, this is not the case when a larger number of images is used. This indicates that increased diversity is especially a crucial component for the small data regime, while capturing larger parts of objects becomes important only beyond this stage. We also make the surprising observation that patches from a single high-quality image ("City") obtain better performances than patches generated from 1000 ImageNet training images. To understand why this might be the case, we note that the high coherency of training patches from a single image strikingly resembles what babies see during their early visual development, *e.g.*, looking at only few toys and people but from many angles (Bambach et al., 2018; Orhan et al., 2020). It is hypothesized that this unique combination of coherence and variability is ideal for learning to recognize objects (Orhan et al., 2020).

Teacher/student architectures. In Fig. 4, we analyze the performances of varying ResNet models by depth or width. We find that overall varying the width is a more parameter-efficient way to obtain higher performances, almost reaching the teacher's 69.5% performance with a ResNet-50x2 at 69.0%.

In addition, in the bottom half of Table 8 (rows *g-m*), we find surprising results: First, in contrast to normal KD, we find that the teacher's performance is not directly related to the final student performance, *e.g.* a ResNet-50 is less well-suited for distilling than a ResNet-18 (rows *i* vs *l*).

Second, we find that the choice of source image is even more important for ImageNet classification (see rows *g-i*), as switching from the "City" even to the "Bridge" one decreases performance considerably and the Noise image does not train at all. Third, we find that the best settings are those in which the student's capacity is higher than that of the teacher (rows *i,m* and Fig. 4). In fact this

Table 8: **IN-1k distillations.** We vary distillation dataset and teacher/student configurations. '-' refers to experiments not run as their compute cost would outweigh the insights gained. (p) means images are patchified. '†' refers to models trained with half the batch size due to memory constraints.

		Setting				Epochs			
	Images	Teacher		Student	10	20	30	50	200
(a)	10x	R50	→	R50	7.6	13.3	-	-	-
(b)	10x (p)	R50	→	R50	17.2	27.3	-	-	-
(c)	100x	R50	→	R50	14.7	25.1	32.3		
(d)	100x (p)	R50	→	R50	23.6	36.1	42.8	-	-
(e)	1000	R50	→	R50	38.0	52.4	57.4	62.5	-
(f)	1000 (p)	R50	→	R50	27.1	39.4	45.2	50.9	-
(g)	1x Noise	R18	→	R50	0.1	0.1	0.1	-	-
(h)	1x Bridge	R18	→	R50	21.2	34.8	40.0	-	-
(i)	1x City	R18	→	R50	34.5	47.0	52.2	56.8	66.2
(j)	1x City	R101	→†	R101	22.4	31.4	-	-	-
(k)	1x City	R50⋆	→	R50	4.6	6.6	-	-	-
(l)	1x City	R50	→	R50	18.0	34.0	39.8	45.6	55.5
(m)	1x City	R18	→†	R50x2	46.1	55.6	59.7	63.1	69.0

Figure 4: **Effect of student architecture.** We vary the architecture of the student by depth and width. Teacher is a ResNet-18, settings as in Table 7 with half batch size.

Figure 5: **Feature space visualization.** *t*-SNE of jointly embedding random patches (·) and CIFAR-10 test set (×) instances with our model distilled to classify semantic classes. We also show example images from patches and actual validation set images (enclosed in a box). Note how most training images are contained within a small region while the network needs to extrapolate for the real images which occupy the outer regions in this plot. Best viewed zoomed-in.

R18→R50x2 setup (row *m*) obtains a performance on ImageNet-12 of 69.0% which matches the teacher's performance within 0.5%.

4.5 ANALYSIS

To better understand how our method is achieving these performances, we next analyse the learned models.

Output confidence scores. In Fig. 3, we visualize the distribution of the confidence scores of the predicted classes for student and teacher models for the training and evaluation data. We observe that the student indeed learns to mimic the teacher's predictions well for the patch training data. However, during evaluation on CIFAR images, the student model exhibits a much broader distribution of values, some with extremely high confidence scores. This might indicate that the student has learned to identify many discriminative features of object classes from the training data, which are all triggered when shown real examples, leading to much higher confidence values.

Feature space analysis. Next, we analyse the network's embedding of training patches when compared to validation-set inputs. For this, we fit a *t*-SNE (Van der Maaten & Hinton, 2008) using

Figure 6: **Visualizing neurons** via activation maximisation of final layer neurons. We compare an ImageNet supervisedly trained model against our model which has been trained with single image distillation. Best viewed zoomed-in. We provide further examples in Appendix B.5.

the features of 5K training patches and 5K test set images in Fig. 5. We find that, as expected, the training patches mapped to individual CIFAR classes do not resemble real counter parts. Moreover, we observe that all the training patches are embedded close to each other in the center, while CIFAR images are clustered towards the outside. This shows that the network is indeed learning features that are well suited for effective extrapolation.

Neuron visualizations. We next analyze a single-image distilled model trained to predict IN-1k classes. In Fig. 6, we visualize four final-layer neurons using the Lucid (Olah et al., 2017) library. When we compare neurons of the standard ImageNet supervised and our distilled model, we find that the neurons activate for very similar looking inputs. The clear neuron visualizations for "panda" or "lifeboat" (and more are provided in Appendix B.5) are especially surprising since this network was trained using only patches from the *City* Image, and has never seen any of these objects during its learning phase.

5 DISCUSSION

The augmented image prior for extrapolation. The results in this paper suggest a summary formulation as follows: *Within the space of all possible images $\mathcal{I}$, a single real image $x \in \mathcal{I}$ and its augmentations $\mathcal{A}(x)$ can provide sufficient diversity for extrapolating to semantic categories in real images.*

Limitations. In this paper, we were mainly concerned with showing that extrapolating from a single image works, empirically. Due to the limited nature of our compute resources, we have not exhaustively analyzed the choice of initial image or patchification augmentations, and longer training (as shown in (Beyer et al., 2022)) would further improve performances.

Potential negative societal impact. While our research question is of fundamental nature, one possible negative impact could be that the method is used to steal models and thus intellectual property from API providers – although in practice the performance varies especially for large-scale datasets (see Table 7).

Conclusion and outlook. In this work, we have analyzed whether it is possible to train neural networks to extrapolate to unseen semantic classes. Our quantitative and qualitative results demonstrate that our novel single-image knowledge distillation framework can indeed enable training networks from scratch to achieve high accuracies on several architectures, datasets and domains. While this paper has set out to answer the question posed in the abstract, in so doing it has raised several further research questions, such as the dependency of the source image and the target semantic classes; how networks combine features for extrapolation; and the role and informational content of augmentations; all of which we hope inspires further research.

REFERENCES

Yuki M. Asano, Christian Rupprecht, and Andrea Vedaldi. A critical analysis of self-supervision, or what we can learn from a single image. In *ICLR*, 2020. 1, 3, 4, 5, 13

Jimmy Ba and Rich Caruana. Do deep nets really need to be deep? In *NeurIPS*, volume 27, 2014. URL https://proceedings.neurips.cc/paper/2014/file/ea8fcd92d59581717e06eb187f10666d-Paper.pdf. 2

Sven Bambach, David Crandall, Linda Smith, and Chen Yu. Toddler-inspired visual object learning. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *NeurIPS*, volume 31, 2018. 2, 7, 12, 15

Manel Baradad, Jonas Wulff, Tongzhou Wang, Phillip Isola, and Antonio Torralba. Learning to see by looking at noise. *arXiv preprint arXiv:2106.05963*, 2021. 5

Lucas Beyer, Xiaohua Zhai, Amélie Royer, Larisa Markeeva, Rohan Anil, and Alexander Kolesnikov. Knowledge distillation: A good teacher is patient and consistent. *CVPR*, 2022. 3, 4, 5, 9, 14

Joanna Bitton and Zoe Papakipos. Augly: A data augmentations library for audio, image, text, and video. https://github.com/facebookresearch/AugLy, 2021. 3, 13

Ondrej Bohdal, Yongxin Yang, and Timothy Hospedales. Flexible dataset distillation: Learn labels instead of images. *arXiv preprint arXiv:2006.08572*, 2020. 3

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *NeurIPS*, volume 33, pp. 1877–1901, 2020. 3

Joan Bruna and Stéphane Mallat. Invariant scattering convolution networks. *PAMI*, 35(8):1872–1886, 2013. 1

Yaohui Cai, Zhewei Yao, Zhen Dong, Amir Gholami, Michael W Mahoney, and Kurt Keutzer. Zeroq: A novel zero shot quantization framework. In *CVPR*, pp. 13169–13178, 2020. 3

Joao Carreira and Andrew Zisserman. Quo vadis, action recognition? a new model and the kinetics dataset. In *CVPR*, pp. 6299–6308, 2017. 6

Hanting Chen, Yunhe Wang, Chang Xu, Zhaohui Yang, Chuanjian Liu, Boxin Shi, Chunjing Xu, Chao Xu, and Qi Tian. Dafl: Data-free learning of student networks. In *ICCV*, 2019. 3

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *AISTATS*, volume 15 of *Proceedings of Machine Learning Research*, pp. 215–223, Fort Lauderdale, FL, USA, 11–13 Apr 2011. PMLR. 7

Wojciech M Czarnecki, Simon Osindero, Max Jaderberg, Grzegorz Swirszcz, and Razvan Pascanu. Sobolev training for neural networks. In *NeurIPS*, 2017. 2

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, pp. 248–255. Ieee, 2009. 7

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021. 1

Christoph Feichtenhofer. X3d: Expanding architectures for efficient video recognition. In *CVPR*, pp. 203–213, 2020. 6

Tommaso Furlanello, Zachary Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born again neural networks. In *ICML*, pp. 1607–1616. PMLR, 2018. 2

Deepti Ghadiyaram, Du Tran, and Dhruv Mahajan. Large-scale weakly-supervised pre-training for video action recognition. In *CVPR*, pp. 12046–12055, 2019. 3

Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. Knowledge distillation: A survey. *IJCV*, 129(6):1789–1819, 2021. 2

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016. 14

Dan Hendrycks, Norman Mu, Ekin Dogus Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple data processing method to improve robustness and uncertainty. In *ICLR*, 2019. 6

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015. 2, 3

Hirokatsu Kataoka, Kazushige Okayasu, Asato Matsumoto, Eisuke Yamagata, Ryosuke Yamada, Nakamasa Inoue, Akio Nakamura, and Yutaka Satoh. Pre-training without natural images. *ACCV*, 2020. 1, 5

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *ICLR*, 2015. 14

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *ICML*, pp. 3519–3529. PMLR, 2019. 7, 11

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009. 4

Yuncheng Li, Jianchao Yang, Yale Song, Liangliang Cao, Jiebo Luo, and Li-Jia Li. Learning from noisy labels with distillation. In *ICCV*, pp. 1910–1918, 2017. 3

Pengpeng Liu, Irwin King, Michael R Lyu, and Jia Xu. Ddflow: Learning optical flow with unlabeled data distillation. In *AAAI*, pp. 8770–8777, 2019. 3

Raphael Gontijo Lopes, Stefano Fenu, and Thad Starner. Data-free knowledge distillation for deep neural networks. *arXiv preprint arXiv:1710.07535*, 2017. 3

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *ICLR*, 2018. 14

Ken MacLean. Voxforge. *Ken MacLean.[Online]. Available: http://www. voxforge. org/home.[Acedido em 2012]*, 2018. 6

Dhruv Mahajan, Ross Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens Van Der Maaten. Exploring the limits of weakly supervised pretraining. In *ECCV*, pp. 181–196, 2018. 1, 3

Paul Micaelli and Amos J Storkey. Zero-shot knowledge transfer via adversarial belief matching. In *NeurIPS*, pp. 9551–9561, 2019. 3, 4, 5

Thao Nguyen, Maithra Raghu, and Simon Kornblith. Do wide and deep networks learn the same things? uncovering how neural network representations vary with width and depth. In *ICLR*, 2020. 11

Timothy Nguyen, Roman Novak, Lechao Xiao, and Jaehoon Lee. Dataset distillation with infinitely wide convolutional networks. *arXiv preprint arXiv:2107.13034*, 2021. 3

Maria-Elena Nilsback and Andrew Zisserman. A visual vocabulary for flower classification. In *CVPR*, volume 2, pp. 1447–1454, 2006. 7

Chris Olah, Alexander Mordvintsev, and Ludwig Schubert. Feature visualization. *Distill*, 2(11):e7, 2017. 9

Aude Oliva and Antonio Torralba. Modeling the shape of the scene: A holistic representation of the spatial envelope. *ICCV*, 42(3):145–175, 2001. 7, 15

Bruno A Olshausen and David J Field. Emergence of simple-cell receptive field properties by learning a sparse code for natural images. *Nature*, 381(6583):607–609, 1996. 1

Tribhuvanesh Orekondy, Bernt Schiele, and Mario Fritz. Knockoff nets: Stealing functionality of black-box models. In *CVPR*, 2019. 5

Emin Orhan, Vaibhav Gupta, and Brenden M Lake. Self-supervised learning through the eyes of a child. *NeurIPS*, 33, 2020. 2, 7

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. Librispeech: an asr corpus based on public domain audio books. In *ICASSP*, pp. 5206–5210. IEEE, 2015. 6

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021. 3

Ilija Radosavovic, Piotr Dollár, Ross Girshick, Georgia Gkioxari, and Kaiming He. Data distillation: Towards omni-supervised learning. In *CVPR*, pp. 4119–4128, 2018. 3

Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014. 2

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014. 14

David Snyder, Guoguo Chen, and Daniel Povey. Musan: A music, speech, and noise corpus. *arXiv preprint arXiv:1510.08484*, 2015. 6

Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. Ucf101: A dataset of 101 human actions classes from videos in the wild. *arXiv preprint arXiv:1212.0402*, 2012. 6, 4

Marco Tagliasacchi, Beat Gfeller, Félix de Chaumont Quitry, and Dominik Roblek. Self-supervised audio representation learning for mobile devices. *arXiv preprint arXiv:1905.11796*, 2019. 14

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. *ICLR*, 2020a. 3, 5, 6

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. In *ECCV*, pp. 776–794. Springer, 2020b. 7

Frederick Tung and Greg Mori. Similarity-preserving knowledge distillation. In *ICCV*, pp. 1365–1374, 2019. 3

Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Deep image prior. In *CVPR*, pp. 9446–9454, 2018. 3

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008. 8

Tongzhou Wang, Jun-Yan Zhu, Antonio Torralba, and Alexei A Efros. Dataset distillation. *arXiv preprint arXiv:1811.10959*, 2018. 3

Pete Warden. Speech commands: A dataset for limited-vocabulary speech recognition. *arXiv preprint arXiv:1804.03209*, 2018. 6

Yuxin Wu and Kaiming He. Group normalization. In *ECCV*, pp. 3–19, 2018. 14

Tete Xiao, Xiaolong Wang, Alexei A Efros, and Trevor Darrell. What should not be contrastive in contrastive learning. In *ICLR*, 2020. 3

Jingwen Ye, Yixin Ji, Xinchao Wang, Xin Gao, and Mingli Song. Data-free knowledge amalgamation via group-stack dual-gan. In *CVPR*, pp. 12516–12525, 2020. 3

Hongxu Yin, Pavlo Molchanov, Jose M Alvarez, Zhizhong Li, Arun Mallya, Derek Hoiem, Niraj K Jha, and Jan Kautz. Dreaming to distill: Data-free knowledge transfer via deepinversion. In *CVPR*, pp. 8715–8724, 2020. 3

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *ICCV*, pp. 6023–6032, 2019. 4, 6, 14

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *BMVC*, 2016a. 14

Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. *arXiv preprint arXiv:1612.03928*, 2016b. 2

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *ICLR*, 2018. 4, 5

Bo Zhao and Hakan Bilen. Dataset condensation with differentiable siamese augmentation. In *ICML*, 2021. 3

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *PAMI*, 2017. 7

The augmented image prior: Distilling 1000 classes by extrapolating from a single image

Appendix

Table of Contents

A ADDITIONAL VISUALIZATIONS

A.1 INPUT IMAGES

Image sources and licences. From top to bottom, the images in Fig. 7 have the following licences and sources: (a): CC-BY (we created it), (b)[2] public domain (NASA) (c)[3] CC BY-SA 3.0 (by David Ball), (d)[4] pixabay licence (personal and commercial use allowed), (e)[5] personal use licence.

Images (b), (d) and (e) are identical to the ones in the repo of (Asano et al., 2020), while (a) we have recreated on our own and (c) is a replacement for a similar one whose licence we could not retrieve.

Audio source. For the experiment on audio representation distillation, we use a 5.5mins English news-clip taken from BBC about how can Europe tackle climate change[6] and a 5mins clip about 11 Germanic languages[7].

A.2 TRAINING PATCHES AND PREDICTIONS

In Fig. 8, we show several training patches as they are being used during training along-side the teacher-network's temperature-adjusted predictions. Only very few training samples can be inter-

---

[2]https://commons.wikimedia.org/wiki/File:Hubble_ultra_deep_field_high_rez_edit1.jpg
[3]https://commons.wikimedia.org/wiki/File:GG-ftpoint-bridge-2.jpg
[4]https://pixabay.com/photos/japan-ueno-japanese-street-sign-217883/
[5]https://www.teahub.io/viewwp/wJmboJ_jungle-animal-wallpaper-wallpapersafari-jungle-animal/
[6]https://www.youtube.com/watch?v=nZgD4iPapVo
[7]https://www.youtube.com/watch?v=iq2_gTETBXM

(a) The "Noise" Image. From uniform noise [0,255]. Size: 2,560x1,920, PNG: 16.3MB.

(b) The "Universe" Image. Size: 2,300x2,100, JPEG: 7.2MB.

(c) The "Bridge" Image. Size: 1,280x853, JPEG: 288KB.

(d) The "City" Image. Size: 2,560x1,920, JPEG: 1.9MB.

(e) The "Animals" Image. Size: 1,300x600, JPEG: 267KB.

Figure 7: **Single Images analysed.** Here we show the images analysed in Table 1.

Figure 8: **ImageNet training data.** Here we visualize the augmented training data used for training along with the temperature-scaled Top-5 predictions of the ImageNet pretrained ResNet-50 teacher.

preted (*e.g.* 3rd row: "nail" or "slide rule"), while for most other patches, the teacher is being very "creative".

Figure 9: **CIFAR-10 training data.** We visualize temperature scaled predictions of WideResNet-40-4 teacher on random patches generated from the Animal image (see Figure 7).

In Fig. 9, we show a similar plot for the training patches used in CIFAR-10 training. Here we show the *whole* teaching signal, and highlight the top-5 predictions of the teacher for visualization.

Finally, in Fig. 10, we show some some augmented training samples for the audio classification experiment. This figure shows how various spectrograms can be generated from a single clip by utilizing many augmentations.

B ADDITIONAL EXPERIMENTS

B.1 VIDEO ACTION RECOGNITION

We conduct further experiments on video action recognition tasks. For this we use the common UCF-101 (Soomro et al., 2012) dataset, more specifically the first split. As distillation data, we generate simple source videos of 12 frames that show a linear interpolation between two crops of

Figure 10: **Audio spectrograms.** We visualize spectrograms generated from a one second segment of the augmented audio. We generate $50K$ audio clips from a 5 minutes audio recording by randomly taking a cropped audio segment of 2 seconds and augmenting via one of the transformation functions mentioned in Section C.1. During model training, we use 1 second segment and apply MixUp augmentation that varies across batch.

(a) Source image.   (b) Patches.

Figure 11: **Satellite image patches.** We visualize random patches of size 32×32 generated from a single satellite image of Yogyakarta Airport, Indonesia. The image is of size 3846×4087 and 17MB large as a JPEG.

the City image. We generate 200K of these videos and apply AugMix (Hendrycks et al., 2019) and CutMix (Yun et al., 2019) during the distillation for additional augmentations. For the architectures we use the recent, state-of-the-art X3D architectures (Feichtenhofer, 2020) as they obtain strong performances and allow for flexible scaling of network architectures. We use a X3D-XS model as the teacher, which is trained with inputs of 160×160 and 4 frames and a temporal subsampling factor of 12. For the student model we scale this X3D-XS model in terms of width and depth by increasing the depth factor and width factor from 2.2 to 3 and 4 respectively, yielding a network with 18.1M parameters compared to 3.2M. For UCF-101 we finetune the teacher model starting from supervised Kinetics-400 (Carreira & Zisserman, 2017) pretraining, which achieves a 90.4% performance. We use a batch size of 128 per GPU on two GPUs, a learning rate of 10^{-3}, a temperature of 5, cosine learning rate schedule with a warmup of 5 epochs, with no weight decay and no dropout. As this experiment takes even longer than the image ones, we have not conducted systematic ablations on these parameters. Instead, we merely picked ones which looked promising after a few epochs but believe that even this small experimental evidence is enough to investigate to what extent these 1-image "fake-videos" can be used for learning to extrapolate.

The results are given in Table 6. We observe a performance of over 72% on UCF-101 using just a single fake-video as the training data along with the pretrained teacher. While this number is far below the state of the art or the teacher's performance, it for example outperforms CLIP's 69.8% zero-shot performance with a ViT-B16 model and shows that the student is able to extrapolate to the action classes of UCF from just one datum.

B.2 VARYING DISTILLATION LOSS FUNCTIONS

In Table 9 we compare the standard KD loss against L1 and L2 losses (using scaled logits as in the KD loss) for training the student. We find that while for CIFAR-10 the choice of the distillation method does not impact the performance, on the more difficult ImageNet dataset, there is a small difference of around -0.4% and -0.5% for L1 and L2 losses as compared to the KD loss at epoch 30. This shows firstly that our method is not dependend on a specific loss for distilling knowledge from a teacher to a student. Secondly, it shows that the standard KD loss is actually a strong baseline, as was also reported in (Tian et al., 2020a).

Table 9: **Distillation Loss Function Comparison.** We compare the distillation performance with different loss functions along with teacher and student supervised training. Results are shown for CIFAR-10 with a WideRNet40-4→WiderRNet16-4 setting and for ImageNet with R18→R50. For ImageNet we show the performance progression after 10/20/30 epochs

Data	Teacher	Student	L1	L2	KD
C10	95.4	95.2	93.3	93.4	93.4
IN-1k	69.8	76.1	36.2/45.1/51.8	25.1/45.9/51.7	34.5/47.0/52.2

B.3 IMAGENET ARGMAX EXPERIMENT

In Table 10, we compare the strength of the distillation signals. For the we compare the full distillation using KD-divergence, as reported in the paper, with a hard cross-entropy loss of the teacher's *argmax* prediction. From Table 10, we find that while training is significantly impaired and slower using this much weaker signal, the final model still reaches a relatively high 43.8% top-1 performance.

Table 10: **ImageNet argmax experiment.** Results are shown for the best setting in the main paper (R18→R50x2, row (m) of Table 8). We compare full distillation using KD-divergence with a hard cross-entropy loss of the teacher's *argmax* prediction.

Type	Setting				Epochs				
	Image	Teacher		Student	10	20	30	50	200
full	1x City	R18	$\rightarrow^\dagger$	R50x2	46.1	55.6	59.7	63.1	69.0
argmax	1x City	R18	$\rightarrow^\dagger$	R50x2	12.5	20.7	24.4	30.2	43.8

B.4 STANDARD DEVIATIONS IN PERFORMANCE

In Table 11, we report the performance of five independent runs on CIFAR-10 dataset to further highlight the robustness of our experimental results. We notice consistent accuracy scores across different training runs with minor changes of $\approx \pm 0.2$.

Table 11: Model training with different random seeds. We compare the performance of five independent runs on CIFAR-10 dataset. We use WRN40-4 as teacher and WRN16-4 as student. "Full" shows the accuracy distilling using CIFAR-10 data, and "Ours" represents distillation using random patches generated from "Animals" image.

Teacher	Student	Full	Ours
95.38 ± 0.09	94.76 ± 0.22	93.26 ± 0.17	93.38 ± 0.07

B.5 NEURON ACTIVATION MAXIMIZATIONS

In Fig. 12, we show further class-neuron activation maximization visualizations for the R50→R50 distillation experiment and compare them to the corresponding ones of the supervised teacher model. Similar to the examples in the main paper, we find that the neurons visualizations are remarkably similar.

In Fig. 13, we show further visualizations of the trained student model from the R50→R50 distillation experiment. We show five randomly chosen neurons for every layer in the ResNet.

B.6 t-SNE OF FEATURE SPACE

We visualize representations of distilled student model on CIFAR-10 validation set in order to highlight semantic relevance of the features in Fig. 14. We extract the feature from penultimate layer of WideR16-4 model for computing 2-D t-SNE embeddings. The visualization clearly highlights that distilled features contain substantial amount of semantic information to correctly differentiate between different object categories.

B.7 CENTERED KERNEL ALIGNMENT COMPARISON

In Fig. 15, we visualize similarity between different layers of the models trained in a general supervised manner and with distillation using patches of 1-image for CIFAR-10 and ImageNet datasets. We use centered kernel alignment (Kornblith et al., 2019) method to identify the resemblance of features learned with these different training approaches. We notice high similarity in representations, which reinforce our empirical evaluation that the student models indeed learn useful features required for differentiating between semantic categories.

B.8 SINGLE-IMAGE TRAINING DATA VS TODDLER DATA

In Fig. 16a, we compute the distances of GIST features (Oliva & Torralba, 2001) of 10K training images of the "City" image at resolution 256×256 in Fig. 16a. Following (Bambach et al., 2018), we L2 normalize these GIST features before computing pair-wise distances and plotting the histogram of the values. To make the comparison of our training data with the visual inputs of toddlers more concrete, we compare low-level GIST (Oliva & Torralba, 2001) features of our 1-image dataset against those computed from visual inputs of a toddler in (Bambach et al., 2018). As we do not have access to the dataset of (Bambach et al., 2018), we copy their Figure 3b for reference in Fig. 16b. While the GIST distances for ImageNet are very different with a mean around 0.75 (Bambach et al., 2018), we find that our single image dataset's distribution in Fig. 16a closely resembles that of the visual inputs of a toddler. While this is one possible explanation for why this type of data might work well for developing visual representations, further research is still required.

B.9 DATA-FREE PRUNING AND QUANTIZATION OF PRE-TRAINED MODELS

Neural network compression has been studied extensively in the literature to produce light-weight models with the objective of improving computational efficiency. In addition to knowledge distilla-

Figure 12: **Visualizing neurons** via activation maximisation of final layer neurons. We compare an ImageNet supervisedly trained model against our model which has been trained with single image distillation.

Figure 13: **Visualizing intermediate neurons** via activation maximisation. We visualize five randomly picked neurons for each layer and show their maximally responding input images.

Dataset	Model	Standard	Quantization (source)	Ours - Quantization (single-image)	Pruning (source)	Ours - Pruning (single-image)
CIFAR-10	ResNet56	93.77	93.64	93.45	93.38	93.18
	VGG11	91.57	91.22	90.97	91.14	90.86
	VGG19	93.28	92.94	93.00	92.84	92.96
	WideRNet16-4	94.81	94.40	94.59	94.76	94.43
	WideRNet40-4	95.42	95.09	94.90	95.29	94.82
CIFAR-100	ResNet56	70.99	70.89	69.85	70.74	70.42
	VGG11	69.65	69.92	68.86	69.77	69.13
	VGG19	70.79	70.60	70.21	70.89	70.56
	WideRNet16-4	75.81	75.45	74.71	75.68	75.51
	WideRNet40-4	78.14	78.27	77.60	77.94	77.78

Table 12: **Self-distillation with a single-image for efficient deep models**. We perform model compression via self-distillation using source data and 50k random patches generated from 'Animals' image for 50% sparsity (in case of pruning) and 8-bits quantization without any noticeable loss in performance.

Figure 14: **t-SNE embeddings of CIFAR-10**. We visualize t-SNE embeddings of a WideR16-4 model distilled from WideR40-4 with random patches generated from an 'Animal' image.

tion, network pruning and quantization are other well-known approaches. In the former, the goal is to remove or sparsify (zeroing-out) the network's weights based on a specific criteria, such as subset of weights with the lowest magnitude. The later is concerned with reducing precision from 32-bits floating numbers to 8-bits and even single bit as binary neural networks. In general, from practical standpoint post-training compression is largely employed in conjunction with fine-tuning to avoid accuracy drop.

Here, we study utilize our proposed single-image distillation framework for post-training model compression without using any real data. Specifically, we ask the question, whether a pre-trained model can be compressed when no in-domain data is available? To this end, we utilize Tensorflow Model Optimization Toolkit[8] to prune and quantize various pre-trained model on CIFAR-10 and CIFAR-100 datasets. We use self-distillation, where a pre-trained model acts as teacher and student clone of it is compressed during fine-tuning phase. In Table 12, we report accuracy scores for the pruned and quantized models in comparison with the standard models and those compressed using real in-domain data. In all the cases, we can notice that there is negligible loss in accuracy, i.e., $<=$ 1%, while using random patches.

Sparsity	ResNet56		VGG11		WideRNet16-4	
	C10	C100	C10	C100	C10	C100
0%	93.77	70.99	91.57	69.65	94.81	75.81
25%	93.55	70.85	91.03	69.37	94.55	75.40
50%	93.18	70.74	90.86	69.13	94.43	75.51
75%	92.68	67.87	90.54	67.81	94.10	74.05
85%	91.50	61.22	89.12	65.23	93.05	71.46

Table 13: **Varying Sparsity**. Pruning results achieved on CIFAR-10/100 for different sparsity rates using self-distillation with random patches generated from the 'Animal' image.

---

[8] https://www.tensorflow.org/model_optimization

(a) WideR16 − 4 via CIFAR-10 supervised training vs 1-image distilled.

(b) R50 via ImageNet supervised training vs 1-image distilled.

Figure 15: **Representation similarity with CKA Kornblith et al. (2019).** We visualize the similarity between supervised representations and those distilled using random patches of 1−image. As in Nguyen et al. (2020), we compute CKA for all the layers in a model using CIFAR-10 testset. The layers in the same block group shows high similarity though both models are trained in different ways, indicating that distilled features are highly similar to those learned in a supervised way.

Further, in Table 13, we vary sparsity ratio and can observe that a model can be pruned up to 75% sparsity with three-points drop in accuracy but with 25% pruning ratio the loss is merely noticeable. In Figure 17, we analyze representational similarity of pruned WideRNet16-4 model with the original trained on CIFAR-100, the diagonal entries highlight that even after 50% sparsity the representations are very similar. To summarize, with model compression use case, we barely scratched the surface of what is possible with our single-image distillation framework and we hope it will inspire further studies and applications in other domains.

C   IMPLEMENTATION DETAILS

All code will be released open-source and is attached as supplementary information to this submission.

(a) **Our 1-image dataset.**

(b) **Toddler data.** Figure from (Bambach et al., 2018).

Figure 16: **Pair-wise distances of L2-normalized GIST features** for 10K images from our 1-image training dataset used for our ImageNet experiments

Figure 17: **Representation similarity with CKA of a pruned and standard WideR16-4 models trained on CIFAR-100.**

C.1 INITIAL PATCH GENERATION

We do not tune the individual patch generation and instead adapt the procedure directly from (Asano et al., 2020)[9]. The augmentations applied to the input image of size $H \times W$ to arrive at individual patches of size $P \times P$ is (in order) as follows:

1) `RC(size=0.5*min(H,W))`

2) `RRC(size=(1.42*P), scale=(2e-3, 1))`

3) `RandomAffine(degrees=30, shear=30)`

4) `RandomVFlip(p=0.5)`

5) `RandomHFlip(p=0.5)`

6) `CenterCrop(size=(P,P))`

7) `ColorJitter(0.4,0.4,0.4,0.1, p=0.5)`

All transformations are standard operations in PyTorch: RC stands for RandomCrop, *i.e.* taking a random crop in the image with a specific size; RRC for RandomResizedCrop, *i.e.* taking a random sized crop withing the size specified in the scale tuple (relative to the input); RandomAffine for random affine transformations (rotation and shear); RandomVFlip and RandomHFlip for random flipping operations in the vertical and horizontal direction, and CenterCrop crops the image in the center to a square image of size $P \times P$. Finally, ColorJitter computes photometric jittering, where the parameters for the strengths are given in the order of brightness, contrast, saturation and hue and applied with a certain probability.

Similarly, for audio clips generation given a single audio, we use augmentation operations from (Bitton & Papakipos, 2021) with default settings. Specifically, to create a single example we apply the following procedure: we randomly crop a segment of 2-seconds, and use randomly sample an augmentation function to create transformed instances and save them in mono format. In our work, we use these augmentations, all with their default settings:

1) `add-background-noise`

2) `change-volume`

3) `clicks`

4) `clip`

5) `harmonic`

6) `high-pass-filter`

7) `low-pass-filter`

8) `normalize`

9) `peaking-equalizer`

10) `percussive`

11) `pitch-shift`

12) `reverb`

13) `speed`

14) `time-stretch`

C.2 COMPUTING LOG-MEL SPECTROGRAMS

The log-Mel spectrograms are generated on-the-fly during training from a randomly selected 1-second crop of an audio waveform as the model's input. We compute it by applying a short-time Fourier transform with a window size of 25ms and a hop size equal to 10ms to extract 64 Mel-

---

[9]https://github.com/yukimasano/single_img_pretraining

spaced frequency bins for each window. During evaluation, we average over the predictions of non-overlapping segments of an entire audio clip.

C.3 AUDIO NEURAL NETWORK ARCHITECTURE

Our audio convolutional neural network is inspired by (Tagliasacchi et al., 2019) and it consists of four blocks. We perform separate convolutions in each block with a kernel size of 4. One on the temporal and another on the frequency dimension, we concatenate their outputs afterward to perform a joint 1×1 convolution. It allows model to capture fine-grained features from each dimension and discover high-level features from shared output. We apply L2 regularization with a rate of 0.0001 in each convolution layer and also use group normalization (Wu & He, 2018). Between the blocks, we utilize max-pooling to reduce the time-frequency dimensions by a factor of 2 and use a spatial dropout rate with a rate of 0.2 to avoid over-fitting. We apply ReLU as a non-linear activation function and feature maps in the convolutions blocks are $24, 32, 64$, and 128. Finally, we aggregate the feature with a global max pooling layer which are fed into a fully-connected layer with number of units equivalent to the number of classes.

C.4 TRAINING

C.4.1 OPTIMIZATION.

For each of these datasets, we first train a teacher network in a usual supervised manner, that is then used for the distillation. For the distillation to the student model, we use a temperature $\tau = 8$ motivated by findings in (Beyer et al., 2022). We keep this temperature fixed throughout the whole of the paper due to limited compute. For optimization, we use AdamW (Loshchilov & Hutter, 2018).

C.4.2 SMALL-SCALE EXPERIMENTS

For experiments on CIFAR-10, CIFAR-100, and other smaller datasets, we use Tensorflow for running experiments on a single T4 GPU with a batch size of 512 using an Adam (Kingma & Ba, 2015) optimizer with a fixed learning rate of 0.001. We use standard augmentations including, random left right flip, and random crop. The supervised models also uses *cutout* augmentations with a cutout size of 16×16. For Mix-up, we sample α uniformly at random between zero and one. In Cut-Mix, we use a fixed value of 0.25 for α and β. With the following setup, each of the single image distillation experiment of 1K epochs took around $2 - 3$ days. The supervised and standard (using source data) distillation models are trained for 100 epochs (per epoch 2000 steps) with a batch size of 128 using SGD for optimization. For VGG (Simonyan & Zisserman, 2014) and ResNet (He et al., 2016) models, we use a learning rate schedule of $0.01, 0.1, 0.01, 0.001$ decayed at following steps $400, 32000, 48000, 64000$ with momentum of 0.9. For WideResNet (Zagoruyko & Komodakis, 2016a), we use a learning rate schedule of $0.1, 0.02, 0.004, 0.0008$ that is decayed at following steps $24000, 48000, 64000, 80000$ with Nesterov enabled.

In audio experiments, we use an Adam (Kingma & Ba, 2015) optimizer with a fixed learning rate of 0.001 and use batch size of 128 and 512 for standard models and single-clip distillation, respectively. Furthermore, we also utilize Mix-Up augmentation during our knowledge distillation experiments.

C.4.3 LARGE-SCALE EXPERIMENTS

We use PyTorch's `DistributedDataParallel` engine for running experiments on 2 A6000 GPUs in parallel with batch-sizes of 512 each. For optimization we use AdamW (Loshchilov & Hutter, 2018) with a learning rate of 0.01 and a weight-decay of 10^{-4}. These values were determined by eyeballing the results from (Beyer et al., 2022) to find a setting that might generalize across datasets, as we do not have enough compute to run hyper-parameter sweeps. With this setup, each 200 epoch experiment took around 5 days. We have also found that halving the batch-size performs equally well, and is more amenable to lower-memory GPUs. For the distillation experiments, we use Cut-Mix (Yun et al., 2019) with its default parameters of $\alpha = \beta = 1.0$.

C.5 GIST FEATURES COMPARISON

In Fig. 16a, we compute the distances of GIST features (Oliva & Torralba, 2001) of 10K training images of the "City" image at resolution 256×256 in Fig. 16a. Following (Bambach et al., 2018), we L2 normalize these GIST features before computing pair-wise distances and plotting the histogram of the values.