Contrastive Natural Language Explanations for Multi-Objective Path Planning

Abstract

This paper introduces a flexible, scalable approach that generates contrastive explanations of navigation plans based on multiple objectives. These explanations in natural language describe a robot controller's beliefs, intentions, and confidence. A new multi-objective path planning algorithm generates optimal single-objective plans, evaluates each of them with respect to the other objectives, and selects one. The objectives that favored the selected plan over the others become reasons in the explanation. Extensive evaluation in simulation demonstrates the system's ability to produce diverse, readily understandable explanations that provide counterfactual examples.

Introduction

Autonomous robots indoors must often plan paths that satisfy multiple competing objectives, such as speed and safety. To appear accountable and trustworthy to the people they encounter, these robots should offer clear but nuanced explanations of their intentions in natural language. Faced with multiple objectives, however, traditional path planners have either compromised among those objectives to select each step or relied on a mathematical combination of them hand-tuned for a particular environment. It is more difficult, however, to explain the full trajectory of such a plan to a human companion. A *contrastive* explanation provides an alternative counterfactual that may address a human questioner's concerns (Miller 2019). The thesis of this work is that humans' demonstrated preference for contrastive explanations should drive the planning process itself. This paper introduces a novel approach, where a set of single-objective planners each constructs an optimal plan and then votes to identify the plan that best addresses all of them. This enables our robot controller to advocate for its chosen plan in contrast to another through their underlying objectives. The resultant natural language explanations address the controller's beliefs, intentions, and confidence. We demonstrate this in a challenging real-world environment.

An agent's *mental model* captures the internal representations and thought processes of another agent in the same environment. Communication helps people construct a mental model of how the robot perceives and reasons about their

shared space, and thereby helps to establish trust (Kulesza et al. 2013). Questions from a person about a robot navigator's plan arise from a gap in the human's mental model of the robot or from a mismatch in their beliefs (Shvo, Klassen, and McIlraith 2020).

A single-objective plan can be justified simply by a statement of that objective (e.g., "I decided to go this way because it is the shortest path"). Such an explanation, however, does not address the questioner's reason for asking, nor does it provide any spatial context. Here, a multi-objective path planner considers several reasons to construct a plan, and uses those objectives to provide a contrastive explanation (e.g., "Although I may come close to obstacles, I'd rather go this way because it is shorter"). Moreover, the system measures a selected plan's adherence to the objectives to describe the controller's confidence in it.

The next sections provide background and related work in multi-objective path planning and Explainable AI Planning (XAIP). Subsequent sections describes *VBMO*, our voting-based multi-objective path planning approach, and the contrastive plan explanation procedure. Finally, we present empirical results and discuss future work.

Background

An optimal graph-search algorithm finds the least cost path from the robot's current location to its target's location. Typically, the algorithm exploits a weighted graph that describes navigable two-dimensional space. Such a graph G represents unobstructed locations there as vertices. An edge in G between two vertices indicates that one can move directly between them, with a label for the cost to do so. For example, if the objective were to minimize path length, labels could record the Euclidean distance between pairs of vertices. Without loss of generality, we cast optimization here as search for minimum cost.

A simple path planner $\mathcal{H}_\beta$ seeks a plan P in G that minimizes a single objective β, such as distance. A plan P is *optimal* with respect to β only if no other plan P' has a lower total cost $\beta(P)$ for that objective, that is, for every other plan $P', \beta(P) \leq \beta(P')$. Even an industrial robot, however, is subject to error. Its sensors may report inaccurately due to lighting or reflective surfaces, and its motors may produce unintended movements, particularly where surfaces are imperfect. Both kinds of errors make it difficult to maneuver

along a carefully chosen path. As a result, a path planner is often tasked with multiple objectives, such as distance and proximity to obstacles.

A *multi-objective* path planner $\mathcal{H}_B$ seeks a plan P that performs well with respect to a set B of objectives. If, for example, $B = \{\beta_1, \beta_2\}$, where β_1 is travel distance and β_2 is proximity to obstacles, $\mathcal{H}_B$ would seek a plan P that scores well on both objectives. Because objectives may conflict, no single plan is likely to be optimal with respect to all of B. Typically, a potential plan will perform better with respect to some β's and worse with respect to others.

Let $B = \{\beta_1, \beta_2, \ldots, \beta_J\}$ be a set of planning objectives with respective plan costs $\{\beta_1(P), \ldots, \beta_J(P)\}$ calculated in graphs labeled by their individual objectives. A plan P_1 *dominates* another plan P_2 ($P_1 \ll P_2$) when $\beta(P_1) \leq \beta(P_2)$ for every $\beta \in B$ and $\beta_j(P_1) < \beta_j(P_2)$ for at least one objective $\beta_j \in B$. Dominance is transitive, that is, if $P_1 \ll P_2$ and $P_2 \ll P_3$, then $P_1 \ll P_3$ (Pardalos, Migdalas, and Pitsoulis 2008). Among all possible plans, a non-dominated plan lies on the *Pareto frontier*, the set of all solutions that cannot be improved on one objective without a penalty to another objective (LaValle 2006). A typical multi-objective planner searches for plans that lie on the Pareto frontier and then an external decision maker chooses among them.

Related Work

Transparent, intelligible communication enables a robot to gain social acceptance and reduce confusion about its abilities (Rosenfeld and Richardson 2019). Although explicable, understandable behavior (e.g., (Chakraborti et al. 2019; Huang et al. 2019)) is a topic of importance, it often comes at the cost of suboptimality. Instead, the robot controller described here produces plans that are both explainable and optimal with respect to at least one objective.

Recent XAIP approaches rely on classical planning (Grea, Matignon, and Aknine 2018; Krarup et al. 2019) or logic (Nguyen et al. 2020) to produce explanations. None of those, however, explains in natural language. Several approaches to sequential tasks explained the state-action-reward representation of Markov decision processes to produce explanations, but the resultant language was not human-friendly nor was it based on human reasoning (Ramakrishnan and Shah 2016; Khan et al. 2011). Another approach used deep learning to produce natural explanations for an autonomous vehicle, but required an annotated dataset for training and did not address indoor navigation (Kim et al. 2018).

A contrastive explanation compares the reason for a decision or plan against another plausible rationale (Hoffmann and Magazzeni 2019). Counterfactual reasons for behavior have been shown to improve trust and understanding (Lim, Dey, and Avrahami 2009). A recent human-subject study showed that people preferred explanations focused on the differences between the robot's planned route and their own expectations (e.g., "my route is shorter, but overlaps more and produces less reward") (Perelman, Evans III, and Schaefer 2020). Similar to our approach, other recent work provided contrastive explanations in natural language for multi-objective path planning modeled as a Markov decision process (Sukkerd, Simmons, and Garlan 2020). It considered

fewer objectives, however, required a hand-labeled map, and was evaluated in much smaller environments.

An early approach to multi-objective optimization treated it as a single-objective problem for a simple weighted sum of the objectives (Zadeh 1963). Others addressed individual objectives in a weighted sum with constraints (Haimes 1973), minimum values (Lee et al. 1972), or ideal values (Wierzbicki 1980). The weighted sum approach has also been applied to the heuristic function of an optimal search algorithm (Refanidis and Vlahavas 2003). All this work, however, required a human expert with knowledge of the relative importance of the objectives to tune the weights (Marler and Arora 2010). Moreover, small changes in the weights may result in dramatically different plans.

Many have used metaheuristics (e.g., evolutionary algorithms) to find non-dominated solutions to multi-objective problems (Deb et al. 2002). These approaches, however, do not guarantee optimality, require tuning many hyperparameters, and are computationally expensive (Talbi et al. 2012). Furthermore, as the number of objectives increases, the fraction of non-dominated solutions approaches one (Farina and Amato 2002) and the size of the Pareto frontier increases exponentially (Jaimes and Coello 2015). As a result, methods that seek Pareto dominance break down with more objectives because it becomes computationally more expensive to compare all the potential non-dominated solutions. VBMO avoids this computation on infinitely many points on the surface of the Pareto frontier. Instead, it only ever compares $|B|$ solutions because it transforms the multi-objective problem into a set of single-objective problems.

A*, the traditional optimal search algorithm, requires an admissible heuristic, one that consistently underestimates its objective (Hart, Nilsson, and Raphael 1968). Other approaches extend A* to address multi-objective search. Multi-objective A* tracks all the objectives simultaneously as it maintains a queue of search nodes to expand (Stewart and White III 1991). NAMOA* extends multi-objective A* with a queue of partial solution paths instead of search nodes, but it is slow, memory hungry, and does not scale well (Mandow and De La Cruz 2008). Multi-heuristic A* modifies A* to consider multiple heuristics, some of which can be inadmissible (Aine et al. 2016). It interleaves expansion of search nodes selected by an admissible heuristic with expansion on search nodes selected by nonadmissible ones. This approach was extended to treat the expansion from nonadmissible heuristics as a multi-armed bandit problem (Phillips et al. 2015). Others have addressed these issues but only for two objectives (Ulloa et al. 2020).

Other multi-objective approaches draw from social choice theory. For example, in multi-attribute utility theory a function evaluates the available choices and selects the one with greatest utility (Keeney, Raiffa, and Meyer 1993). The approach closest to ours formulated multi-objective path planning as a reinforcement learning problem, and voted to select among the actions available at a state based on the expected reward under each objective (Tozer, Mazzuchi, and Sarkani 2017). That approach, however, required hundreds of episodes of training and only considered an artificial 10×20 grid environment with four obstacles.

Algorithm 1: VBMO planning algorithm

Input: *single-objective planners J, shared graph G*
for *each planner $j \in J$* **do**
    Set j's graph G_j to a copy of G
    Label edges in G_j based on j's objective
    Find optimal plan P_j in G_j

for *each planner $j \in J$* **do**
    for *each planner $i \in J$* **do**
        $C_{ij} \leftarrow$ cost of plan P_i in G_j
    Normalize plan scores C_{ij} in [0,10]

for *each plan P_i* **do**
    $Score_i \leftarrow \sum_{j=1}^{J} C_{ij}$
$best \leftarrow argmin_i \; Score_i$
return P_{best}

VBMO, the path planning algorithm introduced here, uses topologically identical graphs whose labels reflect each of its objectives. VBMO constructs an optimal plan in each graph, evaluates each plan in every graph, and then selects the plan with lowest total cost across all of them. This avoids the limitations of other approaches because it addresses each objective independently and then evaluates the resultant plans from the perspective of each planner. The full trajectory of a VBMO plan is inherently explainable in natural language and readily provides contrastive reasons based on the planner's objectives, even in a finely-detailed graph for a large, obstacle-ridden environment.

Voting-based Multi-objective Path Planning

VBMO constructs multiple plans, each of which optimizes a single objective, and then uses range voting to select the plan that maximally satisfies the most objectives. Pseudocode for it appears in Algorithm 1. First, each single-objective planner modifies a copy of the shared graph to reflect its objective in the edge weights. Then VBMO constructs an optimal plan P in that modified graph. In this way, each submitted plan is guaranteed to be optimal for at least one objective.

Once it assembles the set of submitted plans $\mathcal{P}$, VBMO uses each planner's objective to evaluate all of them. Because each planner's underlying graph has the same topological structure (vertices and edges), every vertex v in any plan is known to all the planners. To evaluate planner $\mathcal{H}_i$'s plan $P_i = \langle v_1, v_2, \ldots, v_m \rangle$ from the perspective of planner $\mathcal{H}_j$ with objective β_j, VBMO sums the edge costs from the same sequence of vertices in $\mathcal{H}_j$'s own graph. In this way, each planner $\mathcal{H}_j$ uses its own objective to calculate a *score* C_{ij} for each stored plan P_i.

To avoid any biases that would be introduced by the magnitude of an objective's values, all scores from any $\mathcal{H}_j$ are normalized in $[0, 10]$. Because VBMO seeks to minimize its objectives, a score C_{ij} near 0 indicates that plan P_i closely conforms to objective β_j, while a score near 10 indicates that P_i strongly opposes β_j. Once every planner scores every plan, the plan P_{best} with the lowest total score from all

Table 1: Scores C_{ij} for six plans P_i given six objectives β_j. Normalization ensures that each plan is optimal with respect to its own objective. VBMO selects the plan with minimum total $Score_i$, here P_2.

	β_1	β_2	β_3	β_4	β_5	β_6	$Score_i$
P_1	0.0	1.4	5.0	6.7	2.5	7.5	23.1
P_2	1.2	0.0	1.2	1.1	10.0	1.1	14.6
P_3	5.7	8.6	0.0	2.2	6.3	5.0	27.8
P_4	10.0	7.1	10.0	0.0	3.8	10.0	40.9
P_5	5.7	10.0	2.0	10.0	0.0	6.3	34.0
P_6	2.9	10.0	2.0	1.1	10.0	0.0	26.0

J planners is selected by range voting:

$$P_{best} = \underset{P_i \in \mathcal{P}}{argmin} \sum_{j=1}^{J} C_{ij} \qquad (1)$$

Ties are broken at random. An example appears in Table 1.

Theorem. *Algorithm 1 constructs at least one plan guaranteed to be on the Pareto frontier.*

Proof by induction on the number of objectives J:
Consider first $J = 2$ with objectives $B = \{\beta_1, \beta_2\}$ and respective plans P_1 and P_2. By definition, planner $\mathcal{H}_j$'s plan P_j optimally minimizes its objective, that is, $\beta_j(P_j) \leq \beta_j(P_k)$ for every $P_k \in \mathcal{P}$. Another planner $\mathcal{H}_k$ can score equally well on β_j, but cannot score lower than $\beta_j(P_j)$; otherwise, search would have returned $\mathcal{H}_k$'s plan to $\mathcal{H}_j$. Thus, there are only four possible cases

- *Case 1:* $\beta_1(P_1) = \beta_1(P_2)$ and $\beta_2(P_2) = \beta_2(P_1)$
- *Case 2:* $\beta_1(P_1) < \beta_1(P_2)$ and $\beta_2(P_2) = \beta_2(P_1)$
- *Case 3:* $\beta_1(P_1) = \beta_1(P_2)$ and $\beta_2(P_2) < \beta_2(P_1)$
- *Case 4:* $\beta_1(P_1) < \beta_1(P_2)$ and $\beta_2(P_2) < \beta_2(P_1)$

In case 1, both plans are non-dominated; $P_1 \not\ll P_2$ and $P_2 \not\ll P_1$ because neither's score is strictly less than the other on any objective. In case 2, $P_1 \ll P_2$ and $P_2 \not\ll P_1$, so P_1 is non-dominated. In case 3, $P_1 \not\ll P_2$ but $P_2 \ll P_1$, so P_2 is non-dominated. Finally, in case 4, $P_1 \not\ll P_2$ and $P_2 \not\ll P_1$, so both plans are non-dominated. Thus, when $J = 2$ there is always at least one plan that is non-dominated (i.e., on the Pareto frontier).

Assume now that for $J = k$ objectives $B = \{\beta_1, \ldots, \beta_k\}$ with optimal plans $\{P_1, \ldots, P_k\}$, one of them, plan P_n, is non-dominated. Then, by definition, there is no other plan P_i such that $\beta(P_i) \leq \beta(P_n)$ for all $\beta \in B$ and for some $j \neq k, \beta_j(P_i) < \beta_j(P_n)$. Consider now $J = k + 1$, where we introduce one additional objective β_{k+1} and its optimal plan P_{k+1}. With respect to dominance, there are three possible relationships between P_n and P_{k+1}. If $P_n \ll P_{k+1}$, then P_n remains on the Pareto frontier because it is still non-dominated. If $P_{k+1} \ll P_n$, then P_{k+1} is on the Pareto frontier because transitivity ensures that it is not dominated by any other plan. Finally, if $P_n \not\ll P_{k+1}$ and $P_{k+1} \not\ll P_n$, both plans are non-dominated. Hence, at least one of P_n or P_{k+1} is non-dominated and lies on the Pareto frontier. ∎

VBMO always identifies at least one plan on the Pareto frontier. Moreover, given a set of dominated and non-dominated plans, voting will always pick a non-dominated plan because non-dominated plans have a lower score with respect to at least one objective and therefore a lower total score as well. Thus, VBMO always selects a plan on the Pareto frontier, which makes it an efficient multi-objective path planning approach that does not require finely-tuned weights.

Contrastive Plan Explanations

It has recently been argued that instead of building systems to explain black-box models, models should deliberately be built to be interpretable (Rudin 2019). VBMO's planning procedure makes it an inherently interpretable system without the need for any additional computation. Its output is a set of single-objective plans and their scores on all the objectives under consideration. These plans support readily constructed counterexamples for comparison to produce contrastive explanations.

Given objectives $B = \{\beta_1, \ldots, \beta_J\}$ with associated plans $\mathcal{P} = \{P_1, \ldots, P_J\}$, our explanation generator considers the relative adherence of any plan to those objectives. Each objective β_k is associated with its own partition of [0,10] into bins that reflect how closely any plan diverges from it. For example, if the partition for β_k were $\{[0, 2), [2, 7), [7, 10]\}$, then $\beta_k(P_i) = 0$ would place P_i in the first bin and $\beta_k(P_j) = 4.7$ would place P_j in the second. The generator associates these bins with natural language that describes the adherence to β_k. To do so it uses the function $\mathcal{L}$, which maps a score to a partition and outputs the language associated with that bin. In our example, if β_k's three bins were translated as "a lot," "somewhat," and "a little," then $\mathcal{L}(\beta_k(P_i)) =$ "a lot" and $\mathcal{L}(\beta_k(P_j)) =$ "somewhat."

To compare two plans P_i and P_j, the generator partitions their scores C_{ik} and C_{jk} from each β_k, and bins the scores for the two plans based on each associated partition. It then identifies those objectives β_l where $\beta_l(P_i) < \beta_l(P_j)$, and those β_g where $\beta_g(P_i) > \beta_g(P_j)$. Recall that VBMO minimizes, so the β_l's are objectives that *favor* P_i and the β_g's favor P_j. This method excludes any objective β_k for which $\beta_k(P_i) = \beta_k(P_j)$ because VBMO focuses on how plans differ. Finally, the generator produces a contrastive explanation for a selected plan with natural language descriptions $\mathcal{N}(\beta)$ of the objectives that favor or oppose the plan and the language from $\mathcal{L}$ that associates its scores with those objectives. To do so it instantiates this template:

Although another way may be $[\mathcal{L}(\beta(P_j)) \, \mathcal{N}(\beta)]$,

I believe my way is $\{\mathcal{L}(\beta(P_i)) \, \mathcal{N}(\beta)\}$.

With appropriate punctuation and conjunctions, the portion in square brackets is repeated for every $\beta \in B$ where $\beta(P_i) > \beta(P_k)$, and the portion in curly brackets for every $\beta \in B$ where $\beta(P_i) < \beta(P_k)$. For example, "Although another way may be somewhat shorter and a little less crowded, I believe my way is a lot safer, somewhat less obstructed, and a little more familiar." The order of the β's is randomized to encourage unique explanations. The first line in the template is omitted if every objective prefers P_i.

While the contrastive explanation above describes the robot controller's beliefs and intentions, it does not address its confidence in P_i, the plan it selected from all the plans in $\mathcal{P}$. To do so, the generator uses two metrics: overall preference for the plan and an overall adherence to the objectives. Overall preference for a chosen plan compared to the others is defined as a t-statistic across all total scores. Recall that P_i's total score is $Score_i = \sum_{j=1}^{J} C_{ij}$. Let $\mu_{\mathcal{C}}$ be the average total score for all plans in $\mathcal{P}$ and $\sigma_{\mathcal{C}}$ be their standard deviation. The *overall preference* for the selected plan P_i is

$$\tau_i = \frac{Score_i - \mu_{\mathcal{C}}}{\sigma_{\mathcal{C}}} \qquad (2)$$

Overall preference τ_i for plan P_i indicates how much more the objectives as a group prefer it to the other plans in $\mathcal{P}$. Because VBMO minimizes total score, ideally τ_i is negative and has a large absolute value, to indicate that it is far below the mean total score. In Table 1, for example, $\mu_{\mathcal{C}} = 27.7$ and $\sigma_{\mathcal{C}} = 9.05$, so the overall preference τ_2 for P_2 is -1.45. This indicates a relatively strong preference for P_2 over the other plans because its total score is more than one standard deviation from the mean.

A plan's adherence to the objectives in B can be measured several ways. Intuitively, it should include how often the plan meets the objectives well and poorly. A simple approach would count W_i, how many objectives the plan does well on (e.g., $C_{ij} < 1$) and X_i, how many it does not do well on (e.g., $C_{ij} > 9$). $W_i > X_i$ would then indicate a high adherence, $W_i = X_i$ a medium adherence, and $W_i < X_i$ a low adherence. This approach removes the nuances of VBMO's range voting; it replaces sums of real-valued scores from the objectives with combined approval voting, where a voter can express only approval, disapproval, or indifference (Felsenthal 1989). In Table 1, for example, it would find $W_2 = 1$ and $X_2 = 1$ for P_2. That indicates a medium adherence to the objectives, even though in the range [0,10], 5 out of 6 objectives scored P_2 near 1. Another approach could transform VBMO's scores into a ranking and then use a measure of group coherence (Gehrlein and Lepelley 2016) but that too would ignore the real values.

Instead, the approach used here adapts a measure of inter-rater agreement. Typically, inter-rater agreement is measured with the κ statistic, which compares ratings from two raters on a set of items. Here, we treat each objective β as a rater that evaluates each plan and produces a score (i.e., its rating). While κ indicates whether two objectives score plans similarly, it is not a good measure of the agreement among all the objectives on a single plan. Another measure is the average deviation index, which compares the ratings from multiple raters on a single item (Burke and Dunlap 2002). This works well as a metric of adherence because it accounts for the continuous values of VBMO's scores. Let M_i be the median of the scores C_{ij} for plan P_i from all objectives in B. The adherence α_i of plan P_i is

$$\alpha_i = \frac{\sum_{j=1}^{J} |C_{ij} - M_i|}{J} \qquad (3)$$

Smaller values of α_i indicate strong agreement among the objectives with respect to a plan. A ceiling of $0.2 max(C_{ij})$

Figure 1: Floor plan of a large office environment with the robot's initial pose in red.

Figure 2: Distribution of normalized plan scores C_{ij} across all the planners.

Figure 3: Distribution of total score $Score_i$ for plans P_i in VBMO. Because $0 \leq C_{ij} \leq 10$ and VBMO scores each plan in seven other graphs, $Score_i \leq 70$. VBMO's selected plans have a better (i.e., lower) average $Score_i$ (13.8) than the unselected plans (27.0).

has been proposed to indicate agreement (Burke and Dunlap 2002). In Table 1, $M_2 = 1.15$, so P_2's adherence α_2 is 1.70. This is below the ceiling of 2.0, and so indicates strong agreement among the objectives in favor of the selected plan.

To bin their values for plan P_i and assign natural language with $\mathcal{L}$, we associate both τ_i and α_i with partitions of the real numbers. For example, τ can be partitioned as $\{(-\infty, -0.75], (-0.75, -0.5], (-0.5, +\infty)\}$, with associated language "really," "somewhat," and "not really," and α with $\{[0, 1.5], (1.5, 2.5], (2.5, +\infty)\}$, with associated language "certain," "somewhat certain," and "conflicted." Instead of a ceiling that partitions α into two bins, we use three bins to more finely distinguish the adherence values. Each bin's associated language is classified by its *sentiment*: positive or negative. For example, "really," "somewhat," "certain," and "somewhat certain" are positive and "not really" and "conflicted" are negative.

If the sentiments expressed by $\mathcal{L}(\tau_i)$ and $\mathcal{L}(\alpha_i)$ agree on P_i, the description of the robot controller's confidence in its plan instantiates this template:

I'm $\mathcal{L}(\tau_i)$ sure I want to follow this plan,

and I'm also $\mathcal{L}(\alpha_i)$ about my reasons to go this way.
In Table 1's example, the two measures share the same sentiment for P_2 so the confidence explanation would be "I'm really sure I want to follow this plan, and I'm also certain about my reasons to go this way." Otherwise, if the sentiments do not agree, the description instantiates this template:

Although I'm $\mathcal{L}(\tau_i)$ sure I want to follow this plan,

I'm $\mathcal{L}(\alpha_i)$ about my reasons to go this way.
For example, the measures in Table 1 disagree about P_1. It has the second lowest total score, with $\tau_1 = -0.51$ and $\alpha_1 = 2.55$ so the explanation for P_1 would be "Although I'm somewhat sure I want to follow this plan, I'm conflicted about my reasons to go this way."

Empirical Results

VBMO and its contrastive explanations have been evaluated in extensive simulation experiments with an autonomous robot controller for navigation in large, complex, indoor environments (anonymized for blind review). Written for ROS, the robot operating system, the simulator places our indus-

trial robot on the fifth floor of a real-world office building. This environment is the size of a Manhattan city block ($110 \times 70m$) with 180 rooms of various sizes and several intersecting hallways. The controller overlays a fine grid on the environment's architectural floor plan (shown in Figure 1) to create VBMO's shared underlying graph.

Our controller also learns a cognitively-based spatial model while it travels. Table 2 shows its eight planning objectives B. The first four are based on commonsense principles; the others reference a learned spatial model of the environment. Given a target and planning objectives B, the controller uses VBMO to modify copies of the shared graph and constructs the set of plans $\mathcal{P}$. It then evaluates each plan with respect to every objective, generates an explanation for each of them, and selects a plan.

At the start of an experiment, the robot controller receives a sequence of 40 randomly-selected target locations. For the first target, the robot's initial *pose* (location and orientation) faces east between the elevators. For all other targets, its initial pose is its final pose on the previous target. Table 3 reports the scores C_{ij} for each planner's plan in the others' graphs, averaged over five different sets of 40 targets (200

Table 2: VBMO's planners and their objectives

Planner	Objective	Language $\mathcal{N}$
FAST	Minimize distance traveled	"shorter"
SAFE	Avoid travel near obstructions	"less obstructed"
EXPLORE	Avoid travel along previous paths	"less familiar"
NOVEL	Avoid areas covered by the learned model	"more likely to reveal new areas"
TRAFFIC	Focus on small frequently-traveled areas	"more well-traveled"
HALLWAY	Exploit frequently-traveled vertical, horizontal, and diagonal routes	"more aligned with previous routes"
CIRCLE	Exploit a model of unobstructed circular areas	"more open"
TRACE	Follow refined versions of previous paths	"closer to ways we've gone before"

Table 3: Average normalized plan scores C_{ij} for each planner in every graph. Each plan is optimal in its own graph (i.e., $C_{ii} = 0.0$). The last column is the frequency with which a planner was selected by VBMO in 200 tasks.

	β_{Fast}	β_{Safe}	$\beta_{Explore}$	β_{Novel}	$\beta_{Traffic}$	$\beta_{Hallway}$	β_{Circle}	β_{Trace}	Frequency
FAST	0.00	0.20	3.53	5.30	1.74	1.46	1.30	1.93	32.4%
SAFE	0.00	0.00	3.60	5.52	1.46	1.44	1.18	1.55	27.5%
EXPLORE	3.42	3.62	0.00	4.92	4.94	4.63	3.89	4.52	4.9%
NOVEL	8.07	8.27	5.47	0.00	9.08	8.38	9.44	9.38	0.0%
TRAFFIC	1.47	1.64	5.60	7.06	0.00	2.26	0.91	1.02	16.5%
HALLWAY	1.74	1.91	5.86	6.78	1.88	0.00	1.46	1.89	6.6%
CIRCLE	1.83	2.00	5.45	8.60	0.80	2.34	0.00	0.90	0.5%
TRACE	1.88	2.05	5.98	7.68	0.41	2.32	0.76	0.00	11.5%

tasks in all). Some planners perform well in another's graph (e.g., FAST and SAFE score each other's plans near 0). Only NOVEL scores poorly (i.e., above 9) fairly often. This is because its objective seeks to explore areas of the environment not captured in the learned spatial model, whereas four of the planners exploit that model. As a result, FAST and SAFE were most often selected by VBMO, and NOVEL never was.

The bimodal distribution in Figure 2 describes the overall distribution of all 12800 (8 objectives × 8 plans × 200 tasks) normalized plan scores C_{ij} for all planners. It clearly indicates that most pairs of plans with distinct objectives either strongly conform to an objective or strongly oppose it. This suggests that the controller's objectives are sufficiently different to produce a diverse set of plans. Nearly 7% of objectives scored another's plan as 0, which occurs when two plans are identical. Figure 3 is the distribution of the total scores $Score_i$ for the 1600 (8 × 200) generated plans. A total score of 0 would represent optimal adherence to all the objectives, but most often the selected plan's total score lies in (10, 20] which indicates some opposition to it.

Generation of contrastive explanations requires pairwise plan comparisons. Figure 4(a) reports on 11200 (200×8×7) pairs of distinct objectives β_i and β_j. It shows how often, when plan P_i is compared to plan P_j, the objectives favor P_i, favor P_j, or have no preference between the two. The results show that a majority of the objectives often favor FAST's and SAFE's plans over other plans, that a majority oppose plans from EXPLORE and NOVEL, and that they split about evenly on plans from the other planners.

Figure 4(b) examines how often an objective favors one of the 200 selected plans over the 7 alternatives to it. In those 1400 tests, on average 4.8 objectives favored VBMO's selected plan and 2.3 favored an alternative. When each of the

1400 rejected plans is compared to the 7 others, fewer objectives favor the rejected plan and more objectives favor the alternative plan.

For evaluation, the system generated contrastive explanations for every pair of plans. As in the earlier examples, value partitions were $\{[0, 2), [2, 7), [7, 10]\}$ for all objectives β with associated language "a lot," "somewhat," and "a little"; $\{(-\infty, -0.75], (-0.75, -0.5], (-0.5, +\infty)\}$ for overall preference τ_i with associated language "really," "somewhat," and "not really"; and $\{[0, 1.5], (1.5, 2.5], (2.5, +\infty)\}$ for adherence α_i with associated language "certain," "somewhat certain," and "conflicted." This produced 9803 explanations, 96.8% of which were unique, behavior consistent with the $Score_i$ distributions and the data on objectives' preferences. Explanations averaged 51.2 words and reading grade level averaged 7.8 on the Coleman-Liau index (CLI) (Coleman and Liau 1975). One generated explanation was "Although another way may be a lot more well-traveled, a lot closer to ways we've gone before, somewhat more aligned with previous routes, and somewhat less familiar, I believe my way is a little more likely to reveal new areas, a lot more open, a lot shorter, and a lot less obstructed."

We also examined the values of the two confidence metrics, overall preference τ_i and adherence α_i. Figure 5(a) shows the distribution of τ_i values for each plan P_i. VBMO's selected plan P has an average overall preference of -0.7, which indicates that it is often "really" or "somewhat" preferred. For plans not selected by VBMO, this distribution peaks at about -0.4 with a right skew that indicates many other much less supported plans. Figure 5(b) shows the distribution values for α_i for each plan P_i. For both the selected and rejected plans, the nearly 45% of plans fall in (1.5, 2.5]. Unanimous agreement on the selected plan is clearly not al-

(a) Each planner's support from the other planners

(b) Support for selected and rejected plans from the other planners

Figure 4: How a specific plan P was viewed by other planners' objectives on 200 tasks. Objectives favor P (green), favor some other plan (red), or have no favorite (gray). For example, in (a) when a plan from EXPLORE was evaluated by each of the 7 other objectives, 37% of them favored $P_{Explore}$ and 56% favored an alternative.

Table 4: How confidence metric sentiments co-occur.

	All plans $\mathcal{L}(\alpha)$		
$\mathcal{L}(\tau)$	certain	somewhat certain	conflicted
really	3.5%	3.2%	1.5%
somewhat	11.0%	13.7%	1.7%
not really	20.4%	28.1%	17.0%
	P_{best}		
	certain	somewhat certain	conflicted
really	13.3%	12.2%	3.9%
somewhat	24.9%	25.4%	1.1%
not really	12.7%	6.6%	0.0%

ways the case.

With τ and α each partitioned into three bins, the confidence explanation template can produce only nine different explanations. All nine were generated during the five runs of the experiment. In 152 instances (19 tasks × 8 plans) confidence explanations were not generated because all plans had equal total scores. For the 1448 other plans, confidence explanations averaged 20.6 words with a 5.6 reading grade level. Table 4 shows that 8.2% of all plans had overall preference $\mathcal{L}(\tau_i)$ = "really," to be expected because this data includes seven times more rejected than accepted plans. The selected plans, however, were "really" preferred 29.4%. Moreover, no selected plan was labeled as both "not really" and "conflicted." Across all plans, the confidence explanation most often produced was "I'm not really sure I want to follow this plan, and I'm only somewhat certain about my reasons to go this way."

Discussion

VBMO's current explanations address two important questions: "Why did you select that plan?" and "How confident are you about your plan?" The same approach could be easily extended to address other important questions from a human companion, such as "Why don't we go that way?" or "What makes your plan better than mine?" In some way the person would have to convey either their planning objective β or their plan route P_H to the robot so that VBMO could interpret it in its shared graph and evaluate it with respect to all the objectives in B. The same process would then compare VBMO's selected plan to P_H with respect to B.

Both evolutionary methods and VBMO consider a population of solutions and select among them with a kind of fitness function. VBMO, however, does not require multiple iterations to refine its plan. Instead, it starts with at least one plan already on the Pareto frontier, and uses a shared underlying graph to select a plan that generally performs well with respect to all the objectives. Although VBMO does not need hand-tuned weights to balance multiple objectives, they could be easily incorporated into equation 1 to change an objective's influence on the sum.

Currently the planners modify a graph with respect to features of a learned model and commonsense rationales, but additional planning objectives could be incorporated to produce more nuanced explanations and create more robust plans. For example, path smoothness is an important criterion for indoor navigation, particularly for transport of fragile material. Smoothness could be easily translated into a planning objective, so that it explicitly impacts plan selection. VBMO uses A* for its graph search algorithm but another optimal graph search algorithm could easily be substituted for it.

Because the controller's learned spatial model becomes more knowledgeable as the robot experiences the environment, the planners that rely on the model become better informed over time. As a result, early on in an experiment planners that reference the spatial model produce the same plan as FAST and so their objectives are often excluded from explanations. As a consequence, the average readability of explanations for the first 5 targets is 6.8 but increases linearly to 8.0 for the last 5 targets.

In previous work we generated contrastive explanations

Figure 5: Distributions of τ and α for 200 selected plans. Overall preference is a *t*-statistic, so τ has mean 0. A selected plan must have minimum total score, so its τ value must be negative unless all plans score the same on every objective. There is significant overlap in the α distribution between selected and rejected plans.

but assumed the alternative objective was fixed, and only compared performance on the selected plan's objective and the fixed objective (anonymized for blind review). That approach produced shorter, more understandable explanations but did not address the nuances of the multiple objectives under consideration by VBMO. A potential way to shorten the explanations here would only include objectives that strongly favor or oppose a plan. Future work will evaluate the contrastive explanations with human subjects to gauge how well they are trusted and understood.

Adherence α should measure how much scores concentrate around their median. As Figure 4 shows, it may not be the ideal metric since 4.8 objectives on average favor the selected plan and yet the partition can still categorize it as "conflicted." This occurred, for example, when a plan had $\alpha = 2.59$ based on the 8 scores $\{0.0, 0.0, 0.0, 0.3, 2.2, 2.2, 8.3, 8.4\}$. It was categorized as "conflicted" even though six objectives found that the plan closely conformed to them. Ways to address this would be to to exclude outliers, to modify α to use the mean instead of the median, or use κ to identify which objectives consistently score all plans differently from the way the others do and then give their opinion less weight.

VBMO could encounter a set of objectives B that each generate an optimal plan but is equally poor on all the other objectives. In that case, total scores for all plans would be equal, so the algorithm would select a plan at random, one that would perform well only on its own objective and badly on the others. That relegates the solution to a planner with a single, randomly chosen objective. Other multi-objective planning methods avoid this difficulty because they compromise among all the objectives rather than focus on strong performance from one. To address this issue, VBMO could incorporate additional planners that introduce weighted sums of different objectives but would do less well on any single objective. Unless these additions were simple, they would make it more difficult to generate natural language that explains those weighted sums.

Although VBMO is applied here to path planning for robot navigation, it is more generally applicable to any multi-objective planning problem (e.g., motion or task planning). The contrastive explanation approach described here could also apply to many multi-objective domains; one would first generate an optimal single-objective solution for each objective, and then evaluate the resultant solutions with each of the other objectives. The same metrics used here would then apply. For example, a movie recommendation system could identify the movie most similar to a user's top favorites, the most popular movie, and the best reviewed movie, evaluate each of them on the other objectives, and then select the movie that scores best across the three. A contrastive explanation that might be generated is "Although another movie may be much more popular, I recommend this one because it is somewhat better reviewed and a lot more similar to your favorite movies."

Meanwhile, VBMO is an inherently interpretable approach that generates plans on the Pareto frontier. The plan it selects is guaranteed to be optimal with respect to at least one objective and likely does well on the others. VBMO easily generates contrastive explanations in natural language. These explanations flexibly compare plans with respect to the objectives under consideration and express the controller's confidence in its selected plan. The results with voting-based multi-objective path planning presented here demonstrate that explainable AI planning algorithms need not sacrifice optimality to be well understood.

References

Aine, S.; Swaminathan, S.; Narayanan, V.; Hwang, V.; and Likhachev, M. 2016. Multi-heuristic A*. *The International Journal of Robotics Research* 35(1-3): 224–243.

Burke, M. J.; and Dunlap, W. P. 2002. Estimating interrater agreement with the average deviation index: A user's guide. *Organizational research methods* 5(2): 159–172.

Chakraborti, T.; Sreedharan, S.; Grover, S.; and Kambhampati, S. 2019. Plan Explanations as Model Reconciliation–An Empirical Study. In *2019 14th ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, 258–266. IEEE.

Coleman, M.; and Liau, T. L. 1975. A Computer Readability Formula Designed for Machine Scoring. *Journal of Applied Psychology* 60(2): 283–284.

Deb, K.; Pratap, A.; Agarwal, S.; and Meyarivan, T. 2002. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE transactions on evolutionary computation* 6(2): 182–197.

Farina, M.; and Amato, P. 2002. On the optimal solution definition for many-criteria optimization problems. In *Proceedings of the North American Fuzzy Information Processing Society*, 233–238. IEEE.

Felsenthal, D. S. 1989. On combining approval with disapproval voting. *Behavioral Science* 34(1): 53–60.

Gehrlein, W. V.; and Lepelley, D. 2016. Refining measures of group mutual coherence. *Quality & Quantity* 50(4): 1845–1870.

Grea, A.; Matignon, L.; and Aknine, S. 2018. How explainable plans can make planning faster. In *Workshop on Explainable Artificial Intelligence*, 58–64.

Haimes, Y. Y. 1973. Integrated system identification and optimization. In *Control and Dynamic Systems*, volume 10, 435–518. Elsevier.

Hart, P. E.; Nilsson, N. J.; and Raphael, B. 1968. A Formal Basis for the Heuristic Determination of Minimum Cost Paths. *IEEE Transactions on Systems Science and Cybernetics* 4(2): 100–107.

Hoffmann, J.; and Magazzeni, D. 2019. Explainable AI planning (XAIP): overview and the case of contrastive explanation. *Reasoning Web. Explainable Artificial Intelligence* 277–282.

Huang, S. H.; Held, D.; Abbeel, P.; and Dragan, A. D. 2019. Enabling robots to communicate their objectives. *Autonomous Robots* 43(2): 309–326.

Jaimes, A. L.; and Coello, C. A. C. 2015. Many-objective problems: challenges and methods. In *Springer handbook of computational intelligence*, 1033–1046. Springer.

Keeney, R. L.; Raiffa, H.; and Meyer, R. F. 1993. *Decisions with multiple objectives: preferences and value trade-offs*. Cambridge University Press.

Khan, O.; Poupart, P.; Black, J.; Sucar, L.; Morales, E.; and Hoey, J. 2011. Automatically Generated Explanations for Markov Decision Processes. *Decision Theory Models for Applications in Artificial Intelligence: Concepts and Solutions* 144–163.

Kim, J.; Rohrbach, A.; Darrell, T.; Canny, J.; and Akata, Z. 2018. Textual explanations for self-driving vehicles. In *Proceedings of the European conference on computer vision (ECCV)*, 563–578.

Krarup, B.; Cashmore, M.; Magazzeni, D.; and Miller, T. 2019. Model-based contrastive explanations for explainable planning. In *29th International Conference on Automated Planning and Scheduling-ICAPS 2019*.

Kulesza, T.; Stumpf, S.; Burnett, M.; Yang, S.; Kwan, I.; and Wong, W.-K. 2013. Too Much, Too Little, or Just Right? Ways Explanations Impact End Users' Mental Models. In *2013 IEEE Symposium on Visual Languages and Human-Centric Computing (VL/HCC)*, 3–10. IEEE.

LaValle, S. M. 2006. *Planning algorithms*. Cambridge University Press.

Lee, S. M.; et al. 1972. *Goal programming for decision analysis*. Auerbach Publishers Philadelphia.

Lim, B. Y.; Dey, A. K.; and Avrahami, D. 2009. Why and Why Not Explanations Improve the Intelligibility of Context-Aware Intelligent Systems. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, 2119–2128. ACM.

Mandow, L.; and De La Cruz, J. L. P. 2008. Multiobjective A* search with consistent heuristics. *Journal of the ACM (JACM)* 57(5): 1–25.

Marler, R. T.; and Arora, J. S. 2010. The weighted sum method for multi-objective optimization: new insights. *Structural and multidisciplinary optimization* 41(6): 853–862.

Miller, T. 2019. Explanation in artificial intelligence: Insights from the social sciences. *Artificial intelligence* 267: 1–38.

Nguyen, V.; Vasileiou, S. L.; Son, T. C.; and Yeoh, W. 2020. Explainable Planning Using Answer Set Programming. In *Proceedings of the International Conference on Principles of Knowledge Representation and Reasoning*, volume 17, 662–666.

Pardalos, P. M.; Migdalas, A.; and Pitsoulis, L. 2008. *Pareto optimality, game theory and equilibria*, volume 17. Springer Science & Business Media.

Perelman, B. S.; Evans III, A. W.; and Schaefer, K. E. 2020. Where Do You Think You're Going? Characterizing Spatial Mental Models from Planned Routes. *ACM Transactions on Human-Robot Interaction (THRI)* 9(4): 1–55.

Phillips, M.; Narayanan, V.; Aine, S.; and Likhachev, M. 2015. Efficient search with an ensemble of heuristics. In *Twenty-Fourth International Joint Conference on Artificial Intelligence*.

Ramakrishnan, R.; and Shah, J. 2016. Towards Interpretable Explanations for Transfer Learning in Sequential Tasks. In *2016 AAAI Spring Symposium Series*.

Refanidis, I.; and Vlahavas, I. 2003. Multiobjective heuristic state-space planning. *Artificial Intelligence* 145(1-2): 1–32.

Rosenfeld, A.; and Richardson, A. 2019. Explainability in human–agent systems. *Autonomous Agents and Multi-Agent Systems* 33(6): 673–705.

Rudin, C. 2019. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence* 1(5): 206–215.

Shvo, M.; Klassen, T. Q.; and McIlraith, S. A. 2020. Towards the Role of Theory of Mind in Explanation. In *International Workshop on Explainable, Transparent Autonomous Agents and Multi-Agent Systems*, 75–93. Springer.

Stewart, B. S.; and White III, C. C. 1991. Multiobjective A*. *Journal of the ACM (JACM)* 38(4): 775–814.

Sukkerd, R.; Simmons, R.; and Garlan, D. 2020. Tradeoff-Focused Contrastive Explanation for MDP Planning. In *2020 29th IEEE International Conference on Robot and Human Interactive Communication*, 1041–1048. IEEE.

Talbi, E.-G.; Basseur, M.; Nebro, A. J.; and Alba, E. 2012. Multiobjective optimization using metaheuristics: non-standard algorithms. *International Transactions in Operational Research* 19(1-2): 283–305.

Tozer, B.; Mazzuchi, T.; and Sarkani, S. 2017. Many-objective stochastic path finding using reinforcement learning. *Expert Systems with Applications* 72: 371–382.

Ulloa, C. H.; Yeoh, W.; Baier, J. A.; Zhang, H.; Suazo, L.; and Koenig, S. 2020. A simple and fast bi-objective search algorithm. In *Proceedings of the International Conference on Automated Planning and Scheduling*, volume 30, 143–151.

Wierzbicki, A. P. 1980. The use of reference objectives in multiobjective optimization. In *Multiple criteria decision making theory and application*, 468–486. Springer.

Zadeh, L. 1963. Optimality and non-scalar-valued performance criteria. *IEEE transactions on Automatic Control* 8(1): 59–60.