Path-enhanced Pre-trained Language Model for Knowledge Graph Completion

Abstract

Pre-trained language models (PLMs) have achieved remarkable success in knowledge graph completion (KGC). However, previous methods derive KGC results mainly from triple-level and text-described learning, which lack the capability of capturing long-term relational dependencies between entities and result in inefficient information propagation. Moreover, the absence of a visible reasoning process leads to poor interpretability and credibility of the completions. In this paper, we propose a path-enhanced pre-trained language model-based knowledge graph completion (PEKGC), which employs multi-view generations with multi-hop paths to address issues lacking long-term dependence and interpretability. To get knowledge from local view and long-term view simultaneously, we design a novel triple-level and path-level generations paradigm. Furthermore, to fuse the prediction results of multi-views, we introduce a fact-level reevaluation for both candidate answers and propose a heuristic fusion ranking strategy. Extensive experiments on the benchmark datasets demonstrate that our model significantly improves the performance of the KGC task.

1 Introduction

Knowledge graphs (KGs) are designed to store knowledge in graph-structured format, as seen in Freebase (Bollacker et al., 2008), WordNet (Miller, 1995), and NELL (Carlson et al., 2010). The extensive application of various KGs has greatly benefited numerous downstream tasks, such as question answering, recommendation systems, and information retrieval. However, due to the limited scale of KGs, whether manually or automatically constructed, they invariably suffer from incomplete coverage and fail to encompass the vast expanse of real-world knowledge. This limitation has given rise to the task of knowledge graph completion (KGC), which involves predicting missing links by

Figure 1: An example of PLM-based KGC in triple and path levels. In this triple, (Tu Youyou, Nationality, ?) is a query, and the answer is *China*.

understanding the existing triples within KGs.

Typically, most mainstream KGC methods fall into two categories: embedding-based and path-based methods. Embedding-based methods (Bordes et al., 2013; Yang et al., 2015; Dettmers et al., 2018; Vashishth et al., 2019) focus on mapping entities and relations into a low-dimensional, continuous vector space to capture intrinsic connections, and predict missing links using the learned vector space. By comparison, path-based methods (Das et al., 2018; Qu et al., 2020; Zhu et al., 2021) aim to use the paths between entities and achieve more directly interpretable results. Whereas, both methods aim to directly model all interactions among nodes as possible passing through relation edges. Consequently, they hardly adapt to large-scale growth parameters and knowledge scenarios.

Recently, inspired by the success of pre-training language models (PLMs), such as BERT (Devlin et al., 2019), RoBERTa (Liu et al., 2019), and T5 (Raffel et al., 2020), in NLP tasks, encouraging increased interest in probing PLMs to complete KGs. PLM-based KGC methods not only improve the performance of KGC tasks through the advanced feature extraction capabilities of PLMs but also hold significant potential for introducing high-quality knowledge into large language models. According to the structure of the models, PLM-based models can be divided into two categories: encoder-only models, such as KG-

BERT (Yao et al., 2019), PKGC (Lv et al., 2022), and encoder-decoder models, such as KGT5 (Saxena et al., 2022), KGS2S (Chen et al., 2022). The encoder-only models encode both the query and all candidate entities to calculate their matching confidence. The encoder-decoder models encode the query and then decode possible candidate entities. Overall, PLM-based KGC methods work by converting structured triple-level data into serialized text descriptions sentence and feeding the sentence to PLMs to complete KGs. As illustrated in Figure 1, current PLM-based models (referred to as triple-level PLM) encode the concatenated query text, "*Tu Youyou Nationality [MASK]*", from a "flat" text-described view, and generate the answer entity, *China*, directly.

However, current PLM-based models have primarily flattened triples into a simple triple-level text description, which presents three significant limitations: (i) **low expressiveness**. The embeddings of entities and relations are learned at the triple level, which represents the embeddings are focused only on a local perspective (i.e. one-hop neighbors). Previous research has indicated that relying solely on local relational neighbors for KG learning is not enough (Guo et al., 2019). (ii) **inefficient information propagation**. These models depend solely on one-hop neighbors for aggregating and propagating information, which is highly inefficient for the transfer of semantics and knowledge between entities. (iii) **lack of interpretability**. KGC results are generated directly in response to queries, without the necessary explanations or reasoning, which harm the credibility of completions. Therefore, there is an urgent need for existing methods to leverage rich multi-hop paths of KGs to capture more complex, long-term, or higher-level features to enhance expressiveness, propagation, and interpretability.

To address the aforementioned limitations, in this paper, we propose a Path-enhanced Pre-trained Language Model-based Knowledge Graph Completion method (PEKGC), which employs multi-level generations by an encoder-decoder architecture to tackle issues of lacking long-term dependence and interpretability. To enable PLM-based models capture path-level knowledge from long-term view and bridge relational gaps between multi-hop entities, our model generates candidate entities with reasoning path chains, which also serve as evidence for the generated answers in response to queries. Besides, to extract local knowledge from KGs, our

model also generate answers at a triple level simultaneously. In this way, the model can focus on multi-level knowledge simultaneously and can be cross-validated occurring at both levels. To further re-evaluate and re-rank the joint results of both levels, our model also evaluate answer list at a fact level, i.e., re-calculate the confidence scores of candidate answers generated by two levels. In addition, we use KG soft prompt and position soft prompt to distinguish between KG knowledge and textual knowledge, as well as to mark the internal relationships within triples. Finally, we propose a heuristic fusion ranking method to efficiently fuse and re-rank the generated results of multi-view generations. In summary, the major contributions of this work are as follows:

- We propose a multi-level generation paradigm for knowledge graph completion that captures both local triple-level knowledge and long-term relational dependencies of entities, achieving more directly interpretable results.

- We propose a heuristic fusion ranking strategy for multi-view generations in the inference stage to further combine triple-level and path-level results achieving better ranking performance.

- Extensive experiments are conducted on benchmark datasets, and the results demonstrate that the proposed method [1] outperforms existing state-of-the-art methods.

2 Related Work

2.1 Knowledge Graph Completion

Traditional KGC methods aim to map entities and relations into a low-dimensional and continuous vector space to capture inner connections. These methods can be further subdivided into translation-based methods (Bordes et al., 2013; Sun et al., 2018), semantic matching methods (Yang et al., 2015; Balažević et al., 2019), convolutional neural network-based (CNN-based) methods (Dettmers et al., 2018; Ren et al., 2020), and graph neural network-based (GNN-based) methods (Schlichtkrull et al., 2018; Vashishth et al., 2019). However, with the increase of the scale of KGs, the extraction and expression ability of these methods has gradually encountered bottlenecks. As a result,

---

[1]Our source code is available in supplementary materials.

the performance of the traditional KGC methods becomes hesitant even on benchmark datasets.

2.2 Path-based KGC

To bridge the long-term relational gaps between entities and improve the interpretability of completion results, some methods introduce the multi-hop paths into the KGC task, i.e., path-based methods. These methods can be further subdivided into rule-based methods (Qu et al., 2020; Sadeghian et al., 2019), reinforcement learning-based (RL-based) methods (Das et al., 2018; Lin et al., 2018; Jiang et al., 2023), and propagation path-based methods (Zhu et al., 2021; Zhang et al., 2023). Rule-based methods utilize logical inference and symbolic rules to complete KGs. Even though some of them combine logical rules with embedding or deep learning techniques, but they still suffer from poor generalization and high complexity due to their direct operation on symbols when applied to large-scale KGs. RL-based methods frame multi-hop path reasoning as a finite horizon deterministic partially observed Markov decision process (MDP) and train an agent to navigate on KGs to locate target entities. However, these methods are also limited in scalability for huge-scale KGs due to the vast search space and sparse rewards encountered during training. Propagation path-based methods use relational paths to encode and transmit the intermediate knowledge between entities. Limited by the complexity of propagation, their dimensions are generally small, resulting in weak expression ability and poor scalability.

2.3 Language Model-based KGC

Due to the promising performance of PLMs in few-shot and even zero-shot scenarios, recent research has focused on fine-tuning PLMs for KGC tasks to leverage both the implicit knowledge of PLMs and the structured knowledge of KGs. KG-BERT (Yao et al., 2019) is the first to use BERT for KGC by simply concatenating triples' names as text-based input. Subsequent methods can be categorized into two main types based on their model structures: encoder-only models and encoder-decoder models. Encoder-only models include StAR (Wang et al., 2021), which integrates graph embedding techniques to introduce structured knowledge, CoLE (Liu et al., 2022), which distills selective knowledge between graph embedding and PLMs, PKGC (Lv et al., 2022), which employs soft prompts to convert triples into natural prompt sentences, and

CSProm-KG (Chen et al., 2023), which uses conditional soft prompts to emphasize structural knowledge. Encoder-decoder models include KGT5 (Saxena et al., 2022), which uses a Seq2Seq generative framework to encode query and decode candidate entities, GenKGC (Xie et al., 2022), which introduces entity-aware hierarchical decoding for fast inference, and KG-S2S (Chen et al., 2022), which unifies triples into "flat" text and advance KG soft prompts.

3 Methodology

3.1 Notions

We formally represent a knowledge graph (KG) as $\mathcal{G} = (\mathcal{E}, \mathcal{R}, \mathcal{T})$, where $\mathcal{E}$ is the set of entities, $\mathcal{R}$ is the set of relations, and $\mathcal{T}$ is the set of triples in the KG. Each triple can be expressed as $l = (e_h, r, e_t) \in \mathcal{T}$. For a triple l, there are a set of relational paths $p = \{(e_h, r_1, e_1, ..., r_t, e_t) | (e_h, r_1, e_1) \in \mathcal{T}, ..., (e_{t-1}, r_t, e_t) \in \mathcal{T}\}$ connecting the head entity e_h and the tail entity e_t. Following (Guo et al., 2019), we use Biased Random Walks to generate these paths. Given a query *(Tu Youyou, nationality, ?)*, we can formalize it as $(e_h, r, ?)$, where e_h is the head entity of the query, and r is the relation between the head entity and the tail entity. The task of link prediction in KGC is to infer the tail entity e_t based on the query, and similarly, predicting the head entity e_h for a query $(?, r, e_t)$. Following previous work, for each triple l, we add an inverse triple (e_t, r^{-1}, e_h), where r^{-1} is the inverse relation of r.

3.2 A Seq2Seq Architecture

As illustrated in Figure 2, the proposed PEKGC model follows a sequence-to-sequence (Seq2Seq) architecture, comprising an encoder and a decoder. To train the model to capture knowledge from multi-views, we design two sub-tasks to train the model's capability at different levels (i.e., triple and path levels). Overall, it can be represented as:

$$P(y|x_q) = \prod_{k=1}^{N} P(y_k|x_q, y_{<k}), \quad (1)$$

where x_q is the input sequence, consisting of the concatenated query. For the triple-level generation, y denotes the concatenated target entities' names and descriptions. For the path-level generation, y denotes the concatenated multi-hop reasoning

Figure 2: Overview of proposed PEKGC model, where e_* and r_* represent entities and relations, respectively.

relational paths, target entities' names, and entities' descriptions.

3.3 Two-level Generations

Triple-level Generation To avoid ambiguity issues of entity names (Chen et al., 2022), we introduce entity descriptions to enrich the context information of entities. For the query $(e_h, r, ?)$, we concatenate head entity's name x_h, head entity's description d_h, and relation's name x_r to form their representation on the encoding side, that is:

$$x_q = (x_h, d_h, [\text{SEP}], x_r, [\text{MASK}]), \quad (2)$$

where [SEP] denotes a special separator token, and [MASK] denotes the "?" at the corresponding position to distinguish the queries between $(e_h, r, ?)$ and $(?, r, e_t)$.

On the decoding side, the triple-level task aims to jointly predict the target entity's name and description,

$$y_t = (x_t, d_t). \quad (3)$$

Similar to tail entity predictions, the representations of query and answer for predicting head entities in $(?, r, e_t)$ are as follows:

$$x_q = ([\text{MASK}], x_r, [\text{SEP}], x_t, d_t), \quad (4)$$

$$y_t = (x_h, d_h). \quad (5)$$

Path-level Generation The inputs of path-level generation, x_q, is same as triple-level generation. The goal of its generation is to predict multi-hop reasoning relational paths from head to target entities, target entity's name, and target entity's description simultaneously,

$$y_p = (p_t, x_t, d_t), \quad (6)$$

$$y_p = (p_h, x_h, d_h), \quad (7)$$

where p_t is a concatenated sequence of the relational reasoning paths $p_t = (e_h, r_1, e_1, ..., r_t, e_t)$ from the head entity e_h to the target entity e_t. This sequence serves as a reasoning chain and evidence for the query answer, that is:

$$p_t = (x_h, x_{r_1}, x_{e_1}, ..., x_{r_t}, x_t), \quad (8)$$

where x_{r_*} and x_{e_*} represent the name texts of entities and relations in the path, respectively.

KG Soft Prompt To differentiate between KG and text knowledge, and to emphasize structural knowledge (Chen et al., 2022), we insert KG soft prompts into the encoder's input. Specifically, we define a set of additional trainable prompt embeddings, which are associated with relations of KG. It is worth noting that the number of relations in the KG is significantly smaller than that of entities, thus minimizing the risk of excessive overhead. These embeddings are denoted as $\mathbf{P_r} \in \mathbb{R}^{|\mathcal{R}| \times d}$, where d is the dimension of the encoder. Each relation (r) in the input sequence has a corresponding KG soft prompt $(\mathbf{p_r})$ that is inserted in front of it.

Position Soft Prompt To indicate and prompt the positional relationships among the head entity, relation, and tail entity within a triple, we define a position soft prompt, $\mathbf{P_o} \in \mathbb{R}^{3 \times d}$. This allows the model to learn the internal positional relationship of the triple and effectively distinguish between the predicted head and tail entities.

Instructions Moreover, to further distinguish two-level generation tasks, we insert two specific instruction tags, I_t and I_p, at the beginning of the input sequence: "Predict tail/head entity:" for triple level and "Predict tail/head entity with path:" for path level. Consequently, the input embedding with soft prompts and instructions is updated to:

$$\mathbf{x_q} = [\mathbf{I}; \mathbf{p}_0; \mathbf{x}_h; \mathbf{d}_h; \mathbf{x}_s; \mathbf{p}_1; \mathbf{p}_r; \mathbf{x}_r; \mathbf{p}_2; \mathbf{x}_m], \quad (9)$$

where **I** denotes the encoding of instruction tag, ; denotes a concatenation operation for vectors, $\mathbf{x}_h$ denotes the encoding of head entity's name, $\mathbf{d}_h$ denotes the encoding of head entity's description, $\mathbf{x}_r$ denotes the encoding of relation's name, $\mathbf{p}_r$ represents the KG soft prompt related to r, $\mathbf{p}_0$, $\mathbf{p}_1$ and $\mathbf{p}_2$ are position soft prompts, and $\mathbf{x}_s$ and $\mathbf{x}_m$ are embeddings of special tokens.

Training   For both triple-level and path-level generations, the goals are to predict the answer sequence y_t or y_p. Therefore, the optimization objective is given by:

$$L_g = -\log P_\theta(y|x_q), \qquad (10)$$

where θ represents the parameters of the model.

3.4   Re-evaluation and Fusion Ranking

Fact-level Re-evaluation   To reevaluate and reorder the two group results from triple-level and path-level generations, we also train the encoder of model at fact level. For instance, given a candidate triple $\hat{l} = (e_h, r, \hat{e}_t)$ predicted by triple-level or path-level generations, its confidence score is calculated as:

$$\phi(\mathbf{e}_{hr}, \hat{\mathbf{e}}_t) = \cos(\mathbf{e}_{hr}, \hat{\mathbf{e}}_t) = \mathbf{e}_{hr} \cdot \hat{\mathbf{e}}_t, \qquad (11)$$

where $\mathbf{e}_{hr}$ is the max pooling of the combination encoding of e_h and r, $\hat{\mathbf{e}}_t$ is the encoding of the predicted candidate entity $\hat{e}_t$, and $\cdot$ denotes a dot product operation.

As a result, the training objective of the fact-level encoder is to maximize the confidence scores of the correct triples $(e_h, r, e_t)|(e_h, r, e_t) \in \mathcal{T}$:

$$\mathrm{argmax}\,\phi(\mathbf{e}_{hr}, \mathbf{e}_t). \qquad (12)$$

Consequently, we take correct triples as positive targets and the other entities as negative targets in the same batch during training. Following ([Chen et al., 2020](#); [Wang et al., 2022](#)), we use the InfoNCE loss to achieve this goal:

$$L_f = -\log \frac{e^{(\phi(\mathbf{e}_{hr}, \mathbf{e}_t)-\gamma)/\tau}}{e^{(\phi(\mathbf{e}_{hr}, \mathbf{e}_t)-\gamma)/\tau} + \sum_{i=1}^{N} e^{\phi(\mathbf{e}_{hr}, \mathbf{e}_t')/\tau}}, \qquad (13)$$

where $\gamma > 0$ is a margin factor that encourages the model to increase the confidence scores of the correct triples, and τ is a temperature factor to adjust the relative importance of negatives. The loss of head entity prediction is similar.

Fusion Ranking   In view of the extra consumption of computing resources by reevaluation operation, it is necessary to prune the reevaluation process. Consequently, we propose a heuristic fusion ranking method to cut out unnecessary reevaluations and further improve performance. First, we introduce two definitions:

Definition 1. *(Consistent Prediction) Given a query with triple-level predicted rank list $\hat{A}_t$ and path-level predicted rank list $\hat{A}_p$, it is a consistent prediction if there exists $\hat{A}_{t_0} = \hat{A}_{p_0}$, where $\hat{A}_{t_0}$ and $\hat{A}_{p_0}$ are highest ranking of their list. A set of consistent predictions is given by:*

$$A_C = \{\hat{A}_t | \hat{A}_{t_0} = \hat{A}_{p_0}\}. \qquad (14)$$

Definition 2. *(Hard Prediction) Given a query with triple-level predicted rank list $\hat{A}_t$ and path-level predicted rank list $\hat{A}_p$, it is a hard prediction if there exists $|\hat{A}_t \cap \hat{A}_p| \leq \alpha$ or $|\hat{A}_t| \geq \beta$, $\alpha, \beta \geq 0$. A set of hard predictions is given by:*

$$A_H = \{\hat{A}_t \cup \hat{A}_p \,||\, \hat{A}_t \cap \hat{A}_p| \leq \alpha, |\hat{A}_t| \geq \beta\}. \qquad (15)$$

Consistency prediction indicates that the predicted entities from the two views are relatively aligned, which is a simple prediction. Therefore, we can directly select the path-level ranking as the final result. Hard prediction indicates significant discrepancies between the two views, making the prediction more complex. In these cases, it is necessary to reevaluate and reorder the candidate entities (generated at both levels) using fact-level evaluator. For other cases, that belong to general prediction, we can use any rank or reevaluation rank as the final result. To simplify the actual process, we also choose the path-level rank as the final result.

4   Experiments

To investigate our model's efficiency and effectiveness, we evaluate KGC (link prediction), which aims to produce a ranking list of all entities for a query $((e_h, r, ?)$ or $(?, r, e_t))$, performance on benchmark KGs. We also conduct an ablation study to demonstrate the impact of each proposed module. Additionally, we present examples of reasoning paths in a case study to illustrate that PEKGC effectively predicts high-quality reasoning paths.

4.1   Experiment Setup

Datasets   We adopt two benchmark datasets for the link prediction task, i.e., WN18RR ([Toutanova et al., 2015](#)) and FB15k-237 ([Dettmers et al., 2018](#)). Table 2 lists the details of these two datasets.

Methods	PLM	WN18RR				FB15k-237			
		MRR	Hits@1	Hits@3	Hits@10	MRR	Hits@1	Hits@3	Hits@10
KG-BERT	BERT	21.6	4.1	30.2	52.4	-	-	-	42.0
StAR	RoBERTa	40.1	24.3	49.1	70.9	29.6	20.5	32.2	48.2
GenKGC	BART	-	28.7	40.3	53.5	-	19.2	35.5	43.9
KGT5	T5	50.8	48.7	-	54.4	27.6	21.0	-	41.4
CoLE	BERT	58.5	53.2	60.7	68.9	**38.7**	29.3	42.6	**57.0**
KG-S2S	T5	57.4	53.1	59.5	66.1	33.6	25.7	37.3	49.8
CSProm-KG	BERT	57.5	52.2	59.6	67.8	35.8	26.9	39.3	53.8
PDKGC	RoBERTa	57.7	50.5	60.9	**71.3**	37.9	28.5	41.5	56.6
PEKGC (ours)	T5	**60.0**	**55.3**	**63.1**	68.8	38.1	**31.0**	**42.8**	52.1

Table 1: The performance of PLM-based KGC models on the link prediction task. The Hits@1, Hits@3, Hits@10, and MRR metrics are multiplied by 100. We **highlight** the best approaches.

Metrics Similar to recent works, we use the mean reciprocal rank (MRR) and Hits@k to evaluate the performance of all models, where Hits@k represents the fraction of positive triples ranked in the top k positions.

Settings We realize PEKGC on A100 GPU using the T5-base model (Raffel et al., 2020) with the Adam optimizer, and follow the standard T5 unsupervised training paradigm. Following KG-S2S (Chen et al., 2022), we enclose the entities' descriptions in square brackets, wrap paths in parentheses, and use the "|" token as a special separator. Answer texts are also enclosed by the T5 special tokens. During the data preparation phase, we use Biased Random Walks algorithm to generate related paths for triples in the training set, and tuning the number of paths per triple within the range of {1, 2, 3, 4}. In the training stage, the number of training epochs is set to 100 and 20, with the entity description lengths set to 40 and 80 for the WN18RR and FB15k-237 datasets, respectively. The mini-batch size for the main tasks is chosen from {16, 32, 64}. To maximize the performance of fact-level reevaluation, we search for the optimal mini-batch size within {256, 512, 1024}. The maximum input token length for the encoder is set to 512. We use a learning rate of 0.001, an encode sequence dropout rate of 0.1, a margin factor of 0.02, and a temperature factor of 0.05. In the inference stage, the model generates the raw text without special tokens. We set the maximum output length to 150 and the number of samples for beam search to 40. For hard predictions, we search for α within {1, 2, 3, 4, 5}, and β within {2, 5, 10, 15, 20}.

Baselines Based on link prediction task, we compare our approach with eight PLM-based KGC methods: KG-BERT (Yao et al., 2019), StAR

Datasets	#Ent	#Rel	#Tri	#Degree
WN18RR	40945	11	86835	2.19
FB15k-237	14505	237	272115	19.74

Table 2: Datasets are used in the experiments.

(Wang et al., 2021), GenKGC (Xie et al., 2022), KGT5 (Saxena et al., 2022), CoLE (Liu et al., 2022), KG-S2S (Chen et al., 2022), CSProm-KG (Chen et al., 2023), and PDKGC (Geng et al., 2023).

4.2 Main Results

Table 1 presents the link prediction results for PLM-based models on the WN18RR and FB15k-237 datasets. All baseline results are taken from their respective papers' best performances (Liu et al., 2022; Chen et al., 2022, 2023; Geng et al., 2023). The experimental results confirm that our PEKGC model achieves satisfactory performance compared to baseline models across most metrics. Notably, our PEKGC improves the Hits@1 metric by 4.0% and 5.8% on the WN18RR and FB15k-237 datasets, respectively, compared to the previous best PLM-based models. Particularly on the FB15k-237 dataset, our model significantly reverses the situation where the encoder-decoder approaches (e.g., GenKGC, KGT5, and KG-S2S) underperform encoder-only approaches (e.g., CoLE, CSProm-KG and PDKGC) on Hits@1. We attribute this to Definition 1 of the fusion ranking paradigm, which employs cross-verification of two-level predictions on the top-one results, further improving Hits@1, as evidenced in Table 4. Compared with the improvement of MRR, Definition 1 significantly boosts the performance of Hits@1. Additionally, the results in the table also suggest that both definitions should be used together to

ID	Levels	Answers
		Query: (?, MemberOfDomainRegion, Facer[A dated Briticism]) $\Rightarrow$ Answer: United Kingdom of Great Britain and Northern Ireland
1	Triple Level	United Kingdom of Great Britain and Northern Ireland
	Path Level	Facer $\xrightarrow{MemberOfDomainRegion^{-1}}$ England $\xrightarrow{HasPart^{-1}}$ United Kingdom of Great Britain and Northern Ireland
		Query: (Telephone, VerbGroup, ?]) $\Rightarrow$ Answer: Call
2	Triple Level	Call
	Path Level	Telephone $\xrightarrow{SynsetDomainTopicOf^{-1}}$ Call
		Query: (?, MusicArtistsGenre, Dio]) $\Rightarrow$ Answer: Rock Music
3	Triple Level	Hard Rock & *Heavy Rock* & *Thrash Metal* & *Doom Metal*
	Path Level	Dio $\xrightarrow{MusicArtistsGenre^{-1}}$ Hard Rock $\xrightarrow{MusicParentGenre}$ Rock Music
		Query: (Asheville, LocationTimeZones, ?) $\Rightarrow$ Answer: Eastern Time Zone
4	Triple Level	Eastern Time Zone
	Path Level	Asheville $\xrightarrow{Contains^{-1}}$ Buncombe County $\xrightarrow{LocationTimeZones}$ Eastern Time Zone

Table 3: Four examples are predicted at triple and path level, respectively. The first two queries come from the WN18RR dataset, and the other two comes from the FB15k-237 dataset. The inverse relations of existing relations are denoted by $^{-1}$.

Datasets	Models	MRR	Hits@1
WN18RR	PEKGC	**60.0**	**55.3**
	-Definition 1	59.7	54.1
	-Definition 2	57.8	53.1
FB15k-237	PEKGC	**38.1**	**31.0**
	-Definition 1	36.7	28.9
	-Definition 2	34.6	28.7

Table 4: Comparison of MRR and Hits@1 between PEKGC and models without partial fusion ranking.

Datasets	Models	MRR	Hits@1
WN18RR	PEKGC	**60.0**	**55.3**
	-Path Level	57.4	53.1
	-Soft Prompt	59.5	54.2
	-Fact Level	57.1	52.4
	-Fusion Ranking	59.6	54.1
FB15k-237	PEKGC	**38.1**	**31.0**
	-Path Level	33.6	25.7
	-Soft Prompt	36.4	29.3
	-Fact Level	33.7	26.3
	-Fusion Ranking	34.4	28.0

Table 5: Comparison of MRR and Hits@1 between PEKGC and models without path-level generation, soft prompt, fact-level reevaluation or fusion ranking.

achieve greater improvement.

We observe that PEKGC's performance is weaker than some state-of-the-art models in Hits@10, which can be attributed to common limitations of encoder-decoder models. Since these models rely on generating candidate answers through a decoder, the diversity of answers is constrained. As a result, encoder-decoder models generally face a significant disadvantage on larger rank scales compared to encoder-only models, which can match all entities of the KGs by calculating their matching confidence scores. However, our proposed model still outperforms previous encoder-decoder methods across all indicators. These phenomena demonstrate the effectiveness of the proposed PEKGC, as it indeed improves the generation abilities of encoder-decoder models through path-enhanced multi-level generations and the heuristic fusion ranking paradigm.

4.3 Ablation Study

We conducted an ablation study on two benchmark datasets to evaluate the effectiveness of the proposed modules. As shown in Table 5, "-Path Level" refers to training and predicting solely at the triple level, "-Fact Level" indicates the exclusion of fact-level reevaluations and the reevaluation of hard predictions, "-Soft Prompt" involves removing KG and position prompts from the model, and "-Fusion Ranking" means eliminating the heuristic fusion ranking paradigm and using fact-level reevaluation ranking as the final results in the inference stage.

(a) The value of α.   (b) The value of β.   (c) The number of paths.

Figure 3: Comparison experiments among different parameters on the WN18RR dataset.

We observe that removing any of these modules leads to a significant performance drop across both datasets. Additionally, the final performance is not good when using only the fusion ranking without reevaluating hard predictions, further emphasizing the necessity of reevaluating hard predictions as outlined in Definition 2. On the whole, these ablations validate the effectiveness of the proposed modules.

4.4 Case Study

To gain insight into the difference between the two-level generations, we present four typical queries answered at both the triple and path levels, as shown in Table 3. Triple-level predictions provide entity answers directly, while path-level prediction offers both the entity answer and a reasoning path, which serves as a reasoning chain, significantly enhancing the interpretability of the predictions.

In particular, the third query and answer show the difference in accuracy between the two-level generations. Although "Hard Rock" is a correct answer, "Heavy Rock", "Thrash Metal" and "Doom Metal" are completely fabricated answers produced by the triple-level decoder. The reasons for this phenomenon are twofold: i) Encoder-decoder models adopt a teacher-forcing strategy during training, leading to reduced scalability when predicting unseen triples, especially in 1-N or N-N triples. ii) At times, predicting the correct results directly can be challenging due to the lack of necessary prior knowledge or a step-by-step reasoning process. The paths between entities can provide the required prior knowledge and serve as a reasoning chain to address this issue. The above demonstrates the necessity of introducing paths to enhance the robustness and expansibility of completions. Additionally, the paths incorporated into the generation process play a crucial role in providing human-understandable interpretability.

4.5 Further Analysis

To investigate the impact of key hyperparameters on the model's performance, we conducted further experiments using the WN18RR dataset.

Hyperparameters of Fusion Ranking For the two parameters in fusion ranking, we aim for a smaller value of α and a larger value of β to minimize the number of results requiring re-evaluation, thereby reducing computational overhead. As shown in Figure 3(a)-3(b), an α value of around 4 yields the best performance, while a β value of approximately 10 produces optimal results. Therefore, we recommend setting α to about once to twice the average degree of KG and β to be one-half to one-quarter of the beam size.

Path Numbers for Each Triple Figure 3(c) shows the performance impact of using different numbers of paths for each triple. We observe that the introduction of paths improves the model's performance. However, when the number of paths is ≥ 3, there is no significant improvement. This indicates that an appropriate number of paths is sufficient to achieve satisfactory improvement.

5 Conclusion

We propose a multi-view generation framework, PEKGC, for KGC tasks that captures both local triple-level knowledge and long-term path-level dependencies of entities, achieving more directly interpretable results. To further combine triple-level and path-level results to achieve better ranking performance, we propose a heuristic fusion ranking paradigm for multi-view generations during the inference stage. Experimental results demonstrate the effectiveness of our approach. In future work, we aim to address the challenges of diversity and generalization of PLM-based models.

6 Limitations

Our proposed PEKGC model significantly improves the performance of encoder-decoder KGC models. However, three challenges remain for future work: i) The diversity of generated results is limited, resulting in a high number of identical and homogeneous outputs, which affects the models' universality and robustness; ii) Decoders tend to favor generating seen entities, leading to challenges in flexibility and generalization, especially in 1-N and N-N triples; iii) The generated entities may include fabricated ones that do not exist in KGs, further reducing the number of effective entities produced.

7 Ethics Considerations

Our work adheres to the guidelines outlined in the ACL Code of Ethics. As knowledge graph completion is a widely accepted and long-standing research task, we do not see any significant ethical concerns. As for the scientific artifacts used in our experiments, we confirm to comply with the corresponding intended use and licenses.

References

Ivana Balažević, Carl Allen, and Timothy Hospedales. 2019. Tucker: Tensor factorization for knowledge graph completion. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5185–5194.

Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. 2008. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pages 1247–1250.

Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. 2013. Translating embeddings for modeling multi-relational data. *Advances in neural information processing systems*, 26.

Andrew Carlson, Justin Betteridge, Bryan Kisiel, Burr Settles, Estevam R Hruschka, and Tom M Mitchell. 2010. Toward an architecture for never-ending language learning. In *Twenty-Fourth AAAI conference on artificial intelligence*.

Chen Chen, Yufei Wang, Bing Li, and Kwok-Yan Lam. 2022. Knowledge is flat: A seq2seq generative framework for various knowledge graph completion. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 4005–4017.

Chen Chen, Yufei Wang, Aixin Sun, Bing Li, and Kwok-Yan Lam. 2023. Dipping plms sauce: Bridging structure and text for effective knowledge graph completion via conditional soft prompting. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 11489–11503.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. 2020. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR.

Rajarshi Das, Shehzaad Dhuliawala, Manzil Zaheer, Luke Vilnis, Ishan Durugkar, Akshay Krishnamurthy, Alex Smola, and Andrew McCallum. 2018. Go for a walk and arrive at the answer: Reasoning over paths in knowledge bases using reinforcement learning. In *International Conference on Learning Representations*.

Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. 2018. Convolutional 2d knowledge graph embeddings. In *Thirty-second AAAI conference on artificial intelligence*.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186.

Yuxia Geng, Jiaoyan Chen, Yuhang Zeng, Zhuo Chen, Wen Zhang, Jeff Z Pan, Yuxiang Wang, and Xiaoliang Xu. 2023. Prompting disentangled embeddings for knowledge graph completion with pre-trained language model. *Available at SSRN 4790015*.

Lingbing Guo, Zequn Sun, and Wei Hu. 2019. Learning to exploit long-term relational dependencies in knowledge graphs. In *International conference on machine learning*, pages 2505–2514.

Chunyang Jiang, Tianchen Zhu, Haoyi Zhou, Chang Liu, Ting Deng, Chunming Hu, and Jianxin Li. 2023. Path spuriousness-aware reinforcement learning for multi-hop knowledge graph reasoning. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 3173–3184.

Xi Victoria Lin, Richard Socher, and Caiming Xiong. 2018. Multi-hop knowledge graph reasoning with reward shaping. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3243–3253.

Yang Liu, Zequn Sun, Guangyao Li, and Wei Hu. 2022. I know what you do not know: Knowledge graph embedding via co-distillation learning. In *Proceedings of the 31st ACM international conference on information & knowledge management*, pages 1329–1338.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Xin Lv, Yankai Lin, Yixin Cao, Lei Hou, Juanzi Li, Zhiyuan Liu, Peng Li, and Jie Zhou. 2022. Do pretrained models benefit knowledge graph completion? a reliable evaluation and a reasonable approach. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 3570–3581.

George A Miller. 1995. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11):39–41.

Meng Qu, Junkun Chen, Louis-Pascal Xhonneux, Yoshua Bengio, and Jian Tang. 2020. Rnnlogic: Learning logic rules for reasoning on knowledge graphs. In *International Conference on Learning Representations*.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67.

Feiliang Ren, Juchen Li, Huihui Zhang, Shilei Liu, Bochao Li, Ruicheng Ming, and Yujia Bai. 2020. Knowledge graph embedding with atrous convolution and residual learning. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 1532–1543.

Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. 2019. Drum: End-to-end differentiable rule mining on knowledge graphs. *Advances in Neural Information Processing Systems*.

Apoorv Saxena, Adrian Kochsiek, and Rainer Gemulla. 2022. Sequence-to-sequence knowledge graph completion and question answering. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2814–2828.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. 2018. Modeling relational data with graph convolutional networks. In *15th International Conference on Extended Semantic Web Conference, ESWC 2018*, pages 593–607.

Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. 2018. Rotate: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations*.

Kristina Toutanova, Danqi Chen, Patrick Pantel, Hoifung Poon, Pallavi Choudhury, and Michael Gamon. 2015. Representing text for joint embedding of text and knowledge bases. In *Proceedings of the 2015 conference on empirical methods in natural language processing*, pages 1499–1509.

Shikhar Vashishth, Soumya Sanyal, Vikram Nitin, and Partha Talukdar. 2019. Composition-based multi-relational graph convolutional networks. In *International Conference on Learning Representations*.

Bo Wang, Tao Shen, Guodong Long, Tianyi Zhou, Ying Wang, and Yi Chang. 2021. Structure-augmented text representation learning for efficient knowledge graph completion. In *Proceedings of the Web Conference 2021*, pages 1737–1748.

Liang Wang, Wei Zhao, Zhuoyu Wei, and Jingming Liu. 2022. Simkgc: Simple contrastive knowledge graph completion with pre-trained language models. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4281–4294.

Xin Xie, Ningyu Zhang, Zhoubo Li, Shumin Deng, Hui Chen, Feiyu Xiong, Mosha Chen, and Huajun Chen. 2022. From discrimination to generation: Knowledge graph completion with generative transformer. In *ICLR 2022 Workshop on Deep Learning on Graphs for Natural Language Processing*.

Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. 2015. Embedding entities and relations for learning and inference in knowledge bases. In *International Conference on Learning Representations*.

Liang Yao, Chengsheng Mao, and Yuan Luo. 2019. Kg-bert: Bert for knowledge graph completion. *arXiv preprint arXiv:1909.03193*.

Yongqi Zhang, Zhanke Zhou, Quanming Yao, Xiaowen Chu, and Bo Han. 2023. Adaprop: Learning adaptive propagation for graph neural network based knowledge graph reasoning. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 3446–3457.

Zhaocheng Zhu, Zuobai Zhang, Louis-Pascal Xhonneux, and Jian Tang. 2021. Neural bellman-ford networks: A general graph neural network framework for link prediction. *Advances in Neural Information Processing Systems*, 34.