Inductive Biases for Object-Centric Representations
in the Presence of Complex Textures

Abstract

Understanding which inductive biases could be helpful for the unsupervised learning of object-centric representations of natural scenes is challenging. We use neural style transfer to generate datasets where objects have complex textures while still retaining ground-truth annotations. We find that methods that use a single module to reconstruct both the shape and visual appearance of each object learn more useful representations and achieve better object separation. In addition, we observe that adjusting the latent space size is not sufficient to improve segmentation performance. Finally, the downstream usefulness of the representations is significantly more strongly correlated with segmentation quality than with reconstruction accuracy.

Figure 1: Left: samples from the original datasets. Right: samples from the same datasets with neural style transfer.

1 INTRODUCTION

A core motivation for object-centric learning is that humans interpret complex environments such as natural scenes as the composition of distinct interacting objects. Evidence for this claim can be found in cognitive psychology and neuroscience (Spelke, 1990; Téglás et al., 2011; Wagemans, 2015), particularly in infants (Dehaene, 2020, Chapter 3). Additionally, these concepts have already been successfully applied, e.g., to reinforcement learning (Vinyals et al., 2019; Berner et al., 2019; Mambelli et al., 2022) and physical modelling (Battaglia et al., 2016; Sanchez-Gonzalez et al., 2020). Current object-centric learning approaches try to merge the advantages of connectionist and symbolic methods by representing each object with a distinct vector (Greff et al., 2020). The problem of object separation becomes central for unsupervised methods because, with no additional information other than the data itself, learning to isolate objects in the input can arguably be a challenging task. Several methods

have been proposed to provide inductive biases to achieve this objective (Burgess et al. (2019); Engelcke et al. (2020b); Locatello et al. (2020); Engelcke et al. (2020a); Kipf et al. (2021); Engelcke et al. (2021); see related work in Section 4 for additional references). However, they are typically tested on relatively simple datasets where the objects show little variability in their texture, often being monochromatic. This characteristic may allow object-centric models to successfully separate objects by relying solely on low-level characteristics, such as color (Greff et al., 2019), over more desirable high-level ones, such as shape or even behavior in videos (Kipf et al., 2021).

Little research has been done in the direction of natural objects (Karazija et al., 2021; Engelcke et al., 2021; Kipf et al., 2021), as datasets with such characteristics often do not feature samples that provide exhaustive knowledge of the underlying factors of variation, which are very rich in

Submitted to the 38th Conference on Uncertainty in Artificial Intelligence (UAI 2022). **To be used for reviewing only**.

natural scenes. For this reason, unsupervised methods struggle to learn object-centric representations, and our current understanding regarding the reasons why they are failing is limited (Greff et al., 2019, Section 5).

In this paper, we conduct a systematic experimental study on the inductive biases necessary to learn object-centric representations when objects have complex textures. We make practical choices to obtain significant and interpretable results. We focus on static images and use neural style transfer (Gatys et al., 2016) to apply complex textures to the objects of the Multi-dSprites (Kabra et al., 2019) and CLEVR (Johnson et al., 2017) datasets, as shown in Fig. 1. The increase in complexity is, therefore, controlled. On the one hand, we still have all of the advantages of a procedurally generated dataset, with knowledge over the characteristics of each object, thus avoiding the above-mentioned pitfalls of natural datasets. On the other hand, we present a much more challenging task for the models than the type of data commonly used in unsupervised object-centric learning research.

We investigate MONet (Burgess et al., 2019) and Slot Attention (Locatello et al., 2020), two popular and successful approaches for unsupervised object-centric learning. Both are slot-based autoencoder models that learn to represent objects separately and in a common format. The Slot Attention autoencoder obtains object representations by applying Slot Attention to a convolutional embedding of the input, and then decodes each object representation into RGB color channels and an alpha mask, thus reconstructing both shape and visual appearance via a *single* component. In contrast, MONet reconstructs them with *two* components: a recurrent attention network that segments the input into objects, and a variational autoencoder (VAE) (Kingma and Welling, 2014; Rezende et al., 2014) that separately learns a representation for each object by learning to reconstruct its shape and visual appearance.

A crucial difference between MONet and Slot Attention is that, in MONet, the shape reconstructed by the VAE is *not* used to reconstruct the final image, while the shape from the recurrent attention network is used instead. To still have shape information in the latent representation of the VAE, the training loss includes a KL divergence between the mask predicted by the VAE and the one predicted by the attention network. Therefore shape and visual appearance are, in effect, *separate* unless the KL divergence provides a strong enough signal. Additionally, the learning dynamics are substantially different, as the modules responsible for shape and visual appearance do not share weights.

For this study, we posit two desiderata for object-centric models, adapted from Dittadi et al. (2021b):

Desideratum 1. *Object separation and reconstruction.* The models should have the ability to accurately separate and reconstruct the objects that are present in the input, even those with complex textures. For the models considered here,

this means that they should be able to correctly segment the objects and reproduce their properties in the reconstruction, including their texture.

Desideratum 2. *Object representation.* The models should capture and represent the fundamental properties of each object present in the input. When ground-truth properties are available for the objects, this can be evaluated via a downstream prediction task.

We summarize our **main findings** as follows:

1. Models that better balance the importance of both shape and visual appearance of the objects seem to be less prone to what we call *hyper-segmentation* (see Section 3). We show how this can be achieved with an architecture that uses a single module to obtain both shape and visual appearance of each object. When this is not the case, it becomes significantly more challenging for a model to correctly separate objects and learn useful representations.

2. Hyper-segmentation of the input leads to the inability of the model to successfully encode the characteristics of the elements present in the input. Separation is a reliable indicator of the quality of the representations.

3. The *representation bottleneck* is not sufficient to regulate a model's ability to segment the input. Tuning other hyperparameters such as encoder and decoder capacity appears to be necessary.

In the remainder of this paper, we will present the methods and experimental setup underlying our study, discuss our findings, and lay out practical suggestions for researchers in object-centric learning who might be interested in scaling these methods to natural images.

2 METHODS

In this section, we outline the elements of our study, highlighting the reasons behind our choices.

Datasets. Similarly to Dittadi et al. (2021b), we use neural style transfer (Gatys et al., 2016) to increase the complexity of the texture of the objects in the Multi-dSprites and CLEVR datasets (see Appendix B for details). This allows for textures that have high variability but are still correlated with the shape of the object, as opposed to preset patterns as done in Greff et al. (2019) and Karazija et al. (2021) or completely random ones. We apply neural style transfer to the entire image and then select the objects using the ground-truth segmentation masks (see Fig. 1). Keeping the background simple allows for a more straightforward interpretation of the models' performance.

Models. The models we study are MONet (Burgess et al., 2019) and Slot Attention (Locatello et al., 2020), that ap-

| (a) MONet, baseline. | (b) MONet, best model. |

| (c) Slot Attention, baseline. | (d) Slot Attention, best model. |

Figure 2: Reconstruction and separation performance on Multi-dSprites (from the validation set). From left to right in each subfigure: original input, final reconstruction, and product of the reconstruction and mask for each of the six slots. The improved architecture for Slot Attention splits objects less often. MONet still fails to separate objects correctly although it blurs the reconstructions. See Fig. 13 (Appendix G) for similar results on CLEVR.

proach the problem of separation in two distinct ways, as mentioned in Section 1. MONet uses a recurrent attention module to compute the shape of the objects, and only later is this combined with the visual appearance computed by the VAE from the object representations. Instead, Slot Attention incorporates everything into a single component, with the shape and visual appearance of each object reconstructed from the respective object representation.

Evaluation. Following the two desiderata in Section 1, we separately focus on the *separation*, *reconstruction*, and *representation* performance of the models. *Separation* is measured by the Adjusted Rand Index (ARI) (Hubert and Arabi, 1985), which quantifies the similarity between two partitions of a set. The ARI is 0 when the two partitions are random and 1 when they are identical up to a permutation of the labels. *Reconstruction* is measured using the Mean Squared Error (MSE) between input and reconstructed images. *Representation* is measured by the performance of a simple downstream model trained to predict the properties of each object using only the object representations as inputs. Following previous literature (Locatello et al., 2020; Dittadi et al., 2021b), we match ground-truth objects with object representations such that the overall loss is minimized.

Performance studies. We first establish the *baseline* performance of the models on the style transfer datasets when using the hyperparameters specified in the original papers (for MONet we use parameters suggested by Greff et al. (2019)). We then vary parameters and architectures in an attempt to improve performance. In MONet, we modify the

U-Net used in the attention module by reducing the number of skip connections, we change the latent space size, the number of channels in the encoder and decoder of the VAE, and the β and σ parameters used in the training objective (Burgess et al., 2019). In Slot Attention, we increase the number of layers and channels in both encoder and decoder and increase the size of the latent space. For both models, we investigate how the latent space size alone affects performance. We use multiple random seeds to account for variability in performance (further details in Appendix E).

3 EXPERIMENTS

In this section, we present and discuss the experimental results of our study. We first look at how different architectural biases affect object separation. Then, we investigate representation performance with a downstream property prediction task. Finally, we study how the latent space size alone affects object separation and reconstruction quality.

Architectural biases. Fig. 2 shows the qualitative performance of a selection of models. The MONet baseline (Fig. 2a) shows a rather peculiar behavior: the scene is segmented primarily according to color so that each slot represents fragments of multiple objects that share the same color. We call this behavior *hyper-segmentation*. On the other hand, the Slot Attention baseline (Fig. 2c) produces blurred reconstructions and avoids hyper-segmentation. Here, some objects are still split across more than one slot but, unlike in MONet, we do not observe multiple objects that are far

Figure 3: Qualitative results for the reconstruction of the visual appearance of the objects on Multi-dSprites (from the validation set). In each of the 4 groups, we show the input (leftmost image) and the reconstruction of the visual appearance from each of the six slots, before masking. From the top: MONet Baseline, MONet Best Model, Slot Attention Baseline, Slot Attention Best Model. MONet primarily reconstructs plain colors with little to no regard to objects, while Slot Attention consistently separates objects even in the presence of textures. In Fig. 13 (Appendix G), we show similar results on CLEVR. See also Fig. 12 for results on additional images from Multi-dSprites.

Figure 4: Bar plots of the median performance of the different seeds trained for each of the indicated models (error bars denote 95% confidence intervals). Top: ARI (↑) and MSE (↓) for each dataset and model. Bottom: performance of the downstream model on each feature of the objects. Accuracy is used for categorical features and R^2 for numerical features. A random guess baseline is shown in purple.

apart in the scene being (partially) modeled by the same slot. We observe this quantitatively in Fig. 4 (two uppermost plots): compared to the Slot Attention baseline, the MONet baseline has a significantly worse ARI score but a considerably better MSE. Fig. 13 in Appendix G shows similar results on CLEVR.

These observations can guide our search for better model parameters. Slot Attention is blurring away the small details of the texture and instead focuses on the shape to separate them. MONet, instead, achieves good reconstructions but does so by using the attention module to select pixels that share the same color, as opposed to entire objects, while the VAE simply reconstructs plain colors (see Appendix G for more details). Therefore, for MONet we attempt to sacrifice some reconstruction quality in exchange for better object separation. For Slot Attention, we investigate whether improving the reconstructions negatively affects object separation. We refer to Appendix E for further details and results on the hyperparameter search for MONet and Slot Attention.

When qualitatively looking at the results obtained by the hyperparameter search performed for MONet, we notice a consistent inability of the "component VAE" to capture different characteristics other than simple colors (see Fig. 3), even when strongly penalizing the VAE for reconstructing shapes that are inconsistent with the masks computed by the recurrent attention network (which are directly used for reconstruction). Here, we show and discuss quantitative and qualitative results for the combination of hyperparameters that achieves the best performance, which we call *best model*.

In Fig. 2b, we see persisting hyper-segmentation even though the reconstructions are now blurred. For the best Slot Attention model (Fig. 2d), we observe that the quality of reconstructions has improved, and that the model more often represents an entire object in a single slot. Although the ARI for MONet has also improved, the separation problem is still far from solved, while Slot Attention shows a significant improvement both in terms of ARI and MSE as shown in the two uppermost plots in Fig. 4. Note that, although the ARI has improved from the baseline, the best Slot Attention model cannot achieve a very high ARI score in Multi-dSprites, unlike in CLEVR. The likely reason is that, when a significant portion of an object is occluded by another, the visible shape is being altered significantly and the edges of objects are not clear. Therefore, two explanations of the same scene can still be reasonable while not corresponding to the ground truth. This extreme overlap never happens in CLEVR because of how the dataset was generated (Johnson et al., 2017), which partly explains the difference in ARI score.

Overall, even when MONet partially sacrifices reconstruction quality and begins to blur away the details, hyper-segmentation is still present, as evidenced by our qualitative and quantitative analyses. This suggests that the separation problem in MONet may not simply be caused by the training objective, but rather by its architectural biases. Indeed, improving the reconstruction performance of Slot Attention has, instead, yielded both better separation and more detailed reconstructions, suggesting that generating shape and appearance using a single module is a more favorable

Figure 5: Rank correlation of the ARI and MSE scores with downstream property prediction performance on CLEVR and Multi-dSprites. The correlations are computed over *all* the models trained in our study.

inductive bias for learning representations of objects with complex textures.

Representation performance. To understand the role of separation when learning object-centric representations, we explore the performance on a downstream property prediction task. A model predicts the feature of each object starting from its representation (see Appendix C.1 for details). From Fig. 4, we observe how MONet fails to capture some of the properties in the representations and consistently performs worse than Slot Attention, for both the baseline and the improved versions. This suggests that, as highlighted in Dittadi et al. (2021b), a model that is not capable of correctly separating objects will also fail to accurately represent them.

The trend is also clear from Fig. 5, which shows that a higher ARI score strongly correlates with an increased performance of the downstream model on all object properties. The correlation with MSE is much weaker, which highlights how *strong visual reconstruction performance is not the ultimate indicator for good object representations*. This result does not contradict previous findings (Dittadi et al., 2021b) as here the properties we expect the downstream model to predict have little to do with the texture of the object and, therefore, the model can have poorer reconstructions while still obtaining useful representations.

Representation bottleneck. Object representations are typically obtained by using a low-dimensional latent space for each object. This constitutes a bottleneck in the model, which we term *representation bottleneck* (see Appendix A). Here, we investigate how the size of this bottleneck affects a model's performance.

We observe from Fig. 6 that the MSE improves for both MONet and Slot Attention when the latent space size increases. However, for MONet this comes with a decrease in separation performance. For Slot Attention, when the latent space reaches a critical size (256 in CLEVR and 512 in Multi-dSprites), the performance degrades, and the variability across seeds increases drastically, suggesting this may be due to optimization problems during training. The increase in latent space size arguably increases the model's capacity, but it does not prove to be enough to improve the separation and reconstruction performance significantly. Instead, we

can obtain considerable improvements only by changing architecture.

4 RELATED WORK

Learning representations that reflect the underlying structure of data is believed to be useful for downstream learning and systematic generalization (Bengio et al., 2013; Lake et al., 2017; Greff et al., 2020). While many recent empirical studies have investigated the usefulness of disentangled representations and the inductive biases involved in learning them (Locatello et al., 2019; Van Steenkiste et al., 2019; Träuble et al., 2021; Montero et al., 2021; Dittadi et al., 2021c, 2022), analogous experimental studies in the context of object-centric representations are scarce.

The study by Engelcke et al. (2020a) on the inductive biases in object-centric learning for real-world images is one of the most closely related to our work. There, the authors present an investigation into inductive biases for object separation. However, the focus is only on one specific model and on traditional synthetic datasets, while in our work we study hyper-segmentation on datasets where objects have complex textures.

Karazija et al. (2021) recently proposed ClevrTex, a dataset that introduces challenging textures to scenes from CLEVR (Johnson et al., 2017). In the paper, the performance of pixel-based, glimpse-based and sprite-based models is tested on CLEVR, ClevrTex, and other variants. The experiments show that, without any tuning, the models fail to segment complex scenes. The authors, similarly to what we highlighted in this work, state that "ignoring confounding aspects of the scene rather than representing them might aid in the overall task [of scene segmentation]." Additionally, they observe that pixel-based models (which include MONet and Slot Attention), tend to focus on color to segment the input. In our work, we investigate the mechanism behind the ability of some models to ignore complex textures and more successfully segment the image, proposing a useful inductive bias to achieve better object representations.

A few recent works that propose new object-centric learning methods also include evaluations on more complex datasets. For example, Greff et al. (2019) train IODINE on Textured MNIST and ImageNet, and observe that the model separates the image primarily according to color when the input is complex, which is in agreement with our findings. GENESIS-V2 (Engelcke et al., 2021) was trained on Sketchy and APC, two real-world robot manipulation datasets. However, the authors do not explore the mechanism behind the performance of the models they tested, and do not attempt to optimize the architectures. In the video domain, Kipf et al. (2021) include evaluations on a dataset with complex textures, but train their model to predict optical flow rather than reconstruct the input.

Figure 6: The ARI (↑) and MSE (↓) results for different latent space sizes show that the *representation bottleneck* (see main text) is not a sufficient inductive bias for object separation, as there is no significant change in the ARI metric. Slot Attention is prone to training instability when the latent size exceeds 256. We use two seeds for each latent dimension, and show mean (line) and 95% confidence interval (shaded area).

Relevant work naturally includes object-centric learning methods. Here, we provide a brief overview focusing on slot-based models—a subset of object-centric models that includes those studied in this paper. We will be using the categorization proposed by Greff et al. (2020) to distinguish different ways to tackle object separation.

Models based on **instance slots** (Greff et al., 2016, 2017; Van Steenkiste et al., 2018; Greff et al., 2019; Locatello et al., 2020; Löwe et al., 2020; Huang et al., 2020; Le Roux et al., 2011; Goyal et al., 2019; van Steenkiste et al., 2020; Chen et al., 2019; Yang et al., 2020; Kipf et al., 2019; Racah and Chandar, 2020; Kipf et al., 2021) represent objects with individual slots that share a common format of representation, making no assumption regarding interaction between objects. In short, this introduces a routing problem, as the slots are all equally capable of representing a given object present in the input. To solve this ambiguity, an explicit separation step needs to be introduced, often utilizing some form of interaction between slots.

Models that use **sequential slots** (Eslami et al., 2016; Stelzner et al., 2019; Kosiorek et al., 2018; Kossen et al., 2019; Burgess et al., 2019; Engelcke et al., 2020b, 2021; von Kügelgen et al., 2020) implement the same shared format between slots as instance slots based models, but here the routing problem is solved by reconstructing each object sequentially, conditioning on previous ones. The lack of independence between slots can lead to a decrease in the compositionality of the representations.

Finally, models based on **spatial slots** (Nash et al., 2017; Crawford and Pineau, 2019; Jiang et al., 2020; Crawford and Pineau, 2020; Lin et al., 2020b; Deng et al., 2021; Lin et al., 2020a; Dittadi and Winther, 2019) associate each slot with a spatial coordinate, providing more explicit positional bias in the representation and reconstruction process.

5 CONCLUSIONS

In this paper, we have investigated which inductive biases may be most useful for slot-based unsupervised models to

obtain good object-centric representations of scenes where objects have complex textures. We found that using a single module to reconstruct both the shape and the visual appearance of objects is a suitable approach that naturally balances the importance of these two aspects in the generation process, thereby avoiding hyper-segmentation and achieving a better compromise between precise texture reconstructions and correct object segmentations. Therefore, our recommendation is that models should have separation as an integral part of the representation process. Additionally, we showed that separation strongly correlates with the quality of the representations, while reconstruction accuracy does not: this justifies sacrificing some reconstruction quality. Finally, we observed that the representation bottleneck is not a sufficient inductive bias, as increasing the latent space size can be counterproductive unless the model is already separating the input correctly.

We limited our study to two models based on instance slots and sequential slots. Although they have been shown to be among the most successful ones on this type of data, it would be interesting and natural to extend our study and explore if the same holds for other models that approach the problem in a similar way, such as GENESIS, IODINE, and GENESIS-V2, as well as methods based on spatial slots, such as SPAIR or SPACE. Another interesting avenue for future work is to extend our study to more complex downstream tasks involving abstract reasoning, e.g., in a neuro-symbolic system, where symbol manipulation can be performed either within a connectionist framework (Evans and Grefenstette, 2018; Smolensky, 1990; Battaglia et al., 2018) as argued by Greff et al. (2020), or by purely symbolic methods (Asai and Fukunaga, 2018; Mao et al., 2019; Dittadi et al., 2021a). Finally, it would be relevant to validate our conclusions on additional datasets, and to introduce objects with varying texture complexity, as this could require different model capacities to achieve separation (Engelcke et al., 2020a).

References

Masataro Asai and Alex Fukunaga. Classical planning in deep latent space: Bridging the subsymbolic-symbolic boundary. In *Proceedings of the aaai conference on artificial intelligence*, volume 32, 2018.

Thomas Bachlechner, Bodhisattwa Prasad Majumder, Henry Mao, Gary Cottrell, and Julian McAuley. ReZero is all you need: Fast convergence at large depth. In *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, pages 1352–1361. PMLR, December 2021.

Peter Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, and koray kavukcuoglu. Interaction networks for learning about objects, relations and physics. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, Caglar Gulcehre, Francis Song, Andrew Ballard, Justin Gilmer, George Dahl, Ashish Vaswani, Kelsey Allen, Charles Nash, Victoria Langston, Chris Dyer, Nicolas Heess, Daan Wierstra, Pushmeet Kohli, Matt Botvinick, Oriol Vinyals, Yujia Li, and Razvan Pascanu. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(8):1798–1828, 2013.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, Rafal Józefowicz, Scott Gray, Catherine Olsson, Jakub Pachocki, Michael Petrov, Henrique P. d O. Pinto, Jonathan Raiman, Tim Salimans, Jeremy Schlatter, Jonas Schneider, Szymon Sidor, Ilya Sutskever, Jie Tang, Filip Wolski, and Susan Zhang. Dota 2 with Large Scale Deep Reinforcement Learning. *arXiv:1912.06680*, 2019.

Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. Monet: Unsupervised scene decomposition and representation. *arXiv preprint arXiv:1901.11390*, 2019.

Mickaël Chen, Thierry Artières, and Ludovic Denoyer. Unsupervised object segmentation by redrawing. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Eric Crawford and Joelle Pineau. Spatially invariant unsupervised object detection with convolutional neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3412–3420, 2019.

Eric Crawford and Joelle Pineau. Exploiting spatial invariance for scalable unsupervised object tracking. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 3684–3692, 2020.

Stanislas Dehaene. *How We Learn: Why Brains Learn Better than Any Machine ... for Now*. Viking, New York, 2020.

Fei Deng, Zhuo Zhi, Donghun Lee, and Sungjin Ahn. Generative scene graph networks. In *International Conference on Learning Representations*, 2021.

Andrea Dittadi and Ole Winther. LAVAE: Disentangling location and appearance. In *NeurIPS Workshop on Perception as Generative Reasoning*, 2019.

Andrea Dittadi, Frederik K Drachmann, and Thomas Bolander. Planning from pixels in atari with learned symbolic representations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 4941–4949, 2021a.

Andrea Dittadi, Samuele Papa, Michele De Vita, Bernhard Schölkopf, Ole Winther, and Francesco Locatello. Generalization and robustness implications in object-centric learning. *arXiv preprint arXiv:2107.00637*, 2021b.

Andrea Dittadi, Frederik Träuble, Francesco Locatello, Manuel Wüthrich, Vaibhav Agrawal, Ole Winther, Stefan Bauer, and Bernhard Schölkopf. On the transfer of disentangled representations in realistic settings. In *International Conference on Learning Representations*, 2021c.

Andrea Dittadi, Frederik Träuble, Manuel Wuthrich, Felix Widmaier, Peter Vincent Gehler, Ole Winther, Francesco Locatello, Olivier Bachem, Bernhard Schölkopf, and Stefan Bauer. The role of pretrained representations for the OOD generalization of RL agents. In *International Conference on Learning Representations*, 2022.

Martin Engelcke, Oiwi Parker Jones, and Ingmar Posner. Reconstruction bottlenecks in object-centric generative models. *arXiv preprint arXiv:2007.06245*, 2020a.

Martin Engelcke, Adam R. Kosiorek, Oiwi Parker Jones, and Ingmar Posner. GENESIS: Generative Scene Inference and Sampling with Object-Centric Latent Representations. In *ICLR 2020*, 2020b.

Martin Engelcke, Oiwi Parker Jones, and Ingmar Posner. GENESIS-V2: Inferring unordered object representations without iterative refinement. *arXiv preprint arXiv:2104.09958*, 2021.

SM Ali Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, David Szepesvari, Geoffrey E Hinton, et al. Attend, infer, repeat: Fast scene understanding with generative models. In *Advances in Neural Information Processing Systems*, pages 3225–3233, 2016.

Richard Evans and Edward Grefenstette. Learning explanatory rules from noisy data. *Journal of Artificial Intelligence Research*, 61:1–64, 2018.

Leon Gatys, Alexander Ecker, and Matthias Bethge. A Neural Algorithm of Artistic Style. *Journal of Vision*, 16 (12):326–326, September 2016. ISSN 1534-7362. doi: 10.1167/16.12.326.

Anirudh Goyal, Alex Lamb, Jordan Hoffmann, Shagun Sodhani, Sergey Levine, Yoshua Bengio, and Bernhard Schölkopf. Recurrent independent mechanisms. *arXiv preprint arXiv:1909.10893*, 2019.

Klaus Greff, Antti Rasmus, Mathias Berglund, Tele Hao, Harri Valpola, and Jürgen Schmidhuber. Tagger: Deep Unsupervised Perceptual Grouping. *Advances in Neural Information Processing Systems*, 29, 2016.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Neural expectation maximization. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 6694–6704, 2017.

Klaus Greff, Raphaël Lopez Kaufman, Rishabh Kabra, Nick Watters, Christopher Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-object representation learning with iterative variational inference. In *International Conference on Machine Learning*, pages 2424–2433. PMLR, 2019.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. On the binding problem in artificial neural networks. *arXiv preprint arXiv:2012.05208*, 2020.

Qian Huang, Horace He, Abhay Singh, Yan Zhang, Ser Nam Lim, and Austin R Benson. Better set representations for relational reasoning. *Advances in Neural Information Processing Systems*, 33, 2020.

Lawrence Hubert and Phipps Arabi. Comparing partitions. *Journal of Classification*, 2(1):193–218, December 1985. ISSN 1432-1343. doi: 10.1007/BF01908075.

Alexis Jacq. Neural Transfer Using PyTorch — PyTorch Tutorials 1.10.1+cu102 documentation. https://pytorch.org/tutorials/advanced/neural_style_tutorial.html, 2021.

Jindong Jiang, Sepehr Janghorbani, Gerard De Melo, and Sungjin Ahn. SCALOR: Generative world models with scalable object representations. In *International Conference on Learning Representations*, 2020.

Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2901–2910, 2017.

Rishabh Kabra, Chris Burgess, Loic Matthey, Raphael Lopez Kaufman, Klaus Greff, Malcolm Reynolds, and Alexander Lerchner. Multi-object datasets, 2019.

Laurynas Karazija, Iro Laina, and Christian Rupprecht. Clevrtex: A texture-rich benchmark for unsupervised multi-object segmentation. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.

Diederik P Kingma and Max Welling. Auto-encoding variational Bayes. In *International Conference on Learning Representations*, 2014.

Thomas Kipf, Elise van der Pol, and Max Welling. Contrastive learning of structured world models. *arXiv preprint arXiv:1911.12247*, 2019.

Thomas Kipf, Gamaleldin F Elsayed, Aravindh Mahendran, Austin Stone, Sara Sabour, Georg Heigold, Rico Jonschkowski, Alexey Dosovitskiy, and Klaus Greff. Conditional object-centric learning from video. *arXiv preprint arXiv:2111.12594*, 2021.

Adam R Kosiorek, Hyunjik Kim, Ingmar Posner, and Yee Whye Teh. Sequential attend, infer, repeat: Generative modelling of moving objects. *arXiv preprint arXiv:1806.01794*, 2018.

Jannik Kossen, Karl Stelzner, Marcel Hussing, Claas Voelcker, and Kristian Kersting. Structured object-aware physics prediction for video modeling and planning. *arXiv preprint arXiv:1910.02425*, 2019.

Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behavioral and Brain Sciences*, 40, 2017.

Nicolas Le Roux, Nicolas Heess, Jamie Shotton, and John Winn. Learning a generative model of images by factoring appearance and shape. *Neural Computation*, 23(3):593–650, 2011.

Zhixuan Lin, Yi-Fu Wu, Skand Peri, Bofeng Fu, Jindong Jiang, and Sungjin Ahn. Improving generative imagination in object-centric world models. In *International Conference on Machine Learning*, pages 6140–6149. PMLR, 2020a.

Zhixuan Lin, Yi-Fu Wu, Skand Vishwanath Peri, Weihao Sun, Gautam Singh, Fei Deng, Jindong Jiang, and Sungjin Ahn. SPACE: Unsupervised Object-Oriented Scene Representation via Spatial Attention and Decomposition. In *ICLR 2020*, 2020b.

Francesco Locatello, Stefan Bauer, Mario Lucic, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *International Conference on Machine Learning*, 2019.

Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. *arXiv preprint arXiv:2006.15055*, 2020.

Sindy Löwe, Klaus Greff, Rico Jonschkowski, Alexey Dosovitskiy, and Thomas Kipf. Learning object-centric video models by contrasting sets. *arXiv preprint arXiv:2011.10287*, 2020.

Davide Mambelli, Frederik Träuble, Stefan Bauer, Bernhard Schölkopf, and Francesco Locatello. Compositional multi-object reinforcement learning with linear relation networks. *arXiv preprint arXiv:2201.13388*, 2022.

Jiayuan Mao, Chuang Gan, Pushmeet Kohli, Joshua B. Tenenbaum, and Jiajun Wu. The neuro-symbolic concept learner: Interpreting scenes, words, and sentences from natural supervision. In *International Conference on Learning Representations*, 2019.

Milton Llera Montero, Casimir JH Ludwig, Rui Ponte Costa, Gaurav Malhotra, and Jeffrey Bowers. The role of disentanglement in generalisation. In *International Conference on Learning Representations*, 2021.

Charlie Nash, SM Ali Eslami, Chris Burgess, Irina Higgins, Daniel Zoran, Theophane Weber, and Peter Battaglia. The multi-entity variational autoencoder. In *Neural Information Processing Systems (NeurIPS) Workshop on Learning Disentangled Representations: From Perception to Control*, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019.

Evan Racah and Sarath Chandar. Slot contrastive networks: A contrastive approach for representing objects. *arXiv preprint arXiv:2007.09294*, 2020.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter Battaglia. Learning to Simulate Complex Physics with Graph Networks. In *International Conference on Machine Learning*, pages 8459–8468. PMLR, November 2020.

Paul Smolensky. Tensor product variable binding and the representation of symbolic structures in connectionist systems. *Artificial intelligence*, 46(1-2):159–216, 1990.

Elizabeth S. Spelke. Principles of object perception. *Cognitive Science*, 14:29–56, 1990. ISSN 0364-0213. doi: 10.1016/0364-0213(90)90025-R.

Karl Stelzner, Robert Peharz, and Kristian Kersting. Faster Attend-Infer-Repeat with Tractable Probabilistic Models. In Kamalika Chaudhuri and Ruslan Salakhudinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pages 5966–5975. PMLR, June 2019.

Ernő Téglás, Edward Vul, Vittorio Girotto, Michel Gonzalez, Joshua B. Tenenbaum, and Luca L. Bonatti. Pure Reasoning in 12-Month-Old Infants as Probabilistic Inference. *Science*, 332:1054–1059, May 2011. ISSN 0036-8075, 1095-9203. doi: 10.1126/science.1196404.

Frederik Träuble, Elliot Creager, Niki Kilbertus, Francesco Locatello, Andrea Dittadi, Anirudh Goyal, Bernhard Schölkopf, and Stefan Bauer. On disentangled representations learned from correlated data. In *International Conference on Machine Learning*, pages 10401–10412. PMLR, 2021.

Sjoerd Van Steenkiste, Michael Chang, Klaus Greff, and Jürgen Schmidhuber. Relational neural expectation maximization: Unsupervised discovery of objects and their interactions. *arXiv preprint arXiv:1802.10353*, 2018.

Sjoerd Van Steenkiste, Francesco Locatello, Jürgen Schmidhuber, and Olivier Bachem. Are disentangled representations helpful for abstract visual reasoning? *arXiv preprint arXiv:1905.12506*, 2019.

Sjoerd van Steenkiste, Karol Kurach, Jürgen Schmidhuber, and Sylvain Gelly. Investigating object compositionality in generative adversarial networks. *Neural Networks*, 130: 309–325, 2020.

Oriol Vinyals, Igor Babuschkin, Wojciech M. Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H. Choi, Richard Powell, Timo Ewalds, Petko Georgiev, Junhyuk Oh, Dan Horgan, Manuel Kroiss, Ivo Danihelka, Aja Huang, Laurent Sifre, Trevor Cai, John P. Agapiou, Max Jaderberg, Alexander S. Vezhnevets, Rémi Leblond, Tobias Pohlen, Valentin Dalibard, David Budden, Yury Sulsky, James Molloy, Tom L. Paine, Caglar Gulcehre, Ziyu Wang, Tobias Pfaff, Yuhuai Wu, Roman Ring, Dani Yogatama, Dario Wünsch, Katrina McKinney, Oliver Smith, Tom Schaul, Timothy Lillicrap, Koray Kavukcuoglu, Demis Hassabis, Chris Apps, and David Silver. Grandmaster level in StarCraft II using multi-agent reinforcement learning. *Nature*, 575: 350–354, November 2019. ISSN 1476-4687. doi: 10.1038/s41586-019-1724-z.

Julius von Kügelgen, Ivan Ustyuzhaninov, Peter Gehler, Matthias Bethge, and Bernhard Schölkopf. Towards causal generative scene models via competition of experts. In *ICLR 2020 Workshops*, 2020.

Johan Wagemans. *The Oxford handbook of perceptual organization*. Oxford Library of Psychology, 2015.

Yanchao Yang, Yutong Chen, and Stefano Soatto. Learning to manipulate individual objects in an image. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6558–6567, 2020.

A REMARKS ON NOTATION

The term *representation bottleneck* should not be confused with the *reconstruction bottleneck* introduced by Engelcke et al. (2020a). The representation bottleneck refers to the small size of the latent space, while the reconstruction bottleneck refers to how easy it is for the model to reconstruct the data. In Engelcke et al. (2020a), the reconstruction bottleneck is posited to be the reason behind the models' inability to separate objects into different slots.

Often, in the paper, we refer to *object-centric representations* and *slots* as synonyms, although this is only true for slot-based models.

The term *hyper-segmentation* refers to when a model splits the input into different slots with little to no regard to high-level characteristics of the input, such as the shapes of objects, and instead just uses low-level characteristics, primarily color. This often results in slots that consist of small clusters of pixels with similar color, which means that several objects can be partially represented in the same slot and at the same time each object may be partially represented in multiple slots. This phenomenon is distinct from *over-segmentation* (Engelcke et al., 2020b), where multiple slots may reconstruct a single object but no slot reconstructs (parts of) multiple objects. Examples are shown in the main text of the paper (see Fig. 2b and Fig. 2b), where MONet is hyper-segmenting the input, while Slot Attention is sometimes over-segmenting it.

B DATASETS

The original versions of both datasets are taken from Kabra et al. (2019).

CLEVR. The CLEVR dataset consists of 3D objects placed on a gray background at different distances from the camera. Overlap between objects is kept to a minimum. There are spheres, cylinders, and cubes of eight different colors. The objects can be metallic of opaque. There is a big and small variant of each object and they can be placed in several different orientations. We use the variant of the dataset that has no more than 6 objects in it, as was done in previous object-centric learning research. The total number of samples in the training dataset is 49483, and we leave 2000 samples for validation and 2000 samples for testing.

Multi-dSprites. The Multi-dSprites dataset places several 2D objects on a grayscale background. The objects can be a square, an ellipse, or a heart. They can have any RGB color, orientation, and different levels of overlap. Here, we use 90000 samples for the training, 5000 for validation, and 5000 for testing.

| (a) Samples from original Multi-dSprites. | (b) Samples from style transfer Multi-dSprites. |

| (c) Samples from original CLEVR. | (d) Samples from style transfer CLEVR. |

Figure 7: Samples from the original and neural style transfer datasets.

Neural Style Transfer. Neural Style Transfer was applied in its most basic form (Jacq, 2021) except for a few additions to make running it on several datasets easier. We opted to use *The Starry Night* by Dutch painter *Vincent Van Gogh* as a reference style image (we used the photo from Wikimedia Commons, which is in the public domain). We experimented with several parameters, and we noticed a lot of variability between runs and a more pleasant result from the most basic implementation of the algorithm.

The final version of the datasets was obtained by first applying neural style transfer to each image (optimization happens on an image-to-image basis). This results in the entire scene having the style of the reference image. After obtaining the neural style transfer version of the image, we applied the original segmentation masks of the objects to obtain an image where only the foreground objects have a complex texture, while the background remains the original one.

C EVALUATION

C.1 DOWNSTREAM FEATURE PREDICTION TASK

The setup for the feature prediction task is the same as the one used in Dittadi et al. (2021b). The models used are a simple linear model and an MLP with one hidden layer having 256 neurons and enough outputs to predict all of the features of an object. The input to the model is the object representation of a single object and the output is the predicted features for that object. Let r be the representation of an object, M the model, $\hat{y} = M(r)$ is the output of the model, and y is the target vector such that $y_{i_k:i_{k+1}}$ is the kth feature of the object, a vector of dimension $(i_{k+1} - i_k + 1)$. We use the MSE loss for numerical features and the cross-entropy loss for categorical ones.

Now, it is important to note that, in order to correctly train the model, the representation r needs to be matched with the target vector y of the object that r is representing. However, this is very challenging, as the models can represent any object in any of the slots. Therefore, following Dittadi et al. (2021b), we adopted two different strategies to match slots with objects. The first is called *loss matching*: The loss for each pair of slot and object is computed, resulting in a loss matrix L, where $L_{i,j}$ is the loss between the predicted features from the jth slot and the target features from the ith object in the scene. Then, the Hungarian matching algorithm is used to find the pairs of slots-objects that minimize the sum of the loss. The second approach is called *mask matching*: The masks predicted by the models and the ground masks are matched, to find the pairs that have the smallest difference. By using loss matching, the assumption is that the initial errors that are inevitable (because the downstream model has not been trained yet) will eventually disappear. When using mask matching, this problem disappears, however, we rely on the ability of the models to generate masks that closely match the ground truth, which is not the case for models that are hyper-segmenting the input, as is often the case in our study.

C.2 ARI AND MSE

We use the standard definitions of Adjusted Rand Index and Mean Square Error.

The ARI is computed on the foreground objects and is meant to measure the similarity between two partitions of the same set. The *adjusted* part of the name comes from the fact that the Rand Index has been normalized according to a null hypothesis to give 0 when the partitions are random and 1 when they coincide.

The MSE is computed between each channel in each pixel of the image.

D IMPLEMENTATION OF THE MODELS

The models were re-implemented in PyTorch (Paszke et al., 2019) and run on NVIDIA A100 or NVIDIA TitanRTX GPUs. The total approximate training time to reproduce this study is 300 GPU days.

E HYPERPARAMETER SEARCHES

E.1 BASELINES

The baselines were obtained by training the models on the two datasets with 3 different seeds. The parameters are taken from the original papers, but for MONet we use different values for the foreground and background sigma, as suggested by Greff et al. (2019). We stopped the training for all runs in our study, even the ones described later, to 500k steps.

Parameter	Value(s)
foreground sigma	0.05, 0.5
background sigma	0.03, 0.3
gamma	0.05, 1, 5
latent size	64
latent space MLP size	128
decoder input channels	66
number of skip-connections in U-Net	0, 3, 5
dataset	CLEVR, Multi-dSprites

Table 1: Hyperparameter search for MONet.

E.2 IMPROVING MONET

Starting from the baseline results, we first explored the hyperparameter space manually, to develop an intuition regarding the effect of each hyperparameter on the performance.

We then performed a hyperparameter search for MONet. We ran a full search, resulting in 36 runs. Because of the high number of runs, we decided to use a single seed. The parameters are listed in Table 1. Those that are not listed were kept unchanged. All combinations of parameters are tested, but `foreground sigma` and `background sigma` have been changed in pairs, so that when the foreground sigma is 0.05, the background sigma is 0.03 and when foreground sigma is 0.5, background sigma is 0.3 to keep consistent weights of the reconstruction loss.

Some analysis on the results of these models can be seen in Fig. 8, where we can see how the parameters have little to no impact on the overall performance of the model. What

proved to be most effective was reducing the number of skip connections in the U-Net and using a small sigma for the loss function. However, these results are not very conclusive, as a small number of skip connections is actually just increasing the ARI slightly by reconstructing bigger patches of objects in the slots and not actually separating them correctly.

E.3 REPRESENTATION BOTTLENECK STUDY

The representation bottleneck study was done by changing the latent space of both MONet and Slot Attention with 2 seeds and without changing any other parameter, resulting in 32 runs. The latent sizes tested are shown in Table 2. The findings are summarized in the main text of the paper.

MONet	Slot Attention
8	32
16	64
32	128
64	256
128	512

Table 2: Latent space sizes tested in the study for each of the two models.

E.4 IMPROVING SLOT ATTENTION

We tried to increase the size of the encoder and decoder architecture as much as possible, while being reasonable regarding training time and GPU memory. We tested several architectures, with the objective of improving the overall reconstruction quality by reducing the blurriness. We quickly realised that we needed a very deep architecture, therefore, we opted to use residual layers. The final architecture managed to achieve the best results when averaged over 3 different seeds. Each layer is a stack of two convolutional layers, with Leaky ReLU activation functions, a skip connection and we also employ the re-zero strategy (Bachlechner et al., 2021). We increased the latent size to 512, used upscaling in the encoder and downscaling in the decoder. We fixed the broadcast size of the decoder to 32. We used a stack of 16 residual blocks. The architecture of the encoder is described in Table 3, and the decoder is symmetrical (starting from 256 channels going down and instead of downscaling we have upscaling). To map from the input number of channels to the desired ones we use an additional convolutional layer, the same for the output channels. We did not experiment with the number of iterations that the Slot Attention Module performs, but it would be interesting to understand whether this parameter is very influential in natural scenes.

Name	Number of channels	Activation / Comment
Residual Block	64	Leaky ReLU
Residual Block	64	Leaky ReLU
Residual Block	64	Leaky ReLU
Residual Block	64	Leaky ReLU
Downscaling		Only for CLEVR
Residual Block	64	Leaky ReLU
Residual Block	64	Leaky ReLU
Residual Block	64	Leaky ReLU
Residual Block	64	Leaky ReLU
Downscaling		
Residual Block	128	Leaky ReLU
Residual Block	128	Leaky ReLU
Residual Block	128	Leaky ReLU
Residual Block	128	Leaky ReLU
Residual Block	256	Leaky ReLU
Residual Block	256	Leaky ReLU
Residual Block	256	Leaky ReLU
Residual Block	256	Leaky ReLU

Table 3: Final encoder used for the Slot Attention model that obtained the best results in terms of both ARI and MSE. Residual Blocks always have 2 convolutions and use ReZero (Bachlechner et al., 2021), two downscaling operations are used for the CLEVR dataset, while one for Multi-dSprites. The decoder is perfectly simmetrical to this structure.

Figure 8: Results (top row: ARI; bottom row: MSE) from the hyperparameter search for MONet. Although increasing gamma or foreground sigma in the loss function successfully deteriorates reconstruction performance (MSE), they are not sufficient to improve the ARI (in fact, the increase of foreground sigma actually decreases the ARI). A smaller number of skip connections also achieves the desired higher MSE, which corresponds to higher ARI only for small values of sigma. Often, having big values for gamma and sigma results in trends opposing the desired ones in terms of ARI.

F ADDITIONAL RESULTS

Figure 9: Comparison of the downstream performance for all combinations of slot-object matching and model type (results on from the test set, downstream models trained on the validation set). We notice how accuracy (↑) and R^2 (↑) both increase significantly for both MONet models when using loss matching compared to mask matching (especially for numerical features). This is expected, as the masks generated by MONet suffer substantially from hypersegmentation, which makes mask-matching a very unstable way to pair slots with the correct object. Instead, Slot Attention manages to generate more accurate masks, which results in more consistent performance between mask and loss matching methods.

Figure 10: Pearson's correlation coefficient for all runs, grouped by dataset and showing the different combinations of matching and downstream model. The correlation between downstream model's performance and the ARI (↑) and MSE (↓) metrics shows that ARI is a strongest indicator of good representation quality when the object-centric models are being trained on data with complex texture. Difference in correlation between different matching methods and downstream models is again to be attributed to the poor mask generation quality, which makes mask matching very challenging.

Figure 11: Scatter plots to inspect correlation between downstream performance, and ARI (↑) and MSE (↓). The color shows the different models, which clearly display distinct patterns. A visual inspection shows that there is very little correlation between downstream performance and MSE. Only loss matching is shown here.

G QUALITATIVE RESULTS

(a) Baseline MONet

(b) Best result MONet

(c) Baseline Slot Attention

(d) Best result Slot Attention

Figure 12: Qualitative results for the separation performance of the models in the comparative study on *Multi-dSprites*. From left to right in all subfigures: (top) input, final reconstruction, reconstruction for each of the six slots (no predicted mask is applied here, only the visual appearance part of the reconstruction is shown), (bottom) mask for each of the six slots. Here the difference between the two versions of Slot Attention is even more noticeable, and we can see how MONet is blurring the masks. However, MONet never manages to reconstruct the correct visual appearance, even when a more accurate shape of the objects is being predicted by the attention module. Balancing visual appearance and shape is much more challenging in MONet.

(a) Baseline MONet

(b) Best result MONet

(c) Baseline Slot Attention

(d) Best result Slot Attention

Figure 13: Qualitative results for the separation performance of the models in the comparative study on *CLEVR*. From left to right in all subfigures: (top) input, final reconstruction, reconstruction for each of the six slots (no predicted mask is applied here, only the visual appearance part of the reconstruction is shown), (bottom) mask for each of the six slots. The masks on the improved Slot Attention start to include more of the background for each object. In both baseline and best result, Slot Attention isolates each object in a distinct slot, rarely over-segmenting the input, a stark difference when comparing to Multi-dSprites. For MONet, it manages to perform better in CLEVR than Multi-dSprites, however, the best result is still hypersegmenting the input and not blurring it. Overall, MONet cannot reconstruct the visual appearance using the VAE, and leaves all the heavy lifting to the attention module.