Domain Generalization with MixStyle

Abstract

Though convolutional neural networks (CNNs) have demonstrated remarkable ability in learning discriminative features, they often generalize poorly to unseen domains. Domain generalization aims to address this problem by learning from a set of source domains a model that is generalizable to any unseen domain. In this paper, a novel approach is proposed based on probabilistically mixing instance-level feature statistics of training samples across source domains. Our method, termed MixStyle, is motivated by the observation that visual domain is closely related to image style (e.g., photo vs. sketch images). Such style information is captured by the bottom layers of a CNN where our proposed style-mixing takes place. Mixing styles of training instances results in novel domains being synthesized implicitly, which increase the domain diversity of the source domains, and hence the generalizability of the trained model. MixStyle fits into mini-batch training perfectly and is extremely easy to implement. The effectiveness of MixStyle is demonstrated on a wide range of tasks including category classification, instance retrieval and reinforcement learning.

1 Introduction

Key to automated understanding of digital images is to compute a compact and informative feature representation. Deep convolutional neural networks (CNNs) have demonstrated remarkable ability in representation learning, proven to be effective in many visual recognition tasks, such as classifying photo images into 1,000 categories from ImageNet (Krizhevsky et al., 2012) and playing Atari games with reinforcement learning (Mnih et al., 2013). However, it has long been discovered that the success of CNNs heavily relies on the i.i.d. assumption, i.e. training and test data should be drawn from the same distribution; when such an assumption is violated even just slightly, as in most real-world application scenarios, severe performance degradation is expected (Hendrycks & Dietterich, 2019; Recht et al., 2019).

Domain generalization (DG) aims to address such a problem. In particular, assuming that multiple source domains containing the same visual classes are available for model training, the goal of DG is to learn models that are robust against data distribution changes across domains, known as domain shift, so that the trained model can generalize well to any unseen domains. Comparing to the closely related and more widely studied domain adaptation (DA) problem, DG is much harder in that no target domain data is available for the model to analyze the distribution shift in order to overcome the negative effects. Instead, a DG model must rely on the source domains and focus on learning domain-invariant feature representation in the hope that it would remain discriminative given target domain data.

A straightforward solution to DG is to expose a model with a large variety of source domains. Specifically, the task of learning domain-invariant and thus generalizable feature representation becomes easier when data from more diverse source domains are available for the model. This would reduce the burden on designing special models or learning algorithms for DG. Indeed, model training with large-scale data of diverse domains is behind the success of existing commercial face recognition or vision-based autonomous driving systems. However, collecting data of a large variety of domains is often costly or even impossible. It thus cannot be a general solution to DG.

In this paper, a novel approach is proposed based on probabilistically mixing instance-level feature statistics of training samples across source domains. Our model, termed *MixStyle*, is motivated by the observation that visual domain is closely related to image style. An example is shown in

Figure 1: 2-D t-SNE (Maaten & Hinton, 2008) visualization of the style statistics (concatenation of mean and standard deviation) computed from the first residual block's feature maps of a ResNet-18 (He et al., 2016) trained on four distinct domains (Li et al., 2017). It is clear that different domains are well separated.

Fig. 1: the four images from four different domains depict the same semantic concept (dog), but with distinctive styles (e.g., characteristics in color and texture). When these images are fed into a deep CNN, which maps the raw pixel values into category labels, such style information is removed at the output. However, recent style transfer studies (Huang & Belongie, 2017; Dumoulin et al., 2017) suggest that such style information is preserved at the bottom layers of the CNN through the instance-level feature statistics, as shown clearly in Fig. 4. Importantly, since replacing such statistics would lead to replaced style while preserving the semantic content of the image, it is reasonable to assume that mixing styles from images of different domains would result in images of (mixed) new styles. That is, more diverse domains/styles can be made available for training a more domain-generalizable model.

Concretely, our MixStyle randomly selects two instances of different domains and adopts a probabilistic convex combination between instance-level feature statistics of bottom CNN layers. In contrast to style transfer work (Huang & Belongie, 2017; Dumoulin et al., 2017), no explicit image synthesis is necessary meaning much simpler model design. Moreover, MixStyle perfectly fits into modern mini-batch training. Overall, it is very easy to implement with only few lines of code. To evaluate the effectiveness as well as the general applicability of MixStyle, we conduct extensive experiments on a wide spectrum of datasets covering category classification (Sec. 3.1), instance retrieval (Sec. 3.2) and reinforcement learning (Sec. 3.3). The results demonstrate that MixStyle can significantly improve CNNs' cross-domain generalization performance.

2 METHODOLOGY

2.1 BACKGROUND

Normalizing feature tensors with instance-specific mean and standard deviation has been found effective for removing image style in style transfer models (Ulyanov et al., 2016; Huang & Belongie, 2017; Dumoulin et al., 2017). Such an operation is widely known as instance normalization (IN, Ulyanov et al. (2016)). Let $x \in \mathbb{R}^{B \times C \times H \times W}$ be a batch of tensors, with B, C, H and W denoting the dimension of batch, channel, height and width, respectively, IN is formulated as

$$\text{IN}(x) = \gamma \frac{x - \mu(x)}{\sigma(x)} + \beta, \tag{1}$$

where $\gamma, \beta \in \mathbb{R}^C$ are learnable affine transformation parameters, and $\mu(x), \sigma(x) \in \mathbb{R}^{B \times C}$ are mean and standard deviation computed across the spatial dimension within each channel of each instance (tensor), i.e.

$$\mu(x)_{b,c} = \frac{1}{HW} \sum_{h=1}^{H} \sum_{w=1}^{W} x_{b,c,h,w}, \tag{2}$$

and

$$\sigma(x)_{b,c} = \sqrt{\frac{1}{HW} \sum_{h=1}^{H} \sum_{w=1}^{W} (x_{b,c,h,w} - \mu(x)_{b,c})^2}. \tag{3}$$

Huang & Belongie (2017) introduced adaptive instance normalization (AdaIN), which simply replaces the scale and shift parameters in Eq. (1) with the feature statistics of style input y to achieve arbitrary style transfer:

$$\text{AdaIN}(x) = \sigma(y) \frac{x - \mu(x)}{\sigma(x)} + \mu(y). \tag{4}$$

2.2 MixStyle

Our method, MixStyle, draws inspiration from AdaIN. However, rather than attaching a decoder for image generation, MixStyle is designed for the purpose of regularizing CNN training by perturbing the style information of source domain training instances. It can be implemented as a plug-and-play module inserted between CNN layers of, e.g., a supervised CNN classifier, without the need to explicitly generate an image of new style.

More specifically, MixStyle mixes the feature statistics of two instances with a random convex weight to simulate new styles. In terms of implementation, MixStyle can be easily integrated into mini-batch training. Given an input batch x, MixStyle first generates a reference batch $\tilde{x}$ from x. When domain labels are given, x is sampled from two different domains i and j, e.g., $x = [x^i, x^j]$ (x^i and x^j have the same batch size). Then, $\tilde{x}$ is obtained by swapping the position of x^i and x^j, followed by a shuffling operation along the batch dimension applied to each batch, i.e. $\tilde{x} = [\text{Shuffle}(x^j), \text{Shuffle}(x^i)]$. See Fig. 2(a) for an illustration. In scenarios where domain labels are unknown, x is randomly sampled from the training data, and $\tilde{x}$ is simply obtained by $\tilde{x} = \text{Shuffle}(x)$ (see Fig. 2(b)). Fig. 4 shows that sub-domains exist within each domain, so even if two instances of the same domain are sampled, new domain could be synthesized. After shuffling, MixStyle computes the mixed feature statistics by

$x = [\ x_1\ x_2\ x_3\ x_4\ x_5\ x_6\ ]$

$\tilde{x} = [\ x_5\ x_6\ x_4\ x_3\ x_1\ x_2\ ]$

(a) Shuffling batch w/ domain label

$x = [\ x_1\ x_2\ x_3\ x_4\ x_5\ x_6\ ]$

$\tilde{x} = [\ x_6\ x_1\ x_5\ x_3\ x_2\ x_4\ ]$

(b) Shuffling batch w/ random shuffle

Figure 2: A graphical illustration of how a reference batch is generated. Domain label is denoted by color.

$$\gamma_{mix} = \lambda \sigma(x) + (1 - \lambda)\sigma(\tilde{x}), \tag{5}$$
$$\beta_{mix} = \lambda \mu(x) + (1 - \lambda)\mu(\tilde{x}), \tag{6}$$

where $\lambda \in \mathbb{R}^B$ are instance-wise weights sampled from the Beta distribution, $\lambda \sim Beta(\alpha, \alpha)$ with $\alpha \in (0, \infty)$ being a hyper-parameter. Unless specified otherwise, we set α to 0.1 throughout this paper. Finally, the mixed feature statistics are applied to the style-normalized x,

$$\text{MixStyle}(x) = \gamma_{mix} \frac{x - \mu(x)}{\sigma(x)} + \beta_{mix}. \tag{7}$$

In practice, we use a probability of 0.5 to decide if MixStyle is activated or not in the forward pass. At test time, no MixStyle is applied. Note that gradients are blocked in the computational graph of $\mu(\cdot)$ and $\sigma(\cdot)$. MixStyle can be implemented with only few lines of code. See Algorithm 1 in Appendix A.1 for the PyTorch-like pseudo-code.

3 Experiments

3.1 Generalization in Category Classification

Dataset and implementation details. We choose the PACS dataset (Li et al., 2017), a commonly used domain generalization (DG) benchmark concerned with domain shift in image classification. PACS consists of four domains, i.e. Art Painting, Cartoon, Photo and Sketch, with totally 9,991 images of 7 classes. As shown in Fig. 1, the domain shift mainly corresponds to image style changes.

Table 1: Leave-one-domain-out generalization results (%) on PACS.

Method	Art	Cartoon	Photo	Sketch	Avg
MMD-AAE	75.2	72.7	96.0	64.2	77.0
CCSA	80.5	76.9	93.6	66.8	79.4
JiGen	79.4	75.3	96.0	71.6	80.5
CrossGrad	79.8	76.8	96.0	70.2	80.7
Epi-FCR	82.1	77.0	93.9	73.0	81.5
Metareg	83.7	77.2	95.5	70.3	81.7
L2A-OT	83.3	78.2	96.2	73.6	82.8
ResNet-18	77.0±0.6	75.9±0.6	96.0±0.1	69.2±0.6	79.5
+ Manifold Mixup	75.6±0.7	70.1±0.9	93.5±0.7	65.4±0.6	76.2
+ Cutout	74.9±0.4	74.9±0.6	95.9±0.3	67.7±0.9	78.3
+ CutMix	74.6±0.7	71.8±0.6	95.6±0.4	65.3±0.8	76.8
+ Mixup	76.8±0.7	74.9±0.7	95.8±0.3	66.6±0.7	78.5
+ DropBlock	76.4±0.7	75.4±0.7	95.9±0.3	69.0±0.3	79.2
+ MixStyle w/ random shuffle	82.3±0.2	**79.0**±0.3	**96.3**±0.3	73.8±0.9	82.8
+ MixStyle w/ domain label	**84.1**±0.4	78.8±0.4	96.1±0.3	**75.9**±0.9	**83.7**

For evaluation, a model is trained on three domains and tested on the remaining one. Following prior work (Li et al., 2019; Zhou et al., 2020a), we use ResNet-18 (He et al., 2016) as the classifier where MixStyle is inserted after the 1st, 2nd and 3rd residual blocks. Our code is based on Dassl.pytorch (Zhou et al., 2020b).[1]

Baselines. Our main baselines are general-purpose regularization methods including Mixup (Zhang et al., 2018b), Manifold Mixup (Verma et al., 2019), DropBlock (Ghiasi et al., 2018), CutMix (Yun et al., 2019) and Cutout (DeVries & Taylor, 2017), which are trained using the same training parameters as MixStyle and the optimal hyper-parameter setup as reported in their papers. We also compare with the existing DG methods which reported state-of-the-art performance on PACS. These include domain alignment-based CCSA (Motiian et al., 2017) and MMD-AAE (Li et al., 2018b), Jigsaw puzzle-based JiGen (Carlucci et al., 2019), adversarial gradient-based CrossGrad (Shankar et al., 2018), meta-learning-based Metareg (Balaji et al., 2018) and Epi-FCR (Li et al., 2019), and data augmentation-based L2A-OT (Zhou et al., 2020a).

Comparison with general-purpose regularization methods. The results are shown in Table 1. Overall, we observe that the general-purpose regularization methods do not offer any clear advantage over the vanilla ResNet-18 in this DG task, while MixStyle improves upon the vanilla ResNet-18 with significant margins. MixStyle (w/ domain label) beats Mixup by 5.2% on average, which demonstrates the advantage of mixing style statistics at the feature level over mixing images at the pixel level. MixStyle and DropBlock share some commonalities in that they are both applied to feature maps at multiple layers, but MixStyle significantly outperforms DropBlock in all test domains. The reason why DropBlock is ineffective here is because dropping out activations mainly encourages a network to mine discriminative patterns, but does not reinforce the ability to cope with unseen styles, which is exactly what MixStyle aims to achieve: by synthesizing "new" styles (domains) MixStyle regularizes the network to become more robust to domain shift.

Comparison with state-of-the-art DG methods. Overall, MixStyle outperforms most DG methods by a clear margin, despite being a much simpler method. The performance of MixStyle w/ domain label is nearly 1% better on average than the recently introduced L2A-OT. From a data augmentation perspective, MixStyle and L2A-OT share a similar goal—to synthesize data from pseudo-novel domains. MixStyle accomplishes this goal through mixing style statistics at the feature level. Whereas L2A-OT works at the pixel level: it trains an image generator by maximizing the domain difference (measured by optimal transport) between the original and the generated images, which introduces much heavier computational overhead than MixStyle in terms of GPU memory and training time. It is worth noting that MixStyle's domain label-free version is highly competitive: its 82.8% accuracy is on par with L2A-OT's.

---

[1]https://github.com/KaiyangZhou/Dassl.pytorch.

Table 2: Generalization results on person re-ID datasets.

Model	Market1501→Duke				Duke→Market1501			
	mAP	R1	R5	R10	mAP	R1	R5	R10
ResNet-50	19.3	35.4	50.3	56.4	20.4	45.2	63.6	70.9
+ RandomErase	14.3	27.8	42.6	49.1	16.1	38.5	56.8	64.5
+ DropBlock	18.2	33.2	49.1	56.3	19.7	45.3	62.1	69.1
+ MixStyle w/ random shuffle	**23.8**	42.2	58.8	**64.8**	24.1	51.5	69.4	76.2
+ MixStyle w/ domain label	23.4	**43.3**	**58.9**	64.7	**24.7**	**53.0**	**70.9**	**77.8**
OSNet	25.9	44.7	59.6	65.4	24.0	52.2	67.5	74.7
+ RandomErase	20.5	36.2	52.3	59.3	22.4	49.1	66.1	73.0
+ DropBlock	23.1	41.5	56.5	62.5	21.7	48.2	65.4	71.3
+ MixStyle w/ random shuffle	27.2	**48.2**	**62.7**	**68.4**	27.8	58.1	74.0	**81.0**
+ MixStyle w/ domain label	**27.3**	47.5	62.0	67.1	**29.0**	**58.2**	**74.9**	80.9

3.2 GENERALIZATION IN INSTANCE RETRIEVAL

Dataset and implementation details. We evaluate MixStyle on the person re-identification (re-ID) problem, which aims to match people across disjoint camera views. As each camera view is itself a distinct domain, person re-ID is essentially a cross-domain image matching problem. Compared with image classification, person re-ID poses more challenges because domain shift not only occurs when camera view changes but also between training and test identities (they do not share the same label space). Two commonly used re-ID datasets are adopted: Market1501 (Zheng et al., 2015) and Duke (Ristani et al., 2016; Zheng et al., 2017). For evaluation, we train a model on one dataset and directly test its performance on the other. Ranking accuracy and mean average precision (mAP) are used as the performance measures (displayed in percentage). We test MixStyle on two CNN architectures: ResNet-50 (He et al., 2016) and OSNet (Zhou et al., 2019). The latter was designed specifically for re-ID. In both architectures, MixStyle is inserted after the 1st and 2nd residual blocks. Our code is based on Torchreid (Zhou & Xiang, 2019).[2]

Baselines. We compare with three baseline methods: 1) The vanilla model, which serves as a strong baseline; 2) DropBlock, which was the top-performing competitor in Table 1; 3) RandomErase (Zhong et al., 2020), a widely used regularization method in the re-ID literature (similar to Cutout).

Results. The results are reported in Table 2. It is clear that only MixStyle consistently outperforms the strong vanilla model under both settings with considerable margins, while DropBlock and RandomErase are unable to show any benefit. Notably, RandomErase, which simulates occlusion by erasing pixels in random rectangular regions with random values, has been used as a default trick when training re-ID CNNs. However, RandomErase shows a detrimental effect in the cross-dataset re-ID setting. Indeed, similar to DropBlock, randomly erasing pixels offers no guarantee to improve the robustness when it comes to domain shift.

3.3 GENERALIZATION IN REINFORCEMENT LEARNING

Though RL has been greatly advanced by using CNNs for feature learning in raw pixels (Mnih et al., 2013), it has been widely acknowledged that RL agents often overfit training environments while generalize poorly to unseen environments (Cobbe et al., 2019; Igl et al., 2019).

Dataset and implementation details. We conduct experiments on Coinrun (Cobbe et al., 2019), a recently introduced RL benchmark for evaluating the generalization performance of RL agents. As shown in Fig. 3(a), the goal in Coinrun is to control a character to collect golden coins while avoiding both stationary and non-stationary obstacles. We follow Igl et al. (2019) to construct and train our RL agent: the CNN architecture used in IMPALA (Espeholt et al., 2018) is adopted as the policy network, and is trained by the Proximal Policy Optimization (PPO) algorithm (Schulman et al., 2017). Please refer to Igl et al. (2019) for further implementation details. MixStyle is inserted after the 1st and 2nd convolutional sequences. Training data are sampled from 500 levels while test

---

[2]https://github.com/KaiyangZhou/deep-person-reid.

Figure 3: (a) Coinrun benchmark. (b) Test performance in unseen environments. (c) Difference between training and test performance.

data are drawn from new levels of only the highest difficulty. As domain labels are difficult to define, we use the random shuffle version of MixStyle. Our code is built on top of Igl et al. (2019).[3]

Baselines. Following Igl et al. (2019), we train strong baseline models and add MixStyle on top of them to see whether MixStyle can bring further improvements. To this end, we train two baseline models: 1) Baseline, which combines weight decay and data augmentation;[4] 2) IBAC-SNI (the $\lambda = 0.5$ version), the best-performing model in Igl et al. (2019) which is based on selective noise injection.

Results. The test performance is shown in Fig. 3(b). Comparing Baseline (blue) with Baseline+MixStyle (orange), we can see that MixStyle brings a significant improvement. Interestingly, the variance is also significantly reduced by using MixStyle, as indicated by the smaller shaded areas (for both orange and red lines). These results strongly demonstrate the effectiveness of MixStyle in enhancing generalization for RL agents. When it comes to the stronger baseline IBAC-SNI (green), MixStyle (red) is able to bring further performance gain, suggesting that MixStyle is complementary to IBAC-SNI. This result also shows the potential of MixStyle as a plug-and-play component to be combined with other advanced RL methods. It is worth noting that Baseline+MixStyle itself is already highly competitive with IBAC-SNI. Fig. 3(c) shows the generalization gap from which it can been seen that the models trained with MixStyle (orange & red) clearly generalize faster and better than those without using MixStyle (blue & green).

3.4 ANALYSIS

Where to apply MixStyle? To answer this question, we take the popular ResNet architecture (He et al., 2016) as an example. A ResNet model starts with a convolutional layer, which is followed by four residual blocks, denoted by conv2/3/4/5_x as in He et al. (2016). We experiment with four variants on PACS. The first variant applies MixStyle after conv2_x. The rest incrementally apply MixStyle after conv3_x, conv4_x and conv5_x. The re-

Table 3: Ablation study on where to apply MixStyle.

Model	Accuracy (%)
ResNet-18	79.5
+ MixStyle (conv2_x)	80.1
+ MixStyle (conv23_x)	81.6
+ MixStyle (conv234_x)	**82.8**
+ MixStyle (conv2345_x)	75.6

sults are shown in Table 3. We observe that the accuracy is steadily improved when we apply MixStyle to more layers, and reaches the optimum at 82.8% where MixStyle is jointly applied to conv2_x, conv3_x and conv4_x. However, the accuracy slumps to 75.6% (even lower than the 79.5% baseline) when MixStyle is applied to conv5_x. This makes sense because conv5_x is the closest to the prediction layer and tends to capture semantic content/label-sensitive information rather than style. Specifically, conv5_x is followed by an average pooling layer, which essentially

---

[3]https://github.com/microsoft/IBAC-SNI.

[4]We do not use batch normalization (Ioffe & Szegedy, 2015) or dropout (Srivastava et al., 2014) because they are detrimental to the performance, as shown by Igl et al. (2019).

Figure 4: 2-D visualization of flattened feature maps (top) and the corresponding style statistics (bottom) extracted from different residual blocks. We observe that `conv2_x` to `conv4_x` contain domain-related information while `conv5_x` encodes label-related information.

forwards the mean vector to the prediction layer and thus forces the mean vector to capture label-related information. As a consequence, mixing the statistics at `conv5_x` breaks the inherent label space. This is clearer in Fig. 4: the features and style statistics in `conv2_x` to `conv4_x` form clustering patterns based on the domains while those in `conv5_x` have a high correlation with class labels. Therefore, the rule of thumb is to apply MixStyle to (multiple) bottom to middle layers in a CNN.

Mixing vs. replacing. Unlike the AdaIN formulation, which completely replaces one style with the other, MixStyle mixes two styles via a convex combination. Table 4 shows that mixing is clearly better than replacing. This is easy to understand: mixing diversifies the styles (imagine an interpolation between two data points).

Table 4: Mixing vs. replacing.

	Accuracy (%)
Mixing	**82.8**±0.4
Replacing	82.1±0.5

Random vs. fixed shuffle at multiple layers. Applying MixStyle to multiple layers, which has been shown advantageous in Table 3, raises another question of whether to shuffle the mini-batch at different layers or use the same shuffled order for all layers. Table 5 suggests that using random shuffle at different layers gives a better performance, which may be attributed to the increased noise level that gives a better regularization effect.

Table 5: Random vs. fixed shuffle at multiple layers.

	Accuracy (%)
Random	**82.8**±0.4
Fixed	82.4±0.5

Sensitivity of hyper-parameter. Recall that α is used to control the shape of Beta distribution, which has a direct effect on how the convex weights λ are sampled. The smaller α is, the more likely the value in λ is close to the extreme value of 0 or 1. In other words, a smaller α favors the style statistics in Eqs. (5) & (6) to be dominated by one side. We first evaluate α on PACS. Fig. 5(a) shows that with α increasing from 0.1 to 0.4, the accuracy slightly slides from 82.8% to 81.7%. However, further increasing α does not impact on the accuracy. Therefore, the results suggest that the performance is not too sensitive to α; and selecting α from $\{0.1, 0.2, 0.3\}$ seems to be a good starting point. We further experiment with $\alpha \in \{0.1, 0.2, 0.3\}$ on the re-ID datasets and the Coinrun benchmark. Figs. 5(b) & (c) show that in general the variance for the results of different values is small. Therefore, we suggest practitioners to choose α from $\{0.1, 0.2, 0.3\}$, with $\alpha = 0.1$ being a good default setting.

For more analyses and discussions, please see Appendix A.2.

4 RELATED WORK

Domain generalization, or DG, has been a topical research area. Many DG methods are based on the idea of aligning features between different sources, with a hope that the model can be invariant

Figure 5: Evaluation on the hyper-parameter α on (a) PACS, (b) person re-ID datasets and (c) Coinrun. In (b), M and D denote Market1501 and Duke respectively.

to domain shift given unseen data. For instance, Li et al. (2018b) achieved distribution alignment in the hidden representation of an autoencoder using maximum mean discrepancy; Li et al. (2018c) resorted to adversarial learning with auxiliary domain classifiers to learn features that are domain-agnostic. Recently, meta-learning has drawn attention from the DG community (Li et al., 2018a; Balaji et al., 2018; Dou et al., 2019). The main idea is to expose a model to domain shift during training by using pseudo-train and pseudo-test domains, both drawn from source domains. Data augmentation has also been investigated for DG. Shankar et al. (2018) introduced a cross-gradient training method where source data are augmented by adversarial gradients obtained from a domain classifier. Very recently, Zhou et al. (2020a) proposed to learn a neural network to map source data to pseudo-novel domains by maximizing an optimal transport-based distance measure. Our MixStyle is related in its efforts to synthesizing novel domains, but differs in the fact that it is done implicitly with a much simpler formulation and only few lines of extra code on top of a standard supervised classifier while being more effective.

Generalization in deep RL has been a challenging problem where RL agents often overfit training environments, and as a result, perform poorly in unseen environments with different visual patterns or levels (Zhang et al., 2018a). A natural way to improve generalization, which has been shown effective in (Cobbe et al., 2019; Farebrother et al., 2018), is to use regularization, e.g., weight decay. However, Igl et al. (2019) suggested that stochastic regularization methods like dropout and batch normalization (which uses estimated population statistics) have adverse effect as the training data in RL are essentially model-dependent. As such, they proposed selective noise injection (SNI), which basically combines a stochastic regularization technique with its deterministic counterpart. They further integrated SNI with information bottleneck actor critic (IBAC-SNI) to reduce the variance in gradients. Curriculum learning has been investigated in (Justesen et al., 2018) where the level of training episodes progresses from easy to difficult over the course of training. Gamrian & Goldberg (2019) leveraged the advances in GAN-based image-to-image translation (Liu et al., 2017) to map target data to the source domain which the agent was trained on. Tobin et al. (2017) introduced domain randomization, which diversifies training data by rendering images with different visual effects via a programmable simulator. With a similar goal of data augmentation, Lee et al. (2020) pre-processed input images with a randomly initialized network. Very recent studies (Laskin et al., 2020; Kostrikov et al., 2020) have shown that it is useful to combine a diverse set of label-preserving transformations, such as rotation, shifting and Cutout. Different from the aforementioned methods, our MixStyle works at the feature level and is orthogonal to most existing methods. For instance, we have shown in Sec. 3.3 that MixStyle significantly improves upon IBAC-SNI.

5 CONCLUSION

We presented a simple yet effective domain generalization method, termed MixStyle. MixStyle mixes the feature statistics of two instances to synthesize novel domains, which is inspired by the observation in style transfer work that the feature statistics encode style/domain-related information. Extensive experiments covering a wide range of tasks were conducted to demonstrate that MixStyle yields new state-of-the-art on three different tasks.

REFERENCES

Yogesh Balaji, Swami Sankaranarayanan, and Rama Chellappa. Metareg: Towards domain generalization using meta-regularization. In *NeurIPS*, 2018.

Fabio M. Carlucci, Antonio D'Innocente, Silvia Bucci, Barbara Caputo, and Tatiana Tommasi. Domain generalization by solving jigsaw puzzles. In *CVPR*, 2019.

Karl Cobbe, Oleg Klimov, Chris Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. In *ICML*, 2019.

Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017.

Qi Dou, Daniel C Castro, Konstantinos Kamnitsas, and Ben Glocker. Domain generalization via model-agnostic learning of semantic features. In *NeurIPS*, 2019.

Vincent Dumoulin, Jonathon Shlens, and Manjunath Kudlur. A learned representation for artistic style. In *ICLR*, 2017.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Volodymir Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *ICML*, 2018.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. *arXiv preprint arXiv:1810.00123*, 2018.

Shani Gamrian and Yoav Goldberg. Transfer learning for related reinforcement learning tasks via image-to-image translation. In *ICML*, 2019.

Golnaz Ghiasi, Tsung-Yi Lin, and Quoc V Le. Dropblock: A regularization method for convolutional networks. In *NeurIPS*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *ICLR*, 2019.

Xun Huang and Serge Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. In *ICCV*, 2017.

Maximilian Igl, Kamil Ciosek, Yingzhen Li, Sebastian Tschiatschek, Cheng Zhang, Sam Devlin, and Katja Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. In *NeurIPS*, 2019.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015.

Niels Justesen, Ruben Rodriguez Torrado, Philip Bontrager, Ahmed Khalifa, Julian Togelius, and Sebastian Risi. Illuminating generalization in deep reinforcement learning through procedural level generation. *arXiv preprint arXiv:1806.10729*, 2018.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*, 2012.

Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *arXiv preprint arXiv:2004.14990*, 2020.

Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. In *ICLR*, 2020.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M. Hospedales. Deeper, broader and artier domain generalization. In *ICCV*, 2017.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M. Hospedales. Learning to generalize: Meta-learning for domain generalization. In *AAAI*, 2018a.

Da Liu, Jianshu Zhang, Yongxin Yang, Cong Liu, Yi-Zhe Song, and Timothy M Hospedales. Episodic training for domain generalization. In *ICCV*, 2019.

Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C. Kot. Domain generalization with adversarial feature learning. In *CVPR*, 2018b.

Ya Li, Xinmei Tiana, Mingming Gong, Yajing Liu, Tongliang Liu, Kun Zhang, and Dacheng Tao. Deep domain generalization via conditional invariant adversarial networks. In *ECCV*, 2018c.

Ming-Yu Liu, Thomas Breuel, and Jan Kautz. Unsupervised image-to-image translation networks. In *NeurIPS*, 2017.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *JMLR*, 2008.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Saeid Motiian, Marco Piccirilli, Donald A. Adjeroh, and Gianfranco Doretto. Unified deep supervised domain adaptation and generalization. In *ICCV*, 2017.

Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do imagenet classifiers generalize to imagenet? In *ICML*, 2019.

Ergys Ristani, Francesco Solera, Roger Zou, Rita Cucchiara, and Carlo Tomasi. Performance measures and a data set for multi-target, multi-camera tracking. In *ECCV*, 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Shiv Shankar, Vihari Piratla, Soumen Chakrabarti, Siddhartha Chaudhuri, Preethi Jyothi, and Sunita Sarawagi. Generalizing across domains via cross-gradient training. In *ICLR*, 2018.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *JMLR*, 2014.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *IROS*, 2017.

Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Instance normalization: The missing ingredient for fast stylization. *arXiv:1607.08022*, 2016.

Vikas Verma, Alex Lamb, Christopher Beckham, Amir Najafi, Ioannis Mitliagkas, David Lopez-Paz, and Yoshua Bengio. Manifold mixup: Better representations by interpolating hidden states. In *ICML*, 2019.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *ICCV*, 2019.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018a.

Hongyi Zhang, Moustapha Cisse, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *ICLR*, 2018b.

Liang Zheng, Liyue Shen, Lu Tian, Shengjin Wang, Jingdong Wang, and Qi Tian. Scalable person re-identification: A benchmark. In *ICCV*, 2015.

Zhedong Zheng, Liang Zheng, and Yi Yang. Unlabeled samples generated by gan improve the person re-identification baseline in vitro. In *ICCV*, 2017.

Zhun Zhong, Liang Zheng, Guoliang Kang, Shaozi Li, and Yi Yang. Random erasing data augmentation. In *AAAI*, 2020.

Kaiyang Zhou and Tao Xiang. Torchreid: A library for deep learning person re-identification in pytorch. *arXiv preprint arXiv:1910.10093*, 2019.

Kaiyang Zhou, Yongxin Yang, Andrea Cavallaro, and Tao Xiang. Omni-scale feature learning for person re-identification. In *ICCV*, 2019.

Kaiyang Zhou, Yongxin Yang, Timothy Hospedales, and Tao Xiang. Learning to generate novel domains for domain generalization. In *ECCV*, 2020a.

Kaiyang Zhou, Yongxin Yang, Yu Qiao, and Tao Xiang. Domain adaptive ensemble learning. *arXiv preprint arXiv:2003.07325*, 2020b.

A APPENDIX

A.1 PSEUDO-CODE OF MIXSTYLE

Algorithm 1 provides a PyTorch-like pseudo-code.

Algorithm 1 PyTorch-like pseudo-code for MixStyle.

```
# x: input features of shape (B, C, H, W)
# p: probabillity to apply MixStyle (default: 0.5)
# alpha: hyper-parameter for the Beta distribution (default: 0.1)
# eps: a small value added before square root for numerical stability (default: 1e-6)

if not in training mode:
    return x

if random probability > p:
    return x

B = x.size(0) # batch size

mu = x.mean(dim=[2, 3], keepdim=True) # compute instance mean
var = x.var(dim=[2, 3], keepdim=True) # compute instance variance
sig = (var + eps).sqrt() # compute instance standard deviation
mu, sig = mu.detach(), sig.detach() # block gradients
x_normed = (x - mu) / sig # normalize input

lmda = Beta(alpha, alpha).sample((B, 1, 1, 1)) # sample instance-wise convex weights

if domain label is given:
    # in this case, input x = [x^i, x^j]
    perm = torch.arange(B-1, -1, -1) # inverse index
    perm_j, perm_i = perm.chunk(2) # separate indices
    perm_j = perm_j[torch.randperm(B // 2)] # shuffling
    perm_i = perm_i[torch.randperm(B // 2)] # shuffling
    perm = torch.cat([perm_j, perm_i], 0) # concatenation
else:
    perm = torch.randperm(B) # generate shuffling indices

mu2, sig2 = mu[perm], sig[perm] # shuffling
mu_mix = mu * lmda + mu2 * (1 - lmda) # generate mixed mean
sig_mix = sig * lmda + sig2 * (1 - lmda) # generate mixed standard deviation

return x_normed * sig_mix + mu_mix # denormalize input using the mixed statistics
```

A.2 FURTHER ANALYSIS

MixStyle between same-domain instances. We are interested in knowing if mixing styles between same-domain instances helps performance. To this end, we sample each mini-batch from a single domain during training when using MixStyle. The results are shown in Table 6 where we observe that mixing styles between same-domain instances is about 1% better than the baseline model. This suggests that instance-specific style exists. Nonetheless, the performance is clearly worse than mixing styles between instances of different domains.

Table 6: Investigation on the effect of mixing styles between same-domain instances.

	Accuracy (%)
ResNet18	79.5
+ MixStyle w/ same-domain	80.4
+ MixStyle w/ random shuffle	82.8
+ MixStyle w/ domain label	**83.7**