Enhancing Interpretability: A Versatile Clue-Based Framework for Faithful In-Depth Interpretations

Abstract

Despite the state-of-the-art performance of deep neural networks, they are susceptible to bias and malfunction in unforeseen situations. Moreover, the complex computations underlying their reasoning are not human-understandable, hindering the development of trust and the validation of decisions. Local interpretation methods seek to provide explanations for individual model decisions with two key goals: faithfulness to the model and human-understandability. However, existing approaches often suffer from performance loss, limited applicability to pre-trained models, and unfaithful explanations. Seeking more faithful interpretations, we introduce a novel definition, called Distinguishing Clue, which sets of input regions that uniquely promote specific network decisions, detected through our Local Attention Perception (LAP) module. Our innovative training scheme allows LAP to learn these clues without relying on expert annotations. It also provides means for both general and expert knowledge injection. The system is usable for training networks from scratch, enhancing their interpretability, and interpreting networks that have already been trained. We demonstrate the superiority of the proposed method by evaluating it on different architectures across two datasets, including ImageNet. The proposed framework offers more valid and faithful-to-the-model interpretations than the commonly used explainer methods.

1 Introduction

Artificial Intelligence (AI) has found real-world applications in clinical computer-aided decision systems, medical diagnosis, and autonomous driving. These critical applications raise concerns about whether AI models are trustworthy and whether their decisions are valid (Tjoa & Guan, 2020). Deep Neural Networks (DNNs), among the most successful AI models, make decisions using complex computations that humans do not understand. They are trained end-to-end and are susceptible to learning detours and biases from the dataset rather than the actual concepts. Since AI is now responsible for decisions affecting human rights and ethics, governments have begun enacting laws requiring explanations in certain situations (Goodman & Flaxman, 2017). This has increased the demand for DNNs to explain themselves. Explaining DNNs offers benefits beyond decision verification, including bias detection, trust development, and legal compliance (Caruana et al., 2015); it also helps diagnose and improve the model (Weber et al., 2023; Anders et al., 2022; Gupta et al., 2023). Additionally, knowledge can be discovered from models with superior-than-human performance to enrich human understanding (Du et al., 2019).

Interpreting the decisions of Deep Neural Networks (DNNs) at the level of individual samples has gained attention in recent years, with local interpretation methods providing insights into single predictions. There are two paradigms for local interpretation: intrinsic methods and post-hoc methods. Intrinsic interpretability is achieved by enforcing interpretability directly into the model's architecture and training strategies (Zhang et al., 2018; Chen et al., 2016; Freitas, 2014), enabling the model itself to provide explanations for its decisions. However, these methods do not apply to already trained models (Gilpin et al., 2018; Kim et al., 2018) and often impose architectural constraints or trade-offs with performance (Gilpin et al., 2018). Post-hoc methods, in contrast, provide explanations for models that have already been trained by adopting assumptions and simplifications, which can sometimes lead to misleading interpretations, as they may not be valid in the model's decision-making process (Gilpin et al., 2018; Sixt et al., 2020). Most local interpreters provide interpretations

based on the last few layers of the network, which, although insightful, are inherently low-resolution and fail to precisely localize the input regions responsible for the model's decisions; furthermore, they are insufficient for supporting comprehensive diagnostic analysis of the model. While some methods attempt to provide interpretations based on the middle layers, their explanatory performance typically degrades as interpretations move farther from the decision layer. Independent of the paradigm, there are two crucial objectives in local interpretation: **faithfulness** and **human-understandability**. Faithfulness means that explanations accurately reflect the valid reasons behind the model's decisions, capturing the underlying decision-making process. Human-understandability, on the other hand, requires explanations to be easy to comprehend. Given the need for human-understandability, recent advancements in explainable AI (XAI) have focused on providing interpretations in terms of human-understandable concepts, defined as semantically meaningful groups of input features that are effective in the model's decision-making, rather than single attribution maps of raw features (Schwalbe, 2022). While the initial methods depended on expert-defined concept annotations (Kim et al., 2018; Graziani et al., 2018; Koh et al., 2020), unsupervised local concept-based methods have developed approaches for providing explanations without requiring expert annotations (Ghorbani et al., 2019; Zhang et al., 2021; Fel et al., 2023; Wang et al., 2024). These approaches involve identifying regions that influence decision-making, defining concepts based on these regions across the entire dataset, and expressing these concepts in a human-comprehensible manner, for example, using word phrases (Radford et al., 2021; Ahn et al., 2024; Oikarinen & Weng, 2022). Potential regions are detected using various techniques such as super-pixel segmentation (Ghorbani et al., 2019), random cropping (Fel et al., 2023), object segmentation models trained on large datasets (Kirillov et al., 2023; Sun et al., 2023), and other local interpretation methods (Wang et al., 2022). While the primary focus of these studies has been concept definition for human-understandability, accurately localizing the input regions influencing the model's decision-making is also a critical step. This step leads to extracting more meaningful concepts and providing interpretations that are reliable and sound, aligning with faithfulness as the other core objective of local interpretation methods.

This study directly addresses the practical need for a versatile method to faithfully detect the input regions that are crucial to the model's decision-making process. To this end, we developed a technique with a novel perspective by introducing Distinguishing Clues (DCs) as a set of input regions that favor a subset of network outputs over others. Our framework for local interpretation introduces a set of DCs that distinguish each output from others, along with a module called Local Attention Perception (LAP) that identifies the input regions associated with each DC at any desired network layer, providing in-depth interpretations. Additionally, we propose a new training scheme that enables the training of LAPs without requiring detailed annotations, making the approach broadly applicable to any dataset without additional requirements. Furthermore, this training scheme allows existing knowledge about the task, e.g., the minimum size of distinguishing regions, to be injected into the model's training, thereby enhancing its interpretability. We assessed the superiority of the proposed framework to other local interpretation methods under two settings: training a model from scratch and interpreting an already trained model. The results demonstrate that LAPs can provide a more faithful-to-the-model interpretation than other local interpreters, without causing a performance drop in either setting. We also demonstrated the effectiveness of the provided training scheme through extensive ablation studies. The key contributions are:

- Introducing a versatile framework for local interpretation of DNNs that enhances interpretability without constraining architecture or compromising performance, applicable to both training from scratch and trained models, surpassing renowned local interpreters.

- Defining a *System of Distinguishing Clues* that provides local interpretations promoting each output at different depths of the network, allowing depth-wise diagnosis of the model.

- Proposing a novel training scheme for detecting the DCs without depending on experts' annotations that provides a means for general knowledge injection in training.

- Designing a module for the localization of DCs in the DNNs, usable as both a detached module and a plugged-in module inside the architecture, even in the already trained models, enhancing the performance of the task through the usage of interpretations.

Figure 1: **(a)** Representative images from a 4-class classification task: No Animal (Pixnio, n.d.), Cat (FreeRangeStock, n.d.), Rabbit (Timeless Moon, n.d.), and Ferret (Pexels, n.d.). **(b)** For a network trained on this task, local interpretation scores input pixels based on their contribution to the network's decision for a specific class. Notably, local interpretation differs from segmentation; shared features, such as a furry body, receive low scores in any single class. **(c)** An example clue system for interpreting the network considers three Distinguishing Clues (DC), Cat vs. Others, Rabbit vs. Others, and Ferret vs. Others, each scoring pixels contributing to their respective classes. The "No Animal" class serves as the Background output (BGO), defined by the absence of clues for other classes. The training scheme proposed in this paper enables learning these DCs without expert annotations. **(d)** Local concept-based interpretation scores pixels favoring each class and represents them in a human-understandable form, such as naming. Using more precise local interpretations as input to concept-based methods can lead to the discovery of more effective and meaningful concepts for interpreting network decisions. b, c, and d show sample ideal interpretations for a hypothetical trained network.

2 Method: LAP-Based Interpretation

In this section, we introduce LAP-based interpretation as our method. For this purpose, we first define Distinguishing Clue (DC).

Definition 1 *A **Distinguishing Clue (DC)** is defined as the set of input regions that favor a subset of network outputs (classes) over others.*

Furthermore, when no distinguishable input regions can be identified that explicitly contribute to a given output class, we define the class as **BGO (Background Only)**, indicating that no corresponding DC is required for its interpretation. Since the BGO class represents the absence of class-specific evidence and captures only background responses, there can be at most one such class.

Note that DNNs implicitly learn task-specific discriminative features, progressively refining them with increasing depth through the layers. While the final layers capture the most definitive representations, intermediate layers (or section[1]) develop earlier, less precise understandings. Therefore, we leverage DCs (Definition 1) to identify input regions associated with these features at any network section. These regions serve as local interpretations for the learned representations in DNN networks up to that section. We propose a module called LAP that computes importance probabilities for each element per DC. Elements refer to components of the input data or intermediate feature maps, where each component is represented by a feature vector, such as pixels with RGB channels, voxels in 3D images, or feature map locations, each corresponding to a patch in the input image. A flexible training scheme trains LAPs either as post-hoc interpreters for trained networks or as plug-in modules that provide self-interpretability, enabling LAPs to score DC-wise importance probabilities for each element. While applicable to inputs of various dimensions and modalities, we demonstrate its use for 2D inputs (pixels) in this paper, with the formulation seamlessly extending to any dimensionality or modality. Next, we provide an example for DC and compare it with a similar concept-based interpretation method.

Example 2.1 *Samples of a four-class classification task, with classes "No Animal," "Cat," "Rabbit," and "Ferret," are presented in Fig. 1. a. For these samples, local interpretations (Fig. 1.b), DC-based interpretations (Fig. 1.c), and concept-based interpretations (Fig. 1.d) are provided for a hypothetical model trained on this task. For this example, we have employed a set of three DCs to provide interpretations: "Cat vs. Others," "Rabbit vs. Others," and "Ferret vs. Others" (Fig. 1.c). Each DC assigns scores to input regions that promote its associated class over the others. For example, input regions containing features that promote the class "Cat" over other classes, e.g., triangular ears and large eyes, constitute the DC for "Cat vs. Others." For the "No Animal" class, no distinguishing input regions can be identified that explicitly promote it; instead, the absence of discriminative evidence for the other classes leads the network to favor it. This is called a BGO (Background Only) class in DC-based interpretation and therefore does not require a corresponding DC for interpretation. The DCs together provide the local interpretation for each desired target label.*

The DC-based interpretation is also compared with concept-based interpretation methods, which score pixels favoring each class and represent them in a human-understandable form, such as naming (Fig. 1.d). Both approaches belong to the domain of local interpretation methods and therefore share the common objective of scoring input pixels that promote each target label, making their methods comparable in terms of the validity of the identified pixels. Concept-based methods add an additional step that presents highly scored regions in a human-understandable way.

The following sections detail the definition of DCs, the LAP architecture, and the training scheme; additionally, a summary of key terms is provided in Appendix (App) 4.

2.1 A Complete System of DCs for Discriminating Between outputs

To formalize the problem setting, consider an input space $\mathbb{R}^{F \times H \times W}$ where F, H and W denote input per element's features, height and width, respectively. We also denote N possible outputs as $Y^{1:N}$, and a dataset of input-output pairs $D = \{(X_i, y_i) \in \mathbb{R}^{F \times H \times W} \times Y^{1:N}\}$. Adopting an element-based perspective, we represent each input as a set of elements, where each element is a pair consisting of a spatial location and its corresponding feature vector (i.e., $(\mathbb{R}^F)$). As mentioned in Definition 1, a **DC** is a combination of elements corresponding to discriminative features that promote specific network outputs over others. Formally, each DC, dc_m, promotes a subset of outputs $(Y^{dc_m^+} \subset Y^{1:N})$ over another exclusive subset $(Y^{dc_m^-} \subset Y^{1:N} \setminus Y^{dc_m^+})$. According to Eq. (1), each dc_m is the set of combinations of elements present in inputs related to $Y^{dc_m^+}$ but absent from those related to $Y^{dc_m^-}$. Here, $\mathbb{P}_{H \times W}(\mathbb{R}^F)$ denotes the power set of possible input elements, $\wedge$ and $\vee$ denotes AND and OR functions.

---

[1]We define a section as a width cut that may contain multiple layers belonging to parallel paths in the model architecture, jointly capturing the representational capacity of parallel components at a given network depth.

$$dc_m = \left\{ z \in \mathbb{P}_{H \times W}(\mathbb{R}^F) \middle| \left(\exists (X, y) \in (\mathbb{R}^{F \times H \times W}, Y^{1:N}) : (y \in Y^{dc_m^+}) \wedge (z \subseteq X) \right) \right.$$
$$\left. \wedge \left(\nexists (X, y) \in (\mathbb{R}^{F \times H \times W}, Y^{1:N}) : (y \in Y^{dc_m^-}) \wedge (z \subseteq X) \right) \right\}. \tag{1}$$

For a comprehensive understanding of the rationale behind an output in the network, the system of defined DCs ($DC^{1:M}$) must satisfy the completeness condition as specified in Eq. (2) which holds $\forall y \in Y^{1:N}$. To satisfy completeness, either one output (y) is designated as the Background output (**BGO**), or there exists a subset of DCs (DC_y) that uniquely distinguish y from all other outputs. The **BGO** denotes an output for which no distinguishing clue can be identified; the absence of clues for alternative outputs results in the network selecting the BGO (see Example 2.1). For instance, in binary existence classification, the negative class functions as the BGO, and a single DC distinguishing the positive class from the BGO suffices. Likewise, for an N-class classification task, a one-vs-others scheme can establish a complete set of DCs (see Example 2.1).

$$\left((y = BGO) \wedge (\nexists y' \in Y^{1:N} : (y' \neq y) \wedge (y' = BGO)) \right) \vee \left(\exists DC_y \subset DC^{1:M} : ((\bigcap_{dc_m \in DC_y} Y^{dc_m^+}) = \{y\}) \right), \tag{2}$$
$$\forall y \in Y^{1:N}.$$

2.2 In-Depth LAP Units for DC Localization

LAP: We designed a module called **Local Attention Perception (LAP)** to automatically identify DCs at any network layer. LAP generates probabilistic importance maps that highlight which pixels contribute most to a decision at different network depths. LAP can be viewed as an attention mechanism, since it assigns importance scores to input pixels. However, unlike standard attention, it operates on each pixel's feature vector alone, without explicit key-value pairs, and where "importance to a DC" implicitly serves as the "key" [2]. As shown in Fig. 2.a, an LAP is a trainable unit that takes the feature map from the section of the network we aim to interpret (X^l) and computes DC-specific importance probability maps for that section (I^l), mathematically expressed in Eq. (3) for the l-th LAP. For a system with M DCs, the LAP has M output heads, each estimating the relevance probability of a pixel to one DC (I_{ij}). In this design, probabilities are used instead of raw importance scores because they are more intuitive for humans and enable the use of loss functions for training LAPs, as further detailed in Sec. 2.3. One possible LAP implementation uses stacked convolutional layers with 1×1 kernels and M output channels, followed by a sigmoid activation to generate the final importance probabilities.

$$I_{ij}^l = LAP^l(X_{ij}^l); \qquad LAP^l : \mathbb{R}^F \to [0, 1]^M \tag{3}$$

LAP-Pool: Since LAP generates DC-wise importance maps that highlight key task-specific input regions, these maps can be leveraged within pooling layers as a practical extension of our framework, though this does not constitute the main focus of this work. As illustrated in Fig. 2.b, LAP-Pool aggregates the importance maps computed by LAP into a unified pixel-wise importance score map. For each kernel position in the pooling process, the scores for pixels within the kernel are normalized, and the final feature vector is obtained by weighted averaging these normalized scores. This approach mimics a dynamic zooming mechanism that identifies the most critical pixels under each kernel and propagates their features rather than indiscriminately mixing them, as in average pooling. Consequently, important fine-grained details are preserved and propagated through the network's depth while avoiding artifacts from naive feature mixing. For greater clarity, we have adopted the unified pooling framework of Gao et al. (Gao et al., 2019) to formalize the LAP-Pool procedure in App. A.4.

Aggregation through the depth: As stated earlier, final layers capture the most definitive task-specific features, while intermediate layers develop earlier, less accurate understandings. A single LAP module provides pixel-wise importance probabilities per DC at a chosen network section, reflecting the level of

---

[2]The differences are discussed in detail in App. A.3

Figure 2: **(a)** Architecture of a Local Attention Perception (LAP) unit. LAP takes a feature map as input and outputs a probabilistic importance map that highlights the regions most relevant to each Distinguishing Clue (DC). **(b)** Architecture of a **LAP-Pool** module. LAP-Pool aggregates the probabilistic importance maps of all DCs into a single importance score map, which guides pooling by weighting pixel features based on their importance, preserving the features from the most informative regions. **(c)** LAP units can be applied at various depths of the network to provide sectional and complementary interpretations. LAPs closer to the input produce higher-resolution maps, while those near the output layer yield more decision-relevant interpretations. By aggregating outputs from multiple LAPs, a final interpretation can be constructed that balances spatial detail with decision-level accuracy. **(d)** and **(e)** LAPs can be used in two distinct paradigms for interpreting networks. In the post-hoc interpretation setting (**d**), LAPs analyze and interpret pre-trained networks without modifying their architecture or weights; here, the network parameters are frozen, and only the LAP modules are trained using LAP-specific supervision losses. Alternatively, in the intrinsic interpretation paradigm (**e**), LAPs are integrated during training, allowing both the network and LAP modules to be trained jointly from scratch. In this approach, LAP units can be implemented either as plug-in LAP-Pools or as detached modules at arbitrary points within the network. Combining LAP supervision losses with the main classification loss encourages the network to learn features that explicitly reveal distinguishing clues, resulting in a model that is inherently more interpretable.

understanding up to that layer. Multiple LAP units can be employed to obtain DC-wise importance maps at different network depths, yielding maps with varying resolutions and accuracies, as illustrated in Fig. 2.c. Maps closer to the final decision layer tend to be more accurate, but have lower resolution and less precise spatial alignment with the input image. Conversely, maps nearer the input layer offer higher resolution but are less accurate. To leverage the advantages of both, the DC-wise probability maps are combined across the network depth (see App. A.5), yielding a single, refined local interpretation.

Usage: LAP modules can be employed in two ways: as detached LAPs, which receive the feature map and compute DC-wise importance probability maps without altering the network's forward flow, or as plugged-in LAP-Pools (Fig. 2 d and e). LAP-Pools can be integrated into any convolutional architecture by replacing pooling or adaptive pooling layers. Strided convolutions can likewise be substituted with a stride-one

convolution followed by a LAP-Pool matching the original kernel size and stride. LAPs support various training and deployment scenarios: detached LAPs can be applied to interpret trained models without altering their operation (Fig. 2.d). Alternatively, LAP-Pools and LAP modules can be trained jointly with networks from scratch in an end-to-end manner, as shown in Fig. 2.e. Additionally, LAPs enable a selective fine-tuning setting, where LAP-Pools are integrated into pre-trained models and optimized either independently or alongside specific network components, while freezing the remaining parameters. This approach leverages the selective nature of pooling operations as learned feature-stream selectors, facilitating the efficient adaptation of existing architectures.

2.3 Weakly Supervised Training Scheme for Learning DCs

As previously described, each input is associated with a part of the defined DCs, namely those that support its ground-truth label over other possible labels. The goal of the LAP supervision loss is to leverage this information to train LAPs to detect elements in the feature maps that are truly related to each DC. To achieve this, we have defined three key terms in the loss:

- **Coverage:** For a positively associated DC with a sample, there must be at least some elements in the sample's feature map that are related to the DC. The **Min Active Ratio (MinAR)** term encourages LAPs to assign high importance probabilities to these elements.

- **Precision:** Not all elements in a feature map are related to a positively associated DC. The **Max Active Ratio (MaxAR)** term discourages LAPs from assigning high importance scores to irrelevant elements, such as background regions, by limiting the number of elements it selects as relevant.

- **Exclusion:** There should be no elements related to a negatively associated DC, i.e., those supporting labels other than the ground truth, in the feature map of a sample. The **Inactive Ratio (IAR)** term discourages LAPs from assigning high importance probabilities to elements for the irrelevant DCs.

Thus, during training, LAP learns that elements that frequently appear in samples associated with a particular DC, and are absent in others, represent the true evidence for that DC.

To express it formally, each DC, $dc_m \in DC^{1:M}$, corresponds to discriminative elements that favor $Y^{dc_m^+}$ over $Y^{dc_m^-}$. We leverage this definition to develop a weakly supervised training scheme for LAPs, enabling them to learn to detect these discriminative elements for each DC, without relying on expert annotations. As shown in Eq. (4), the supervision loss for the l-th LAP, denoted as L_{LS_l}, is composed of three terms for each DC dc_m. The **MinAR** and **MaxAR** loss terms are applied to DC-present samples (i.e., those with ground truth in $Y^{dc_m^+}$), while the **IAR** is applied to DC-absent samples (i.e., those with ground truth in $Y^{dc_m^-}$). The loss terms are normalized by the number of DC-present and DC-absent samples for dc_m, represented as n_m^+ and n_m^-, respectively. The 3 terms are explained in detail below.

$$L_{LS_l} = \sum_{m=1}^{M} \left(\frac{\sum_{(X^l, y): y \in Y^{dc_m^+}} \left(L_{LS_{l,m}}^{MinAR}(X^l, y) + L_{LS_{l,m}}^{MaxAR}(X^l, y) \right)}{n_m^+} + \frac{\sum_{(X^l, y): y \in Y^{dc_m^-}} L_{LS_{l,m}}^{IAR}(X^l, y)}{n_m^-} \right) \quad (4)$$

The **MinAR** loss encourages LAP to assign high importance probabilities to at least a specified portion of elements (γ^{MinAR}) in DC-present samples, ensuring sufficient coverage. Conversely, the **MaxAR** loss restricts LAP from assigning high importance to more than a particular portion of elements in DC-present samples (γ^{MaxAR}), promoting precise localization, especially in deeper layers with larger receptive fields. Since DC-related input regions may appear in the receptive fields of all elements, the network might otherwise consider all of them DC-related. Finally, the **IAR** loss penalizes high importance probabilities in DC-absent samples, compelling LAP to avoid false activations. To maintain balance with MinAR, IAR is applied only to a selected portion (γ^{IAR}) of challenging elements rather than the entire set. The loss terms for the l-th LAP and the m-th DC, given a sample with input embedding X^l to the LAP and ground-truth label y, are computed as follows. Let $I^{l,m}$ denote the output of the l-th LAP for the m-th DC for input X^l according to Eq. (3). The operators Top-K($I^{l,m}$) and Bot-K($I^{l,m}$) return the indices of the K largest and smallest

elements of $I^{l,m}$, respectively, and n_e denotes the number of elements in X^l. Using these definitions, the corresponding loss terms are:

$$L_{\text{LS}_{l,m}}^{\text{MinAR}}(X^l, y) = \frac{-2}{K_{\text{MinAR}}} \times \sum_{i \in \text{Top-K}_{\text{MinAR}}(I^{l,m})} \ln(I_i^{l,m}) \quad ; \quad K_{\text{MinAR}} = \lceil \gamma^{\text{MinAR}} \times n_e^l \rceil$$

$$L_{\text{LS}_{l,m}}^{\text{MaxAR}}(X^l, y) = \frac{-1}{K_{\text{MaxAR}}} \times \sum_{i \in \text{Bot-K}_{\text{MaxAR}}(I^{l,m})} \ln(1 - I_i^{l,m}) \quad ; \quad K_{\text{MaxAR}} = \lceil (1 - \gamma^{\text{MaxAR}}) \times n_e^l \rceil \quad (5)$$

$$L_{\text{LS}_{l,m}}^{\text{IAR}}(X^l, y) = \frac{-1}{K_{\text{IAR}}} \times \sum_{i \in \text{Top-K}_{\text{IAR}}(I^{l,m})} \ln(1 - I_i^{l,m}) \quad ; \quad K_{\text{IAR}} = \lceil \gamma^{\text{IAR}} \times n_e^l \rceil$$

In equation 5, $I_i^{l,m}$ denotes the importance probability calculated for the i-th element for the m-th DC in $I^{l,m}$. For **MinAR**, positive cross-entropy loss is calculated over the K_{MinAR} elements with the highest importance probabilities for the dc$_m$ ($i \in \text{Top-K}_{\text{MinAR}}(I^{l,m})$), whereas for **MaxAR**, negative cross-entropy loss is calculated over the K_{MaxAR} elements with the lowest importance probabilities ($i \in \text{Bot-K}_{\text{MaxAR}}(I^{l,m})$). In contrast, for **IAR**, which is applied on the DC-absent samples, negative cross-entropy loss is calculated over K_{MinAR} elements with the highest importance scores ($i \in \text{Top-K}_{\text{IAR}}(I^{l,m})$), i.e., the challenging ones that are mistakenly scored high. More notes on pixel selection are provided in App. A.6. Notably, the first term is multiplied by 2 to balance the effect of positive and negative losses for dc$_m$. γ^{MinAR}, γ^{MaxAR}, and γ^{IAR} are hyper-parameters. If general knowledge about the domain exists, e.g., the expected size range of Distinguishing Clues (DCs), it can be injected into training through these parameters. Otherwise, they can be treated like standard hyper-parameters and selected based on validation performance. Further details are provided in App. A.10.1.

Although the training scheme is designed not to rely on expert annotations, if someone wishes to use detailed annotations, the proposed method can also fully inject expert knowledge into the training. The details are provided in App. A.7. Additionally, beyond the main loss terms, optional consistency losses can be applied to encourage agreement between output probability maps from different LAPs. Further details are provided in App. A.8.

3 Experiments

The primary purpose of the experiments is to assess the success of the proposed method, LAP, in interpreting models compared to other white-box local interpreters, from the perspective of faithful localization. Comparisons were conducted under both post-hoc interpretation and training-from-scratch schemes to evaluate general applicability. To this end, we compared LAP's interpretations with those from widely used white-box local interpretation methods that require little to no modification, as well as recognized methods published in top-tier venues: Guided Back-propagation (GBP) (Springenberg et al., 2014), Grad-CAM (GC) (Selvaraju et al., 2017), Guided Grad-CAM (GGC) (Selvaraju et al., 2017), DeepLIFT (DL) (Shrikumar et al., 2017), and Relevance-CAM (RC) (Lee et al., 2021), as well as one unsupervised concept-based local interpretation method, CRAFT (CR) (Fel et al., 2023). Additionally, we compared LAP with the self-interpretability method BotCL (Wang et al., 2023), which requires network modification and tuning. Implementations from Captum (Kokhlikyan et al., 2020) in PyTorch (Ansel et al., 2024) were used for the first four methods, while the original GitHub repositories were used for the latter two. Furthermore, the performance and interpretability of the LAP-extended architectures were compared with those of the original architectures to assess LAP's impact on overall performance as a secondary output of this study.

In the experiments, LAP's generality was validated on two common CNN architectures, ResNet (He et al., 2016) and Inception-V3 (Szegedy et al., 2016). We evaluated our method on two datasets from different domains: a medical dataset and the well-known ImageNet. Further details regarding the choice of architectures and interpretation methods for comparison are provided in App. A.9. The experimental setup and results for these datasets are presented in the following subsections. Runtime efficiency and the practical feasibility of the proposed method are confirmed in App. A.13.

Table 1: Classification F1-Score and Balanced Accuracy (BA) on the RSNA test dataset for the vanilla ResNet18 and Inception3 models, BotCL-extended models (BCL-), LAP-extended models trained using the proposed weak supervision (WSL-), and LAP-extended models trained using expert annotations (BBL-). LAP-extended models achieve higher average performance metrics compared to the vanilla and BotCL-extended models across both architectures. Notably, the WSL version trained without expert annotations performs on par with the BBL version trained with expert annotations. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

	ResNet 18 (RN)				Inception V3 (I3)			
	RN	BCL-RN	WSL-RN	BBL-RN	I3	BCL-I3	WSL-I3	BBL-I3
F1	94.58$\pm$0.27	94.79$\pm$0.26	94.88$\pm$0.22	**94.92**$\pm$0.19	95.15$\pm$0.41	95.22$\pm$0.25	95.28$\pm$0.19	**95.32**$\pm$0.24
BA	94.52$\pm$0.25	94.74$\pm$0.26	94.72$\pm$0.27	**94.86**$\pm$0.2	95.14$\pm$0.39	95.17$\pm$0.28	**95.25**$\pm$0.17	95.21$\pm$0.3

Baselines: We consider Guided Back-propagation (GBP) (Springenberg et al., 2014), Grad-CAM (GC) (Selvaraju et al., 2017), Guided Grad-CAM (GGC) (Selvaraju et al., 2017), DeepLIFT (DL) (Shrikumar et al., 2017), Relevance-CAM (RC) (Lee et al., 2021), CRAFT (CR) (Fel et al., 2023), and BotCL (BCL) (Wang et al., 2023) as baselines in our experiments.

Datasets: We consider datasets, RSNA Pneumonia Detection (Anouk Stein et al., 2018), and ImageNet Object Recognition (Russakovsky et al., 2015).

3.1 RSNA pneumonia detection

Experimental Setup: The RSNA pneumonia dataset was published in a Kaggle challenge in 2018 (Anouk Stein et al., 2018). The dataset contains chest X-ray images of 8851 healthy people and 6012 patients with lung pneumonia. Pneumonia regions are annotated by experts using bounding boxes. We used the dataset for a binary classification task with two base architectures: ResNet-18 and Inception-V3. To assess the effect of LAPs as internal modules, we also adopted LAP-extended ResNet-18 and LAP-extended Inception-V3 architectures, in each of which 4 LAP-Pools were used in different layers from shallow to deep ones (App. A.10.2). According to Sec. 2.1, we used a single DC, "pneumonia," to interpret the decisions. We trained LAP-extended models using two approaches: weak supervision without expert annotations (WSL-), following the explanations in Sec. 2.3, and experts' knowledge injection (BBL-), where experts' bounding boxes were used to train the LAPs as described in App. A.7. Additionally, we applied the self-interpretation method of BotCL to train BotCL-extended architectures (BCL-) (Wang et al., 2023), which served as another baseline for comparison.

The experiments were repeated five times with different seeds to report the mean and standard deviation.

Classification Performance: We used two metrics to evaluate model classification performance on the test set: Balanced Accuracy (BA) and F1-Score. The results are reported for all four versions of each of the two architectures in ResNet-18 and Inception-V3. For both ResNet-18 and Inception-V3 architectures, in Table 1, the average performance of the LAP-extended models slightly surpasses that of the vanilla (p-value ≤ 0.05 in an unpaired t-test) and BotCL-extended models. Notably, the performance of the LAP-extended model trained with the proposed weak supervision method (**WSL-**), which does not rely on expert annotations, closely aligns with that of the LAP-extended model trained using expert bounding boxes (**BBL-**). Detailed performance metrics are provided in App. A.11.1.

Evaluation of Interpretation Score Maps: Several evaluation metrics have been introduced in the literature for evaluating interpretation methods. In this study, we have employed two distinct evaluation methods for our two datasets based on the nature of their domain (further explanations are provided in App. A.9.1). For the RSNA dataset, following the "object localization" method (Lee et al., 2021), the Intersection over Union (IoU) metric was calculated between the binarized interpretation maps and the bounding boxes provided by experts for correctly predicted positive cases of pneumonia. Various binarization approaches have been adopted in the literature, ranging from selecting a fixed portion, e.g., 15% of the top-scored pixels (Selvaraju et al., 2017), to adopting a threshold of mean + standard deviation ("$\mu + \sigma$") over the individual interpretation score maps (Lee et al., 2021). We used three approaches to assess interpretations

Table 2: IoU of the binarized interpretation maps with expert annotations on correctly classified positive RSNA test samples. Results are provided for the vanilla ResNet18 and Inception3 models, BotCL-extended models (BCL-), LAP-extended models trained using the proposed weak supervision (WSL-), and LAP-extended models trained using expert annotations (BBL-). LAP-based interpretations produce binarized maps that are significantly closer to expert annotations compared to other interpretation methods across all eight architectures. Additionally, while the BotCL approach reduces similarity to expert annotations relative to the vanilla models, the proposed LAP supervision loss enhances the detection of relevant regions, even for other interpretation methods such as CRAFT and Relevance-CAM. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds. Not Applicable (NA): The BotCL interpretation method applies only to BotCL-extended architectures.

Models	IoU Between Expert Annotations and Binarized Interpretation Maps (Threshold: $\mu + \sigma$)							
	DL	GGC	GC	GBP	RC	CR	BotCL	LAP
ResNet18	13.6±0.81	8.99±1.46	22.63±1.47	7.86±1.4	6.9±1.49	21.29±1.89	NA	**31.37±2.79**
BCL-RN	14.04±1.39	8.21±2.10	17.05±1.58	9.56±0.79	20.05±4.37	17.79±4.22	17.19±3.52	**25.01±2.48**
WSL-RN	15.07±0.51	12.21±0.77	13.85±1.75	12.56±0.77	34.24±0.99	32.41±1.41	NA	**36.28±1.19**
BBL-RN	15.72±0.67	13.95±0.56	18.87±5.03	13.77±0.91	25.75±3.81	34.92±5.28	NA	**43.26±1.51**
Inception3	13.12±0.73	7.73±0.78	26.86±0.96	8.17±0.81	27.93±0.97	26.86±1.30	NA	**29.52±0.93**
BCL-I3	12.66±0.68	5.68±2.50	3.10±3.59	7.81±0.62	7.03±4.87	3.96±5.60	1.62±1.22	**24.40±2.05**
WSL-I3	14.14±0.51	6.09±1.19	7.89±2.14	6.82±1.62	33.43±0.76	32.87±1.01	NA	**35.75±0.62**
BBL-I3	15.28±0.41	8.12±1.54	21.03±3.36	8.43±1.67	36.35±1.13	31.77±3.32	NA	**41.46±1.87**

from different perspectives. Note that the BotCL interpretation method applies only to BotCL-extended architectures. The results for "$\mu + \sigma$" are presented in Tab. 2, and the results for the other approaches are available in App. A.11.2. Notably, LAPs inherently provide a classification over the interpretation maps and do not require external thresholds. We adopted LAP as a post-hoc interpreter for the vanilla and the BotCL-extended architectures, and as an intrinsic interpreter for the LAP-extended ones. Across all three binarization approaches, the IoU for LAPs is significantly higher than that of the other interpreters for all models (p-value ≤ 0.001 in a paired t-test).

The IoU of LAP's importance maps with the ground truth bounding boxes ranges from 24% to 43%. In comparison, the next most successful methods, Relevance-CAM (RC) and CRAFT, range from 7% to 36% and 4% to 35%, respectively, across the same models. Additionally, LAPs trained with the proposed weak-supervision method (requiring no expert annotations) achieve 35–36% IoU, compared to 41–43% IoU for LAPs trained with expert bounding boxes.

Interestingly, the interpretation maps of CRAFT and Relevance-CAM, which outperform the other methods except for LAP, also improve in LAP-extended architectures (32–35% and 26–36%, respectively), compared to the vanilla architectures (21–27% and 7–28%), while decreasing in BotCL-extended architectures (4–18% and 7–20%).

Model Diagnosis via Interpretation Maps: LAPs also enable us to diagnose the decision-making process for each individual image by providing through-the-depth interpretations. Interpretations of LAPs for four examples are shown in Fig. 3 using a WSL-ResNet-50 model. The sources of errors made by the model in the first and third cases are identifiable. In the first case, the initial two LAPs correctly detected the pneumonia region, but the model later altered its decision. In the third case, the model incorrectly identified pneumonia regions highlighted by the LAPs. Notably, the final LAP interpretation is aligned with the model's decisions. It can also be observed that the aggregated result, denoted as "LAP All," is as high-resolution as the first LAP while being as accurate as the last one. For true-positive predictions, LAP interpretations show a satisfactory overlap with infection bounding boxes, whereas other methods fail to capture all boxes. Overall, the regions highlighted by LAP are also more reasonable. Additional examples from other models are provided in App. A.15. Each LAP can also function as a standalone predictor, aiding in model diagnosis. Related experiments are detailed in App. A.14.1.

Ablation Studies: To assess the effectiveness of the proposed weakly supervised training scheme, we trained the LAP-extended ResNet-18 architecture under three additional settings: two naive weak-supervision methods, in which the MaxAR loss term is omitted and IAR is applied to all pixels ($\gamma^{\mathrm{IAR}} = 1$); in one of

Figure 3: Examples of WSL-ResNet18 interpretations (LAPs) compared to RSNA bounding boxes (BB) and other interpretation methods. LAP is faithful to the model's prediction (P), showing from which layer the model has differed from the ground truth (GT).

these, the MinAR term is applied to only the top pixel ($\gamma^{\mathrm{MinAR}} = \frac{1}{HW}$), while in the other, MinAR is applied to all pixels ($\gamma^{\mathrm{MinAR}} = 1$). For the third setting, a hybrid approach is adopted, in which MinAR is applied to a proportion of pixels according to the proposed method ($\gamma^{\mathrm{MinAR}} = 0.1$), while IAR and MaxAR terms remain the same as in the naive weak-supervision settings. The classification performance metrics and the IoU of the binarized interpretation maps with expert bounding boxes are reported in Tab. 3.

It is observed that the proposed training scheme leads to the highest self-interpretability (36.28%) while maintaining task-specific performance close to the best configuration (F1 of 94.88% vs. 95.00%). In contrast, configurations with naive settings exhibit significant degradation in interpretability (13.94%). Additionally, we conducted another ablation study to assess the sensitivity of results to the ratio hyper-parameters of the LAP Supervision Loss. The results presented in App. A.11.4 confirm the suitability of the proposed approach for setting these hyper-parameters based on a general knowledge of the problem domain (App. A.10.1). According to the results, the ratio of γ^{MinAR} is the most influential one; when it is large (0.5) or small (0.01), it resembles the naive weakly supervised settings, and the results degrade (IoU of 25% vs. 36%). The most suitable value for this parameter corresponds to the expected distinguishing clue size (0.1 in this problem).

Table 3: Comparison of classification performance (Balanced Accuracy (BA) and F1-Score) and similarity of binarized interpretation maps to expert bounding boxes (IoU) for LAP-extended ResNet-18 models. Models were trained under four different settings: the proposed weak-supervision scheme, two naive weak-supervision settings, and one hybrid setting. The model trained with the proposed scheme produces interpretation maps closest to the expert annotations while maintaining classification performance near the best configuration. In contrast, models trained with the naive settings exhibit substantial degradation in their interpretation maps. All values are reported as mean ± standard deviation over five independently trained models initialized with different random seeds.

Configuration	BA	F1	IoU
Proposed method ($\gamma^{\mathrm{MinAR}} = 0.1, \gamma^{\mathrm{MaxAR}} = 0.5, \gamma^{\mathrm{IAR}} = 0.1$)	94.72±0.27	94.88±0.22	**36.28**±1.19
Hybrid method ($\gamma^{\mathrm{MinAR}} = 0.1, \gamma^{\mathrm{MaxAR}} = 1, \gamma^{\mathrm{IAR}} = 1$)	94.79±0.22	94.87±0.21	31.90±1.35
Naive weak-supervision V1 ($\gamma^{\mathrm{MinAR}} = \frac{1}{HW}, \gamma^{\mathrm{MaxAR}} = 1, \gamma^{\mathrm{IAR}} = 1$)	**94.92**±0.22	**95.00**±0.20	4.40±1.23
Naive weak-supervision V2 ($\gamma^{\mathrm{MinAR}} = 1, \gamma^{\mathrm{MaxAR}} = 1, \gamma^{\mathrm{IAR}} = 1$)	94.61±0.25	94.74±0.19	13.94±0.08

3.2   Imagenet

Experimental Setup:

In this experiment, we examined the applicability of the proposed method to already trained models by evaluating its performance on the ImageNet classification task (Russakovsky et al., 2015), which involves

Figure 4: Interpretations of LAP-ResNet50 on ImageNet, highlighting the regions corresponding to each of the top-3 predicted classes as indicated in the legend.

recognizing objects with substantial variation in scale. We employed three architectures, ResNet50, InceptionV3, and EfficientNetB0, from the torchvision model zoo (maintainers & contributors, 2016). Each model was evaluated under two paradigms: post-hoc and plugged-in interpretation. Post-hoc interpretation uses detached LAPs, which are trained while the backbone network is frozen and therefore do not affect the network's classification performance. In contrast, plugged-in LAPs involve fine-tuning the full LAP-extended architecture for a few epochs. For each architecture, two LAPs were implemented, with concept sets defined using the one-vs-others strategy described in Sec. 2.1 to interpret each class. Additional details regarding the experimental setup are provided in App. A.10.3.

Classification Performance: The performance of the base (original) models was first assessed using the Top-1 accuracy metric and then compared with their LAP-extended counterparts, in which the LAP module was plugged into the pretrained networks and tuned for a few epochs. The LAP extension improved ResNet50's accuracy from 76.14% to 76.40%, yielded a slight improvement for InceptionV3 from 76.08% to 76.16%, and resulted in no change for EfficientNetB0, which achieved 77.67% accuracy.

Model Diagnosis via Interpretation Maps: Examples of LAP interpretations are provided in Fig. 4, highlighting which input regions resulted in each of the top-3 predictions. For example, in an image containing an airship and cars, the yellow coloration near the cars inadvertently increased the prediction score for the taxi class. Additional examples are available in App. A.15.

Evaluation of Interpretation Score Maps: For comparing LAP's interpretation with other interpretation methods, we followed the method presented in (Petsiuk et al., 2018) (the reasons are discussed in App. A.9.1). The interpretation methods were evaluated across two target layers: the last convolutional layer commonly utilized by various interpretation methods like CAM, which, while offering valuable insights, has low resolution and does not allow assessment of intermediate layers; and another layer before the last non-adaptive pooling that has higher resolution.

We compared the faithfulness of different interpretation methods on each model by modifying the input images based on the interpretation scores. Faithfulness was evaluated by keeping $k\%$ pixels with the highest scores provided by the interpretation method, zeroing out the rest of the image, and then passing the modified image through the network for re-evaluation. The results for LAP-extended ResNet50 are presented in Fig. 5 for percentages of 10%, 30%, 50%, 70%, and 90%. In this experiment, the interpretation scores were calculated based on the predicted class, and the results were evaluated with respect to the original predictions. A faithful interpretation method would capture the influencing regions for decision-making in the model, thereby keeping the original decision for the modified image.

Across all percentages, LAP retains higher original prediction accuracy than the other interpretation methods, with the effect most pronounced for the top 10–30% of pixels. Additionally, while the faithfulness of other methods decreases notably when interpreting layer 3 as the target, LAP maintains its performance.

The results for other architectures can be found in App. A.12.1, showing similar trends. LAP overperforms all methods in all 12 cases, but two which is slightly overperformed by GradCam.

Figure 5: Assessing the faithfulness of different interpretation methods on the ImageNet dataset for Lap-Extended ResNet 50 over the outputs of layers 3 and 4. Faithfulness is evaluated by keeping a ratio of pixels ranked by the interpretation method (K%), zeroing out the rest, and evaluating the prediction on the modified image w.r.t the prediction of the original image. LAP is shown to be more faithful than the other models, especially when interpretation is demanded for the middle layers.

4   Discussion

In this section, we provide the discussion of our results in previous section. Interpretations were produced by training a module called LAP using our designed weakly supervised loss, without relying on expert annotations. The module supported two paradigms: post-hoc and plugged-in. In the post-hoc paradigm, LAP modules were trained separately while the base network remained frozen, ensuring that the main model's performance was unaffected. In the plugged-in paradigm, LAP modules were integrated into the model architecture. The extended architecture was either trained from scratch using both the LAP supervision loss and the task-specific loss, or fine-tuned on pretrained networks for a few epochs to learn interpretations. We assessed interpretations across two datasets from different perspectives.

The interpretation maps in the RSNA dataset were assessed on correctly classified positive test samples by comparing them to the expert bounding boxes using the IoU metric, which represent the expected and clinically relevant regions. We observed five key findings:

1. Interpretation maps generated by LAP were significantly closer to the expert bounding boxes across all four extensions of the two base architectures (p-value ≤ 0.001).

2. LAP-extended architectures trained using the proposed weak-supervision method (requiring no expert annotations) achieved interpretation quality comparable to models trained with expert bounding boxes (35–36% IoU compared to 41–43%). This highlights the practical value of the method, as acquiring pixel-level expert labels is expensive and often infeasible, especially for large-scale datasets.

3. Among the three interpretation methods with the highest average IoU scores, i.e. LAP, Relevance-CAM, and CRAFT, LAP was the only method that did not exhibit significant degradation across any architecture. In contrast, Relevance-CAM and CRAFT degraded to IoU values as low as 3.96% and 7.05%, respectively, whereas the lowest IoU observed for LAP remained at 24%, indicating that competing methods are less consistent and may fail on certain model configurations.

4. The performance of all three methods degraded in architectures extended and trained using the BotCL self-interpretation method compared to the original architectures (from ranges of 30–31%, 7–28%, and 21–27% to 24–25%, 7–20%, and 14–18%, respectively). In contrast, all methods improved

in both LAP-extended architectures, including the model trained without expert bounding boxes as supervision (36–36%, 33–34%, and 32–33%, respectively). These results suggest that LAP-based supervision during training enhances overall model interpretability, benefiting not only LAP but also other interpretation methods.

5. We further demonstrated the diagnostic value of binarized interpretation maps by visualizing LAP and other interpretation methods on four representative cases with varying ground-truth and predicted labels. LAP consistently identified regions that were more clinically plausible for model decision-making and produced binarized regions of appropriate size across images with differing expert bounding box scales, unlike competing methods. This property was particularly valuable when interpretation maps were used as auxiliary outputs, such as for treatment planning in medical applications. Moreover, the layered architecture of LAP-based interpretation enabled analysis of which network components contributed to prediction errors, offering a useful tool for debugging and refining model architectures.

In the ImageNet dataset, the faithfulness of different interpretation methods was evaluated by retaining varying percentages of the highest-scoring pixels, masking the remaining pixels, feeding the modified inputs to the model, and measuring the accuracy of reproducing the original predictions. This experiment evaluated interpretations using two different target layers, allowing assessment of each method's ability to provide in-depth, layer-wise interpretability, which is useful for model diagnosis. For both the original and LAP-extended versions of the three architectures, ResNet-50, Inception-V3, and EfficientNet-B0, LAP achieved the highest faithfulness in 10 out of 12 cases, and was marginally outperformed by Grad-CAM in the remaining two cases. Notably, LAP achieved strong accuracy when retaining only the top 10–30% of pixels, indicating precise localization of regions that drive model decision-making. Additionally, while all methods showed substantial degradation when a middle layer was used as the target, LAP maintained relatively consistent performance, highlighting its effectiveness for diagnosing model behavior across network depth.

As an auxiliary experiment, we demonstrated that training LAP-extended architectures from scratch led to enhanced average performance on the RSNA dataset across both ResNet-18 and Inception-V3 architectures (F1-scores improved from 94.58 and 95.15 to 94.88 and 95.28 without expert annotations, and further increased to 94.92 and 95.32 when expert annotations were used in training LAPs). Additionally, we observed that fine-tuning LAP-extended architectures on the ImageNet dataset could slightly improve the base accuracy, with the largest improvement seen in LAP-extended ResNet-50, where accuracy increased from 76.16% to 76.40%. Despite these encouraging results, the ability of LAP-extension to enhance the performance of base architectures requires further systematic investigation, which we propose for future studies, as it falls outside the primary focus of this paper.

5 Related works

Introduction & Gradient-Based Methods: This study belongs to the category of white-box local interpretation methods, where the interpreter has full access to the model's architecture and intermediate feature maps. One of the earliest approaches in this domain is Class Activation Mapping (CAM) (Zhou et al., 2016), which uses the weights of the fully connected layer to determine the importance of features for each class and then calculates pixel scores based on channel-wise activations and their corresponding importance, making it applicable only to networks with a single fully connected layer following the last convolutional layer. Gradient-based methods estimate the network's behavior using the gradients of class scores with respect to the input, approximating the network via a first-order Taylor expansion. In this view, the gradients serve as weights indicating feature importance. Vanilla Gradient (Simonyan et al., 2013) uses raw gradients to identify important features but produces noisy importance maps. Guided Backpropagation (Springenberg et al., 2014) filters out negative gradient flows to highlight important pixels, although this filtering can lead to false positives. Grad-CAM (Selvaraju et al., 2017) follows the same principle as CAM but uses gradients to determine channel importance, making it more broadly applicable. Guided Grad-CAM (Selvaraju et al., 2017) combines Guided Backpropagation and Grad-CAM to produce fine-grained importance maps.

Score-Based Methods: Gradient-based methods suffer from gradient saturation problems, leading to near-zero importance scores. Score-based methods like Layer-wise Relevance Propagation (LRP) (Bach et al., 2015; Binder et al., 2016) and DeepLift (Shrikumar et al., 2017) propagate scores instead of gradients to calculate the importance of neurons. LRP has defined layer-specific rules to distribute the relevance score of each neuron in each layer to their input neurons. The rules assign relevances based on the contribution of the input neurons to the neurons in the next layer. DeepLift uses a similar procedure to LRP but calculates scores based on the difference in the output achieved compared to a baseline input. However, defining a suitable and meaningful baseline for all applications is challenging. Recently, some works have combined the CAM with score-based interpretations to improve both. Score-CAM (Wang et al., 2020) adopts a DeepLift-style scoring scheme to find the channel-wise increase of confidence and then uses the confidence scores in the CAM method. Similar to Score-CAM, Relevance-CAM (Lee et al., 2021) uses the LRP method to find the importance of channels in any layer and then applies the CAM method to find the corresponding regions in the input. Relevance-CAM has demonstrated superior performance over other CAM-based methods.

Concept-Based Methods: Despite previous literature providing interpretations as attribution maps on raw features, concept-based interpretation methods offer explanations in a more human-comprehensible manner by utilizing concepts as semantically meaningful groups of input features (Schwalbe, 2022). Initial concept-based methods depended on expert annotations (Kim et al., 2018), which are expensive and not available for all datasets. To address this limitation, later methods focused on mining concepts using unsupervised techniques such as clustering (Ghorbani et al., 2019; Kowal et al., 2024), matrix factorization (Zhang et al., 2021; Fel et al., 2023), and principal component analysis (Zhang et al., 2021). Alternatively, some approaches incorporate encoder-decoder modules within the main architecture to reconstruct embeddings while encoding a dense set of concepts (Akpudo et al., 2025). Recent studies on unsupervised local concept-based interpretation methods enable localization of concepts within input data, either by extending conventional local interpretation methods like LRP (Achtibat et al., 2023), GradCam (Fel et al., 2023), and unsupervised segmentations (Wang et al., 2024), or by calculating similarity with concept or prototype vectors (Chen et al., 2019; Wang et al., 2023; Huy et al., 2025; Zhu et al., 2025), or with CLIP's provided embeddings for the concepts' terms (Benou & Raviv, 2025; Zhang et al., 2025). Methods such as CRAFT (Fel et al., 2023) and MCPNet (Wang et al., 2024) have proposed techniques to identify concepts recursively in different network sections, rather than only in the layer before the final decision.

In summary, despite recent advances in expressing concepts in human-comprehensible ways, faithful and precise detection of the input regions influencing a model's decision-making remains a valuable yet underexplored challenge, as much of the recent focus has shifted toward concept definition and human understandability. Our method, as a novel local interpretation approach, focuses on faithful localization of these influential regions and, from this perspective, is comparable to both traditional raw-feature-based local interpreters and concept-based local interpretation methods.

6 Conclusion and Future Works

In this paper, we introduced a versatile framework for achieving more faithful local interpretations of deep neural networks by leveraging a novel definition: Distinguishing Clues (DCs). Our framework comprised a Complete System of DCs that identified input regions promoting each network output, a module named LAP that localized these clues, and a novel training scheme that enabled LAPs to learn from general problem knowledge without relying on expert annotations.

We assessed our framework in two key scenarios: training models from scratch and interpreting fully trained networks. In both cases, LAPs served dual roles: as external modules for post-hoc interpretation and as plugged-in modules providing intrinsic interpretability. Experiments across two challenging datasets, one being medical, demonstrated that our framework consistently outperformed well-known white-box explainers in faithfully detecting decision-influencing regions. LAPs further enabled insightful per-case and layer-wise diagnosis of models, while the performance of other interpreters significantly dropped when interpreting non-final convolutional layers. Moreover, incorporating LAPs during model training enhanced the model's interpretability, evident not only in LAP outputs but also in the quality of interpretations produced by other methods. To explore practical benefits, we extended LAP as an internal pooling module, resulting in improved average model performance when trained from scratch. When integrated into pretrained ImageNet

models and fine-tuned for few epochs, LAP showed clear improvements in 2 out of 3 tested architectures, with performance gains appearing to depend on the base architecture's optimization level and susceptibility to overfitting during fine-tuning. Since the core of this study focuses on presenting a local interpretation method, we confined ourselves to exploring LAP's performance enhancement to the provided level, leaving further exploration for future studies.

Integrating LAP directly into the model architecture represents a promising direction for future research. While we evaluated LAP-extended models and observed consistent performance improvements, more in-depth analysis is still required. In addition, future work could investigate dynamic, per-sample ratio adjustment strategies to further improve both performance and interpretability beyond the results reported in this study. Such approaches could eliminate the need to set fixed, loss-related hyperparameters prior to training. Additionally, amid the current surge of interest in large language models (LLMs) and vision–language models (VLMs), model interpretability remains a significant challenge. This work could be further extended and systematically compared against existing interpretability methods developed for these models.

References

Reduan Achtibat, Maximilian Dreyer, Ilona Eisenbraun, Sebastian Bosse, Thomas Wiegand, Wojciech Samek, and Sebastian Lapuschkin. From attribution maps to human-understandable explanations through concept relevance propagation. *Nature Machine Intelligence*, 5(9):1006–1019, 2023.

Yong Hyun Ahn, Hyeon Bae Kim, and Seong Tae Kim. Www: a unified framework for explaining what where and why of neural networks by interpretation of neuron concepts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10968–10977, 2024.

Ugochukwu Ejike Akpudo, Yongsheng Gao, Jun Zhou, and Andrew Lewis. Trance: Transformative nonlinear concept explainer for cnns. *IEEE Transactions on Neural Networks and Learning Systems*, 2025.

Christopher J Anders, Leander Weber, David Neumann, Wojciech Samek, Klaus-Robert Müller, and Sebastian Lapuschkin. Finding and removing clever hans: Using explanation methods to debug and improve deep models. *Information Fusion*, 77:261–295, 2022.

MD Anouk Stein, Carol Wu, Chris Carr, George Shih, Jamie Dulkowski, kalpathy, Leon Chen, Luciano Prevedello, MD Marc Kohli, Mark McDonald, Peter, Phil Culliton, Safwan Halabi MD, and Tian Xia. Rsna pneumonia detection challenge. `https://kaggle.com/competitions/rsna-pneumonia-detection-challenge`, 2018. Kaggle.

Jason Ansel, Edward Yang, Horace He, Natalia Gimelshein, Animesh Jain, Michael Voznesensky, Bin Bao, Peter Bell, David Berard, Evgeni Burovski, Geeta Chauhan, Anjali Chourdia, Will Constable, Alban Desmaison, Zachary DeVito, Elias Ellison, Will Feng, Jiong Gong, Michael Gschwind, Brian Hirsh, Sherlock Huang, Kshiteej Kalambarkar, Laurent Kirsch, Michael Lazos, Mario Lezcano, Yanbo Liang, Jason Liang, Yinghai Lu, CK Luk, Bert Maher, Yunjie Pan, Christian Puhrsch, Matthias Reso, Mark Saroufim, Marcos Yukio Siraichi, Helen Suk, Michael Suo, Phil Tillet, Eikan Wang, Xiaodong Wang, William Wen, Shunting Zhang, Xu Zhao, Keren Zhou, Richard Zou, Ajit Mathews, Gregory Chanan, Peng Wu, and Soumith Chintala. PyTorch 2: Faster Machine Learning Through Dynamic Python Bytecode Transformation and Graph Compilation. In *29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 2 (ASPLOS '24)*. ACM, April 2024. doi: 10.1145/3620665.3640366. URL `https://docs.pytorch.org/assets/pytorch2-2.pdf`.

Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus-Robert Müller, and Wojciech Samek. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10(7):e0130140, 2015.

Itay Benou and Tammy Riklin Raviv. Show and tell: Visually explainable deep neural nets via spatially-aware concept bottleneck models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 30063–30072, 2025.

Alexander Binder, Grégoire Montavon, Sebastian Lapuschkin, Klaus-Robert Müller, and Wojciech Samek. Layer-wise relevance propagation for neural networks with local renormalization layers. In *International conference on artificial neural networks*, pp. 63–71. Springer, 2016.

Rich Caruana, Yin Lou, Johannes Gehrke, Paul Koch, Marc Sturm, and Noemie Elhadad. Intelligible models for healthcare: Predicting pneumonia risk and hospital 30-day readmission. In *Proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1721–1730, 2015.

Chaofan Chen, Oscar Li, Chaofan Tao, Alina Barnett, Jonathan K Su, and Cynthia Rudin. This looks like that: deep learning for interpretable image recognition. *Advances in neural information processing systems*, 32, 2019.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. *Advances in neural information processing systems*, 29, 2016.

Mengnan Du, Ninghao Liu, and Xia Hu. Techniques for interpretable machine learning. *Communications of the ACM*, 63(1):68–77, 2019.

Thomas Fel, Agustin Picard, Louis Bethune, Thibaut Boissin, David Vigouroux, Julien Colin, Rémi Cadène, and Thomas Serre. Craft: Concept recursive activation factorization for explainability. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2711–2721, 2023.

FreeRangeStock. White cat [free stock photo]. `https://freerangestock.com/photos/124599/white-cat-.html`, n.d. Accessed: 2025-08-13.

Alex A Freitas. Comprehensible classification models: a position paper. *ACM SIGKDD explorations newsletter*, 15(1):1–10, 2014.

Ziteng Gao, Limin Wang, and Gangshan Wu. Lip: Local importance-based pooling. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3355–3364, 2019.

Amirata Ghorbani, James Wexler, James Y Zou, and Been Kim. Towards automatic concept-based explanations. *Advances in neural information processing systems*, 32, 2019.

Leilani H Gilpin, David Bau, Ben Z Yuan, Ayesha Bajwa, Michael Specter, and Lalana Kagal. Explaining explanations: An overview of interpretability of machine learning. In *2018 IEEE 5th International Conference on data science and advanced analytics (DSAA)*, pp. 80–89. IEEE, 2018.

Bryce Goodman and Seth Flaxman. European union regulations on algorithmic decision-making and a "right to explanation". *AI magazine*, 38(3):50–57, 2017.

Mara Graziani, Vincent Andrearczyk, and Henning Müller. Regression concept vectors for bidirectional explanations in histopathology. In *International Workshop on Machine Learning in Clinical Neuroimaging*, pp. 124–132. Springer, 2018.

Avani Gupta, Saurabh Saini, and PJ Narayanan. Concept distillation: leveraging human-centered explanations for model improvement. *Advances in Neural Information Processing Systems*, 36:63724–63737, 2023.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Ta Duc Huy, Sen Kim Tran, Phan Nguyen, Nguyen Hoang Tran, Tran Bao Sam, Anton van den Hengel, Zhibin Liao, Johan W Verjans, Minh-Son To, and Vu Minh Hieu Phan. Interactive medical image analysis with concept-based similarity reasoning. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 30797–30806, 2025.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International conference on machine learning*, pp. 2668–2677. PMLR, 2018.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 4015–4026, 2023.

Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In *International conference on machine learning*, pp. 5338–5348. PMLR, 2020.

Narine Kokhlikyan, Vivek Miglani, Miguel Martin, Edward Wang, Bilal Alsallakh, Jonathan Reynolds, Alexander Melnikov, Natalia Kliushkina, Carlos Araya, Siqi Yan, et al. Captum: A unified and generic model interpretability library for pytorch. *arXiv preprint arXiv:2009.07896*, 2020.

Matthew Kowal, Richard P Wildes, and Konstantinos G Derpanis. Visual concept connectome (vcc): Open world concept discovery and their interlayer connections in deep models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10895–10905, 2024.

Jeong Ryong Lee, Sewon Kim, Inyong Park, Taejoon Eo, and Dosik Hwang. Relevance-cam: Your model already knows where to look. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 14944–14953, 2021.

TorchVision maintainers and contributors. TorchVision: PyTorch's Computer Vision library, November 2016. URL https://github.com/pytorch/vision.

Tuomas Oikarinen and Tsui-Wei Weng. Clip-dissect: Automatic description of neuron representations in deep vision networks. *arXiv preprint arXiv:2204.10965*, 2022.

Mensah Kwabena Patrick, Adebayo Felix Adekoya, Ayidzoe Abra Mighty, and Baagyire Y Edward. Capsule networks–a survey. *Journal of King Saud University-computer and information sciences*, 34(1):1295–1310, 2022.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Vitali Petsiuk, Abir Das, and Kate Saenko. RISE: randomized input sampling for explanation of black-box models. In *British Machine Vision Conference 2018, BMVC 2018, Newcastle, UK, September 3-6, 2018*, pp. 151. BMVA Press, 2018. URL http://bmvc2018.org/contents/papers/1064.pdf.

Pexels. Person Holding Ferret [free stock photo]. https://www.pexels.com/photo/person-holding-ferret-5403275/, n.d. Accessed: 2025-08-13.

Pixnio. garden, grass, summer, land, soil, lawn, environment, leaf, nature, field [public domain image]. https://pixnio.com/nature-landscapes/grass/garden-grass-summer-land-soil-lawn-environment-leaf-nature-field, n.d. Accessed: 2025-08-13.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PmLR, 2021.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Gesina Schwalbe. Concept embedding analysis: A review. *arXiv preprint arXiv:2203.13909*, 2022.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *International conference on machine learning*, pp. 3145–3153. PMlR, 2017.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. *arXiv preprint arXiv:1312.6034*, 2013.

Leon Sixt, Maximilian Granz, and Tim Landgraf. When explanations lie: Why many modified bp attributions fail. In *International conference on machine learning*, pp. 9046–9057. PMLR, 2020.

Jost Tobias Springenberg, Alexey Dosovitskiy, Thomas Brox, and Martin Riedmiller. Striving for simplicity: The all convolutional net. *arXiv preprint arXiv:1412.6806*, 2014.

Ao Sun, Pingchuan Ma, Yuanyuan Yuan, and Shuai Wang. Explain any concept: Segment anything meets concept-based explanation. *Advances in Neural Information Processing Systems*, 36:21826–21840, 2023.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Timeless Moon. White Rabbit Sleeping [image]. `https://timelessmoon.getarchive.net/amp/media/rabbit-white-sleep-fcde83`, n.d. Accessed: 2025-08-13.

Erico Tjoa and Cuntai Guan. A survey on explainable artificial intelligence (xai): Toward medical xai. *IEEE transactions on neural networks and learning systems*, 32(11):4793–4813, 2020.

Andong Wang, Wei-Ning Lee, and Xiaojuan Qi. Hint: Hierarchical neuron concept explainer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10254–10264, 2022.

Bor-Shiun Wang, Chien-Yi Wang, and Wei-Chen Chiu. Mcpnet: An interpretable classifier via multi-level concept prototypes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10885–10894, 2024.

Bowen Wang, Liangzhi Li, Yuta Nakashima, and Hajime Nagahara. Learning bottleneck concepts in image classification. In *Proceedings of the ieee/cvf conference on computer vision and pattern recognition*, pp. 10962–10971, 2023.

Haofan Wang, Zifan Wang, Mengnan Du, Fan Yang, Zijian Zhang, Sirui Ding, Piotr Mardziel, and Xia Hu. Score-cam: Score-weighted visual explanations for convolutional neural networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, pp. 24–25, 2020.

Leander Weber, Sebastian Lapuschkin, Alexander Binder, and Wojciech Samek. Beyond explaining: Opportunities and challenges of xai-based model improvement. *Information Fusion*, 92:154–176, 2023.

Jianyang Zhang, Qianli Luo, Guowu Yang, Wenjing Yang, Weide Liu, Guosheng Lin, and Fengmao Lv. Attribute-formed class-specific concept space: Endowing language bottleneck model with better interpretability and scalability. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 30291–30300, 2025.

Quanshi Zhang, Ying Nian Wu, and Song-Chun Zhu. Interpretable convolutional neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8827–8836, 2018.

Ruihan Zhang, Prashan Madumal, Tim Miller, Krista A Ehinger, and Benjamin IP Rubinstein. Invertible concept-based explanations for cnn models with non-negative concept activation vectors. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 11682–11690, 2021.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2921–2929, 2016.

Zhijie Zhu, Lei Fan, Maurice Pagnucco, and Yang Song. Interpretable image classification via non-parametric part prototype learning. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 9762–9771, 2025.

A Appendix

A.1 Code Availability

The codes will be published as a Github repository upon acceptance. The codes are also uploaded with the main paper and supplementary material for the current submission. The codes, final trained models, training logs, and notebooks for running the codes are all available in this google drive . Notably, an anonymous account has been created for this end.

A.2 Summary of Terms

Tab. 4 provides a summary of the terms used throughout the paper alongside their definitions and roles.

Table 4: Terms, their definitions and roles.

Term	Meaning	Role
DC (Distinguishing Clue)	Minimal evidence region within input or intermediate feature maps that indicates a preference toward a particular subset of decisions over alternative options	Considered as probabilistic attribution maps of interpretation for the specified subset of decisions.
DC system	A set of DCs that collectively specify the regions within input or intermediate feature maps that promote each individual decision relative to all other possible decisions.	Providing interpretations in the form of probabilistic attribution maps for each individual decision.
LAP (Local Attention Perception)	A module that highlights the regions related to each DC for a target network layer	Produces importance maps for all DCs for the specified target layer.
LAP-Pool	Adopts LAP in the inner process of a pooling layer.	Leverages task-specific interpretations in the pooling operations.
LAP Supervision Loss	The loss used for training LAPs.	Training LAPs to automatically detect regions related to each DC without depending on expert annotations.
MinAR / MaxAR / IAR	Loss components of the LAP Supervision Loss that ensures coverage, precision, and exclusion respectively.	Training LAPs to precisely detect regions relevant to each DC in the samples that have the DC, while teaching it not to detect irrelevant regions in samples lacking the DC

A.3 The Difference Between LAP and Attention Mechanism

Unlike attention mechanisms, LAP does not apply a softmax function over the DC-wise importance maps for each sample. This design choice is motivated by the fact that the size of the affecting regions can vary substantially across samples. Applying a softmax over all DC-wise importance maps would assign lower per-pixel scores to large affecting regions compared to smaller ones, rendering the resulting scores incomparable in an absolute sense across different samples. This effect can be observed in Fig. 3. Indeed, all interpretation methods except LAP have produced binarized interpretation maps that highlight nearly the same number of pixels across cases, despite the fact that the expert-annotated affecting regions differ in size between samples.

From another perspective, LAP also does not apply a softmax function across different DCs at a single pixel location. A single pixel does not necessarily belong to only one DC; instead, a set of pixels collectively forms a DC within an image. For example, as shown in Fig. 4, pixels belonging to the yellow spaceship have incorporated into the spaceship DC, while some of those same pixels, due to their proximity to building windows, have also incorporated into the taxi DC.

Instead, LAP applies a sigmoid function independently to each DC at each pixel, estimating the probability that a given pixel is incorporated into a particular DC. This formulation yields probabilistic outputs with an absolute meaning, making the scores directly comparable across different samples.

A.4 Formal Equations of LAP-Pool

We adopt the unified pooling framework of Gao et al. (Gao et al., 2019) to formalize the LAP-Pool procedure in Eq. (6). $O_{a',b'}^l$ represents the output corresponding to a pooling sliding kernel of size $W_K \times H_K$ positioned with its top-left corner at (a, b), computed from the input feature map under the kernel $X_{a:a+H_K, b:b+W_K}^l$ and the weighting function $\mathscr{W}^l$. Here $\odot^*$ denotes element-wise multiplication with broadcasting, where the three-dimensional tensor $X_{a:a+H_K, b:b+W_K}^l$ is multiplied by the two-dimensional tensor $\mathscr{W}^l(X_{i:i+H_K, j:j+W_K})$.

$$
\begin{cases}
O_{a',b'}^l = \dfrac{\Sigma(\mathscr{W}^l(X_{a:a+H_K, b:b+W_K}^l) \odot^* X_{a:a+H_K, b:b+W_K}^l)}{\Sigma(\mathscr{W}^l(X_{a:a+H_K, b:b+W_K}^l))} \\
\mathscr{W}^l : \mathbb{R}^{F \times H_K \times W_K} \to R^{H_K \times W_K}
\end{cases}
\tag{6}
$$

In this work, $\mathscr{W}^l$ is composed of two steps: pixel-wise scoring, $\mathscr{S}^l$, and local kernel-wise normalization, $\mathscr{N}^l$, according to Eq. (7). Pixel-wise importance scores $(Q_{i,j}^l)$ are calculated by aggregating DC-wise importance probability maps (I_{ij}^l) using either a trainable or fixed function such as sum or max (denoted by $\mathscr{A}^l$). The aggregated scores within each pooling kernel region $(Q_{a:a+H_K, b:b+W_K}^l)$ are then normalized locally to produce the final pixel-wise weights. Any suitable local normalization method may be adopted here. In our case, we use a Gaussian kernel centered at the pixel with the highest local score, allowing sensitivity to the most highlighted pixel to be modulated via a trainable parameter α. When $\alpha = 0$, $\mathscr{N}(V) = 1 + \epsilon$, and as $\alpha \to \infty$, the coefficient of pixels other than $\max V$ approaches ϵ, and LAP conveys only the features of the most highlighted local pixel. A small constant ϵ is added to avoid zero weights, ensuring gradient flow across all pixels and preventing division by zero during weighted averaging in (Eq. (6)).

$$
\begin{cases}
\mathscr{W}^l(X_{a:a+H_K, b:b+W_K}^l) = \mathscr{N}^l(Q_{a:a+H_K, b:b+W_K}^l) \quad ; \quad Q_{i,j}^l = \mathscr{A}^l(I_{i,j}^l) \\
\mathscr{N}^l(Q_{a:a+H_K, b:b+W_K}^l)_{i,j} = e^{-\alpha^2(\max(\{Q_{a:a+H_K, b:b+W_K}^l\}) - Q_{i,j}^l)^2} + \epsilon \\
\mathscr{N}^l : \mathbb{R}^{H_K \times W_K} \to \mathbb{R}^{H_K \times W_K} \quad ; \quad \mathscr{A}^l : \mathbb{R}^M \to \mathbb{R}^1
\end{cases}
\tag{7}
$$

A.5 Integrating LAPs' scores to one unified interpretation map

LAPs can be considered a sequence of information through the depth of the network. Shallower LAPs cannot capture enough information due to their low receptive field. Therefore, they are likely to make more mistakes. Some pixels may have been assumed to be important but were found unimportant in the deeper layers and vice versa. However, they produce more detailed maps because of the low receptive field and high resolution. We devised an algorithm to integrate interpretations from the final LAP layers iteratively to the initial layers. In this way, we can have both accuracy and resolution. The procedure's pseudo-code is presented in Algorithm 1, in which α is the decay factor to adjust the impact of shallower LAPs. Iteratively, the algorithm modifies the current integrated map, R_{l+1}, with the current LAP attention map, P_l. Considering one pixel of R_{l+1}, $r_{l+1} \in \mathbb{R}$, and the set of its corresponding pixels in P_l, $p_l \in \mathbb{R}^{H_K \times W_K}$, if r_{l+1} is active, i.e., greater than 0.5, at least one pixel in the corresponding zone must have been responsible. If any pixel of the p_l is active, the credit only belongs to the active pixels. Otherwise, the current LAP does not comprehend the importance of this zone. Therefore, the credit belongs to all of them. Using this scheme, we prune the

produced importance map from the last LAP, which is expected to be the most accurate, to the first. When choosing the topK pixels based on the ground truth bounding box size, the scores have been added without being clipped to keep the order of scores below 0.5 and have a proper selection.

Algorithm 1 Pseudo-code for integrating the currently integrated map pixel on the position (i, j) from the L^{th} LAP to $l + 1^{\text{th}}$ LAP with l^{th} LAP attention map in the corresponding kernel. This procedure is repeated for each pixel of each LAP layer, from L to 1.

1: $\alpha \leftarrow 0.8$ $\triangleright$ the impact decay factor
2: $L \leftarrow$ The number of LAP layers
3: **procedure** INTEGRATEPIXEL$(R, P, l, i, j, H_K, W_K)$
4:     $p_l \leftarrow$ GETKERNEL(P_l, i, j, H_K, W_K) $\triangleright$ l^{th} LAP attention map for (i, j)'s corresponding kernel of size $H_K \times W_K$
5:     **if** $l = L$ **then**
6:        **return** p_l
7:     **end if**
8:     $r_{l+1} \leftarrow R_{l+1}[i, j]$ $\triangleright$ current integrated map pixel from L^{th} LAP to $l + 1^{\text{th}}$ LAP
9:     $r_l \leftarrow r_{l+1}$ repeated to size $H_K \times W_K$ $\triangleright$ The result integrated map
10:     **if** $r_{l+1} \geq 0.5$ & $\max\{p_l\} \geq 0.5$ **then**
11:        **for** $i' : [0, H_K)$ **do**
12:           **for** $j' : [0, W_K)$ **do**
13:              $p \leftarrow p_l[i', j'] \times \alpha^{L-l}$ $\triangleright$ Apply the decay factor
14:              **if** $p_l[i', j'] \geq 0.5$ **then**
15:                 $r_l[i', j'] \leftarrow \max\{r_{l+1}, p\}$
16:              **else**
17:                 $r_l[i', j'] \leftarrow p$
18:              **end if**
19:           **end for**
20:        **end for**
21:     **end if**
22:     **return** r_l
23: **end procedure**

A.6 Notes on Element Selection in LAP Supervision Loss

In the LAP supervision loss presented in Eq. (4), all three loss terms rely on selecting candidate elements based on their importance probabilities of the related DC ($I^{l,m}$). While it is possible to use the importance probabilities from a single LAP layer to train that same layer, our experiments show that aggregating importance probabilities across multiple LAP layers for ranking leads to more stable and accurate results.

We also observed that selecting the Top-K and Bot-K element sets based solely on the probabilities assigned by the DC head can be sensitive to the model's initial parameters, particularly when rankings are computed independently for each LAP layer. In such cases, LAP layers with large receptive fields often become biased toward incorrect regions of the input. To mitigate this issue, we introduced an auxiliary module, referred to as the *discriminative scoring module*, which shares the same architecture as the original scoring module. This module is used to determine the Top-K and Bot-K elements sets, based on the *sum of outputs from both scoring modules*. It is trained using the first and third terms of the LAP supervision loss from Eq. (4), with $K_{\text{MinAR}} = K_{\text{IAR}} = n_e$. To avoid injecting misleading gradients into the main model, especially since many input regions may be shared across different DCs, we detached the input to the discriminative scoring module during training.

A.7 Detailed Expert Knowledge Injection in LAP Supervision Loss

Human experts make their decisions based on specific features of the input. For example, jaggedness is one of the factors considered in classifying a tumor as malignant. Neural networks trained freely may or may not

capture all the relevant reasons behind their decisions. They may become biased toward a dominant feature in the training dataset and thus lose generalization. LAP provides an easy way to inject expert knowledge into the network due to the probabilistic behavior of its scoring module. Experts can highlight the important input regions for their decision-making for each DC. The highlighted maps can be resized to match each LAP's input size and used as ground truth to train the DC scoring heads. The proposed LAP supervision loss enables the use of expert annotations instead of bootstrapped labels in the weak supervision process. For this end, in Eq. (5), in the $L_{\text{LS}_{l,m}}^{\text{MinAR}}$, and $L_{\text{LS}_{l,m}}^{\text{MaxAR}}$ loss terms, the exact positive and negative elements annotated by expert can be used instead of Top-$\text{K}_{\text{MinAR}}(I^{l,m})$ and Bot-$\text{K}_{\text{MaxAR}}(I^{l,m})$ respectively. The third term should be kept the same to keep the balance but in this scenario K_{IAR} can also be set equal to the average size of DC annotated by expert in all DC-positive cases. The altered loss terms are calculated as follows. Let $\hat{A}^{l,m}$ denote the binary expert annotation map, resized to the input size of the l-th LAP for the m-th DC. We define $\text{Pos}(\hat{A}^{l,m})$ as the set of pixels labeled 1, $\text{Neg}(\hat{A}^{l,m})$ as the set of pixels labeled 0, n_e as the total number of elements in X^l, and n_m^+ as the total number of DC-present samples for the m-th DC. Using these definitions, the corresponding loss terms are:

$$L_{\text{LS}_{l,m}}^{\text{MinAR}}(X^l, y, \hat{A}^{l,m}) = \frac{-2}{|\text{Pos}(\hat{A}^{l,m})|} \times \sum_{i \in \text{Pos}(\hat{A}^{l,m})} \ln(I_i^{l,m})$$

$$L_{\text{LS}_{l,m}}^{\text{MaxAR}}(X^l, y, \hat{A}^{l,m}) = \frac{-1}{|\text{Neg}(\hat{A}^{l,m})|} \times \sum_{i \in \text{Neg}(\hat{A}^{l,m})} \ln(1 - I_i^{l,m}) \tag{8}$$

$$L_{\text{LS}_{l,m}}^{\text{IAR}}(X^l, y) = \frac{-1}{K_{\text{IAR}}} \times \sum_{i \in \text{Top-K}_{\text{IAR}}^{l,m}} \ln(1 - I_i^{l,m}) \quad ; \quad K_{\text{IAR}} = \lceil \frac{\sum_{(X^l, y, \hat{A}^{l,m}) : y \in Y^{\text{dc}+}_m} |\text{Pos}(\hat{A}^{l,m})|}{n_m^+} \times n_e^l \rceil$$

A.8 Inter-LAP Concordance Loss Term for Inter-Layer Knowledge Sharing

Intuitively, if one LAP layer detects a DC in a part of the input, subsequent layers should detect it as well. To encourage this, we optionally apply the Jensen-Shannon divergence loss, defined in Eq. (9), on the importance probability maps of the m-th DC for two consecutive LAPs, l and $l + 1$, for a single sample (X, y). Here, $\mathcal{JS}(I^{l,m}, R(I^{l+1,m}))$ denotes the Jensen-Shannon divergence loss for importance probability maps $I^{l,m}$, and the resized $I^{l+1,m}$ (resized via binary interpolation to match the dimensions of $I^{l,m}$). In this equation n_e denotes the total number of elements in the largest map. This loss encourages consecutive LAP layers to reinforce each other's detection of clues and is applied to every pair of consecutive layers in our experiments.

$$\mathcal{JS}(I^{l,m}, R(I^{l+1,m})) = \frac{1}{2n_e} \sum_{(i)} \left[(I_i^{l,m} - R(I_i^{l+1,m})) \ln \frac{I_i^{l,m}}{R(I_i^{l+1,m})} + (R(I_i^{l+1,m}) - I_i^{l,m}) \ln \frac{1 - I_i^{l,m}}{1 - R(I_i^{l+1,m})} \right] \tag{9}$$

A.9 Experiments Setup

The main goal of this study is to propose a practical interpretation method that is generally applicable to all neural networks, including those that have already been trained. Notably, other published papers in the literature on general interpretation methods have mostly assessed their proposed method on the whole version or a part of the ImageNet dataset using architectures like ResNet (Fel et al., 2023; Achtibat et al., 2023; Lee et al., 2021; Ghorbani et al., 2019; Selvaraju et al., 2017). Following the literature, we conducted the experiments using two well-known and widely used architectures, ResNet and InceptionV3. While both architectures have high performance, they have different core ideas. ResNet is famous for its residual connections that prepare uninterrupted gradient paths to prevent gradient fading. Inception-V3 is known for its multi-resolution analysis, which applies kernels of different sizes to the feature map at each network level. These differences shed more light on the performance of different interpretation methods.

ImageNet was adopted as a widely used dataset for the choice of dataset in assessing interpretation methods. Besides ImageNet, as the medical domain proposes challenges that do not exist in object detection datasets, we also adopted the RSNA Pneumonia Detection dataset in a binary classification task to assess the general applicability of local interpretation methods.

As mentioned in the main text, the interpretation method has been compared with five widely used white-box local interpretation methods, and two recent concept-based local interpretation methods. We have not compared the interpretation method with methods not applicable to all CNNs in general (e.g., the methods developed for the transformers), the ones not applicable to already trained models (e.g., self-interpretation methods that alter the architecture), the ones that have not provided an algorithm for a unified interpretation (e. g. LIP (Gao et al., 2019)), the global interpretation methods that have not compared their results with any local method (e.g. (Ghorbani et al., 2019; Zhang et al., 2021)), and the methods that depend on other explainers we have compared our results with (e.g., HINT (Wang et al., 2022)). Also, the human-centered interpretation methods are set aside as they need a human for the task.

A.9.1   The choice of evaluation method for assessing interpretations

Various evaluation metrics have been utilized in different studies to evaluate interpretation methods. Each has advantages and disadvantages, making each more appropriate for specific domains. In this study, we have employed two distinct evaluation methods for our two datasets based on the nature of their domain.

RSNA pneumonia detection

For the RSNA dataset, the input images are X-rays of the entire chest, and different parts of the image find different meanings based on their surroundings. In this sense, the domain differs from an object recognition dataset, where individuals can comprehend the object from its parts. Therefore, evaluation methods that involve removing parts of the image may influence the model's decision-making process due to producing out-of-distribution images. Methods like blurring may also result in artifacts that resemble pneumonia. Alternatively, the interpretation methods are expected to capture the most distinguishing parts between images that belong to different categories. All pneumonia regions are, in fact, the distinguishing parts. We have used the "object localization" (Lee et al., 2021) to evaluate the interpretation methods. To this end, the Intersection over Union (IoU) metric was calculated between the interpretation maps and the bounding boxes provided by experts for pneumonia in true positive cases.

ImageNet

Unlike the RSNA dataset, in which the images of the two classes were only different in "pneumonia regions," the ImageNet dataset has 1000 classes, some of which are highly similar and only differ in small details, like different classes of dogs. Therefore, the interpretation methods are not expected to highlight the whole object as a distinguishing decision reason. So, IoU cannot be a good representative of performance.

A.10   Training configurations

A.10.1   A General Guide for Selecting Hyper-parameters of LAP Supervision Loss

In the training method described in Sec. 2.3, three hyper-parameters are involved: γ^{MinAR}, γ^{MaxAR}, and γ^{IAR}. There are two main approaches for setting these hyper-parameters:

1. **Using domain knowledge:** If the approximate range of sizes for Distinguishing Clues (DCs) is known, this information can guide the setting of γ^{MinAR} and γ^{MaxAR}. It is recommended to set γ^{MinAR} based on the median size of the DCs, and γ^{MaxAR} based on the maximum expected size. For γ^{IAR}, it is preferable to set it equal to γ^{MinAR} to ensure that the contribution of each element in the IAR loss term is balanced with that of the MinAR term.

2. **Empirical tuning:** Similar to typical hyperparameter tuning, one can define a candidate set of values, train LAPs using each configuration, and select the one that yields the highest faithfulness on validation data. Again, it is recommended to set $\gamma^{\text{IAR}} = \gamma^{\text{MinAR}}$ to maintain balance in the loss

terms. For this purpose, a method similar to the one used for assessing faithfulness on the ImageNet dataset (Sec. 3.2) can be applied.

A.10.2 RSNA

The RSNA pneumonia detection dataset contains chest X-ray images of 8851 healthy people and 6012 patients with lung pneumonia. We randomly selected 81% of the data for training, 9% for validation, and 10%

For weak supervision, we used cross-entropy loss on the classification head, LAP supervision loss, and inter-LAPs concordance loss with weights of 1, 10 per LAP, and 1 per LAP pair, respectively. The weights of LAP supervision losses were set to 10 as we observed fast over-fitting of the main classifier compared to the LAP modules on the validation dataset.

We used $\gamma^{\mathrm{MinAR}} = 0.1, \gamma^{\mathrm{MaxAR}} = 0.5, \gamma^{\mathrm{IAR}} = 0.1$ as the hyper-parameter values of the LAP supervision loss. The first two were set based on the possible range of DC sizes, i.e., infection, in the positive samples. We chose the median and maximum of the infection bounding boxes as the mentioned bounds. The third was set to 0.1 to keep the balance between the element-wise loss factor of IAR and MinAR. For full supervision, we used cross-entropy loss on the classification head alongside cross-entropy loss on LAPs. We considered experts' bounding boxes as the ground truth with the same weights for LAP modules as in the weak supervision.

We trained the models for 200 epochs and stopped the runs if no progress was achieved on the validation data for 100 consecutive epochs. We selected the model related to the epoch with the best performance on validation data as the final model. We used balanced batches of size 64 (32 healthy and 32 pneumonia samples) and the ADAM optimizer with an initial learning rate of 10^{-4} and a decay coefficient of 10^{-6} in training. The models were trained using the Pytorch framework on a GEFORCE RTX 2080 Ti GPU.

A.10.3 ImageNet

For the ImageNet dataset, 3 different architectures were adopted: ResNet50, InceptionV3, and EfficientNetB0. Since the objects in the ImageNet dataset have variable sizes and many are as large as half the image, only two LAPs were used in the architectures — one replacing the final adaptive pool and the other replacing the last non-adaptive pooling or strided convolution. For training LAPs, we incorporated our proposed weakly supervised loss — comprising γ^{MinAR} and γ^{IAR} both set to 0.1, and excluding MaxAR — weighted by a factor of 0.1 alongside the primary cross-entropy loss. The γ^{MinAR} hyper-parameter was selected from the set [0.01, 0.1, 0.4] based on validation data, and as described in Sec. A.10.1, γ^{IAR} was set equal to it. The models were trained using a learning rate of 10^{-4} and a weight decay coefficient of 10^{-6}, a batch size of 1000, and the simple augmentation of resize and crop. Training was conducted in PyTorch on an Nvidia Quadro RTX 8000 GPU.The details of training for LAP-extended versions that provide intrinsic interpretability and detached LAPs (DLAP) that provide post-hoc interpretability for the original models are expressed as follows:

- **DLAP-ResNet50:** Detached LAPs were trained for one epoch.

- **LAP-ResNet50:** One LAP-Pool replaced the strided convolution in Layer4, feeding the output of Layer3, and another LAP-Pool replaced the final adaptive-pool. The architecture from Layer 4 and all layers after that were tuned for 10 epochs.

- **DLAP-Inception3:** Detached LAPs were trained for 5 epochs.

- **LAP-InceptionV3:** For this architecture, a LAP-Pool replaced the final adaptive pool and the LAP in the middle layer was used in the detached mode over the outputs of Mixed7a layer as the original InceptionV3 model was heavily overtrained and tuning large parts of it resulted in degraded performance. The altered model was initialized with the original InceptionV3 weights, and the trained detached LAPs from DLAP-InceptionV3. The replaced pool and all layers after it were tuned for 3 epochs.

- **DLAP-EfficientNetB0:** Detached LAPs were trained for 5 epochs.

- **LAP-EfficientNetB0:** Same as LAP-InceptionV3, for this architecture, a LAP-Pool replaced the final adaptive pool and the LAP in the middle layer was used in the detached mode over the outputs of layer6.0 as the original EfficientNetB0 model was heavily overtrained and tuning large parts of it resulted in degraded performance. The altered model was initialized with the original EfficientNetB0 weights, and the trained detached LAPs from DLAP-EfficientNetB0. The replaced pool and all layers after it were tuned for 3 epochs.

A.11 Further Results on RSNA Pneumonia Detection

A.11.1 RSNA Pneumonia Detection Full Performance Evaluation Metrics

We evaluated the performance of the models using five metrics: accuracy, sensitivity, specificity, Balanced Accuracy (BA), and F1-score. Sensitivity and specificity are recalls of positive and negative classes that are widely used in medical domains. BA is their average, which provides a fair metric for imbalanced datasets. The results are presented in Tab. 5.It is observed that using LAP-supervision loss terms has enhanced sensitivity while, as a trade-off, degrading specificity. This suggests that the loss has encouraged the models to detect more evidence associated with the positive class, at the cost of increased false positives in some cases. Nevertheless, when considering fair single metrics for imbalanced datasets, such as F1-score and balanced accuracy, LAP-extension has resulted in an overall improvement in average performance.

Table 5: Performance metrics on RSNA Pneumonia Classification task. We evaluated accuracy, sensitivity, specificity, balanced accuracy, and F1-score for the vanilla ResNet18 (RN) and Inception3 (I3) models, BotCL-extended models (BCL-), LAP-extended models trained using the proposed weak supervision (WSL-), and LAP-extended models trained using expert annotations (BBL-). LAP-extended variants have achieved higher mean performances compared to the vanilla ones. All values are reported as mean ± standard deviation over five independently trained models initialized with different random seeds.

Model	Accuracy	Sensitivity	Specificity	Balanced Accuracy	F1
Org ResNet 18	94.5±0.24	93.63±0.95	95.42±0.67	94.52±0.25	94.58±0.27
BCL-RN	94.72±0.26	93.69±0.29	**95.80**±0.31	94.74±0.26	94.79±0.26
WSL-RN	94.73±0.26	**95.11**±0.73	94.34±1.11	94.72±0.27	94.88±0.22
BBL-RN	**94.84**±0.19	94.12±1.44	95.6±1.56	**94.86**±0.2	**94.92**±0.19
Inception V3	95.1±0.4	93.71±0.82	**96.57**±0.33	95.14±0.39	95.15±0.41
BCL-I3	95.15±0.27	94.29±0.54	96.05±0.85	95.17±0.28	95.22±0.25
WSL-I3	95.22±0.18	93.97±0.42	96.55±0.27	**95.25**±0.17	95.28±0.19
BBL-I3	**95.25**±0.21	**94.33**±1.22	96.21±1.1	95.21±0.3	**95.32**±0.24

A.11.2 Different Choices of Binarization Approaches for Interpretation Score Maps

Binarized interpretation score maps provide a common sense for the important regions in decision-making. Labeling a region as important or not is crucial in vital applications like medical diagnosis for validating the model's decision. For example, in breast cancer classification, regions highlighted as important will be analyzed in further medical diagnosis. Therefore, the region of extension and multi-focal importance detection are important in this field. Accordingly, in pneumonia detection, we focused on assessing the order of importance provided by interpretation maps and binarized interpretation maps.

Various binarization approaches have been adopted in the literature, from selecting a fixed portion, e.g., 15% of the top-scored pixels (Selvaraju et al., 2017), to adopting a threshold of mean + standard deviation ("$\mu + \sigma$") over the individual interpretation scores maps (Lee et al., 2021). We utilized three different approaches to assess interpretations from different points of view. The results for the adoption of "$\mu + \sigma$" as threshold were presented in the main text (Tab. 2). Focusing on the other two approaches, in the first method, following the option of the fixed portion of highly scored pixels, rather than using a fixed percentage for all images, the number of pneumonia pixels known from the expert bounding boxes was used for each image (**Binarization by Top-Scored Selection**). We believe this results in a more fair comparison as the images in the dataset

are highly diverse in the size of their pneumonia bounding boxes. The results are presented in Tab. 6. It is observed that LAP has achieved significantly higher performance than the other methods in all models. (p-value ≤ 0.001 using a paired t-test for original architectures and WS variants. BBs are excluded to provide a more fair results.)

Although binarization by Top-Scored Selection allows for a fair comparison of the order of scores by considering the size of the distinguishing area, the information is not known in test-time interpretation. Therefore, we also adopted a global thresholding method for binarization to assess the interpretation maps (**Binarization by Thresholding**). Notably, LAPs inherently provide a classification over the distinguishing pixels. We first normalized each importance map by its maximum value to find a global threshold for other interpretation methods. Then, we created a dataset from the normalized pixel-wise interpretation scores over the validation samples. We assigned the positive label to all the pixels under the experts' annotated boxes and the negative to the others. We used RidgeClassifier of sklearn (Pedregosa et al., 2011) to classify the pixels. We also used balanced weighting to address the issue with the highly imbalanced dataset. We used the point with the prediction label equal to zero as the threshold for binarization. We applied this method for each trained model separately and used the resulting threshold to evaluate the model's interpretations. The results are presented in Tab. 7. Like the other methods, LAPs lead to significantly higher IoU scores than the other methods. (p-value ≤ 0.001 using a paired t-test for original architectures and WS variants. BBs are excluded to provide a more fair results.)

Table 6: Assessment of binarized interpretation maps using the "Binarization by TopK Selection" approach for the vanilla models of ResNet18 and Inception3, BotCL-extended models (BCL-), LAP-extended models trained by the proposed weak supervision (WSL-), and expert annotations (BBL-). While LAP-extension has enhanced the models' interpretability, LAP provides significantly better interpretations compared to the other interpretation methods across all of the models. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

	IoU Between Expert Annotations and Binarized Interpretation Maps (TopK Selection)							
Model	DL	GGC	GC	GBP	RC	CR	BotCL	LAP
ResNet18	19.69±0.98	19.56±1.35	27.17±1.95	16.74±1.24	9.86±1.37	27.77±2.07	NA	**33.70**±3.48
BCL-RN	21.77±1.08	17.12±2.58	20.76±2.60	20.84±1.17	25.02±5.02	24.42±4.35	22.70±3.71	**26.72**±2.66
WSL-RN	22.40±0.61	21.80±0.84	18.37±1.95	21.54±0.66	41.35±1.22	39.42±3.41	NA	**41.96**±1.43
BBL-RN	22.60±0.78	24.08±0.86	24.70±4.83	23.03±1.27	31.02±4.66	43.74±4.66	NA	**55.95**±1.46
Inception V3	23.42±0.33	24.09±1.60	32.69±1.24	22.30±1.23	33.96±1.42	32.14±1.83	NA	**43.34**±1.48
BCL-I3	22.69±0.85	18.32±8.33	8.13±5.81	23.56±1.32	13.39±4.42	5.88±6.27	5.17±2.50	**26.93**±9.42
WSL-I3	22.90±0.17	14.55±2.91	8.80±2.18	14.71±3.24	**41.30**±0.70	40.81±0.88	NA	39.06±0.84
BBL-I3	24.12±0.50	19.11±3.40	25.35±3.88	18.03±3.22	45.88±0.66	38.85±5.38	NA	**55.72**±0.48

Table 7: Assessment of binarized interpretation maps using the "Binarization by Thresholding" approach for the vanilla models of ResNet18 and Inception3, BotCL-extended models (BCL-), LAP-extended models trained by the proposed weak supervision (WSL-), and expert annotations (BBL-). While LAP-extension has enhanced the models' interpretability, LAP provides significantly better interpretations compared to the other interpretation methods across all of the models. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

	IoU Between Expert Annotations and Binarized Interpretation Maps (Learned Threshold)							
Model	DL	GGC	GC	GBP	RC	CR	BotCL	LAP
ResNet18	16.37±0.77	16.28±1.05	21.62±1.94	13.89±0.90	11.75±0.64	24.55±1.38	NA	**31.37**±2.79
BCL-RN	17.89±1.31	13.65±1.90	18.33±2.34	16.36±1.12	19.91±3.14	21.41±3.68	20.28±2.92	**25.01**±2.48
WSL-RN	18.91±0.56	18.45±0.82	17.40±1.45	18.44±0.71	34.91±0.97	32.82±3.55	NA	**36.28**±1.19
BBL-RN	19.02±0.80	20.57±0.65	18.54±1.05	19.76±1.03	24.93±2.44	31.91±8.25	NA	**43.26**±1.51
Inception V3	19.26±0.40	16.99±1.38	25.49±1.46	16.60±1.23	27.05±1.49	25.55±0.69	NA	**29.52**±0.93
BCL-I3	18.47±0.84	12.69±5.50	8.79±5.19	16.70±1.30	16.05±2.40	4.10±5.41	3.06±1.46	**24.40**±2.05
WSL-I3	19.32±0.26	12.47±1.82	8.65±1.08	12.84±2.22	32.60±0.98	33.60±1.57	NA	**35.75**±0.62
BBL-I3	20.49±0.55	15.30±2.29	17.03±4.08	14.93±2.28	35.05±2.37	26.40±5.36	NA	**41.46**±1.87

A.11.3 Other metrics for assessing interpretations on RSNA

To provide a more comprehensive assessment of interpretation maps for the RSNA dataset, we have adopted two additional metrics alongside the standard IoU calculation with expert bounding boxes. Given that bounding boxes are inherently rectangular and may not perfectly align with the actual infected area, more flexible evaluation metrics may help in shedding light on the performance of interpretation methods. In this regard, the sensitivity of bounding box capturing and truncated IoU were adopted as complementary metrics. For sensitivity, we have considered a bounding box 'captured' if at least half of it is covered by the binarized interpretation map, reporting the percentage of captured boxes relative to the total. The truncated IoU only includes half of each bounding box containing the highest-scored pixels detected by each method in calculating IoU, ensuring that a hypothetical perfect method would achieve an IoU score greater than or equal to any imperfect method. Both metrics utilize either binarized maps generated using the dynamic threshold of $\mu + \sigma$ or the automatically learned threshold closest to the ground truth map. Results presented in Tab. 8 and Tab. 9 demonstrate that LAP outperforms all other methods across both metrics, showcasing its superiority from multiple perspectives.

Table 8: Assessment of the sensitivity of the interpretation methods regarding capturing expert bounding boxes for the vanilla models of ResNet18 and Inception3, BotCL-extended models (BCL-), LAP-extended models trained by the proposed weak supervision (WSL-), and expert annotations (BBL-). While LAP-extension has enhanced the models' interpretability, LAP provides significantly better interpretations compared to the other interpretation methods across all of the models. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

| Model | Sensitivity of Capturing Expert Bounding Boxes | | | | | | | |
	DL	GGC	GC	GBP	RC	CR	BotCL	LAP
ResNet18	0.06±0.10	0.05±0.06	46.75±4.17	0.00±0.00	9.12±2.68	48.43±4.49	NA	**57.82±6.12**
BCL-RN	0.12±0.14	0.76±0.42	32.33±3.96	0.29±0.21	36.10±8.95	31.27±9.77	29.67±7.51	**41.66±6.98**
WSL-RN	0.01±0.03	0.09±0.09	24.16±4.10	0.13±0.17	76.56±4.17	75.76±4.20	NA	**79.43±7.89**
BBL-RN	0.03±0.03	0.16±0.16	36.16±12.85	0.04±0.05	52.06±8.03	71.81±4.79	NA	**74.36±2.32**
Inception V3	0.00±0.00	0.06±0.13	58.37±2.71	0.01±0.03	60.30±3.78	55.43±1.67	NA	**79.40±3.35**
BCL-I3	0.00±0.00	0.01±0.03	4.88±7.13	0.03±0.05	15.07±12.50	8.11±12.81	0.85±0.94	**47.74±16.90**
WSL-I3	0.00±0.00	0.00±0.00	13.67±4.17	0.00±0.00	72.49±2.63	69.48±2.51	NA	**78.57±3.33**
BBL-I3	0.00±0.00	0.00±0.00	43.82±10.11	0.00±0.00	70.77±4.63	59.31±6.37	NA	**73.66±2.23**

Table 9: Assessment of the interpretation methods by calculating truncated IoU for the vanilla models of ResNet18 and Inception3, BotCL-extended models (BCL-), LAP-extended models trained by the proposed weak supervision (WSL-), and expert annotations (BBL-). While LAP-extension has enhanced the models' interpretability, LAP provides significantly better interpretations compared to the other interpretation methods across all of the models. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

| Model | Truncated IoU Between Expert Annotations and Binarized Interpretation Maps (Best Thresholding) | | | | | | | |
	DL	GGC	GC	GBP	RC	CR	BotCL	LAP
ResNet18	14.20±0.89	10.86±1.54	24.97±1.98	8.70±1.36	7.34±1.39	26.60±1.74	NA	**35.04±4.02**
BCL-RN	15.32±1.53	10.08±1.61	19.45±2.38	11.53±1.09	22.18±5.29	21.34±5.09	19.94±3.90	**26.38±3.32**
WSL-RN	16.55±0.68	13.95±0.82	15.83±2.02	14.10±0.75	41.19±1.57	39.32±3.18	NA	**41.59±1.63**
BBL-RN	17.05±0.89	16.75±0.79	21.40±5.32	15.63±1.14	29.18±4.95	41.04±4.98	NA	**56.70±1.62**
Inception V3	16.18±0.49	13.66±1.76	29.83±1.60	12.21±1.67	31.96±1.69	30.16±1.24	NA	**40.55±1.59**
BCL-I3	15.15±0.87	9.72±4.50	3.79±3.57	13.15±1.56	9.57±4.85	4.09±5.91	1.90±1.16	**26.13±8.16**
WSL-I3	16.32±0.36	7.82±1.48	8.35±2.38	8.40±1.99	39.39±1.29	38.95±1.64	NA	**40.94±0.90**
BBL-I3	18.08±0.55	11.41±2.64	23.82±4.49	10.48±2.57	43.09±1.80	36.51±3.85	NA	**56.76±0.55**

A.11.4 Ablation Study on the Hyper-parameters of the LAP Supervision Loss

We conducted another ablation study on the RSNA dataset using the ResNet-18 network to assess the effect of different values for the hyperparameters in the LAP-supervision loss function (Eq. (4)). The results are presented in Tab. 10. In eight settings, the network was trained with different values of γ^{MinAR}, γ^{MaxAR}, and γ^{IAR}. The settings were named as triplets of $[\gamma^{\text{MinAR}}][\gamma^{\text{MaxAR}}][\gamma^{\text{IAR}}]$, where O stands for the default

value, *L* for a much lower value, and *H* for a much higher value. The values of the hyperparameters are presented in Tab. 11. It was observed that the proposed setting, based on general domain knowledge according to Sec. A.10.2, outperformed the others in terms of both task-specific performance metrics and interpretation-based metrics. Compared to the classification performance of the base ResNet-18 architecture presented in Tab. 1, all settings achieved a higher average F1-score. Among the settings, three had lower F1-scores compared to the others: LOO, OHO, and HHH. It appears that using a much higher value for γ^{MinAR} has the largest negative effect on task-specific performance. Additionally, using a much lower value for γ^{MinAR} is also detrimental, as observed in the Naive weak-supervision V1 setting in Tab. 3.

Focusing on the IoU of binarized interpretation maps, four settings exhibited drastically lower IoU after thresholding compared to the others: LOO, LLL, HOO, and HHH. It was observed that interpretability is primarily sensitive to a single hyperparameter: γ^{MinAR}. Using either a much higher or much lower value for γ^{MinAR} results in a noticeable decrease in the IoU of the binarized interpretation score maps when self-thresholding is applied. This occurs because the chosen value represents the expected size of the distinguishing part, which allows the network to explore an appropriate portion of the image. A much higher value forces the network to select irrelevant pixels as distinguishing parts, deteriorating the gradient flow, while a much lower value prevents the network from exploring all distinguishing parts, causing it to focus only on highly distinctive pixels and reducing generalization. This experiment demonstrates that hyperparameters can be selected using the method described in Sec. A.10.2, without the need to try numerous values. Notably, all configurations except the ones mentioned above achieve substantially higher IoU compared to other interpretation methods (Tab. 2).

Table 10: Task-specific performance metrics and IoUs of infection bounding boxes of RSNA and binarized interpretation maps of the LAP ResNet 18 network trained with different configurations using two binarization approaches, thresholding and TopK selection by ground truth. Configurations are presented as triplets of $[\gamma^{\mathrm{MinAR}}][\gamma^{\mathrm{MaxAR}}][\gamma^{\mathrm{IAR}}]$, in which *O* stands for the default value, *L* for a lower value, and *H* for a higher one. The selected configuration based on the general domain-specific knowledge has resulted in both high task-specific performance metrics and interpretation metrics. All values are reported as mean ± standard deviation over five independently trained models initialized with different random seeds.

Training Configuration	Performance Metrics					IoU	
	Accuracy	Sensitivity	Specificity	B Acuuracy	f1	Thresholding	TopK
Proposed	94.73±0.26	**95.11**±0.73	94.34±1.11	94.72±0.27	94.88±0.22	36.28±1.19	41.96±1.43
LOO	94.46±0.21	94.68±1.01	94.24±0.83	94.46±0.2	94.61±0.23	25.82±0.82	39.49±1.4
OLO	94.73±0.27	93.61±0.42	**95.91**±0.76	94.76±0.29	94.8±0.26	36.08±0.65	42.19±1.23
OOL	**94.86**±0.31	94.1±0.52	95.66±0.32	**94.88**±0.3	94.94±0.31	36.16±2.99	43.15±3.48
LLL	94.75±0.29	94.25±0.79	95.28±0.81	94.76±0.29	94.85±0.29	24.32±2.47	42.15±0.78
HOO	94.73±0.15	94.44±0.32	95.03±0.55	94.74±0.16	94.84±0.13	26.05±0.5	39.21±3.32
OHO	94.57±0.26	94.61±0.62	94.51±0.7	94.56±0.26	94.69±0.25	**36.64**±1.67	**43.49**±2.25
OOH	94.85±0.27	94.51±0.32	95.21±0.3	94.86±0.27	**94.95**±0.26	35.63±3.35	41.38±3.96
HHH	94.49±0.31	93.93±0.75	95.08±1.2	94.5±0.33	94.59±0.27	20.58±1.13	34.42±0.91

Table 11: The values used for γ^{MinAR}, γ^{MaxAR}, and γ^{IAR} hyper-parameters in the ablation study of RSNA.

Type	O	L	H
γ^{MinAR}	0.1	0.01	0.5
γ^{MaxAR}	0.5	0.1	0.9
γ^{IAR}	0.1	0.01	0.5

A.11.5 Assessing the Effect of Aggregation in Interpretation

As mentioned in the main text, LAPs can be used separately to present a sectional interpretation for the network. The deeper the LAP, the closer and more representative to the final decider, but with a lower resolution that makes the exact locating of the distinguishing DCs difficult. As discussed in Sec. 2.2 and Sec. A.5, we adopted the hierarchical relations of LAPs to provide an aggregated interpretation score map that has benefited from the high resolutions of the shallower LAPs to enhance the interpretations of the deeper

LAP. To assess the sectional interpretations provided by different LAPs, the IoU between the thresholded interpretation score maps and the ground truth expert bounding boxes are calculated according to Tab. 12. The metric was also calculated for the aggregations of LAPs (Aggregated), which is the metric used all over the paper. Notably, the metric achieved by two LAPs in two different sections might represent the ability of the network to detect the exact location of infected zones, i.e. the distinguishing regions, in different depths. Therefore, we cannot compare the metric achieved by an aggregation with an LAP different from the aggregation's last layer. The metrics reported in the table indicate the ultimate suffering of the deepest LAP, i.e. LAP4, from the low resolution. It can be observed that using the aggregation has resulted in a great enhancement for LAP4 in all of the architectures. Additionally, in the proposed training scheme, with no expert supervision included, using the aggregation has resulted in the best DC locating compared to the isolated LAPs.

Table 12: IoU between the binarized interpretation score maps based on thresholding for LAPs in different sections of the original architectures, LAP-extended architectures trained with the proposed weakly supervised method (WSL), and LAP-extended architectures trained with the infection bounding boxes annotated by experts (BBL). The results for the aggregated interpretation score maps are also presented as Aggregated. Comparing Aggregated, which is the one used in all comparisons in this paper, with LAP4, it can be observed that aggregation has enhanced the IoU scores by adopting the resolution of the previous layers. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

Model	LAP1	LAP2	LAP3	LAP4	Aggregated
ResNet 18	24.63±2.60	29.43±2.70	**32.18**±1.64	25.22±0.36	31.37±2.79
Inception V3	26.56±0.49	**36.16**±1.10	25.40±0.65	24.74±0.69	29.52±0.93
WSL ResNet	34.92±2.04	36.14±0.98	33.37±1.36	25.47±1.69	**36.28**±1.19
WSL Inception	29.30±0.90	35.64±0.62	33.42±0.46	25.82±0.34	**35.75**±0.62
BBL ResNet	40.01±1.91	**46.11**±1.07	45.44±1.14	39.96±0.46	43.26±1.51
BBL Inception	28.52±1.58	**47.64**±1.14	44.13±1.84	40.65±0.98	41.46±1.87

A.12 Further Results on ImageNet Object Classification

A.12.1 Comparing faithfulness of the interpretation methods on ImageNet with respect to the predicted label

We compared the faithfulness of different interpretation methods on each model by modifying the input images based on the interpretation scores. Faithfulness was evaluated by keeping $k\%$ pixels with the highest scores provided by the interpretation method, zeroing out the rest of the image, and then passing the modified image through the network for re-evaluation. The results are presented in Fig. 6 for percentages of 10%, 30%, 50%, 70%, and 90% across six model variants: LAP-Extended and Original versions of ResNet50, InceptionV3, and EfficientNetB0 [3]. In this experiment, the interpretation scores were calculated based on the predicted class, and the results were also evaluated with respect to the original predictions. A faithful interpretation method would capture the influencing regions for decision-making in the model, thereby keeping the original decision for the modified image. We assessed the faithfulness of interpretations derived from two different layers: the last convolutional layer before the Adaptive Pooling—commonly used by CAM-based methods—and an earlier convolutional layer that outputs a higher-resolution feature map than the final one (the layer before the last pooling). Our method demonstrates the highest faithfulness compared to other interpretation techniques across both layers and all evaluated models, confirming it as the most faithful overall. While the competing method CradCam has slightly outperformed LAP in the case of EfficientNet with the target being the last convolutional layer, the differences are minimal. Notably, LAP provides significantly better interpretation maps for the intermediate layer, highlighting the limitations of other methods in interpreting deeper layers, which is crucial for thorough model diagnosis.

---

[3]As CRAFT requires days to generate interpretations, it has only been compared across three architectures: LAP-ResNet50, Original ResNet-50, and LAP-EfficientNet-B0.

Figure 6: Assessing the faithfulness of different interpretation methods on the ImageNet dataset for various models over the outputs of two different layers. Faithfulness is evaluated by keeping a ratio of pixels ranked by the interpretation method (K%), zeroing out the rest of the image, and evaluating the prediction on the modified image with respect to the original prediction. LAP generally outperforms other methods, especially for middle-layer interpretations; only in two cases—both with the target layer being the last convolutional layer—does the competing method CradCam slightly outperform LAP, while in the remaining ten cases LAP shows superior faithfulness.

A.12.2 Comparing faithfulness of the interpretation methods on ImageNet with respect to the ground truth

We compared the faithfulness of different interpretation methods on the LAP-Extended ResNet 50 network (with layer3 as target of the interpretation) on the ImageNet dataset by modifying the input images based on the interpretation scores. Faithfulness was evaluated by keeping $k\%$ of pixels with the highest scores provided by the interpretation method and zeroing out the rest of the parts of the image, then passing the modified image as input through the network for re-evaluation. The results are presented in Fig. 7 for percentages of 10%, 30%, 50%, 70% and 90%. In this experiment, the interpretation scores were calculated based on the ground truth class, and the results were also evaluated with respect to the ground truth. A faithful interpretation method would capture the effective regions for decision-making in the model, keeping the former decision for the modified image. Our method represents the highest faithfulness than other interpretation methods in Top1 and Top5 accuracies, introducing itself as the most confident.

Figure 7: Assessing the faithfulness of different interpretation methods on the ImageNet dataset for LAP-Extended ResNet 50 and layer 3 as the target. Faithfulness is evaluated by keeping a ratio of pixels with the highest scores provided by the interpretation method (K%) for the ground truth class, then zeroing out the rest parts of the image, and evaluating the prediction based on the modified image with respect to the prediction of the original image. Our method in Top1 and Top5 accuracies exceeds the other methods.

A.13 Assessing Execution Times

In terms of assessing computational efficiency, the required time for both phases, "training time" and "inference time," has been calculated for both datasets. In this section, inference time refers to the time needed to run the model to produce outputs and interpret those outputs, which must be practical for real-world applications. Conversely, training time should be manageable to make the method affordable for users. The following subsections include the details.

A.13.1 Training Time

Tab. 13 represents the time required to train different versions of each model for one epoch on an RTX Quadro 8000 GPU. Comparing the times required to train original architectures with the LAP-extended versions, and considering the fact that LAPs only need a few epochs to be trained as explained in Sec. A.10.3. The training time for LAP is both reasonable and affordable. In the case of CRAFT, the required time is excessive and unaffordable. BotCL, on the other hand, requires training the architecture from scratch and therefore needs more than 100 epochs to be trained, making it as unaffordable as CRAFT for large datasets like ImageNet at small research centers and small companies.

Table 13: Training times required for different architectures over 1 epoch for the original architecture, LAP-extended version trained with the proposed weakly supervised approach as a plugged-in module (WSL-), LAPs being tuned as post-hoc interpreters (DLAP-), and BotCL-expanded version. In the case of CRAFT, the total required time has been calculated as the algorithm does not work by epochs. In some cases, the extended version of the model takes less time to be trained as portions of the original network have been frozen. The results indicate the feasibility of adopting LAPs for interpreting the model, especially as they only need a few epochs, even one, to train them.

Dataset	Architecture	Org	WSL-	DLAP-	BotCL-	CRAFT
RSNA	ResNet-18	41 s	60 s	42 s	43 s	30 min
	InceptionV3	102 s	141 s	70 s	80 s	42 min
ImageNet	ResNet-50	2 hr 15 min	1 hr 45 min	1 hr 23 min	—	128 hr
	InceptionV3	2 hr 44 min	1 hr 44 min	1 hr 44 min	—	—
	EfficientNetB0	1 hr 25 min	1 hr 16 min	1 hr 16 min	—	258 hr

A.13.2   Inference Time

In order to examine whether extending the networks with LAP poses lingering execution time in the test phase, we calculated the time required for running the model and interpreting the results for different architectures and different interpretation methods in a Colab Notebook with a T4 accelerator. The results for 761 positive test cases are presented in Sec. A.13.2. It can be observed that LAP has been significantly faster than all the methods in all architectures, but one with a slight difference: GC on the original ResNet. As the complexity of the model increases, e.g. in Lap-extended Inception architecture vs the original ResNet, the execution time of the other interpretation methods increases vastly, while LAP is not affected by that. To be more strict, if we compare the interpretation time of any other interpretation method on the original architectures with the interpretation time of LAP in the LAP-extended architectures, we can conclude that if interpretation is consumed as an inseparable part in running the model, LAP-extension has led to saving time rather than proposing time problems.

Table 14: The pure "prediction + interpretation" time in seconds for 761 positive test cases in a Colab Notebook with a T4 accelerator for different interpretation methods and different architectures. Run times are calculated for the vanilla ResNet18 (RN) and Inception3 (I3) models, BotCL-extended models (BCL-), LAP-extended models trained using the proposed weak supervision (WSL-), and LAP-extended models trained using expert annotations (BBL-). Comparing the time required for interpretation with LAPs in the LAP-extended architectures with the other methods in the original architectures indicates that LAP-extension has not introduced extra time cost considering interpretation as an essential aspect for the modern utilization of deep networks. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

Entry	DL	GGC	GC	GBP	RC	LAP	BotCL	CRAFT
ResNet18	4.98 ± 0.34	4.14 ± 0.18	$\mathbf{2.06} \pm 0.23$	3.21 ± 0.33	8.49 ± 0.17	2.52 ± 0.23	NA[*]	100.98 ± 5.93
BCL-RN	6.5 ± 0.1	5.83 ± 0.1	3.48 ± 0.12	4.71 ± 0.15	?	?	$\mathbf{2.99} \pm 0.17$	138.02 ± 5.47
WSL-RN	8.19 ± 0.11	7.31 ± 0.26	4.03 ± 0.31	5.94 ± 0.36	10.32 ± 0.14	$\mathbf{2.79} \pm 0.28$	NA	130.86 ± 8.02
BBL-RN	7.55 ± 0.08	6.71 ± 0.23	3.51 ± 0.29	5.33 ± 0.47	10.22 ± 0.13	$\mathbf{2.8} \pm 0.32$	NA	130.02 ± 3.12
Inception V3	23.58 ± 0.59	90.47 ± 0.34	23.06 ± 0.14	11.63 ± 0.31	35.57 ± 0.37	$\mathbf{5.14} \pm 0.5$	NA	RL[†]
BCL-I3	23.63 ± 0.36	87.53 ± 0.19	25.03 ± 0.19	13.71 ± 0.21	36.04 ± 0.49	?	$\mathbf{7.95} \pm 0.18$	RL
WSL-I3	31.71 ± 0.17	146.85 ± 0.28	49.99 ± 0.06	20.04 ± 0.19	46.95 ± 0.07	$\mathbf{4.86} \pm 0.21$	NA	RL
BBL-I3	24.85 ± 0.25	119.31 ± 0.15	38.8 ± 0.08	16.28 ± 0.19	44.65 ± 0.04	$\mathbf{4.72} \pm 0.21$	NA	RL

[*] Not Applicable: The BotCL interpretation method applies only to BotCL-extended architectures.
[†] The experiment was interrupted due to exceeding the resource limits in Google Colab.

The required inference time was also measured for different models on the ImageNet dataset. The results presented in Tab. 15 show that LAP is among the fastest methods. Having an efficient inference time and superior interpretative performance across various domains makes it a compelling choice for practical applications.

Table 15: The time required to run the model and interpret outputs on the ImageNet validation data was measured for various interpretation approaches. LAP proved to be one of the fastest methods. Reasonable time combined with its superior performance, makes LAP a highly suitable choice for practical applications.

Model	LAP	DL	GGC	GBP	RC	GC	CRAFT
Org ResNet50	179	276	188	137	523	**127**	500
LAP-ResNet50	220	362	283	205	561	**153**	500
Org InceptionV3	232	423	282	215	784	**170**	-*
LAP-InceptionV3	230	438	296	224	788	**171**	-
Org EfficientNetB0	127	138	135	108	186	**105**	-
LAP-EfficientNetB0	120	143	135	125	186	**104**	230

* CRAFT was assessed on only three models, as training it requires substantial time (see Tab. 13).

A.14 LAPs as standalone predictors

A.14.1 RSNA pneumonia detection

Each LAP layer can also be used as a standalone predictor. In pneumonia classification, if an LAP has assigned a probability of more than 0.5 to at least one pixel, it has found pneumonia in the image. The prediction of the LAP for these samples is assumed to be positive and otherwise negative. We evaluated the predictivity of LAP modules as standalone deciders and the compatibility of their predictions with the model's decisions. According to Tab. 16, as expected, the deeper the layer and the larger its receptive field, the higher the predictivity and the compatibility. Assessing LAPs allows us to diagnose the model from various directions. In this example, for an architecture as complicated as Inception V3, LAP_3 has nearly reached the performance of the whole model. Even in the BB versions, it surpasses the performance of LAP_4 and the final decider. We can decide that the layers after LAP_3 have suffered more from overfitting to the training data, resulting in a performance drop in the test data. Additionally, it can be observed that the BB-LAPs in both architectures generally have higher accuracies than WS-LAPs, especially in LAP_2. This observation implies that using exact supervision leads to better learning in shallower layers of the network, and the DNNs try to recover the performance in deeper layers. Notably, the adopted weakly supervised training scheme has resulted in the enhancement of the predictivity of LAPs in shallower layers (LAP_2) compared to the vanilla models, for which the LAPs are trained as post-hoc explainers over a frozen fully trained model.

Table 16: Results on the RSNA dataset for vanilla and LAP-extended models trained by the proposed weakly supervised loss (WS) and expert annotations (BB). F1 metrics of LAPs as stand-alone predictors w.r.t. ground truth (predictivity) and model prediction (model compatibility) provide an approach for the diagnosis of the model in a global sense. All values are reported as mean $\pm$ standard deviation over five independently trained models initialized with different random seeds.

Model	Predictivity				Model compatibility			
	LAP_1	LAP_2	LAP_3	LAP_4	LAP_1	LAP_2	LAP_3	LAP_4
ResNet 18	67.78±0.0	68.24±0.3	81.52±0.34	93.3±0.82	66.87±0.71	67.36±0.68	81.18±0.92	95.65±1.05
WSL-RN	71.05±2.85	85.61±4.59	92.78±1.66	93.26±1.16	71.29±2.26	86.63±4.3	95.45±1.69	96.29±1.2
BBL-RN	71.03±2.99	89.13±2.66	94.66±0.28	95.04±0.21	70.26±3.63	89.25±3.44	97.04±0.76	98.98±0.4
Inception V3	67.78±0.0	81.86±2.0	95.17±0.35	93.76±1.29	66.41±0.43	80.59±2.52	97.98±0.24	96.41±1.11
WSL-I3	67.78±0.0	89.51±1.0	95.21±0.09	95.27±0.11	66.54±0.27	89.13±1.55	98.33±0.44	98.53±0.45
BBL-I3	67.78±0.0	94.02±1.17	95.3±0.13	95.24±0.13	66.85±1.01	94.88±0.69	99.61±0.17	99.7±0.14

A.14.2 ImageNet

In contrast to RSNA, which has a simple DC, ImageNet has 1000 DCs with objects of high-variance sizes. Therefore, evaluating the LAP's predictivity and model compatibility is not straightforward. We defined the DC size features, $F_C \in \mathbb{R}^{1000}$, as the sum of pixels' importance scores in each DC map. Then, we

trained a 2-layer network to classify the samples according to F_C. To evaluate the predictivity and model compatibility of the LAP, we compared the predictions of the mentioned MLP network with ground-truth and LAP-Extended ResNet 50 predictions, respectively. The results are presented in Tab. 17 for the LAP at layer 4 which uses the output of the layer 3 in the model. Despite the depth of the layer and its distance from the final decider, complexity of the prediction task, the high similarity between many of the classes in the domain, and the highly summarized information extracted from the DCs' score maps, the LAP has achieved high predictivity and model compatibility.

Table 17: The top-1 and top-5 accuracies have been computed for the original model (ResNet 50), and tuned LAP-extended model. The tuned model performs better than the original model and is also accommodated with self-interpretability. The accuracy of the LAP predictor over the output of layer 3 w.r.t. ground truth (predictivity) and the model's prediction (model compatibility) show its effectiveness despite its distance from the final layer.

Model	Model performance		LAP predictions		Compatibility with the model	
	Top-1 Acc.	Top-5 Acc.	Top-1 Acc.	Top-5 Acc.	Top-1 Acc.	Top-5 Acc.
ResNet 50	76.13	92.86	-	-	-	-
LAP ResNet 50	**76.40**	92.93	71.98	86.4	71.98	90.83

A.15 More examples of LAP interpretations

Due to the limited number of pages in the main paper, we have provided more images interpreted with LAP for RSNA and Imagenet in Figs. 8 and 9, respectively.

Figure 8: Examples of all models' interpretations (LAPs) compared to RSNA bounding boxes (BB) and other interpretation methods (GBP, GC, GGC, DL, and RC) on the RSNA dataset. The probability assigned by each model is presented, and the background color represents the final decision of the model. Despite other methods, LAP interpretation is faithful to the model's prediction and helps diagnose the layer from which the model has made a mistake in decision-making.

A.16 Importance based pooling

Pooling layers and strided convolutions are widely used in CNNs to increase the receptive field and decrease memory consumption. Gao et al. have proposed a unified framework for formulating different pooling strategies, called Local Aggregation and Normalization (LAN), and a pooling method called Local Importance Pooling (LIP) (Gao et al., 2019). This framework aggregates features within local sliding windows by weighted averaging. The weights are assigned based on the importance of the features. According to this framework, average pooling assumes the same importance score for all the pixels and is susceptible to feature fading. Max pooling assigns one to the highest feature and zeroes to all the others, leading to sparse gradient paths and slow training. Strided convolutions give importance based on the pixel's location in the window and are

Figure 9: Further DC-wise interpretation Examples of LAP ResNet 50 on ImageNet dataset. For each example, DC heads related to the top-5 predictions of the model are illustrated separately. The probability assigned by the model for each DC head is presented, too. The interpretation maps clarify why the model has chosen each class as one of its top 5.

more sensitive to shift variances. LIP has used the attention mechanism to assign importance weights to the features. LIP is applied feature-wise, which makes it different from our proposed architecture. All of the mentioned pooling layers except strided convolutions can lead to loss of relative spatial relations, as they select different features from different spatial locations (Patrick et al., 2022).

A.17   Licenses of the assets

- **RSNA**: The dataset is freely available for download from Kaggle. Based on the competition website "the competition data is allowed to be used for the competition, participation on Kaggle website forums, academic research and education, and other commercial or non-commercial purposes as long as the attribution for the dataset and the individual items (sound files) are provided when required."

- **ImageNet**: The dataset of ImageNet Large Scale Visual Recognition Challenge 2012-2017 is freely available for download from the ImageNet website. Based on the website, "researchers shall use the Database only for non-commercial research and educational purposes."