DATEFORMER: TRANSFORMER EXTENDS LOOK-BACK HORIZON TO PREDICT LONGER-TERM TIME SERIES

ABSTRACT

Transformers have demonstrated impressive strength in long-term series forecasting. Existing prediction research mostly focused on mapping past short sub-series (lookback window) to future series (forecast window). The longer training dataset time series will be discarded, once training is completed. Models can merely rely on lookback window information for inference, which impedes models from analyzing time series from a global perspective. And these windows used by Transformers are quite narrow because they must model each time-step therein. Under this point-wise processing style, broadening windows will rapidly exhaust their model capacity. This, for fine-grained time series, leads to a bottleneck in information input and prediction output, which is mortal to long-term series forecasting. To overcome the barrier, we propose a brand-new methodology to use Transformer for time series prediction. Specifically, we split time series into patches by day and reform point-wise to patch-wise processing, which considerably enhances the information input and output of Transformers. To further help models leverage the whole training set's global information during inference, we distill the information, store it in time representations, and replace series with time representations as the main modeling entities. Our designed time-modeling Transformer—Dateformer yields state-of-the-art accuracy on 7 real-world datasets with a 33.6% relative improvement and extends the maximum forecast range to half-year.[1]

1 INTRODUCTION

Time series forecasting is a critical demand across many application domains, such as energy consumption, economics planning, traffic and weather forecast. This task can be roughly summed up as predicting future time series by observing their past values. In this paper, we study *long-term forecasting* that involves a longer-range forecast horizon than regular time series forecasting.

Logically, historical observations are always available. But most models (including various Transformers) predict the future by analyzing the part of past sub-series closest to the present. Longer historical series is merely used to train model. For short-term forecasting that more concerns series local (or call short-term) pattern, the closest sub-series carried information is enough. But not for long-term forecasting that requires models to grasp time series' global pattern: overall trend, long-term seasonality, etc. Methods that only observe the recent sub-series can't accurately distinguish the 2 patterns and hence produce sub-optimal predictions (see Figure 1a). However, it's impracticable to thoughtlessly input entire training set series as lookback window. Not only is no model yet can tackle such a lengthy series, but learning dependence from therein is also tough. Thus, we ask: *how do enable models to inexpensively use the global information in training set during inference?*

In addition, the throughput of Transformers (Zhou et al., 2022; Liu et al., 2021; Wu et al., 2021; Zhou et al., 2021; Kitaev et al., 2020; Vaswani et al., 2017), which show the best performance in long-term forecasting, is relatively limited, especially for fine-grained time series (e.g., recorded per 15 min, half-hour, hour). Given a common time series recorded every 15 minutes (96 time-steps per day), with 24GB memory, they mostly fail to predict next month from 3 past months of series, even if they have struggled to reduce self-attention's computational complexity. They can't afford such a lengthy of series and thus cut down lookback window to trade off a flimsy prediction. If they are

---

[1]Code will be released soon.

requested to predict 3 months, how do respond? These demands are quite frequent and important in many application fields. For fine-grained series, we argue, it has reached the bottleneck to extend the forecast horizon through improving self-attention to be more efficient. So, in addition to modifying self-attention, *how do enhance the time series information input and output of Transformers?*

We analyze the second question first. Prior works process time series in a point-wise style: each time-step in time series will be modeled individually. For Transformers, each time-step value is mapped to a token and feed-forwarded. This style wears out the models that endeavor to predict fine-grained time series over longer-term, yet has never been questioned. In fact, similar to images (He et al., 2022), many time series are natural signals with temporal information redundancy—e.g., a missing time-step value can be interpolated from neighboring time-steps. The finer series granularity, the higher their redundancy and the more accurate interpolations. Therefore, the point-wise style is information-inefficient and wasteful. To improve information density of fine-grained time

(a) Two Year Load   (b) Full Day Load

Figure 1: (a) depicts two-year power load of an area. (b) illustrates the area's full day load on Jan 2, 2012, a week ago, a week later, and a year ago: compared to a week ago or later, the time semantics on Jan 2, 2012, is closer to a year ago.

series, we split them into patches and reform the point-wise to patch-wise processing, which considerably reduces tokens and enhances information efficiency. To maintain equivalent token information across time series with different granularity, we fix the patch size as day.

Nevertheless, splitting time series into patches is not a silver bullet for the first question. Even if do so, the whole training set patches series are still too lengthy. And we just want the global information therein, for this purpose to model the whole series is not a good deal. As everyone knows, time is one of the most important properties of time series and plenty of series characteristics are determined by or affected by it. Can time be used as a container to store time series' global information? Driven by this, we try to distill training set's global information into time representations and further substitute time series with these time representations as the main modeling entities. But *how to represent time?* As a preliminary, we also provide a superior method to represent time, see section 2 for details.

In this paper, we challenge using merely vanilla Transformers to predict long-term series. We base vanilla Transformers to design a brand-new forecast framework named **Dateformer**, it regards day as time series atomic unit, which remarkable reduces Transformer tokens and hence improves series information input and output, particularly for fine-grained time series. This also benefits Autoregressive prediction: less error accumulation and faster reasoning. Besides, to better tap training set's global information, we distill, store it in the container of time representations, and take these time representations as main modeling entities for Transformers. **Dateformer** achieves the state-of-the-art performance on 7 benchmark datasets. Our main contributions are summarized as follows:

- We analyze information characteristics of time series and propose splitting time series into patches. This considerably reduces tokens and improves series information input and output thereby enabling vanilla Transformers to tackle long-term series forecasting problems.
- To better tap training set's global information, we use time representations as containers to distill it and take time as main modeling object. Accordingly, we design the first time-modeling time series forecast framework exploiting vanilla Transformers—**Dateformer**.
- As a preliminary work, we also provide a superior time-representing method to support the time-modeling strategy, please see section 2 for details.[2]

2   TIME-REPRESENTING

To facilitate distilling training set's global information, we should establish appropriate time representations as the container to store it. In this paper, we split time series into patches by day, so we mostly study a special case of it—*how to represent a date?*

---

[2]Related works in Appendix B.

To record days, humans invent calendars and use them to guide daily activities. Therefore, the date in calendar contains rich semantics: what day of the week, month, or year is today, is it a holiday, and so on. A rough date-embedding can be generated by stacking these date features into a vector. We utilize a set of simple algorithms to automatically generate date-embeddings (see Appendix C).

But this date-embedding is static. In practice, people pay different attention to various date features and this attention will be dynamically adjusted as the date context change. At ordinary times, people are more concerned about what day of week or month is today. When approaching important festivals, the attention may be shifted to other date features. For example, few people care that Jan 2, 2012, is a Monday because the day before it is New Year's Day (see Figure 1b). This semantics shifting is similar to the polysemy in NLP field, we call it date polysemy. It reminds us: a superior date-representation should consider the contextual information of date. However, the date axis is extended infinitely. The contextual boundaries of date are open, which is distinct from words that are usually located in sentences and hence have a comparatively closed context. Intuitively, distant dates exert a weak influence on today, so it makes sense to select nearby dates as context. Inspired by this, to encode dynamic date-representations, we introduce **D**ate **E**ncoder **R**epresentations from **T**ransformers (**DERT**), a convolution-style BERT (Devlin et al., 2019).

Figure 2: **D**ate **E**ncoder **R**epresentations from **T**ransformers. To encoding the Jan 2, DERT selects date-embeddings of some days before and after it as the contextual padding (the green block).

Concretely, DERT slides a fixed window Transformer encoder on the date axis to select date-embeddings input. The input window contains date-embeddings of: some days before the target day (pre-days padding), the target day to be represented, and some days after the target day (post-days padding). After encoding, we only pick the target day's date-representation out and attach liner layers to it. These linear layers act as the implementations of 2 pre-training tasks we design.

Auto-correlation prediction We observed that many time series display varied intraday trend and periodicity on different kinds of days. Like more steady in holidays, or on the contrary. To leverage it, we utilize the circular auto-correlation in stochastic process theory (Chatfield, 2003; Papoulis & Pillai, 2002) to assess sequences' stability. According to Wiener-Khinchin theorem (Wiener, 1930), series auto-correlation can be calculated by Fast Fourier Transforms. Thus, we Score the stability of a series $\mathcal{X}$ with L-length by following equations:

$$\mathcal{S}_{\mathcal{X}\mathcal{X}}(f) = \mathcal{F}(\mathcal{X}_t)\mathcal{F}^*(\mathcal{X}_t) = \int_{-\infty}^{\infty} \mathcal{X}_t e^{-i2\pi t f} \, \mathrm{d}t \overline{\int_{-\infty}^{\infty} \mathcal{X}_t e^{-i2\pi t f} \, \mathrm{d}t}$$

$$\mathcal{R}_{\mathcal{X}\mathcal{X}}(\tau) = \frac{\mathcal{F}^{-1}(\mathcal{S}_{\mathcal{X}\mathcal{X}}(f))}{\ell_2 Norm} = \frac{\int_{-\infty}^{\infty} \mathcal{S}_{\mathcal{X}\mathcal{X}}(f) e^{i2\pi f \tau} \, \mathrm{d}f}{\sqrt{\mathcal{X}_1^2 + \mathcal{X}_2^2 + \cdots + \mathcal{X}_L^2}} \tag{1}$$

$$Score = \mathrm{Score}(\mathcal{X}) = \frac{1}{L} \sum_{\tau=0}^{L-1} \mathcal{R}_{\mathcal{X}\mathcal{X}}(\tau)$$

where $\mathcal{F}$ denotes Fast Fourier Transforms, $*$ and $\mathcal{F}^{-1}$ denote the conjugate and inverse Transforms respectively. DERT is asked to predict a day series $Score$ only relying on its date-representation.

Mean prediction   Predicting time series mean is a direct yet effective task, we require DERT to predict daily mean from date-representation. This task will lose some intraday information of time series patches, so we design the former task to mitigate it. During pre-training, the 2 tasks each contribute half of the pre-training loss:

$$Pretrained\ Loss = \frac{\text{MSE}(\text{linearLayer}_1(\boldsymbol{d}), Mean) + \text{MSE}(\text{linearLayer}_2(\boldsymbol{d}), Score)}{2}$$

where $\boldsymbol{d}$ denotes dynamic date-representation produced by DERT, $Mean$ denotes series ground-truth mean on this day, and $Score$ is calculated by equation 1. Our DERT relies on supervised pre-training tasks, so it's series-specified—different series datasets need to re-train respective DERT.

3   DATEFORMER

We believe that time series fuse 2 patterns of components: global and local pattern. The global pattern is derived from time series inherent characteristics and hence doesn't fluctuate violently. While the local pattern is caused by some accidental factors such as sudden changes in the weather, so it's not long-lasting. As aforementioned, the global pattern should be grasped from entire training set series, and the local pattern can be captured from lookback window series. Based on this, we design *Dateformer*, it distills training set's global information into date-representations, and then leverages the information to produce a ***global prediction***. The lookback window is used to provide local pattern information, and then contributes a ***local prediction***. *Dateformer* fuses the 2 predictions into a *final prediction*. To enhance Transformer's throughput, we split time series into patches by day, and apply *Dateformer* in a patch-wise processing style. Therefore, we deal with time series forecasting problems at a day level—predicting next H days time series from historical series.

3.1   GLOBAL PREDICTION

We distill whole training set's global information and store it in date-representations. Then, in the prediction stage, we can draw a *global prediction* from therein to represent learned global pattern.

Figure 3: Take Jan 2 as an example: to get the day's *global prediction*, we duplicate Jan 2 date-representation into G copies (G denotes series time-steps number every day), and plus sequential positional encodings. A position-wise feed-forward network maps them to *global prediction*.

As shown in Figure 3, given a date-representation $\boldsymbol{d}$, we duplicate it to G copies (G denotes series time-steps number every day), and add sequential positional encodings[3] to these copies, to refine the date-representation to a finer time scale. Then, to get a *global prediction* corresponding to this date, we employ a position-wise feed-forward network to map these time-representations into time series.

Before formally training the entire Dateformer, we separately train this simple network on training set to distill therein global information, thereby preserving time series' global pattern. Of course, for some datasets, end-to-end training Dateformer is also appropriate, we discuss it in Appendix F.

---

[3]We use the canonical Positional Encoding proposed by Vaswani et al. (2017), other PEs is also feasible.

Figure 4: Take Jan 2 as an example: to get the day's *local prediction*, we utilize Transformer to learn series residuals similarities W_i between Jan 2 and the lookback window (left), and use the similarities to aggregate *Series Residuals* of lookback window into the *local prediction* (right).

3.2 LOCAL PREDICTION

To better capture the local pattern from lookback window, we eliminate the learned global pattern from lookback window series. As described in the previous section, for a day in lookback window, we can get this day's *global prediction* from its date-representation. Then, this day's *Series Residual* $\boldsymbol{r}$ will be produced using following equation:

$$Series\ Residual\ \boldsymbol{r} = Series - Global\ Prediction \tag{2}$$

where $Series$ denote this day's ground-truth time series. We apply the operation to all days in lookback window, to produce the *Series Residuals* $\{\boldsymbol{r}_1, \boldsymbol{r}_2, \cdots\}$ of the whole lookback window. Subsequently, we utilize a vanilla Transformer to learn a *local prediction* from the *Series Residuals*.

Concretely, as shown in Figure 4, we feed the lookback window *Series Residuals* into Transformer encoder. For multivariate time series, pre-flattening series is required. The encoder output will be sent into Transformer decoder as a cross information to help decoder refine input date-representations. To learn pair-wise similarities of the forecast day and each day in lookback window, the decoder eats date-representations of lookback window and forecast day, to exchange information between them. Given a lookback window of P days, the similarities are calculated by:

$$Series\ Residuals = \{\boldsymbol{r}_1, \boldsymbol{r}_2, \cdots, \boldsymbol{r}_P\}$$
$$Date\ Representations = \{\boldsymbol{d}_1, \boldsymbol{d}_2, \cdots, \boldsymbol{d}_P, \boldsymbol{d}_{P+1}\}$$
$$\{\widehat{\boldsymbol{d}_1}, \widehat{\boldsymbol{d}_2}, \cdots, \widehat{\boldsymbol{d}_P}, \widehat{\boldsymbol{d}_{P+1}}\} = \text{Decoder}(Date\ Representations, \tag{3}$$
$$\text{Encoder}(Series\ Residuals))$$
$$Similarities = \{W_1, W_2, \cdots, W_P\} = \text{SoftMax}(\text{FFN}(\widehat{\boldsymbol{d}_1}, \widehat{\boldsymbol{d}_2}, \cdots, \widehat{\boldsymbol{d}_P}))$$

then, we can get a *local prediction* corresponding $\boldsymbol{d}_{P+1}$ by Aggregating *Series Residuals*:

$$Local\ Prediction = \text{Aggregate}(Series\ Residuals)$$
$$= W_1 \times \boldsymbol{r}_1 + W_2 \times \boldsymbol{r}_2 + \cdots + W_P \times \boldsymbol{r}_P \tag{4}$$

3.3 FINAL PREDICTION

Now, we can obtain a *final prediction* by adding the *global prediction* and *local prediction*:

$$Final\ Prediction = Global\ Prediction + Local\ Prediction \tag{5}$$

For multi-day forecast, we need to encode multi-day date-representations and produce their corresponding *global predictions* and *local predictions*. Thus, we design Dateformer to automatically conduct these procedures and fuse them into the *final predictions*, just like a scheduler.

Figure 5: Overview of Dateformer (9-predict-3 days case, 2 pre- and 4 post-days padding). For multi-day forecast, Dateformer slides DERT to encode date-representations of lookback and forecast window. The *global predictions* are generated through a feed-forward propagation to time representations. Dateformer recursively calls Transformer to aggregate multi-day *local predictions*.

Refer to Figure 5, for multi-day forecast, we input into Dateformer: i) static date-embeddings of: pre-days padding, lookback window, forecast window, and post-days padding to encode multi-day date-representations; ii) lookback window series to provide local information supporting the *local prediction*. Dateformer slides DERT to encode dynamic date-representations of lookback and forecast window. Then, the *global predictions* can be produced by a single feed-forward propagation.

For the *local predictions*, Dateformer recursively calls the Transformer to day-wise predict. Autoregression is applied in the procedure—the previous prediction is used for subsequent predictions:

$$Series\ Residuals = \{\boldsymbol{r}_1, \boldsymbol{r}_2, \cdots, \boldsymbol{r}_P\}$$
$$Local\ Prediction\ \boldsymbol{r}_{P+1} = \text{Aggregate}(Series\ Residuals)$$
$$Series\ Residuals = \{\boldsymbol{r}_0, \boldsymbol{r}_1, \boldsymbol{r}_2, \cdots, \boldsymbol{r}_P, \boldsymbol{r}_{P+1}\} \tag{6}$$
$$Local\ Prediction\ \boldsymbol{r}_{P+2} = \text{Aggregate}(Series\ Residuals) \cdots$$

To retard error accumulation, we adopt 3 tricks: 1) Dateformer employs Autoregression for only *local predictions*, the *global predictions* with most numerical scale of time series are generated in a single feed-forward propagation, which restricts the error's scale; 2) Dateformer regards day as time series basic unit. For fine grained time series, the day-wise Autoregression remarkable reduces errors propagation times and accelerates prediction; 3) During *local prediction* Autoregression, when a day predicted *local prediction* patch (such as $\boldsymbol{r}_{P+1}$ in equation 6) is appended to the $Series\ Residuals$ tail, Dateformer will insert earlier past a day ground-truth residual (such as $\boldsymbol{r}_0$ in equation 6) into their head to balance the proportion between true local information and predicted residuals.

We didn't adopt the one-step forward generative style prediction that is proposed by Zhou et al. (2021) and followed by other Transformer-based forecast models because the style lacks scalability. For different length forecast demands, they have to re-train models. We are committed to providing a scalable forecast style to tackle forecast demands of various lengths. Although has defects of slow prediction speed and error accumulation, Autoregression can achieve the idea. So we still adopt Autoregression and fix its defects. Dateformer has excellent scalability. It can be trained on short-term forecasting task while robustly generalizing to long-term forecasting tasks. For each dataset, **we only train Dateformer once to deal with forecast demands for any number of days**.

4 EXPERIMENTS

Datasets We extensively perform experiments on 7 real-world datasets, including energy, traffic, economics, and weather: (1) *ETT* (Zhou et al., 2021) dataset collects 2 years (July 2016 to July 2018) electricity data from 2 transformers located in China, including oil temperature and load recorded every 15 minutes or hourly; (2) *ECL*[4] dataset collects the hourly electricity consumption data of 321 Portugal clients from 2012 to 2015; (3) *PL*[5] dataset contains power load series of 2 areas in China from 2009 to 2015. It's recorded every 15 minutes and carries incomplete weather data. We eliminate the climate information and stack the 2 series into a multivariate time series; (4) *Traffic*[6] contains hourly record value of road occupancy rate in San Francisco from 2015 to 2016; (5) *Weather*[7] is a collection of 21 meteorological indicators series recorded every 10 minutes by a German station for the 2020 whole year; (6) *ER*[8] collects the daily exchange rate of 8 countries from March 2001 to March 2022. We split all datasets into training, validation, and test set by the ratio of 6:2:2 for *ETT* and *PL* datasets and 7:1:2 for others, just following the standard protocol.

Baselines We select 6 strong baseline models for multivariate forecast comparisons, including 4 state-of-the-art Transformer-based, 1 RNN-based, and 1 CNN-based models: FEDformer(Zhou et al., 2022) (ICML 2022), Autoformer (Wu et al., 2021) (NeurIPS 2021), Informer (Zhou et al., 2021) (AAAI 2021 Best Paper Award), Pyraformer (Liu et al., 2021) (ICLR 2022 Oral), LSTM (Hochreiter & Schmidhuber, 1997), and TCN (Bai et al., 2018).

Implementation details Our proposed models are trained with L2 loss, and using AdamW (Loshchilov & Hutter, 2017) optimizer with weight decay of $7e^{-4}$. We adjust learning rate by OneCycleLR (Smith & Topin, 2019) which use 3 phase scheduling with the percentage of the cycle spent increasing the learning rate is 0.4, and the max learning rate is $1e^{-3}$. Batch size for pretraining is 64, and 32 for others. The total epochs are 100, but the models normally super converges very quickly. All experiments are repeated 3 times, implemented by PyTorch(Paszke et al., 2019), and trained on a NVIDIA RTX3090 24GB GPUs. Numbers of the pre-days and post-days padding are 7 and 14 respectively. There are 1 layer in DERT encoder, and the inside Transformer contains 4 layers both in encoder and decoder. The details of Transformer-based baselines are in Appendix H.

4.1 MAIN RESULTS

We show Dateformer's performance here. Due to splitting time series by day, we evaluate models with a wide range of forecast days: 1d, 3d, 7d, 30d, 90d (or 60d), and 180d covering short-, medium-, and long-term forecast demands. For coarse-grained *ER* series, we still follow the forecast horizon setups proposed by Wu et al. (2021). Our idea is to break the information bottleneck to models, so we didn't restrict models' input. Any input length is allowed as long as the model can afford it. For these baselines, if existing, we'll choose the input length recommended in their paper. Otherwise, an estimated input length will be given by us. We empirically select 7d, 9d, 12d, 26d, 46d (or 39d), and 60d as corresponding lookback days for Dateformer, and **we only train it once on the 7d-predict-1d task** to test all setups for each dataset. For fairness, all these sequence-modeling baselines are trained time-step-wise but tested day-wise. Due to the space limitation, only multivariate comparisons is shown here, see Appendix D for univariate comparisons and Table 11 for standard deviations results.

Multivariate results Our proposed Dateformer achieves consistent state-of-the-art performance under all forecast setups on all 7 benchmark datasets. The longer forecast horizon, the more significant improvement. For the long-term forecasting setting (>60 days), Dateformer gives MSE reduction: **82.5%** ($0.585 \rightarrow 0.144$, $1.672 \rightarrow 0.176$) in *PL*, **42%** ($1.056 \rightarrow 0.690$) in *ETTm1*, **38.6%** ($0.702 \rightarrow 0.431$) in *ETTh2*, **59.8%** ($0.316 \rightarrow 0.220$, $2.231 \rightarrow 0.240$) in *ECL*, **79.4%** ($2.557 \rightarrow 0.526$) in *Traffic*, and **31.5%** in *ER*. Overall, Dateformer yields a **33.6%** averaged accuracy improvement among all setups. Compared with other models, its errors rise mostly steadily

---

[4]https://archive.ics.uci.edu/ml/datasets/ElectricityLoadDiagrams20112014

[5]This dataset is provided by the 9th China Society of Electrical Engineering cup competition.

[6]http://pems.dot.ca.gov/

[7]https://www.bgc-jena.mpg.de/wetter/

[8]https://fred.stlouisfed.org/categories/158

Table 1: Multivariate time series forecasting results. OOM: Out Of Memory. - means failing to train because validation set is too short to provide even a sample. (Number) in parentheses denotes each dataset's time-steps number every day. A lower MSE or MAE indicates a better prediction. The best results are highlighted in **bold** and the second best results are highlighted with a underline.

Models		**Dateformer**		FEDformer		Autoformer		Informer		Pyraformer		LSTM		TCN	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
PL(96)	1	**0.042**	0.141	0.105	0.231	0.098	0.201	0.067	0.157	0.052	**0.139**	0.796	0.577	0.111	0.211
	3	**0.076**	**0.187**	0.149	0.264	0.405	0.479	0.251	0.331	0.134	0.230	0.672	0.553	0.197	0.296
	7	**0.093**	**0.211**	0.196	0.303	0.398	0.462	0.370	0.424	0.211	0.313	0.970	0.698	0.216	0.304
	30	**0.115**	**0.249**	0.423	0.471	0.902	0.727	0.373	0.458	0.268	0.381	2.025	1.115	0.698	0.649
	90	**0.144**	**0.291**	OOM	OOM	OOM	OOM	OOM	OOM	0.585	0.590	3.394	1.359	1.415	0.956
	180	**0.176**	**0.320**	OOM	OOM	OOM	OOM	OOM	OOM	OOM	OOM	3.312	1.462	1.672	1.004
ETTm1(96)	1	**0.322**	**0.355**	0.341	0.390	0.491	0.476	0.640	0.570	0.515	0.505	1.058	0.709	0.734	0.667
	3	**0.368**	**0.381**	0.419	0.439	0.598	0.522	0.963	0.750	0.849	0.713	1.505	0.890	0.833	0.722
	7	**0.417**	**0.410**	0.473	0.468	0.646	0.547	1.129	0.800	1.053	0.818	1.897	1.028	0.881	0.729
	30	**0.438**	**0.446**	0.547	0.525	0.681	0.581	1.132	0.831	1.020	0.806	2.970	1.240	1.033	0.811
	90	**0.690**	**0.600**	OOM	OOM	OOM	OOM	OOM	OOM	1.056	0.845	1.855	1.010	1.081	0.821
ETTh2(24)	1	**0.234**	**0.306**	0.246	0.327	0.289	0.364	1.606	0.997	0.412	0.498	1.074	0.723	1.126	0.874
	3	**0.311**	**0.363**	0.334	0.381	0.347	0.395	1.928	1.111	1.140	0.832	1.583	0.873	1.900	1.138
	7	**0.383**	**0.413**	0.412	0.426	0.451	0.451	6.200	2.024	4.877	1.747	2.429	1.111	4.410	1.741
	30	**0.437**	**0.472**	0.466	0.483	0.510	0.511	4.091	1.717	4.674	1.869	2.014	1.052	2.919	1.503
	90	**0.431**	**0.486**	0.719	0.618	0.702	0.631	2.571	1.217	3.330	1.511	3.754	1.436	3.356	1.503
ECL(24)	1	**0.113**	**0.218**	0.169	0.288	0.174	0.293	0.328	0.412	0.268	0.372	0.368	0.425	0.365	0.436
	3	**0.148**	**0.251**	0.186	0.302	0.215	0.329	0.358	0.430	0.308	0.388	0.475	0.474	0.434	0.471
	7	**0.163**	**0.266**	0.201	0.316	0.208	0.320	0.387	0.459	0.281	0.381	0.786	0.634	0.362	0.432
	30	**0.187**	**0.291**	0.242	0.351	0.259	0.364	0.400	0.460	0.288	0.382	1.304	0.834	0.442	0.484
	90	**0.220**	**0.322**	0.316	0.404	0.382	0.439	0.550	0.552	OOM	OOM	1.815	1.048	0.501	0.513
	180	**0.240**	**0.339**	-	-	-	-	-	-	-	-	2.231	1.159	-	-
Traffic(24)	1	**0.343**	**0.252**	0.547	0.357	0.554	0.363	0.678	0.383	0.600	0.337	1.220	0.622	0.814	0.480
	3	**0.430**	**0.284**	0.581	0.367	0.625	0.391	0.721	0.404	0.635	0.358	1.902	0.878	1.582	0.743
	7	**0.434**	**0.289**	0.613	0.382	0.705	0.439	0.768	0.425	0.639	0.356	2.509	1.114	0.803	0.444
	30	**0.469**	**0.308**	0.652	0.395	0.686	0.420	0.959	0.534	OOM	OOM	2.413	1.089	1.120	0.615
	90	**0.526**	**0.339**	-	-	-	-	-	-	-	-	2.557	1.128	-	-
Weather(144)	1	**0.220**	**0.288**	0.234	0.304	0.327	0.377	0.370	0.424	0.231	0.310	5.868	1.478	0.267	0.328
	3	**0.281**	**0.329**	0.338	0.375	0.370	0.402	0.628	0.560	0.388	0.427	4.232	1.417	0.468	0.452
	7	**0.320**	**0.360**	0.495	0.472	0.474	0.461	1.093	0.768	0.442	0.460	5.727	1.469	0.523	0.510
	30	**0.414**	**0.428**	0.688	0.580	0.724	0.604	2.789	1.303	0.823	0.676	7.141	1.804	0.878	0.711
	60	**0.539**	**0.531**	-	-	-	-	-	-	-	-	8.168	1.766	-	-
ER(1)	96	**0.022**	**0.107**	0.041	0.154	0.040	0.154	0.248	0.361	0.194	0.340	0.452	0.520	0.482	0.541
	192	**0.043**	**0.152**	0.062	0.194	0.061	0.193	0.430	0.474	0.337	0.440	0.536	0.558	0.496	0.558
	336	**0.070**	**0.195**	0.087	0.233	0.096	0.246	0.756	0.642	0.607	0.600	0.825	0.705	0.557	0.586
	720	**0.112**	**0.255**	0.165	0.317	0.389	0.422	1.073	0.773	0.963	0.772	0.866	0.729	0.677	0.652

as forecast horizon grows. It means that Dateformer gives the most credible and robust long-range forecast. Note that our Dateformer still contributes the best predictions on the *ER* series, which is **coarse-grained time series without seasonality.**

4.2 ANALYSIS

We try to analyze the 2 forecast components' contributions to the *final prediction* and explain why Dateformer's predictive errors rise mostly slowly as forecast days extend. We use separate *global prediction* or *local prediction* component to predict then compare their results, as shown in Table 2.

Table 2: Comparison of different forecast components results.

Datasets		*PL*			*ECL*			*Traffic*		
Forecast Days		1	30	180	1	30	180	1	7	90
Global	MSE	0.129	0.132	**0.156**	0.310	0.303	0.302	0.634	0.640	0.656
Prediction	MAE	0.264	0.268	**0.297**	0.395	0.392	0.392	0.355	0.356	0.362
Local	MSE	**0.029**	0.406	1.386	**0.101**	0.249	0.378	**0.330**	0.545	0.725
Prediction	MAE	**0.115**	0.457	0.908	**0.201**	0.327	0.412	**0.239**	0.341	0.414
Final	MSE	0.042	**0.115**	0.176	0.113	**0.187**	**0.240**	0.343	**0.434**	**0.526**
Prediction	MAE	0.141	**0.249**	0.320	0.218	**0.291**	**0.339**	0.252	**0.289**	**0.339**

It can be seen that errors of the separate *global prediction* hardly rise as forecast horizon grows. The separate *local prediction*, however, is rapidly deteriorating. This may prove our hypothesis that time series have 2 patterns of components: global and local pattern. As stated in section 3, the global pattern will not fluctuate violently, while the local pattern is not long-lasting. Therefore, as forecast horizon grows, *global prediction* that still keep stable errors is especially important for long-term forecasting. Although do best in short-term forecasting, errors of *local prediction* increase rapidly as forecast days extend because local pattern is not long-lasting. As time goes on, the local pattern shifts gradually. For distant future days, current local pattern even degenerates into a noise that encumbers predictions: comparing the 180 days prediction cases on *PL*, the best prediction is contributed by the separate *global prediction* instead of the *final prediction* that disturbed by the noise. Not only local pattern, but Dateformer also grasps global pattern, so its errors rise mostly steadily. To intuitively understand the 2 patterns' contributions, we use Auto-correlation that presents the same periodicity with source series to analyze the seasonality and trend of *ETT* oil temperature series.

| (a) Ground-Truth | (b) Global Prediction | (c) Series Residuals | (d) Remainder |

Figure 6: Auto-correlation of four time series from *ETT* oil temperature series: (a) Ground-truth; (b) Global Prediction; (c) Ground-truth − Global Prediction; (d) Ground-truth − Final Prediction.

As shown in Figure 6a, the *ETT* oil temperature series mixes complex multi-scale seasonality, and the *global prediction* almost captures it perfectly in 6b. But see Figure 6c, we can find *global prediction* fail to accurately estimates series mean: although a sharp descent occurs in the left end after eliminate the *global prediction*, it didn't immediately drop to near 0. Because local pattern will effect series trends. The local pattern is not long-lasting, so we can only approximate it from lookback window. After subtracting the *final prediction*, we get an Auto-correlation series of random oscillations around 0 in 6d, which indicates source series is as unpredictable as white noise series.

4.3 ABLATION STUDIES

We conduct ablation studies about input lookback window length and proposed time-representing method, related results and discussions are in Appendix E. Due to the space limitation, we only list major finds here. (1) Our Dateformer can benefit from longer lookback windows, but not for other Transformers; (2) The proposed dynamic time-representing method can effectively enhance Dateformer's performance; (3) But sequence-modeling Transformers, which underestimate the significance of time and let it just play an auxiliary role, may not benefit from better time-encodings.

In addition, we also conduct ablation studies about the proposed 2 pre-training tasks in section 2. Beyond all doubt, the pre-training task of mean prediction is naturally effective. Removing this task to pre-train, Dateformer's predictions remarkable deteriorates. But for some datasets, pre-training DERT on only this task also damages Dateformer's performance. Auto-correlation prediction can induce DERT to concern time series intraday information, thereby encoding finer date-representations.

5 CONCLUSIONS

In this paper, we challenge employing merely vanilla Transformers to predict long-term series. We analyze information characteristic of time series and propose splitting time series into patches to enhance Transformer's throughout. Besides, we distill the whole training set's global information and store it in time representations, to help the model grasp time series' global pattern. The proposed Dateformer yields consistent state-of-the-art performance on extensive 7 real-world datasets.

REFERENCES

Shaojie Bai, J Zico Kolter, and Vladlen Koltun. An empirical evaluation of generic convolutional and recurrent networks for sequence modeling. *arXiv preprint arXiv:1803.01271*, 2018.

George EP Box and Gwilym M Jenkins. Some recent advances in forecasting and control. *Journal of the Royal Statistical Society. Series C (Applied Statistics)*, 1968.

Chris Chatfield. *The analysis of time series: an introduction*. Chapman and hall/CRC, 2003.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *arXiv:1810.04805 [cs]*, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. *arXiv preprint arXiv:2001.04451*, 2020.

Guokun Lai, Wei-Cheng Chang, Yiming Yang, and Hanxiao Liu. Modeling long-and short-term temporal patterns with deep neural networks. In *The 41st International ACM SIGIR Conference on Research & Development in Information Retrieval*, pp. 95–104, 2018.

Shiyang Li, Xiaoyong Jin, Yao Xuan, Xiyou Zhou, Wenhu Chen, Yu-Xiang Wang, and Xifeng Yan. Enhancing the locality and breaking the memory bottleneck of transformer on time series forecasting. *Advances in Neural Information Processing Systems*, 32, 2019.

Shizhan Liu, Hang Yu, Cong Liao, Jianguo Li, Weiyao Lin, Alex X Liu, and Schahram Dustdar. Pyraformer: Low-complexity pyramidal attention for long-range time series modeling and forecasting. In *International Conference on Learning Representations*, 2021.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Boris N Oreshkin, Dmitri Carpov, Nicolas Chapados, and Yoshua Bengio. N-beats: Neural basis expansion analysis for interpretable time series forecasting. *arXiv preprint arXiv:1905.10437*, 2019.

Athanasios Papoulis and S Unnikrishna Pillai. *Probability, random variables, and stochastic processes*. Tata McGraw-Hill Education, 2002.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 2019.

Yao Qin, Dongjin Song, Haifeng Chen, Wei Cheng, Guofei Jiang, and Garrison Cottrell. A dual-stage attention-based recurrent neural network for time series prediction. *arXiv preprint arXiv:1704.02971*, 2017.

David Salinas, Valentin Flunkert, Jan Gasthaus, and Tim Januschowski. Deepar: Probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 36(3):1181–1191, 2020.

Rajat Sen, Hsiang-Fu Yu, and Inderjit S Dhillon. Think globally, act locally: A deep neural network approach to high-dimensional time series forecasting. *Advances in neural information processing systems*, 32, 2019.

Leslie N Smith and Nicholay Topin. Super-convergence: Very fast training of neural networks using large learning rates. In *Artificial intelligence and machine learning for multi-domain operations applications*, volume 11006, pp. 1100612. International Society for Optics and Photonics, 2019.

Sean J Taylor and Benjamin Letham. Forecasting at scale. *The American Statistician*, 2018.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Norbert Wiener. Generalized harmonic analysis. *Acta mathematica*, 55(1):117–258, 1930.

Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. *Advances in Neural Information Processing Systems*, 34, 2021.

Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. Informer: Beyond efficient transformer for long sequence time-series forecasting. In *Proceedings of AAAI*, 2021.

Tian Zhou, Ziqing Ma, Qingsong Wen, Xue Wang, Liang Sun, and Rong Jin. FEDformer: Frequency enhanced decomposed transformer for long-term series forecasting. In *Proc. 39th International Conference on Machine Learning (ICML 2022)*, 2022.

A FUTURE WORKS

In this paper, as a preliminary work, we briefly introduced the dynamic date-representation and DERT, but didn't talk about their transferability. Actually, under certain conditions, a DERT that is pre-trained on a time series dataset can transfer to other similar datasets to encode date-representations. For example, *PL* and *ETT* are similar electrical series datasets recorded in different cities of China, *PL* range from 2009 to 2015 while *ETT* range from 2016 to 2018, but we found the DERT that is pre-trained on *PL* can directly transfer to forecast tasks on *ETT*. More interestingly, with the transferred DERT, Dateformer demonstrates a fairly good few sample learning potential. On the *ETT* series, even though only one-third of training samples are provided, Dateformer still can converge to the same performance level as the full training samples provided (see Table 3). The details are not completely clear yet, we will further study in future works.

Table 3: Few sample learning results on *ETTm1*, only MSE is reported.

Models	Dateformer-*ETTm1*-pre-trained				Dateformer-*PL*-pre-trained			
Samples	353	233	113	1	353	233	113	1
1	0.326	0.331	0.333	0.422	**0.322**	0.324	0.332	0.373
3	0.370	0.374	0.383	0.445	0.368	**0.365**	0.381	0.399
7	0.418	0.422	0.427	0.478	0.417	**0.414**	0.426	0.443
30	0.443	0.442	0.435	0.476	0.438	0.437	**0.435**	0.453
90	0.702	0.711	0.680	0.698	0.690	0.680	**0.678**	0.696

Refer to Table 3, we train 2 Dateformers on *ETT* series ranging full 12 months (353 samples), 8 months (233 samples), 4 months (113 samples) and 8 days (1 sample), to test all forecast horizon setups on the same test set. The Dateformer whose DERT is pre-trained on *PL* series shows the same performance level, even a slightly better because *PL* is a bigger dataset with a longer time span. And fewer samples are required: 4 months of *ETT* series is enough for Dateformer to convergence.

B RELATED WORKS

Time series forecasting is an enduring research topic, and numerous works have been developed to deal with the task. They can be roughly divided into two categories: statistical methods and deep learning models. ARIMA (Box & Jenkins, 1968), Prophet (Taylor & Letham, 2018), and the filtering methods are representative methods of the former. The deep learning models mainly include RNN-based (Recurrent Neural Network based), CNN-based (Convolutional Neural Network based), and Transformer-based structures.

LSTM (Hochreiter & Schmidhuber, 1997) and GRU (Chung et al., 2014) employ gating mechanisms to extend series dependence learning distance and relieve the gradient vanishing or explosion of RNN. DeepAR (Salinas et al., 2020) further combines LSTM and Autoregression for time series probabilistic distribution forecasting. LSTNet (Lai et al., 2018) adopts CNN and recurrent-skip connections to modeling short- and long-term patterns of time series. Some RNN-based works introduced the attention mechanism to capture long-range temporal dependence, so as to improve predictions (Qin et al., 2017). However, RNN's intrinsic flaws (difficulty capturing long-range dependence, slow reasoning, and accumulating error) prevent them from predicting long-term series.

Temporal convolutional network (TCN) (Bai et al., 2018) is CNN-based representative work, which models temporal dependence with the causal convolution. DeepGLO (Sen et al., 2019) also mentioned the concept of global and local, and employs TCN to model them. Nevertheless, **the global concept in their paper refers to relationships between related other time series, which is distinct from this paper refers to the global historical observation on the series itself.**

Transformer (Vaswani et al., 2017) recently becomes popular in long-term series forecasting, owing to its excellent long-range dependence capturing capability. But directly applying Transformer to long-term series forecasting is computationally prohibitive due to inside self-attention's quadratic complexity about sequence length in both memory and time. Many studies are proposed to resolve the problem. LogTrans (Li et al., 2019) presented *LogSparse* attention that reduces the

computational complexity to $\mathcal{O}(L(\log L)^2)$, and Reformer (Kitaev et al., 2020) presented local-sensitive hashing (LSH) attention with $\mathcal{O}(L \log L)$ complexity. Informer (Zhou et al., 2021) proposed *probSparse* attention of $\mathcal{O}(L \log L)$ complexity, and further renovated the vanilla Transformer architecture. Autoformer (Wu et al., 2021) and FEDformer (Zhou et al., 2022) built decomposed blocks in Transformer and introduced low complexity enhanced attention in frequency domain or Auto-correlation to replace self-attention. Pyraformer (Liu et al., 2021) adopted hierarchical multi-resolution PAM attention to achieve $\mathcal{O}(L)$ complexity and learn multi-scale temporal dependence. To extend forecast horizon, all these variant Transformers designed various modified self-attentions or substitutes to reduce computational complexity, so as to tackle longer time series.

In CV community, ViT (Dosovitskiy et al., 2020) split images into patches, to enable vanilla Transformers to tackle abundant pixels. Compared to highly abstract human language, we argue that information characteristic of time series is more similar to it of images. They both are natural signals and exist numerical continuity between adjacent signals. Inspired by this, we follow ViT to split time series into patches, thereby enhancing time series forecasting Transformers' throughput, and enabling vanilla Transformers to predict long-term series.

In addition to these structures, there are also other neural network methods such as N-BEATS (Oreshkin et al., 2019) that uses decomposition. Above most forecast methods can be summarized as learning a mapping from lookback window to forecast window, and they some leverage time feature assist prediction. However, in the end, they are confined by information because they can only rely on the local information in lookback window. To our best knowledge, we are the first time series forecasting work that distills the whole training set's global information into time-representations and takes time instead of series as the primary modeling entities—time-modeling strategy.

C DATE EMBEDDING

Observing the movement of celestial planets, changes in temperature, or the rise and fall of plants, our forefathers distilled a set of laws, that is calendars. A wealth of wisdom is encapsulated in the calendar. People's activities are guided by the calendar and we believe that's the fundamental source of seasonality in many time series. We try to introduce the wisdom in our models as a priori knowledge. We use the Gregorian calendar as solar calendar and the traditional Chinese calendar as lunar calendar to deduce our date-embedding. Besides, the vacation and weekday information is also taken into count. In our code, we provide the date-embeddings range from 2001 to 2023 for 12 countries or regions: Australia, British, Canada, China, Germany, Japan, New Zealand, Portugal, Singapore, Switzerland, USA, and San Francisco.

Our static date-embedding stacks the following date features: *abs_day, year, day (month_day), year_day, weekofyear, lunar_year, lunar_month, lunar_day, lunar_year_day, dayofyear, dayofmonth, monthofyear, dayofweek, dayoflunaryear, dayoflunarmonth, monthoflunaryear, jieqiofyear, jieqi_day, dayofjieqi, holidays, workdays, residual_holiday, residual_workday.* As an example, we embed today by following equations:

$$abs\_day = \frac{\text{days that have passed from December 31, 2000}}{365.25 * 5}$$

$$year = \frac{\text{this year} - 1998.5}{25}$$

$$day = \frac{\text{days that have passed in this month}}{31}$$

$$year\_day = \frac{\text{days that have passed in this year}}{366}$$

$$weekofyear = \frac{\text{weeks that have passed in this year}}{54}$$

$$lunar\_year = \frac{\text{this lunar year} - 1998.5}{25}$$

$$lunar\_month = \frac{\text{this lunar month}}{12}$$

$$lunar\_day = \frac{\text{days that have passed in this lunar month}}{30}$$

$$lunar\_year\_day = \frac{\text{days that have passed in this lunar year}}{384}$$

$$dayofyear = \frac{\text{days that have passed in this year} - 1}{\text{total days in this year} - 1} - 0.5$$

$$dayofmonth = \frac{\text{days that have passed in this month} - 1}{\text{total days in this month} - 1} - 0.5$$

$$monthofyear = \frac{\text{months that have passed in this year} - 1}{11} - 0.5$$

$$dayofweek = \frac{\text{days that have passed in this week} - 1}{6} - 0.5$$

$$dayoflunaryear = \frac{\text{days that have passed in this lunar year} - 1}{\text{total days in this lunar year} - 1} - 0.5$$

$$dayoflunarmonth = \frac{\text{days that have passed in this lunar month} - 1}{\text{total days in this lunar month} - 1} - 0.5$$

$$monthoflunaryear = \frac{\text{lunar months that have passed in this lunar year} - 1}{11} - 0.5$$

$$jieqiofyear = \frac{\text{solar terms that have passed in this year} - 1}{23} - 0.5$$

$$jieqi\_day = \frac{\text{days that have passed in this solar term}}{15}$$

$$dayofjieqi = \frac{\text{days that have passed in this solar term} - 1}{\text{total days in this solar term} - 1} - 0.5$$

We standardize these date features by respective corresponding maximum. For unbounded features (e.g., abs_day and $year$), we use a large number to standardize them. For example, we can use 100 to standardize $year$, then need not worry about it in our lifetime. With DERT encoding, our model shows excellent generalization when facing a date never seen before (See Table 2). Due to the complexity, equations of some date features are omitted. Email authors if interested.

D   UNIVARIATE RESULTS

Baselines   We also select 6 strong baseline models for univariate forecast comparisons, covering state-of-the-art deep learning models and classic statistical methods: FEDformer(Zhou et al., 2022), Autoformer (Wu et al., 2021), Informer (Zhou et al., 2021), N-BEATS (Oreshkin et al., 2019), DeepAR (Salinas et al., 2020), and ARIMA (Box & Jenkins, 1968).

Table 4: Univariate series forecast results. A lower MSE or MAE indicates a better prediction. The best results are highlighted in **bold** and the second best results are highlighted with a underline.

Models		**Dateformer**		FEDformer		Autoformer		Informer		N-BEATS		DeepAR		ARIMA	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
PL(96)	1	**0.040**	**0.133**	0.132	0.249	0.145	0.240	0.058	0.144	0.092	0.170	0.211	0.272	0.996	0.801
	3	**0.087**	**0.190**	0.183	0.290	0.350	0.416	0.197	0.277	0.209	0.272	0.543	0.506	1.163	0.878
	7	**0.103**	**0.212**	0.236	0.326	0.491	0.504	0.371	0.399	0.242	0.295	0.554	0.512	1.325	0.926
	30	**0.113**	**0.239**	0.516	0.507	0.841	0.696	0.418	0.470	0.430	0.448	1.758	1.063	5.594	1.292
	90	**0.135**	**0.276**	OOM	OOM	OOM	OOM	OOM	OOM	0.442	0.517	1.311	0.863	7.801	1.739
	180	**0.162**	**0.305**	OOM	OOM	OOM	OOM	OOM	OOM	OOM	OOM	1.932	1.115	9.824	2.039
Traffic(24)	1	**0.097**	**0.167**	0.181	0.288	0.257	0.361	0.211	0.304	0.139	0.229	0.326	0.399	0.461	0.499
	3	**0.118**	**0.199**	0.231	0.342	0.293	0.390	0.232	0.327	0.144	0.236	0.441	0.457	0.796	0.703
	7	**0.122**	**0.204**	0.228	0.329	0.343	0.425	0.250	0.342	0.162	0.260	0.839	0.683	1.240	0.915
	30	**0.134**	**0.221**	0.252	0.349	0.294	0.389	0.302	0.393	0.200	0.306	0.518	0.503	1.627	1.086
	90	**0.157**	**0.236**	-	-	-	-	-	-	-	-	0.695	0.617	1.739	1.130
ER(1)	96	**0.042**	**0.157**	0.069	0.206	0.097	0.238	0.341	0.508	0.235	0.378	0.179	0.342	0.086	0.190
	192	**0.079**	**0.223**	0.108	0.266	0.124	0.281	0.453	0.581	1.697	1.112	0.427	0.584	0.213	0.282
	336	**0.118**	**0.267**	0.149	0.312	0.144	0.305	0.695	0.738	5.616	2.119	0.535	0.659	0.191	0.320
	720	**0.187**	**0.344**	0.209	0.373	0.297	0.439	2.540	1.522	5.154	1.767	1.221	1.012	0.267	0.364

Univariate results In the univariate time series forecasting setting, Dateformer still achieves consistent state-of-the-art performance under all forecast setups. For the long-term forecasting setting, Dateformer gives MSE reduction: **82.3%** ($0.442 \rightarrow 0.135$, $1.932 \rightarrow 0.162$) in *PL*, **77.4%** ($0.695 \rightarrow 0.157$) in *Traffic*, **23.7%** in *ER*. Overall, Dateformer yields a **41.6%** averaged accuracy improvement among all univariate forecast setups on the given 3 representative datasets.

E ABLATION STUDIES

E.1 IMPACT OF INPUT LENGTH

In this section, we study the impact on several Transformer-based models of different input lengths. On representative 8 forecast tasks, which cover short-, middle-, and long-term forecasting on various time series datasets, we gradually extend their lookback window and record their predictive errors on different input window sizes. The results are shown in the form of line charts as follows.

Figure 7: The errors lines of several Transformers with different input lookback days of: predicting next (a) 7-day on *ETTh1*,(b) 1-day on *ETTh2*,(c) 3-day on *ETTm1*,(d) 7-day on *PL*,(e) 30-day on *ECL*,(f) 3-day on *Traffic*,(g) 1-day on *Weather*,(h) 720-day on *ER* time series.

As shown in Figure 7, with lookback window extends, Dateformer's predictive errors gradually reduce until stable, which indicates that Dateformer can leverage more information to continuously improve prediction. Although not the best under narrow lookback windows, Dateformer finally outperforms other all baseline Transformers as lookback window grows. But other Transformers may not benefit from larger input windows. Their performances are unstable, and even deteriorate as input length extends. This is against common sense: more information intake should lead to better predictions. Compared to them, the information utilization upper limit of Dateformer is higher. We can always expect better predictions by feeding longer lookback window series, at least not worse.

E.2 IMPACT OF TIME ENCODING

In this paper, we contribute 2 time-encodings: the static date-embedding that is generated by stacking more date features straightforwardly, and the dynamic date-representation that further considers date contextual information. So, we try to clarify which time-encoding is better, and how well other Transformers perform when better time-encodings are provided.

E.2.1 WHICH TIME ENCODING BETTER?

The better time-encoding should be able to represent time more accurately and accommodate more series global information. Thus, we employ the 2 time-encoding to distill time series' global information through 2 *global prediction* components with roughly the same number of parameters, and then check their *global prediction* quality. The results are shown below.

Table 5: *Global prediction* comparison using 2 time-encoding.

Datasets		*PL*			*ECL*			*Traffic*		
Forecast Days		1	30	180	1	30	180	1	7	90
Dynamic	MSE	**0.129**	**0.132**	**0.156**	**0.310**	**0.303**	**0.302**	**0.634**	**0.640**	**0.656**
Resenting	MAE	**0.264**	**0.268**	**0.297**	**0.395**	**0.392**	**0.392**	**0.355**	**0.356**	**0.362**
Static	MSE	0.177	0.181	0.193	0.316	0.306	0.305	0.655	0.659	0.669
Embedding	MAE	0.306	0.310	0.325	0.398	0.393	0.393	0.363	0.362	0.363

As shown in Table 5, the *global prediction* component that employs dynamic date-representation always contributes a better *global prediction*. This is enough to prove the effectiveness of our proposed dynamic time-representing method. In order to more intuitively show the importance of date contextual information, and how DERT pays attention to date context, we visualize some attention weight distributions of DERT encoder. The figures are shown as follows.

Figure 8: DERT encoder attention weight distributions from *PL* dataset during 2012, the darker the cell, the greater the attention weight. (a) is encoding Jan 2, Jan 1 is New Year's day; (b) is encoding Jan 24, in traditional Chinese lunar calendar, Jan 22 is New Year's Eve and Jan 23 is the Spring Festival; (c) is encoding Apr 5, Apr 4 is the Qingming Festival. (d) is encoding Oct 2, Sep 30 is the Mid-Autumn Festival in Chinese lunar calendar, and Oct 1 is National Day in Gregorian calendar.

In Figure 8, when approaching important festivals, DERT pays more attention to these festivals. The more important festival, the more concentrated attention. In China, the Spring Festival is the most important festival of a year. So, we can see the most intensive attention on the day in Figure 8b, and other days barely receive little attention. But refer to Figure 8c , although very intensive attention on Apr 4, some attention is still distributed to other days. Because the Qingming Festival is not as important as the Spring Festival. DERT won't pay excessive attention to it. This is completely in line with Chinese habits. Besides, DERT can also tackle the changeable date semantics in different calendars. In the traditional Chinese lunar calendar, Sep 30, 2012, is the Mid-Autumn Festival while Oct 1 is Chinese National Day in the Gregorian calendar. The interval between the 2 festivals change

every year, and in some years they are even on the same day. In Figure 8d, they both exert influence on Oct 2. We can't sure how their influence change when they are on the same day or on adjacent days, so let DERT learn from data. We also call the similar problem as date polysemy. Note that we didn't tell DERT which day is a festival, all knowledge about festivals is learned by itself.

E.2.2   HOW WELL OTHER TRANSFORMERS PERFORM USING BETTER TIME ENCODINGS?

These Transformer-based baselines for comparison also leverage time features to assistant predictions. They adopt the time embedding that proposed by Zhou et al. (2021). We are inspired by it too, so follow it and stack more date features into our static date-embedding. In this section, we try to clarify how well they perform when better time-encodings are provided. We modify these Transformers to employ the time-encodings mentioned in the previous section, to compare the impact of different time-encoding on them. To better understand the role of time on these sequence-modeling Transformers, we eliminate time embedding as a comparison. The results are as follows.

Table 6: Ablation of time-encoding on *ETTh1* forecast tasks with MSE metric. **Without** eliminates time-encoding. **Origin** adopts time-encoding proposed by Zhou et al. (2021). **Static** and **Dynamic** denote the static date-embedding and dynamic date-representation respectively. Note that **Origin** and **Static** are essentially the same, but **Static** just simply collects more time features.

Forecat Days	3				90			
Models	Without	Origin	Static	Dynamic	Without	Origin	Static	Dynamic
FEDformer	**0.359**	0.360	0.374	0.367	**0.853**	1.027	1.250	1.142
Autoformer	**0.415**	0.436	0.441	0.422	1.029	**0.929**	1.327	1.257
Informer	**0.695**	0.788	0.747	0.872	1.395	1.291	**1.168**	1.672
Pyraformer	0.606	0.605	0.600	**0.591**	1.064	1.100	1.079	**0.987**
Reformer	0.723	0.776	0.840	**0.699**	1.179	1.210	1.245	**1.085**
Dateformer	-	0.386	0.413	**0.369**	-	0.721	0.711	**0.691**

Table 7: Ablation of time-encoding on *Traffic* forecast tasks with MSE metric. - denotes can't train, because time-encoding is necessary for Dateformer. The best results are highlighted in **bold**.

Forecat Days	7				30			
Models	Without	Origin	Static	Dynamic	Without	Origin	Static	Dynamic
FEDformer	0.626	0.613	0.601	**0.592**	0.676	0.652	0.630	**0.624**
Autoformer	0.807	0.705	0.653	**0.641**	1.285	0.686	0.673	**0.667**
Informer	**0.751**	0.768	0.787	0.774	0.966	**0.959**	1.196	1.072
Pyraformer	0.646	**0.639**	0.644	0.671	OOM	OOM	OOM	OOM
Reformer	0.978	0.720	0.703	**0.696**	1.470	**0.683**	0.721	0.885
Dateformer	-	0.483	0.451	**0.434**	-	0.510	0.487	**0.475**

Refer to Table 6 and 7, as a time-modeling method that mainly models time, Dateformer consistently benefits from better time-encodings, thereby improving predictions. However, better time-encodings may not enhance other Transformers that mainly model series, and they only leverage time-encoding in an auxiliary style just like positional encoding. In some forecast cases, better time-encodings can improve their predictions. But in some other cases, eliminating time-encoding results in the best prediction. Their utilization of time is unstable. Besides, simply collecting more time features does not necessarily work, sometimes even encumber predictions (see 3 days prediction case in Table 6).

E.3 Ablation study about pre-training tasks

In section 2, we design 2 pre-training tasks for DERT: mean prediction and Auto-correlation prediction. Here, we check their effectiveness. We separately use pre-training task to train DERT, and compare their prediction results. The results are shown as follows.

Table 8: Comparison of Dateformer using different pre-training tasks. **Mean** adopts only pre-training task of mean prediction. **Auto** employs separate Auto-correlation prediction to pre-train DERT. **Both** combines the 2 pre-training tasks together, and it's adopted by us.

Time Series Datasets		PL			ECL			ETTm1		
Forecast Days	Metric	Mean	Auto	Both	Mean	Auto	Both	Mean	Auto	Both
1	MSE	0.044	**0.041**	0.042	0.123	0.128	**0.113**	0.328	0.336	**0.326**
	MAE	0.146	**0.138**	0.141	0.232	0.240	**0.218**	**0.355**	0.362	0.356
3	MSE	0.096	0.094	**0.076**	0.159	0.165	**0.148**	0.372	0.381	**0.370**
	MAE	0.217	0.207	**0.187**	0.265	0.275	**0.251**	0.383	0.389	**0.382**
7	MSE	0.115	0.115	**0.093**	0.173	0.181	**0.163**	0.425	0.434	**0.418**
	MAE	0.243	0.236	**0.211**	0.280	0.290	**0.266**	0.415	0.420	**0.411**
30	MSE	0.143	0.142	**0.115**	0.195	0.207	**0.187**	0.452	0.447	**0.443**
	MAE	0.284	0.277	**0.249**	0.301	0.311	**0.291**	0.453	0.451	**0.448**
90	MSE	0.165	0.171	**0.144**	0.229	0.234	**0.220**	0.735	**0.687**	0.702
	MAE	0.311	0.314	**0.291**	0.332	0.337	**0.322**	0.622	**0.600**	0.600
180	MSE	0.189	0.204	**0.176**	0.251	0.257	**0.240**	-	-	-
	MAE	0.333	0.344	**0.320**	0.349	0.353	**0.339**	-	-	-

As shown in Table 8, for pre-training DERT, the separate mean prediction or Auto-correlation prediction task is effective. But combining them can obtain better date-representations. The mean prediction will lose some intraday information of time series, so we design the Auto-correlation prediction to mitigate the problem, it can induce DERT to tap some time series intraday information.

F Training Details

There are 3 relatively independent components in Dateformer: DERT encoder, *global prediction*, and *local prediction*. They all can be trained separately. We found that Dateformers with different training stages strategies have different predictive performances. For some datasets, pre-training DERT or *global prediction* component is necessary. For other datasets, end-to-end training the entire Dateformer is also feasible. Thus, we design a 3-stage training methodology to tap the full capacity of Dateformer, and do the best on various forecast horizon demands of different datasets.

Pre-training In section 2, we introduce 2 tasks to pre-train DERT, and the first step is to pre-train the DERT encoder. Time series are split into patches by day to supervise the learning of DERT. Each task contributes half of the pre-training loss. The pre-training stage aims to provide superior time representations as a container to distill and store global information from training set.

Warm-up The second step is using the separately *global prediction* component to distill time series global information from training set, we call it warm-up phase. In warm-up, the pre-trained DERT encoder is loaded, then we train the separately *global prediction* component on training set. We insert this stage to force the *global prediction* component to remember the global characteristics of time series, so as to help Dateformer produce more robust long-range predictions. Furthermore, it also serves as the adapter when transferring a DERT from other datasets. This phase is optional, and we observed that a better short-term forecast is usually provided by the Dateformer skipping warm-up. More credible long-term predictions, however, always draw from the preheated one.

Formal training   Dateformer loads pre-trained DERT or *global prediction* component then start training. We would use a small learning rate to fine-tune the pre-trained parameters. With enough memory, Dateformer can extrapolate to any number of days in the future, once trained.

Table 9: Comparisons of different training strategies, where Dateformer[11] goes through all 3 stages. Dateformer[10] skips the warm-up, and Dateformer[01] skips the pre-training. Dateformer[00] is end-to-end trained.∗ denotes the group of results is selected to compare with other models in main text.

Models	Dateformer[11]		Dateformer[10]		Dateformer[01]		Dateformer[00]	
Metric	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAEE
PL(96) 1	0.042*	0.141*	0.032	0.119	0.044	0.142	**0.027**	**0.112**
3	**0.076***	0.187*	0.107	0.220	0.078	0.192	0.077	**0.176**
7	**0.093***	**0.211***	0.147	0.271	0.097	0.219	0.122	0.227
30	**0.115***	**0.249***	0.275	0.375	0.133	0.269	0.324	0.384
90	**0.144***	**0.291***	0.600	0.587	0.166	0.311	0.798	0.679
180	**0.176***	**0.320***	0.911	0.733	0.218	0.358	1.238	0.843
ETTm1(96) 1	0.344	0.368	**0.322***	**0.355***	0.345	0.363	0.325	0.356
3	0.383	0.396	**0.368***	**0.381***	0.389	0.390	0.369	0.382
7	0.441	0.431	**0.417***	**0.410***	0.439	0.420	0.417	0.411
30	0.494	0.487	**0.438***	**0.446***	0.477	0.472	0.440	0.447
90	0.789	0.646	**0.690***	0.600*	0.723	0.614	0.693	**0.598**
ETTh2(24) 1	0.234	0.303	**0.226**	**0.292**	0.234*	0.306*	0.228	0.295
3	0.315	0.362	**0.296**	**0.340**	0.311*	0.363*	0.299	0.345
7	0.406	0.422	**0.369**	**0.389**	0.383*	0.413*	0.372	0.394
30	0.458	0.471	0.407	0.438	0.437*	0.472*	**0.404**	**0.436**
90	0.537	0.521	0.590	0.553	**0.431***	**0.486***	0.582	0.542
ECL(24) 1	0.113*	0.218*	0.101	0.198	0.121	0.231	**0.100**	**0.198**
3	0.148*	0.251*	**0.146**	**0.237**	0.158	0.265	0.156	0.241
7	**0.163***	0.266*	0.166	**0.257**	0.175	0.284	0.175	0.261
30	**0.187***	**0.291***	0.219	0.306	0.202	0.311	0.226	0.309
90	**0.220***	**0.322***	0.334	0.391	0.239	0.346	0.354	0.399
180	**0.240***	**0.339***	0.338	0.392	0.255	0.362	0.353	0.398
Traffic(24) 1	0.341	0.248	0.340	0.240	0.343*	0.252*	**0.339**	**0.239**
3	0.459	0.293	0.557	0.321	**0.430***	**0.284***	0.484	0.293
7	0.468	0.301	0.578	0.337	**0.434***	**0.289***	0.494	0.306
30	0.503	0.319	0.621	0.362	**0.469***	**0.308***	0.543	0.332
90	0.559	0.344	0.685	0.389	**0.526***	**0.339***	0.609	0.358
Weather(144) 1	0.224	0.294	0.223	0.295	**0.220***	**0.288***	0.223	**0.286**
3	0.289	0.338	0.285	0.338	**0.281***	**0.329***	0.285	0.329
7	0.332	0.370	0.326	0.369	**0.320***	**0.360***	0.329	0.364
30	0.427	0.435	0.419	0.438	0.414*	0.428*	**0.413**	**0.422**
60	0.545	0.540	0.537	0.536	0.539*	0.531*	**0.524**	**0.524**
ER(1) 96	0.045	0.160	**0.022***	**0.107***	0.036	0.135	0.022	0.107
192	0.076	0.206	**0.043***	**0.152***	0.065	0.181	0.043	0.152
336	0.137	0.274	**0.070***	**0.195***	0.093	0.221	0.070	0.195
720	0.336	0.426	**0.112***	**0.255***	0.138	0.282	0.113	0.256

We use different training stages to train Dateformer, and results are shown in Table 9. It can be seen that different training stage setups can lead to different performances of Dateformers. There is no versatile training strategy does best on all forecast horizons of all datasets. Generally, the pre-training and warm-up can induce Dateformers to be more concerned with the global pattern of time series, and produce robust long-term predictions. For some datasets, before distilling global information from training set, pre-training a DERT encoder can enhance the distilling effect. But for other datasets, the 2 stages can be combined into one. Actually, the *global prediction* is also a fairly good pre-training task for DERT. The end-to-end trained Dateformer always contributes the best short-term predictions. Because we train Dateformer in the short-term forecasting task of 7d-predict-1d, the direct end-to-end training makes Dateformer more care local pattern of time series.

G HYPER PARAMETER SENSITIVITY

We check the robustness with respect to the hyper-parameters: pre-days and post-days paddings. We select 6 groups of paddings: (1, 1), (3, 3), (7, 7), (7, 14), (14, 14) and (30, 30). To be more intuitive, we test the *global prediction* component with above several paddings on *PL* dataset.

Table 10: Dateformer's *global prediction* performance on *PL* dataset using several paddings.

Paddings	1, 1		3, 3		7, 7		7, 14		14, 14		30, 30	
Metric	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
1	0.155	0.290	0.151	0.285	**0.127**	**0.264**	0.134	0.270	0.139	0.278	0.156	0.291
3	0.155	0.290	0.152	0.286	**0.128**	**0.264**	0.134	0.271	0.139	0.278	0.157	0.292
7	0.156	0.291	0.153	0.287	**0.128**	**0.265**	0.134	0.271	0.139	0.278	0.157	0.293
30	0.161	0.296	0.158	0.292	**0.132**	**0.269**	0.137	0.274	0.142	0.281	0.161	0.297
90	0.179	0.315	0.176	0.311	**0.145**	**0.284**	0.151	0.291	0.156	0.297	0.177	0.314
180	0.190	0.326	0.187	0.324	**0.155**	**0.295**	0.165	0.305	0.173	0.314	0.197	0.335

As shown in Table 10, too large or too small padding sizes will make the prediction performance worse. The moderate padding size (7, 7) leads to the best *global prediction*. This is also consistent with how people generally think—we don't simply consider the here and now, but also don't think too far ahead. In the main text, to balance predictive performances between various time series datasets, we use the padding size of (7, 14) instead of the best (7, 7).

H BASELINES DETAILS

In this paper, we select several state-of-the-art Transformer-based baselines for comparison. The implementations of Autoformer (Wu et al., 2021), Informer (Zhou et al., 2021), and Reformer (Kitaev et al., 2020) are from the Autoformer's repository [9]. And the implementations of FEDformer[10] (Zhou et al., 2022) and Pyraformer[11] (Liu et al., 2021) are from their respective repository. We adopt the hyper-parameters setting that is recommended in their repositories but unify the token's dimension d_{model} as 512. We fix the input series length as 96 time-steps for FEDformer, Autoformer, Informer, and Reformer. This is recommended by them or empirical results, and we founded extending their input length will result in unstable performances of these baselines (see section E.1). For Pyraformer, facing longer forecast horizons, we extend its input length as their paper recommended. For more detailed hyper-parameters setting please refer to their code repositories.

---

[9]https://github.com/thuml/Autoformer

[10]https://github.com/MAZiqing/FEDformer

[11]https://github.com/alipay/Pyraformer

I MAIN RESULTS WITH STANDARD DEVIATIONS

We repeat all experiments 3 times, and the results with standard deviations are shown in Table 11.

Table 11: Quantitative results with fluctuations of different forecast days for multivariate forecast.

Models		**Dateformer**		FEDformer		Autoformer		Informer		Pyraformer	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
PL(96)	1	$\mathbf{0.042}_{\pm0.003}$	$0.141_{\pm0.006}$	$0.105_{\pm0.001}$	$0.231_{\pm0.003}$	$0.098_{\pm0.013}$	$0.201_{\pm0.017}$	$0.067_{\pm0.002}$	$0.157_{\pm0.003}$	$0.052_{\pm0.002}$	$\mathbf{0.139}_{\pm0.002}$
	3	$\mathbf{0.076}_{\pm0.001}$	$\mathbf{0.187}_{\pm0.001}$	$0.149_{\pm0.004}$	$0.264_{\pm0.005}$	$0.405_{\pm0.022}$	$0.479_{\pm0.018}$	$0.251_{\pm0.045}$	$0.331_{\pm0.015}$	$0.134_{\pm0.003}$	$0.230_{\pm0.002}$
	7	$\mathbf{0.093}_{\pm0.001}$	$\mathbf{0.211}_{\pm0.002}$	$0.196_{\pm0.009}$	$0.303_{\pm0.007}$	$0.398_{\pm0.096}$	$0.462_{\pm0.073}$	$0.370_{\pm0.014}$	$0.424_{\pm0.005}$	$0.211_{\pm0.005}$	$0.313_{\pm0.001}$
	30	$\mathbf{0.115}_{\pm0.004}$	$\mathbf{0.249}_{\pm0.005}$	$0.423_{\pm0.020}$	$0.471_{\pm0.010}$	$0.902_{\pm0.371}$	$0.727_{\pm0.182}$	$0.373_{\pm0.013}$	$0.458_{\pm0.013}$	$0.268_{\pm0.003}$	$0.381_{\pm0.003}$
	90	$\mathbf{0.144}_{\pm0.003}$	$\mathbf{0.291}_{\pm0.004}$	OOM	OOM	OOM	OOM	OOM	OOM	$0.585_{\pm0.001}$	$0.590_{\pm0.004}$
	180	$\mathbf{0.176}_{\pm0.004}$	$\mathbf{0.320}_{\pm0.004}$	OOM	OOM	OOM	OOM	OOM	OOM	OOM	OOM
ETTm1(96)	1	$\mathbf{0.322}_{\pm0.008}$	$\mathbf{0.355}_{\pm0.004}$	$0.341_{\pm0.005}$	$0.390_{\pm0.004}$	$0.491_{\pm0.046}$	$0.476_{\pm0.014}$	$0.640_{\pm0.058}$	$0.570_{\pm0.024}$	$0.515_{\pm0.036}$	$0.505_{\pm0.020}$
	3	$\mathbf{0.368}_{\pm0.006}$	$\mathbf{0.381}_{\pm0.004}$	$0.419_{\pm0.008}$	$0.439_{\pm0.001}$	$0.598_{\pm0.029}$	$0.522_{\pm0.014}$	$0.963_{\pm0.082}$	$0.750_{\pm0.042}$	$0.849_{\pm0.061}$	$0.713_{\pm0.027}$
	7	$\mathbf{0.417}_{\pm0.006}$	$\mathbf{0.410}_{\pm0.003}$	$0.473_{\pm0.003}$	$0.468_{\pm0.004}$	$0.646_{\pm0.075}$	$0.547_{\pm0.026}$	$1.129_{\pm0.051}$	$0.800_{\pm0.040}$	$1.053_{\pm0.010}$	$0.818_{\pm0.007}$
	30	$\mathbf{0.438}_{\pm0.002}$	$\mathbf{0.446}_{\pm0.001}$	$0.547_{\pm0.029}$	$0.525_{\pm0.018}$	$0.681_{\pm0.031}$	$0.581_{\pm0.009}$	$1.132_{\pm0.005}$	$0.831_{\pm0.004}$	$1.020_{\pm0.013}$	$0.806_{\pm0.009}$
	90	$\mathbf{0.690}_{\pm0.019}$	$\mathbf{0.600}_{\pm0.007}$	OOM	OOM	OOM	OOM	OOM	OOM	$1.056_{\pm0.018}$	$0.845_{\pm0.009}$
ETTh2(24)	1	$\mathbf{0.234}_{\pm0.001}$	$\mathbf{0.306}_{\pm0.002}$	$0.246_{\pm0.012}$	$0.327_{\pm0.010}$	$0.289_{\pm0.010}$	$0.364_{\pm0.007}$	$1.606_{\pm0.198}$	$0.997_{\pm0.060}$	$0.412_{\pm0.030}$	$0.498_{\pm0.018}$
	3	$\mathbf{0.311}_{\pm0.005}$	$\mathbf{0.363}_{\pm0.002}$	$0.334_{\pm0.011}$	$0.381_{\pm0.003}$	$0.347_{\pm0.008}$	$0.395_{\pm0.004}$	$1.928_{\pm0.283}$	$1.111_{\pm0.087}$	$1.140_{\pm0.033}$	$0.832_{\pm0.014}$
	7	$\mathbf{0.383}_{\pm0.010}$	$\mathbf{0.413}_{\pm0.005}$	$0.412_{\pm0.004}$	$0.426_{\pm0.002}$	$0.451_{\pm0.019}$	$0.451_{\pm0.014}$	$6.200_{\pm0.470}$	$2.024_{\pm0.065}$	$4.877_{\pm0.752}$	$1.747_{\pm0.158}$
	30	$\mathbf{0.437}_{\pm0.015}$	$\mathbf{0.472}_{\pm0.002}$	$0.466_{\pm0.010}$	$0.483_{\pm0.003}$	$0.510_{\pm0.004}$	$0.511_{\pm0.004}$	$4.091_{\pm0.180}$	$1.717_{\pm0.032}$	$4.674_{\pm0.293}$	$1.869_{\pm0.055}$
	90	$\mathbf{0.431}_{\pm0.033}$	$\mathbf{0.486}_{\pm0.008}$	$0.719_{\pm0.035}$	$0.618_{\pm0.017}$	$0.702_{\pm0.056}$	$0.631_{\pm0.032}$	$2.571_{\pm0.023}$	$1.217_{\pm0.011}$	$3.330_{\pm0.036}$	$1.511_{\pm0.014}$
ECL(24)	1	$\mathbf{0.113}_{\pm0.002}$	$\mathbf{0.218}_{\pm0.003}$	$0.169_{\pm0.001}$	$0.288_{\pm0.001}$	$0.174_{\pm0.006}$	$0.293_{\pm0.007}$	$0.328_{\pm0.009}$	$0.412_{\pm0.006}$	$0.268_{\pm0.006}$	$0.372_{\pm0.006}$
	3	$\mathbf{0.148}_{\pm0.002}$	$\mathbf{0.251}_{\pm0.002}$	$0.186_{\pm0.001}$	$0.302_{\pm0.001}$	$0.215_{\pm0.024}$	$0.329_{\pm0.020}$	$0.358_{\pm0.006}$	$0.430_{\pm0.006}$	$0.308_{\pm0.007}$	$0.388_{\pm0.004}$
	7	$\mathbf{0.163}_{\pm0.002}$	$\mathbf{0.266}_{\pm0.003}$	$0.201_{\pm0.002}$	$0.316_{\pm0.002}$	$0.208_{\pm0.007}$	$0.320_{\pm0.006}$	$0.387_{\pm0.009}$	$0.459_{\pm0.006}$	$0.281_{\pm0.008}$	$0.381_{\pm0.008}$
	30	$\mathbf{0.187}_{\pm0.001}$	$\mathbf{0.291}_{\pm0.002}$	$0.242_{\pm0.002}$	$0.351_{\pm0.003}$	$0.259_{\pm0.005}$	$0.364_{\pm0.005}$	$0.400_{\pm0.008}$	$0.460_{\pm0.004}$	$0.288_{\pm0.005}$	$0.382_{\pm0.004}$
	90	$\mathbf{0.220}_{\pm0.003}$	$\mathbf{0.322}_{\pm0.003}$	$0.316_{\pm0.008}$	$0.404_{\pm0.006}$	$0.382_{\pm0.066}$	$0.439_{\pm0.033}$	$0.550_{\pm0.019}$	$0.552_{\pm0.011}$	OOM	OOM
	180	$\mathbf{0.240}_{\pm0.002}$	$\mathbf{0.339}_{\pm0.003}$	-	-	-	-	-	-	-	-
Traffic(24)	1	$\mathbf{0.343}_{\pm0.004}$	$\mathbf{0.252}_{\pm0.001}$	$0.547_{\pm0.004}$	$0.357_{\pm0.004}$	$0.554_{\pm0.006}$	$0.363_{\pm0.008}$	$0.678_{\pm0.018}$	$0.383_{\pm0.017}$	$0.600_{\pm0.002}$	$0.337_{\pm0.001}$
	3	$\mathbf{0.430}_{\pm0.007}$	$\mathbf{0.284}_{\pm0.003}$	$0.581_{\pm0.003}$	$0.367_{\pm0.002}$	$0.625_{\pm0.041}$	$0.391_{\pm0.025}$	$0.721_{\pm0.023}$	$0.404_{\pm0.013}$	$0.635_{\pm0.005}$	$0.358_{\pm0.005}$
	7	$\mathbf{0.434}_{\pm0.006}$	$\mathbf{0.289}_{\pm0.002}$	$0.613_{\pm0.001}$	$0.382_{\pm0.001}$	$0.705_{\pm0.009}$	$0.439_{\pm0.008}$	$0.768_{\pm0.021}$	$0.425_{\pm0.011}$	$0.639_{\pm0.005}$	$0.356_{\pm0.004}$
	30	$\mathbf{0.469}_{\pm0.004}$	$\mathbf{0.308}_{\pm0.002}$	$0.652_{\pm0.001}$	$0.395_{\pm0.003}$	$0.686_{\pm0.020}$	$0.420_{\pm0.011}$	$0.959_{\pm0.030}$	$0.534_{\pm0.017}$	OOM	OOM
	90	$\mathbf{0.526}_{\pm0.002}$	$\mathbf{0.339}_{\pm0.001}$	-	-	-	-	-	-	-	-
Weather(144)	1	$\mathbf{0.220}_{\pm0.001}$	$\mathbf{0.288}_{\pm0.002}$	$0.234_{\pm0.001}$	$0.304_{\pm0.002}$	$0.327_{\pm0.023}$	$0.377_{\pm0.017}$	$0.370_{\pm0.029}$	$0.424_{\pm0.022}$	$0.231_{\pm0.011}$	$0.310_{\pm0.011}$
	3	$\mathbf{0.281}_{\pm0.002}$	$\mathbf{0.329}_{\pm0.002}$	$0.338_{\pm0.001}$	$0.375_{\pm0.004}$	$0.370_{\pm0.009}$	$0.402_{\pm0.006}$	$0.628_{\pm0.008}$	$0.560_{\pm0.006}$	$0.388_{\pm0.011}$	$0.427_{\pm0.010}$
	7	$\mathbf{0.320}_{\pm0.005}$	$\mathbf{0.360}_{\pm0.001}$	$0.495_{\pm0.112}$	$0.472_{\pm0.068}$	$0.474_{\pm0.044}$	$0.461_{\pm0.035}$	$1.093_{\pm0.057}$	$0.768_{\pm0.024}$	$0.442_{\pm0.007}$	$0.460_{\pm0.002}$
	30	$\mathbf{0.414}_{\pm0.005}$	$\mathbf{0.428}_{\pm0.003}$	$0.688_{\pm0.021}$	$0.580_{\pm0.011}$	$0.724_{\pm0.008}$	$0.604_{\pm0.005}$	$2.789_{\pm0.326}$	$1.303_{\pm0.061}$	$0.823_{\pm0.007}$	$0.676_{\pm0.005}$
	60	$\mathbf{0.539}_{\pm0.010}$	$\mathbf{0.531}_{\pm0.003}$	-	-	-	-	-	-	-	-
ER(1)	96	$\mathbf{0.022}_{\pm0.001}$	$\mathbf{0.107}_{\pm0.001}$	$0.041_{\pm0.002}$	$0.154_{\pm0.004}$	$0.040_{\pm0.001}$	$0.154_{\pm0.003}$	$0.248_{\pm0.005}$	$0.361_{\pm0.003}$	$0.194_{\pm0.006}$	$0.340_{\pm0.005}$
	192	$\mathbf{0.043}_{\pm0.001}$	$\mathbf{0.152}_{\pm0.001}$	$0.062_{\pm0.001}$	$0.194_{\pm0.002}$	$0.061_{\pm0.002}$	$0.193_{\pm0.004}$	$0.430_{\pm0.063}$	$0.474_{\pm0.030}$	$0.337_{\pm0.013}$	$0.440_{\pm0.008}$
	336	$\mathbf{0.070}_{\pm0.001}$	$\mathbf{0.195}_{\pm0.001}$	$0.087_{\pm0.002}$	$0.233_{\pm0.005}$	$0.096_{\pm0.007}$	$0.246_{\pm0.008}$	$0.756_{\pm0.056}$	$0.642_{\pm0.028}$	$0.607_{\pm0.110}$	$0.600_{\pm0.060}$
	720	$\mathbf{0.112}_{\pm0.001}$	$\mathbf{0.255}_{\pm0.001}$	$0.165_{\pm0.006}$	$0.317_{\pm0.005}$	$0.389_{\pm0.313}$	$0.422_{\pm0.131}$	$1.073_{\pm0.021}$	$0.773_{\pm0.011}$	$0.963_{\pm0.030}$	$0.772_{\pm0.011}$

J SHOWCASES

In order to more intuitively show Dateformer's prediction results, we visualized the ground-truth time series and predictions of several forecast tasks. The charts are shown as follows.

(a) Dateformer	(b) FEDformer	(c) Autoformer	(d) Informer

Figure 9: 3 days prediction cases from *ETTm1* oil temperature series

It can be seen that Dateformer's predictions are closest to the ground-truth. Compared to other models, Dateformer accurately grasps time series' global pattern: e.g., overall trend and long-range seasonality, that is what other models are not good at. Because they can only look lookback window series to predict. But the global pattern must be captured from whole training set series.

Figure 10: 3 days prediction cases from *ETTh2* oil temperature series

Figure 11: 7 days prediction cases from *Traffic* series

Figure 12: 7 days prediction cases from *P*ower *L*oad series

Figure 13: Mid-long-term prediction cases of Dateformer from *P*ower *L*oad series