Sequential Latent Variable Models for Few-Shot High-Dimensional Time-Series Forecasting

Abstract

Modern applications increasingly require learning and forecasting latent dynamics from high-dimensional time-series. Compared to univariate time-series forecasting, this adds a new challenge of reasoning about the latent dynamics of an *unobserved* abstract state. Sequential latent variable models (LVMs) present an attractive solution, although existing works either struggle with long-term forecasting or have difficulty learning across diverse dynamics. In this paper, we first present a conceptual framework of sequential LVMs to unify existing works, contrast their fundamental limitations, and identify an intuitive solution to *long-term forecasting for diverse dynamics* via meta-learning. We then present the first framework of few-shot forecasting for high-dimensional time-series: instead of learning a single dynamic function, we leverage data of diverse dynamics and learn to adapt latent dynamic functions to few-shot support series. This is realized via Bayesian meta-learning underpinned by: 1) a latent dynamic function conditioned on knowledge derived from few-shot support series, and 2) a meta-model that learns to extract such dynamic-specific knowledge via feed-forward embedding of support set. We compared the presented framework with a comprehensive set of baseline models trained 1) globally on the large meta-training set with diverse dynamics, and 2) individually on single dynamics, both with and without fine-tuning to k-shot support series used by the meta-models. We demonstrated that the presented framework is agnostic to the latent dynamic function of choice and, at meta-test time, is able to forecast for new dynamics given variable-shot of support series.

1 Instruction

In many applications, an ultimate goal is to forecast the future states or trajectories of a dynamic system from its high-dimensional observations such as series of images. Compared to the relatively well-studied *univariate* time-series forecasting (Makridakis et al., 2018; Oreshkina et al., 2020; Salinas et al., 2020), *high-dimensional* time-series forecasting raise new challenges: it requires the extraction of the dynamics of an abstract latent state that is not directly observed (Botev et al., 2021).

Sequential latent variable models (LVMs) provide an attractive solution that, unlike autoregressive models, abstracts a a latent dynamic function $\mathbf{z}_i = f(\mathbf{z}_{<i}; \boldsymbol{\theta}_z)$ with state $\mathbf{z}_i$ and parameter $\boldsymbol{\theta}_z$, in separation from $\mathbf{z}_i$'s emission to high-dimensional observations $\mathbf{x}_i = g(\mathbf{z}_i)$ (Chung et al., 2015). Once learned, this pair of models can support long-term forecasting given only initial frames of observations. They may also support controlled generation of new dynamics similar to the generation of static images. Despite rapid progress, however, critical bottlenecks remain in reaching these goals.

The earlier formulation of sequential LVMs relies on a natural extension of the static LVMs: as illustrated in Fig. 1A, the latent state $\mathbf{z}_i$ is modeled as the latent variable for the generation of $\mathbf{x}_i$, and a sequential encoder is used to facilitate the inference of $\mathbf{z}_i$ from current and past observations $\mathbf{x}_{\leq i}$ (Chung et al., 2015; Krishnan et al., 2017). Recent works have argued to instead model and infer the parameter of the latent dynamic function $\boldsymbol{\theta}_z$: till now, existing approaches assumed linearized latent dynamic functions at each time instant i, with time-varying linear coefficients $\boldsymbol{\theta}_{z,i}$ (Karl et al., 2017; Fraccaro et al., 2017; Rangapuram et al., 2018; Klushyn et al., 2021). This results in a LVM formulation as illustrated in Fig. 1B1, where the latent variable $\boldsymbol{\theta}_{z,i}$ is inferred

Figure 1: Sequential latent-variable models for forecasting high-dimensional sequences.

at each i from observations $\mathbf{x}_{\leq i}$. While strong at time-series reconstructions and classifications, a fundamental limitation make these sequential LVMs less suited for the purpose of long-term forecasting: the generative ability of the latent dynamic function to forecast is weakened without near-term observations to support the explicit modeling and inference of $\mathbf{z}_i$ or $\boldsymbol{\theta}_{z,i}$.

This limitation in the mainstream sequential LVMs raises a natural question: are we able to relax the assumption of linear dynamic function and directly infer its $\boldsymbol{\theta}_z$? Works adopting this idea have emerged: as illustrated in Fig. 1B2, by modeling a single $\boldsymbol{\theta}_z$ – either deterministic (Rubanova et al., 2019; Botev et al., 2021) or stochastic (Yildiz et al., 2020) – $f(\mathbf{z}_{<i}; \boldsymbol{\theta}_z)$ is asked to predict a time sequence using only an inferred initial state. This formulation has shown strong long-term forecasting, although with its own fundamental limitation: it learns a *single dynamic function* global to all training sequences. This would not only require all training data to share identical latent dynamics, but also has difficulty to forecast for test sequences with dynamics different from or unknown to the training.

In this paper, we answer this important open question of *long-term forecasting for diverse dynamics*. We first present a conceptual framework of sequential LVMs to unify existing works, and identify an intuitive solution to the underlying critical gap via meta-learning: instead of *learning a single dynamic function*, we can learn to pull knowledge across datasets of different dynamics and *learn to adapt a dynamic function* to few-shot high-dimensional time-series. We then present a Bayesian meta-learning framework as illustrated in Fig. 1C: instead of being a single fixed function as in Fig. 1B2, we let the latent dynamic function be conditioned on knowledge derived from few-shot support time-series via a feed-forward set-embedding meta-model; given k-shot time-series of a specific dynamics, the model is asked to forecast for query time-series using only the initial frames, meta-learned across varying dynamics. We develop this framework to be agnostic to the latent dynamic functions of choice, and with the flexibility to forecast with variable size of k.

We evaluated the presented framework in benchmark image sequences with mixed physics including bouncing balls (Fraccaro et al., 2017), pendulum (Botev et al., 2021), and mass spring Botev et al. (2021). We further applied it to forecasting real-world physics of the diffusion-reaction of electrical waves over 3D geometrical meshes of the heart. Without prior works in few-shot high-dimensional time-series forecasting, we evaluated the presented work with sequential LVMs representative each of the formulations in Fig. 1A-B, along with a recent autoregressive model designed to learn to forecast for diverse dynamics (Donà et al., 2020). Each baseline model was trained on 1) the large meta-training set with diverse dynamics and 2) individually for each dynamics, both with and without fine-tuning to k-shot support data when needed. Experimental results demonstrated clear margins of improvements by the presented work in forecasting diverse dynamics, with added ability to recognize clusters of distinct dynamics and allow controlled time-series generation given only initial conditions.

2 RELATED WORKS & BACKGROUND

Sequential LVMs: Related works on learning a latent dynamic function from high-dimensional time-series have been presented under different terminologies, such as variational latent recurrent

models (Chung et al., 2015; Rubanova et al., 2019; Yildiz et al., 2020), deep state space models (SSM) (Krishnan et al., 2017; Karl et al., 2017; Fraccaro et al., 2017; Rangapuram et al., 2018; Li et al., 2019; Klushyn et al., 2021), and deterministic encoding-decoding models (Botev et al., 2021). Among the first is the variational recurrent neural networks (VRNN) (Chung et al., 2015), followed by a series of deep SSM models (Krishnan et al., 2017; Li et al., 2019) focused on modeling the dependence of the posterior and transitional density of the latent state $\mathbf{z}_k$ on past latent states $\mathbf{z}_{<k}$ and observations $\mathbf{x}_{<k}$ (Fig. 1A). Alternatively, there has been a line of deep SSMs that aims to infer the parameters of the latent dynamic function instead (Karl et al., 2017; Fraccaro et al., 2017; Rangapuram et al., 2018; Klushyn et al., 2021). Till now all existing approaches assumed linear latent dynamics, where the linear transition matrix at each time frame k is modeled as a linear combination of a set of global matrices. The linear coefficients are time-varying and to be inferred from observations $\mathbf{x}_{<k}$ as illustrated in Fig. 1B1. In both formulations, the reliance on inferred time-varying inputs to the latent dynamic function (states or parameters) reduces its ability to forecast without near-term observations.

In parallel, a set of models (Fig. 1B2) have been presented that aims to learn a latent dynamic function that forecast a sequence using only an inferred initial state, in stochastic (Rubanova et al., 2019; Yildiz et al., 2020) or deterministic forms (Botev et al., 2021). The resulting latent dynamic function is strong at forecasting, albeit only a single function is learned at a time. We build on and advance this formulation to learning to learn a dynamic-specific function from few-shot observations.

Modeling switching dynamics in sequential LVMs, often based on the formulation in Fig. 1A, shares the presented idea of using context variables to control the latent dynamics (Becker-Ehmck et al., 2019; Linderman et al., 2017). They however are concerned with the switching of dynamics within a time-series, whereas we are interested in learning to learn dynamics from k-shot support series.

Sequential neural processes (SNPs) are also sequential LVMs based on the formulation in Fig. 1A (Singh et al., 2019; Qin et al., 2019). Similar to the presented work, SNPs are underlined by Bayesian meta-learning. They however are concerned with using partially observed frames within a time-series as support sets, for the query of unobserved frames in the same time-series.

Autoregressive dynamic modeling: Autoregressive models are also popular for modeling and forecasting dynamics, especially for approximating physics-based simulations (Wang et al., 2020; Pfaff et al., 2020). Some recent works have focused on the issue of generalizing across dynamics by, for instance, disentangling spatial and temporal modeling (Donà et al., 2020) or learning dynamic-specific functions in addition to a global dynamic function (Yin et al., 2021). None of these works considered meta-learning or few-shot adaption of dynamic functions as a solution, nor can autoregressive models support controlled generation of synthesized time-series as we will demonstrate in Section 5.

General few-shot learning: Few-shot learning has seen substantial progress with static data. Recent types of meta-models include weight initialization (Finn et al., 2017; Yoon et al., 2018), model optimizers (Ravi & Larochelle, 2016), and feed-forward models to condition (Garnelo et al., 2018) or parameterize the primary networks (Bertinetto et al., 2016; Sung et al., 2018). Compared to the former two, feed-forward meta-models replace test-time optimization with simple feed-forward passes using support data. It thus constitutes the basis of the presented few-shot forecasting methods.

Few-shot time-series forecasting: Meta-learning is well studied in univariate time-series forecasting (Montero-Manso et al., 2020) including recent deep-learning advances (Oreshkin et al., 2021). Few-shot forecasting for high-dimensional time-series, however, has not been attempted to our knowledge.

3 Unifying conceptual framework for learning latent dynamics

We first describe a LVM framework that unifies existing works under two choices of probabilistic graphical models (PGMs). It includes a dynamic function of latent $\mathbf{z}_k$ and its emission to data $\mathbf{x}_k$: $\mathbf{z}_k = f(\mathbf{z}_{<k}; \boldsymbol{\theta}_z), \mathbf{x}_k = g(\mathbf{z}_k)$, where $\boldsymbol{\theta}_z$ represents the parameter of the latent dynamic function.

System states as latent variables: One natural choice of the latent variable is the latent state $\mathbf{z}_k$ underlying the observations $\mathbf{x}_k$. This gives rise to the PGM as illustrated in Fig. 1A, where the marginal likelihood of an observed sequence $\mathbf{x}_{0:T}$ can be expressed as:

$$p(\mathbf{x}_{0:T}) = \int_{\mathbf{z}_{0:T}} p(\mathbf{x}_0|\mathbf{z}_0)p(\mathbf{z}_0) \prod_{i=1}^{T} p(\mathbf{x}_i|\mathbf{z}_i)p(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{<i})d\mathbf{z}_{0:T} \tag{1}$$

where $p(\mathbf{x}_i|\mathbf{z}_i)$ describes emission and $p(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{<i})$ describes latent dynamics. To facilitate inference, a variational approximation of the posterior density $q(\mathbf{z}_{0:T}|\mathbf{x}_{0:T})$ is often modeled as:

$$q(\mathbf{z}_{0:T}|\mathbf{x}_{0:T}) = \prod\nolimits_{i=1}^{T} q(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{\leq i}) \tag{2}$$

The evidence lower bound (ELBO) of Equation (1) can then be derived as:

$$\log p(\mathbf{x}_{0:T}) \geq \sum\nolimits_{i=0}^{T} \mathbb{E}_{q(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{\leq i})}\left[\log p(\mathbf{x}_i|\mathbf{z}_i)\right] - \mathrm{KL}(q(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{\leq i})||p(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{<i})) \tag{3}$$

Existing works adopting this PGM (Chung et al., 2015; Krishnan et al., 2017; Li et al., 2019) differ primarily in how $p(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{<i})$ and $q(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{\leq i})$ are modeled. The first term above encourages reconstruction using the inferred $q(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{\leq i})$ at each time frame i; this weakens the latent dynamic function underlying $p(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{<i})$ that is constrained only by the KL-divergence term. This leads to limited ability to forecast without near-term $\mathbf{x}_{\leq i}$ to support the inference of $q(\mathbf{z}_i|\mathbf{z}_{<i}, \mathbf{x}_{\leq i})$.

System parameters as latent variables: An alternative choice of the latent variable are the parameters themselves of the LVM equation, especially $\boldsymbol{\theta}_z$ of the latent dynamic function. This gives rise to the PGM in Fig. 1B, where the marginal likelihood of $\mathbf{x}_{0:T}$ can now be expressed as:

$$p(\mathbf{x}_{0:T}) = \int_{\mathbf{z}_0} p(\mathbf{x}_0|\mathbf{z}_0)p(\mathbf{z}_0)d\mathbf{z}_0 \int_{\boldsymbol{\theta}_z} \prod\nolimits_{i=1}^{T} p(\mathbf{x}_i|\mathbf{z}_i)|_{\mathbf{z}_i = f(\mathbf{z}_{<i};\boldsymbol{\theta}_z)} d\boldsymbol{\theta}_z \tag{4}$$

where the observations are explained by an initial latent state $\mathbf{z}_0$ and parameter $\boldsymbol{\theta}_z$ of the latent dynamic function. With a variational approximation of the posterior density $q(\boldsymbol{\theta}_z, \mathbf{z}_0)$ and an assumption of their prior densities $p(\mathbf{z}_0)$ and $p(\boldsymbol{\theta}_z)$, the ELBO of Equation (4) becomes:

$$\log p(\mathbf{x}_{0:T}) \geq \mathbb{E}_{q(\boldsymbol{\theta}_z, \mathbf{z}_0)}\left[\log p(\mathbf{x}_{0:T}|\mathbf{z}_0, \boldsymbol{\theta}_z)\right] - \mathrm{KL}(q(\mathbf{z}_0)||p(\mathbf{z}_0)) - \mathrm{KL}(q(\boldsymbol{\theta}_z)||p(\boldsymbol{\theta}_z)) \tag{5}$$

This covers different lines of existing works depending on how $q(\boldsymbol{\theta}_z)$ and $p(\boldsymbol{\theta}_z)$ are modeled. In a series of works (Karl et al., 2017; Fraccaro et al., 2017; Rangapuram et al., 2018; Klushyn et al., 2021), $\boldsymbol{\theta}_z$ is modeled as time-varying system parameters $\boldsymbol{\theta}_{z,0:T}$. This involves intricate temporal modeling of $q(\boldsymbol{\theta}_{z,i}|\mathbf{x}_{\leq i})$ and $p(\boldsymbol{\theta}_{z,i}|\mathbf{z}_{\leq i})$ over time as illustrated in Fig. 1B1. Because the latent dynamic function relies on time-varying $\boldsymbol{\theta}_{z,0:T}$, its forecasting again relies on near-term observations to support the inference of $\boldsymbol{\theta}_{z,i}$. Alternatively, $q(\boldsymbol{\theta}_z)$ can be simply assumed to be global across observations and the dynamic function becomes a Bayesian neural network as presented by (Yildiz et al., 2020). As a more special case, $\boldsymbol{\theta}_z$ can be deterministic which leads to the latent ODE model presented by (Rubanova et al., 2019). If we further assume $\mathbf{z}_0$ to be deterministic, we arrive at the set of deterministic encoding-decoding network with latent dynamic functions examined by (Botev et al., 2021). This set of formulations, as summarized in Fig. 1B2, shares the advantage of strong long-term forecasting, albeit a fundamental limitation in learning a single dynamic function at a time.

In Section 5, we will include representative models from each PGM to provide empirical evidence for the identified limitations. With this basis, we derive an intuitive solution to the identified critical gaps by extending the PGM in Fig. 1B2 to the presented PGM in Fig. 1C: instead of learning a single dynamic function, we will learn to adapt a latent dynamic function to few-shot support time-series.

4 FEW-SHOT FORECASTING VIA BAYESIAN META-LEARNING

Consider a dataset $\mathcal{D}$ of high-dimensional time-series with M similar but distinct underlying dynamics: $\mathcal{D} = \{\mathcal{D}_j\}_{j=1}^{M}$. For each $\mathcal{D}_j$, we consider disjoint few-shot *support* series $\mathcal{D}_j^s = \{\mathbf{x}_{0:T}^{s,1}, \mathbf{x}_{0:T}^{s,2}, ..., \mathbf{x}_{0:T}^{s,k}\}$ and *query* series $\mathcal{D}_j^q = \{\mathbf{x}_{0:T}^{q,1}, \mathbf{x}_{0:T}^{q,2}, ..., \mathbf{x}_{0:T}^{q,l}\}$ where $k \ll l$. Instead of maximizing the marginal likelihood of $\mathbf{x}_{0:T}$ for all $\mathbf{x}_{0:T} \in \mathcal{D}$ as in Equation (4), we formulate a meta-objective to learn to maximize the marginal likelihood of $\mathbf{x}_{0:T}^q$ for all query series $\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q$ when conditioned on support series $\mathcal{D}_j^s$, for all dynamics $j \in \{1, 2, ..., M\}$:

$$p(\mathbf{x}_{0:T}^q|\mathcal{D}_j^s) = \int_{\mathbf{c}} p(\mathbf{x}_{0:T}^q|\mathbf{c})p(\mathbf{c}|\mathcal{D}_j^s)d\mathbf{c}, \quad \mathbf{x}_{0:T}^q \in \mathcal{D}_j^q \tag{6}$$

where $p(\mathbf{x}_{0:T}^q|\mathbf{c})$, though similar to Equation (4), is now conditioned on (thus adapted to) knowledge derived from support series of a specific dynamics. $p(\mathbf{c}|\mathcal{D}_j^s)$ is the meta-model describing how to extract such dynamic-specific knowledge from few-shot support set $\mathcal{D}_j^s$.

Set-conditioned latent dynamic functions: We model $p(\mathbf{x}_{0:T}^q|\mathbf{c})$ based on Equation (4) as:

$$p(\mathbf{x}_{0:T}^q|\mathbf{c}) = \int_{\mathbf{z}_0} p_{\theta_x}(\mathbf{x}_0|\mathbf{z}_0)p(\mathbf{z}_0)d\mathbf{z}_0 \prod_{i=1}^{T} p_{\theta_x}(\mathbf{x}_i|\mathbf{z}_i)|_{\mathbf{z}_i = f(\mathbf{z}_{i-1},\mathbf{c};\theta_z)} \tag{7}$$

where the latent dynamic function is parameterized by $\boldsymbol{\theta}_z$ but conditioned on embedding $\mathbf{c}$ from the support set. To focus on $\mathbf{c}$, we assume $\boldsymbol{\theta}_z$ to be deterministic and global as in (Rubanova et al., 2019; Botev et al., 2021). As an example, we can describe $\mathbf{z}_i = \tilde{\mathbf{z}}_{i-1} + \Delta\mathbf{z}_i$ where $\Delta\mathbf{z}_i$ conditions gated recurrent units (GRUs) (Chung et al., 2014) on $\mathbf{c}$, as detailed in Appendix B. This conditioning can be generalized to other functional form of $f(\cdot)$, which we will demonstrate in experiments.

Meta-model for amortized variational inference: We model $p_\zeta(\mathbf{c}|\mathcal{D}_j^s)$ with a meta-model parameterized by ζ in the form of feed-forward embedding of support set $\mathcal{D}_j^s$. Specifically, each support sequence $\mathbf{x}_{0:T}^s \in \mathcal{D}_j^s$ is first encoded through a neural function $h_\phi(\mathbf{x}_{0:T}^s)$ with blocks of interlaced spatial convolution and temporal compression layers. To extract knowledge shared by the set, the embedding from all sequences in $\mathcal{D}_j^s$ is aggregated by an averaging function: $\frac{1}{k}\sum_{\mathbf{x}_{0:T}^s \in \mathcal{D}_j^s} h_\phi(\mathbf{x}_{0:T}^s)$, where k is the size of the support set. The value of k can be fixed or variable in our framework. This set embedding parameterizes $p_\zeta(\mathbf{c}|\mathcal{D}_j^s) \sim \mathcal{N}(\boldsymbol{\mu}_c, \boldsymbol{\sigma}_c^2)$ via separate linear layers.

To enable inference, we approximate the posterior density $p(\mathbf{c}|\mathcal{D}_j^s, \mathbf{x}_{0:T}^q)$ as $q_\zeta(\mathbf{c}|\mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)$, sharing the same meta set-embedding model by augmenting $\mathcal{D}_j^s$ with $\mathbf{x}_{0:T}^q$. The ELBO of Equation (6) across all dynamics $\mathcal{D} = \{\mathcal{D}_j\}_{j=1}^M$ can then be derived as:

$$\sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \log p(\mathbf{x}_{0:T}^q|\mathcal{D}_j^s) \geq \sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \mathbb{E}_{q_\phi(\mathbf{z}_0^q),q_\zeta(\mathbf{c}|\mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)}[\log p_{\theta_x}(\mathbf{x}_{0:T}^q|\mathbf{z}_0^q,\mathbf{c})] \tag{8}$$

$$-\text{KL}(q_\phi(\mathbf{z}_0^q|\mathbf{x}_{0:l_{z_0}}^q)||p(\mathbf{z}_0)) - \text{KL}\left(q_\zeta(\mathbf{c}|\mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)||p_\zeta(\mathbf{c}|\mathcal{D}_j^s)||\right)$$

where $q_\phi(\mathbf{z}_0^q|\mathbf{x}_{0:l_{z_0}}^q) \sim \mathcal{N}(\boldsymbol{\mu}_{z_0}, \boldsymbol{\sigma}_{z_0}^2)$ is parameterized by an encoder with $l_{z_0} = 2$ in all experiments. $p(\mathbf{z}_0)$ is assumed to be $\mathcal{N}(0,\mathbf{I})$. The likelihood term is estimated with reparameterization trick (Kingma & Welling, 2013), and the KL-divergence terms are calculated analytically.

The optimization of Equation (8) is realized via episodic training common to meta-training where, in each training episode, data in each dynamic set $\mathcal{D}_j$ is divided into disjoint support set $\mathcal{D}_j^s$ and query set $\mathcal{D}_j^q$. The model is asked to – using k-shot support series – forecast the *full* query series initialized with only the initial state (inferred from l_{z_0} frames), across all dynamics.

5 EXPERIMENTS ON BENCHMARK IMAGE SEQUENCES

Data: We first considered benchmark images generated with controllable physics, including bouncing ball Fraccaro et al. (2017), Hamiltonian pendulum (Botev et al., 2021), and Hamiltonian mass spring systems (Botev et al., 2021). Details of data generation are available in Appendix F.

While existing works typically considered training a model from data created with each single dynamics above, we intentionally created training and testing data with diverse dynamics. This includes 1) a bouncing ball dataset with 16 different directions of gravity, each with 3000 samples simulated using a combination of different initial positions and velocities (*gravity-16*); and 2) a mixed-physics dataset consisting of bouncing balls under 4 gravity directions, and pendulums and mass springs each with four different values of friction coefficients of $0, 0.05, 0.1, 0.15$ (*mixed-physics*). Each physics with a unique parameter is represented by 3000 samples.

Models: Without prior works in few-shot high-dimensional time-series forecasting, we consider baseline models representative of each formulation outlined in Fig. 1A-B. This includes VRNN Chung et al. (2015) and DKF Krishnan et al. (2017) representing Fig. 1A1, DVBF Karl et al. (2017) and KVAE Fraccaro et al. (2017) representing Fig. 1B1, and three models representing Fig. 1B2 with choices of latent dynamic functions as residual GRUs, neural ordinary differential equation (NODE), and a residual version of the Recurrent Generative Network (RGN-res) (Botev et al., 2021). We also consider a recent autoregressive model designed to tackle forecasting diverse dynamics (Donà et al., 2020). All baseline models were 1) trained using the entire meta-training data consisting of mixed dynamics, 2) trained in 1) and further fine-tuned to the meta-test k-shot support set ($k = 15$)

Table 1: Comparison of the presented meta-models with all baselines trained on the meta-training set for gravity-16 data. The improvement of meta-GRU-res (best-performing) over its closest baseline is statistically significant in all metrics ($p < 0.01$, paired t-test).

PGM type	Model	MSE↓	VPT-MSE↑	Dist↓	VPT-Dist↑
Fig. 1C	meta-GRU-res	**1.44(0.34)e-2**	**0.68(0.26)**	**2.88(1.45)**	**0.97(0.07)**
	meta-NODE	1.60(0.26)e-2	0.58(0.22)	6.10(2.63)	0.80(0.12)
	meta-RGN-res	1.59(0.24)e-2	0.56(0.21)	6.97(3.08)	0.76(0.13)
Fig. 1B2	GRU-res	1.63(0.21)e-2	0.50(0.17)	10.4(3.30)	0.61(0.09)
	GRU-res finetune	1.65(0.24)e-2	0.50(0.18)	9.35(3.33)	0.66(0.12)
	NODE	1.69(0.18)e-2	0.48(0.16)	10.9(3.32)	0.59(0.08)
	NODE finetune	1.70(0.19)e-2	0.48(0.17)	10.4(3.23)	0.61(0.09)
	RGN-res	1.70(0.17)e-2	0.47(0.16)	11.2(3.39)	0.58(0.09)
	RGN-res finetune	1.72(0.19)e-2	0.47(0.17)	10.0(3.36)	0.62(0.11)
Fig. 1B1	DVBF	2.32(14.4)e-2	0.02(0.10)	45.3(0.00)	0.00(0.00)
	DVBF finetune	2.33(13.4)e-2	0.02(0.10)	45.3(0.00)	0.00(0.00)
	KVAE	3.37(1.36)e-2	0.24(0.19)	4.81(3.61)	0.57(0.29)
Fig. 1A	DKF	4.01(0.29)e-2	0.10(0.05)	10.3(3.11)	0.48(0.20)
	DKF finetune	4.01(0.29)e-2	0.10(0.05)	10.3(3.12)	0.48(0.20)
	VRNN	1.78(10.9)e-2	0.24(0.11)	23.1(21.6)	0.51(0.07)
	VRNN finetune	2.15(12.2)e-2	0.21(0.16)	8.31(11.6)	0.75(0.19)
Autoregressive	Donà et al	3.52(0.26)e-2	0.001(0.01)	13.7(3.05)	0.06(0.15)

(except for (Donà et al., 2020) as we were uncertain about a proper approach of fine-tuning due to its specialized architecture), and 3) trained individually for each single dynamics using the corresponding meta-training data, with and without fine-tuning to the meta-test k-shot support set ($k = 15$). We also attempted another recent autoregressive model that learns diverse dynamics by adding individual dynamic-specific functions to a global dynamic function (Yin et al., 2021), although with failed convergence perhaps due to the large number of dynamics included in our experiments.

For each of the global latent dynamic models (GRU-res, NODE, and RGN-res), we extended it into our few-shot framework. All of these models were trained to forecast for a sequence of 20 frames using only the first 3 frames. We investigated k-shot forecasting when k is fixed at different values of $k = 1, 5, 10, 15$, or allowed to be variable at both meta-training and -test with 15 as the upper limit.

For VRNN, DKF, DVBF, and KVAE, we used their public implementations for training and evaluation. Similar network components with the meta-models were scaled to have comparable parameter scales. Because of their reliance on observed time frames to support prediction, 8 observed frames were exposed to the encoder to reconstruct the 8 frames and forecast the additional 12 frames.

Metrics: We considered four quantitative metrics on meta-test series. We included the commonly used mean squared error (MSE) of forecasted images, and the recently-proposed metric of Valid Prediction Time (VPT) that measures how long the predicted object's trajectory remains close to the ground truth trajectory based on the MSE (VPT-MSE) (Botev et al., 2021). Because pixel-level MSE does not necessary well capture the quality of the predicted dynamics due to the small object size on the image, we further introduced two new metrics: distance (Dist) between the ground-truth and predicted location of the moving object; and VPT determined based on this distance error (VPT-Dist).

Comparison with baseline models trained on full dynamics: For *gravity-16* data, we used 10 gravity in meta-training, 2 in meta-validation, and 4 in meta-testing. Table 1 summarizes the quantitative test performance of the three k-shot meta-models obtained with $k = 15$, in comparison to each of the baseline models trained from the full meta-training set. These quantitative results are further illustrated by visual examples in Fig. 2 (shaded blue): all the baseline models, including their fine-tuned versions, struggled with limited forecasting ability, especially evidenced by the error in predicting the movement of the ball over time (Dist and VPT-Dis). For DKF/VRNN/KVAE, there were strong reconstruction and near-term forecasting from partially observed frames (marked by red vertical lines), but incorrect forecasting further away from the observed frames. GRU-res/NODE/RGN-res

Figure 2: Forecasting on gravity-16 under (blue) full dynamics and (orange) single dynamics training.

Figure 3: A: Comparison with baselines trained on mixed-physics. B: Forecasting examples.

Figure 4: Comparison with baselines trained on single dynamics in meta-training data on gravity-16.

and their fine-tuned versions exhibited difficulty to describe mixed gravity. We contrast each of these models with its few-shot meta formulation in consecutive rows in Fig. 2, highlighting how the presented method improved dynamic-specific forecasting agnostic to the dynamic function of choice.

For *mixed-physics* data, for each of the three physics, we included three dynamic settings in meta-training and left out one in meta-testing. Fig. 3A summarized the test results of the presented meta-GRU-res (with variable k) with representative baseline models – note that we broke down the performance measures by physics systems, but all models were trained on full mixed physics. Visual examples are shown in Fig. 3B. As shown, DKF and DVBF again demonstrated limited ability for long-term forecasting across all physics. KVAE, VRNN, and the finetuned global latent GRU-res were more successful with the mass spring and pendulum systems with relatively simpler dynamics, yet they struggled with the gravity system. The presented meta-GRU-res model consistently outperformed all the baselines across all dynamics, with a larger gain in more complex dynamics.

Comparison with baseline models trained on single dynamics: Fig. 4 summarizes the performance of representative baseline models when trained on a single gravity on *gravity-16* data in comparison

Table 2: Performance metrics of meta-GRU-res models with fixed vs. variable k values

K	Mode	MSE↓	VPT-MSE↑	Dist↓	VPT-Dist↑
1	Fixed	1.80(0.21)e-2	0.44(0.16)	10.6(3.40)	0.60(0.10)
5	Fixed	1.53(0.36)e-2	0.61(0.25)	3.49(1.89)	0.94(0.10)
10	Fixed	1.46(0.34)e-2	0.65(0.26)	3.08(1.58)	0.96(0.08)
15	Fixed	**1.44(0.34)e-2**	**0.68(0.26)**	**2.88(1.45)**	**0.97(0.07)**
	Variable	**1.50(0.34)e-2**	**0.64(0.25)**	**3.44(1.80)**	**0.94(0.10)**

Figure 5: A: t-SNE plot of support-set embedding **c** from stochastic (left) and deterministic (right) meta-models. B: Generated forecasting by sampling the distribution of **c** given the same z_0.

to meta-GRU. Complete results can be found in Appendix D. As shown, in both test dynamics known and unknown to the training, the meta-models outperformed the single-dynamic baselines, suggesting the added benefits of learning across dynamics. This margin of improvements remained even when the single-dynamics baselines were fine-tuned to the k-shot support series of unknown test dynamics.

Visual examples of these baselines are also shown in Fig. 2 (orange shade). Apart from comparisons to the meta-models, it was clear that the global latent GRU-res was able to achieve stronger forecasting when trained on single gravity compared to mixed-gravity earlier. DKF-type of formulations still struggled with longer-term forecasting, regardless training with single or mixed gravity. These provide empirical evidence for the limitations we identified in Section 3 for each PGM formulation.

Ablation study: Table 2 summarized the effect of k on k-shot forecasting using the meta-GRU-res model. As expected, model performance improved as the size of k increased. Even with $k = 5$, however, the performance was significantly better than all the base models summarized in Table 1. Allowing k to be variable had no noticeable effect on model performance. This flexibility highlights the practicality of the presented framework to forecast with any given size of support series.

Latent embedding and generation of diverse dynamics: Fig. 5A shows the distribution of the latent embedding **c** obtained from randomly-selected support set, in comparison to a deterministic version of the presented meta-model on *mixed-physics* data. As shown, the presented framework was able to recognize and separate the three dynamics using the k-shot support set: given an initial $\mathbf{z}_0$, it was then able to generate different time-series within the same dynamics as well as across dynamics by sampling the distribution of **c** (Fig. 5B). This was not possible with its deterministic counterpart.

6 FORECASTING OF CARDIAC ELECTRICAL DYNAMICS

Finally, we considered the modeling and forecasting of more complex dynamics describing real-world physics of the propagation of electrical waves in the heart. This physics can be described by reaction-diffusion partial differential equations (PDEs) as below (Aliev & Panfilov, 1996):

$$\frac{\partial u}{\partial t} = \nabla(\mathbf{D}\nabla u) - cu(u - \theta)(u - 1) - uv; \quad \frac{\partial v}{\partial t} = \varepsilon(u, v)(-v - cu(u - \theta - 1)). \quad (9)$$

Figure 6: Visual examples (A) and performance metrics of meta-GRU versus other baselines trained on the meta-training set for forecasting electrical dynamics on the heart.

When solved over the 3D geometrical mesh of the heart, u over space and time describes the time series of high-dimensional 3D electrical potential on the heart. Parameters ε, c, θ and $\mathbf{D}$ reflect the material properties of an individual's heart and influence the obseved dynamics. Emerging neural approximations of this PDE-based physics simulation (Fresca et al., 2021) is typically tied to a specific configuration of these PDE parameters. Here, we test the ability of the presented framework to generate and forecast a diverse set of this physics-based dynamics using few-shot support series.

Data: We solved Equation (9) in a heart mesh simulating 3D electrical propagation originating from various locations in the heart, with a total of 15 settings of material properties representing 15 dynamic systems with different locations of injury to the heart muscle. We use 9 dynamics in meta-training, 3 in meta-validation, and 3 in meta-testing, with disjoint time-series with different initial conditions (meta-training: 450; meta-test: 2,020). We let k vary between 1 and 5.

Models: We adopted a base encoding-decoding architecture with a graph-CNN encoder/decoder and an ODE-GRU latent dynamic function $\mathbf{z}_k = f(\mathbf{z}_{<k}; \boldsymbol{\theta}_z)$ similar to that described in (Jiang et al., 2021). We trained it with a global $\boldsymbol{\theta}_z$ (global GRU), an individual $\boldsymbol{\theta}_z$ for each material parameter setting (single-dynamics GRU), a conditioned $f(\mathbf{z}_{i-1}, \mathbf{c}; \boldsymbol{\theta}_z)$ with $\mathbf{c}$ encoded from individual training series (instance-specific GRU), and the presented framework (meta GRU). We further added a strong baseline using the original PDEs (9) with material parameters optimized by a SOTA approach from k-shot support series as described in (Dhamala et al., 2018) (personalized virtual heart / PVH).

Metrics: We used quantitative metrics of MSE and spatial correlation coefficient (CC) between the forecast and actual time-series of 3D electrical propagation.

Results: Fig. 6A provides an example illustrating how electrical wave propagates around locations of muscle injury specific to the setting of material properties (column 1). Meta-GRU showed the most accurate details of this propagation block compared to its various baseline counterparts. This gain in forecasting performance is quantitatively summarized in Fig. 6B across all meta-test time-series, and an additional visual example can be found in Appendix E. Note that the PVH represents a strong baseline relying on solving the actual PDEs in Equations (9), which took on average 5 minutes each versus 0.24 seconds by the meta-GRU; moreover, to optimize PDE parameters on average required 100 calls to the PDEs, versus 0.032 seconds for meta-GRU to adapt to specific dynamics.

7 CONCLUSIONS AND DISCUSSION

In this paper, we present a sequential LVM framework to unify existing approaches to learning latent dynamics, identify their limitations associated with the underlying choices of PGMs, and provide empirical evidence for the identified limitations. We further identify meta-learning as an intuitive solution to the identified open gaps, present the first framework for few-shot high-dimensional time-series forecasting, and demonstrate that its performance gain is agnostic to the underlying choice of latent dynamic functions. **Limitations:** An avenue of future work is to expand the latent dynamic functions in this framework, especially those integrating strong inductive biases based on physics such as Hamiltonian mechanics (Botev et al., 2021).

REFERENCES

Rubin R Aliev and Alexander V Panfilov. A simple two-variable model of cardiac excitation. 7(3): 293–301, 1996.

Philip Becker-Ehmck, Jan Peters, and Patrick Van Der Smagt. Switching linear dynamics for variational bayes filtering. In *International Conference on Machine Learning*, pp. 553–562. PMLR, 2019.

Luca Bertinetto, J. F Henriques, J Valmadre, P. H. S. Torr, and Vedaldi A. Learning feed-forward one-shot learners. In *Neural Information Processing Systems*, 2016.

Aleksandar Botev, Andrew Jaegle, Peter Wirnsberger, Daniel Hennes, and Irina Higgins. Which priors matter? benchmarking models for learning latent dynamics. In *Advances in Neural Information Processing Systems*, 2021.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. In *Advances in Neural Information Processing Systems*, 2015.

Jwala Dhamala, Sandesh Ghimire, John L Sapp, B Milan Horáček, and Linwei Wang. High-dimensional bayesian optimization of personalized cardiac model parameters via an embedded generative model. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 499–507. Springer, 2018.

Jérémie Donà, Jean-Yves Franceschi, Sylvain Lamprier, and Patrick Gallinari. Pde-driven spatiotemporal disentanglement. *arXiv preprint arXiv:2008.01352*, 2020.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International conference on machine learning*, pp. 1126–1135. PMLR, 2017.

Marco Fraccaro, Simon Kamronn, Ulrich Paquetz, and Ole Winthery. A disentangled recognition and nonlinear dynamics model for unsupervised learning. In *Advances in Neural Information Processing Systems*, 2017.

Stefania Fresca, Andrea Manzoni, Luca Dedè, and Alfio Quarteroni. Pod-enhanced deep learning-based reduced order models for the real-time simulation of cardiac electrophysiology in the left atrium. *Frontiers in physiology*, pp. 1431, 2021.

M. Garnelo, D. Rosenbaum, C. J. Maddison, T. Ramalho, D. Saxton, M. Shanahan, Y. W. Teh, D. J. Rezende, , and S. M. A. Eslami. Conditional neural processes. In *International conference on machine learning*, 2018.

Laurent Girin, Simon Leglaive, Xiaoyu Bie, Julien Diard, Thomas Hueber, and Xavier Alameda-Pineda. Dynamical variational autoencoders: A comprehensive review. *Foundations and Trends® in Machine Learning*, 15(1-2):1–175, 2021. ISSN 1935-8237. doi: 10.1561/2200000089.

Xiajun Jiang, Ryan Missel, Maryam Toloubidokhti, Zhiyuan Li, Omar Gharbia, John L Sapp, and Linwei Wang. Label-free physics-informed image sequence reconstruction with disentangled spatial-temporal modeling. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 361–371. Springer, 2021.

Maximilian Karl, Maximilian Soelch, Justin Bayer, and Patrick van der Smagt. Deep variational bayes filters: Unsupervised learning of state space models from raw data. In *International Conference on Learning Representations*, 2017.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Alexej Klushyn, Richard Kurle, Maximilian Soelch, Botond Cseke, and Patrick van der Smagt. Latent matters: Learning deep-state-space models. In *Advances in Neural Information Processing Systems*, 2021.

Rahul G. Krishnan, Uri Shalit, and David Sontag. Structured inference networks for nonlinear state space models. In *Association for the Advancement of Artificial Intelligence*, 2017.

L Li, J Yan, X Yang, and Y Jin. Learning interpretable deep state space model for probabilistic time series forecasting. In *International Joint Conference on Artificial Intelligence*, 2019.

Scott Linderman, Matthew Johnson, Andrew Miller, Ryan Adams, David Blei, and Liam Paninski. Bayesian learning and inference in recurrent switching linear dynamical systems. In *Artificial Intelligence and Statistics*, pp. 914–922. PMLR, 2017.

S Makridakis, E Spiliotis, and V Assimakopoulos. S. Statistical and machine learning forecasting methods: Concerns and ways forward. *PLoS ONE*, 13, 2018.

P. Montero-Manso, G. Athanasopoulos, R. J. Hyndman, and T. S Talagala. FFORMA: Feature-based forecast model averaging. *International Journal of Forecasting*, 36, 2020.

Boris N. Oreshkin, Dmitri Carpov, Nicolas Chapados, and Yoshua Bengio. Meta-learning framework with applications to zero-shot time-series forecasting. In *AAAI Conference on Artificial Intelligence*, 2021.

B. N. Oreshkina, D. Carpov, N. Chapados, and Y. Bengio. N-beats: Neural basis expansion analysis for interpretable time series forecasting. In *International Conference on Learning Representations*, 2020.

Tobias Pfaff, Meire Fortunato, Alvaro Sanchez-Gonzalez, and Peter W Battaglia. Learning mesh-based simulation with graph networks. *arXiv preprint arXiv:2010.03409*, 2020.

Shenghao Qin, Jiacheng Zhu, Jimmy Qin, Wenshuo Wang, and Ding Zhao. Recurrent attentive neural process for sequential data. In *arXiv*, 2019.

Syama Sundar Rangapuram, Matthias Seeger, Jan Gasthaus, Lorenzo Stella, Yuyang Wang, and Tim Januschowski. Deep state space models for time series forecasting. In *Neural Information Processing Systems*, 2018.

S. Ravi and H. Larochelle. Optimization as a model for few- shot learning. In *International Conference on Learning Representations (ICLR)*, 2016.

Yulia Rubanova, Ricky T. Q. Chen, and David Duvenaud. Latent odes for irregularly-sampled time series. In *Neural Information Processing Systems*, 2019.

David Salinas, Valentin Flunkert, Jan Gasthaus, and Tim Januschowski. Deepar: Probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 36: 1181–1191, 2020.

Gautam Singh, Jaesik Yoon, and Youngsung Son. Sequential neural processes. In *Neural Information Processing Systems*, 2019.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip H.S. Torr, and Timothy M. Hospedales. Learning to compare: Relation network for few-shot learning. In *Computer Vision and Pattern Recognition*, 2018.

Rui Wang, Robin Walters, and Rose Yu. Incorporating symmetry into deep dynamics models for improved generalization. *arXiv preprint arXiv:2002.03061*, 2020.

C. Yildiz, M. Heinonen, and H. Lahdesmaki. ODE^{2}VAE: Deep generative second order odes with bayesian neural networks. In *Neural Information Processing Systems*, 2020.

Yuan Yin, Ibrahim Ayed, Emmanuel de Bézenac, Nicolas Baskiotis, and Patrick Gallinari. Leads: Learning dynamical systems that generalize across environments. *Advances in Neural Information Processing Systems*, 34:7561–7573, 2021.

Jaesik Yoon, Taesup Kim, Ousmane Dia, Sungwoong Kim, Yoshua Bengio, and Sungjin Ahn. Bayesian model-agnostic meta-learning. *Advances in neural information processing systems*, 31, 2018.

A DERIVATION OF EQUATION 8

$$\sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \log p(\mathbf{x}_{0:T}^q | \mathcal{D}_j^s)$$

$$= \sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \int_{\mathbf{c}} p(\mathbf{x}_{0:T}^q | \mathbf{c}) p_\zeta(\mathbf{c} | \mathcal{D}_j^s) d\mathbf{c}$$

$$= \sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \int_{\mathbf{c}} \int_{\mathbf{z}_0} \left[p_{\theta_x}(\mathbf{x}_0 | \mathbf{z}_0, \mathbf{c}) \prod_{i=1}^{T} p_{\theta_x}(\mathbf{x}_i | \mathbf{z}_i, \mathbf{c}) \right]$$

$$\cdot \frac{p(\mathbf{z}_0)}{q_\phi(\mathbf{z}_0 | \mathbf{x}_{0:l_{z_0}}^q)} \frac{p_\zeta(\mathbf{c} | \mathcal{D}_j^s)}{q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)} \cdot q_\phi(\mathbf{z}_0 | \mathbf{x}_{0:l_{z_0}}^q) q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q) d\mathbf{z}_0 d\mathbf{c}$$

$$\geq \sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \int_{\mathbf{c}} \int_{\mathbf{z}_0} \left[\log p_{\theta_x}(\mathbf{x}_{0:T}^q | \mathbf{z}_0^q, \mathbf{c}) - \log \frac{q_\phi(\mathbf{z}_0 | \mathbf{x}_{0:l_{z_0}}^q)}{p(\mathbf{z}_0)} \right.$$

$$\left. - \log \frac{q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)}{p_\zeta(\mathbf{c} | \mathcal{D}_j^s)} \right] \cdot q_\phi(\mathbf{z}_0 | \mathbf{x}_{0:l_{z_0}}^q) q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q) d\mathbf{z}_0 d\mathbf{c}$$

$$= \sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \mathbb{E}_{q_\phi(\mathbf{z}_0^q), q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)} [\log p_{\theta_x}(\mathbf{x}_{0:T}^q | \mathbf{z}_0^q, \mathbf{c})]$$

$$- \mathrm{KL}(q_\phi(\mathbf{z}_0^q | \mathbf{x}_{0:l_{z_0}}^q) || p(\mathbf{z}_0)) - \mathrm{KL}\left(q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q) || p_\zeta(\mathbf{c} | \mathcal{D}_j^s) \right)$$

B GATED RECURRENT UNIT (GRU) SET-CONDITIONING

We condition the GRU cell of the transition function through Equation 10,

$$\begin{aligned}
\mathbf{z}_{i-1}^{(1)} &= \mathrm{ELU}(\boldsymbol{\alpha}_1 \mathbf{z}_{i-1} + \boldsymbol{\beta}_1 \mathbf{c} + \boldsymbol{\gamma}_1), \quad \mathbf{g}_{i-1} = \sigma(\mathbf{W}_1 \mathbf{z}_{i-1}^{(1)} + \mathbf{b}_1) \\
\mathbf{z}_{i-1}^{(2)} &= \mathrm{ELU}(\boldsymbol{\alpha}_2 \mathbf{z}_{i-1} + \boldsymbol{\beta}_2 \mathbf{c} + \boldsymbol{\gamma}_2), \quad \mathbf{h}_{i-1} = \mathrm{ELU}(\mathbf{W}_2 \mathbf{z}_{i-1}^{(2)} + \mathbf{b}_2) \\
\tilde{\mathbf{z}}_{i-1} &= \boldsymbol{\alpha}_3 \mathbf{z}_{i-1} + \boldsymbol{\beta}_3 \mathbf{c} + \boldsymbol{\gamma}_3, \quad \Delta \mathbf{z}_i = (1 - \mathbf{g}_{i-1}) \odot (\mathbf{W}_3 \tilde{\mathbf{z}}_{i-1} + \mathbf{b}_3) + \mathbf{g}_{i-1} \odot \mathbf{h}_{i-1},
\end{aligned} \tag{10}$$

where $\boldsymbol{\theta}_z = \{\mathbf{W}_i, \mathbf{b}_i, \boldsymbol{\alpha}_i, \boldsymbol{\beta}_i, \boldsymbol{\gamma}_i\}_{i=1}^3$ are learnable parameters of the dynamic function.

C EXTRA CONSTRAINT TO META-MODEL

We considered adding an additional regularization to the set embedding $p_\zeta(\mathbf{c} | \mathcal{D}_j^s)$ so that it is constrained to a reasonable range. Since the true posterior density $p_\zeta(\mathbf{c} | \mathcal{D}_j^s)$ is unknown, we assume that it is bounded by a standard Gaussian distribution $\mathcal{N}(0, \mathbf{I})$. Therefore, the objective function of the model becomes:

$$\arg \min \sum_{j=1}^{M} \sum_{\mathbf{x}_{0:T}^q \in \mathcal{D}_j^q} \mathbb{E}_{q_\phi(\mathbf{z}_0^q), q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q)} [\log p_{\theta_x}(\mathbf{x}_{0:T}^q | \mathbf{z}_0^q, \mathbf{c})]$$

$$- \mathrm{KL}(q_\phi(\mathbf{z}_0^q | \mathbf{x}_{0:l_{z_0}}^q) || p(\mathbf{z}_0)) - \mathrm{KL}\left(q_\zeta(\mathbf{c} | \mathcal{D}_j^s \cup \mathbf{x}_{0:T}^q) || p_\zeta(\mathbf{c} | \mathcal{D}_j^s) \right)$$

$$- \mathrm{KL}\left(p_\zeta(\mathbf{c} | \mathcal{D}_j^s) || \mathcal{N}(0, \mathbf{I}) \right)$$

We applied the extra constraint to the proposed meta-GRU-res model for both fixed and variable k at different value of $k = 1, 5, 9, 15$ and evaluated on *gravity-16* dataset. Fig. 7 summaries the quantitative test performance of the two models trained with and without the constraint on the set embedding. The constraint generally had no noticeable effect on model performance. Visual examples at $k = 1$ are also shown in Fig. 8. It shows that when k is small, the model with the constraint had a slightly better performance.

Figure 7: Comparison with models with and without constraint.

Figure 8: Examples of models with and without constraint.

D   COMPLETE RESULTS OF KNOWN AND UNKNOWN DYNAMICS

Here we provide complete results of base models trained on single dynamics of *gravity-16* in Table 3. We note that the VRNN fails to converge in any of the single dynamics cases, in contrast to its full dynamics training, which is likely due to the lower data availability in these settings. The other baselines DKF and KVAE see similar decreases in performance compared to their full meta-training set performance.

E   ADDITIONAL CARDIAC FIGURE

Here we provide an additional result on the cardiac experiments in Figure 9, this time highlighting the performance of the model on unknown dynamic cardiac dynamics when compared against the baselines. We use a varying support set k size between 1 to 5 samples. The proposed model manages to effectively model around the scar tissue present in the ground truth. The baselines, besides the expensive personalized virtual heart (PVH), are unable to account for the specific dynamics of this subject and propagate over it.

F   DATA DETAILS

In this section, we give the specific data sizes and splits used for training throughout the experiments, as well as generation procedures and considerations for each.

For the bouncing balls, we leveraged the PyMunk Physics Engine (`www.pymunk.org`) to perform simulations under various gravity following (Fraccaro et al., 2017). For pendulum and mass spring systems, we leveraged the Hamiltonian Dynamics Suite presented in (Botev et al., 2021). The suite's default physical parameters were used and friction coefficients were introduced to build non-energy conserving systems. For data consistency, we extracted the red color channel of pendulum and mass spring systems to generate gray-scale images.

For *gravity-16* experiments, we generated bouncing balls dynamic trajectories on 32×32 images. All dynamics are under 16 different gravitational constants, where $g = 3 + \epsilon, \epsilon \sim U(0, 1)$ and the direction of each gravity is evenly distributed over the 2D space. We took the trajectories samples at every $\Delta t = 0.2$ intervals. The initial position of the ball is set to a 16×16 region centered in the image, and the initial velocity is randomly sampled from $[0, 10]$ on both x and y directions. Each gravity setting has 3,000 samples in total. For *gravity-16* data, we used 10 gravity in meta-training, 2 in meta-validation, and 4 in meta-testing. We also left out samples from both meta-training and

Table 3: Comparison of the presented meta and base models on known and unknown dynamics.

Model	Dynamics	MSE↓	VPT-MSE↑	Dist↓	VPT-Dist↑
meta-GRU-res	known	**1.43(0.34)e-2**	**0.68(0.26)**	**2.86(1.44)**	**0.97(0.06)**
	unknown	**1.45(0.33)e-2**	**0.67(0.25)**	**2.96(1.49)**	**0.97(0.07)**
meta-NODE	known	1.60(0.26)e-2	0.58(0.23)	6.05(2.65)	0.80(0.12)
	unknown	1.62(0.26)e-2	0.57(0.22)	6.23(2.54)	0.80(0.12)
meta-RGN-res	known	1.59(0.25)e-2	0.57(0.21)	6.89(3.08)	0.76(0.13)
	unknown	1.60(0.23)e-2	0.56(0.20)	7.23(3.09)	0.75(0.13)
GRU-res	known	1.80(0.29)e-2	0.46(0.23)	6.86(3.95)	0.77(0.19)
	unknown	1.99(0.277)e-2	0.37(0.18)	8.07(3.56)	0.69(0.17)
GRU-res finetune	unknown	2.03(0.27)e-2	0.35(0.17)	8.51(3.42)	0.66(0.18)
NODE	known	1.97(0.21)e-2	0.30(0.20)	10.6(4.13)	0.60(0.17)
	unknown	2.06(0.22)e-2	0.27(0.17)	11.1(3.71)	0.57(0.16)
NODE finetune	unknown	2.07(0.21)e-2	0.27(0.17)	11.2(3.72)	0.55(0.16)
RGN-res	known	1.93(0.22)e-2	0.34(0.20)	10.1(4.11)	0.61(0.18)
	unknown	2.03(0.22)e-2	0.30(0.16)	10.8(3.72)	0.57(0.16)
RGN-res finetune	unknown	2.05(0.22)e-2	0.29(0.16)	10.7(3.62)	0.56(0.16)
DKF	known	3.89(0.32)e-2	0.08(0.06)	10.7(3.17)	0.46(0.20)
	unknown	3.88(0.32)e-2	0.08(0.06)	10.7(3.23)	0.45(0.20)
DKF finetune	unknown	3.89(0.32)e-2	0.08(0.06)	10.8(3.24)	0.45(0.20)
VRNN	known	2.32(14.6)e-2	0.02(0.11)	45.3(0.00)	0.00(0.00)
	unknown	2.32(14.6)e-2	0.01(0.08)	45.3(0.00)	0.00(0.00)
VRNN finetune	unknown	2.34(14.5)e-2	0.04(0.15)	45.3(0.00)	0.00(0.00)
DVBF	known	2.32(14.3)e-2	0.01(0.02)	45.2(0.00)	0.00(0.00)
	unknown	2.43(14.1)e-2	0.01(0.07)	45.3(0.00)	0.00(0.00)
DVBF finetune	unknown	2.35(14.1)e-2	0.01(0.08)	45.3(0.00)	0.00(0.00)
KVAE	known	3.42(1.30)e-2	0.39(0.34)	5.05(3.57)	0.5(0.34)
	unknown	3.46(1.36)e-2	0.22(0.19)	5.17(3.91)	0.53(0.28)
Donà et al	known	3.58(0.33)e-2	0.00(0.01)	13.7(3.36)	0.07(0.18)
	unknown	3.56(0.34)e-2	0.00(0.01)	14.1(3.84)	0.08(0.19)

meta-validation sets ($\sim$1500 for each gravity) to evaluate the performance of the model on the known dynamics.

For *mixed-physics* experiments, we generated a mixed-physics dataset consisting of bouncing balls under 4 gravity directions, and pendulums and mass springs each with four different values of friction coefficients of $0, 0.05, 0.1, 0.15$. The bouncing ball dataset is similar to *gravity-16* experiment except for the 4 gravity directions. Both pendulums and mass springs took the trajectories samples at every $\Delta t = 0.2$ intervals. In pendulums, the mass of the particle $m = 0.5$, the gravitational constant $g = 3$ and the pivot length $l = 1$. The friction coefficients are chosen in $0, 0.05, 0.1, 0.15$. In mass springs, the mass of the particle $m = 0.5$, the spring force coefficient $k = 2$. The friction coefficients are chosen in $0, 0.05, 0.1, 0.15$. For each of the three physics, we included three dynamic settings in meta-training and left out one in meta-testing.

For cardiac electrical dynamics, we generated 3D electrical signal propagation in the heart simulated by the Aliev-Panfilov model Aliev & Panfilov (1996) on 3 heart meshes and a total of 12 different tissue parameters (4 on each heart) representing different injury to the heart muscle. This was treated as 12 tasks in meta-learning. All 12 tasks appeared in meta-training and -testing, with disjoint time sequences resulting from different external stimulations (meta-training: 300; meta-test: 2,020).

All ball data can be found here: `https://drive.google.com/drive/folders/1b1Z68kuMbj5CGp5COF8p10EKxgoHixFS?usp=sharing`. The heart data can be found

Figure 9: Example of forecasting *unknown* electrical dynamics on the heart.

here: `https://drive.google.com/drive/folders/1Nd91ShilxjPzOZazUO_pIsD3XvgLb7bR?usp=sharing`.

G   IMPLEMENTATION DETAILS

In this section, we give the specific hyper-parameters on each experiment over all models, as well as resources and considerations for each. All experiments were run on NVIDIA Tesla T4s with 16 GB memory.

G.0.1   ARCHITECTURE FOR META MODELS

The implementation of our proposed meta models is here: `https://drive.google.com/drive/folders/1OXbcYfobohTLbIUa8nR5jKgtQIeoWOVV?usp=sharing`. Specifically in the configuration file, the type of transition function can be changed by `trans_mode` and `trans_args` in the model section. The size of the support set is controlled by `k_shot` in the data section, and the variable/fixed K is set up by `changeable` in both training and evaluation section. During meta-testing, the paired support and query sets should be put under `eval_tags` and `pred_tags` in the data section. Detailed hyperparameter settings are shown below.

Meta Model Architecture

- Domain Input: 20 observation timesteps of 32×32 dimensions
- Initialization Input: 3 observation timesteps of 32×32 dimensions
- Optimizer: Adam, 5×10^{-4} learning rate
- Transition: Gated transition function(GRU-res) / Recurrent Generative Network (RGN-res) / Neural Ordinary Differential Equation (NODE)
- Batch size: 50
- Number of epochs: 200
- Training time: 1.5 - 5 hours
- Latent Units: 8
- Transition Units: 100
- Domain Encoder Filters: [8, 16, 8]
- Domain Time Units: [10, 5, 1]

- Initial Encoder Filters: [8, 16, 8]
- Emission Filters: [32, 16, 8, 1]
- KL term initialization: $\lambda_1 = 10^{-2}$
- KL term set-embedding: $\lambda_2 = 10^{-2}$

G.0.2 ARCHITECTURE FOR BASELINE MODELS

The implementation of baseline models is here: `https://drive.google.com/drive/folders/1OXbcYfobohTLbIUa8nR5jKgtQIeoWOVV?usp=sharing`. The setting of transition function can be changed by `trans_mode` and `trans_args` in the model section. The testing sets should be put under `pred_tags` in the data section. Detailed hyperparameter settings are shown below.

Baseline Model Architecture

- Initialization Input: 3 observation timesteps of 32×32 dimensions
- Optimizer: Adam, 5×10^{-4} learning rate
- Transition: Gated transition function(GRU-res) / Recurrent Generative Network (RGN-res) / Neural Ordinary Differential Equation (NODE)
- Batch size: 50
- Number of epochs: 200
- Training time: 1.3 hours
- Latent Units: 8
- Transition Units: 100
- Initial Encoder Filters: [8, 16, 8]
- Emission Filters: [32, 16, 8, 1]
- KL term initialization: $\lambda_1 = 10^{-2}$

G.0.3 ARCHITECTURE FOR DKF

The DKF model (Krishnan et al., 2017) we used is based on this implementation: `https://github.com/yjlolo/pytorch-deep-markov-model`. Our implementation is provided in our code. We modified the script to perform reconstruction of the observed part of input sequences and prediction of the unobserved parts. Specifically, the output of the correction function was used in the decoder in the reconstruction phase, while the transition module was used for prediction. Detailed hyperparameter settings are shown below.

DKF Architecture

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 5×10^{-4} learning rate
- Transition: Gated transition function
- Batch size: 50
- Number of epochs: 200
- Training time: 1.2 hours
- Encoder Units: [2048, 2048, 100]
- RNN Units: 100
- Correction Units: 100
- Transition Units: 100
- Emission Filters: [32, 16, 8, 1]

G.0.4 ARCHITECTURE FOR DVBF

The PyTorch implementation of DVBF (Karl et al., 2017) we used can be found here: `https://github.com/gregorsemmler/pytorch-dvbf`. Our implementation is provided in our code. We modified this script to perform initial state generation, as highlighted in DVBF's experiments (Karl et al., 2017). We found lacking convergence in more complex dynamics and lower data-availability scenarios, specifically bouncing ball settings. We detail the hyperparameter values chosen per experiment with respect to the hyperparameters found in this repository.

DVBF Architecture on Gravity-16

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 1×10^{-3} learning rate annealed to 1×10^{-4} over 100 epochs
- Delayed KL Weight: between epochs=[5,25], linearly annealed from 0.01 to 1
- Batch-size: 25
- Number of Epochs: 100
- Training time: 15 hours
- Number of matrices α_t: 8
- Code vector dim w_t: 8
- Feature dim z_t: 8
- State dim s_t: 1024
- RNN Hidden Size: 100
- Inference Size: 32
- Transition Size: 64
- Encoder CNN Filters: [8, 32, 8]
- Decoder CNN Filters: [8, 32, 8]

DVBF Architecture on Mixed-Physics

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 1×10^{-3} learning rate annealed to 1×10^{-4} over 100 epochs
- Delayed KL Weight: between epochs=[5,25], linearly annealed from 0.01 to 1
- Batch-size: 25
- Number of Epochs: 100
- Training time: 15 hours
- Number of matrices α_t: 8
- Code vector dim w_t: 8
- Feature dim z_t: 8
- State dim s_t: 1024
- RNN Hidden Size: 100
- Inference Size: 32
- Transition Size: 64
- Encoder CNN Filters: [8, 32, 8]
- Decoder CNN Filters: [8, 32, 8]

G.0.5 ARCHITECTURE FOR KVAE

The public implementation of KVAE (Fraccaro et al., 2017) we used can be found here: `https://github.com/simonkamronn/kvae`. No significant modifications were made to the repo - primarily just output formatting. When attempting to scale the hyperparameter K (number of mixture components for the LG-SSM matrices), we ran into numerical loss instability and lacking convergence in reconstruction. We detail the hyperparameter values chosen per experiment with respect to the hyperparameters found in this repository.

KVAE Architecture on Gravity-16

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 7×10^{-3} learning rate exponentially decayed by 0.85 over 20 epochs
- Batch-size: 32
- Number of Epochs: 80
- Training time: 2 hours
- K: 3
- Latent variable dim a_t: 4
- Latent state dim z_t: 8
- Control dim u_t (unused): 1
- RNN Hidden Size: 50
- RNN Layers: 2
- Encoder CNN Filters: [3, 32, 32, 32]
- Decoder CNN Filters: [3, 32, 32, 32]

KVAE Architecture on Mixed-Physics

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 7×10^{-3} learning rate exponentially decayed by 0.85 over 20 epochs
- Batch-size: 32
- Number of Epochs: 80
- Training time: 2 hours
- K: 3
- Latent variable dim a_t: 4
- Latent state dim z_t: 8
- Control dim u_t (unused): 1
- RNN Hidden Size: 50
- RNN Layers: 2
- Encoder CNN Filters: [3, 32, 32, 32]
- Decoder CNN Filters: [3, 32, 32, 32]

G.0.6 ARCHITECTURE FOR VRNN

The DVAE code implementation Girin et al. (2021) of VRNN (Chung et al., 2015) we used can be found here: `https://github.com/XiaoyuBIE1994/DVAE/blob/master/dvae/model/vrnn.py`. The model was modified to take its own reconstructions as inputs to the feature extractor at every timestep after the true sequence observation period. We detail the hyperparameter values chosen per experiment with respect to the hyperparameters found in this repository.

VRNN Architecture on Gravity-16

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 1×10^{-3} learning rate
- Batch-size: 50
- Number of Epochs: 80
- Training time: 8 hours
- Latent state dim z_t: 32
- Dropout probability: 0.2
- Dense X Size: 128
- Dense Z Size: 128
- Dense H(X)-Z Size: 128
- Dense H(Z)-X Size: 128
- Dense H(Z) Size: 128
- RNN Layers: 2
- RNN Dim: 64
- Beta coefficient: 1.0
- Activation: LeakyReLU(1.0)

VRNN Architecture on Mixed-Physics

- Input: 8 observation and 12 prediction timesteps of 32×32 dimensions
- Optimizer: Adam, 1×10^{-3} learning rate
- Batch-size: 50
- Number of Epochs: 80
- Training time: 8 hours
- Latent state dim z_t: 32
- Dropout probability: 0.2
- Dense X Size: 128
- Dense Z Size: 128
- Dense H(X)-Z Size: 128
- Dense H(Z)-X Size: 128
- Dense H(Z) Size: 128
- RNN Layers: 2
- RNN Dim: 64
- Beta coefficient: 1.0
- Activation: LeakyReLU(1.0)