Moderate Coreset: A Universal Method of Data Selection for Real-world Data-efficient Deep Learning

Abstract

Deep learning methods nowadays rely on massive data, resulting in substantial costs of data storage and model training. Data selection is a useful tool to alleviate such costs, where a coreset of massive data is extracted to practically perform on par with full data. Based on carefully-designed score criteria, existing methods first count the score of each data point and then select the data points whose scores lie in a certain range to construct a coreset. These methods work well in their respective preconceived scenarios but are not robust to the change of scenarios, since the optimal range of scores varies as the scenario changes. The issue limits the application of these methods, because realistic scenarios often mismatch preconceived ones, and it is inconvenient or unfeasible to tune the criteria and methods accordingly. In this paper, to address the issue, a concept of the moderate coreset is discussed. Specifically, given any score criterion of data selection, different scenarios prefer data points with scores in different intervals. As the score median is a proxy of the score distribution in statistics, the data points with scores close to the score median can be seen as a proxy of full data and generalize different scenarios, which are used to construct the moderate coreset. As a proof-of-concept, a universal method that inherits the moderate coreset and uses the distance of a data point to its class center as the score criterion, is proposed to meet complex realistic scenarios. Extensive experiments confirm the advance of our method over prior state-of-the-art methods, leading to a strong baseline for future research.

1 Introduction

Large-scale datasets, comprising millions of examples, are becoming the de-facto standard to achieve state-of-the-art deep learning models (Zhao et al., 2021; Zhao & Bilen, 2021; Paul et al., 2021). Unfortunately, at such scales, both storage costs of the data and computation costs of deep learning model training are tremendous and usually unaffordable by startups or non-profit organizations (Wang et al., 2018a; Coleman et al., 2020; Sorscher et al., 2022; Pooladzandi et al., 2022), which limits the success of deep learning models to specialized equipment and infrastructure (Yang et al., 2022). For instance, the storage needs of ImageNet-22k (Deng et al., 2009) and BDD100K datasets (Yu et al., 2020a) are 1TB and 1.8TB respectively. Training PaLM (Chowdhery et al., 2022) once requires a training dataset containing 780 billion high-quality tokens and then takes almost 1,920 TPU years. Additionally, hyper-parameter tuning or network architecture search could further increase the computation costs, which is pessimistic (Strubell et al., 2019; Schwartz et al., 2020).

Data selection came into being to deal with large data and mitigate the above issues for data-efficient deep learning. More specifically, data selection aims to find the most essential data points and build a coreset of large data. Training on the coreset is expected to continue the model performance achieved by training on the large data (Huang et al., 2021b; Chen et al., 2021). Based on carefully-designed score criteria, recent works have presented various algorithms of data selection, e.g., in terms of loss values (Han et al., 2018; Jiang et al., 2018), forgetfulness (Toneva et al., 2019; Sorscher et al., 2022), and gradient matching (Paul et al., 2021; Pooladzandi et al., 2022). In respect of procedures, these works first sort the scores achieved by all data points and then simply select the data points with either smaller scores or larger scores, according to different scenarios. For instance, for a loss-based score criterion, if data is presumed a priori to be perfectly labeled, larger-loss data points are more

important and selected (Lei et al., 2022). Conversely, if data is corrupted by outliers, smaller-loss data points are more critical because of the concern on model robustness (Lyu & Tsang, 2019).

State-of-the-art methods on data selection can achieve promising performance as they show. However, they are specially designed for preconceived scenarios. The deliberate characteristic makes them work well under certain situations and demands, but not stable or even extremely sensitive to the change of situations or demands, even though the change is slight (the concerns on complex realistic scenarios are detailed in Section 2.2). The issue severely restrict the practical applications of the methods, since realistic scenarios cannot always match preconceived ones well, and realistic demands are frequently changed over time (Hendrycks & Gimpel, 2017; Wu et al., 2021; Arjovsky et al., 2019; Piratla et al., 2020; Creager et al., 2021; Shen et al., 2021; Li et al., 2022). It is inconvenient, troubled, and often unachievable to tweak our method accordingly (Lu et al., 2018).

In this paper, to address the issue, we discuss a new concept about data selection, i.e., the moderate coreset, which is generic in multiple realistic tasks without any task-specific prior knowledge and adjustments. For the construction of the moderate coreset, given any score criterion of data selection, we characterize the score statistics as a distribution with respect to different scenarios. Namely, different scenarios correspond to and require data points with scores in different ranges. The distribution can be generally depicted by the median of scores (James et al., 2013). Accordingly, data points with scores that are close to the score median can be seen as a proxy of all data points, which is used to build a moderate coreset and generalize different scenarios.

As a proof-of-concept, we present a universal method of data selection in complex realistic scenarios. Specifically, working with extracted representations extracted by deep models, we implement the distance of a data point to its class center as a score criterion. Data points with scores close to the score median are selected as a coreset for following tasks. Comparing the complicated and time-consuming data selection procedure of many works, e.g., using Hessian calculation (Yang et al., 2022), our method is simple and does not need to access model architectures and retrain models. We show that existing state-of-the-art methods are not robust to the slight change of presumed scenarios. The proposed method is more superior to them in diverse data selection scenarios.

Contributions. Before delving into details, we clearly emphasize our contribution as follows:

- Different from prior works targeting preconceived scenarios, we focus on data selection in the real world, where encountered scenarios always mismatch preconceived ones. The concept of the moderate coreset is proposed to generalize different tasks without any task-specific prior knowledge and fine-tuning.

- As a proof-of-concept, we propose a universal method operating on deep representations of data points for data selection in various realistic scenarios. The method successfully combines the advantages of simplicity and effectiveness.

- Comprehensive experiments for the comparison of our method with state-of-the-arts are provided. Results demonstrate that our method is leading in multiple realistic cases, achieving lower time cost in data selection and better performance on follow-up tasks. This creates a strong baseline of data selection for future research.

2 BACKGROUND

2.1 DATA SELECTION RECAP

Data selection vs. data distillation/condensation. Data selection is a powerful tool as discussed. In data-efficient deep learning, there are also other approaches that are widely studied nowadays, such as data distillation (Cazenavette et al., 2022; Bohdal et al., 2020; Wang et al., 2018a; Such et al., 2020; Nguyen et al., 2021; Sucholutsky & Schonlau, 2021) and data condensation (Wang et al., 2022; Zhao et al., 2021; Zhao & Bilen, 2021). This series of works focus on *synthesizing* a small but informative dataset as an alternative of the original large-scale dataset. However, the works on data distillation and condensation are criticized for only synthesizing a small number of examples (e.g., 50 images per class) due to computational power limitations (Yang et al., 2022). In addition, their performance is far from satisfactory. Therefore, the performances of data distillation/condensation and data selection are not directly comparable.

Score criteria in data selection. Data selection has recently gained lots of interest. As for the procedure of data selection, generally speaking, existing methods first design a score criterion based on a preconceived scenario (e.g., using prior knowledge or other scenario judgment techniques). Afterwards, all data points of a dataset are sorted with the score criterion. The data points with scores in a certain range are selected for follow-up tasks. For instance, regarding the scenario where data is corrupted with outliers, the data points with smaller losses are favored. Popular score criteria include but do not limit to prediction confidence (Pleiss et al., 2020), loss values (Jiang et al., 2018; Wei et al., 2020), margin separation (Har-Peled et al., 2007), gradient norms (Paul et al., 2021), and influence function scores (Koh & Liang, 2017; Yang et al., 2022; Pooladzandi et al., 2022).

2.2 INSTABILITY OF PRIOR WORKS TO CHANGED SCENARIOS

With designed score criteria, prior state-of-the-art methods have achieved promising performance in their respective scenarios. Unfortunately, they are not robust or rather unstable to the change of scenarios, which limits their realistic applications. We detail the issue in three practical respects.

Distribution shift scenarios. For methods intended for ideal data, they cannot be applied directly when data contains outliers, because outliers will be identified to contribute more to model learning (Zhang & Sabuncu, 2018) and selected. Conversely, for the methods for the data involving outliers, they will select data points far from the decision boundary for model robustness. However, the uncontaminated data points close to the decision boundary are more important for model performance (Huang et al., 2010), which are entangled with contaminated ones and cannot be identified exactly. A covariate-shift problem (Sugiyama & Kawanabe, 2012) arises to degenerate model performance, if we only use the data points far from the decision boundary for model training.

Changing demands of coreset sizes. Different scenarios have different requirements of coreset sizes. Specifically, if a coreset is allowed to have a relatively large size, the coreset built by the data points that contribute more to model generalization (e.g., those close to the decision boundary), can work well for next tasks. However, if a small size is required, the selection with only these data points will make the convergence of deep models difficult to hurt model performance (Bengio et al., 2009; Zhou & Wu, 2021). Namely, the data selection way is unstable to the change in coreset sizes.

Varied competence on deep models. Lots of state-of-the-art methods rely on accessing the architectures of deep models and the permission of model retraining for data selection (Toneva et al., 2019; Yang et al., 2022; Sorscher et al., 2022; Paul et al., 2021; Feldman & Zhang, 2020). In some scenarios, requirements for these methods can be met to make them work well. However, if the requirement is not satisfied due to secrecy concerns, these methods will become invalid.

Obviously, the issue of instability to changed scenarios restricts the applications of existing methods, since realistic scenarios cannot always match preconceived ones. Moreover, in many cases, it is expensive or not possible to tune methods frequently according to the changes, which demonstrates the urgency of developing new technologies.

3 METHODOLOGY

3.1 PRELIMINARIES

In the sequel, vectors, matrices, and tuples are denoted by bold-faced letters. We use $\|\cdot\|_p$ as the ℓ_p norm of vectors or matrices. Let $[n] = \{1, \ldots, n\}$. Let $\mathbb{I}[\mathcal{B}]$ be the indicator of the event $\mathcal{B}$.

We define the problem of data selection in data-efficient deep learning. Formally, we are given a large-scale dataset $\mathcal{S} = \{\mathbf{s}_1, \ldots, \mathbf{s}_n\}$ with a sample size n, where $\mathbf{s}_i = (\mathbf{x}_i, y_i)$, $\mathbf{x}_i \in \mathbb{R}^d$, and $y_i \in [k]$. The aim of data selection here is to find a subset of $\mathcal{S}$ for follow-up tasks, which reduces both storage and training consumption. The subset is called the *coreset* that is expected to practically perform on par with full data $\mathcal{S}$. We denote the coreset as $\mathcal{S}^* = \{\hat{\mathbf{s}}_1, \ldots, \hat{\mathbf{s}}_m\}$ with a sample size m and $\mathcal{S}^* \subset \mathcal{S}$. The data selection ratio in building the coreset is then m/n.

3.2 PROCEDURE DESCRIPTION

Representation extraction. Given a well-trained deep model denoted by $f(\cdot) = g(h(\cdot))$, where $h(\cdot)$ denotes the part of the model mapping input data to hidden representations at the penultimate

layer, and $g(\cdot)$ is the part mapping such hidden representations to the output $f(\cdot)$ for classification. Namely, for a data point $\mathbf{s} = (\mathbf{x}, y)$, its hidden representation is $h(\mathbf{x})$. Therefore, with the trained deep model $f(\cdot)$ and full training data $\mathcal{S} = \{\mathbf{s}_1, \ldots, \mathbf{s}_n\}$, the hidden representations of all data points are acquired as $\{\mathbf{z}_1 = h(\mathbf{x}_1), \ldots, \mathbf{z}_n = h(\mathbf{x}_n)\}$. At the representational level, the class center of each class is

$$\left\{ \mathbf{z}^j = \frac{\sum_{i=1}^n \mathbb{I}[y_i = j] \mathbf{z}_i}{\sum_{i=1}^n \mathbb{I}[y_i = j]} \right\}_{j=1}^k, \tag{1}$$

where the mean of the representations from one class is calculated as the mean of every single dimension in the representations.

Distance-based score for data selection. With hidden representations $\{\mathbf{z}_1, \ldots, \mathbf{z}_n\}$ and representational class centers $\{\mathbf{z}^1, \ldots, \mathbf{z}^k\}$, the Euclidean distance from each representation to the corresponding class center can be simply calculated with $d(\mathbf{s}) = \|\mathbf{z} - \mathbf{z}^j\|_2$. The set consisting of the distances is $\{d(\mathbf{s}_1), \ldots, d(\mathbf{s}_n)\}$ with the median as $\mathcal{M}(d(\mathbf{s}))$. All data points are then sorted with an ascending order based on the distance set, which are denoted by $\{d(\tilde{\mathbf{s}}_1), \ldots, d(\tilde{\mathbf{s}}_n)\}$. Afterwards, the data points with distances close to the distance median $\mathcal{M}(d(\mathbf{s}))$ are selected as the coreset $\mathcal{S}^*$, i.e.,

$$\left\{ d(\tilde{\mathbf{s}}_1), \quad \ldots, \quad d(\tilde{\mathbf{s}}_a), \quad d(\tilde{\mathbf{s}}_{a+1}), \quad \ldots, \quad \mathcal{M}(d(\mathbf{s})), \quad \ldots, \quad d(\tilde{\mathbf{s}}_{n-a}), \quad d(\tilde{\mathbf{s}}_{n-a+1}), \quad \ldots, \quad d(\tilde{\mathbf{s}}_n) \right\}$$
$$\downarrow \qquad\qquad \downarrow \qquad\quad \downarrow \qquad\qquad\qquad \downarrow \qquad\qquad\qquad \downarrow \qquad\qquad \downarrow \qquad\qquad \downarrow$$
$$\left\{ \tilde{\mathbf{s}}_1, \quad \ldots, \quad \tilde{\mathbf{s}}_a \quad \tilde{\mathbf{s}}_{a+1}, \quad \ldots, \quad \tilde{\mathbf{s}} \quad \ldots, \quad \tilde{\mathbf{s}}_{n-a}, \quad \tilde{\mathbf{s}}_{n-a+1} \quad \ldots, \quad \tilde{\mathbf{s}}_n \right\}, \tag{2}$$

where $a = (n - m)/2$ relates to the data selection ratio. The set $\{\tilde{\mathbf{s}}_{a+1}, \ldots, \tilde{\mathbf{s}}_{n-a}\}$ is regarded as the coreset $\mathcal{S}^* \subset \mathcal{S}$ for follow-up tasks.

It should be noted that the distance-based score is similar to the confidence-based score. That is to say, for a data point, a closer distance to its class center means that the deep model often gives a higher class posterior probability for this data point. However, the proposed method is easier to apply in the real world. The reason is that representations are more accessible than class posterior probabilities, e.g., directly using the public pretrained models of multiple tasks as representation extractors. Clearly, it is convenient to implement our method without accessing the internal structures of deep models and retraining them. The superiority leads to low time costs of data selection. The lower time costs are consistent with the aim of data-efficient deep learning, which allow our method to be applied to large-scale datasets, e.g., ImageNet (Deng et al., 2009).

3.3 MORE JUSTIFICATIONS FOR THE PROPOSED METHOD

We provide more justifications to discuss why our method can work well in realistic scenarios. The justifications come from two perspectives that are popularly used to analyze robustness and generalization of deep models.

Representation structures. Prior works have claimed that model performance (e.g., accuracy and robustness) is highly related to representation structures (Yu et al., 2020b; Chan et al., 2022). Good representations should satisfy the following three properties and obtain a trade-off among them. (1) Between-class discriminative: representations of data from different classes are highly uncorrelated. (2) Within-class compressible: representations of data from the same class should be relatively correlated. (3) Maximally diverse representations: variance of representations for each class should be as large as possible as long as they stay uncorrelated from the other classes. Referring to Figure 1, we can see that the proposed method meets the three properties, where the trade-off is achieved. However, the data selection with the other ways cannot balance these three properties simultaneously. This perspective can provide support for the effectiveness of our method in realistic scenarios.

Representation information measurement. Information bottleneck theory (Tishby et al., 2000; Achille & Soatto, 2018) has claimed that optimal representations should be both *sufficient* and *minimal* for various practical tasks. As did in (Achille & Soatto, 2018), we give the following definition.

Definition 1 (Sufficient and minimal representations) *We say that a representation* $\mathbf{z}$ *of* $\mathbf{x}$ *is sufficient for* y *if* $y \perp\!\!\!\perp \mathbf{x}|\mathbf{z}$ *or equivalently if* $I(\mathbf{z}; y) = I(\mathbf{x}; y)$*; it is minimal when* $I(\mathbf{x}; \mathbf{z})$ *is smallest among sufficient representations.*

(a)   (b)   (c)

Figure 1: Illustrations of representation structures achieved by different data selection ways. Different shapes, i.e., the circle and cross, correspond different classes. Pentagrams correspond class centers. The shaded data points are selected for coresets. (a) Selecting data points closer to class centers. (b) Selecting data points far from class centers. (c) Selecting data points with distances close to the distance median.

We use a mutual information estimator (Belghazi et al., 2018) to estimate $I(\mathbf{z}; y)$, $I(\mathbf{x}; y)$, and $I(\mathbf{x}; \mathbf{z})$. Experiments are conducted on CIFAR-100 (Krizhevsky, 2009). Each estimation is repeated 20 times for reported mean. As shown in Table 1, compared with the other

Methods / Ratio	20%		30%	
Metrics	$\lvert I(\mathbf{z}; y) - I(\mathbf{x}; y)\rvert$	$I(\mathbf{x}; \mathbf{z})$	$\lvert I(\mathbf{z}; y) - I(\mathbf{x}; y)\rvert$	$I(\mathbf{x}; \mathbf{z})$
Method (a)	1.901 bits	2.087 bits	2.022 bits	2.384 bits
Method (b)	0.611 bits	6.512 bits	1.235 bits	3.702 bits
Method (c) (ours)	1.652 bits	4.010 bits	1.956 bits	2.737 bits

Table 1: Comparison of different data selection ways based on representation information measurement. Method (a) selects data points closer to class centers. Method (b) selects data points far from class centers. Method (c) selects data points with the distances close to the distance median.

two data selection ways, our method achieves a trade-off between sufficiency and minimality, which justifies the effectiveness of our method.

4 Evaluations in Ideal Scenarios

4.1 Experimental Setup

Datasets and network structures. We evaluate the effectiveness of our method on three popularly used datasets, i.e., CIFAR-100 (Krizhevsky, 2009), Tiny-ImageNet (Le & Yang, 2015), and ImageNet-1k (Deng et al., 2009). We first study the effectiveness of data selection methods with a preconfigured network structure. That is to say, the coreset and full data are utilized for the same network structure. ResNet-50 (He et al., 2016) is exploited here.

Baselines. Multiple data selection methods act as baselines for comparison. Specifically, we use

- "Random" means that we randomly select partial data from full data.
- "Herding" (Welling, 2009) selects data points that are closer to class centers.
- "Forgetting" (Toneva et al., 2019) selects data points that are easy to be forgotten during optimization.
- "GraNd-score" (Paul et al., 2021) includes data points with larger loss gradient norms.
- "EL2N-score" (Paul et al., 2021) focuses on data points with larger norms of the error vector that is the predicted class probabilities minus one-hot label encoding.
- "Optimization-based" (Yang et al., 2022) employs the influence function (Koh & Liang, 2017) and picks data points that yields strictly constrained generalization gap.
- "Self-sup.-selection" (Sorscher et al., 2022) selects data points on the difficulty of each data point by the distance to its nearest cluster centroid, after self-supervised pre-training and clustering. To avoid the tuning of the cluster number, we set it to the class number. Data points with larger distances are selected here.

Notice that the methods Forgetting, GraNd-score, and EL2N-score rely on model retraining for data selection. Besides, the method Optimization-based has heavy computational costs, due to the cal-

(a) Evaluations on CIFAR-100.   (b) Evaluations on Tiny-ImageNet.   (c) Evaluations on ImageNet-1k.

Figure 2: Illustrations of comparing our proposed method with several data selection baselines on CIFAR-100 (a), Tiny-ImageNet (b), and ImageNet-1k (c). Note that the method Optimization-based is not compared on ImageNet-1k due to its huge time costs of data selection. Exact numerical results can be found in in Appendix A for convenient checks.

culation of Hessian in the influence function[1] and its iterative data selection process. The method Self-sup.-selection is troubled by the same issue, where both self-supervised pre-training and clustering are time-consuming (Na et al., 2010; Jaiswal et al., 2020). By contrast, Herding and our method only need a distance calculation and a sort operation when there is a representation extractor, leading to low time consumption in data selection. We name the proposed method as **Moderate-DS**.

Implementation details. All experiments are conducted on NVIDIA GTX3090 GPUs with Py-Torch (Paszke et al., 2019). For experiments on CIFAR-100, we adopt a batch size of 128, an SGD optimizer with a momentum of 0.9, weight decay of 5e-4, and an initial learning rate of 0.1. The learning rate is divided by 5 after the 60th epoch, the 120th epoch, and the 160th epoch. 200 epochs are set in total. Data augmentation of random crop and random horizontal flip is used. For experiments on Tiny-ImageNet, we adopt a batch size of 256, an SGD optimizer with a momentum of 0.9, weight decay of 1e-4, and an initial learning rate of 0.1. The learning rate is divided by 10 after the 30th epoch and the 60th epoch. 90 epochs are set totally. Random horizontal flips are used to augment training data. In each experiment, we perform five individual runs with different random seeds. For experiments on ImageNet-1k, following (Sorscher et al., 2022), the VISSL library (Goyal et al., 2021) is exploited. We adopt a base learning rate of 0.01, a batch size of 256, an SGD optimizer with a momentum of 0.9, and a weight decay of 1e-3. 100 epochs are set totally. Note that because of huge calculation consumptions, the experiment in each case is performed once. All hyperparameters and experimental settings of training before and after data selection are kept the same.

4.2 COMPARISON WITH THE STATE-OF-THE-ARTS

We use test accuracy achieved by training on coresets to verify the effectiveness of the proposed method. For experiments on CIFAR-100 and Tiny-ImageNet, as shown in Figure 2, the proposed method is much competitive with state-of-the-art methods. Particularly, when the data selection ratio is low, e.g., 20%, 30%, and 40%, our method always achieves the best performance. Besides, for experiments on more challenging ImageNet-1k, we can see that our method obtains the best results when data selection ratios are 60%, 70%, and 90%. Also, the achieved result in the 80% case is very close to the best one. Therefore, combining the above discussions on data selection time consumption, we can claim that our method can achieve promising performance on follow-up tasks with lower time costs in data selection.

4.3 MORE ANALYSES

Unseen network structure generalization. Prior works (Yang et al., 2022) show that, although we perform data selection with a predefined network structure, the selected data, i.e., the coreset, can generalize to those unknown network architectures that are inaccessible during data selection. As did in this line, we train ResNet-50 on CIFAR-100 and Tiny-ImageNet for data selection and further use the selected data to train different network architectures, i.e., SENet (Hu et al., 2018) and

---

[1]We utilize the PyTorch implementation in https://github.com/nimarb/pytorch_influence_functions.

CIFAR-100					
Model transfer	ResNet-50→SENet		ResNet-50→EfficientNet-B0		
Method / Ratio	20%	30%	20%	30%	Ave. rank ↓
Random	53.57±1.18	61.08±1.20	42.42±1.36	53.54±1.11	3.8
Herding	53.77±0.66	62.52±0.36	43.90±1.10	52.75±0.77	3.5
Forgetting	46.35±0.96	56.21±0.87	37.98±0.15	43.89±0.43	7.0
GraNd-score	49.98±0.54	57.26±0.74	39.34±0.88	49.36±1.02	5.8
EL2N-score	39.09±1.32	47.31±0.64	26.50±0.33	37.03±0.52	8.0
Optimization-based	54.02±0.77	60.84±0.95	43.92±0.50	52.88±0.66	3.0
Self-sup.-selection	54.16±0.42	60.22±0.55	43.65±0.94	48.39±1.50	4.0
Moderate-DS	**55.57±0.56**	**63.01±0.31**	**48.58±0.15**	**54.37±0.32**	**1.0**
Tiny-ImageNet					
Model transfer	ResNet-50→SENet		ResNet-50→EfficientNet-B0		
Method / Ratio	20%	30%	20%	30%	Ave. rank ↓
Random	34.13±0.71	39.57±0.53	32.88±1.52	39.11±0.94	3.5
Herding	34.86±0.55	38.60±0.68	32.21±0.54	37.53±0.22	5.0
Forgetting	33.40±0.64	39.79±0.78	31.12±0.21	38.38±0.65	5.0
GraNd-score	35.12±0.54	41.14±0.42	33.20±0.67	**40.02±0.35**	1.8
EL2N-score	31.08±1.11	38.26±0.45	31.34±0.49	36.88±0.32	7.5
Optimization-based	33.18±0.52	39.42±0.77	32.16±0.90	38.52±0.50	5.0
Self-sup.-selection	31.74±0.71	38.45±0.39	30.99±1.03	37.96±0.77	7.0
Moderate-DS	**36.04±0.15**	**41.40±0.20**	**34.26±0.48**	39.57±0.29	**1.3**

Table 2: Mean and standard deviation of results (%) on CIFAR-100 and Tiny-ImageNet with transferred models. The average rank is calculated with the ranks of a method in 20% and 30% cases of "ResNet-50→SENet" and "ResNet-50→EfficientNet-B0". The best result in each case is in bold.

Figure 3: Illustrations of results of ablation study on different data selection ways. (a) Evaluations on CIFAR-100. (b) Evaluations on Tiny-ImageNet.	Figure 4: Illustrations of boosting advanced methods with moderate coresets. (a) Evaluations on CIFAR-100. (b) Evaluations on Tiny-ImageNet.

EfficientNet-B0 (Tan & Le, 2019). The experimental results in Table 2 show that the selected data by our method has a good generalization on unseen network architectures. The superiority indicates that the proposed method can be employed in a wide range of applications regardless of specific network architectures.

Ablation study. We compare the proposed method with the other three data selection ways that share the same distance-based score criterion. Specifically, we perform data selection with (1) data points close to class centers (i.e., Herding); (2) data points far from class centers (named as Herding-c); (3) data points at two ends, i.e., both data points close to class centers and far from class centers (named as Two-ends). Experiments are conducted on CIFAR-100 and Tiny-ImageNet. Note that data points far from class centers make model training difficult, hence degenerating model performance, especially when the coreset is limited to a small size. The results are shown in Figure 3, which demonstrate that our method is more promising than other data selection ways.

Boosting baselines with moderate coresets. As discussed before, we propose the concept of moderate coresets, which can be applied to other score-based data selection methods. To support the claim, we apply moderate coresets to boost baselines GraNd-score and EL2N-score. In other words, based on the score criteria of GraNd-score and EL2N-score, we select the data points with scores close to the score median. We name the boosted methods as GraNd-score+ and EL2N-score+ respectively. Experiments are conducted on CIFAR-100 and Tiny-ImageNet. We provide the evidence in Figure 4, which demonstrates the use of moderate coresets can bring clear performance improvement.

Figure 5: Illustrations of comparing our proposed method with several data selection baselines on synthetic CIFAR-100 and Tiny-ImageNet, where corruption is injected. Exact numerical results (mean±standard deviation) can be found in in Appendix A for convenient checks.

5 EVALUATIONS IN COMPLEX REALISTIC SCENARIOS

5.1 ROBUSTNESS TO CORRUPTED IMAGES

In realistic scenes, training data is always polluted by corrupted images (Wang et al., 2018b; Hendrycks & Dietterich, 2019; Li et al., 2021; Xia et al., 2021). Here, we demonstrate that our method is more robust than several state-of-the-art methods, when corrupted images occur. Specifically, to corrupt images, we employ the following five types of realistic noises, i.e., *Gaussion noise*, *random occlusion*, *resolution*, *fog*, and *motion blur*, as shown in Figure 6 of Appendix B. The noises are then injected into the fractional images of CIFAR-100 and Tiny-ImageNet. The other settings are kept unchanged. The corruption rate is set to 5%, 10%, and 20% respectively. Experimental results are presented in Figure 5.

As can be seen, for CIFAR-100 and Tiny-ImageNet with corrupted images, with the variability of selection ratios, our method outperforms baseline methods in most cases. More specifically, for the method that prefers easier data reduce the side-effect of corrupted images, e.g., Herding, although corrupted images can be less selected, a covariate-shift problem (Sugiyama & Kawanabe, 2012) arises to degenerate model performance if we only use these data. In addition, for the method that prefers harder data, e.g., Forgetting, the corruptions are incorrectly selected, leading to unsatisfactory performance. Compared with baselines, our method selects moderate data to avoid corruption meanwhile ensure generalization, which hence achieves better performance.

5.2 ROBUSTNESS TO LABEL NOISE

Real-world datasets inevitably involve label noise, where partial clean labels are flipped to incorrect ones, resulting in mislabeled data (Northcutt et al., 2021). Label-noise robustness is of significance for the method's application (Song et al., 2022). To discuss the robustness of different data selection methods against label noise, we conduct synthetic experiments with CIFAR-100 and Tiny-ImageNet. Symmetric label noise (Patrini et al., 2017) is injected to generate mislabeled data. The noise rate is set to 20%. Although mislabeled data makes class centers somewhat biased, Herding and our method can empirically works well. Experimental results are provided in Table 3. The results demonstrate that, compared with prior state-of-the-arts, our method is very effective in the situation of data selection under label noise.

5.3 DEFENSE AGAINST ADVERSARIAL ATTACKS

It has been shown that deep networks are vulnerable to adversarial examples that are crafted by adding imperceptible but adversarial noise on natural examples (Szegedy et al., 2014; Ma et al.,

	CIFAR-100 (Label noise)		Tiny-ImageNet (Label noise)		
Method / Ratio	20%	30%	20%	30%	Ave. rank ↓
Random	34.47±0.64	43.26±1.21	17.78±0.44	23.88±0.42	3.8
Herding	**42.29±1.75**	**50.52±3.38**	18.98±0.44	24.23±0.29	**1.5**
Forgetting	36.53±1.11	45.78±1.04	13.20±0.38	21.79±0.43	5.0
GraNd-score	31.72±0.67	42.80±0.30	18.28±0.32	23.72±0.18	4.5
EL2N-score	29.82±1.19	33.62±2.35	13.93±0.69	18.57±0.31	7.8
Optimization-based	32.79±0.62	41.80±1.69	14.77±0.95	22.52±0.77	5.8
Self-sup.-selection	31.08±0.78	41.87±0.63	15.10±0.73	21.01±0.36	6.3
Moderate-DS	40.25±0.12	48.53±1.60	**19.64±0.40**	**24.96±0.30**	**1.5**

Table 3: Mean and standard deviation of experimental results (%) on CIFAR-100 and Tiny-ImageNet with mislabeled data. The average rank is calculated with the ranks of a method in 20% and 30% cases in two synthetic datasets. The best result in each case is in bold.

	CIFAR-100 (PGD attacks)		CIFAR-100 (GS attacks)		
Method / Ratio	20%	30%	20%	30%	Ave. rank ↓
Random	43.23±0.31	**52.86±0.34**	44.23±0.41	53.44±0.44	1.8
Herding	40.21±0.72	49.62±0.65	39.92±1.03	50.14±0.15	5.0
Forgetting	35.90±1.30	47.37±0.99	37.55±0.53	46.88±1.91	6.8
GraNd-score	40.87±0.84	50.13±0.30	40.77±1.11	49.88±0.83	3.8
EL2N-score	26.61±0.58	34.50±1.02	26.72±0.66	35.55±1.30	8.0
Optimization-based	38.29±1.77	46.25±1.82	41.36±0.92	49.10±0.81	5.5
Self-sup.-selection	40.53±1.15	49.95±0.50	40.74±1.66	51.23±0.25	4.0
Moderate-DS	**43.60±0.97**	51.66±0.39	**44.69±0.68**	**53.71±0.37**	**1.3**
	Tiny-ImageNet (PGD attacks)		Tiny-ImageNet (GS attacks)		
Method / Ratio	20%	30%	20%	30%	Ave. rank ↓
Random	20.93±0.30	26.60±0.98	22.43±0.31	26.89±0.31	3.5
Herding	21.61±0.36	25.95±0.19	23.04±0.28	27.39±0.14	3.0
Forgetting	20.38±0.47	26.12±0.19	22.06±0.31	27.21±0.21	4.5
GraNd-score	20.76±0.21	26.34±0.32	22.56±0.30	27.52±0.40	3.0
EL2N-score	16.67±0.62	22.36±0.42	19.93±0.57	24.65±0.32	7.8
Optimization-based	19.26±0.77	24.55±0.92	21.26±0.24	25.88±0.37	6.0
Self-sup.-selection	19.23±0.46	23.92±0.51	19.70±0.20	24.73±0.39	7.3
Moderate-DS	**21.81±0.37**	**27.11±0.20**	**23.20±0.13**	**28.89±0.27**	**1.0**

Table 4: Mean and standard deviation of experimental results (%) on CIFAR-100 and Tiny-ImageNet with adversarial examples. The average rank is calculated with the ranks of a method in 20% and 30% cases of two types of attacks. The best result in each case is in bold.

2018; Eykholt et al., 2018; Huang et al., 2021a). In the real world, adversarial robustness is greatly important for the application of a method (Tramèr et al., 2018; Dong et al., 2022).

We utilize two popularly used adversarial attacks, i.e., PGD attacks (Madry et al., 2017) and GS attacks (Goodfellow et al., 2014). We set default perturbation budget $\epsilon = 8/255$ for both CIFAR-100 and Tiny-ImageNet. We use the adversarial attacks and the models trained on CIFAR-100 and Tiny-ImageNet to achieve adversarial examples. Afterwards, different methods are applied on adversarial examples and model retraining on selected data. Experimental results are provided in Table 4. As can be seen, the proposed method is more robust than several state-of-the-art methods, leading to the first average rank. The results confirm that our method is more competitive to be applied in practice.

6 CONCLUSION

In this paper, we focus on data selection to boost data-efficient deep learning. Different from existing works that are usually limited to preconceived scenarios, we propose a concept of the moderate coreset to generalize different scenarios. As a proof-of-concept, a universal method operating with data representations is presented for data selection in various circumstances. Extensive experiments confirm the effectiveness of the proposed method. For future work, we are interested in adapting our method to other domains such as natural language processing. Furthermore, we are also interested in applying the concept of the moderate coreset concept to multiple advanced data selection methods theoretically and empirically.

REFERENCES

Alessandro Achille and Stefano Soatto. Emergence of invariance and disentanglement in deep representations. *The Journal of Machine Learning Research*, 19(1):1947–1980, 2018.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Mohamed Ishmael Belghazi, Aristide Baratin, Sai Rajeswar, Sherjil Ozair, Yoshua Bengio, Aaron Courville, and R Devon Hjelm. Mine: mutual information neural estimation. *arXiv preprint arXiv:1801.04062*, 2018.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *ICML*, pp. 41–48, 2009.

Ondrej Bohdal, Yongxin Yang, and Timothy Hospedales. Flexible dataset distillation: Learn labels instead of images. *arXiv preprint arXiv:2006.08572*, 2020.

George Cazenavette, Tongzhou Wang, Antonio Torralba, Alexei A Efros, and Jun-Yan Zhu. Dataset distillation by matching training trajectories. In *CVPR*, pp. 4750–4759, 2022.

Kwan Ho Ryan Chan, Yaodong Yu, Chong You, Haozhi Qi, John Wright, and Yi Ma. Redunet: A white-box deep network from the principle of maximizing rate reduction. *Journal Machine Learning Research*, 23(114):1–103, 2022.

Tianlong Chen, Yu Cheng, Zhe Gan, Jingjing Liu, and Zhangyang Wang. Data-efficient gan training beyond (just) augmentations: A lottery ticket perspective. In *NeurIPS*, pp. 20941–20955, 2021.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

Cody Coleman, Christopher Yeh, Stephen Mussmann, Baharan Mirzasoleiman, Peter Bailis, Percy Liang, Jure Leskovec, and Matei Zaharia. Selection via proxy: Efficient data selection for deep learning. In *ICLR*, 2020.

Elliot Creager, Jörn-Henrik Jacobsen, and Richard Zemel. Environment inference for invariant learning. In *ICML*, pp. 2189–2200, 2021.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, pp. 248–255, 2009.

Yinpeng Dong, Ke Xu, Xiao Yang, Tianyu Pang, Zhijie Deng, Hang Su, and Jun Zhu. Exploring memorization in adversarial training. In *ICLR*, 2022.

Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *CVPR*, pp. 1625–1634, 2018.

Vitaly Feldman and Chiyuan Zhang. What neural networks memorize and why: Discovering the long tail via influence estimation. In *NeurIPS*, pp. 2881–2891, 2020.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Priya Goyal, Quentin Duval, Jeremy Reizenstein, Matthew Leavitt, Min Xu, Benjamin Lefaudeux, Mannat Singh, Vinicius Reis, Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Ishan Misra. Vissl. https://github.com/facebookresearch/vissl, 2021.

Bo Han, Quanming Yao, Xingrui Yu, Gang Niu, Miao Xu, Weihua Hu, Ivor Tsang, and Masashi Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. In *NeurIPS*, 2018.

Sariel Har-Peled, Dan Roth, and Dav Zimak. Maximum margin coresets for active and noise tolerant learning. In *IJCAI*, pp. 836–841, 2007.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *ICLR*, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *ICLR*, 2017.

Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *CVPR*, pp. 7132–7141, 2018.

Hanxun Huang, Yisen Wang, Sarah Erfani, Quanquan Gu, James Bailey, and Xingjun Ma. Exploring architectural ingredients of adversarially robust deep neural networks. In *NeurIPS*, pp. 5545–5559, 2021a.

Jiawei Huang, Ruomin Huang, Wenjie Liu, Nikolaos Freris, and Hu Ding. A novel sequential coreset method for gradient descent algorithms. In *ICML*, pp. 4412–4422, 2021b.

Sheng-Jun Huang, Rong Jin, and Zhi-Hua Zhou. Active learning by querying informative and representative examples. In *NeurIPS*, 2010.

Ashish Jaiswal, Ashwin Ramesh Babu, Mohammad Zaki Zadeh, Debapriya Banerjee, and Fillia Makedon. A survey on contrastive self-supervised learning. *Technologies*, 9(1):2, 2020.

Gareth James, Daniela Witten, Trevor Hastie, and Robert Tibshirani. *An introduction to statistical learning*, volume 112. Springer, 2013.

Lu Jiang, Zhengyuan Zhou, Thomas Leung, Li-Jia Li, and Li Fei-Fei. Mentornet: Learning data-driven curriculum for very deep neural networks on corrupted labels. In *ICML*, pp. 2304–2313, 2018.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *ICML*, pp. 1885–1894, 2017.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *CS 231N*, 7(7):3, 2015.

Shiye Lei, Fengxiang He, Yancheng Yuan, and Dacheng Tao. Understanding deep learning via decision boundary. *arXiv preprint arXiv:2206.01515*, 2022.

Junnan Li, Caiming Xiong, and Steven CH Hoi. Mopro: Webly supervised learning with momentum prototypes. In *ICLR*, 2021.

Xiaotong Li, Yongxing Dai, Yixiao Ge, Jun Liu, Ying Shan, and Ling-Yu Duan. Uncertainty modeling for out-of-distribution generalization. In *ICLR*, 2022.

Jie Lu, Anjin Liu, Fan Dong, Feng Gu, Joao Gama, and Guangquan Zhang. Learning under concept drift: A review. *IEEE Transactions on Knowledge and Data Engineering*, 31(12):2346–2363, 2018.

Yueming Lyu and Ivor W Tsang. Curriculum loss: Robust learning and generalization against label corruption. In *ICLR*, 2019.

Xingjun Ma, Bo Li, Yisen Wang, Sarah M Erfani, Sudanthi Wijewickrema, Grant Schoenebeck, Dawn Song, Michael E Houle, and James Bailey. Characterizing adversarial subspaces using local intrinsic dimensionality. In *ICLR*, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Shi Na, Liu Xumin, and Guan Yong. Research on k-means clustering algorithm: An improved k-means clustering algorithm. In *International Symposium on intelligent information technology and security informatics*, pp. 63–67, 2010.

Timothy Nguyen, Zhourong Chen, and Jaehoon Lee. Dataset meta-learning from kernel ridge-regression. In *ICLR*, 2021.

Curtis Northcutt, Lu Jiang, and Isaac Chuang. Confident learning: Estimating uncertainty in dataset labels. *Journal of Artificial Intelligence Research*, 70:1373–1411, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, 2019.

Giorgio Patrini, Alessandro Rozza, Aditya Krishna Menon, Richard Nock, and Lizhen Qu. Making deep neural networks robust to label noise: A loss correction approach. In *CVPR*, pp. 1944–1952, 2017.

Mansheej Paul, Surya Ganguli, and Gintare Karolina Dziugaite. Deep learning on a data diet: Finding important examples early in training. In *NeurIPS*, pp. 20596–20607, 2021.

Vihari Piratla, Praneeth Netrapalli, and Sunita Sarawagi. Efficient domain generalization via common-specific low-rank decomposition. In *ICML*, pp. 7728–7738, 2020.

Geoff Pleiss, Tianyi Zhang, Ethan Elenberg, and Kilian Q Weinberger. Identifying mislabeled data using the area under the margin ranking. In *NeurIPS*, pp. 17044–17056, 2020.

Omead Pooladzandi, David Davini, and Baharan Mirzasoleiman. Adaptive second order coresets for data-efficient machine learning. In *ICML*, pp. 17848–17869, 2022.

Roy Schwartz, Jesse Dodge, Noah A Smith, and Oren Etzioni. Green ai. *Communications of the ACM*, 63(12):54–63, 2020.

Zheyan Shen, Jiashuo Liu, Yue He, Xingxuan Zhang, Renzhe Xu, Han Yu, and Peng Cui. Towards out-of-distribution generalization: A survey. *arXiv preprint arXiv:2108.13624*, 2021.

Hwanjun Song, Minseok Kim, Dongmin Park, Yooju Shin, and Jae-Gil Lee. Learning from noisy labels with deep neural networks: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, 2022.

Ben Sorscher, Robert Geirhos, Shashank Shekhar, Surya Ganguli, and Ari S Morcos. Beyond neural scaling laws: beating power law scaling via data pruning. *arXiv preprint arXiv:2206.14486*, 2022.

Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. In *ACL*, 2019.

Felipe Petroski Such, Aditya Rawal, Joel Lehman, Kenneth Stanley, and Jeffrey Clune. Generative teaching networks: Accelerating neural architecture search by learning to generate synthetic training data. In *ICML*, pp. 9206–9216, 2020.

Ilia Sucholutsky and Matthias Schonlau. Soft-label dataset distillation and text dataset distillation. In *IJCNN*, pp. 1–8, 2021.

Masashi Sugiyama and Motoaki Kawanabe. *Machine learning in non-stationary environments: Introduction to covariate shift adaptation*. MIT press, 2012.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *ICML*, pp. 6105–6114, 2019.

Naftali Tishby, Fernando C Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.

Mariya Toneva, Alessandro Sordoni, Remi Tachet des Combes, Adam Trischler, Yoshua Bengio, and Geoffrey J Gordon. An empirical study of example forgetting during deep neural network learning. In *ICLR*, 2019.

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. Ensemble adversarial training: Attacks and defenses. In *ICLR*, 2018.

Kai Wang, Bo Zhao, Xiangyu Peng, Zheng Zhu, Shuo Yang, Shuo Wang, Guan Huang, Hakan Bilen, Xinchao Wang, and Yang You. Cafe: Learning to condense dataset by aligning features. In *CVPR*, pp. 12196–12205, 2022.

Tongzhou Wang, Jun-Yan Zhu, Antonio Torralba, and Alexei A Efros. Dataset distillation. *arXiv preprint arXiv:1811.10959*, 2018a.

Yisen Wang, Weiyang Liu, Xingjun Ma, James Bailey, Hongyuan Zha, Le Song, and Shu-Tao Xia. Iterative learning with open-set noisy labels. In *CVPR*, pp. 8688–8696, 2018b.

Hongxin Wei, Lei Feng, Xiangyu Chen, and Bo An. Combating noisy labels by agreement: A joint training method with co-regularization. In *CVPR*, 2020.

Max Welling. Herding dynamical weights to learn. In *ICML*, pp. 1121–1128, 2009.

Zhi-Fan Wu, Tong Wei, Jianwen Jiang, Chaojie Mao, Mingqian Tang, and Yu-Feng Li. Ngc: a unified framework for learning with open-world noisy data. In *ICCV*, pp. 62–71, 2021.

Xiaobo Xia, Tongliang Liu, Bo Han, Mingming Gong, Jun Yu, Gang Niu, and Masashi Sugiyama. Instance correction for learning with open-set noisy labels. *arXiv preprint arXiv:2106.00455*, 2021.

Shuo Yang, Zeke Xie, Hanyu Peng, Min Xu, Mingming Sun, and Ping Li. Dataset pruning: Reducing training data by examining generalization influence. *arXiv preprint arXiv:2205.09329*, 2022.

Fisher Yu, Haofeng Chen, Xin Wang, Wenqi Xian, Yingying Chen, Fangchen Liu, Vashisht Madhavan, and Trevor Darrell. Bdd100k: A diverse driving dataset for heterogeneous multitask learning. In *CVPR*, pp. 2636–2645, 2020a.

Yaodong Yu, Kwan Ho Ryan Chan, Chong You, Chaobing Song, and Yi Ma. Learning diverse and discriminative representations via the principle of maximal coding rate reduction. In *NeurIPS*, pp. 9422–9434, 2020b.

Zhilu Zhang and Mert Sabuncu. Generalized cross entropy loss for training deep neural networks with noisy labels. In *NeurIPS*, 2018.

Bo Zhao and Hakan Bilen. Dataset condensation with differentiable siamese augmentation. In *ICML*, pp. 12674–12685, 2021.

Bo Zhao, Konda Reddy Mopuri, and Hakan Bilen. Dataset condensation with gradient matching. In *ICLR*, 2021.

Xiaoling Zhou and Ou Wu. Which samples should be learned first: Easy or hard? *arXiv preprint arXiv:2110.05481*, 2021.

A EXACT NUMERICAL EXPERIMENTAL RESULTS

In the main paper, we have provided the illustrations of comparing the proposed method (Moderate-DS) with several state-of-the-arts. Here, exact numerical experimental results are presented in Tables 5, 6, and 7 for checks and references.

CIFAR-100							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	50.26±3.24	53.61±2.73	64.32±1.77	71.03±0.75	74.12±0.56	78.14±0.55	3.6
Herding	48.39±1.42	50.89±0.97	62.99±0.61	70.61±0.44	74.21±0.49	78.14±0.55	4.8
Forgetting	35.57±1.40	49.83±0.91	59.65±2.50	**73.34±0.39**	**77.50±0.53**	78.14±0.55	4.4
GraNd-score	42.65±1.39	53.14±1.28	60.52±0.79	69.70±0.68	74.67±0.79	78.14±0.55	5.4
EL2N-score	27.32±1.16	41.98±0.54	50.47±1.20	69.23±1.00	75.96±0.88	78.14±0.55	6.6
Optimization-based	42.16±3.30	53.19±2.14	58.93±0.98	68.93±0.70	75.62±0.33	78.14±0.55	5.6
Self-sup.-selection	44.45±2.51	54.63±2.10	62.91±1.20	70.70±0.82	75.29±0.45	78.14±0.55	3.8
Moderate-DS	**51.83±0.52**	**57.79±1.61**	**64.92±0.93**	71.87±0.91	75.44±0.40	78.14±0.55	**1.8**
CIFAR-100 with 5% corrupted images							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	43.14±3.04	54.19±2.92	64.21±2.39	69.50±1.06	72.90±0.52	77.26±0.39	4.0
Herding	42.50±1.27	53.88±0.37	60.54±0.94	69.15±0.55	73.47±0.89	77.26±0.39	4.8
Forgetting	32.42±0.74	49.72±1.64	54.84±2.20	70.22±2.00	75.19±0.40	77.26±0.39	5.0
GraNd-score	42.24±0.57	53.48±0.76	60.17±1.66	69.16±0.81	73.35±0.81	77.26±0.39	5.4
EL2N-score	26.13±1.75	39.01±2.14	49.89±1.87	68.36±1.41	75.18±0.36	77.26±0.39	6.8
Optimization-based	38.25±3.04	50.88±0.62	57.26±0.93	68.02±0.39	73.77±0.56	77.26±0.39	6.2
Self-sup.-selection	44.24±0.48	55.99±1.21	61.03±0.59	69.96±1.07	74.56±1.17	77.26±0.39	2.8
Moderate-DS	**46.78±1.90**	**57.36±1.22**	**65.40±0.39**	**71.46±0.19**	**75.64±0.61**	77.26±0.39	**1.0**
CIFAR-100 with 10% corrupted images							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	43.27±3.01	53.94±2.78	62.17±1.29	68.41±1.21	73.50±0.73	76.50±0.63	3.6
Herding	44.34±1.07	53.31±1.49	60.13±0.38	68.20±0.74	74.34±0.14	76.50±0.63	4.2
Forgetting	30.43±0.70	47.50±1.43	53.16±0.44	70.36±0.82	75.11±0.71	76.50±0.63	5.0
GraNd-score	36.36±1.06	52.26±2.06	60.22±1.39	68.96±0.68	72.78±0.51	76.50±0.63	5.2
EL2N-score	21.75±1.56	30.80±2.23	41.06±1.23	64.82±1.48	73.47±1.30	76.50±0.63	7.6
Optimization-based	37.22±0.39	48.92±1.38	56.88±1.48	67.73±2.15	72.94±1.90	76.50±0.63	6.2
Self-sup.-selection	42.01±1.31	54.47±1.19	61.37±0.68	68.52±1.24	74.73±0.36	76.50±0.63	3.2
Moderate-DS	**47.02±0.66**	**55.60±1.67**	**62.18±1.86**	**71.83±0.78**	**75.66±0.66**	76.50±0.63	**1.0**
CIFAR-100 with 20% corrupted images							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	40.99±1.46	50.38±1.39	57.24±0.65	65.21±1.31	71.74±0.28	74.92±0.88	4.2
Herding	**44.42±0.46**	53.57±0.31	60.72±1.78	69.09±1.73	73.08±0.98	74.92±0.88	2.0
Forgetting	26.39±0.17	40.78±2.02	49.95±2.31	65.71±1.28	**73.67±1.12**	74.92±0.88	5.2
GraNd-score	36.33±2.66	46.21±1.48	55.51±0.76	64.59±2.04	70.14±1.36	74.92±0.88	5.4
EL2N-score	21.64±2.03	23.78±1.66	35.71±1.17	56.32±0.86	69.66±0.43	74.92±0.88	4.6
Optimization-based	33.42±1.60	45.37±2.81	54.06±1.74	65.19±1.27	70.06±0.83	74.92±0.88	6.0
Self-sup.-selection	42.61±2.44	54.04±1.90	59.51±1.22	68.97±0.96	72.33±0.20	74.92±0.88	2.8
Moderate-DS	42.98±0.87	**55.80±0.95**	**61.84±1.96**	**70.05±1.29**	**73.67±0.30**	74.92±0.88	**1.2**

Table 5: Mean and standard deviation of experimental results (%) on different versions of CIFAR-100. The average rank is calculated with the ranks of a method in 20%, 30%, 40%, 60%, and 80% cases. The best result in each case is in bold.

B SUPPLEMENTARY EXPERIMENTAL SETTINGS

In the main paper, we employ five types of realistic noises, i.e., *Gaussion noise*, *random occlusion*, *resolution*, *fog*, and *motion blur* to corrupt images. The noise is shown in Figure 6.

Figure 6: Examples of noise injected to CIFAR-100 images.

Tiny-ImageNet							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	24.02±0.41	29.79±0.27	34.41±0.46	40.96±0.47	45.74±0.61	49.36±0.25	2.8
Herding	24.09±0.45	29.39±0.53	34.13±0.37	40.86±0.61	45.45±0.33	49.36±0.25	3.8
Forgetting	22.37±0.71	28.67±0.54	33.64±0.32	41.14±0.43	**46.77±0.31**	49.36±0.25	3.6
GraNd-score	23.56±0.52	29.66±0.37	34.33±0.50	40.77±0.42	45.96±0.56	49.36±0.25	3.6
EL2N-score	19.74±0.26	26.58±0.40	31.93±0.28	39.12±0.46	45.32±0.27	49.36±0.25	6.8
Optimization-based	13.88±2.17	23.75±1.62	29.77±0.94	37.05±2.81	43.76±1.50	49.36±0.25	8.0
Self-sup.-selection	20.89±0.42	27.66±0.50	32.50±0.30	39.64±0.39	44.94±0.34	49.36±0.25	6.2
Moderate-DS	**25.29±0.38**	**30.57±0.20**	**34.81±0.51**	**41.45±0.44**	46.06±0.33	49.36±0.25	**1.2**
Tiny-ImageNet with 5% corrupted images							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	23.51±0.22	28.82±0.72	32.61±0.68	39.77±0.35	44.37±0.34	49.02±0.35	4.0
Herding	23.09±0.53	28.67±0.37	33.09±0.32	39.71±0.31	45.04±0.15	49.02±0.35	3.8
Forgetting	21.36±0.28	27.72±0.43	33.45±0.21	**40.92±0.45**	**45.99±0.51**	49.02±0.35	3.0
GraNd-score	22.47±0.23	28.85±0.83	33.81±0.24	40.40±0.15	44.86±0.49	49.02±0.35	3.0
EL2N-score	18.98±0.72	25.96±0.28	31.07±0.63	38.65±0.36	44.21±0.68	49.02±0.35	7.0
Optimization-based	13.65±1.26	24.02±1.35	29.65±1.86	36.55±1.84	43.64±0.71	49.02±0.35	8.0
Self-sup.-selection	19.35±0.57	26.11±0.31	31.90±0.37	38.91±0.29	44.43±0.42	49.02±0.35	5.8
Moderate-DS	**24.63±0.78**	**30.27±0.16**	**34.84±0.24**	40.86±0.42	45.60±0.31	49.02±0.35	**1.4**
Tiny-ImageNet with 10% corrupted images							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	22.67±0.27	28.67±0.52	31.88±0.30	38.63±0.36	43.46±0.20	48.40±0.32	4.4
Herding	22.01±0.18	27.82±0.11	31.82±0.26	39.37±0.18	44.18±0.27	48.40±0.32	4.2
Forgetting	20.06±0.48	27.17±0.36	32.31±0.22	40.19±0.29	**45.51±0.48**	48.40±0.32	3.0
GraNd-score	21.52±0.48	26.98±0.43	32.70±0.19	40.03±0.26	44.87±0.35	48.40±0.32	3.4
EL2N-score	18.59±0.13	25.23±0.18	30.37±0.22	38.44±0.32	44.32±1.07	48.40±0.32	6.6
Optimization-based	14.05±1.74	23.98±1.77	29.12±0.61	36.28±1.88	43.52±0.31	48.40±0.32	7.8
Self-sup.-selection	19.47±0.26	26.51±0.55	31.78±0.14	38.87±0.54	44.69±0.29	48.40±0.32	5.4
Moderate-DS	**23.79±0.16**	**29.56±0.16**	**34.60±0.12**	**40.36±0.27**	45.10±0.23	48.40±0.32	**1.2**
Tiny-ImageNet with 20% corrupted images							
Method / Selection ratio	20%	30%	40%	60%	80%	100%	Ave. rank ↓
Random	19.99±0.42	25.93±0.53	30.83±0.44	37.98±0.31	42.96±0.62	46.68±0.43	4.4
Herding	19.46±0.14	24.47±0.33	29.72±0.39	37.50±0.59	42.28±0.30	46.68±0.43	6.6
Forgetting	18.47±0.46	25.53±0.23	31.17±0.24	39.35±0.44	44.55±0.67	46.68±0.43	4.2
GraNd-score	20.07±0.49	26.68±0.44	31.25±0.40	38.21±0.49	42.84±0.72	46.68±0.43	1.8
EL2N-score	18.57±0.30	24.42±0.44	30.04±0.15	37.62±0.44	42.43±0.61	46.68±0.43	6.4
Optimization-based	13.71±0.26	23.33±1.84	29.15±2.84	36.12±1.86	42.94±0.52	46.88±0.43	7.4
Self-sup.-selection	20.22±0.23	26.90±0.50	31.93±0.49	39.74±0.52	44.27±0.10	46.68±0.43	2.2
Moderate-DS	**23.27±0.33**	**29.06±0.36**	**33.48±0.11**	**40.07±0.36**	**44.73±0.39**	46.68±0.43	**1.0**

Table 6: Mean and standard deviation of experimental results (%) on Tiny-ImageNet. The average rank is calculated with the ranks of a method in 20%, 30%, 40%, 60%, and 80% cases. The best result in each case is in bold.

ImageNet-1k						
Method / Selection ratio	60%	70%	80%	90%	100%	Ave. rank ↓
Random	87.91	88.63	89.52	89.57	90.86	6.8
Herding	88.25	88.81	89.60	90.02	90.86	5.5
Forgetting	89.13	89.47	90.10	90.37	90.86	3.8
GraNd-score	88.21	89.30	89.94	90.41	90.86	4.8
EL2N-score	88.48	89.82	90.34	90.57	90.86	2.5
Optimization-based	-	-	-	-	-	-
Self-sup.-selection	87.59	89.56	**90.74**	90.49	90.86	3.5
Moderate-DS	**89.23**	**89.94**	90.65	**90.75**	90.86	**1.3**

Table 7: Top-5 test accuracy (%) on ImageNet-1k. The average rank is calculated with the ranks of a method in 60%, 70%, 80%, and 90% cases. The best result in each case is in bold.