Soft Merging of Experts with Adaptive Routing

Abstract

Neural networks that learn to route their inputs through different "expert" subnetworks provide a form of modularity that standard dense models lack. Despite their possible benefits, modular models with learned routing often underperform their parameter-matched dense counterparts as well as models that use non-learned heuristic routing strategies. In this paper, we hypothesize that these shortcomings stem from the gradient estimation techniques used to train modular models that use non-differentiable discrete routing decisions. To address this issue, we introduce **S**oft **M**erging of **E**xperts with **A**daptive **R**outing (SMEAR), which avoids discrete routing by using a single "merged" expert constructed via a weighted average of all of the experts' parameters. By routing activations through a single merged expert, SMEAR does not incur a significant increase in computational costs and enables standard gradient-based training. We empirically validate that models using SMEAR outperform models that route based on metadata or learn routing through gradient estimation. Furthermore, we provide qualitative analysis demonstrating that the experts learned via SMEAR exhibit a significant amount of specialization.

1 Introduction

Neural networks typically use all of their parameters to process a given input. As such, the capabilities of a model are distributed across the parameters of a model in a self-organizing way (Zeiler & Fergus, 2014; De Cao et al., 2021; Csordás et al., 2021; Bau et al., 2020; Wang et al., 2022a). Explicitly specializing different parts of a model to different capabilities can provide various benefits, including reduced interference across downstream tasks (Sanh et al., 2021; Wei et al., 2021; Zamir et al., 2018; Bao et al., 2021) or languages (Pires et al., 2019; Liu et al., 2020b; Xue et al., 2020). Furthermore, dedicating specific parameters to specific capabilities enables a form of modularity where a capability can be added, removed, or modified by adding, removing, or modifying the corresponding parameters (Pfeiffer et al., 2023). Activating only a subset of the model's parameter for a given input also decouples the computational cost of a model from the number of parameters it has (Shazeer et al., 2017; Fedus et al., 2021), though we do not focus on this benefit in this paper.

Conditional computation techniques provide a way to build models that adaptively choose a subset of their parameters to apply to a given input. A common way to use conditional computation in this setting is to introduce specialized subnetworks called *experts* that are controlled by *routers* that decide which experts should be active. When the model is trained on diverse data, this form of conditional computation can enable modular learning by allowing experts to specialize to different types of inputs and flexibly share knowledge (Ma et al., 2019). However, because routing involves making a discrete decision as to which expert to use, the loss on the model's prediction cannot back-propagate though the routing decision to update the router. Consequently, models with conditional computation often require gradient estimation techniques for training (Clark et al., 2022; Fedus et al., 2021; Bengio et al., 2013). In practice, past work has shown that models with conditional computation do not always learn effective routing strategies. For example, Mittal et al. (2022) investigate models with a continuous router in a controlled setting and find the models do not route examples from the same group to the same experts and perform poorly compared to models with oracle routing. However, models with task- or domain-specific subnetworks (Gururangan et al., 2021; Kudugunta et al., 2021) provide evidence that it is possible to train performant models with specialized experts. As an

Figure 1: The discrete routing decisions commonly used in models that route activations among experts require the use of gradient estimation (left). We propose SMEAR (right), which uses a given router's distribution to average the parameters of the corresponding experts and then routes the input through a single merged expert. SMEAR achieves better performance than models with discrete routing, can be trained with standard backpropagation, and does not incur significant additional computational costs.

extreme example, Roller et al. (2021) achieves results comparable to learned routing with a fixed random routing. Relatedly, Fedus et al. (2021) find the gain from scaling up parameters by $30\times$ with a sparsely activated model is smaller than scaling up both parameters and FLOPs by $3\times$ in a dense model. As a possible explanation, Clark et al. (2022) study how models with conditional computation improve with scale and find a detrimental term that scales with the product of the log number of experts and active parameters.

In this work, we hypothesize that issues with conditional computation stem from issues with gradient estimation. Specifically, we focus on experimental settings where we can compare learned routing to a performant hand-designed heuristic routing scheme. We find that the gradient estimation techniques we consider often produce models that underperform heuristic routing, despite the fact that they could in principle learn a better routing strategy. To address this shortcoming, we introduce **S**oft **M**erging of **E**xperts with **A**daptive **R**outing (SMEAR), a method for training modular models with specialized experts and learned routing. Given an input, which may be a sequence of tokens or an image, SMEAR works by using the router's distribution of the input over experts to compute a weighted average of the parameters of the individual experts. The input activations are then sent through the *merged* expert, which results in a similar computational cost to discrete routing with a single expert. However, the fact that all components of SMEAR are fully differentiable enables standard gradient-based training. Empirically, we show that SMEAR significantly attains a favorable performance/cost tradeoff to 1) discrete routing solutions found via gradient estimation, 2) heuristic routing schemes, and 3) state-of-the-art baselines for learning modular models. We also qualitatively validate that the experts learned by SMEAR specialize to different types of inputs and share parameters across related tasks. Put together, our results show that SMEAR provides an effective alternative for modular models that use adaptive routing among expert subnetworks.

After providing background on conditional computation models and gradient estimators in the following section, we define SMEAR in section 3. We then describe our experimental findings in section 4, discuss related works in section 5, and conclude in section 6.

2 Background

To provide the necessary background for our work, we first explain how sparsely activated neural networks use conditional computation, then discuss gradient estimators that enable learning discrete routing strategies. In addition, we discuss different ways to hand-design "heuristic" routing strategies as well as preexisting techniques for learning modular models that we use as baselines.

2.1 Routing Among Experts

In models that use discrete routing among experts (i.e. subnetworks), experts are organized into blocks that are incorporated as an intermediate layer in a neural network. An expert routing block B comprises a set of

N experts $\{f_1, f_2, \ldots, f_N\}$ and a router R. Experts in the same block accept inputs and produce outputs of the same dimensionality. Given a hidden-state representation u, the output of the i-th expert with parameters θ_i is $f_i(u, \theta_i)$.

2.2 Gradient Estimators

In sparsely activated models that involve discrete adaptive routing, it is not possible to train the router's parameters with standard gradient-based learning. Fortunately, gradient estimators can provide approximate gradients to the router parameters. There are a few common designs shared by models that use gradient estimators to train routers. Their router R often applies a lightweight network to some intermediate hidden states v in the model. The output of the lightweight routing network $R(v)$ parameterizes a discrete probability distribution over the N experts. Different gradient estimators vary in how they make the routing decision from $R(v)$ and how they construct the output from the chosen expert. Additionally, some estimators may introduce additional loss terms.

REINFORCE Gradients can be estimated through discrete operations using reinforcement learning techniques (Schulman et al., 2015; Bengio et al., 2013). In reinforcement learning, a policy loss is used to train an agent to learn optimal actions in an environment. In this paper, we experiment with the REINFORCE algorithm which computes the policy loss as $\log(\pi)r$ where r denotes the received reward for taking an action whose assigned probability is π. When applied to models that use discrete routing among experts, the goal is to train the model to choose the optimal expert to process a given input. Here, the router R acts as an agent that samples an expert to use according to the routing probabilities. In order to train such a router, the router's assigned probability to the sampled expert is used as π and the negative of the model's loss is used as the reward r. The router is therefore trained to pick experts that maximize the reward which, in turn, minimizes the loss. The REINFORCE estimator often suffers from high variance because of the sampling operation. This motivates the use of baselines, which reduce variance without changing the optimal solution. In our work, we follow Clark et al. (2022) and use a baseline b that is generated by a small neural network with a single hidden layer that takes as input v and is trained with the Huber loss. The overall loss function is then

$$L = -\mathbb{E}_{i \sim R(v)} \alpha \log R(v)_i (r - b) - \beta R(v) \log R(v) + \gamma L_{\text{Huber}}(r, b)$$

where α, β, and γ are hyperparameters that correspond to policy gradient weight, policy entropy weight, and value loss weight. In practice, we approximate the expectation with a single sample. During inference, the output of the block B is just $f_i(u, \theta_i)$ where $i = \arg\max R(v)$.

Straight Through Gumbel-Softmax (ST-Gumbel) The Gumbel-Softmax trick (Jang et al., 2016; Maddison et al., 2016) provides a continuous differentiable approximation to sampling from a categorical distribution like the one parameterized by a router. Specifically, Gumbel noise is added to the logits of the distribution and a temperature scale is applied in the softmax operation. Denoting $g_i \sim \text{Gumbel}(0, 1)$ and τ as the temperature, the Gumbel-Softmax trick produces the following modified distribution:

$$\hat{R}(v)_i = \frac{\exp((\log(R(v)_i) + g_i)/\tau)}{\sum_{j=1}^{N} \exp((\log(R(v)_i) + g_i)/\tau)}$$

The expert f_i with the highest assigned probability is chosen by applying an $\arg\max$ operation. In order to approximate gradients through the $\arg\max$ operation, we use the Straight-Through estimator which replaces $f_i(u, \theta_i)$ with $(1 - \text{sg}[\hat{R}(v)_i] + \hat{R}(v)_i)f_i(u, \theta_i)$ where sg stands for the stop-gradient operator. During forward pass, the multiplier for $f_i(u, \theta_i)$ becomes 1 and the multiplier receives gradients for the term $\hat{R}(v)_i$ in the backward pass. In practice, the temperature τ is gradually annealed from a high to low value so that the approximated samples are more and more similar to discrete samples. During inference, we choose an expert according to $\arg\max R(v)$.

Top-k Shazeer et al. (2017) propose a gradient estimation scheme where the router sends the input through the k experts that are assigned the highest probability. Fedus et al. (2021) later found that this router

could be used effectively when $k = 1$. Specifically, the estimator selects the subnetwork with the highest probability and scales its output using its corresponding routing probability. The output of the block is therefore $R(v)_i f_i(u, \theta_i)$, where $i = \arg\max R(v)$.

DSelect-k Hazimeh et al. (2021) proposed a differentiable approximation for the discrete Top-k operation. They parameterize each selection among N experts using m binary variables $z_1, z_2, \ldots z_m$, produced using a learnable weight W as $z = W(v)$, where $m = \log_2(N)$. The selector function r takes these variables and computes

$$r(z)_i = \prod_{j \in B(i-1)} (z_j) \prod_{j \in 1,\ldots,m \setminus B(i-1)} (1 - z_j)$$

where $i \in 1, \ldots, N$ and $B(l)$ returns the non-zero indices in the binary representation of the integer l. A differentiable step function S based on a cubic polynomial is used for the z variables. Finally, each selector operation happens k times to get Top-k selection and an additional learnable parameter G provides a probability distribution over these k selections using the softmax fuction. In addition, entropy regularization is applied to the output of the selector function r, ensuring that it results in one-hot selection during inference. In our work, we consider $k = 1$ to maintain a computational cost similar to other baselines.

2.3 Heuristic Routing

As a point of comparison for techniques that learn adaptive routing, we experiment with three baseline routing strategies that do not require a trained router.

Tag Routing If we have prior knowledge about the data that a model will be applied to, we can hand-design a heuristic routing strategy for choosing which expert to use for a given example based on data properties. Tag routing takes advantage of "tags" associated with a given example (such as its domain or task) and associates each expert in an expert routing block with a particular tag. In this work, we assume each example has a single tag and route each example to its tag's expert.

Hash Routing Roller et al. (2021) propose hash routing, which uses a fixed hashing function to determine which expert to use for a given example. Specifically, each example is assigned a random expert choice in each expert routing block which is used consistently over the course of training and inference. This approach disregards any shared characteristics across examples.

Single-Expert As an additional baseline, we consider models where all inputs are routed to a single expert in each routing block. To provide a fair comparison to models with N experts per block on the basis of both computational cost or parameter count, we consider models with a single expert with either the same number (compute-matched, referred to as "1$\times$ compute") or $N\times$ (parameter-matched, referred to as "1$\times$ parameters") as many parameters as a single expert.

2.4 Methods for Learning Modular Models

Beyond the simple baselines discussed above, we consider three recently proposed methods that aim to learn modular models.

Adamix Adamix (Wang et al., 2022b) uses random routing for each example during training and adds a consistency loss to encourage experts to share information and discourage divergence. During inference, the parameters of all experts are averaged together to form a single expert and no adaptive routing is used.

Latent Skills Latent Skills (Ponti et al., 2022) assumes that the task for each example is known and trains a task-skill matrix that specifies which experts are active for a given task. The binary task-skill matrix is fixed and learned via the Gumbel-Sigmoid trick Maddison et al. (2016). During inference, a merged expert is formed for each task by averaging the parameters of the skill experts weighted according to the task-skill matrix.

Soft MoE Puigcerver et al. (2023) recently proposed Soft MoE, which assigns "slots" to each expert and passes a weighted average of input tokens into each slot. All operations in Soft MoE method are differentiable, avoiding the need for the gradient estimation. We consider Soft MoE with a single slot per expert to ensure fair comparison by having computational cost equivalent to other discrete routing baselines.

3 Soft Merging of Experts with Adaptive Routing

As we will later show in section 4, the gradient estimation techniques used to train models with discrete routing often fail to produce performant routing strategies. Our goal in this work is therefore to explore whether it is possible to train models with adaptive routing among experts without resorting to gradient estimation. Specifically, we aim to achieve better performance by designing an expert and router architecture that facilitates standard end-to-end gradient-based training but does not increase computational costs.

Ensemble Routing One simple idea would be to pass the input of a given expert routing block through *every* expert, and then compute an average of the experts' outputs weighted according the router's distribution, i.e. exactly computing $\mathbb{E}_{i \sim R(v)} f_i(u, \theta_i)$. We refer to this approach as an *ensemble* routing strategy since it corresponds to using the ensemble prediction of the experts. Since the operations involved in computing the average are all differentiable, using an ensemble routing strategy would allow for exact computation of gradients and end-to-end-learning. Unfortunately, such an approach would incur a significant increase in computational costs because it requires computing the output of every expert rather than a single expert.

Merging Experts To explore an alternative fully-differentiable expert routing block, we take inspiration from recent work on *merging* models (Matena & Raffel, 2021; Wortsman et al., 2022b;c; Choshen et al., 2022b; Don-Yehiya et al., 2022; McMahan et al., 2017). These works have shown that averaging the parameters of models that share a common architecture can often produce an aggregate model that shares the capabilities of the individual models. Notably, Wortsman et al. (2022b); Matena & Raffel (2021) found that averaging the weights of multiple fine-tuned models produced a single model that performs comparably to an ensemble of the models. In addition, both Adamix (Wang et al., 2022b) and Latent Skills (Ponti et al., 2022) include steps that involve averaging expert parameters, though neither of these methods learn an adaptive per-example routing strategy. Motivated by these findings, we propose **S**oft **M**erging of **E**xperts with **A**daptive **R**outing (SMEAR), which constructs a single merged expert whose parameters are computed as the weighted average of the experts within a routing block. Each expert's weight is set according to the corresponding routing probability generated by the router. In SMEAR, the input to the routing block is fed into the merged expert and the merged expert's output is used as the output of the block. By averaging parameters, SMEAR implicitly assumes that all experts in the routing block share an identical architecture (thereby inducing a natural one-to-one mapping between parameters in each expert). To the best of our knowledge, all past works focused on routing among experts use experts with a common architecture, so we do not see this assumption as a major limitation.

More explicitly, we define SMEAR as computing the output of an expert routing block using a merged expert computed as

$$\bar{f}(u, \sum_i R(v)_i \theta_i)$$

The merged expert shares the same architecture with the individual experts f_i. Notably, the input of the routing block is only ever processed by $\bar{f}$; activations are never fed to any of the individual experts. To break symmetry, all experts are randomly initialized with different parameter values. Importantly, all operations in SMEAR are fully differentiable, enabling standard gradient-based end-to-end learning. In addition, SMEAR retains the ability to learn an adaptive routing strategy that can route different examples to different experts without relying on hand-specified tags (as in Latent Skills and tag-based routing). We will later show qualitatively that this leads to meaningful specialization of different experts in real-world experiments (section 4.3).

Computational Costs Importantly, SMEAR only ever computes the output of a single expert, suggesting that SMEAR's computational cost could be comparable to single-expert discrete routing and significantly

lower than ensemble routing. However, the averaging operation in SMEAR incurs a nontrivial computational cost. To quantify this cost, we focus on the common expert architecture comprising a dense layer that projects from d-dimensional activations to an m-dimensional vector followed by a nonlinearity and an additional dense layer projecting from m dimensions back to d. For simplicity, we ignore the (relatively minor) cost of the nonlinearity. We assume the input is a length-L sequence of activations with size $L \times d$. In this case, computing the output of the merged experts incurs a computational cost of approximately $L \times 4 \times d \times m$ FLOPs and ensemble routing with N experts would require $N \times L \times 4 \times d \times m$ FLOPs. SMEAR additionally must average together the parameters of N experts, which costs an additional $N \times 2 \times d \times m$ FLOPs.

Some past work on models with discrete routing has the router choose a different expert for each entry in the input sequence of activations (e.g. Fedus et al., 2021; Lewis et al., 2021; Roller et al., 2021). This would require computing the expert average L times, which would make the cost of SMEAR similar to that of ensemble routing. We therefore focus on settings where models make a *single* routing choice for an entire input example (e.g. Gururangan et al., 2021; Kudugunta et al., 2021; Ye et al., 2022). This results in a total cost of approximately $(L \times 4 + N \times 2) \times d \times m$ for SMEAR. Consequently, as long as $L \times 4 \gg N \times 2$, SMEAR and discrete routing have roughly the same computational costs. Given that L is on the order of hundreds or thousands of tokens for text-based tasks and on the order of thousands for vision tasks, $L \times 4$ will be much larger than $N \times 2$ as long as there is a modest number of experts. In our experiments within the T5-GLUE setting, where $L = 128$ and $N = 8$, this results in a minimal runtime difference. Furthermore, we would expect SMEAR to be approximately $\frac{N \times L}{N + L}$ times cheaper than ensemble routing. More concretely, we will later experimentally validate that the wall-clock time required to process an example with SMEAR in real-world experiments is roughly the same as using discrete routing and significant faster than ensemble routing.

4 Experiments

In order to thoroughly evaluate the effectiveness of SMEAR, we perform experiments in two real-world settings that differ in model architecture and modality. We are particularly interested in whether a given approach for learning routing outperforms the heuristic routing strategies described in section 2. As such, we focus on experimental settings where a performant "tag routing" baseline can be designed, i.e. where we have oracle access to metadata that can be used to appropriately route examples. Specifically, we experiment with fine-tuning T5.1.1 Base (Raffel et al., 2020) on datasets from GLUE (Wang et al., 2018) (referred to as T5-GLUE) and fine-tuning a ResNet18 (He et al., 2016) on DomainNet (Peng et al., 2019) (ResNet-DomainNet). In these settings, we add experts to an existing pre-trained backbone in the same way that Adapters are used for parameter-efficient fine-tuning (Houlsby et al., 2019). While past work has also considered using discrete routing among experts to train large-scale models from scratch (Fedus et al., 2021; Shazeer et al., 2017), we focus on modular fine-tuned models in this work and leave large-scale experiments for future work.

4.1 Settings

T5-GLUE In this setting, we focus on training a T5 model (Raffel et al., 2020) on the GLUE meta-benchmark (Wang et al., 2018) for natural language understanding. We provide background on the GLUE dataset and the example format we use in appendix B.1. We follow the approach of Mahabadi et al. (2021) for splitting each GLUE dataset into train, eval, and test splits. Past work has demonstrated improved performance on RTE by co-training with MNLI (Phang et al., 2018; Devlin et al., 2018; Pruksachatkun et al., 2020; Vu et al., 2020; Choshen et al., 2022a), and we congruously found that sharing an expert between RTE and MNLI produced a stronger tag routing strategy. In the interest of making our baselines as strong as possible, we use this improved tag routing scheme in all experiments. We use the pretrained T5.1.1 Base model as the backbone and adapt the model in a way similar to adding adapters (Houlsby et al., 2019) for a single task, i.e. we keep all pretrained parameters frozen except for layer normalization parameters and insert expert routing blocks after self-attention, feed-forward and cross-attention modules. The T5 1.1 Base model has 12 Transformer layers in both the encoder and decoder, resulting in a total of $12 \times 2 = 24$ blocks in the encoder and $12 \times 3 = 36$ blocks in the decoder, or 60 expert routing blocks in total. In each block, we

Figure 2: Average accuracy and inference speed (in examples processed per second) for models using different routing approaches on our T5-GLUE and ResNet-DomainNet settings. Routing approaches are grouped by color; groups are (in order of the legend) our method (SMEAR), methods that do not use adaptive routing (1× compute, 1× parameters, Adamix, and Hash), methods that make use of metadata (Tag and Latent Skills), methods that learn adaptive routing (Top-k, ST-Gumbel, REINFORCE, DSelect-k, and Soft MoE), and methods that ensemble expert outputs (Ensemble). We omit Hash routing from the plots because its poor performance (66.9% on T5-GLUE and 52.4% on ResNet-DomainNet) hampers readability. Exact numerical results for all methods and standard deviation across five runs are provided in appendix F.

introduce eight experts (one for each dataset in GLUE). The router architecture is simply a linear classifier, i.e. a linear projection layer consisting of a weight matrix of shape d x N, where d is the model dimension and N is the number of experts in the MoE layer, followed by a softmax nonlinearity. To help avoid saturating the softmax nonlinearity, we apply layer normalization both to the input of the router as well as the rows of the linear layer. In the encoder, the router takes as input the preceding hidden states, which are averaged across the sequence and fed into the router. In the decoder, the routers receive the average of the encoder's final hidden states instead of the decoder hidden states to prevent information leakage from later target tokens. We also include expert dropout Liu et al. (2022b) where each expert is dropped with a probability of 0.1 wherever it was found to be beneficial (a detailed ablation can be found in table 1). In GLUE, dataset sizes vary by three orders of magnitude, and we therefore found that load-balancing losses (as used e.g. in (Shazeer et al., 2017; Fedus et al., 2021; Lepikhin et al., 2020) to encourage uniform usage across experts) tended to hurt performance, so we did not include them.

ResNet-DomainNet In this setting, we focus on adapting an ImageNet pre-trained ResNet18 model (He et al., 2016) to datasets within DomainNet (Peng et al., 2019). DomainNet is a collection of object recognition datasets that cover six distinct domains and all share the same label space corresponding to 345 object categories. We treat the domain of each example as its tag. As in the T5-GLUE setting, we freeze the pretrained model and insert eight expert routing blocks after each of the eight residual layer groups in the model. Each block includes six experts corresponding to the number of domains. We use the same architecture for routers as in T5-GLUE and feed average-pooled hidden states into the router to compute the routing probability. Experts in this setting use batch normalization on their input instead of layer normalization in the output, following (Rebuffi et al., 2017). As in T5-GLUE, we omit load-balancing losses due to dramatically different sizes across domains in DomainNet.

We only provide the average performance across datasets/domains in the main paper due to space limitations. Full results are provided in appendix F.

4.2 Results

To assess the overall effectiveness of routing strategies learned with SMEAR, we compare to learned routing using the gradient estimators, heuristic routing strategies, and modular baselines from section 2. A summary

(a) T5-GLUE model

(b) ResNet-DomainNet model

Figure 3: Average routing distributions produced by SMEAR for two routers from the T5-GLUE model and two from the ResNet-DomainNet model. For a given router, we average all routing distributions across all examples from a given dataset.

of our results is shown in fig. 2. First, we find that models using routing strategies learned through gradient estimation often underperform heuristic routing strategies – while the best-performing estimator (REINFORCE) in T5-GLUE outperforms tag routing, all estimators perform worse than tag routing in ResNet-DomainNet. On the other hand, we observed some cases where gradient estimation-based routing outperforms hash or single-expert routing, which suggests that the learned routing strategies were nontrivial. Pertinently, in all experimental settings, SMEAR matches or outperforms every other routing strategy, including both routing learned by gradient estimators and all heuristic routing strategies. In particular, SMEAR achieves 2.7% improvement over tag routing in T5-GLUE and 0.6% improvement over tag routing in ResNet-DomainNet, suggesting effective specialization and sharing of experts. SMEAR additionally outperforms the single-expert parameter-matched baseline (1× parameters) by 1.4% in T5-GLUE and 1.2% in ResNet-DomainNet, further highlighting the importance of modularity.

As an upper bound on performance, we also compare SMEAR to expert ensembling ("Ensemble") which averages the outputs of all experts and incurs significantly higher computational cost. SMEAR matches the performance of ensemble routing in T5-GLUE and modestly underperforms it in ResNet-DomainNet, despite being significantly computationally cheaper. Compared to Adamix, which similarly averages experts

but does not learn a routing strategy, SMEAR achieves 3.2% higher performance in T5-GLUE and 4% higher in ResNet-DomainNet. Since the Soft MoE method averages input tokens, it's inapplicable for the encoder-decoder model in T5-GLUE, where future tokens are not available for averaging in the decoder during inference. Hence, we include Soft MoE for ResNet-DomainNet where SMEAR outperforms it by 1.5%. Additionally, SMEAR exceeds the DSelect-k method by 2.7% in ResNet-DomainNet. However, despite extensive hyperparameter tuning we encountered training instabilites with the DSelect-k method in T5-GLUE and therefore omit those results. Moreover, while the performance improvement of SMEAR over Latent Skills is relatively small (0.6% in T5-GLUE and 0.1% in ResNet-DomainNet), a major advantage of SMEAR over Latent Skills is that it does not assume access to oracle tags (which are not always available in real-world settings) and instead learns an adaptive routing strategy. Finally, we highlight the consistency of improvements achieved by SMEAR across a diverse range of datasets and architectures, confirming its generality and robustness.

We additionally plot the inference speed (in terms of number of examples processed per second) of each method in fig. 2. The single-expert, Adamix, Hash, and Tag routing methods are the fastest since they do not use any routing networks. Despite the slight overhead of averaging the weights in SMEAR, we observe that its inference speed is almost identical to that of discrete adaptive routing (as learned via gradient estimation techniques). This confirms that the performance gains attained by SMEAR do not incur significant additional costs. Ensembling expert outputs is the slowest, with a 1.2× slowdown in T5-GLUE and 1.3× slowdown in ResNet-DomainNet compared to SMEAR.

Scaling Thus far, we have always set the number of experts equal to the number of tasks (in T5-GLUE) or domains (in DomainNet). However, with learned routing there is no reason to force this constraint, so we therefore tested the scalability of SMEAR by evaluating its performance with twice as many experts (16 for T5-GLUE and 12 for ResNet-DomainNet). We found a significant improvement (0.8%) when doubling the number of experts on ResNet-DomainNet, but no significant change on T5-GLUE (81.3 ± 1.1 vs. 81.6 ± 1.1). This suggests there is no benefit to increasing capacity in the T5-GLUE setting. The complete results for doubling the number of experts are presented in appendix F (labeled "SMEAR 2×").

4.3 Qualitative Analysis

In this section, we provide qualitative analysis of the routing learned by SMEAR by visualizing the average router distribution across all examples in a given dataset for every router in each model. Figure 3 shows four select visualizations (two from a SMEAR-based model trained in T5-GLUE and two from ResNet-DomainNet). Across the two T5-GLUE router distributions shown in fig. 3, we observe significantly different behavior – one mainly follows a tag routing-style strategy whereas the other routes most datasets to the same expert. However, we note that the tag-style router utilizes shared experts for RTE, MRPC, and MNLI; notably, these tasks are somewhat similar in that they all involve determining similarity among pairs of sentences. In the single-expert-style router, STS-B (the only regression task) and SST-2 (which has a distinct output vocabulary) are given dedicated experts, and MNLI (a large and relatively challenging dataset) is routed through many different experts. More broadly, we highlight that there is generally a great deal of sparsity in the learned routing distributions, suggesting a significant amount of expert specialization. In ResNet-DomainNet, we can see that examples from the Quickdraw domain are routed to two specific experts in both cases. Additionally, we observe that the router distribution of the Painting and Real domains are highly correlated. Other domains such as Clipart and Sketch seem to evenly use experts. Interestingly, there is less expert specialization in the ResNet-DomainNet model, suggesting that there may be more similarities between the individual domains in DomainNet compared to the tasks in GLUE.

In general, other approaches for learning routing did not exhibit as intuitive or meaningful specialization and sharing. In ResNet-DomainNet, Top-k demonstrates uniform routing in the initial layers but chooses a single expert in the last layer. REINFORCE, ST-Gumbel, and DSelect-k tend to exhibit mostly degenerate single-expert routing. Interestingly, all these gradient estimators learn to assign a distinct expert for the Quickdraw dataset. However, this degree of specialization is insufficient for achieving superior performance scores. In T5-GLUE, these estimators display degenerate routing in some layers, while showing a tendency to share a few experts (approximately 3 out of 8) in other layers across tasks. Methods such as Latent Skills

and Ensemble utilize most experts in the MoE layer (similar to SMEAR). Routing distribution visualizations for all methods and all layers can be found in appendix G.

5 Related Work

Models with Conditional Computation Given the difficulties of training models with discrete routing strategies, there is a large body of literature investigating effective methods for training such models. Deecke et al. (2020); Hazimeh et al. (2021); Dua et al. (2021) start training with most of the experts activated and gradually introduce sparsity. Kudugunta et al. (2021); Ponti et al. (2022); Ma et al. (2019); Gupta et al. (2022) group examples from the same task together and introduce task-specific parameters in the router. Zuo et al. (2021); Wang et al. (2022b) explore random routing with consistency regularization as a form of model ensembling. Other works avoid learned routing by hand-crafting heuristic routing strategies. Gururangan et al. (2021) built sparsely activated language models where different domains use separate experts and then weights the experts for new domains. Tang et al. (2022); Pfeiffer et al. (2022; 2020) assign experts based on task-related human knowledge. Our focus on settings where performant routing schemes can be hand-designed takes inspiration from this line of work.

Because sparsely activated models disentangle computation and parameter count, significant effort has gone into leveraging conditional computation to create massive pre-trained models with a feasible computation cost (Fedus et al., 2022; Shazeer et al., 2017; Fedus et al., 2021; Du et al., 2022; Zoph et al., 2022; Yu et al., 2022). Many works explore different routing methods in this setting, with a major focus on balancing the load across experts (Lewis et al., 2021; Zhou et al., 2022; Kool et al., 2021; Roller et al., 2021). Li et al. (2022a) demonstrate that models structured as sparse mixture-of-experts generalize effectively to novel domains, as compared to other domain generalization algorithms in vision transformers. Another line of work aims to introduce ways to convert trained dense models into similar-sized sparse models with a lower computational footprint (Lee-Thorp & Ainslie, 2022; Zhang et al., 2022; Komatsuzaki et al., 2022). More generally, there are other forms of conditional computation beyond the formulation we describe in this work (Han et al., 2021). Modular networks (Kirsch et al., 2018; Jiang & Bansal, 2019; Hu et al., 2017) use a router to assemble heterogeneous subnetworks into a network layout specific to a given input example. Early exiting (Graves, 2016; Xin et al., 2020; Liu et al., 2020a; Bengio et al., 2015) saves computation by terminating inference in earlier layers or recurrent steps.

Gradient Estimation Techniques Many gradient estimators have been proposed to produce approximate gradients for backpropagating through discrete steps. Clark et al. (2022) uses a learned baseline to reduce the variance of the REINFORCE estimator. The REBAR estimator (Tucker et al., 2017) adds a reparameterizable term to REINFORCE as a baseline that results in a more effective unbiased estimator. This additional term incorporates a relaxed sample similar to Gumbel-Softmax (Jang et al., 2016). RELAX (Grathwohl et al., 2017) is similar to REBAR but uses a learnable neural network for the reparameterizable term. Kool et al. (2019) uses additional samples as a built-in baseline for REINFORCE. Yin & Zhou (2018) and Dong et al. (2020) use the idea of coupling between multiple samples to reduce the variance of the gradient estimator for improved training of models with binary latent variables. Dong et al. (2021) improve upon Yin & Zhou (2018) and Dong et al. (2020) by extending the estimator to categorical variables. These studies have theoretically analyzed gradient estimators, focusing on the bias and variance of these gradients and suggesting enhancements through improved relaxation techniques and variance reduction techniques. The fundamental theoretical advantage of our method lies in its ability to enable exact gradient computation through standard backpropagation. In preliminary experiments, we did not find any major gains from using more sophisticated gradient estimation techniques, but designing gradient estimators with discrete routing in mind could yield more performant routing strategies.

Issues with Conditional Computation A great deal of past work has highlighted issues with models that use conditional computation. Clark et al. (2022) study the scaling laws of sparse language models and discovered a computational cutoff above which no additional benefits are observed. Relatedly, Du et al. (2022) observe worse results when further scaling up the number of experts. Chi et al. (2022) highlight that using the model's activations as input to the router can cause the representations to "collapse". Dai et al. (2022)

demonstrate that learned routing decisions can fluctuate significantly over training. Mittal et al. (2022) create a set of simple and compositional data distributions and show that systems with modular architecture can not find the most performant solution when trained end-to-end. Ye et al. (2022) experiment with various designs for multi-task learning with task-level routing and find that the performance never surpasses simple multi-task baselines. We show a possibility to avoid these issues with a fully differentiable routing strategy that does not increase computational costs.

Weight Averaging Methods   Many prior works utilize parameter averaging for ensembling. Wortsman et al. (2022c); Ilharco et al. (2022) average the weights of a pre-trained and a fine-tuned model to improve performance on target tasks as well as robustness to distribution shift. Choshen et al. (2022b) similarly show that merging multiple models fine-tuned on different datasets can provide a better initialization than using the original pre-trained model for further fine-tuning on new unseen datasets. The phenomenon of linear mode connectivity, as observed by Frankle et al. (2020), Qin et al. (2022) and Entezari et al. (2021), refers to the tendency of models to converge to a single low-loss basin, which makes it possible to average the weights of models without increasing loss. Juneja et al. (2022) found that tasks with different generalization strategies have high barriers when linearly interpolated, whereas tasks with similar generalization are linearly mode connected and can be averaged. They defined several generalization strategies and found that sets of tasks form clusters with those strategies. In our case, the router plays the role of identifying experts with similar generalization properties when conditioned on the input and performs the averaging.

Yang et al. (2019); Zhang et al. (2021) compute convolution kernels by averaging weights of individual kernels. Maziarz et al. (2019) learn a task-specific binary allocation matrix, where each allocation corresponds to a convolution kernel. Since the convolution operation is linear, weight averaging and ensembling are mathematically equivalent in the aforementioned works. However, SMEAR performs averaging on non-linear and parameter efficient experts that, when trained alone, can match the performance of the fully fine-tuned model Houlsby et al. (2019). π-Tuning Wu et al. (2023) employs a set of existing task specific experts, retrieving the top k experts for a downstream task and learns to interpolate among these experts for the downstream task. While π-Tuning enables transfer learning to a new downstream task by learning to interpolate, our focus is on developing a routing algorithm that learns how to share or specialize experts without using any metadata. Wortsman et al. (2022b) average multiple models fine-tuned from large pre-trained models with different hyperparameters, using techniques such as uniform averaging and greedy averaging by picking those models that increase the average performance using a validation set. Gururangan et al. (2021); Li et al. (2022b) use data in novel domains to estimate weights to average each of their domain-specific subnetworks. Izmailov et al. (2018) average model parameters along a training trajectory and show that the resultant model generalizes better than the solution found by SGD at the end of training. Our work instead learns a router that implements an adaptive routing strategy over the course of the training process.

Concurrent work by Zadouri et al. (2023) used SMEAR for training a mixture-of-experts-style model with LoRA (Hu et al., 2021)- and IA^3 (Liu et al., 2022a)-based experts. They show that the resultant model outperforms full model finetuning in generalizing to unseen tasks. Model averaging is also a common step in distributed optimization, where it is widely used in federated learning (McMahan et al., 2017) and has recently been used for distributed fine-tuning (Wortsman et al., 2022a), multi-domain training (Li et al., 2022b), and multitask training (Don-Yehiya et al., 2022). There are also works that utilize different styles of merging instead of weight averaging of parameters, such as reweighting parameters in accordance with their approximate Fisher information (Matena & Raffel, 2021), aligning features by fitting a linear projection (Jin et al., 2022), and permuting columns to account for permutation symmetries (Ainsworth et al., 2022). We are interested in applying these more sophisticated merging methods to SMEAR in future work.

6   Conclusion

In this work, we sought to address shortcomings of models with discrete routing among experts that can lead them to underperform heuristic non-learned routing. We hypothesized that these issues stem from the gradient estimation techniques required to propagate gradients through discrete routing decisions and therefore focused on designing an expert routing architecture that allows exact calculation of gradients. Our approach, called SMEAR, works by computing a weighted average of expert parameters where the weighting

is set according to the output of a learned router. We compared the performance of models using SMEAR to discrete routing models that were trained via various gradient estimation techniques. In experimental settings covering different modalities and model architectures, we found that SMEAR outperformed all models with discrete routing as well as performant heurstic routing strategies. Notably, this performance boost comes with no increase in computational costs. SMEAR also matched or outperformed existing state-of-the-art methods for learning modular models through expert averaging while removing the requirement for oracle task labels. Through qualitative analysis, we further confirmed that the experts learned in a model using SMEAR specialize to different types of inputs and that the router learns a nontrivial strategy that exploits commonalities across different examples. In future work, we are interested in exploring different expert architectures (Liu et al., 2022a; Hu et al., 2021) and improved merging methods (Matena & Raffel, 2021; Ainsworth et al., 2022; Jin et al., 2022). Given access to a larger amount of compute, we would also be excited to try out SMEAR in the large-scale settings where discrete routing has been used (Fedus et al., 2021; Zoph et al., 2022; Du et al., 2022) to see whether it helps fix the poor scaling properties of models with discrete routing (Clark et al., 2022).

References

Samuel K Ainsworth, Jonathan Hayase, and Siddhartha Srinivasa. Git re-basin: Merging models modulo permutation symmetries. *arXiv preprint arXiv:2209.04836*, 2022.

Stephen H Bach, Victor Sanh, Zheng-Xin Yong, Albert Webson, Colin Raffel, Nihal V Nayak, Abheesht Sharma, Taewoon Kim, M Saiful Bari, Thibault Fevry, et al. Promptsource: An integrated development environment and repository for natural language prompts. *arXiv preprint arXiv:2202.01279*, 2022.

Hangbo Bao, Li Dong, and Furu Wei. Beit: Bert pre-training of image transformers. *arXiv preprint arXiv:2106.08254*, 2021.

David Bau, Jun-Yan Zhu, Hendrik Strobelt, Agata Lapedriza, Bolei Zhou, and Antonio Torralba. Understanding the role of individual units in a deep neural network. *Proceedings of the National Academy of Sciences*, 117(48):30071–30078, 2020.

Emmanuel Bengio, Pierre-Luc Bacon, Joelle Pineau, and Doina Precup. Conditional computation in neural networks for faster models. *arXiv preprint arXiv:1511.06297*, 2015.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Luisa Bentivogli, Peter Clark, Ido Dagan, and Danilo Giampiccolo. The fifth pascal recognizing textual entailment challenge. In *TAC*, 2009.

Daniel Cer, Mona Diab, Eneko Agirre, Inigo Lopez-Gazpio, and Lucia Specia. Semeval-2017 task 1: Semantic textual similarity-multilingual and cross-lingual focused evaluation. *arXiv preprint arXiv:1708.00055*, 2017.

Zewen Chi, Li Dong, Shaohan Huang, Damai Dai, Shuming Ma, Barun Patra, Saksham Singhal, Payal Bajaj, Xia Song, and Furu Wei. On the representation collapse of sparse mixture of experts. *arXiv preprint arXiv:2204.09179*, 2022.

Leshem Choshen, Elad Venezian, Shachar Don-Yehia, Noam Slonim, and Yoav Katz. Where to start? analyzing the potential value of intermediate models. *arXiv preprint arXiv:2211.00107*, 2022a.

Leshem Choshen, Elad Venezian, Noam Slonim, and Yoav Katz. Fusing finetuned models for better pretraining. *arXiv preprint arXiv:2204.03044*, 2022b.

Aidan Clark, Diego de Las Casas, Aurelia Guy, Arthur Mensch, Michela Paganini, Jordan Hoffmann, Bogdan Damoc, Blake Hechtman, Trevor Cai, Sebastian Borgeaud, et al. Unified scaling laws for routed language models. In *International Conference on Machine Learning*, pp. 4057–4086. PMLR, 2022.

Róbert Csordás, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Are neural nets modular? inspecting functional modularity through differentiable weight masks. In *International Conference on Learning Representations*, 2021.

Damai Dai, Li Dong, Shuming Ma, Bo Zheng, Zhifang Sui, Baobao Chang, and Furu Wei. Stablemoe: Stable routing strategy for mixture of experts. *arXiv preprint arXiv:2204.08396*, 2022.

Nicola De Cao, Wilker Aziz, and Ivan Titov. Editing factual knowledge in language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, 2021.

Lucas Deecke, Timothy Hospedales, and Hakan Bilen. Latent domain learning with dynamic residual adapters. *arXiv preprint arXiv:2006.00996*, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Bill Dolan and Chris Brockett. Automatically constructing a corpus of sentential paraphrases. In *Third International Workshop on Paraphrasing (IWP2005)*, 2005.

Shachar Don-Yehiya, Elad Venezian, Colin Raffel, Noam Slonim, Yoav Katz, and Leshem Choshen. Cold fusion: Collaborative descent for distributed multitask finetuning. *arXiv preprint arXiv:2212.01378*, 2022.

Zhe Dong, Andriy Mnih, and George Tucker. Disarm: An antithetic gradient estimator for binary latent variables. *Advances in neural information processing systems*, 33:18637–18647, 2020.

Zhe Dong, Andriy Mnih, and George Tucker. Coupled gradient estimators for discrete latent variables. *Advances in Neural Information Processing Systems*, 34:24498–24508, 2021.

Nan Du, Yanping Huang, Andrew M Dai, Simon Tong, Dmitry Lepikhin, Yuanzhong Xu, Maxim Krikun, Yanqi Zhou, Adams Wei Yu, Orhan Firat, et al. Glam: Efficient scaling of language models with mixture-of-experts. In *International Conference on Machine Learning*, pp. 5547–5569. PMLR, 2022.

Dheeru Dua, Shruti Bhosale, Vedanuj Goswami, James Cross, Mike Lewis, and Angela Fan. Tricks for training sparse translation models. *arXiv preprint arXiv:2110.08246*, 2021.

Rahim Entezari, Hanie Sedghi, Olga Saukh, and Behnam Neyshabur. The role of permutation invariance in linear mode connectivity of neural networks. *arXiv preprint arXiv:2110.06296*, 2021.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity, 2021.

William Fedus, Jeff Dean, and Barret Zoph. A review of sparse expert models in deep learning. *arXiv preprint arXiv:2209.01667*, 2022.

Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In *International Conference on Machine Learning*, pp. 3259–3269. PMLR, 2020.

Will Grathwohl, Dami Choi, Yuhuai Wu, Geoffrey Roeder, and David Duvenaud. Backpropagation through the void: Optimizing control variates for black-box gradient estimation. *arXiv preprint arXiv:1711.00123*, 2017.

Alex Graves. Adaptive computation time for recurrent neural networks. *arXiv preprint arXiv:1603.08983*, 2016.

Shashank Gupta, Subhabrata Mukherjee, Krishan Subudhi, Eduardo Gonzalez, Damien Jose, Ahmed Hassan Awadallah, and Jianfeng Gao. Sparsely activated mixture-of-experts are robust multi-task learners. *ArXiv*, abs/2204.07689, 2022.

Suchin Gururangan, Mike Lewis, Ari Holtzman, Noah A Smith, and Luke Zettlemoyer. Demix layers: Disentangling domains for modular language modeling. *arXiv preprint arXiv:2108.05036*, 2021.

Yizeng Han, Gao Huang, Shiji Song, Le Yang, Honghui Wang, and Yulin Wang. Dynamic neural networks: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Hussein Hazimeh, Zhe Zhao, Aakanksha Chowdhery, Maheswaran Sathiamoorthy, Yihua Chen, Rahul Mazumder, Lichan Hong, and Ed Chi. Dselect-k: Differentiable selection in the mixture of experts with applications to multi-task learning. *Advances in Neural Information Processing Systems*, 34:29335–29347, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for nlp. In *International Conference on Machine Learning*, pp. 2790–2799. PMLR, 2019.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Ronghang Hu, Jacob Andreas, Marcus Rohrbach, Trevor Darrell, and Kate Saenko. Learning to reason: End-to-end module networks for visual question answering. In *Proceedings of the IEEE international conference on computer vision*, pp. 804–813, 2017.

Gabriel Ilharco, Mitchell Wortsman, Samir Yitzhak Gadre, Shuran Song, Hannaneh Hajishirzi, Simon Kornblith, Ali Farhadi, and Ludwig Schmidt. Patching open-vocabulary models by interpolating weights. *arXiv preprint arXiv:2208.05592*, 2022.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Yichen Jiang and Mohit Bansal. Self-assembling modular networks for interpretable multi-hop reasoning. *arXiv preprint arXiv:1909.05803*, 2019.

Xisen Jin, Xiang Ren, Daniel Preotiuc-Pietro, and Pengxiang Cheng. Dataless knowledge fusion by merging weights of language models. *arXiv preprint arXiv:2212.09849*, 2022.

Jeevesh Juneja, Rachit Bansal, Kyunghyun Cho, João Sedoc, and Naomi Saphra. Linear connectivity reveals generalization strategies. *arXiv preprint arXiv:2205.12411*, 2022.

Louis Kirsch, Julius Kunze, and David Barber. Modular networks: Learning to decompose neural computation. *Advances in neural information processing systems*, 31, 2018.

Aran Komatsuzaki, Joan Puigcerver, James Lee-Thorp, Carlos Riquelme Ruiz, Basil Mustafa, Joshua Ainslie, Yi Tay, Mostafa Dehghani, and Neil Houlsby. Sparse upcycling: Training mixture-of-experts from dense checkpoints. *arXiv preprint arXiv:2212.05055*, 2022.

Wouter Kool, Herke van Hoof, and Max Welling. Buy 4 reinforce samples, get a baseline for free! 2019.

Wouter Kool, Chris J Maddison, and Andriy Mnih. Unbiased gradient estimation with balanced assignments for mixtures of experts. *arXiv preprint arXiv:2109.11817*, 2021.

Sneha Kudugunta, Yanping Huang, Ankur Bapna, Maxim Krikun, Dmitry Lepikhin, Minh-Thang Luong, and Orhan Firat. Beyond distillation: Task-level mixture-of-experts for efficient inference. *arXiv preprint arXiv:2110.03742*, 2021.

James Lee-Thorp and Joshua Ainslie. Sparse mixers: Combining moe and mixing to build a more efficient bert. *arXiv preprint arXiv:2205.12399*, 2022.

Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. Gshard: Scaling giant models with conditional computation and automatic sharding. *arXiv preprint arXiv:2006.16668*, 2020.

Hector Levesque, Ernest Davis, and Leora Morgenstern. The winograd schema challenge. In *Thirteenth international conference on the principles of knowledge representation and reasoning*, 2012.

Mike Lewis, Shruti Bhosale, Tim Dettmers, Naman Goyal, and Luke Zettlemoyer. Base layers: Simplifying training of large, sparse models. In *International Conference on Machine Learning*, pp. 6265–6274. PMLR, 2021.

Bo Li, Jingkang Yang, Jiawei Ren, Yezhen Wang, and Ziwei Liu. Sparse fusion mixture-of-experts are domain generalizable learners. *arXiv preprint arXiv:2206.04046*, 2022a.

Margaret Li, Suchin Gururangan, Tim Dettmers, Mike Lewis, Tim Althoff, Noah A. Smith, and Luke Zettlemoyer. Branch-train-merge: Embarrassingly parallel training of expert language models. *ArXiv*, abs/2208.03306, 2022b.

Haokun Liu, Derek Tam, Mohammed Muqeeth, Jay Mohta, Tenghao Huang, Mohit Bansal, and Colin Raffel. Few-shot parameter-efficient fine-tuning is better and cheaper than in-context learning. *arXiv preprint arXiv:2205.05638*, 2022a.

Rui Liu, Young Jin Kim, Alexandre Muzio, and Hany Hassan. Gating dropout: Communication-efficient regularization for sparsely activated transformers. In *International Conference on Machine Learning*, pp. 13782–13792. PMLR, 2022b.

Weijie Liu, Peng Zhou, Zhe Zhao, Zhiruo Wang, Haotang Deng, and Qi Ju. Fastbert: a self-distilling bert with adaptive inference time. *arXiv preprint arXiv:2004.02178*, 2020a.

Yinhan Liu, Jiatao Gu, Naman Goyal, Xian Li, Sergey Edunov, Marjan Ghazvininejad, Mike Lewis, and Luke Zettlemoyer. Multilingual denoising pre-training for neural machine translation. *Transactions of the Association for Computational Linguistics*, 8:726–742, 2020b.

Jiaqi Ma, Zhe Zhao, Jilin Chen, Ang Li, Lichan Hong, and Ed H Chi. Snr: Sub-network routing for flexible parameter sharing in multi-task learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 216–223, 2019.

Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. *arXiv preprint arXiv:1611.00712*, 2016.

Rabeeh Karimi Mahabadi, Sebastian Ruder, Mostafa Dehghani, and James Henderson. Parameter-efficient multi-task fine-tuning for transformers via shared hypernetworks. *arXiv preprint arXiv:2106.04489*, 2021.

Michael Matena and Colin Raffel. Merging models with fisher-weighted averaging. *arXiv preprint arXiv:2111.09832*, 2021.

Krzysztof Maziarz, Efi Kokiopoulou, Andrea Gesmundo, Luciano Sbaiz, Gabor Bartok, and Jesse Berent. Flexible multi-task networks by learning parameter allocation. *arXiv preprint arXiv:1910.04915*, 2019.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Sstatistics*, 2017.

Sarthak Mittal, Yoshua Bengio, and Guillaume Lajoie. Is a modular architecture enough? *arXiv preprint arXiv:2206.02713*, 2022.

Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 1406–1415, 2019.

Jonas Pfeiffer, Ivan Vulic, Iryna Gurevych, and Sebastian Ruder. Mad-x: An adapter-based framework for multi-task cross-lingual transfer. In *EMNLP*, 2020.

Jonas Pfeiffer, Naman Goyal, Xi Victoria Lin, Xian Li, James Cross, Sebastian Riedel, and Mikel Artetxe. Lifting the curse of multilinguality by pre-training modular transformers. In *NAACL*, 2022.

Jonas Pfeiffer, Sebastian Ruder, Ivan Vulić, and Edoardo Maria Ponti. Modular deep learning. *arXiv preprint arXiv:2302.11529*, 2023.

Jason Phang, Thibault Févry, and Samuel R Bowman. Sentence encoders on stilts: Supplementary training on intermediate labeled-data tasks. *arXiv preprint arXiv:1811.01088*, 2018.

Telmo Pires, Eva Schlinger, and Dan Garrette. How multilingual is multilingual bert? *arXiv preprint arXiv:1906.01502*, 2019.

Edoardo M Ponti, Alessandro Sordoni, and Siva Reddy. Combining modular skills in multitask learning. *arXiv preprint arXiv:2202.13914*, 2022.

Yada Pruksachatkun, Jason Phang, Haokun Liu, Phu Mon Htut, Xiaoyi Zhang, Richard Yuanzhe Pang, Clara Vania, Katharina Kann, and Samuel R Bowman. Intermediate-task transfer learning with pretrained models for natural language understanding: When and why does it work? *arXiv preprint arXiv:2005.00628*, 2020.

Joan Puigcerver, Carlos Riquelme, Basil Mustafa, and Neil Houlsby. From sparse to soft mixtures of experts. *arXiv preprint arXiv:2308.00951*, 2023.

Yujia Qin, Cheng Qian, Jing Yi, Weize Chen, Yankai Lin, Xu Han, Zhiyuan Liu, Maosong Sun, and Jie Zhou. Exploring mode connectivity for pre-trained language models. *arXiv preprint arXiv:2210.14102*, 2022.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. *arXiv preprint arXiv:1606.05250*, 2016.

Sylvestre-Alvise Rebuffi, Hakan Bilen, and Andrea Vedaldi. Learning multiple visual domains with residual adapters. *Advances in neural information processing systems*, 30, 2017.

Stephen Roller, Sainbayar Sukhbaatar, Jason Weston, et al. Hash layers for large sparse models. *Advances in Neural Information Processing Systems*, 34:17555–17566, 2021.

Victor Sanh, Albert Webson, Colin Raffel, Stephen H Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, et al. Multitask prompted training enables zero-shot task generalization. *arXiv preprint arXiv:2110.08207*, 2021.

John Schulman, Nicolas Heess, Theophane Weber, and Pieter Abbeel. Gradient estimation using stochastic computation graphs. *Advances in Neural Information Processing Systems*, 28, 2015.

Iyer Shankar, Dandekar Nikhil, and Csernai Kornel. First quora dataset release: question pairs (2017). https://www.quora.com/q/quoradata/First-Quora-Dataset-Release-Question-Pairs, 2017.

Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *arXiv preprint arXiv:1701.06538*, 2017.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 conference on empirical methods in natural language processing*, pp. 1631–1642, 2013.

Duyu Tang, Fan Zhang, Yong Dai, Cong Zhou, Shuangzhi Wu, and Shuming Shi. One model, multiple tasks: Pathways for natural language understanding. *ArXiv*, abs/2203.03312, 2022.

George Tucker, Andriy Mnih, Chris J Maddison, John Lawson, and Jascha Sohl-Dickstein. Rebar: Low-variance, unbiased gradient estimates for discrete latent variable models. *Advances in Neural Information Processing Systems*, 30, 2017.

Tu Vu, Tong Wang, Tsendsuren Munkhdalai, Alessandro Sordoni, Adam Trischler, Andrew Mattarella-Micke, Subhransu Maji, and Mohit Iyyer. Exploring and predicting transferability across nlp tasks. *arXiv preprint arXiv:2005.00770*, 2020.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

Xiaozhi Wang, Kaiyue Wen, Zhengyan Zhang, Lei Hou, Zhiyuan Liu, and Juanzi Li. Finding skill neurons in pre-trained transformer-based language models. *arXiv preprint arXiv:2211.07349*, 2022a.

Yaqing Wang, Subhabrata Mukherjee, Xiaodong Liu, Jing Gao, Ahmed Hassan Awadallah, and Jianfeng Gao. Adamix: Mixture-of-adapter for parameter-efficient tuning of large language models. *arXiv preprint arXiv:2205.12410*, 2022b.

Alex Warstadt, Amanpreet Singh, and Samuel R Bowman. Neural network acceptability judgments. *Transactions of the Association for Computational Linguistics*, 7:625–641, 2019.

Jason Wei, Maarten Bosma, Vincent Y Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M Dai, and Quoc V Le. Finetuned language models are zero-shot learners. *arXiv preprint arXiv:2109.01652*, 2021.

Adina Williams, Nikita Nangia, and Samuel R Bowman. A broad-coverage challenge corpus for sentence understanding through inference. *arXiv preprint arXiv:1704.05426*, 2017.

Mitchell Wortsman, Suchin Gururangan, Shen Li, Ali Farhadi, Ludwig Schmidt, Michael Rabbat, and Ari S Morcos. lo-fi: distributed fine-tuning without communication. *arXiv preprint arXiv:2210.11948*, 2022a.

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning*, pp. 23965–23998. PMLR, 2022b.

Mitchell Wortsman, Gabriel Ilharco, Jong Wook Kim, Mike Li, Simon Kornblith, Rebecca Roelofs, Raphael Gontijo Lopes, Hannaneh Hajishirzi, Ali Farhadi, Hongseok Namkoong, et al. Robust fine-tuning of zero-shot models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7959–7971, 2022c.

Chengyue Wu, Teng Wang, Yixiao Ge, Zeyu Lu, Ruisong Zhou, Ying Shan, and Ping Luo. *pi*-tuning: Transferring multimodal foundation models with optimal multi-task interpolation. In *International Conference on Machine Learning*, pp. 37713–37727. PMLR, 2023.

Ji Xin, Raphael Tang, Jaejun Lee, Yaoliang Yu, and Jimmy Lin. Deebert: Dynamic early exiting for accelerating bert inference. *arXiv preprint arXiv:2004.12993*, 2020.

Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. mt5: A massively multilingual pre-trained text-to-text transformer. *arXiv preprint arXiv:2010.11934*, 2020.

Brandon Yang, Gabriel Bender, Quoc V Le, and Jiquan Ngiam. Condconv: Conditionally parameterized convolutions for efficient inference. *Advances in Neural Information Processing Systems*, 32, 2019.

Qinyuan Ye, Juan Zha, and Xiang Ren. Eliciting transferability in multi-task learning with task-level mixture-of-experts. *arXiv preprint arXiv:2205.12701*, 2022.

Mingzhang Yin and Mingyuan Zhou. Arm: Augment-reinforce-merge gradient for stochastic binary networks. *arXiv preprint arXiv:1807.11143*, 2018.

Ping Yu, Mikel Artetxe, Myle Ott, Sam Shleifer, Hongyu Gong, Ves Stoyanov, and Xian Li. Efficient language modeling with sparse all-mlp. *arXiv preprint arXiv:2203.06850*, 2022.

Ted Zadouri, Ahmet Üstün, Arash Ahmadian, Beyza Ermiş, Acyr Locatelli, and Sara Hooker. Pushing mixture of experts to the limit: Extremely parameter efficient moe for instruction tuning. *arXiv preprint arXiv:2309.05444*, 2023.

Amir R Zamir, Alexander Sax, William Shen, Leonidas J Guibas, Jitendra Malik, and Silvio Savarese. Taskonomy: Disentangling task transfer learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3712–3722, 2018.

Matthew D. Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *13th European Conference on Computer Vision*, 2014.

Mingda Zhang, Chun-Te Chu, Andrey Zhmoginov, Andrew Howard, Brendan Jou, Yukun Zhu, Li Zhang, Rebecca Hwa, and Adriana Kovashka. Basisnet: Two-stage model synthesis for efficient inference. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3081–3090, 2021.

Zhengyan Zhang, Yankai Lin, Zhiyuan Liu, Peng Li, Maosong Sun, and Jie Zhou. Moefication: Transformer feed-forward layers are mixtures of experts. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 877–890, 2022.

Yanqi Zhou, Tao Lei, Hanxiao Liu, Nan Du, Yanping Huang, Vincent Zhao, Andrew Dai, Zhifeng Chen, Quoc Le, and James Laudon. Mixture-of-experts with expert choice routing. *arXiv preprint arXiv:2202.09368*, 2022.

Barret Zoph, Irwan Bello, Sameer Kumar, Nan Du, Yanping Huang, Jeff Dean, Noam Shazeer, and William Fedus. Designing effective sparse expert models. *arXiv preprint arXiv:2202.08906*, 2022.

Simiao Zuo, Xiaodong Liu, Jian Jiao, Young Jin Kim, Hany Hassan, Ruofei Zhang, Tuo Zhao, and Jianfeng Gao. Taming sparsely activated transformer with stochastic experts. *arXiv preprint arXiv:2110.04260*, 2021.

A   Compute resources used

Here we provide details on the compute resources used in our experiments. All models were trained on 48GB A6000s, except for the Ensemble method, which was trained on 80GB A100s. The training time for each T5-GLUE experiment was approximately 108 hours while each ResNet-DomainNet experiment required approximately 11 hours of training.

B   Experiment Details

In this section, we provide details on the experimental setup and hyperparameter choices for the T5-GLUE and ResNet-DomainNet experiments described in the main text. We implemented Adamix Wang et al. (2022b) and ran with the hyperparameters listed in the below subsections. In Latent Skills Ponti et al. (2022), we use Adapters consistent with all other experiments and chose learning rate ratio of 10 for skill matrix, which we found to be best after sweeping for $\{1, 10, 100\}$ in both the settings. For exact implementation details of above methods, we refer the reader to each of the respective works.

It is also important to mention that SMEAR's memory footprint is comparable to that of other methods. Since each expert's size is moderate, we compute expert outputs by preparing an expert for each example and applying them to the examples in parallel utilizing `torch.bmm` operation. Thus, none of the methods need an extra weight-sized tensor. Training on T5-GLUE requires around 30GB of memory for SMEAR and other methods, with no significant differences observed in ResNet-DomainNet.

B.1   T5-GLUE

GLUE consists of nine datasets (SST-2 (Socher et al., 2013), CoLA (Warstadt et al., 2019)), MNLI (Williams et al., 2017), RTE (Bentivogli et al., 2009), QQP (Shankar et al., 2017), MRPC (Dolan & Brockett, 2005), STS-B (Cer et al., 2017), QNLI (Rajpurkar et al., 2016), and WNLI (Levesque et al., 2012)) that cover a wide range of natural language processing tasks. Following convention, we exclude WNLI and use the remaining eight datasets. We use the prompted form of these datasets available in PromptSource (Bach et al., 2022), which maps each example into a natural language request-and-response form. During training, we randomly select a prompt templates for each example; during evaluation, we evaluate each example using all of its dataset's templates. In the T5-GLUE experiments in this paper, we concatenated all 8 datasets of GLUE and perform multitask training. T5 models were trained for $600k$ steps using a learning rate of $3e^{-4}$, with $2k$ warmup steps, and batch size of 128. The AdamW optimizer was used with its default settings. We ran the ST-Gumbel estimator with a τ value of 10 and an anneal rate of $1e^{-6}$ by sweeping τ in the range of $\{1, 10\}$ and the anneal rate in the range of $\{1e^{-4}, 1e^{-5}, 1e^{-6}\}$. For the REINFORCE estimator, we used the same values as in (Clark et al., 2022), $\alpha = 1e^{-2}$, $\beta = 5e^{-4}$, and $\gamma = 1e^{-2}$. The adapters here use swish non-linearity in between.

B.2   ResNet-DomainNet

In the ResNet-DomainNet experiments, all the domains from DomainNet were concatenated to perform multitask training similar to T5-GLUE. ResNet models were trained for $100k$ steps with batch size of 128 and a learning rate of $1e^{-3}$, with no warm up, using Adam optimizer. We used τ value of 10 and anneal rate of $1e^{-4}$ for the ST-Gumbel estimator by sweeping τ in the range of $\{1, 10\}$ and the anneal rate in the range of $\{1e^{-4}, 1e^{-5}, 1e^{-6}\}$. The values of α, β, and γ for the REINFORCE estimators are same as in T5-GLUE experiments. The hyperparameter that weighs entropy regularization in Dselect-k is chosen as 0.1 which worked best among $\{0.01, 0.1, 1\}$. The adapters also used a swish non-linearity in between.

C   Expert dropout

Table 1 illustrates the impact of expert dropout on methods that do not make use of metadata but learn adaptive routing, namely methods that are trained through gradient estimation and SMEAR. We conduct this ablation on a single seed to limit the amount of computation. The results show that SMEAR benefits

from an improvement of 2.9% on T5-GLUE, and Top-k achieves a 1.2% and 0.2% improvement on T5-GLUE and ResNet-DomainNet respectively. As a result, we include expert dropout for these two methods when discussed in the main text. However, expert dropout has a negative impact on the performance of ST-Gumbel and REINFORCE methods, and thus, we exclude it for these two methods in the main text.

Routing	T5-GLUE	ResNet-DomainNet
Top-k	77.2	59.8
w/ Expert dropout 0.1	78.4 (+1.2)	60.0 (+0.2)
ST-Gumbel	78.3	58.3
w/ Expert dropout 0.1	77.2 (-1.1)	57.9 (-0.4)
REINFORCE	79.8	59.8
w/ Expert dropout 0.1	78.2 (-1.6)	59.8 (+0.0)
SMEAR	80.2	62.0
w/ Expert dropout 0.1	83.1 (+2.9)	62.0 (+0.0)

Table 1: Performance comparision of different adaptive routing methods w and w/o dropout on a single seed. The results indicate that SMEAR and Top-k method benefit from the expert dropout, while ST-Gumbel and REINFORCE are negatively affected.

D   License

T5 is licensed under Apache 2.0. The ResNet model we used is licensed under BSD 3-Clause License. QNLI uses CC BY-SA 4.0 license. MultiNLI uses data sources of multiple different licenses(Williams et al., 2017). CoLA, SST-2, RTE, MRPC, STS-B, QQP, and DomainNet allow non-commercial research use cases. Our code for T5-GLUE is based on HyperformerMahabadi et al. (2021), which is shared under Apache 2.0. The code for ResNet-DomainNet is developed by us.

E   Ethics Statement

We are not aware of any negative ethical implications of our work. Our work does not involve human subjects and is primarily focused on diagnosing issues with an efficient class of neural networks. While conditional computation has been used to design extremely large neural networks (Shazeer et al., 2017; Fedus et al., 2021; Du et al., 2022) that have high computational costs (and, correspondingly, energy usage), our work primarily focuses on smaller-scale models.

F   Full results on T5-GLUE and ResNet-DomainNet

We show the full results of T5-GLUE in table 2 and ResNet-DomainNet in table 3.

G   Routing distribution in all routing blocks

Here, we present the routing distribution across all routing blocks in both T5-GLUE and ResNet-DomainNet as learned by SMEAR. This is depicted in fig. 4, fig. 5, fig. 6, and fig. 7.

For other learned routing methods, refer to the corresponding figures for detailed routing distributions:

- **Latent Skills**: fig. 8, fig. 9, fig. 10, and fig. 11.

- **Top-k**: fig. 12, fig. 13, fig. 14, and fig. 15.

- **ST-Gumbel**: fig. 16, fig. 17, fig. 18, and fig. 19.

- **REINFORCE**: fig. 20, fig. 21, fig. 22, and fig. 23.

Routing	RTE acc	SST-2 acc	MRPC f1	MRPC acc	STS-B pearson	STS-B spearman	QQP f1	QQP acc	MNLI acc	QNLI acc	CoLA mcc	Average
SMEAR	$69.9_{2.6}$	$90.9_{0.8}$	$90.5_{1.5}$	$86.9_{2.2}$	$87.0_{0.7}$	$86.6_{0.8}$	$86.9_{0.3}$	$90.1_{0.2}$	$84.9_{0.5}$	$90.2_{0.6}$	$33.8_{6.4}$	$81.6_{1.0}$
1× parameters	$72.3_{2.1}$	$92.1_{0.5}$	$89.9_{0.5}$	$86.0_{0.8}$	$85.5_{0.8}$	$85.3_{0.9}$	$87.0_{0.3}$	$90.2_{0.2}$	$84.1_{0.5}$	$89.9_{0.7}$	$20.1_{8.1}$	$80.2_{0.8}$
1× compute	$67.3_{3.3}$	$91.9_{0.2}$	$89.2_{2.7}$	$85.5_{3.4}$	$87.4_{0.8}$	$87.3_{0.7}$	$85.6_{0.3}$	$89.2_{0.2}$	$84.5_{0.7}$	$89.9_{0.5}$	$5.1_{3.7}$	$78.4_{1.1}$
Adamix	$70.2_{3.2}$	$92.4_{0.6}$	$87.4_{1.4}$	$83.3_{1.2}$	$86.7_{0.6}$	$86.6_{0.7}$	$85.7_{0.2}$	$89.4_{0.1}$	$85.4_{0.3}$	$90.5_{0.4}$	$5.1_{1.1}$	$78.4_{0.4}$
Hash	$58.8_{2.7}$	$85.6_{1.3}$	$77.7_{2.6}$	$68.5_{3.2}$	$65.4_{2.4}$	$65.2_{1.8}$	$76.8_{0.2}$	$82.8_{0.3}$	$72.0_{0.9}$	$80.0_{0.5}$	$2.9_{2.5}$	$66.9_{0.9}$
Tag	$71.7_{2.9}$	$90.3_{0.5}$	$85.4_{0.7}$	$79.5_{0.8}$	$82.2_{1.1}$	$81.5_{1.2}$	$86.2_{0.4}$	$89.5_{0.3}$	$84.4_{0.8}$	$87.9_{0.9}$	$25.1_{8.3}$	$78.5_{1.2}$
Latent Skills	$70.4_{4.6}$	$90.8_{0.8}$	$90.0_{1.0}$	$85.8_{2.1}$	$86.6_{1.5}$	$86.3_{1.4}$	$86.4_{0.4}$	$89.8_{0.3}$	$84.9_{0.9}$	$89.3_{1.4}$	$30.8_{5.5}$	$81.0_{1.6}$
Top-k	$68.2_{2.3}$	$92.5_{0.4}$	$88.6_{0.7}$	$84.7_{1.7}$	$87.7_{1.6}$	$87.4_{1.7}$	$85.3_{0.4}$	$89.0_{0.5}$	$84.9_{0.9}$	$90.1_{0.9}$	$2.0_{2.0}$	$78.2_{0.9}$
ST-Gumbel	$67.6_{2.3}$	$92.1_{0.7}$	$88.8_{1.0}$	$84.8_{1.7}$	$86.9_{1.0}$	$86.8_{0.8}$	$85.7_{0.1}$	$89.2_{0.2}$	$84.5_{0.3}$	$89.1_{0.5}$	$1.3_{1.7}$	$77.9_{0.4}$
REINFORCE	$70.9_{3.3}$	$92.6_{0.5}$	$89.8_{1.6}$	$86.0_{2.1}$	$87.4_{0.6}$	$87.2_{0.5}$	$86.1_{0.3}$	$89.5_{0.2}$	$85.8_{0.4}$	$90.8_{0.7}$	$14.1_{6.9}$	$80.0_{0.8}$
Ensemble	$72.9_{1.6}$	$91.5_{0.4}$	$90.9_{1.4}$	$87.7_{1.4}$	$85.7_{1.5}$	$85.1_{1.6}$	$86.8_{0.3}$	$90.1_{0.2}$	$84.7_{0.5}$	$89.8_{0.6}$	$33.7_{6.1}$	$81.7_{1.0}$
SMEAR 2×	$70.9_{3.1}$	$90.9_{0.7}$	$89.5_{1.1}$	$85.8_{1.0}$	$86.9_{0.9}$	$86.5_{1.0}$	$86.8_{0.4}$	$90.1_{0.3}$	$84.4_{0.5}$	$89.6_{0.8}$	$33.1_{6.5}$	$81.3_{1.1}$

Table 2: Full T5-GLUE results.

Routing	Clipart	Infograph	Painting	Quickdraw	Real	Sketch	Final Accuracy
SMEAR	$64.2_{0.1}$	$31.2_{0.3}$	$57.8_{0.3}$	$62.3_{0.1}$	$74.3_{0.1}$	$56.0_{0.2}$	$62.0_{0.1}$
1× parameters	$63.3_{0.3}$	$29.8_{0.3}$	$56.4_{0.3}$	$61.5_{0.1}$	$72.9_{0.1}$	$54.9_{0.4}$	$60.8_{0.1}$
1× compute	$60.2_{0.3}$	$27.9_{0.3}$	$54.8_{0.1}$	$59.0_{0.2}$	$72.3_{0.1}$	$52.6_{0.2}$	$59.0_{0.1}$
Adamix	$58.9_{0.2}$	$27.0_{0.2}$	$54.1_{0.2}$	$57.2_{0.3}$	$72.1_{0.1}$	$51.2_{0.2}$	$58.0_{0.2}$
Hash	$53.5_{0.3}$	$23.4_{0.3}$	$49.8_{0.4}$	$48.6_{0.3}$	$68.5_{0.1}$	$45.7_{0.2}$	$52.4_{0.1}$
Tag	$62.8_{0.4}$	$30.2_{0.3}$	$58.0_{0.2}$	$61.7_{0.2}$	$74.1_{0.1}$	$55.1_{0.3}$	$61.4_{0.1}$
Latent Skills	$64.5_{0.4}$	$31.2_{0.4}$	$58.9_{0.1}$	$61.6_{0.3}$	$74.2_{0.1}$	$56.3_{0.2}$	$61.9_{0.2}$
Top-k	$61.6_{0.2}$	$29.6_{0.2}$	$55.8_{0.4}$	$60.2_{0.3}$	$73.0_{0.2}$	$53.5_{0.1}$	$60.0_{0.1}$
ST-Gumbel	$59.9_{0.3}$	$27.6_{0.4}$	$54.5_{0.3}$	$58.1_{0.5}$	$72.1_{0.2}$	$51.9_{0.4}$	$58.5_{0.2}$
REINFORCE	$61.3_{0.3}$	$29.1_{0.2}$	$55.9_{0.2}$	$60.4_{0.3}$	$72.8_{0.1}$	$53.6_{0.2}$	$60.0_{0.1}$
DSelect-k	$60.6_{0.2}$	$28.4_{0.3}$	$55.1_{0.3}$	$59.5_{0.3}$	$72.5_{0.2}$	$52.5_{0.4}$	$59.3_{0.2}$
Soft MoE	$62.7_{0.2}$	$29.3_{0.3}$	$56.5_{0.2}$	$60.3_{0.2}$	$73.3_{0.1}$	$54.9_{0.1}$	$60.5_{0.1}$
Ensemble	$65.7_{0.1}$	$32.3_{0.0}$	$58.5_{0.3}$	$63.7_{0.2}$	$74.6_{0.1}$	$57.6_{0.2}$	$62.9_{0.1}$
SMEAR 2×	$65.3_{0.1}$	$31.8_{0.1}$	$58.4_{0.5}$	$63.3_{0.3}$	$74.9_{0.2}$	$57.3_{0.1}$	$62.8_{0.1}$

Table 3: Full ResNet-DomainNet results.

Figure 4: Routing distribution learnt by SMEAR in the routing blocks of ResNet-DomainNet

- **Dselect-k**: fig. 24

- **Ensemble**: fig. 25, fig. 26, fig. 27, and fig. 28.

Figure 5: Routing distribution learnt by SMEAR in the encoder routing blocks (1-24) of T5-GLUE

Figure 6: Routing distribution learnt by SMEAR in the decoder routing blocks (25-48) of T5-GLUE

Figure 7: Routing distribution learnt by SMEAR in the decoder routing blocks (49-60) of T5-GLUE

Figure 8: Routing distribution learnt by Latent Skills routing in the routing blocks of ResNet-DomainNet

Figure 9: Routing distribution learnt by Latent Skills in the encoder routing blocks (1-24) of T5-GLUE

Figure 10: Routing distribution learnt by Latent Skills in the decoder routing blocks (25-48) of T5-GLUE

Figure 11: Routing distribution learnt by Latent Skills in the decoder routing blocks (49-60) of T5-GLUE

Figure 12: Routing distribution learnt by Top-k routing in the routing blocks of ResNet-DomainNet

Figure 13: Routing distribution learnt by Top-k in the encoder routing blocks (1-24) of T5-GLUE

Figure 14: Routing distribution learnt by Top-k in the decoder routing blocks (25-48) of T5-GLUE

Figure 15: Routing distribution learnt by Top-k in the decoder routing blocks (49-60) of T5-GLUE

Figure 16: Routing distribution learnt by ST-Gumbel routing in the routing blocks of ResNet-DomainNet

Figure 17: Routing distribution learnt by ST-Gumbel in the encoder routing blocks (1-24) of T5-GLUE

Figure 18: Routing distribution learnt by ST-Gumbel in the decoder routing blocks (25-48) of T5-GLUE

Figure 19: Routing distribution learnt by ST-Gumbel in the decoder routing blocks (49-60) of T5-GLUE

Figure 20: Routing distribution learnt by REINFORCE routing in the routing blocks of ResNet-DomainNet

Figure 21: Routing distribution learnt by REINFORCE in the encoder routing blocks (1-24) of T5-GLUE

Figure 22: Routing distribution learnt by REINFORCE in the decoder routing blocks (25-48) of T5-GLUE

Figure 23: Routing distribution learnt by REINFORCE in the decoder routing blocks (49-60) of T5-GLUE

Figure 24: Routing distribution learnt by Dselect-k routing in the routing blocks of ResNet-DomainNet

Figure 25: Routing distribution learnt by Ensemble routing in the routing blocks of ResNet-DomainNet

Figure 26: Routing distribution learnt by Ensemble in the encoder routing blocks (1-24) of T5-GLUE

Figure 27: Routing distribution learnt by Ensemble in the decoder routing blocks (25-48) of T5-GLUE

Figure 28: Routing distribution learnt by Ensemble in the decoder routing blocks (49-60) of T5-GLUE