ZERO-SHOT FAIRNESS WITH INVISIBLE DEMOGRAPHICS

ABSTRACT

In a statistical notion of algorithmic fairness, we partition individuals into groups based on some key demographic factors such as race and gender, and require that some statistics of a classifier be approximately equalized across those groups. Current approaches require complete annotations for demographic factors, or focus on an abstract worst-off group rather than demographic groups. In this paper, we consider the setting where the demographic factors are only partially available. For example, we have training examples for white-skinned and dark-skinned males, and white-skinned females, but we have *zero examples* for dark-skinned females. We could also have zero examples for females regardless of their skin colors. Without additional knowledge, it is impossible to directly control the discrepancy of the classifier's statistics for those invisible groups. We develop a disentanglement algorithm that splits a representation of data into a component that captures the demographic factors and another component that is invariant to them based on a context dataset. The context dataset is much like the deployment dataset, it is unlabeled but it contains individuals from all demographics including the invisible. We cluster the context set, equalize the cluster size to form a "perfect batch", and use it as a supervision signal for the disentanglement. We propose a new discriminator loss based on a learnable attention mechanism to distinguish a perfect batch from a non-perfect one. We evaluate our approach on standard classification benchmarks and show that it is indeed possible to protect invisible demographics.

1 INTRODUCTION

Machine learning is already involved in decision-making processes that affect peoples' lives such as in screening job candidates (Raghavan et al., 2020) and in pricing credit (Hurley & Adebayo, 2017). Efficiency can be improved, costs can be reduced, and personalization of services and products can be greatly enhanced – these are some of the drivers for the widespread development and deployment of machine learning algorithms. Algorithms such as classifiers, however, are trained from large amount of labeled data, and can therefore encode and even reinforce past discriminatory practices that are present in the data. The classifier might treat some groups of individuals unfavorably, for example, denying credit on the grounds of language, gender, age and their combined effect. Algorithmic fairness aims at building machine learning algorithms that can take biased datasets and outputs fair/unbiased decisions for people with differing protected attributes, such as race, gender, and age.

A typical setting of algorithmic fairness is as follows. We are given a training set of observations $x \in \mathcal{X}$, their corresponding protected attributes $s \in \mathcal{S}$, and the target label $y \in \mathcal{Y}$ for learning a classifier. In a statistical notion of algorithmic fairness e.g. (Kamiran & Calders, 2012; Hardt et al., 2016; Zafar et al., 2017), we control the discrepancy of a classifier's loss for a small number of demographic groups defined on protected attributes. Recently, several works have considered the setting where protected attributes are unknown (Kearns et al., 2018; Hashimoto et al., 2018; Khani et al., 2019). They aim to control the losses of groups whose size is greater than some predefined value. These works focus on an *abstract* worst-off group rather than demographic groups. It has been noted that the implied worst-off groups may differ from well-specified demographic groups who are known to suffer from past discriminatory practices (Hashimoto et al., 2018).

We are interested in the setting that is in between having complete annotations for demographic groups and having none. In this paper, we introduce algorithmic fairness with *invisible demographics*.

Figure 1: Overview of learning with invisible demographics: the train dataset, the context dataset and the proposed approach using a perfect dataset.

Who are the invisible demographics? In the context of machine learning systems, those are individuals with thin or non-existent labeled training data. The invisible population is primarily composed of individuals with certain protected attributes (Hendricks, 2005; Abualghaib et al., 2019; Perez, 2019). We now elaborate on several algorithmic decision scenarios involving invisible demographics. One scenario is when we observe partial outcomes for some of the demographic groups, e.g. we have labeled training data for males (with positive and negative outcomes), but for the group of females, we only observe the one-sided labels (negative outcome). Another scenario is when we do not observe any outcome for some of the demographic (sub)groups, e.g. we have training samples for white-skinned and dark-skinned males, and white-skinned females, but we have zero labeled data for dark-skinned females. An extreme version of the last scenario is when we do not observe any outcome for females regardless of their skin colors, e.g. we only have training samples for males and no training examples for females. To summarize, in the invisible demographics problem, we *define* the demographics groups that are expected to be seen, so they are not abstract. However, not all of the demographics are observed (labeled) during training, forming missing or invisible demographics.

This paper presents learning disentangled representations in the presence of invisible demographics. Our source of supervision is motivated by the observation that we want to deploy our classifier to the eventual real-world population. This deployment dataset will contain individuals from all demographics. We thus consider the setting where unlabeled data is available for learning disentangled representation. We call this data a *context set* and this context set is much like the deployment dataset, it is unlabeled but it contains all demographics including the invisible ones.

We aim to convert our unlabeled context set into a *perfect dataset* (Kleinberg et al., 2016; Chouldechova, 2017), a dataset in which the target label and protected attribute are independent (i.e. $y \perp s$). We will then use this perfect dataset as the inductive bias for learning disentangled representations. How do we construct this perfect dataset without labels? We assume that the number of demographic groups (hence clusters) is known a priori corresponding to the diverse demographic groups in the real-world population in which our machine learning system will be deployed. We use unsupervised kmeans clustering, or a supervised clustering based on rank statistics; the latter one allows to form the clusters that also support annotations in the train data. Once the clusters have been found, we can equalize the cluster size to form a perfect dataset and use it as an input for learning a disentangled fair representation. See fig. 1 for an overview of our learning with invisible demographic framework.

Specifically, our paper provides the following main contributions:

1. A problem of algorithmic fairness with invisible demographics where we have *zero data* for some of demographics and we still have to make predictions for those groups.
2. Applying clustering methods to the task of transforming *unlabeled context dataset* into a perfect dataset.
3. Theoretical and experimental justification that the disentangled model with *the perfect dataset as an inductive bias* provides a well-disentangled fair representation, one component captures the demographic factors and another component is invariant to them.

Related work We describe related work in three areas: zero-shot learning, semi-supervised learning, and disentangled representation learning. **On zero-shot learning.** The setting with incomplete training data, where we aim to account for seen and unseen outcomes is also known as *generalized zero-shot learning*. Traditionally, zero-shot learning transfers knowledge from classes for which we

have training data to classes for which we do not have via auxiliary knowledge, e.g. via prototype examples (Larochelle et al., 2008), intermediate class description such as semantic attributes (Lampert et al., 2009; Xian et al., 2018), word2vec embeddings (Bucher et al., 2019). Our method similarly uses a context set as a source of auxiliary knowledge but in in contrast to generalized zero-shot learning, our context set is an unlabeled pool of data, where class descriptions are unknown. **On semi-supervised learning.** Wick et al. (2019) proposed a semi-supervised method that can successfully harness unlabeled data to correct for the selection bias and label bias in the training data. The unlabeled data, despite not containing the target label y, *is* labeled in terms of the protected variable s. Our setting is significantly harder because there is no label information about y and s in the context set. **On disentangled representations learning.** Locatello et al. (2019a) suggested that disentanglement in representation learning may be a useful property to encourage fairness when protected variables are not observed. In order for disentangled representations to improve fairness measure without the knowledge of protected attribute s, they have to assume that the target label y and the protected attribute s are independent, i.e. $y \perp s$. The independence assumption is necessary because those unsupervised disentanglement methods can only discard s that are not correlated with y. Though, in fairness settings, the variable s is correlated with the variable y, and therefore unsupervised methods are not suitable for fairness (Jaiswal et al., 2018b; 2019). Indeed, experiments in (Locatello et al., 2019a) were wholly done with procedurally generated synthetic datasets involving 2D and 3D shapes. Without some supervision or inductive bias, disentangled representation methods would not solve the issue of algorithmic fairness with invisible demographics (Locatello et al., 2019b).

2 METHODOLOGY

2.1 THEORETICAL BACKGROUND

In this section, we first formulate mathematically the problem of invisible demographics and its associated issue of algorithmic fairness. We then motivate theoretically the idea of perfect dataset for achieving fairness, and its use for an inductive bias in learning disentangled representations.

Invisible demographics and algorithmic fairness. Let S denote the set of discrete-valued protected attributes with an associated domains $\mathcal{S}$. S can take the values taken by a single protected attribute, or, $S = S_1 \times S_2 \times \ldots \times S_p$ with $S_1, \ldots, S_p$ be discrete-valued protected attributes more generally. X, with the associated domain $\mathcal{X}$, represents other attributes of the data. Let $\mathcal{Y}$ denote the space of class labels for a classification task ($\mathcal{Y} = \{0, 1\}$ for binary classification or $\mathcal{Y} = \{1, 2, \ldots, C_{\text{cls}}\}$ for multi-class classification). For ease of exposition, we assume that we have multiple sources of samples, one for each combination of class label y and protected attribute s. That is, we have:

$$\mathcal{M}_{ys}, \qquad \forall y \in \mathcal{Y}, \forall s \in \mathcal{S}, \tag{1}$$

where, for example, the source $\mathcal{M}_{y=0, s=0}$ contains all data points with class label $y = 0$ and protected attribute $s = 0$. As in a standard supervised learning task, we have access to a training set $D^{\text{tr}} = \{(x_i, s_i, y_i)\}$, that is used to learn a model $M : \mathcal{X} \rightarrow \mathcal{Y}$. This labeled training dataset, however, lacks samples from some of the sources:

$$\exists y \in \mathcal{Y}, \exists s \in \mathcal{S} : D^{tr} \cap \mathcal{M}_{ys} = \varnothing. \tag{2}$$

For example, we might not have samples from two sources: $\mathcal{M}_{y=0, s=0}$ and $\mathcal{M}_{y=1, s=0}$. In binary classification, this corresponds to zero-labeled data for the *invisible demographic* group $s = 0$. Or we only observe a negative outcome for the invisible demographic $s = 0$, i.e. we have $\mathcal{M}_{y=1, s=0} = \varnothing$.

Once the model M is trained, we deploy it to the real-world population with diverse demographic groups. That is, we have a deployment set, $D^t = \{(x_i)\}$ which has overlap with all sources:

$$D^t \cap \mathcal{M}_{ys} \neq \varnothing \qquad \forall y \in \mathcal{Y}, \forall s \in \mathcal{S}. \tag{3}$$

If the model relies only on the incomplete training set, it is not unreasonable to expect that the model to easily misunderstand the *invisible*s. We can all agree that this sounds unfair, and we would like to rectify this. We will be precise shortly about the adopted mathematical definitions of fairness.

We propose to alleviate the issue of unfairness to the *invisibles* by mixing labeled with unlabeled data, which is usually much cheaper to obtain. In this paper, we call this unlabeled data a context set $\mathcal{D}^{ctx} = \{(x_i)\}$. This context set has overlap with all sources:

$$\mathcal{D}^{ctx} \cap \mathcal{M}_{ys} \neq \varnothing \qquad \forall y \in \mathcal{Y}, \forall s \in \mathcal{S} \tag{4}$$

The context set is much like the deployment set: it has no information about class labels y or the protected attributes s.

We adopt a statistical notion of algorithmic fairness in which it balances a certain condition between groups of individuals with different protected attributes. The term $\bar{y}$ below is the prediction of a machine learning model M. Several statistical fairness criteria have been proposed (Kamiran & Calders, 2012; Hardt et al., 2016; Zafar et al., 2017; Chouldechova, 2017; Raghavan et al., 2020) (shown below for the case where s and y are binary):

$$\Pr(\bar{y}=1|s=0) = \Pr(\bar{y}=1|s=1) \qquad \text{(equality of acceptance rate)} \quad (5)$$

$$\Pr(\bar{y}=1|s=0,y=1) = \Pr(\bar{y}=1|s=1,y=1) \qquad \text{(equality of true positive rate)} \quad (6)$$

$$\Pr(\bar{y}=0|s=0,y=0) = \Pr(\bar{y}=0|s=1,y=0) \qquad \text{(equality of true negative rate)} \quad (7)$$

$$\Pr(y=1|s=0,\bar{y}=1) = \Pr(y=1|s=1,\bar{y}=1) \qquad \text{(equality of positive predicted value)} \quad (8)$$

$$\Pr(y=0|s=0,\bar{y}=0) = \Pr(y=0|s=1,\bar{y}=0) \qquad \text{(equality of negative predicted value).} \quad (9)$$

Generally, those statistical notions can be expressed in terms of different (conditional) independence statements between the involved random variables (Barocas et al., 2019): $\bar{y} \perp s$ (eq. 5), $\bar{y} \perp s \mid y$ (eq. 6–7), and $y \perp s \mid \bar{y}$ (eq. 8–9). If our training set has no positive outcome for the demographic $s = 0$, i.e. $\mathcal{M}_{y=1,s=0} = \varnothing$, the true positive rate for this group will suffer, and therefore we will likely not be able to satisfy, among others, equality of true positive rate (eq. 6).

Perfect dataset. We call a dataset for which $y \perp s$ holds, a perfect dataset (Chouldechova, 2017; Kleinberg et al., 2016). If we have access to a perfect dataset, we could equalize true positive/negative rates (eq. 6–7) and also equalize positive/negative predicted values (eq. 8–9) for all demographic groups. This can be shown by using the sum and product rule of conditional probabilities, e.g. (Kannan et al., 2019). Let's consider a binary-valued protected attribute, s' versus s''. For s', we can compute: $\Pr(y = 1|\bar{y} = 1, s') = \Pr(\bar{y}=1|y=1,s')\Pr(y=1|s')\big/\big(\Pr(\bar{y}=1|y=1,s')\Pr(y=1|s')+\Pr(\bar{y}=1|y=0,s')(1-\Pr(y=1|s'))\big)$, and accordingly for s''. The conditional probability on the left hand side is a positive predicted value, and this quantity can be expressed in terms of true positive/negative rates and the base (prior) rate, shown on the right hand side. If we have a perfect dataset ($y \perp s$ holds, which means equal base rates $\Pr(y = 1|s') = \Pr(y = 1|s'')$), an equality in the true positive/negative rates will give us an equality in the positive/negative predicted values. Similarly, with a perfect dataset, we can equalize true positive/negative rates (eq. 6–7) and also acceptance rates (eq. 5) for all demographic groups. From the sum probability rule, we have: $\Pr(\bar{y} = 1|s') = \Pr(\bar{y} = 1|y = 1, s')\Pr(y = 1|s') + \Pr(\bar{y} = 1|y = 0, s')(1 - \Pr(y = 1|s'))$ for s' value, and accordingly for s'' value. Here, an acceptance rate on the left hand side is related to true positive/negative rates and the base (prior) rate as shown on the right hand side. In general, however, our given dataset is likely to be imperfect. In this paper, we pursue learning a fair classifier for all demographics as learning disentangled representations with an *approximately* perfect dataset.

Disentangled representation. Disentanglement learning aims to find a split representation of a data point x and a mapping function f such that $f(x) = (z_1, z_2, \ldots, z_p)$ where $z_1, z_2, \ldots, z_p$ are p distinct (independent) factors of variations. We can mathematically formalize this intuitive definition using group and representation theories Higgins et al. (2018), or using structural causal models Suter et al. (2019). Specifically in this paper, we would like to split representation of data into two factors as $f(x) = (z_y, z_s)$ where z_y contains factors that are relevant for y-prediction and z_s contains factors related to demographic group s. As noted by Jaiswal et al. (2018a; 2019) (also vide sec. 1), since the protected variable s is correlated with the class label y, we need annotations of undesired nuisance variable s to be successful in using disentanglement learning methods for fairness. We only have annotations of variable s in the training set $\mathcal{D}^{tr} = \{(x_i, s_i, y_i)\}$, however, crucially, this set contains missing demographic groups. We have all demographic groups in the context set $\mathcal{D}^{ctx} = \{(x_i)\}$ (also in the deployment set $\mathcal{D}^{tr} = \{(x_i)\}$), though, the challenge is we should not expect annotations of protected variable s at the deployment time. The next section will show that we can still leverage the context set for learning the disentangled representations.

Disentanglement with a perfect dataset. Our framework for learning the disentangled representations comprises four core modules: 1) an *encoder* function f that embeds x into a bipartite space $f(x) \rightarrow (z_y, z_s)$; 2) a *decoder* function g that learns the inverse of f, mapping back from the embedded space into the input domain $g(z_y, z_s) \rightarrow \tilde{x}$; 3) a *predictor* function l that predicts y from z_y, and 4) a *discriminator* function h that classifies whether a given batch of samples embedded in z_y derives from the either context set or the training set; this marks a significant departure from the

(a) Architecture of our proposed method.

(b) Example representation of the distribution matching algorithm. In this case, the training set is lacking examples of purple 4's. By enforcing the subspace z_y to have the same distribution for both the training and test set, the model is encouraged to learn a representation that is invariant to color (or s in general.) For this to work, it is crucial that the batches are balanced.

Figure 2: Overview of the disentangling framework with a perfect dataset as an inductive bias.

typical GAN discriminator, which takes as input batches of data and yields a prediction for each sample independently of the other samples in the batch. Fig. 2a shows our framework, where the training signal comes from the perfect dataset. Formally, given the training set, $\mathcal{D}^{tr}$ and samples from the *balanced* (i.e. *perfect* – see section 2.2 for how this details on how this can be practically achieved) context set $\mathcal{X}_{perf}$, our learning objective can be written as:

$$L_{match} = \sum_{x \in \mathcal{X}_{tr} \bigcup \mathcal{X}_{perf}} L_{recon}(x, g(z_s, z_y)) + \lambda_1 \sum_{x \in \mathcal{X}_{tr}} L_{sup}(y, l(z_y)) +$$
$$+ \lambda_2 \left(\log h(f(z_y \subset \mathcal{X}_{perf})) + \log(1 - h(f(z_y \subset \mathcal{X}_{tr}))) \right), \quad (10)$$

where L_{recon} and L_{sup} denote the reconstruction loss, and supervised loss, respectively, and λ_1 and λ_2 are pre-factors. In practice, this objective is computed over mini-batches, B, and the discriminator h is trained via the standard JSD loss (Goodfellow et al., 2014) to map a batch of data points from the training set and the context set to a binary label: 1 if the batch is judged to have been sampled from the context set, 0 otherwise. Its goal is to effectively estimate the probability that a batch of samples, as a set, has been sampled from one distribution or the other. Since the task is a set-prediction one, we require that the function it defines respects the exchangeability of the batch dimension – that is the discriminator's predictions should take into account dependencies between samples in a batch but should be invariant to the order in which they appear, i.e. we have $h(\{z_y\}_{b=i}^B) = h(\{z_y\}_{b=\pi(i)}^B)$ for all permutations $\pi \in \Pi$. To render the entirety of the function h composed of sub-functions $h_1(h_2(h_3...)))$, it requires only the innermost, sub-function, ρ in the chain to have this property. While there are a number of choices when it comes to defining ρ, we choose a weighted average $\rho = \frac{1}{B} \sum_i (\{\text{attention}(z_y)\}_{b=i}^B)$, with weights computed according to a learned attention mechanism. It takes the form of the scaled dot-product attention (Vaswani et al., 2017) $\text{attention}(Q, K, V) := \text{softmax}(QK^T/\sqrt{d})V$, , weighting values (V) according to the similarity between the associated key (K) and query (Q) matrices, as measured by their dot-product. Q, K, and V are used after they have been embedded into linear subspaces by matrix-multiplication with learned weight matrices of dimension $\mathbb{R}^{m \times d}$. We found that defining K and V as z_y, and Q as the mean of z_y over B, yielded good results and leave it to future work to explore more sophisticated methods. The result of ρ is then processed by a series of fully-connected layers, following the DeepSets (Zaheer et al., 2017) paradigm, which ultimately computes a single prediction for the current batch.

We know that the independence condition $y \perp s$ holds in the perfect set, but not in the training set due to sampling bias. To do well, the discriminator should rely on this knowledge. More concretely, since the context and training set have differing support over $\mathcal{S} \times \mathcal{Y}$, namely $\text{Sup}(\mathcal{S}_{tr} \times Y_{tr}) \subset \text{Sup}(\mathcal{S}_{perf} \times \mathcal{Y}_{perf})$, that support serves as an indicator of the distribution from which the data has been drawn. The scenarios we consider dictate $\text{Sup}(\mathcal{Y}_{tr}) = \text{Sup}(\mathcal{Y}_{perf})$, making the disentangling well-posed. However, since we wish to use $\text{Sup}(\mathcal{S}_{ctx} \times \mathcal{Y}_{ctx}) \setminus \text{Sup}(\mathcal{S}_{tr} \times \mathcal{Y}_{tr})$ as the training signal for the encoder, and not the relative frequency of the target classes, it is important that, like the context set, we weight the samples of the training set such that $p(s_{tr}|y_{tr})(p(y_{tr})$ is equal for all

$s_{tr}, y_{tr} \in \mathcal{S}_{tr} \times \mathcal{Y}_{tr}$. To guide the network towards the desired solution, we supplement this implicit constraint with the explicit constraint that z_y be predictive of y, which we achieve using a linear predictor l; whenever we have $|S| > 1$ (in our experiments this corresponds to the *partial outcomes* setting) we also impose the same constraint on z_s, but with respect to s. With these conditions met, to fool the discriminator, the encoder must separate out information pertaining to S into the embedded space z_s not part of the discriminator's input, leaving only the unprotected information in z_y.

2.2 Implementation

Our framework overall entails two steps: 1) a method to construct a perfect dataset from an unlabeled context set, and 2) a method to produce disentangled representations using the perfect dataset.

Constructing approximately perfect dataset via clustering. We cluster the data points from the context set into $K = |\mathcal{Y}| \cdot |\mathcal{S}|$ number of clusters, i.e. the number of data sources $\mathcal{M}_{y,s}$. We use k-means clustering algorithm, and a recent method based on rank statistics (Han et al., 2020). The cluster assignments can then be used as the basis for constructing a *perfect dataset* for the subsequent disentangling phase. As a result of clustering, the data points in the context set $\mathcal{D}^{ctx}$ are labeled with cluster assignments $\mathcal{D}^{ctx} = \{(x_i, c_i)\}$, $c_i = C(z_i)$. We balance $\mathcal{D}^{ctx}$ so that all clusters have equal size to form a perfect dataset (see fig. 1), and use it as a supervision signal for the disentangling.

Clustering requirements. We do not need to explicitly name the clusters (i.e. finding the demographic groups and labels that the clusters correspond to is unnecessary). The clustering is needed for drawing an equal number of samples from each cluster, for each batch of data. Thus, constructing the perfect dataset in this way does not require solving the linear assignment problem of cluster-source association. In our experiments, we provide an analysis with unsupervised k-means clustering where we do not use annotations from the training set even for the *known* groups. When clustering with the training labels (such as with the rank statistics approach), we use the information that they provide to ensure samples from the *known* subgroups are clustered together with others with the same label.

3 Experiments

We conduct experiments using the Colored MNIST (Kim et al., 2019; Arjovsky et al., 2019; Kehrenberg et al., 2020) and Adult Income (Dheeru & Karra Taniskidou, 2017) datasets that are publicly available. We compare the performance of the proposed approach with several baselines. To validate the first step of creating the perfect dataset, we compare three approaches: the proposed model with clustering via rank statistics (`ZSF+bal. (ranking)`), with clustering via k-means (`ZSF+bal. (k-means)`), and without balancing, when the context set $\mathcal{D}^{ctx}$ is used directly (`ZSF`); followed by the disentangling step as described. Additionally, we evaluate a variant where the batches are balanced with ground truth labels (`ZSF+bal. (ground truth)`). To validate the second step of learning fair representation via disentangling, we compare with two other baselines. We train a binary classifier on the labeled training data without fairness consideration (`CNN` for Colored MNIST and `MLP` for Adult Income). We compare to the fairness without demographics (`FWD`) method (Hashimoto et al., 2018) that learns fair classifier with abstract groups. This is the only fairness based method that is sensible to evaluate in the setting with invisible demographics. In the setting of learning with partial outcomes, i.e. when we observe one-sided outcome for one of the demographics, we can compare with two additional fairness-aware baselines. The first is an adaptation of our model based on a common fair representation learning paradigm (Edwards & Storkey, 2015; Madras et al., 2018) in which an adversary is used to minimize the mutual information between s and the representation z. We refer to this model as `MIM` (Mutual Information Minimization). This adaptation amounts to just modifying the adversarial loss but is only applicable in the setting where both protected groups are present in the training data (*partial outcome setting*), hence making it less general than our distribution-matching approach which can handle cases in which demographics are missing entirely. The second is the frequency-count-based *reweighting* method of Kamiran & Calders (2012) `Kamiran & Calders LR`. We note, however, that the method assumes that all combinations of y and s are observed in the labeled data. Nevertheless, even in the *partial outcome setting* that we address (where we have samples labeled for all values of s but not for all combinations of s and y), the method yields fairer classifications than the unregularized logistic regression baseline. We report the following performance metrics: clustering accuracy on the context set, classification accuracy and fairness metrics of the prediction task on the test set.

Table 1: Results on Colored MNIST dataset for the task of *two* versus *four* digits classification with a binary protected attribute (purple, green). We consider the scenarios of learning with partial outcomes (20 repeats) and missing demographic (8 repeats). The fairness measures are: the ratio of acceptance rates (AR ratio), true positive rates (TPR ratio), and true negative rates (TNR ratio) between the two demographics, respectively (the closer to one the fairer).

Learning with partial outcomes, the source $\mathcal{M}_{y=\text{'four'}\ s=purple}$ is invisible.

	Cluster. Acc. ↑	Acc. ↑	AR ratio → 1.0 ←	TPR ratio → 1.0 ←	TNR ratio → 1.0 ←
ZSF+bal. (ranking)	**0.83 ± 0.17**	0.88 ± 0.08	0.53 ± 0.33	0.53 ± 0.33	0.99 ± 0.03
ZSF+bal. (k-means)	0.78 ± 0.17	**0.93 ± 0.07**	**0.73 ± 0.26**	**0.74 ± 0.27**	0.996 ± 0.003
ZSF+bal. (ground truth)	(1.0)	0.92 ± 0.06	0.68 ± 0.24	0.69 ± 0.24	**0.997 ± 0.003**
ZSF	N/A	0.82 ± 0.07	0.25 ± 0.28	0.25 ± 0.28	0.994 ± 0.005
FWD Hashimoto et al. (2018)	N/A	0.79 ± 0.04	0.12 ± 0.16	0.12 ± 0.17	0.99 ± 0.005
CNN	N/A	0.758 ± 0.007	0.0 ± 0.001	0.0 ± 0.001	0.992 ± 0.004

Learning with missing demographics (purple color), two sources $\mathcal{M}_{y=\text{'four'}\ s=purple}$, $\mathcal{M}_{y=\text{'two'}\ s=purple}$ are invisible.

	Cluster. Acc. ↑	Acc. ↑	AR ratio → 1.0 ←	TPR ratio → 1.0 ←	TNR ratio → 1.0 ←
ZSF+bal. (ranking)	0.69 ± 0.2	0.83 ± 0.12	0.75 ± 0.17	**0.76 ± 0.32**	0.58 ± 0.29
ZSF+bal. (k-means)	**0.71 ± 0.15**	0.79 ± 0.11	0.64 ± 0.2	0.59 ± 0.31	0.58 ± 0.35
ZSF+bal. (ground truth)	(1.0)	0.84 ± 0.12	**0.92 ± 0.03**	0.70 ± 0.24	0.65 ± 0.25
ZSF	N/A	**0.88 ± 0.14**	0.84 ± 0.1	0.69 ± 0.28	**0.80 ± 0.32**
FWD Hashimoto et al. (2018)	N/A	0.76 ± 0.02	0.26 ± 0.22	0.42 ± 0.45	0.60 ± 0.46
CNN	N/A	0.76 ± 0.02	0.47 ± 0.41	0.32 ± 0.30	0.71 ± 0.26

Colored MNIST dataset. The colored MNIST dataset is a variant of the MNIST dataset in which the digits are colored, and the color simulates the protected attributes of the digit. We study binary classification, digit *two* versus digit *four*, and explore two settings: with one digit-color source invisible (learning with partial outcomes) and two digit-color sources invisible (learning with missing demographics). Specifically, in the first setting we have training data for digit *two* in green and purple colors, but the digit *four* only comes in green color, so the source $\mathcal{M}_{y=\text{'four'}\ s=purple}$ is invisible. The second setting is learning with missing demographics, where we have training data for both digits in green, but we do not have training data for the demographics of purple color, i.e. two sources $\mathcal{M}_{y=\text{'two'}s=purple}$ and $\mathcal{M}_{y=\text{'four'}s=purple}$) are invisible. At test time and in the context set we observe all possible colored digits combinations. We follow the colorization procedure outlined by Kim et al. (2019), with the mean color values selected so as to be maximally dispersed. The images are symmetrically zero-padded to a size of 32x32. In the 2-digit case, we use 5,339 images in the unlabeled context set, 2,328 training samples, and 2,014 for testing the classifier.

We report the results in Table 1. In both settings, we are able to clearly outperform the baselines. In the partial outcome setting, we can see that balancing the batches (`bal.`), to emulate a perfect dataset, significantly improves performance, not only in terms of accuracy but in all fairness metrics. `k-means` clustering and `ground truth` perform particularly well. For the setting with missing demographics, `ranking` clustering and `ground truth` perform well. Though, we notice that `ZSF` gives high accuracy, at the expense of fairness metrics.

Adult Income dataset. The Adult Income dataset is a common dataset for evaluating fair machine learning models. In this dataset, each instance is described by 14 characteristics including gender, education, marital status, number of work hours per week among others, along with a label denoting income level ($\geq$50K or not). We transform the representation into 62 real and binary features along with the protected attribute s. In the whole dataset, 30% of the male individuals earn more than \$50K per year (high income), however of the female individuals only 11% have a high income. Following the common setting e.g. (Zemel et al., 2013), we consider gender to be the protected attribute.

For evaluation, we balanced the test set such that all elements of $S \times Y$ are equally sized, observing that a random subset of the data could lead to a majority classifier achieving comparable accuracy to the fairness-unaware baselines, while achieving perfect fairness in terms of TPR ratios. We repeat the procedure with five different train/context/test splits and report the average performance over the five runs. We study the following two settings. 1) *Invisible demographics*: we have training data for males with positive and negative outcomes, but do not have labeled data for females, i.e. $\mathcal{M}_{y=1s=0}$ and $\mathcal{M}_{y=0s=0}$ are missing; 2) *Partial outcomes*: we have labeled training data for males $s = 1$ with both positive and negative outcomes, but for the group of females $s = 0$, we only observe the one-sided negative outcome, so the source $\mathcal{M}_{y=1s=0}$ is invisible.

Table 2: Results on the Adult Income dataset for the binary classification task of predicting whether an individual earns >\$50,000 with a binary protected attribute (gender). We consider two scenarios: one where an entire demographic is missing (females are missing from the training set; **Top**) and one where we only partially observe outcomes for one of the demographics (all females earn less than \$50,000; **Bottom**). The fairness measures are: AR (Acceptance Rate) ratio, TPR (True Positive Rate) ratio, and TNR (True Negative Rate) ratio.

Learning with partial outcomes, the source $\mathcal{M}_{y=\text{'above \$50,000'},s=\text{'female'}}$ is invisible.

	Cluster. Acc. ↑	Acc. ↑	AR ratio → 1.0 ←	TPR ratio → 1.0 ←	TNR ratio → 1.0 ←
ZSF+bal. (ranking)	**0.695 ± 0.003**	**0.679 ± 0.025**	0.34 ± 0.16	0.38 ± 0.18	0.906 ± 0.012
ZSF+bal. (k-means)	0.340 ± 0.014	0.661 ± 0.014	0.23 ± 0.06	0.27 ± 0.06	0.906 ± 0.012
ZSF	N/A	0.667 ± 0.015	0.28 ± 0.17	0.33 ± 0.20	0.898 ± 0.016
MIM	N/A	0.677 ± 0.028	0.52 ± 0.30	0.55 ± 0.27	0.940 ± 0.030
MIM+bal. (ranking)	**0.695 ± 0.003**	0.606 ± 0.008	0.30 ± 0.10	0.27 ± 0.08	**0.965 ± 0.011**
FWD Hashimoto et al. (2018)	N/A	0.663 ± 0.008	0.19 ± 0.03	0.21 ± 0.03	0.903 ± 0.015
Kamiran & Calders (2012) LR	N/A	0.638 ± 0.008	0.22 ± 0.05	0.25 ± 0.05	0.948 ± 0.010
MLP	N/A	0.664 ± 0.005	0.18 ± 0.03	0.20 ± 0.03	0.906 ± 0.017

Learning with missing demographics (Females),
Learning with missing demographics (Females), two sources $\mathcal{M}_{y=\text{'above \$50,000' } s=\text{'female'}}$, $\mathcal{M}_{y=\text{'below \$50,000' } s=\text{'female'}}$ are invisible.

	Cluster. Acc. ↑	Acc. ↑	AR ratio → 1.0 ←	TPR ratio → 1.0 ←	TNR ratio → 1.0 ←
ZSF+bal. (ranking)	**0.610 ± 0.005**	0.757 ± 0.021	0.86 ± 0.07	**0.93 ± 0.05**	0.939 ± 0.022
ZSF+bal. (k-means)	0.332 ± 0.012	0.742 ± 0.042	0.76 ± 0.30	0.76 ± 0.29	0.956 ± 0.030
ZSF	N/A	0.735 ± 0.028	0.69 ± 0.20	0.75 ± 0.21	0.927 ± 0.009
FWD Hashimoto et al. (2018)	N/A	**0.776 ± 0.028**	0.79 ± 0.12	0.78 ± 0.08	**0.96 ± 0.02**
MLP	N/A	0.748 ± 0.009	0.68 ± 0.09	0.75 ± 0.11	0.924 ± 0.006

The results for both of these settings are given in Table 2. *Partial outcomes*. We see that ZSF consistently outperforms the non-MIM baselines in terms of fairness (AR ratio and TPR ratio) and performs on-par or better than them in terms of accuracy. The importance of the context-set being properly balanced for our method is reflected in the superiority of ZSF+bal. (ranking), while the k-means variant fails to recognize the correct clustering according to $S \times Y$ and the downstream accuracy suffers. The MIM baseline with *no balancing* (MIM), does however, come out on top on the basis of fairness and accuracy alike, but as stressed before, cannot generalize to the *invisible demographics* setting, where $|S_{tr}| = 1$. While FWD, on the other hand, is generalizable, it performs no better than the baseline MLP according to our computed metrics. *Invisible demographics*. In the absence of $s_{tr} = $ Female altogether, FWD outperforms the baseline MLP in all respects, being the top-performer in accuracy among the tabulated methods. However, ZSF+bal. (ranking) shows to be considerably fairer according to two of the fairness metrics (AR ratio and TPR ratio), at the cost of accuracy, and again demonstrates the importance of a balanced context set. In both settings, even though the clustering accuracy is far from perfect, it is good enough benefit the distribution matching phase, indicating that while L_{match} is sensitive to the quality of X_{perf}, it is not overly so.

4 DISCUSSION AND CONCLUSION

We have introduced a problem of algorithmic fairness in the presence of *invisible demographics*, which is at the intersection of demographic group fairness with each training data point annotated with protected attributes, and abstract group fairness with unknown protected attributes. We want to protect well-specified demographic groups but some demographics have non-existent labeled training data - those individuals are the invisible demographics. Our proposed model consists of discovering the missing demographic clusters in the unlabeled context set and subsequently learning a disentangled fair representation that can be used at deployment. We consider the train and context sets as coming from the same data domain, such that the knowledge about invisible demographics can be directly transferred from the latter. Extending the model to allow for a domain adaptation step between those sets will be explored in the future. This work is the first attempt in addressing learning with invisible demographics, and we hope it will spark broad interest in the community.

REFERENCES

Ola Abualghaib, Nora Groce, Natalie Simeu, Mark Carew, and Daniel Mont. Making visible the invisible: Why disability-disaggregated data is vital to "leave non-one behind". *Sustainability*, 11, 2019.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Arturs Backurs, Piotr Indyk, Krzysztof Onak, Baruch Schieber, Ali Vakilian, and Tal Wagner. Scalable fair clustering. *arXiv preprint arXiv:1902.03519*, 2019.

Solon Barocas, Moritz Hardt, and Arvind Narayanan. *Fairness and Machine Learning*. fairmlbook.org, 2019. http://www.fairmlbook.org.

Maxime Bucher, Tuan-Hung Vu, Matthieu Cord, and Patrick Pérez. Zero-shot semantic segmentation. In *Advances in Neural Information Processing Systems*, 2019.

Flavio Chierichetti, Ravi Kumar, Silvio Lattanzi, and Sergei Vassilvitskii. Fair clustering through fairlets. In *Advances in Neural Information Processing Systems*, pp. 5029–5037, 2017.

Alexandra Chouldechova. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big data*, 5(2):153–163, 2017.

Dua Dheeru and Efi Karra Taniskidou. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Harrison Edwards and Amos Storkey. Censoring representations with an adversary. *arXiv preprint arXiv:1511.05897*, 2015.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial nets. In Zoubin Ghahramani, Max Welling, Corinna Cortes, Neil D. Lawrence, and Kilian Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27: Annual Conference on Neural Information Processing Systems 2014, December 8-13 2014, Montreal, Quebec, Canada*, pp. 2672–2680, 2014.

Kai Han, Sylvestre-Alvise Rebuffi, Sébastien Ehrhardt, Andrea Vedaldi, and Andrew Zisserman. Automatically discovering and learning new visual categories with ranking statistics. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=BJl2_nVFPB.

Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 3315–3323. Curran Associates, Inc., 2016.

Tatsunori B. Hashimoto, Megha Srivastava, Hongseok Namkoong, and Percy Liang. Fairness without demographics in repeated loss minimization. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1934–1943. PMLR, 2018.

Jon Hendricks. Ageism: Looking across the margin in the new millennium. *Generations*, 3:5–7, 2005.

Irina Higgins, David Amos, David Pfau, Sébastien Racanière, Loïc Matthey, Danilo J. Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *CoRR*, abs/1812.02230, 2018.

Lingxiao Huang, Shaofeng Jiang, and Nisheeth Vishnoi. Coresets for clustering with fairness constraints. In *Advances in Neural Information Processing Systems*, pp. 7587–7598, 2019.

Mikella Hurley and Julius Adebayo. Credit scoring in the era of big data. *Yale Journal of Law and Technology*, 18:148–216, 2017.

Ayush Jaiswal, Rex Yue Wu, Wael Abd-Almageed, and Prem Natarajan. Unsupervised adversarial invariance. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 5092–5102. Curran Associates, Inc., 2018a.

Ayush Jaiswal, Rex Yue Wu, Wael Abd-Almageed, and Prem Natarajan. Unsupervised adversarial invariance. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 5092–5102. Curran Associates, Inc., 2018b.

Ayush Jaiswal, Rex Yue Wu, Wael AbdAlmageed, and Premkumar Natarajan. Unified adversarial invariance. *CoRR*, abs/1905.03629, 2019.

F. Kamiran and T. Calders. Data preprocessing techniques for classification without discrimination. *Knowledge and Information Systems*, 33(1):1–33, 2012.

Sampath Kannan, Aaron Roth, and Juba Ziani. Downstream effects of affirmative action. In *Proceedings of the Conference on Fairness, Accountability, and Transparency, FAT* 2019, Atlanta, GA, USA, January 29-31, 2019*, pp. 240–248. ACM, 2019. doi: 10.1145/3287560.3287578. URL https://doi.org/10.1145/3287560.3287578.

Michael Kearns, Seth Neel, Aaron Roth, and Zhiwei Steven Wu. Preventing fairness gerrymandering: Auditing and learning for subgroup fairness. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 2564–2572. PMLR, 2018.

Thomas Kehrenberg, Myles Scott Bartlett, Oliver Thomas, and Novi Quadrianto. Null-sampling for interpretable and fair representations. In *Computer Vision – ECCV 2020*. Springer International Publishing, 2020. ISBN 9783030586041. doi: 10.1007/978-3-030-58604-1. URL https://www.ecva.net/papers/eccv_2020/papers_ECCV/papers/123710562.pdf.

Fereshte Khani, Aditi Raghunathan, and Percy Liang. Maximum weighted loss discrepancy. *CoRR*, abs/1906.03518, 2019.

Byungju Kim, Hyunwoo Kim, Kyungsu Kim, Sungjin Kim, and Junmo Kim. Learning not to learn: Training deep neural networks with biased data. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

Jon Kleinberg, Sendhil Mullainathan, and Manish Raghavan. Inherent trade-offs in the fair determination of risk scores. *arXiv preprint arXiv:1609.05807*, 2016.

Christoph H Lampert, Hannes Nickisch, and Stefan Harmeling. Learning to detect unseen object classes by between-class attribute transfer. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, 2009.

Hugo Larochelle, Dumitru Erhan, and Yoshua Bengio. Zero-data learning of new tasks. In *Association for the Advancement of Artificial Intelligence (AAAI)*, 2008.

Francesco Locatello, Gabriele Abbati, Thomas Rainforth, Stefan Bauer, Bernhard Schölkopf, and Olivier Bachem. On the fairness of disentangled representations. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 14611–14624. Curran Associates, Inc., 2019a.

Francesco Locatello, Stefan Bauer, Mario Lucic, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *International Conference on Machine Learning (ICML)*, 2019b.

David Madras, Elliot Creager, Toniann Pitassi, and Richard Zemel. Learning adversarially fair and transferable representations. *arXiv preprint arXiv:1802.06309*, 2018.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *the Journal of machine Learning research*, 12:2825–2830, 2011.

Caroline Criado Perez. *Invisible women: Exposing data bias in a world designed for men*. Chatto & Windus, 2019.

Manish Raghavan, Solon Barocas, Jon M. Kleinberg, and Karen Levy. Mitigating bias in algorithmic hiring: evaluating claims and practices. In Mireille Hildebrandt, Carlos Castillo, Elisa Celis, Salvatore Ruggieri, Linnet Taylor, and Gabriela Zanfir-Fortuna (eds.), *FAT* '20: Conference on Fairness, Accountability, and Transparency, Barcelona, Spain, January 27-30, 2020*, pp. 469–481. ACM, 2020.

R. Suter, D. Miladinovic, B. Schölkopf, and S. Bauer. Robustly disentangled causal mechanisms: Validating deep representations for interventional robustness. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6056–6065. PMLR, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Michael Wick, Swetasudha Panda, and Jean-Baptiste Tristan. Unlocking fairness: a trade-off revisited. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8783–8792. Curran Associates, Inc., 2019.

Yongqin Xian, Christoph H Lampert, Bernt Schiele, and Zeynep Akata. Zero-shot learning—a comprehensive evaluation of the good, the bad and the ugly. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(9):2251–2265, 2018.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez-Rodriguez, and Krishna P. Gummadi. Fairness beyond disparate treatment & disparate impact: Learning classification without disparate mistreatment. In *Proceedings of the 26th International Conference on World Wide Web, WWW 2017, Perth, Australia, April 3-7, 2017*, pp. 1171–1180, 2017.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *Advances in neural information processing systems*, pp. 3391–3401, 2017.

Richard Zemel, Yu Wu, Kevin Swersky, Toniann Pitassi, and Cynthia Dwork. Learning fair representations. In S. Dasgupta and D. McAllester (eds.), *International Conference on Machine Learning (ICML)*, Proceedings of Machine Learning Research, pp. 325–333. PMLR, 2013.

A WHY NOT USE A FAIR CLUSTERING METHOD?

Current fair clustering methods (Chierichetti et al., 2017; Backurs et al., 2019; Huang et al., 2019) cluster based on the protected attribute and thus are not applicable to our setting in which the context set is unlabeled and the training set is incomplete with respect to s.

B DATASET CONSTRUCTION

B.1 COLORED MNIST BIASING PARAMETERS

To simulate a real-word setting where the data, labeled or otherwise, is usually not naturally balanced, we bias the Colored MNIST training and context sets by downsampling certain color/digit combinations. The proportions of each such combination *retained* in the *partial outcomes* (in which we have one source missing from the training set) and *invisible demographics* (in which we have two sources missing from the training set) are enumerated in Table 3 and 4, respectively.

Table 3: Biasing parameters for the training (left) and context (right) sets of Colored MNIST in the *partial outcomes* setting.

Combination	Proportion retained		Combination	Proportion retained
(y = 2, s = purple)	1.0		(y = 2, s = purple)	0.7
(y = 2, s = green)	0.4		(y = 2, s = green)	0.6
(y = 4, s = purple)	0.0		(y = 4, s = purple)	0.4
(y = 4, s = green)	1.0		(y = 4, s = green)	1.0

Table 4: Biasing parameters for the training (left) and context (right) sets of Colored MNIST in the *invisible demographics* setting.

Combination	Proportion retained		Combination	Proportion retained
(y = 2, s = purple)	0.0		(y = 2, s = purple)	0.7
(y = 2, s = green)	0.85		(y = 2, s = green)	0.6
(y = 4, s = purple)	0.0		(y = 4, s = purple)	0.4
(y = 4, s = green)	1.0		(y = 4, s = green)	1.0

B.2 BALANCING OF THE ADULT INCOME TEST-SET

A naive balancing of the set set such that

$$|\{x \in X | s = 0, y = 0\}| = |\{x \in X | s = 1, y = 0\}| \quad \text{and} \tag{11}$$
$$|\{x \in X | s = 0, y = 1\}| = |\{x \in X | s = 1, y = 1\}| \,.$$

that is, for both target classes $y = 0$ and $y = 1$, the proportions of the groups $s = 0$ and $s = 1$ are made to be the same, is intuitive, yet at the same time precludes sensible comparison of the accuracy/fairness trade-off of the different classifiers. Indeed, with the above conditions, a majority classifier (predicting all 1s or 0s) achieves comparable accuracy to the fairness-unaware baselines, while also yielding perfect fairness, by definition. This observation motivated us to devise an alternative scheme, where we balance the test set according to the following constraints

$$|\{x \in X | s = 0, y = 0\}| = |\{x \in X | s = 0, y = 1\}| \tag{12}$$
$$= |\{x \in X | s = 1, y = 1\}| = |\{x \in X | s = 1, y = 0\}|.$$

That is, all subsets of $\mathcal{S} \times \mathcal{Y}$ are made to be equally sized. Under this new scheme the accuracy of the the majority classifier is 50% for the binary-classification task.

C OPTIMIZATION

In addition to the losses stated in the distribution matching objective, L_{match}, in the main text, we also regularize the encoder by the ℓ^2 norm of its embedding, finding this to work better than more complex regularization methods such as spectral normalization (Miyato et al., 2018) for the sake of improving the stability of the adversarial training.

For evaluating on the Adult Income dataset we use scikit-learn's (Pedregosa et al., 2011) logistic regression (`LR`) model, optimized with LBFGS, as the base classifier for K&C, `MIM` and our method (`ZSF`). SVM and LR with cross-validation (`LRCV`) from the same library are also included as baselines. Due to the discrepancy between the training and test sets leading to biased CV estimates, we found that using `LR` with a fixed regularization constant ($C = 1.0$) consistently yielded better performance. For the `FWD` baseline, logistic regression was again used but with it trained via gradient descent (Adam, learning rate=1×10^{-3}) instead of via convex optimization due to the non-standard loss function.

D CODE

We will make the code publicly available.