Holomorphic Equilibrium Propagation Computes Exact Gradients Through Finite Size Oscillations

Abstract

Equilibrium propagation (EP) is an alternative to backpropagation (BP) that allows the training of deep neural networks with local learning rules. It thus provides a compelling framework for training neuromorphic systems and understanding learning in neurobiology. However, EP requires infinitesimal teaching signals, thereby limiting its applicability in noisy physical systems. Moreover, the algorithm requires separate temporal phases and has not been applied to large-scale problems. Here we address these issues by extending EP to holomorphic networks. We show analytically that this extension naturally leads to exact gradients even for finite-amplitude teaching signals. Importantly, the gradient can be computed as the first Fourier coefficient from finite neuronal activity oscillations in continuous time without requiring separate phases. Further, we demonstrate in numerical simulations that our approach permits robust estimation of gradients in the presence of noise and that deeper models benefit from the finite teaching signals. Finally, we establish the first benchmark for EP on the ImageNet 32×32 dataset and show that it matches the performance of an equivalent network trained with BP. Our work provides analytical insights that enable scaling EP to large-scale problems and establishes a formal framework for how oscillations could support learning in biological and neuromorphic systems.

1 Introduction

The backpropagation (BP) of error algorithm [1] underpins the ability of state-of-the-art deep neural networks to learn useful representations from structured data such as speech, vision, and text [2]. BP stands out as the most successful algorithm to solve the credit assignment problem in artificial neural networks [3, 4], which can be defined by the following question: How should a synaptic connection be modified in order to improve the global performance of the network to perform a task, as measured by some objective function? This is a difficult question since individual synapse may have a complicated influence on downstream processing. BP solves credit assignment through the chain rule of differentiation [1]. Although BP is efficiently implemented in software, it is difficult to conceive how BP could plausibly be implemented in biological systems. The problematic aspects are BP's use of symmetric connections and the need for two separate phases: A nonlinear forward pass that propagates neuronal activity and a linear backward pass that carries signed gradient signals [3]. These two types of processing are also inconvenient for training physical neural networks, since both should be handled by the same circuit, and explicitly propagating errors does not harness the device mismatches typical of neuromorphic hardware [5, 6]. Despite its implausibility, representations learned with BP match representations of in-vivo data [7] better than networks trained with purely

biologically-motivated learning rules such as STDP [8, 9]. This discrepancy raises the question as to whether and how neural dynamics could implement gradient-based credit assignment, and whether it could be as effective as BP to learn useful representations [3].

Equilibrium propagation (EP) [10] is an alternative algorithm for performing credit assignment in dynamical systems that converge to a fixed point, such as energy-based models [11]. EP also proceeds in two phases: In the first phase the dynamical system is presented with static input data until the units settle into an equilibrium or fixed point. We refer to this state as the free equilibrium. In a second phase, a teaching signal slightly nudges designated output units towards a target value until the dynamics settle into a second equilibrium that is called the nudged equilibrium. EP estimates loss gradients by comparing the neuronal activity between the two equilibria. EP is appealing because the resulting learning rule is spatially local when the energy function consists of two-body interactions, as for instance in continuous Hopfield networks [11]. Furthermore EP provably approximates the true gradient in the limit of vanishing nudging [10]. More generally, the implicit differentiation carried out by EP makes it suitable for meta learning [12], where explicitly backpropagating errors through an inner optimization loop becomes prohibitive due to the high memory requirement of storing intermediate time steps for regular automatic differentiation.

Nevertheless, classic EP [10, 13, 14] has several limitations. First, EP estimates only approach the actual loss gradient in the limit of a vanishing nudging or teaching signal. This requirement makes it impractical for noisy neuromorphic systems where noise can confound small amplitude teaching signals and also unrealistic as a model for learning in the brain where feedback strongly modulates processing. Moreover, the mechanisms by which biological circuits could satisfy the requirement for separate phases remains elusive. Finally, while EP can train deep networks on CIFAR10 [14], it has remained an open question whether it can be scaled up to larger and more complex tasks [4].

In this article, we show that by extending EP with holomorphic network dynamics it naturally estimates exact gradients for finite teaching signals. Mathematically, the exact gradients are encoded as a Fourier coefficient of adiabatic neural oscillations. This finding suggest a natural way of estimating the gradients online through suitable synaptic filtering operations which dispenses with the need for separate phases, in a similar spirit to Baldi and Pineda [15] for contrastive Hebbian learning [16]. We introduce holomorphic equilibrium propagation (holomorphic EP) and demonstrate that its tolerance to higher nudging amplitudes is conducive for training deeper network architectures allowing us to use it to train convolutional neural networks (CNNs) on challenging benchmark problems such as CIFAR100 and Imagenet 32×32 [17]. More specifically, our contributions are the following:

- We develop the theory of holomorphic EP and prove that this allows estimating exact gradients from finite teaching signal amplitudes. The gradient is encoded as the first Fourier coefficient of adiabatic oscillations that can be measured locally at synapses.

- We numerically quantify the accuracy of our estimate and show that it outperforms classic EP, especially in the presence of substrate noise and in deep neural networks.

- We demonstrate learning with an always-on oscillating teaching signal, thereby alleviating the need for separated phases.

- Finally, we show that holomorphic EP achieves the same performance as BP in deep CNNs trained on CIFAR10, CIFAR100 [18], and ImageNet 32×32 [17].

2 Background and previous work

Equilibrium propagation (EP).   EP [10] allows training convergent dynamical systems to optimize a loss function. We denote neuronal unit activity by the vector $\mathbf{s}$, and the learnable parameters such as weights and biases by $\boldsymbol{\theta}$ (Fig. 1a). The system's dynamics are given as the gradient of a scalar energy function $E(\boldsymbol{\theta}, \mathbf{s})$:

$$\frac{\mathrm{d}\mathbf{s}}{\mathrm{d}t} = -\frac{\partial E}{\partial \mathbf{s}}(\boldsymbol{\theta}, \mathbf{s}).$$ (1)

Figure 1: **a)** Schematic of the neuron model of a continuous Hopfield network [11] with holomorphic activation function σ. The neuron s_i receives input both from upstream and downstream neurons s_j plus a bias current b_i. **b)** Typical setup for supervised learning: The input $\mathbf{x}$ is clamped at a constant value, causing the network dynamics to settle into a fixed point. A complex-valued oscillating teaching signal enters at the output and causes neuronal activity to fluctuate around the fixed point.

As a consequence, EP can train any energy-based models, e.g., Hopfield networks [11] to perform classification [10, 13, 14]. In classic EP training proceeds in two phases. First, a subset of units are clamped to the input $\mathbf{x}$ and the system goes to a 'free' fixed point denoted by $\mathbf{s}_0^*$. Second, the loss function $\ell(\mathbf{y}, \boldsymbol{\theta}, \mathbf{s})$ scaled with a small positive nudging factor β is added to the energy function E which yields the total energy $F(\boldsymbol{\theta}, \mathbf{s}, \beta, \mathbf{y}) := E + \beta\ell(\boldsymbol{\theta}, \mathbf{s}, \mathbf{y})$. This addition corresponds to the teaching signal which causes the system to reach a second equilibrium $\mathbf{s}_\beta^*$, again by minimizing the total energy F. Although we write that ℓ takes all units $\mathbf{s}$ as argument, in practice typically only output units which encode the target label and thus serve as inputs for teaching signals are considered. The learning objective of the system is to optimize the loss function ℓ at the free fixed point, which is defined by $\mathcal{L}(\boldsymbol{\theta}, \mathbf{x}, \mathbf{y}) := \ell(\boldsymbol{\theta}, \mathbf{s}_0^*, \mathbf{y})$. Scellier and Bengio [10] showed that:

$$\lim_{\beta \to 0} \frac{1}{\beta} \left(\frac{\partial F}{\partial \boldsymbol{\theta}}(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta, \mathbf{y}) - \frac{\partial F}{\partial \boldsymbol{\theta}}(\boldsymbol{\theta}, \mathbf{s}_0^*, 0, \mathbf{y}) \right) = \frac{\mathrm{d}\mathcal{L}}{\mathrm{d}\boldsymbol{\theta}}. \tag{2}$$

This result requires F to be twice continuously differentiable and assumes that one can apply the implicit function theorem to the equilibrium equation $\partial_\mathbf{s} F(\boldsymbol{\theta}, \mathbf{s}_0^*, 0) = 0$ (the $\mathbf{y}$ arguments is thereafter omitted for clarity), so that $\beta \mapsto \mathbf{s}_\beta^*$ is a continuously differentiable map [10]. In practice, the left-hand side of Eq. (2) is estimated by finite differences [10, 13, 14, 19]. The appeal of EP for biological plausibility [3, 20] and neuromorphic hardware [15, 21–23] arises from the fact that (i) the system only needs to propagate neural activities (Fig. 1a) and (ii) in layered neural networks with a Hopfield energy [11] (Fig. 1b), the left-hand side of Eq. (2) can be computed by a Hebbian-like learning rule as the product of pre- and postsynaptic activity. In summary, EP implicitly propagates error signals through differences of neuronal activity during the two phases, whereas BP propagates error gradients explicitly [3, 20]. However, Eq. (2) only holds in the limit $\beta \to 0$ where activity differences vanish, which can pose a problem in the presence of noise or when activity differences vanish with network depth, which is related to the problem of vanishing gradients. In the following, we introduce holomorphic EP which avoids these issues by estimating exact gradients with finite β, and thus from finite amplitude teaching signals.

3 Theoretical results

Our main contribution is to show that if F is holomorphic, i.e., differentiable in the sense of complex variables, holomorphic EP computes the gradient of the objective function $\mathcal{L}$ for finite β, i.e., without requiring the vanishing nudging signals (cf. Eq. (2)). To accomplish this holomorphic EP requires a non-vanishing teaching signal that evolves 'adiabatically' in the complex plane with respect to the dynamics of the system (Fig. 1b). In other words, we require the dynamical system to relax to its equilibrium on a much shorter timescale than the timescale of the nudge.

Derivation of Holomorphic EP. To show that holomorphic EP yields an unbiased gradient through finite adiabatic nudging, we use the same notation as in Section 2. Specifically, we extend the theory by Scellier and Bengio [10] to the complex case and to dynamical systems, or networks whose scalar function governing the dynamics is holomorphic. In line with classic EP we assume that the dynamical system has a free fixed point as described above.

Theorem 1 (Holomorphic Equilibrium Propagation). *Let F be a scalar function governing the dynamics, so that the holomorphic implicit function theorem can be applied to the fixed point equation $\partial_\mathbf{s} F(\boldsymbol{\theta}, \mathbf{s}_0^*, 0) = 0$, then the gradient formula of equilibrium propagation (Eq. (2)) holds in the sense of complex differentiation.*

Proof. The proof is an extension of the one provided for the real nudging case [10]. The holomorphic implicit function theorem ensures that there exists an open set $U \in \mathbb{C}$ including 0 such that the implicit map $\beta \in U \mapsto \mathbf{s}_\beta^*$ is holomorphic on U. In particular, the fixed point $\mathbf{s}_\beta^*$ is defined on U (see Fig. 2b for how this area looks for a toy example). The proof proceeds in two steps. First we show that the total derivatives of F with respect to $\boldsymbol{\theta}$ and β can still be interchanged for complex variables by virtue of the Schwarz theorem. Second we show that, at the fixed point, the total derivative of F with respect to β ($\boldsymbol{\theta}$) is still equal to the partial derivatives with respect to β ($\boldsymbol{\theta}$). To that end, we apply the chain rule of complex differentiation in:

$$\frac{\mathrm{d}F}{\mathrm{d}\beta}(\boldsymbol{\theta}, \mathbf{s}_\beta, \beta) = \frac{\partial F}{\partial \beta}(\boldsymbol{\theta}, \mathbf{s}_\beta, \beta) + \frac{\partial F}{\partial \mathbf{s}_\beta} \cdot \frac{\partial \mathbf{s}_\beta}{\partial \beta}(\boldsymbol{\theta}, \mathbf{s}_\beta, \beta) + \frac{\partial F}{\partial \overline{\mathbf{s}}_\beta} \cdot \frac{\partial \overline{\mathbf{s}}_\beta}{\partial \beta}(\boldsymbol{\theta}, \mathbf{s}_\beta, \beta), \tag{3}$$

where $\overline{\mathbf{s}}$ denotes the complex conjugate of $\mathbf{s}$. At equilibrium, the second term on the right hand side cancels by definition of the fixed point, and the third term is zero because F is holomorphic, i.e., its derivative with respect to the conjugate variable is zero according to the Cauchy-Riemann condition [24]. The same argument holds for the derivative with respect to $\boldsymbol{\theta}$. Therefore, interchanging the total derivatives of F with respect to β and $\boldsymbol{\theta}$, and replacing the inner total derivatives by the partial derivatives, we obtain that the EP gradient formula (Eq. (2)) still holds, but for the differentiation with respect to a *complex* β:

$$\frac{\mathrm{d}}{\mathrm{d}\beta}\bigg|_{\beta=0} \left(\frac{\partial F}{\partial \boldsymbol{\theta}}(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta) \right) = \frac{\mathrm{d}}{\mathrm{d}\boldsymbol{\theta}} \frac{\partial F}{\partial \boldsymbol{\theta}}(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta) = \frac{\mathrm{d}\mathcal{L}}{\mathrm{d}\boldsymbol{\theta}}, \tag{4}$$

which concludes the proof (a more detailed version is in Appendix A.1). $\qquad\square$

In particular, the function $\beta \in U \mapsto \partial_{\boldsymbol{\theta}} F(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta)$, is also holomorphic by composition. The left hand side of Eq. (4) can thus be computed as the Cauchy integral [24] on an arbitrary closed path γ leading around zero once and counterclockwise in U:

$$\frac{\mathrm{d}}{\mathrm{d}\beta}\bigg|_{\beta=0} \left(\frac{\partial F}{\partial \boldsymbol{\theta}}(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta) \right) = \frac{1}{2\mathrm{i}\pi} \oint_\gamma \frac{1}{\beta^2} \frac{\partial F}{\partial \boldsymbol{\theta}}(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta) \mathrm{d}\beta, \tag{5}$$

where i denotes the imaginary unit. A natural choice for γ is a circle in the complex plane with radius $|\beta| > 0$ that we choose to parameterize with time $t \in [0, T] \mapsto \beta(t) = |\beta|e^{2\mathrm{i}\pi t/T}$, where T is the time needed for a full period. After the change of variable $\mathrm{d}\beta = (2\mathrm{i}\pi\beta/T)\mathrm{d}t$, the gradient is given by:

$$\frac{\mathrm{d}\mathcal{L}}{\mathrm{d}\boldsymbol{\theta}} = \frac{1}{T|\beta|} \int_0^T \frac{\partial F}{\partial \boldsymbol{\theta}} \left(\boldsymbol{\theta}, \mathbf{s}_{\beta(t)}^*, \beta(t) \right) e^{-2\mathrm{i}\pi t/T} \mathrm{d}t. \tag{6}$$

In conclusion, we have shown that introducing holomorphic dynamics allows to dispense with the requirement of vanishing teaching signal $|\beta| \to 0$ in the limit of 'adiabatic' nudging which corresponds to integrating over infinitely many fixed points with a *finite* $|\beta|$. Note, that complex-valued teaching signals $\beta \in \gamma$ produce fixed points in the complex plane, so that units take complex values. In particular, multi-layered neural networks (Fig. 1b) can be trained by using the continuous Hopfield dynamics [11]. The learnable parameters are the weights and biases $\boldsymbol{\theta} = (w_{ij}, b_i)$ and the total energy function F for optimizing the squared error loss is given by:

$$F(\boldsymbol{\theta}, \mathbf{s}, \beta, \mathbf{y}) = \frac{1}{2} \sum_i s_i^2 - \frac{1}{2} \sum_{i \neq j} w_{i,j} \sigma(s_i) \sigma(s_j) - \sum_i b_i \sigma(s_i) + \beta \sum_{i \in \text{output}} (s_i - y_i)^2. \tag{7}$$

If the activation function σ is holomorphic, which is true in the case of sigmoid functions, we can apply Eq. (6) to obtain:

$$-\frac{\mathrm{d}\mathcal{L}}{\mathrm{d}w_{ij}} = \frac{1}{T|\beta|} \int_0^T \sigma_i^*(t) \sigma_j^*(t) e^{-2\mathrm{i}\pi t/T} \mathrm{d}t, \tag{8}$$

where $\sigma_i^*(t) := \sigma(s_{i,\beta(t)}^*)$. Therefore, assuming a T-periodic teaching signal (Fig. 1b), the gradient is proportional to the first exponential Fourier coefficient of the product of the oscillating activities. Although this formulation assumes complex neuronal output, we show in Appendix A.2 that the gradient in Eq. (8) can be expressed in terms of the real part or imaginary part only. The complex teaching signal is therefore best thought of as a way to produce unbiased neuronal oscillations on the nudging timescale. In the next section, we numerically estimate the Fourier coefficient of Eq. (6) with a fixed number of points N on the circle which we use to train networks in the subsequent experiments and to compare it to the actual loss gradient computed with automatic differentiation.

Numerical estimation of the loss gradient as a Fourier coefficient. Next, we explain how to estimate the gradient from the corresponding Fourier coefficient (Eq. (6)). In practice, we use a Riemann sum to compute the integral numerically. To that end, we fix the nudging radius $|\beta| > 0$ such that the circular path lies in the domain U in which equilibria exist as described in Section 3. We sample the path with $N \geq 2$ nudging points $\{\beta_k := |\beta|e^{2i\pi k/N} \; ; \; k \in [0, ..., N-1]\}$, and define the estimator:

$$\hat{\nabla}(N) := \frac{1}{N|\beta|} \sum_{k=0}^{N-1} \frac{\partial F}{\partial \boldsymbol{\theta}} \left(\boldsymbol{\theta}, \mathbf{s}_{\beta_k}^*, \beta_k \right) e^{-2i\pi k/N}. \tag{9}$$

We have that $\hat{\nabla}(N) \xrightarrow[N \to \infty]{} \frac{\mathrm{d}\mathcal{L}}{\mathrm{d}\boldsymbol{\theta}}$, and the remaining bias term when using N points is:

$$\hat{\nabla}(N) - \frac{\mathrm{d}\mathcal{L}}{\mathrm{d}\boldsymbol{\theta}} = \sum_{\substack{p \equiv 0 \ (N)}}^{\infty} \frac{C_{p+1}|\beta|^p}{(p+1)!}, \tag{10}$$

where C_p is the p-th derivative in 0 of the function $\beta \mapsto \partial_{\boldsymbol{\theta}} F(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta)$ (see Appendix A.3 for the proof). The bias term in Eq. 10 converges to zero with increasing N because it is a sub-sum of the $(N+1)$-th order remainder of the series expansion of $\beta \mapsto \partial_{\boldsymbol{\theta}} F(\boldsymbol{\theta}, \mathbf{s}_\beta^*, \beta)$ in 0. The rate of convergence depends on the C_p coefficients and the radius $|\beta|$. In the case $N = 2$, the estimate of Eq. (9) coincides with the 'symmetric' estimate of Laborieux et al. [14]. However, the bias term on the right hand side of Eq. (10) is only valid when the dynamics are holomorphic. Next, we illustrate the approach in a toy experiment, and list three practical improvements brought by holomorphic EP.

4 Experiments

In all the experiments, we used the discrete setting of convergent recurrent neural networks of [13], and the readout scheme of [14] for optimizing the cross-entropy loss function with EP. All simulations were implemented in Jax [25] and Haiku [26] (Apache License 2.0). The datasets were obtained from the Tensorflow datasets library [27]. Our code is publicly available on GitHub [redacted]. The details of simulations and hyperparameters can be found in Appendix E and F.

Demonstration of Holomorphic Equilibrium Propagation in a toy experiment. To test how well the theoretical results of Section 3 hold in practice, we implemented a small-scale multi-layer perceptron with layer dimensions 6-4-4-4, including input and output layers. The activation function was a shifted sigmoid, which is holomorphic (see Appendix B). The network was fed with a randomly generated Gaussian input and a one-hot target. The dark blue region in Figure 2b shows the map of complex β for which the network settles to a fixed point after 200 time steps. We found experimentally that the area in the complex plane where stable fixed points exist strongly depends on the activation function and the weight initialization (see Appendix D). As β evolves on the circle of radius 0.1 ($N = 24$) hidden layer neurons settle into different equilibrium points in the complex plane (Fig. 2a). We observed that while the teaching signal $\beta = |\beta|e^{2i\pi t/T}$ was purely sinusoidal, the non-linearity of the network induces neural oscillations that are not purely sinusoidal. Nevertheless, the gradient is contained in the first mode of these non-linear oscillations (Fig. 2c).

To understand how the gradient is computed accurately when the magnitude of the teaching signal is increased, we recorded the adiabatic product of activities $\sigma_i^*(t)\sigma_j^*(t)$ for one pair of neurons (dark

Figure 2: Overview of holomorphic EP for a small multi-layer perceptron. **a)** Neural oscillations sampled at $N = 24$ points in the complex plane relative to the free fixed-point in the center (left, point sizes increasing with time). The corresponding real part values over two periods (right). **b)** Map of the euclidean norm between two consecutive steps of the dynamics in the complex plane spanned by β. The map describes the network's dynamical stability. Dark blue areas correspond to regions with associated stable fixed points. Light blue indicates lack of stability. **c)** Adiabatic correlations between two neurons for various values of $|\beta|$ (dark blue dots). Filtering the mode corresponding to the period T of teaching oscillations gives the light blue dots, the temporal mean of which (orange cross) is the gradient (grey plus sign). **d)** Cosine similarity with the true gradient of Holomorphic EP (orange), and classic EP [10] (blue). $\star$ corresponds to the teaching radius $|\beta|$ of the circular path in panel d). Holomorphic EP breaks down when the path passes through unstable (light) regions.

blue) over one teaching period and for increasing values of $|\beta|$ (Fig. 2c). In the case $|\beta| = 0.001$, the perturbation induced by the sinusoidal teaching signal is also purely sinusoidal, and the gradient magnitude is simply the radius of the circle. However, when $|\beta|$ is increased to 0.01, the linear approximation of the perturbation becomes less accurate, because higher powers of β become significant in the series expansion around the free fixed point. The gradient could still be well approximated by taking the mean of the two radii corresponding to real positive and negative β, as done by Laborieux et al. [14]. Increasing $|\beta|$ further to 0.1 and 0.5 yields an even more deformed perturbation, but the gradient is still correctly contained in the first Fourier coefficient of the perturbation. Holomorphic EP breaks down when β reaches amplitudes for which the corresponding path intersects with areas in which no stable equilibrium exists (cf. Fig. 2b, light areas). However, as we will see in the next sections, the finite teaching amplitudes are beneficial when the neuronal dynamics are subject to noise and when training deep neural networks.

Holomorphic EP can estimate the gradient in continuous time. Our theoretical findings allow us to revisit in a principled way an idea introduced by Baldi and Pineda [15] for a continuous-time-implementation of contrastive Hebbian learning [16] and learning rules looking to maximize slowness [28, 29]. In this context, the oscillating teaching signal is always-on, and the dynamical network is governed by three mechanisms acting on distinct timescales. The smallest timescale T_{dyn} is the typical time needed by the network to reach its fixed point. The second timescale is the period of one teaching oscillation T_{osc}, and the third timescale is the number of periods after which synaptic plasticity occurs T_{plas}. The gradient can be estimated online by:

$$\widetilde{\nabla}(T_{\text{plas}}) := -\frac{1}{T_{\text{plas}}|\beta|} \int_0^{T_{\text{plas}}} \sigma_i(t)\sigma_j(t)e^{-2\mathrm{i}\pi t/T_{\text{osc}}}\mathrm{d}t, \tag{11}$$

which converges to the gradient if $T_{\text{dyn}} \ll T_{\text{osc}} \ll T_{\text{plas}}$ (see Appendix A.4). This expression is similar to Eq. (5.2) in [15]. However their teaching signal oscillates discreetly between 0 and 1, and therefore produces a biased estimate of the gradient. To test the influence of the oscillation timescale

Figure 3: **a)** Cosine dissimilarity between the true gradient obtained with BP through time and the online estimate ($N = 10$) as a function of the number of oscillation periods. Different curves correspond to different oscillations periods, with darker colors meaning slower oscillations. **b)** Measure of the residual convergence of the network as a function of the oscillation period T_{osc}. **c)** Cosine similarity of holomorphic EP ($N = 15$) and classic EP with the true gradient as a function of the teaching amplitude $|\beta|$ in the presence of neuronal output noise. The network used in all three panels is a multi-layer perceptron with two hidden layers of 256 neurons each, fed with a minibatch of ten MNIST samples.

218 T_{osc} on the online estimate of Eq. (11), we compared the online estimation of the gradient over several
219 periods between several values of T_{osc}. To this end, we used a multi-layer perceptron with two hidden
220 layers with 256 units each, which we fed with a minibatch of MNIST data [30]. We observed that the
221 gradient could be accurately estimated in a few periods for high enough T_{osc} (Fig. 3a, dark curves).
222 However, when the oscillations were too fast, a non-vanishing bias remained in the gradient estimates
223 even for many periods (Fig. 3a, lighter curves). This bias is in all likelihood due to the inability of the
224 system to reach the fixed point (Fig. 3b). Finally, we found that given appropriate period timings,
225 holomorphic EP used in the online setting can train a network on MNIST (Table 1). Importantly, the
226 online formulation of holomorphic EP allows to dispense with the requirement of strictly separate
227 learning phases by replacing them with separate plasticity mechanisms acting on different timescales.

Table 1: MNIST training and validation errors for classic EP, Holomorphic EP, and online Holomorphic EP, with and without noise. All results are averages ($n = 3$) $\pm$ one standard deviation.

	Classic EP [10]		Holo. EP		Online Holo. EP	
Noise	Train (%)	Val (%)	Train (%)	Val (%)	Train (%)	Val. (%)
No	0.15 ± 0.03	2.25 ± 0.05	0.02 ± 0.01	1.97 ± 0.08	0.11 ± 0.01	2.05 ± 0.02
Yes	1.85 ± 0.06	3.09 ± 0.06	0.14 ± 0.03	1.96 ± 0.07	0.13 ± 0.03	1.91 ± 0.16

228 **Finite size teaching oscillations provide robustness to noise.** To analyze holomorphic EP's
229 robustness to noise, we injected a small zero-mean Gaussian input to each neuron in the network in
230 addition to the input from other neurons. We then used a single minibatch from the MNIST dataset to
231 compute gradient estimates using classic EP and holomorphic EP. The latter was computed by using
232 one realisation using $N = 15$ points, whereas the classic EP estimate was computed using the true
233 free fixed point ($\beta = 0$), and an average over N nudged fixed points to provide a fair comparison.
234 We found that for small β when noise amplitudes are comparable to the activity changes caused by
235 teaching oscillations the gradient estimate diverge from the true gradient of the noise-free system
236 (Fig. 3c). To some extent this effect could be mitigated by choosing a finite teaching signal ($\beta \gg 0$).
237 However, since β also increases the bias for classic EP this creates a trade-off between choosing
238 β either too small or too large. Importantly, even for the optimal choice of β, classic EP did not
239 accurately approximate the gradient of the noise-free system. In contrast, holomorphic EP thanks
240 to its robustness to finite teaching signals did provide an accurate estimate of the gradient despite
241 the noise. We verified that holomorphic EP is indeed more robust to noise than classic EP when
242 used to train the network (Table 1). Thus, holomorphic EP combined with finite teaching amplitudes
243 provides an effective way for training noisy computational substrates.

Figure 4: **a)** Cosine dissimilarity between holomorphic EP and the true gradient in a holomorphic (plain lines) seven-layer VGG-like CNN [31], and a non-holomorphic version using max pooling and ReLUs (dashed lines). Input data is a minibatch of ImageNet32 [17] consisting of 10 images. The left plot shows a comparison of the gradient with respect to the parameters of network's output layer. The right plot takes into account the gradient with respect to all network parameters. **b)** Cosine dissimilarity in function of N for three teaching amplitude values. Increasing N is only required for higher amplitudes. **c)** Average training error on CIFAR10. The average is calculated over three random initializations and error bars correspond to two standard deviations.

Table 2: Validation accuracy of BP and holomorphic EP. All values are averages ($n = 3$) $\pm$ stddev.

| | CIFAR10 | CIFAR100 | | ImageNet 32×32 | |
	Top-1 (%)	Top-1 (%)	Top-5 (%)	Top-1 (%)	Top-5 (%)
BP	88.3 ± 0.1	62.0 ± 0.5	86.2 ± 0.1	37.2 ± 0.4	60.9 ± 0.1
h-EP	88.6 ± 0.2	61.6 ± 0.1	86.0 ± 0.1	36.5 ± 0.3	60.8 ± 0.4

Holomorphic EP matches BP performance on large-scale vision benchmarks To test holomorphic EP's ability to train deep neural networks, we first investigated the influence of the number of fixed points N and the teaching amplitude $|\beta|$ on the approximating quality $\hat{\nabla}(N)$ of the loss gradient in a seven-layer VGG-like architecture ([31]; Fig. 4a,b). We ensured holomorphic dynamics by using softmax pooling layers [23] instead of the non-holomorphic max pooling, and by relying on sigmoid weighted linear units (dSiLU) [32] (see Appendix B) instead of standard ReLUs. We first considered a minibatch of ten images from the ImageNet 32×32 dataset [17] and computed the gradient using holomorphic EP as well as BP for reference. We found that the change to holomorphic dynamics already improved upon the gradient estimates used in previous work [14, 19]. Moreover, we observed that for the last layer increasing N only extended the range of usable teaching magnitudes $|\beta|$, but did not improve the quality of the gradient estimate. This phenomenon can be understood from Eq. (10), since higher N reduces the bias term considerably, which accommodates higher teaching magnitude $|\beta|$. However, larger amplitudes tended to improve the total gradient, particularly in deep layers where small teaching magnitudes were not enough to produce sufficient error signals (see Appendix C for details). Additionally, larger N were only required when using a higher teaching amplitude (Fig. 4b). Finally, we tested how the gradient quality impacts the network training accuracy on CIFAR10. We observed that the non-holomorphic VGG was unable to reach low training error (Fig. 4c), which is consistent with the poor gradient quality (Fig 4a). Changing to a holomorphic architecture with the same number of points resulted in a substantial improvement of training accuracy, which was further boosted when training with $N = 4$ consistent with our theory.

Finally, we wondered whether holomorphic EP could train deep neural networks on large-scale datasets, which has remained an open problem for most if not all alternative algorithms to BP [4]. To this end, we trained a five-layer CNN based on the VGG architecture [31] on multiple vision benchmarks including CIFAR10, CIFAR100 [18], and the 32×32 pixels version of ImageNet [17], which contains 1.2 million data points and 1000 classes like the full ILSVRC dataset [33]. In all cases we found that the validation accuracy reached by networks trained with BP and holomorphic EP using only two fixed points ($N = 2$) were identical within their uncertainties (Table 2). Note that the networks trained with BP were the feed-forward equivalent of the holomorphic networks used with

EP, but with ReLUs instead of dSiLU, which did not give satisfactory results. Thus, holomorphic EP permits training deep CNNs on ImageNet 32×32 to comparable performance levels as standard BP.

5 Discussion

We have introduced holomorphic EP which extends classic EP in that it computes exact loss gradients when integrating over finite size adiabatic neuronal oscillations caused by a teaching signal (Section 3). Importantly, such integration can be accomplished online with purely local learning rules which makes it an exciting theoretical framework for studying learning in the brain where oscillations are ubiquitously observed [34, 35]. In practice we found that numerically evaluating a small number of points during one oscillation cycle provides an excellent gradient approximation that outperforms classic EP and thanks to the finite oscillation amplitude is robust to noise which is an advantage for training neuromorphic hardware systems [21, 22, 36]. Additionally, the possibility of using finite teaching signals is conducive for training deep CNNs, where infinitesimal teaching signals as used by classic EP may vanish (Section 4).

A body of previous work has attempted to reconcile BP with neurobiology [3, 37]. EP is most closely related to classic theories of predictive coding (PC) [38–44] which similarly assumes convergent network dynamics cast into an energy minimization problem. PC further assumes that errors are encoded in neuronal dynamics, dedicated dendritic compartments, or separate temporal phases [20, 39, 45, 46]. In a similar vein, Target Propagation (TP) [47–49] assumes locally encoded error signals which in some cases are obtained by iterating approximate inverses, a property reminiscent of EP [50–52] which comes with theoretical guarantees [53]. However, all previous EP studies and most of the works above, with two notable exceptions [37, 49], were all limited to small-scale problems [4]. In contrast, we demonstrate in this article that holomorphic EP scales to ImageNet32.

While the ability to run holomorphic EP online makes it an appealing model for credit assignment in biological neural networks, this interpretation has several notable shortcomings. First, holomorphic EP requires complex-valued neuronal outputs which hampers a direct comparison to neurobiology. However, complex outputs have a long-standing tradition in computational neuroscience where they appear in complex variations of Hopfield networks [54–56], in the framework of theta neurons [57], and phasor networks [58] where they capture oscillatory neuronal dynamics with respect to a reference oscillation. It is conceivable that holomorphic EP can be interpreted within such a framework, however, establishing formal equivalences will require future work. Importantly, holomorphic EP is notably different from the above studies in that the complex values are only required to compute a real-valued gradient. To the best of our knowledge, this is the first use of complex numbers in the context of credit assignment. As a direct consequence, holomorphic EP requires a holomorphic dynamical system which precludes the use of max pooling and ReLUs. However, we found that holomorphic alternatives exists which empirically yield comparable performance. Like other algorithms holomorphic EP requires symmetric synaptic connectivity between layers which seems biologically implausible. While theoretical guarantees for exact gradient computation are lost without strict symmetry [59], it may not be required for learning [60–62]. Alternatively, symmetry may be acquired through plastic feedback connections [63, 64]. Although our approach neither uses time-varying input nor neuronal spiking dynamics, spiking extensions to EP have been proposed [65, 66]. However, applying our theory to time varying data will likely require novel theoretical concepts [67] and establishing links to present spike-based approaches [37, 68–70].

Our work augments classic EP with desirable properties for potential neuromorphic applications, which promise power-efficient and equitable artificial intelligence (AI) at the edge and in IoT devices [71–73]. As exciting as such developments are, they also risk negative societal impacts, e.g., through mass surveillance or allowing AI systems with potentially discriminatory biases to permeate our everyday lives further. A transparent research strategy and taking into account ethical considerations early during product design will be essential to avoid such adverse outcomes. On the upside, our theoretical work further consolidates EP as a conceptual framework for understanding the brain, a fundamental requirement to inform future biomedical research targeted at nervous system disorders.

References

[1] David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning representations by back-propagating errors. *nature*, 323(6088):533–536, 1986.

[2] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[3] Timothy P Lillicrap, Adam Santoro, Luke Marris, Colin J Akerman, and Geoffrey Hinton. Backpropagation and the brain. *Nature Reviews Neuroscience*, 21(6):335–346, 2020.

[4] Sergey Bartunov, Adam Santoro, Blake Richards, Luke Marris, Geoffrey E Hinton, and Timothy Lillicrap. Assessing the scalability of biologically-motivated deep learning algorithms and architectures. *Advances in neural information processing systems*, 31, 2018.

[5] Pritish Narayanan, Alessandro Fumarola, Lucas L Sanches, Kohji Hosokawa, Scott C Lewis, Robert M Shelby, and Geoffrey W Burr. Toward on-chip acceleration of the backpropagation algorithm using nonvolatile memory. *IBM Journal of Research and Development*, 61(4/5):11–1, 2017.

[6] Stefano Ambrogio, Pritish Narayanan, Hsinyu Tsai, Robert M Shelby, Irem Boybat, Carmelo Di Nolfo, Severin Sidler, Massimo Giordano, Martina Bodini, Nathan CP Farinha, et al. Equivalent-accuracy accelerated neural-network training using analogue memory. *Nature*, 558(7708):60–67, 2018.

[7] Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the national academy of sciences*, 111(23):8619–8624, 2014.

[8] Yang Dan and Mu-ming Poo. Spike timing-dependent plasticity of neural circuits. *Neuron*, 44 (1):23–30, 2004.

[9] Amirhossein Tavanaei, Masoud Ghodrati, Saeed Reza Kheradpisheh, Timothée Masquelier, and Anthony Maida. Deep learning in spiking neural networks. *Neural networks*, 111:47–63, 2019.

[10] Benjamin Scellier and Yoshua Bengio. Equilibrium propagation: Bridging the gap between energy-based models and backpropagation. *Frontiers in computational neuroscience*, 11:24, 2017.

[11] John J Hopfield. Neurons with graded response have collective computational properties like those of two-state neurons. *Proceedings of the national academy of sciences*, 81(10):3088–3092, 1984.

[12] Nicolas Zucchet, Simon Schug, Johannes von Oswald, Dominic Zhao, and João Sacramento. A contrastive rule for meta-learning. *arXiv preprint arXiv:2104.01677*, 2021.

[13] Maxence Ernoult, Julie Grollier, Damien Querlioz, Yoshua Bengio, and Benjamin Scellier. Updates of equilibrium prop match gradients of backprop through time in an rnn with static input. *Advances in neural information processing systems*, 32, 2019.

[14] Axel Laborieux, Maxence Ernoult, Benjamin Scellier, Yoshua Bengio, Julie Grollier, and Damien Querlioz. Scaling equilibrium propagation to deep convnets by drastically reducing its gradient estimator bias. *Frontiers in neuroscience*, 15:129, 2021.

[15] Pierre Baldi and Fernando Pineda. Contrastive learning and neural oscillations. *Neural computation*, 3(4):526–545, 1991.

[16] Javier R Movellan. Contrastive hebbian learning in the continuous hopfield model. In *Connectionist models*, pages 10–17. Elsevier, 1991.

[17] Patryk Chrabaszcz, Ilya Loshchilov, and Frank Hutter. A downsampled variant of imagenet as an alternative to the cifar datasets. *arXiv preprint arXiv:1707.08819*, 2017.

[18] Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

[19] Artur Luczak, Bruce L McNaughton, and Yoshimasa Kubo. Neurons learn by predicting future activity. *Nature Machine Intelligence*, pages 1–11, 2022.

[20] James CR Whittington and Rafal Bogacz. Theories of error back-propagation in the brain. *Trends in cognitive sciences*, 23(3):235–250, 2019.

[21] Jack Kendall, Ross Pantone, Kalpana Manickavasagam, Yoshua Bengio, and Benjamin Scellier. Training end-to-end analog neural networks with equilibrium propagation. *arXiv preprint arXiv:2006.01981*, 2020.

[22] Gianluca Zoppo, Francesco Marrone, and Fernando Corinto. Equilibrium propagation for memristor-based recurrent neural networks. *Frontiers in neuroscience*, 14:240, 2020.

[23] A Stergiou, R Poppe, and G Kalliatakis. Refining activation downsampling with softpool. arxiv 2021. *arXiv preprint arXiv:2101.00440*.

[24] Walter Appel. Mathematics for physics and physicists. 2007.

[25] James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL `http://github.com/google/jax`.

[26] Tom Hennigan, Trevor Cai, Tamara Norman, and Igor Babuschkin. Haiku: Sonnet for JAX, 2020. URL `http://github.com/deepmind/dm-haiku`.

[27] Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL `http://tensorflow.org/`. Software available from tensorflow.org.

[28] Manu Srinath Halvagal and Friedemann Zenke. The combination of hebbian and predictive plasticity learns invariant object representations in deep sensory networks. *bioRxiv*, 2022.

[29] Laurenz Wiskott and Terrence J Sejnowski. Slow feature analysis: Unsupervised learning of invariances. *Neural computation*, 14(4):715–770, 2002.

[30] Li Deng. The mnist database of handwritten digit images for machine learning research. *IEEE Signal Processing Magazine*, 29(6):141–142, 2012.

[31] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[32] Stefan Elfwing, Eiji Uchibe, and Kenji Doya. Sigmoid-weighted linear units for neural network function approximation in reinforcement learning. *Neural Networks*, 107:3–11, 2018.

[33] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

[34] Juergen Fell and Nikolai Axmacher. The role of phase synchronization in memory processes. *Nature reviews neuroscience*, 12(2):105–118, 2011.

[35] Andreas K Engel, Pascal Fries, and Wolf Singer. Dynamic predictions: oscillations and synchrony in top–down processing. *Nature Reviews Neuroscience*, 2(10):704–716, 2001.

[36] Menachem Stern, Daniel Hexner, Jason W Rocks, and Andrea J Liu. Supervised learning in physical networks: From machine learning to learning machines. *Physical Review X*, 11(2): 021045, 2021.

[37] Alexandre Payeur, Jordan Guerguiev, Friedemann Zenke, Blake A Richards, and Richard Naud. Burst-dependent synaptic plasticity can coordinate learning in hierarchical circuits. *Nature neuroscience*, 24(7):1010–1019, 2021.

[38] Rajesh PN Rao and Dana H Ballard. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. *Nature neuroscience*, 2(1):79–87, 1999.

[39] Georg B Keller and Thomas D Mrsic-Flogel. Predictive processing: a canonical cortical computation. *Neuron*, 100(2):424–435, 2018.

[40] Yanping Huang and Rajesh PN Rao. Predictive coding. *Wiley Interdisciplinary Reviews: Cognitive Science*, 2(5):580–593, 2011.

[41] James CR Whittington and Rafal Bogacz. An approximation of the error backpropagation algorithm in a predictive coding network with local hebbian synaptic plasticity. *Neural computation*, 29(5):1229–1262, 2017.

[42] Beren Millidge, Alexander Tschantz, and Christopher L Buckley. Predictive coding approximates backprop along arbitrary computation graphs. *arXiv preprint arXiv:2006.04182*, 2020.

[43] Robert Rosenbaum. On the relationship between predictive coding and backpropagation. *Plos one*, 17(3):e0266102, 2022.

[44] Karl Friston. The free-energy principle: a unified brain theory? *Nature reviews neuroscience*, 11(2):127–138, 2010.

[45] João Sacramento, Rui Ponte Costa, Yoshua Bengio, and Walter Senn. Dendritic cortical microcircuits approximate the backpropagation algorithm. *Advances in neural information processing systems*, 31, 2018.

[46] Paul Haider, Benjamin Ellenberger, Laura Kriener, Jakob Jordan, Walter Senn, and Mihai A Petrovici. Latent equilibrium: Arbitrarily fast computation with arbitrarily slow neurons. *Advances in Neural Information Processing Systems*, 34:17839–17851, 2021.

[47] Yoshua Bengio. How auto-encoders could provide credit assignment in deep networks via target propagation. *arXiv preprint arXiv:1407.7906*, 2014.

[48] Dong-Hyun Lee, Saizheng Zhang, Asja Fischer, and Yoshua Bengio. Difference target propagation. In *Joint european conference on machine learning and knowledge discovery in databases*, pages 498–515. Springer, 2015.

[49] Maxence Ernoult, Fabrice Normandin, Abhinav Moudgil, Sean Spinney, Eugene Belilovsky, Irina Rish, Blake Richards, and Yoshua Bengio. Towards scaling difference target propagation by learning backprop targets. *arXiv preprint arXiv:2201.13415*, 2022.

[50] Nasir Ahmad, Marcel A van Gerven, and Luca Ambrogioni. Gait-prop: A biologically plausible learning rule derived from backpropagation of error. *Advances in Neural Information Processing Systems*, 33:10913–10923, 2020.

[51] Bill Podlaski and Christian K Machens. Biological credit assignment through dynamic inversion of feedforward networks. *Advances in Neural Information Processing Systems*, 33:10065–10076, 2020.

[52] Yoshua Bengio. Deriving differential target propagation from iterating approximate inverses. *arXiv preprint arXiv:2007.15139*, 2020.

[53] Alexander Meulemans, Francesco Carzaniga, Johan Suykens, João Sacramento, and Benjamin F Grewe. A theoretical framework for target propagation. *Advances in Neural Information Processing Systems*, 33:20024–20036, 2020.

[54] Akira Hirose. Dynamics of fully complex-valued neural networks. *Electronics letters*, 28(16): 1492–1494, 1992.

[55] Stanislaw Jankowski, Andrzej Lozowski, and Jacek M Zurada. Complex-valued multistate neural associative memory. *IEEE Transactions on neural networks*, 7(6):1491–1496, 1996.

[56] E Paxon Frady and Friedrich T Sommer. Robust computation with rhythmic spike patterns. *Proceedings of the National Academy of Sciences*, 116(36):18050–18059, 2019.

[57] G Bard Ermentrout and Nancy Kopell. Parabolic bursting in an excitable system coupled with a slow oscillation. *SIAM journal on applied mathematics*, 46(2):233–253, 1986.

[58] Connor Bybee, E Paxon Frady, and Friedrich T Sommer. Deep learning in spiking phasor neural networks. *arXiv preprint arXiv:2204.00507*, 2022.

[59] Benjamin Scellier, Anirudh Goyal, Jonathan Binas, Thomas Mesnard, and Yoshua Bengio. Generalization of equilibrium propagation to vector field dynamics. *arXiv preprint arXiv:1808.04873*, 2018.

[60] Timothy P Lillicrap, Daniel Cownden, Douglas B Tweed, and Colin J Akerman. Random synaptic feedback weights support error backpropagation for deep learning. *Nature communications*, 7(1):1–10, 2016.

[61] Julien Launay, Iacopo Poli, François Boniface, and Florent Krzakala. Direct feedback alignment scales to modern deep learning tasks and architectures. *Advances in neural information processing systems*, 33:9346–9360, 2020.

[62] Arild Nøkland. Direct feedback alignment provides learning in deep neural networks. *Advances in neural information processing systems*, 29, 2016.

[63] Mohamed Akrout, Collin Wilson, Peter Humphreys, Timothy Lillicrap, and Douglas B Tweed. Deep learning without weight transport. *Advances in neural information processing systems*, 32, 2019.

[64] Yali Amit. Deep learning with asymmetric connections and hebbian updates. *Frontiers in computational neuroscience*, 13:18, 2019.

[65] Peter O'Connor, Efstratios Gavves, and Max Welling. Training a spiking neural network with equilibrium propagation. In *The 22nd international conference on artificial intelligence and statistics*, pages 1516–1523. PMLR, 2019.

[66] Erwann Martin, Maxence Ernoult, Jérémie Laydevant, Shuai Li, Damien Querlioz, Teodora Petrisor, and Julie Grollier. Eqspike: spike-driven equilibrium propagation for neuromorphic implementations. *Iscience*, 24(3):102222, 2021.

[67] Jack Kendall. A gradient estimator for time-varying electrical networks with non-linear dissipation. *arXiv preprint arXiv:2103.05636*, 2021.

[68] Friedemann Zenke and Surya Ganguli. Superspike: Supervised learning in multilayer spiking neural networks. *Neural computation*, 30(6):1514–1541, 2018.

[69] Guillaume Bellec, Franz Scherr, Anand Subramoney, Elias Hajek, Darjan Salaj, Robert Legenstein, and Wolfgang Maass. A solution to the learning dilemma for recurrent networks of spiking neurons. *Nature communications*, 11(1):1–15, 2020.

[70] Jacques Kaiser, Hesham Mostafa, and Emre Neftci. Synaptic plasticity dynamics for deep continuous local learning (decolle). *Frontiers in Neuroscience*, 14:424, 2020.

[71] Carver Mead. Neuromorphic electronic systems. *Proceedings of the IEEE*, 78(10):1629–1636, 1990.

[72] Giacomo Indiveri, Bernabé Linares-Barranco, Tara Julia Hamilton, André van Schaik, Ralph Etienne-Cummings, Tobi Delbruck, Shih-Chii Liu, Piotr Dudek, Philipp Häfliger, Sylvie Renaud, et al. Neuromorphic silicon neuron circuits. *Frontiers in neuroscience*, 5:73, 2011.

[73] Catherine D Schuman, Thomas E Potok, Robert M Patton, J Douglas Birdwell, Mark E Dean, Garrett S Rose, and James S Plank. A survey of neuromorphic computing and neural networks in hardware. *arXiv preprint arXiv:1705.06963*, 2017.