When the Sun Goes Down: Repairing Photometric Losses for All-Day Depth Estimation

Abstract: Self-supervised deep learning methods for joint depth and ego-motion estimation can yield accurate trajectories without needing ground-truth training data. However, as they typically use photometric losses, their performance can degrade significantly when the assumptions these losses make (e.g. temporal illumination consistency, a static scene, and the absence of noise and occlusions) are violated. This limits their use for e.g. nighttime sequences, which tend to contain many point light sources (including on dynamic objects) and low signal-to-noise ratio (SNR) in darker image regions. In this paper, we show how to use a combination of three techniques to allow the existing photometric losses to work for both day and nighttime images. First, we introduce a per-pixel neural intensity transformation to compensate for the light changes that occur between successive frames. Second, we predict a per-pixel residual flow map that we use to correct the reprojection correspondences induced by the estimated ego-motion and depth from the networks. And third, we denoise the training images to improve the robustness and accuracy of our approach. These changes allow us to train a single model for both day and nighttime images without needing separate encoders or extra feature networks like existing methods. We perform extensive experiments and ablation studies on the challenging Oxford RobotCar dataset to demonstrate the efficacy of our approach for both day and nighttime sequences.

1 Introduction

An ability to capture 3D scene structure is crucial for many applications, including autonomous driving [1], robotic manipulation [2], and augmented reality [3]. Many methods use LiDAR or fixed-baseline stereo to acquire the depth needed to reconstruct a scene, but researchers have also long been interested in estimating depth from monocular images, driven by the ubiquity, low cost, low power consumption and ease of deployment of monocular cameras. By contrast, LiDAR can be power-hungry, and stereo rigs must be calibrated and time-synchronised to achieve good performance.

Multi-view monocular depth estimation approaches have long used variable-baseline stereo over multiple images to recover depth [4, 5]. Meanwhile, progress in deep learning has opened up the additional possibility of estimating depth from a single monocular image. Deep learning methods for depth estimation can be broadly divided into two types, namely supervised methods [6, 7], and self/unsupervised methods [8, 9, 10]. Typically, supervised approaches have achieved very good results for the dataset(s) on which they are trained, but their need for ground-truth information during training has often hindered their deployment in new domains.

By contrast, self/unsupervised methods have typically adopted the use of a geometry-based loss function, inspired by the strong physical principles of traditional methods [11, 12]. This loss function is commonly referred to as the photometric or appearance loss, and is based on the assumptions that (i) the scene is static (i.e. contains no moving objects), (ii) the illumination in the scene is diffusive (i.e. there are no specular reflections) and temporally consistent (i.e. the pixels to which any scene

Submitted to the 6th Conference on Robot Learning (CoRL 2022). Do not distribute.

Figure 1: (a) The challenges posed by night-time images: (1) low visibility and noise (patch enhanced for better readability); (2) moving light sources with saturating image regions; (3) point light sources; (4) extreme motion blur. (b) Despite these adverse conditions, which violate the assumptions made by the photometric loss, our method can successfully estimate accurate depth maps.

point projects in any two consecutive frames have the same intensity), and (iii) the images are free of noise and occlusions [11, 12, 13, 14]. In practice, many of these assumptions are at least partly false, which can lead to errors in the estimated depth: scenes are quite likely to contain dynamic objects (e.g. cars, cyclists and pedestrians, in an outdoor driving scenario), surface materials are rarely fully diffusive, and occlusions are common. During the day, it is somewhat reasonable to assume that the illumination is moderately temporally consistent for image sequences captured outdoors, as the sun is by far the dominant light source in that case, and the light it casts changes only slowly over time; however, at night, the numerous point light sources that are typically turned on after dark (e.g. car headlights, lamp posts, etc.) can cause the illumination to change drastically from one frame to the next. At night, also, the motion blur associated with the movement of dynamic objects in the scene (including the ego-vehicle) becomes worse, owing to the longer exposure times typically used when capturing night-time images [15, 16], and the signal-to-noise ratio of the (darker) images becomes much lower than it would be during daytime. Such issues, as illustrated in Figure 1, inhibit the straightforward use of deep networks based on photometric loss for night-time sequences.

In this paper, we address this problem by directly targeting violations of the temporal illumination consistency, static scene and noise-free assumptions on which the photometric loss relies. As shown by our day and night results in Table 1, these three together account for much of the discrepancy in performance between daytime and night-time. A lack of temporal illumination consistency caused by point light sources in the scene can cause pixels to be incorrectly matched between consecutive frames. To rectify this, we propose a novel per-pixel neural intensity transformation that learns to compensate for these light sources (see §3.2). Whilst conceptually straightforward, this approach is surprisingly effective, as our results in §4 demonstrate. Interestingly, they also show that it is able to operate well over wide (motion parallax) baselines, allowing us to leverage the better depth estimation performance that wider baselines offer. To correct for dynamic objects in the scene, as well as motion blur, we predict a per-pixel residual flow map (see §3.3) that we use to correct the reprojection correspondences induced by the estimated ego-motion and depth from the networks. This improves depth estimation performance at any time of day (see §4), but has additional theoretical benefits for night-time sequences because of the greater motion blur from which they typically suffer. Lastly, we robustify our approach against noise by incorporating Neighbour2Neighbour [17], a state-of-the-art denoising module, in our photometric loss formulation (see §3.4).

2   Related Work

Estimating depth from images has a long history in computer vision. Several methods use either stereo images [18, 19, 20], or two or more images taken from different viewing angles [21, 22, 23]. We try to solve this problem using a single monocular image, without any constraints on the scene of interest. Various methods have addressed this problem using supervised learning [6, 7, 24, 25, 26]. However, it is infeasible to have ground-truth depth maps for training on every scene, which limits the application of these methods and helps motivate unsupervised solutions to this problem.

Figure 2: The architecture of our proposed method (see §3 for details).

Unsupervised Methods: Garg et al. [8] proposed a geometry-based loss function to train a network in a completely unsupervised fashion using a pair of stereo images. Monodepth [27] improved this by using differentiable image warping [28] and structural similarity-based [29] image comparison loss. SfMLearner [30] used only monocular images to jointly learn depth and ego-motion. It was further improved by combining stereo and monocular losses in [31, 32]. Later, GeoNet [33] and EPC [34] learnt per-pixel optical flow maps along with depth and ego-motion to mitigate the effect of moving objects. Some methods use GAN-based learning to train their systems [10, 35, 36]. Recently, Monodepth2 [37] extended Monodepth to the temporal domain, proposing a few architectural changes and robust loss functions to achieve state-of-the-art results. HR-Depth [38] used an effective skip connection and a convolution block to integrate spatial and semantic information. SD-SSMDE [39] introduced a two-stage training strategy to improve scale and inter-frame scale consistency in depth by utilising depth estimation from the first stage as a pseudo-label. Based on channel-wise attention, CADepth-Net [40] proposed structure perception and detail emphasis modules for capturing the context of scenes with the detail for the depth estimation. RM-Depth [41] proposed recurrent modulation units for an effective fusion of deep features with fewer parameters, and a warping-based motion field for moving objects to improve the scene rigidity, leading to enhanced depth estimation. More broadly, recent years have also seen a wide range of other advances in depth estimation, e.g. changes to the network architecture [42], the addition of extra loss functions [43], and better handling of dynamic objects [44]. However, all of these methods have been tested on standard daytime datasets, whereas our method is designed to work at night as well.

Nighttime Methods: All the methods above are trained using photometric loss as the main supervision signal, and with an assumption of temporal illumination consistency, which is not valid at night. A few methods such as DeFeat-Net [45], ADFA [46] and [14] have explored how to estimate depth information from nighttime RGB images. DeFeat-Net [45] learns n-dimensional deep feature representations (assumed to be illumination-invariant) using a pixel-wise contrastive loss. The feature maps are simultaneously used along with the images for photometric loss calculation during training. ADFA [36] mimics a daytime depth estimation model by learning a new encoder that can generate 'day-like' features from nighttime images using a domain adaptation approach. Instead of feature translation as in [46], the authors in [14] propose a joint network for image translation and stereo image-based depth estimation. Recently, photometric losses are again used with an image enhancement module and a GAN based depth regulariser in [47]. Liu et al. [48] divided the day and nighttime images into view-invariant and variant feature maps using separate encoders, and used the view-invariant information for depth estimation. All these methods either need two separate encoders for day and nighttime images [46, 48, 47], or need to learn an illumination-invariant fea-

110 ture space [45]. By contrast, our proposed method learns in a completely self-supervised fashion,
111 without needing stereo images, ground-truth depth information or any additional feature learning.

3 Method

3.1 Baseline Method

114 We first recap the core tenets of existing photometric loss methods, which typically use two net-
115 works, a depth network (or *DepthNet*) and a motion network (or *MotionNet*). The *DepthNet* takes
116 an individual colour image as input, and is used to predict a depth image D_t for each colour image
117 I_t in the input sequence. The *MotionNet* takes a consecutive pair of images I_t and I_{t+1} as input,
118 and is used to output the ego-motion $T_{t,t+1}$ of the camera between them. The estimated depth and
119 ego-motion can be used to reproject a pixel $\mathbf{u} = [u, v]^\top$ in frame I_t into I_{t+1}, the subsequent frame
120 in the sequence, via $\dot{V}_t(\mathbf{u}) = KT_{t,t+1}D_t(\mathbf{u})K^{-1}\dot{\mathbf{u}}$, in which $\dot{\mathbf{u}}$ denotes the homogeneous form of
121 $\mathbf{u}$, $K \in \mathbb{R}^{3\times3}$ encodes the camera intrinsics, and $\dot{V}_t(\mathbf{u}) \in \mathbb{R}^3$ denotes the homogeneous form of
122 $V_t(\mathbf{u}) \in \mathbb{R}^2$, a 2D point in the image plane of I_{t+1} (which may or may not lie within the bounds of
123 the actual image). This can be used to reconstruct an image I'_t by sampling from I_{t+1} around the
124 reprojected points, using bilinear interpolation [28] to achieve a smoother result. Formally,

$$I'_t(\mathbf{u}) = \begin{cases} \text{interpolate}(I_{t+1}, V_t(\mathbf{u})) & \text{if } \mathbf{u} \in M_t \\ \mathbf{0} & \text{otherwise,} \end{cases} \tag{1}$$

125 in which $M_t = \{\mathbf{u} : \rho(V_t(\mathbf{u})) \in \Omega(I_{t+1})\}$ is the set of pixels whose reprojections into I_{t+1}, when
126 rounded to the nearest pixel using ρ, fall within the image bounds $\Omega(I_{t+1})$. The reconstructed image
127 I'_t can then be compared to the original image I_t to calculate the loss values needed for training. The
128 loss we target, namely *photometric loss*, has been used by many recent deep learning-based depth
129 estimation techniques [8, 31, 30, 36]. It is normally calculated as a convex combination of pixel-wise
130 difference and single-scale structural dissimilarity (SSIM) [29], via

$$L_p^{(t)} = \frac{1}{|M_t|} \sum_{\mathbf{u}\in M_t} \left(\alpha \frac{1-SSIM(I_t(\mathbf{u}),I'_t(\mathbf{u}))}{2} + (1-\alpha)\left|I_t(\mathbf{u}) - I'_t(\mathbf{u})\right| \right). \tag{2}$$

131 Most existing unsupervised methods (e.g. [30, 31, 37, 42]) use this as the backbone of their formu-
132 lation. To ensure a fair comparison with current night-time state-of-the-art methods [45, 48, 47], we
133 base our modifications in this paper on Monodepth2 [37], a commonly used baseline.

3.2 Lighting Change Compensation

135 The numerous point light sources that are typically turned on after dark (e.g. car headlights, lamp
136 posts, etc.) can cause the illumination of a scene to change significantly from frame I_t to frame I_{t+1}.
137 A problematic special case occurs when a light source moves with the camera (e.g. car headlights),
138 which can lead to large holes in the estimated depth directly in front of the ego-vehicle [45, 48]. In
139 our approach, we compensate for the illumination changes by estimating a per-pixel transformation
140 that, when applied to I_{t+1}, can mitigate the changes in lighting that have occurred since I_t. We
141 draw some inspiration from [49, 50, 51], which use a single whole-image transformation based on
142 two scalar values to compensate for the difference in exposure time between a pair of images, based
143 on the observation that such a difference creates approximately uniform intensity changes over the
144 entire image. However, in our case, the intensity changes are far from uniform over the image, owing
145 to both the motions of the ego-vehicle and other objects in the scene, and the distances between the
146 ego-vehicle and static point light sources. For this reason, we propose a per-pixel formulation here.

147 Our approach starts by passing the features produced by the last convolutional layer of the *Motion-
148 Net* through a *lighting change decoder* to estimate two per-pixel change images, C_t and B_t (see
149 Figure 2). These (respectively) aim to capture the per-pixel changes in contrast (scale) and bright-
150 ness (shift) that have occurred between the two input frames. As shown in Figure 4, the brightness
151 image B_t broadly captures the extra light added to the image by e.g. vehicle headlights, and the con-
152 trast image C_t broadly captures the changes in ambient light due to the motion of the ego-vehicle

towards or away from point light sources such as street lamps. We use these images to transform the reconstructed image I'_t via $\tilde{I}_t = C_t \odot I'_t + B_t$, in which $\odot$ denotes the Hadamard product.

3.3 Motion Compensation

As seen in §3.1, the standard photometric loss makes use of correspondences between consecutive frames that have been established via reprojection, based on the ego-motion and depth estimated by the networks. Assuming that (i) the ego-motion and depth have been estimated well, (ii) the scene is static, and (iii) there is minimal motion blur, the correspondences established in this way will broadly match those that would have been established had we used the ground truth optic flow $\Phi_t(\cdot)$ from frame t to frame $t + 1$. However, if objects move with respect to the background scene, or anything visible in the image moves with respect to the ego-camera (which can cause motion blur), then the reprojection correspondences may be incorrect. To correct for these errors, we predict a residual flow map R_t, such that for each pixel $\mathbf{u} \in \Omega(I_t)$, $R_t(\mathbf{u}) \in \mathbb{R}^2$ is an estimate of $(\mathbf{u} + \Phi_t(\mathbf{u})) - V_t(\mathbf{u})$, the 2D offset from the reprojection correspondence of $\mathbf{u}$, namely $V_t(\mathbf{u})$, to its ground truth correspondence in frame $t + 1$, namely $\mathbf{u} + \Phi_t(\mathbf{u})$. We can then add $R_t(\mathbf{u})$ to $V_t(\mathbf{u})$ for each pixel $\mathbf{u}$ to obtain a potentially more accurate correspondence for use in reconstructing I'_t via Equation 1.

Some methods [34, 33, 44] already exist that predict residual flow for daytime images. By contrast, we avoid using a separate encoder-decoder network or computationally-intensive image warping-based bilinear interpolation for supervision. Instead, we estimate residual flow using an efficient sparsity-based formulation. This involves introducing a *residual flow decoder* that takes the features of the final convolutional layer of the *MotionNet* as input and the features of previous layers in the *MotionNet* via skip connections, and outputs residual flow maps $\{R_{t,s} : s \in \{0, 1, 2, 3\}\}$ at four different scales (each $R_{t,s}$ has a width and height that is $1/2^s$ that of I_t, and $R_{t,0} \equiv R_t$).

There is no direct supervision available to learn the residual flow maps. For this reason, we choose instead to encourage sparsity in the residual flow estimates, so that the estimated depth and ego-motion can explain the majority of the scene, and the left-over can be explained by the residual flow maps. To achieve this, we adopt the sparsity loss from [44], i.e.

$$L_r^{(t)} = \sum_{s=0}^{3} \langle |R_{t,s}| \rangle / 2^s \sum_{\mathbf{u} \in \Omega(I_{t,s})} \sqrt{1 + |R_{t,s}(\mathbf{u})| / \langle |R_{t,s}| \rangle}, \tag{3}$$

in which $I_{t,s}$ is a downsampled version of I_t at scale s, and $\langle |R_{t,s}| \rangle$ is the spatial average of the absolute residual flow map $|R_{t,s}|$. By contrast with [44], here we introduce a normalising factor of $1/2^s$ at each scale, since the original loss was for scene flow, where the flow magnitude is independent of the resolution of the flow maps, which is not the case for the 2D residual flow we consider.

3.4 Image Denoising

Image noise is yet another key factor that affects the performance of the photometric loss. In practice, it is independent of the respective image, and is mainly caused by a low SNR in the darker regions of the image. Handling this noise is of crucial importance, as photometric loss is the only training signal, and supervises all of the modules we have mentioned thus far. To remove the noise from the images, we chose to use Neighbour2Neighbour [17], a state-of-the-art unsupervised denoising model trained on ImageNet with zero-mean Gaussian noise. The standard deviation values were varied from 5 to 50 during training. This model can either be used to denoise all images input to the network at both training time and test time, or it can be used solely at training time to denoise the images for the purpose of calculating the loss. In practice, we chose the latter approach, as denoising at test time has two major disadvantages: (i) it can significantly add to the computational burden at runtime, slowing down the depth estimation; and (ii) any errors in the denoising process can lead to downstream errors in the depth maps, even though the depth estimation model itself might have been trained well. By contrast, restricting denoising to training time has the advantage of allowing us to make the depth and motion networks robust to noise by training them on the original images.

3.5 Full Pipeline

We can now formulate our full pipeline as follows:

$$
\begin{aligned}
D_t &= \mathcal{D}(I_t), \; f_n = \mathcal{ME}_{1:n}([I_t, I_{t+1}]) \\
T_{t,t+1} &= \mathcal{MD}(f_N), \; R_t = \mathcal{RFD}(\{f_n : 1 \leq n \leq N\}), \; (C_t, B_t) = \mathcal{LCD}(f_N) \\
\mathcal{I}_t &= \mathcal{DN}(I_t), \; \mathcal{I}_{t+1} = \mathcal{DN}(I_{t+1}) \\
\mathcal{I}_t' &= \mathrm{reconstruct}(\mathcal{I}_{t+1}, V_t + R_t) \\
\tilde{\mathcal{I}}_t &= C_t \odot \mathcal{I}_t' + B_t \\
L_p^{(t)} &= \tfrac{1}{|M_t|} \sum_{\mathbf{u} \in M_t} \left(\alpha \tfrac{1 - SSIM(\mathcal{I}_t(\mathbf{u}), \tilde{\mathcal{I}}_t(\mathbf{u}))}{2} + (1 - \alpha) \left| \mathcal{I}_t(\mathbf{u}) - \tilde{\mathcal{I}}_t(\mathbf{u}) \right| \right)
\end{aligned}
\tag{4}
$$

The inputs to our system are a consecutive pair of images I_t and I_{t+1}, whilst $\mathcal{D}$ denotes the *Depth-Net*, $\mathcal{ME}_{1:n}$ denotes the first n layers of the N-layer *MotionNet* encoder, $\mathcal{MD}$ denotes the *Motion-Net* decoder, $\mathcal{RFD}$ denotes the residual flow decoder, $\mathcal{LCD}$ denotes the lighting change decoder, and $\mathcal{DN}$ denotes the denoiser [17]. The reconstruct function reconstructs $\mathcal{I}_t'$ as per Equation 1.

3.6 Making the Pipeline Bidirectional

Monodepth2 [37] calculates its photometric loss not only in the forwards direction, from I_t to I_{t+1}, but also in the backwards direction, from I_t to I_{t-1}, before combining the losses. This allows us to use the idea of minimum reprojection error to account for occluded pixels, and so we do the same. We also adopt the auto-masking losses $L_a^{(t)}$ from Monodepth2 [37], as even though our method can cope with moving objects, it is very difficult to use parallax to disentangle the motion of objects that are moving in the same direction and at the same speed as the ego-vehicle. We further include the commonly used edge-aware gradient smoothing loss $L_g^{(t)}$ to maintain spatial smoothness over the estimated depth maps. Our final loss $L^{(t)}$ then becomes the weighted sum

$$
L^{(t)} = \min \left(L_{p-}^{(t)}, L_{p+}^{(t)}, L_{a-}^{(t)}, L_{a+}^{(t)} \right) + \lambda_r \left(L_{r-}^{(t)} + L_{r+}^{(t)} \right) + \lambda_g L_g^{(t)},
\tag{5}
$$

in which $+/-$ denote the forward/backward versions of the losses, and $\lambda_r, \lambda_g \in \mathbb{R}$ are the weights.

4 Experiments

In §4.1, we compare our depth estimation performance to a number of state-of-the-art approaches in a variety of different daytime and/or night-time contexts. In §4.2, we present a study on the effect of parallax to help explain the importance of our neural intensity transformation module. Finally, in §4.3, we perform an ablation study to analyse the contributions made by the three individual components of our approach. Further experiments can be found in the supplementary material.

4.1 Depth Evaluation

We compare with 4 state-of-the-art unsupervised monocular methods: Monodepth2 [37], DeFeat-Net [45], ADDS-Depth-Night [48] and RNW [47] (see Figure 3 and Table 1). We tested our model with 3 different data variations: day only (d), night only (n), and a mix of day and night ($d\&n$). Mon-odepth2 [37] can be trained with all 3 configurations, although it has already been outperformed by DeFeat-Net [45] in the $d\&n$ setting. For the d and n settings, we outperform it by a significant margin in both error and accuracy (see Table 1). DeFeat-Net [45] and ADDS-Depth-Night [48] were originally trained with a $d\&n$ configuration. We evaluated the pre-trained models they released on our test split. Our method outperforms both methods by a significant margin on the nighttime sequences (see Table 1). Please note that we do not use any additional feature representation-based losses as used in DeFeat-Net [45], or paired day and night images as used in ADDS-Depth-Net [48]. RNW [47], another recent method, is also built on Monodepth2, but targets nighttime data only. As per Figure 3, our depth estimation results are sharp and better able to preserve edges than the competing methods. We also found that using a longer baseline improves depth estimation performance. However, naïvely using a wider baseline without also using our neural intensity transform can lead to a severe decrease in accuracy, particularly for nighttime images.

Test	Method	Train	Abs. Rel.	Sq. Rel.	RMSE	Log RMSE	$\delta < 1.25$	$\delta < 1.25^2$	$\delta < 1.25^3$
Day	Monodepth2 [37]	d	0.219	4.525	7.641	0.285	0.679	0.862	0.930
	Ours	d	**0.191**	**1.710**	**6.158**	**0.253**	**0.713**	**0.904**	**0.962**
	DeFeat-Net [45]	d & n	0.247	2.980	7.884	0.305	0.650	0.866	0.943
	RNW [47]	d & n	0.297	2.608	7.996	0.359	0.431	0.773	0.930
	ADDS-Depth-Night [48]	d & n	0.239	2.089	6.743	0.295	0.614	0.870	0.950
	Ours	d & n	**0.176**	**1.603**	**6.036**	**0.245**	**0.750**	**0.912**	**0.963**
Night	Monodepth2 [37]	n	0.453	21.310	11.420	0.444	0.700	0.873	0.930
	RNW MCIE + SBM [47]	n	0.350	7.934	8.994	0.407	0.674	0.861	0.922
	Ours	n	**0.186**	**1.656**	**6.288**	**0.248**	**0.728**	**0.919**	**0.969**
	DeFeat-Net [45]	d & n	0.334	4.589	8.606	0.358	0.586	0.827	0.911
	ADDS-Depth-Night [48]	d & n	0.287	2.569	7.985	0.339	0.490	0.816	0.946
	RNW [47]	d & n	0.185	1.710	6.549	0.262	0.733	0.910	0.960
	Ours	d & n	**0.174**	**1.637**	**6.302**	**0.245**	**0.754**	**0.915**	**0.964**

Table 1: A quantitative comparison of our method. The results of Monodepth2 [37] are reported after retraining it. Those of DeFeat-Net [45] and ADDS-Depth-Night [48] are reported using the checkpoints from their public repositories. The evaluation uses a maximum depth of 50m. Underlined methods use daytime images as main supervision or for regularisation losses.

Figure 3: A qualitative comparison of our proposed method with the state of the art.

4.2 Effect of Parallax

To better understand how depth estimation performance is affected by increasing the average parallax (metric separation) between the images we use to calculate the photometric loss, we constructed a new nighttime training split by increasing the intra-triplet stride (see supplementary material) to 2, which increased the average parallax between the images from 0.353m to 0.706m. Without our neural intensity transformation, the depth estimation performance significantly decreased compared to the original nighttime training split (see the difference between the RMSEs of the baseline in the top and bottom parts of Table 2). A key cause of this in night images is likely the headlights of the ego-vehicle, which can cause the pixel intensities to change drastically between frames. However, with our neural intensity transformation, the depth estimation performance was found to instead increase, which we hypothesise to be because by compensating for the lighting changes, we make it possible to exploit the stronger supervision that can be offered by a wider baseline.

4.3 Ablation Study

Lighting Change Compensation. In Figure 4(a), we show several reference images and their lighting change maps. The intensity changes are non-uniform, so we cannot use the existing correction approaches from [49, 50, 51]. We also observe that our method is able to clearly disentangle both the changes in ambient light resulting from movement towards/away from point light sources (captured by C_t) and the additional light added to the road pixels in the images by the ego-vehicle headlights (captured by B_t). Our neural intensity transform significantly reduces the RMSE error compared to the baseline (see Table 2), and is also able to fill in holes in front of the ego-vehicle (see Figure 3).

Stride	Method	Abs. Rel.	Sq. Rel.	RMSE	Log RMSE	$\delta < 1.25$	$\delta < 1.25^2$	$\delta < 1.25^3$
1	Baseline	0.266	5.647	6.305	0.331	0.759	0.9013	0.947
	w/ NIT	0.190	1.824	4.848	0.257	0.763	0.919	0.965
	w/ Denoising	0.163	1.256	4.193	0.224	0.801	0.935	0.973
	Full Model	0.154	1.174	4.120	0.216	0.811	0.939	0.976
2	Baseline	0.602	63.914	14.726	0.467	0.785	0.902	0.939
	w/ NIT	0.169	1.727	4.693	0.236	0.812	0.929	0.967
	Full Model	0.131	0.926	3.731	0.188	0.852	0.949	0.980

Table 2: Ablation study showing the importance of different modules in our system. The maximum depth was set to 30m for this study. 'Stride' denotes intra-triplet stride (see supplementary material).

Figure 4: Visualisations of (a) estimated light changes; (b) residual flow and estimated depth; (c) the effects of denoising on the training loss over time.

Motion Compensation. In Figure 4(b), we show several reference images and their residual flow and depth maps. In the second column, one can clearly see that our method is able to distinguish pixels on moving objects such as cars and pedestrians from static pixels. This effect can be observed for both daytime and night-time images, showcasing the generality of our approach through a single unified training pipeline. In Table 2, it can be seen that correcting the reprojection correspondences using the residual flow map we predict leads to a significant improvement in accuracy.

Image Denoising. Denoising the images while calculating the training loss should ideally reduce the ambiguity in establishing pixel correspondences between the images, giving a robust supervision signal for training our system and thereby achieving lower error and higher accuracy. This effect can be clearly seen in the training error plot shown in Figure 4(c), where we compare our baseline+NIT model with and without denoising. The denoising results in much more accurate depth maps, improving both the RMSE and accuracy metrics as shown in Table 2.

5   Limitations

Our method has a number of limitations. First, as is typical of monocular methods, it is only able to estimate depth up to scale. Second, like most stereo approaches (whether variable-baseline like ours, or fixed-baseline with a rigid stereo rig), it struggles to preserve the detail of distant parts of the scene because of limited parallax. Third, it also struggles to recover structural detail from very dark image regions (e.g. see Figure 1(b)). And finally, in common with most vision-based depth estimation methods, it does not consistently perform well for transparent surfaces like glass.

6   Conclusions

In this paper, we propose a self-supervised method to learn a single model to estimate depth maps from monocular day and nighttime RGB images. By compensating for the illumination changes that can occur from one frame to the next, we enable accurate nighttime depth estimation in non-uniform lighting conditions. Moreover, by predicting per-pixel residual flow and using it to correct the reprojection correspondences induced by the estimated ego-motion and depth, we improve our method's ability to cope with both moving objects in the scene and motion blur. Finally, by denoising the input images prior to calculating the photometric loss, we improve the loss's ability to provide a strong supervision signal, making the entire system more robust and accurate.

References

[1] E. Yurtsever, J. Lambert, A. Carballo, and K. Takeda. A survey of autonomous driving: Common practices and emerging technologies. *IEEE Access*, 8:58443–58469, 2020.

[2] J. Sanchez, J.-A. Corrales, B.-C. Bouzgarrou, and Y. Mezouar. Robotic manipulation and sensing of deformable objects in domestic and industrial applications: a survey. *The International Journal of Robotics Research*, 37(7):688–716, 2018.

[3] M. A. Livingston, Z. Ai, J. E. Swan, and H. S. Smallman. Indoor vs. outdoor depth perception for mobile augmented reality. In *2009 IEEE Virtual Reality Conference*, pages 55–62. IEEE, 2009.

[4] R. A. Newcombe, S. J. Lovegrove, and A. J. Davison. DTAM: Dense tracking and mapping in real-time. In *Proceedings of the IEEE International Conference on Computer Vision*, 2011.

[5] K. Wang and S. Shen. MVDepthNet: Real-time Multiview Depth Estimation Neural Network. In *3DV*, 2018.

[6] D. Eigen, C. Puhrsch, and R. Fergus. Depth map prediction from a single image using a multi-scale deep network. In *Advances in neural information processing systems*, pages 2366–2374, 2014.

[7] F. Liu, C. Shen, and G. Lin. Deep convolutional neural fields for depth estimation from a single image. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5162–5170, 2015.

[8] R. Garg, V. K. BG, G. Carneiro, and I. Reid. Unsupervised cnn for single view depth estimation: Geometry to the rescue. In *European Conference on Computer Vision*, pages 740–756. Springer, 2016.

[9] H. Zhan, R. Garg, C. S. Weerasekera, K. Li, H. Agarwal, and I. Reid. Unsupervised learning of monocular depth estimation and visual odometry with deep feature reconstruction. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 340–349, 2018.

[10] Y. Almalioglu, M. R. U. Saputra, P. P. de Gusmao, A. Markham, and N. Trigoni. Ganvo: Unsupervised deep monocular visual odometry and depth estimation with generative adversarial networks. *2017 IEEE International Conference on Robotics and Automation (ICRA)*, 2019.

[11] C. Kerl, J. Sturm, and D. Cremers. Dense visual slam for rgb-d cameras. In *2013 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 2100–2106. IEEE, 2013.

[12] C. Kerl, J. Sturm, and D. Cremers. Robust odometry estimation for rgb-d cameras. In *2013 IEEE International Conference on Robotics and Automation*, pages 3748–3754. IEEE, 2013.

[13] A. I. Comport, E. Malis, and P. Rives. Accurate quadrifocal tracking for robust 3d visual odometry. In *Proceedings 2007 IEEE International Conference on Robotics and Automation*, pages 40–45. IEEE, 2007.

[14] A. Sharma, L.-F. Cheong, L. Heng, and R. T. Tan. Nighttime stereo depth estimation using joint translation-stereo learning: Light effects and uninformative regions. In *2020 International Conference on 3D Vision (3DV)*, pages 23–31. IEEE, 2020.

[15] T. Portz, L. Zhang, and H. Jiang. Optical flow in the presence of spatially-varying motion blur. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1752–1759. IEEE, 2012.

[16] A. Rav-Acha and S. Peleg. Restoration of multiple images with motion blur in different directions. In *Proceedings Fifth IEEE Workshop on Applications of Computer Vision*, pages 22–28. IEEE, 2000.

[17] T. Huang, S. Li, X. Jia, H. Lu, and J. Liu. Neighbor2neighbor: Self-supervised denoising from single noisy images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14781–14790, 2021.

[18] D. Scharstein and R. Szeliski. A taxonomy and evaluation of dense two-frame stereo correspondence algorithms. *International journal of computer vision*, 47(1-3):7–42, 2002.

[19] D. Scharstein and C. Pal. Learning conditional random fields for stereo. In *2007 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE, 2007.

[20] L. Zou and Y. Li. A method of stereo vision matching based on opencv. In *2010 International Conference on Audio, Language and Image Processing*, pages 185–190. IEEE, 2010.

[21] J. L. Schonberger and J.-M. Frahm. Structure-from-motion revisited. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4104–4113, 2016.

[22] Y. Dai, H. Li, and M. He. Projective multiview structure and motion from element-wise factorization. *IEEE transactions on pattern analysis and machine intelligence*, 35(9):2238–2251, 2013.

[23] F. Yu and D. Gallup. 3d reconstruction from accidental motion. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3986–3993, 2014.

[24] L. Ladicky, J. Shi, and M. Pollefeys. Pulling things out of perspective. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 89–96, 2014.

[25] N. dos Santos Rosa, V. Guizilini, and V. Grassi. Sparse-to-continuous: Enhancing monocular depth estimation using occupancy maps. In *2019 19th International Conference on Advanced Robotics (ICAR)*, pages 793–800. IEEE, 2019.

[26] H. Fu, M. Gong, C. Wang, K. Batmanghelich, and D. Tao. Deep ordinal regression network for monocular depth estimation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2002–2011, 2018.

[27] C. Godard, O. Mac Aodha, and G. J. Brostow. Unsupervised monocular depth estimation with left-right consistency. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6602–6611. IEEE, 2017.

[28] M. Jaderberg, K. Simonyan, A. Zisserman, et al. Spatial transformer networks. In *Advances in neural information processing systems*, pages 2017–2025, 2015.

[29] Z. Wang, A. C. Bovik, H. R. Sheikh, and E. P. Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

[30] T. Zhou, M. Brown, N. Snavely, and D. G. Lowe. Unsupervised learning of depth and ego-motion from video. In *CVPR*, 2017.

[31] V. M. Babu, K. Das, A. Majumdar, and S. Kumar. Undemon: Unsupervised deep network for depth and ego-motion estimation. In *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1082–1088. IEEE, 2018.

[32] R. Li, S. Wang, Z. Long, and D. Gu. Undeepvo: Monocular visual odometry through unsupervised deep learning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7286–7291. IEEE, 2018.

[33] Z. Yin and J. Shi. GeoNet: Unsupervised learning of dense depth, optical flow and camera pose. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, volume 2, 2018.

[34] C. Luo, Z. Yang, P. Wang, Y. Wang, W. Xu, R. Nevatia, and A. Yuille. Every pixel counts++: Joint learning of geometry and motion with 3d holistic understanding. *arXiv preprint arXiv:1810.06125*, 2018.

[35] F. Aleotti, F. Tosi, M. Poggi, and S. Mattoccia. Generative adversarial networks for unsupervised monocular depth prediction. In *15th European Conference on Computer Vision (ECCV) Workshops*, volume 1, page 8, 2018.

[36] M. Vankadari, S. Kumar, A. Majumder, and K. Das. Unsupervised learning of monocular depth and ego-motion using conditional patchgans. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 5677–5684. International Joint Conferences on Artificial Intelligence Organization, 7 2019. doi:10.24963/ijcai.2019/787. URL https://doi.org/10.24963/ijcai.2019/787.

[37] C. Godard, O. Mac Aodha, M. Firman, and G. Brostow. Digging into self-supervised monocular depth estimation. *arXiv preprint arXiv:1806.01260*, 2018.

[38] X. Lyu, L. Liu, M. Wang, X. Kong, L. Liu, Y. Liu, X. Chen, and Y. Yuan. Hr-depth: High resolution self-supervised monocular depth estimation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 2294–2301, 2021.

[39] A. Petrovai and S. Nedevschi. Exploiting pseudo labels in a self-supervised learning framework for improved monocular depth estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1578–1588, 2022.

[40] J. Yan, H. Zhao, P. Bu, and Y. Jin. Channel-wise attention-based network for self-supervised monocular depth estimation. In *2021 International Conference on 3D Vision (3DV)*, pages 464–473. IEEE, 2021.

[41] T.-W. Hui. Rm-depth: Unsupervised learning of recurrent monocular depth in dynamic scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1675–1684, 2022.

[42] V. Guizilini, R. Ambrus, S. Pillai, A. Raventos, and A. Gaidon. 3d packing for self-supervised monocular depth estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2485–2494, 2020.

[43] C. Shu, K. Yu, Z. Duan, and K. Yang. Feature-metric loss for self-supervised learning of depth and egomotion. In *European Conference on Computer Vision*, pages 572–588. Springer, 2020.

[44] H. Li, A. Gordon, H. Zhao, V. Casser, and A. Angelova. Unsupervised monocular depth learning in dynamic scenes. *arXiv preprint arXiv:2010.16404*, 2020.

[45] J. Spencer, R. Bowden, and S. Hadfield. Defeat-net: General monocular depth via simultaneous unsupervised representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14402–14413, 2020.

[46] M. Vankadari, S. Garg, A. Majumder, S. Kumar, and A. Behera. Unsupervised monocular depth estimation for night-time images using adversarial domain feature adaptation. In *European Conference on Computer Vision*, pages 443–459. Springer, 2020.

[47] K. Wang, Z. Zhang, Z. Yan, X. Li, B. Xu, J. Li, and J. Yang. Regularizing nighttime weirdness: Efficient self-supervised monocular depth estimation in the dark. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 16055–16064, 2021.

[48] L. Liu, X. Song, M. Wang, Y. Liu, and L. Zhang. Self-supervised monocular depth estimation for all day images using domain separation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 12737–12746, 2021.

[49] H. Jin, P. Favaro, and S. Soatto. Real-time feature tracking and outlier rejection with changes in illumination. In *Proceedings Eighth IEEE International Conference on Computer Vision. ICCV 2001*, volume 1, pages 684–689. IEEE, 2001.

[50] S. Baker and I. Matthews. Lucas-kanade 20 years on: A unifying framework. *International journal of computer vision*, 56(3):221–255, 2004.

[51] N. Yang, L. v. Stumberg, R. Wang, and D. Cremers. D3vo: Deep depth, deep pose and deep uncertainty for monocular visual odometry. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1281–1292, 2020.