Diffusion Visual Counterfactual Explanations

Maximilian Augustin[*]   **Valentyn Boreiko**[*]   **Francesco Croce**   **Matthias Hein**
University of Tübingen

Abstract

Visual Counterfactual Explanations (VCEs) are an important tool to understand the decisions of an image classifier. They are "small" but "realistic" semantic changes of the image changing the classifier decision. Current approaches for the generation of VCEs are restricted to adversarially robust models and often contain non-realistic artefacts, or are limited to image classification problems with few classes. In this paper, we overcome this by generating Diffusion Visual Counterfactual Explanations (DVCEs) for arbitrary ImageNet classifiers via a diffusion process. Two modifications to the diffusion process are key for our DVCEs: first, an adaptive parameterization, whose hyperparameters generalize across images and models, together with distance regularization and late start of the diffusion process, allows us to generate images with minimal semantic changes to the original ones but different classification. Second, our cone regularization via an adversarially robust model ensures that the diffusion process does not converge to trivial non-semantic changes, but instead produces realistic images of the target class which achieve high confidence by the classifier. Code is available under https://github.com/valentyn1boreiko/DVCEs.

1 Introduction

It can be argued that one of the main problems hindering the widespread use of machine learning and image classification in particular, which is the focus of our paper, is the missing possibility to explain the decisions of black-box models such as neural networks. This is not only a problem for decisions affecting humans where the current draft for AI regulation in Europe [10] requires "transparency", but it is a pressing problem in all applications of machine learning. The reason, to some extent, is that humans would like to understand but also control if the learning algorithm has captured the "concepts" of the underlying classes or if it just predicts well using spurious features, artefacts in the data set, or other sources of error. In this paper, we focus on model-agnostic explanations which can be applied to any classifier and do not rely on the specific structure of the classifier such as decision trees or linear classifiers. In this area, in particular for image classification, sensitivity based explanations [4], explanations based on feature attributions [3], saliency maps [48, 47, 18, 57, 52], Shapley additive explanations [32], and local fits of interpretable models [40] have been proposed. Moreover, [56] proposed counterfactual explanations (CEs), which are instance-specific explanations. They can be applied to any classifier and it has been argued that they are close to the human justification of decisions [35] using counterfactual reasoning: "I would have recognized it as zebra (instead of horse) if it had had black and white stripes." For a given classifier almost all methods for the generation of CEs [56, 16, 36, 6, 39, 55, 45] try to solve the following problem: "Given a target class c what is the minimal change δ of input x, such that $x + \delta$ is classified as class c with high probability and is a realistic instance of my data generating distribution?" From the perspective of "debugging" existing machine learning models, CEs are interesting as they construct a concrete input $x + \delta$ with a different classification that allows the developer to test if the model has learned the correct features.

---

[*]Equal contribution.

Original	Class 1	Class 2	Original	Class 1	Class 2
chimpanzee 0.88	orangutan: 0.99	gorilla: 0.98	Chesapeake Bay ret.: 0.97	golden retriever: 0.99	labrador retriever: 0.92

Figure 1: Our method DVCE creates visual counterfactual explanations (VCEs) that explain any given classifier (here: non-robust ConvNeXt) by changing an image of one class into a similar target class by changing class relevant features in the foreground while preserving the overall image structure.

The main problem with visual counterfactual explanations (VCEs), that is CEs for image classification, and the reason why they are not widely used is that the tasks of generating CEs and the generation of adversarial examples [53] are very related. Thus even imperceivable changes of the image can already change the prediction of the classifier, however, the resulting noise patterns do not show the user if the classifier has picked up the right class-specific features. One possible solution is using adversarially robust models [44, 1, 7], which have been shown to produce semantically meaningful VCEs by directly maximizing the probability of the target class in image space. These approaches have the downside that they only can generate VCEs for robust models which is a significant restriction as these models are not competitive in terms of prediction accuracy. The second approach is to restrict the generation of VCEs using a generative model or constraining the set of potential image manipulations [20, 21, 43, 8, 19, 46, 28]. However, these approaches are either restricted to datasets with a small number of classes, cannot provide explanations for arbitrary classifiers, or the generated images look realistic but are far away from the original one so that the VCE and the original image have so little in common that not much insight can be gained.

Recently, [27] trained a StyleGAN2 [25] model to discover and manipulate class attributes. While their approach yields impressive results on smaller-scale datasets with few similar classes (for example, different bird species), the authors did not demonstrate that the method scales to complex tasks such as ImageNet with hundreds of classes where different classes require different sets of attributes. Another disadvantage is that the StyleGAN model needs to be retrained for every classifier, making it prohibitively expensive to explain multiple large models. Moreover, [26] have proposed a loss to do VCEs in the latent space of a GAN/VAE. While they show promising results for MNIST/FMNIST, those for ImageNet are not clear, and there is no code available. Furthermore, to explain a classifier, the conditional information during the generation of explanations should ideally come only from the classifier itself, but [26] rely on a conditional GAN which might introduce a bias.

In this paper, we overcome the aforementioned challenges by generating our Diffusion Visual Counterfactual Explanations (DVCEs) for arbitrary ImageNet classifiers (an example can be seen in Fig 1). We use the progress in the generation of realistic images using diffusion processes [49, 24, 50, 51] reaching recently the level of GANs [15]. Similarly to [38, 2], we use a classifier and a distance-type regularization to guide the generation of the images. Two modifications to the diffusion process are key elements for our DVCEs: i) a combination of distance regularization and starting point of the diffusion process together with an adaptive reparameterization lets us generate VCEs visually close to the original image in a controlled way so that hyperparameters can be fixed across images and even across models, ii) our cone regularization of the gradient of the classifier via an adversarially robust model ensures that the diffusion process does not converge to trivial non-semantic changes but instead produces realistic images of the target class which achieve high confidence by the classifier. Our approach can in principle be employed for any dataset where a generative diffusion model and an adversarially robust model are available. In a qualitative comparison (Sec. 4.1) and a user study (App. C) we show that our DVCEs outperform the recent method of [7] as well as an adaptation of [2] for the generation of VCEs.

2 Diffusion models

Diffusion models [15, 49, 50, 24, 37] are generative models that consist of two steps: *forward diffusion* process (and thus a Markov process) that transforms the data distribution to a prior distribution (which

is usually assumed to be a standard normal distribution) and the *reverse diffusion* process that transforms the prior distribution back to the data distribution.The existence of the (continuous-time) reverse diffusion process was closer investigated in [51].

In the discrete-time setting, a Markov chain $\{x_1, ..., x_T\}$ for any data point x_0 in the forward direction is defined via a Markovian process that adds noise to the data point at each timestep:

$$q(x_t|x_{t-1}) = \mathcal{N}(\sqrt{1-\beta_t}x_{t-1}, \beta_t I), \tag{1}$$

where $\{\beta_1, ..., \beta_T\}$ is some variance schedule, chosen such that $q(x_T) \sim \mathcal{N}(0, I)$. Note that given x_0, it is possible to sample from $q(x_t|x_0)$ in closed form instead of applying noise t times using:

$$q(x_t|x_0) = \mathcal{N}(\sqrt{\overline{\alpha}_t}x_0, 1 - \overline{\alpha}_t I), \tag{2}$$

$$x_t = \sqrt{\overline{\alpha}_t}x_0 + \epsilon\sqrt{1-\overline{\alpha}_t}, \epsilon \sim \mathcal{N}(0, I), \tag{3}$$

where $\overline{\alpha}_t := \prod_{k=1}^{t}(1-\beta_k)$. Knowing these conditional distributions, one can use Bayes theorem to derive the conditional distribution of the reverse step $q(x_{t-1}|x_t, x_0)$

$$q(x_{t-1}|x_t, x_0) = \mathcal{N}(\tilde{\mu}_t(x_t, x_0), \tilde{\beta}_t I), \tag{4}$$

where $\tilde{\mu}_t(x_t, x_0) = \frac{\sqrt{\overline{\alpha}_{t-1}}\beta_t}{1-\overline{\alpha}_t}x_0 + \frac{\sqrt{\alpha_t}(1-\overline{\alpha}_{t-1})}{1-\overline{\alpha}_t}x_t$ and $\tilde{\beta}_t = \frac{1-\overline{\alpha}_{t-1}}{1-\overline{\alpha}_t}\beta_t$, as shown in [33]. In practice, one then uses a neural network to approximate $q(x_{t-1}|x_t, x_0)$ by dropping conditioning on x_0:

$$p_\theta(x_{t-1}|x_t) = \mathcal{N}(\mu_\theta(x_t, t), \Sigma_\theta(x_t, t)). \tag{5}$$

To sample from $p_\theta(x_0)$, one samples x_T from $\mathcal{N}(0, I)$ and then follows the reverse process by repeatedly sampling from the transition probabilities $p_\theta(x_{t-1}|x_t)$.

Instead of predicting $\mu_\theta(x_t, t)$ directly, it has been shown in [24] that the best performing parameterization uses a neural network $\epsilon_\theta(x_t, t)$ to approximate the source noise ϵ in (3) and the loss used for training resembles that of a denoising model:

$$L_{\text{simple}}(\theta, T, q(x_0)) := \sum_{t=1}^{T} \mathbb{E}_{x_0 \sim q(x_0)}\mathbb{E}_{\epsilon \sim \mathcal{N}(0,I)}||\epsilon - \epsilon_\theta(x_t, t)||_2^2. \tag{6}$$

The mean of the reverse step μ_θ in (5) can be derived by plugging (3) in $\tilde{\mu}_t(x_t, x_0)$ as:

$$\mu_\theta(x_t, t) = \frac{1}{\sqrt{1-\beta_t}}(x_t - \frac{\beta_t}{\sqrt{1-\overline{\alpha}_t}}\epsilon_\theta(x_t, t)). \tag{7}$$

This is, however, only one of the possible equivalent parameterization of the learning objective as shown in [33]. Because the objective L_{simple} does not give a learning signal for $\Sigma_\theta(x_t, t)$, in practice one combines L_{simple} with another loss based on a variational lower bound of the data likelihood [49], which unlike L_{simple} allows us to learn the covariances $\Sigma_\theta(x_t, t)$.

2.1 Class conditional sampling

There exist diffusion models trained with and without knowledge about classes in the dataset [15, 23]. For our experiments, we only use the class-unconditional diffusion model, such that all class-conditional features are introduced by the classifier which we want to explain. For the noise-aware classifier $p_\phi(y|\cdot, \cdot) : \mathbb{R}^d \times \{1, ..., T\} \to [0, 1]$, with parameters ϕ, that is trained on noisy images corresponding to the various time-steps [15], the reverse process transitions are then of the form:

$p_{\theta,\phi}(x_{t-1}|x_t, y) = Z\, p_\theta(x_{t-1}|x_t)\, p_\phi(y|x_t, t)$ (8) for a normalization constant Z. As we would like to explain any classifier and not only noise-aware ones, we follow the approach of [2], where a classifier $p_\phi(y|\cdot)$ is given as input the denoised sample $\hat{x}_0 = f_{\text{dn}}(x_t)$ of x_t, using the mapping:

$$f_{\text{dn}} : \mathbb{R}^d \times \{1, ..., T\} \to \mathbb{R}^d, \quad (x_t, t) \mapsto \frac{x_t}{\sqrt{\overline{\alpha}_t}} - \frac{\sqrt{1-\overline{\alpha}_t}\epsilon_\theta(x_t, t)}{\sqrt{\overline{\alpha}_t}}. \tag{9}$$

This mapping, derived from (3) estimates the noise-free image x_0 by using the noise approximated by the model $\epsilon_\theta(x_t, t)$ for a given time-step t. With this, we can define a time-step aware posterior $p_\phi(y|x_t, t)$ for any classifier $p_\phi(y|\cdot)$ as $p_\phi(y|x_t, t) = p_\phi(y|f_{\text{dn}}(x_t, t))$.

The issue is that efficient sampling from the original diffusion model is possible only because the reverse process is made of normal distributions. As we need to sample from $p_{\theta,\phi}(x_{t-1}|x_t, y)$ hundreds of times to obtain a single sample from the data distribution, it is not possible to use MCMC-samplers with high complexity to sample from each of the individual transitions. In [15], they proposed to solve it by approximating $p_{\theta,\phi}(x_{t-1}|x_t, y)$ with slightly shifted versions of $p_\theta(x_{t-1}|x_t)$ to make closed-form sampling possible. Such transition kernels are given by:

$$p_{\theta,\phi}(x_{t-1}|x_t, y) = \mathcal{N}(\mu_t, \Sigma_\theta(x_t, t)), \tag{10}$$

$$\mu_t = \mu_\theta(x_t, t) + \Sigma_\theta(x_t, t)\nabla_{x_t} \log p_\phi(y|x_t, t), \tag{11}$$

which we further adapt for the goal of generating VCEs and use in our experiments.

3 Diffusion Visual Counterfactual Explanations

A VCE z for a chosen target class c, a given classifier f, and an input x should satisfy the following criteria: i) **validity:** the VCE z should be classified by f as the desired target class c with high probability, ii) **realism:** the VCE z should be indistinguishable or at least close to a natural image, iii) **minimality/closeness:** the difference between the VCE z and the original image x should be the minimal semantic modification necessary to change the class, in particular, the generated image z should be close to x while being valid and realistic, e.g. by changing the object in the image and leaving the background unchanged. Note that targeted adversarial examples are valid but do not show meaningful semantic changes in the target class for a non-robust model and are not realistic.

The $l_{1.5}$-SVCEs of [7] optimize the predicted probability of a classifier into the target class by manipulating the image and is very close to the generation of adversarial examples and thus works only for robust classifiers. They have used an adversarially robust ImageNet classifier that was trained to be multiple-norm robust (MNR) as proposed in [12]. In our paper we use this model under the name MNR-RN50 (see Sec. 4.2). The realism of the image comes purely from the generative properties of robust classifiers [44] which can lead to artefacts. In contrast, our Diffusion Visual Counterfactual Explanations (DVCEs) work for any classifier and our generated images are more realistic due to the integration of diffusion models. An approach similar to our DVCE framework is Blended Diffusion of [2] which manipulates the image inside a masked region. In fact, it is easy to adapt it to the task of VCEs by allowing the whole image to be manipulated. DVCE and Blended Diffusion share the same diffusion model, but, as we show in the Appendix, Blended Diffusion cannot be applied to arbitrary classifiers and requires image-specific hyperparameter tuning, see Fig. 2.

3.1 Adaptive Parameterization

For generating the DVCE of the original image $\hat{x}$, we do not want to sample just any image x from $p(x|y)$ (high realism and validity) but also to make sure that $d(x, \hat{x})$ is small. To do this, we have to condition our diffusion process on $\hat{x}$. Using the introduced denoising function f_{dn} and analogously to the derivation in [15] and following application in [28], the mean of the transition kernel becomes:

$$\mu_\theta(x_t, t) + \Sigma_\theta(x_t, t)\nabla_{x_t}\Big[C_c \log p_\phi\big(y|f_{\mathrm{dn}}(x_t, t)\big) - C_d d\big(\hat{x}, f_{\mathrm{dn}}(x_t, t)\big)\Big], \tag{12}$$

where C_c is the coefficient of the classifier, and C_d the one of the distance guiding loss. Intuitively, we take a step in the direction that increases the classifier score while staying close to $\hat{x}$. Note that the last term can be interpreted as the log gradient of a distribution with density $\exp(-\frac{d_t(\hat{x}, \cdot)}{\sigma})$, where $\sigma = \frac{1}{C_d}$ and $d_t(\hat{x}, \cdot) = d(\hat{x}, f_{\mathrm{dn}}(\cdot, t))$, thus we introduce a time-aware prior distribution that enforces our output to be similar to $\hat{x}$. In our work, we use the l_1-distance as it produces sparse changes. Several works have tried to minimize some distance during the diffusion process, implicitly in [9] or explicitly, but for the background, in [2]. However, there is no principled way to choose the coefficient for such a regularization term. It turns out that it is impossible to find a parameter setting for Blended Diffusion [2] that works across images and classifiers. Thus, we propose a parameterization

$$g_{\mathrm{update}} = C_c \frac{\nabla_{x_t} \log p_\phi(y|f_{\mathrm{dn}}(x_t, t)))}{\|\nabla_{x_t} \log p_\phi(y|f_{\mathrm{dn}}(x_t, t)))\|_2} - C_d \frac{\nabla_{x_t} d(\hat{x}, f_{\mathrm{dn}}(x_t, t))}{\|\nabla_{x_t} d(\hat{x}, f_{\mathrm{dn}}(x_t, t))\|_2}, \tag{13}$$

which adapts to the predicted mean of the diffusion model that we use to change μ_t in (11) to

$$\mu_t = \mu_\theta(x_t, t) + \Sigma_\theta(x_t, t) \|\mu_\theta(x_t, t)\|_2 \, g_{\mathrm{update}}. \tag{14}$$

Original	DVCE	Blended Diffusion C_c 10			Blended Diffusion C_c 25		
		$C_d = 100$	500	1000	100	500	1000
keeshond: 0.38	chow: 1.00	chow: 0.77	chow: 0.55	chow: 0.07	chow: 0.99	chow: 0.64	chow: 0.80
lynx: 0.72	cheetah: 0.99	cheetah: 0.67	cheetah: 0.38	cheetah: 0.77	cheetah: 0.95	cheetah: 0.73	cheetah: 0.98
weasel: 0.41	guinea pig: 1.00	guinea pig: 0.86	guinea pig: 0.12	guinea pig: 0.05	guinea pig: 0.93	guinea pig: 0.97	guinea pig: 0.70

Figure 2: DVCEs for the robust MNR-RN50 model (taken from [7]) in the second column and DVCEs using the setting of [2], such that regularization is applied for the whole image. We can see that due to our adaptive parameterization, the same parameter works across different images for DVCEs ($C_c = 0.1, C_d = 0.15$), and across different classifiers (see Fig. 5). For Blended Diffusion, it is difficult to choose a set of hyperparameters that, even for a single classifier, works for multiple images. For the l_2 and LPIPS regularization weights of Blended Diffusion, we report the parameter of LPIPS and always use an l_2 weight 10 times as large (the ratio used in [2]).

This adaptive parameterization allows for fine-grained control of the influence of the classifier and distance regularization so that now the hyperparameters C_c and C_d have the same influence across images and even classifiers. It facilitates the generation of DVCEs as otherwise hyperparameter finetuning would be necessary for each image as in Blended Diffusion, see Fig. 2 for a comparison. However, even with our adaptive parameterization, it is still not easy to produce semantically meaningful changes close to $\hat{x}$ as can be seen in App. B.2. Thus, as in [2], we vary the starting point in the diffusion process and observe in App. B.2 that starting from step $\frac{T}{2}$ of the forward diffusion process, together with the adaptive parameterization and using as the distance the l_1-distance, provides us with sparse but semantically meaningful changes. In our experiments, we set $T = 200$.

3.2 Cone Projection for Classifier Guidance

A goal for our DVCEs is to be applied to any image classifier regardless of whether it is adversarially robust or not. This is because using diffusion with the new mean (14) to a non-robust classifier does not work and leads to very small modifications of the image, which are similar to adversarial examples without meaningful changes. The reason is that the gradients of non-robust classifiers are noisier and less semantically meaningful than those of the robust classifiers. We illustrate this for a non-robust Swin-Transformer[29] in Fig. 3 where hardly any changes are generated. Note that this is even the case if we first denoise the sample using the denoising function f_{dn} (9).

As a solution, we suggest projecting the gradient of a robust classifier with parameters v, $\nabla_{x_t} \log p_{\text{robust},v}(y|f_{\text{dn}}(x_t,t))$, onto a cone centered at the gradient of the classifier, $\nabla_{x_t} \log p_\phi(y|f_{\text{dn}}(x_t,t))$. More precisely, we define

$$g_{\text{proj}} = P_{\text{cone}(\alpha,\nabla_{x_t} \log p_\phi(y|f_{\text{dn}}(x_t,t)))}\left[\nabla_{x_t} \log p_{\text{robust},v}\big(y|f_{\text{dn}}(x_t,t)\big)\right],$$

where $\text{cone}(\alpha,v) := \{w \in \mathbb{R}^d : \angle(v,w) \leq \alpha\}$ is the cone of angle α around vector v, and the projection $P_{\text{cone}(\alpha,v)}$ onto $\text{cone}(\alpha,v)$ is given as:

$$P_{\text{cone}(\alpha,v)}[w] := \begin{cases} \langle u,w \rangle\, u, & \angle(w,v) > \alpha \\ w, & \text{else,} \end{cases}$$

where $P_{v\perp}(w) := w - \frac{\langle w,v \rangle}{\langle v,v \rangle} v$ and we define $u = \sin(\alpha) \frac{P_{v\perp}(w)}{\|P_{v\perp}(w)\|_2} + \cos(\alpha) \frac{v}{\|v\|_2}$ (note that $\|u\|_2 = 1$ and $\langle u,v \rangle = \cos(\alpha)$). The idea of this projection is that in this way we reduce drastically the noise in the gradient of the non-robust classifier. Note, however, that the projection of the gradient of the robust classifier onto the cone generated by the non-robust classifier is always an ascent direction for $\log p_\phi(y|f_{\mathrm{dn}}(x_t,t))$ and we still have the goal of maximizing this objective (note that g_{proj} is not necessarily an ascent direction for $\log p_{\mathrm{robust},v}(y|f_{\mathrm{dn}}(x_t,t))$). Thus, one can see the cone projection as a form of regularization of $\nabla_{x_t} \log p_\phi(y|f_{\mathrm{dn}}(x_t,t))$ which guides the diffusion process into semantically meaningful changes to the images.

Original	Non-robust	Robust	Cone Proj.	Original	Non-robust	Robust	Cone Proj.
ladybug	weevil: 0.99	weevil: 1.00	weevil: 0.99	ringlet	monarch: 0.47	monarch: 1.00	monarch: 0.98

Figure 3: DVCEs for the non-robust Swin-Transformer[29], robust MNR-RN50 model, and cone-projected DVCEs for Swin-Transformer[29]. While the adversarially robust classifier and using a cone projection are guiding the diffusion process to produce class-specific features, using gradients of the non-robust classifier does not yield perceptually aligned changes.

3.3 Final Scheme for Diffusion Visual Counterfactuals

Our solution for a non-adversarially robust classifier $p_\phi(y|\cdot)$ is to use Algorithm 1 of [15] by replacing the update step with:

$$g_{\mathrm{proj}} = P_{\mathrm{cone}(\alpha, \nabla_{x_t} \log p_\phi(y|f_{\mathrm{dn}}(x_t,t)))} \Big[\nabla_{x_t} \log p_{\mathrm{robust},v}\big(y|f_{\mathrm{dn}}(x_t,t)\big) \Big],$$

$$g_{\mathrm{update}} = C_c \frac{g_{\mathrm{proj}}}{\|g_{\mathrm{proj}}\|_2} - C_d \frac{\nabla_{x_t} d(\hat{x}, f_{\mathrm{dn}}(x_t,t))}{\|\nabla_{x_t} d(\hat{x}, f_{\mathrm{dn}}(x_t,t))\|_2},$$

$$\mu_t = \mu_\theta(x_t,t) + \Sigma_\theta(x_t,t) \|\mu_\theta(x_t,t)\|_2 \, g_{\mathrm{update}},$$

$$p(x_{t-1}|x_t, \hat{x}, y) = \mathcal{N}(\mu_t, \Sigma_\theta(x_t,t)).$$

For a robust model, the only difference is that the cone projection is omitted and one uses $g_{\mathrm{proj}} = \nabla_{x_t} \log p_{\mathrm{robust},v}\big(y|f_{\mathrm{dn}}(x_t,t)\big)$. In all our experiments we use $C_c = 0.1$, and $C_d = 0.15$ unless we show ablations for one of the parameters. The angle α for the cone projection is fixed to $30°$. In strong contrast to Blended Diffusion, these parameters generalize across images and even classifiers and allow us to generate VCEs for arbitrary classifiers for which a diffusion model is available.

4 Experiments

In this section, we evaluate the quality of the DVCE. We start by comparing DVCE to existing works in Sec. 4.1. In Sec. 4.2, we compare DVCEs for various state-of-the-art ImageNet models and show how our method can be used to interpret differences between classifiers. For all experiments, we use the same set of hyperparameters for DVCE given in the last section without any further hyperparameter tuning. The diffusion model used for DVCE is taken from [15], is trained class-unconditionally on ImageNet images of size 256x256, and uses a modified UNet[41] architecture (more details in [15]). User study, further experiments, ablations, and details are in the Appendix.

4.1 Method comparison

We compare DVCEs with VCEs produced by Blended Diffusion [2] and recent method for VCEs based purely on optimization [7]. As the latter only works for adversarially robust classifiers, we use the multiple-norm robust model from [7], MNR-RN50, as the classifier to create VCEs for all three methods. As this model is robust on its own, we do not use the cone projection for its DVCEs.

First, we present a qualitative evaluation in Fig. 4, where we transform one image into two different classes that are close to the true one in the WordNet hierarchy[34]. The radius of the $l_{1.5}$-ball of [7]

Original	Target class 1			Target class 2		
	DVCE (ours)	$l_{1.5}$-SVCEs [7]	Blended Diff. [2]	DVCE (ours)	$l_{1.5}$-SVCEs [7]	Blended Diff [2]
mashed potato: 0.25	guacamole: 1.00	guacamole: 0.91	guacamole: 0.90	carbonara: 1.00	carbonara: 0.95	cabronara: 0.99
cheetah: 1.00	leopard: 0.96	leopard: 0.90	leopard: 0.39	tiger: 1.00	tiger: 0.97	tiger: 0.94
cheesburger: 0.54	pizza: 1.00	pizza: 1.00	pizza: 0.94	potpie: 0.99	potpie: 0.90	potpie: 0.82
hognose snake: 0.49	king snake: 1.00	king snake: 0.98	king snake: 0.98	night snake: 0.71	night snake: 0.82	night snake: 0.47
dingo: 0.85	timber wolf: 0.98	timber wolf: 0.97	timber wolf: 0.77	white wolf: 0.98	white wolf: 0.97	white wolf: 0.92
promontory: 0.66	alp: 1.00	alp: 0.90	alp: 0.82	volcano: 1.00	volcano: 0.99	volcano: 0.96

Figure 4: Comparison of different VCE-methods for the robust MNR-RN50 (taken from [7]). We show for each target class our DVCEs (left column), the $l_{1.5}$-SVCEs of [7] (middle), and the adaptation of Blended Diffusion [2] for VCEs (right). For each original image (outer left column) we show the VCEs for two target classes. See the text for the parameter selection of all methods. Only DVCEs satisfy all desired properties of VCEs. Blended Diffusion fails for leopard and tiger and often produces images far away from the original one (pizza, potpie, timber wolf, white wolf, and alp). $l_{1.5}$-SVCEs show artefacts (white wolf, volcano, night snake) and have often lower image quality.

is chosen as the smallest $r \in \{50, 75, 100, 150\}$ such that the confidence in the target class is larger than 0.90 per image. For Blended Diffusion, we select the image with the smallest classifier and regularization weight that reaches confidence larger than 0.9 from the set of parameters discussed in Sec. 3.3. If 0.9 is not reached by any setting, we show the one with the highest confidence for both baselines. As Fig. 4 shows, DVCEs is the only method that satisfies all desired properties of VCEs. For example, for "mashed potato", DVCE preserves the bowl and only changes the content into either guacamole or carbonara. Our qualitative comparison shows that the same hyperparameter setting of DVCE can handle different classes and transfer between similar classes, such as different snakes or wolf types, as well as different object sizes.

In contrast, both $l_{1.5}$-SVCEs and Blended Diffusion VCEs require different hyperparameters for different images to achieve high confidence in the target class. Even with the six parameter configurations, Blended Diffusion is not able to produce always images with high confidence in the target class. More problematic for VCEs is that the resulting images can have high confidence but not look realistic (cheetah $\rightarrow$ tiger) or do not resemble the original image at all (dingo $\rightarrow$ timber wolf/white wolf). Even if the method works with the given parameters, for example, mashed potato $\rightarrow$ guacamole or carbonara, the overall image quality cannot match that of DVCE as often the images contain overly bright colors. In the case of the volcano VCE, DVCE shows class features like lava whereas Blended Diffusion VCE can not clearly be labeled as a volcano. For the $l_{1.5}$-SVCEs, one often needs large radii to achieve the desired confidence of 0.90, which often results in images that do not look realistic.

For further comparison of VCEs, we provide in Tab. 1 the quantitative evaluation of realism, validity, and closeness, where we discuss the results. As in [7] the authors noticed that there is a risk of having low FID scores for the VCEs that do not change the starting images significantly, we propose the simple "crossover" evaluation of FID and other metrics, such that the distribution of labels of original images is different from the distribution of the target classes for VCEs (more details are in App. E).

Moreover, we have conducted a user study (20 users), in which participants have decided, what are the percentage of total images to have one of the three different properties (numbers for 3 methods sorted in the same order as in Tab. 1): **meaningful** - **62.0%**, 48.4%, 38.7%; **realism** - 34.7%, 24.6%, **52.2%**; **subtle** - 45.0%, **50.6%**, 31.0%. This confirms that DVCEs generate more meaningful features in the target classes. More details are in App. C.

Metric	Closeness				Validity	Realism
	$l_1 \downarrow$	$l_{1.5} \downarrow$	$l_2 \downarrow$	LPIPS-Alex $\downarrow$	Mean Conf. $\uparrow$	Avg. FID $\downarrow$
DVCEs (ours)	12799	293	48	0.35	0.932	**17.6**
$l_{1.5}$-SVCEs[7]	**5139**	**139**	**26**	**0.20**	**0.945**	25.6
Blended Diffusion[2]	35678	722	108	0.58	0.825	27.9

Table 1: Quantitative evaluation of VCEs. DVCEs outperform Blended Diffusion [2] VCEs in all metrics. Moreover, they achieve comparable to $l_{1.5}$-SVCEs Mean Conf. (validity), while outperforming them significantly in Avg. FID. (realism) but do larger changes to the image than SVCE (closeness).

4.2 Model comparison

Non-robust models. In Fig. 5 we show that DVCEs can be generated for various state-of-the-art ImageNet [42] models. We use a Swin-Transformer[29], a ConvNeXt [30] and a Noisy-Student EfficientNet [58, 54]. Both the Swin-Transformer and the ConvNeXt are pretrained on ImageNet21k [14] whereas the EfficientNet uses noisy-student self-training on a large unlabeled pool. As all models do not yield perceptually aligned gradients, we use the cone projection with $30°$ angle described in Sec. 3.2 with the robust model from the previous section. All other parameters are identical to the previous experiment. We highlight that DVCE is the first method capable of explaining (in the sense of VCEs) arbitrary classifiers on a task as challenging as ImageNet. Overall, DVCEs satisfy all desired properties of VCEs. It also allows us to inspect the most important features of each model and class. For the stupa and church classes, for example, it seems like all models use different roof and tower structures as the most prominent feature as they spent most of their budget on changing those.

Robust models. Here, we want to examine the influence of the different architectures that were trained robustly as in [12] on the resulting DVCEs. There, the authors take inspiration from the result for linear classifiers in Theorem 3.1[11], which states that when such a classifier is robust with respect to the l_1- and l_∞-balls, it is robust also in the largest l_p ball, which fits in the convex hull for any $1 \leq p \leq \infty$. This motivated them further to devise an adversarial training scheme that with some probability performs for each batch either l_1- or l_∞-attack and yields classifiers more adversarially robust for all $1 \leq p \leq \infty$. We will call this scheme multiple-norm robust finetuning. For models trained in such a way, [7] have shown that the generated VCEs are better (both in terms of FID and qualitatively) if generated with respect to a sparse norm, such as $l_{1.5}$. While our DVCEs are biased by the l_1 regularization, we do not have hard constraints in any l_p-norm. Thus, we decide to use multiple-norm robust models to be robust to a broad range of perturbation

Original	Target Class 1			Target Class 2		
	Swin-Transformer	ConvNeXt	EfficientNet	Swin-Transformer	ConvNeXt	EfficientNet
loggerhead	leatherback: 0.93	leatherback: 0.99	leatherback: 0.99	box turtle: 0.97	box turtle: 0.99	box turtle: 0.99
black and golden garden spider	black widow: 0.95	black widow: 0.99	black widow: 1.00	tarantula: 0.99	tarantula: 1.00	tarantula: 1.00
sea urchin	sea cucumber: 0.98	sea cucumber: 0.99	sea cucumber: 0.99	starfish: 0.98	starfish: 0.99	starfish: 0.98
hen of the woods	agaric: 0.93	agaric: 1.00	agaric: 0.98	gyromitra: 0.96	gyromitra: 0.99	gyromitra: 1.00
lorikeet	macaw: 0.99	macaw: 0.99	macaw: 0.99	african grey: 0.98	african grey: 0.99	african grey: 0.99
mosque	stupa: 0.98	stupa: 0.98	stupa: 1.00	church: 0.99	church: 0.99	church: 0.98
red wolf	coyote: 0.99	coyote: 1.00	coyote: 1.00	timber wolf: 0.99	timber wolf: 0.99	timber wolf: 1.00

Figure 5: DVCEs for three non-robust classifiers: Swin-Transformer[29] , ConvNeXt[30] and EfficientNet[58]. For each original image (outer left column) we show DVCEs into two target classes. Please zoom into the images to see more fine-grained details and differences.

types. For this, we compare in Fig. 6 multiple-norm (MNR) fine-tuned models : MNR-RN50 based on a l_2-robust ResNet50 [17], MNR-XCiT based on a l_∞-robust ViT [13] and MNR-DeiT based on a robust data-efficient image transformer [5]. It can be seen here that all the models that use multiple-norm robust finetuning have equally good DVCEs, each of which provides slightly different explanations. More examples and further experiments are in App. B.4.

Original	Target Class 1			Target Class 2		
	MNR-RN50	MNR-XCiT	MNR-DeiT	MNR-RN50	MNR-XCiT	MNR-DeiT
pirate ship	liner ship: 1.00	liner ship: 1.00	liner ship: 1.00	container ship: 1.00	container ship: 1.00	container ship: 1.00
mashed potato	dough: 1.00	dough: 1.00	dough: 1.00	carbonara: 1.00	carbonara: 1.00	carbonara: 1.00

Figure 6: We compare DVCEs for three different robust models (no cone projection) which are all fine-tuned to be multiple-norm adversarially robust [12], that is against l_1, l_2 and l_∞-perturbations. More examples can be found in Fig. 10.

5   Limitations, Future Work and Societal impact

In comparison to GANs, diffusion-based approaches can be expensive to evaluate as they require multiple iterations of the reverse process to create one sample. This can be an issue when creating a large amount of VCEs and makes deployment in a time-sensitive setting challenging.

We also rely on a robust model during the creation of VCEs for the cone projection. While we show that standard classifiers do not yield the desired gradients, training robust models can be challenging. An interesting direction for future research is thus to replace the cone projection with another "denoising" procedure for the gradient of a non-robust model.

From a theoretical standpoint, using conditional sampling with reverse transitions of the form (8) is justified, in practice, however, we have to approximate the reverse transitions with shifted normal distributions of the form (10). This approximation relies on the conditioning function having low curvature, and it can be hard to verify this once we start adding a classifier, distance and other possible terms and it is unclear how this influences the outcome of the diffusion process.

The quantitative evaluation of VCEs is difficult, as the standard FID metric compares the distribution of features of a classifier over a test and a generated dataset. However, for VCEs it is not only important to generate realistic images, but also to achieve high confidence and to create meaningful changes. Moreover, metrics such as IM1, IM2 [31] for VCEs rely on a well-trained (V)AE for every class, which is difficult to achieve for a dataset with 1000 classes and high-resolution images. Future research should therefore try to develop metrics for the quantitative evaluation of VCEs and we think that the evaluation in Tab. 1 is the first step in that direction.

DVCEs and VCEs in general help to discover biases of the classifiers and thus have a positive societal impact, however one can abuse them for unintended purposes as any conditional generative model.

6   Conclusion

We have proposed DVCEs, a novel way to create VCEs for any state-of-the-art ImageNet classifier using diffusion models and our cone projection. DVCEs can handle vastly different image configurations, object sizes, and classes and satisfy all desired properties of VCEs.

Acknowledgement

M.H. and V.B. acknowledge support by the DFG Excellence Cluster Machine Learning - New Perspectives for Science, EXC 2064/1, Project number 390727645.

References

[1] Maximilian Augustin, Alexander Meinke, and Matthias Hein. Adversarial robustness on in- and out-distribution improves explainability. In *ECCV*, 2020.

[2] Omri Avrahami, Dani Lischinski, and Ohad Fried. Blended diffusion for text-driven editing of natural images. In *CVPR*, 2022.

[3] Sebastian Bach, Alexander Binder, Frederick Klauschen Gregoire Montavon, Klaus-Robert Müller, and Wojciech Samek. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PLoS One*, 2015.

[4] David Baehrens, Timon Schroeter, Stefan Harmeling, Motoaki Kawanabe, Katja Hansen, and Klaus-Robert Müller. How to explain individual classification decisions. *JMLR*, 2010.

[5] Yutong Bai, Jieru Mei, Alan Yuille, and Cihang Xie. Are transformers more robust than cnns? In *NeurIPS*, 2021.

[6] Solon Barocas, Andrew D. Selbst, and Manish Raghavan. The hidden assumptions behind counterfactual explanations and principal reasons. In *FAT*, 2020.

[7] Valentyn Boreiko, Maximilian Augustin, Francesco Croce, Philipp Berens, and Matthias Hein. Sparse visual counterfactual explanations in image space. *arXiv preprint, arXiv:2205.07972*, 2022.

[8] Chun-Hao Chang, Elliot Creager, Anna Goldenberg, and David Duvenaud. Explaining image classifiers by counterfactual generation. In *ICLR*, 2019.

[9] Jooyoung Choi, Sungwon Kim, Yonghyun Jeong, Youngjune Gwon, and Sungroh Yoon. Ilvr: Conditioning method for denoising diffusion probabilistic models. *ICCV*, 2021.

[10] EU Commission. Regulation for laying down harmonised rules on AI. *European Commission*, 2021.

[11] Francesco Croce and Matthias Hein. Provable robustness against all adversarial l_p-perturbations for $p \geq 1$. In *ICLR*, 2020.

[12] Francesco Croce and Matthias Hein. Adversarial robustness against multiple l_p-threat models at the price of one and how to quickly fine-tune robust models to another threat model. *arXiv preprint, arXiv:2105.12508*, 2021.

[13] Edoardo Debenedetti. Adversarially robust vision transformers. Master's thesis, Swiss Federal Institue of Technology, Lausanne (EPFL), 2022.

[14] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: a large-scale hierarchical image database. *CVPR09*, 2009. License: No license specified.

[15] Prafulla Dhariwal and Alex Nichol. Diffusion models beat gans on image synthesis. In *NeurIPS*, 2021.

[16] Amit Dhurandhar, Pin-Yu Chen, Ronny Luss, Chun-Chen Tu, Paishun Ting, Karthikeyan Shanmugam, and Payel Das. Explanations based on the missing: Towards contrastive explanations with pertinent negatives. In *NeurIPS*, 2018.

[17] Logan Engstrom, Andrew Ilyas, Hadi Salman, Shibani Santurkar, and Dimitris Tsipras. Robustness (python library), 2019. License: MIT.

[18] Christian Etmann, Sebastian Lunz, Peter Maass, and Carola-Bibiane Schönlieb. On the connection between adversarial robustness and saliency map interpretability. In *ICML*, 2019.

[19] Yash Goyal, Ziyan Wu, Jan Ernst, Dhruv Batra, Devi Parikh, and Stefan Lee. Counterfactual visual explanations. In *ICML*, 2019.

[20] Lisa Anne Hendricks, Zeynep Akata, Marcus Rohrbach, Jeff Donahue, Bernt Schiele, and Trevor Darrell. Generating visual explanations. In *ECCV*, 2016.

[21] Lisa Anne Hendricks, Ronghang Hu, Trevor Darrell, and Zeynep Akata. Grounding visual explanations. In *ECCV*, 2018.

[22] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *NeurIPS*, 2017.

[23] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. In *NeurIPS 2021 Workshop on Deep Generative Models and Downstream Applications*, 2021.

[24] Pieter Abbeel Jonathan Ho, Ajay Jain. Denoising diffusion probabilistic models. In *NeurIPS*, 2020.

[25] Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of StyleGAN. In *Proc. CVPR*, 2020.

[26] Saeed Khorram and Li Fuxin. Cycle-consistent counterfactuals by latent transformations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

[27] Oran Lang, Yossi Gandelsman, Michal Yarom, Yoav Wald, Gal Elidan, Avinatan Hassidim, William T. Freeman, Phillip Isola, Amir Globerson, Michal Irani, and Inbar Mosseri. Explaining in style: Training a gan to explain a classifier in stylespace. *ICCV*, 2021.

[28] Xihui Liu, Dong Huk Park, Samaneh Azadi, Gong Zhang, Arman Chopikyan, Yuxiao Hu, Humphrey Shi, Anna Rohrbach, and Trevor Darrell. More control for free! image synthesis with semantic diffusion guidance. *CoRR*, 2021.

[29] Ze Liu, Fand Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *ICCV*, 2021.

[30] Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A convnet for the 2020s. *arXiv preprint, arXiv:2201.03545*, 2022.

[31] Arnaud Looveren and Janis Klaise. Interpretable counterfactual explanations guided by prototypes. *arXiv preprint, arXiv:1907.02584*, 2019.

[32] Scott M. Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *NeurIPS*, 2017.

[33] Calvin Luo. Understanding diffusion models: A unified perspective. *arXiv preprint, arXiv:2208.11970*, 2022.

[34] George A. Miller. Wordnet: A lexical database for english. *Commun. ACM*, 1995.

[35] Tim Miller. Explanation in artificial intelligence: Insights from the social sciences. *Artificial Intelligence*, 2019.

[36] Ramaravind K. Mothilal, Amit Sharma, and Chenhao Tan. Explaining machine learning classifiers through diverse counterfactual explanations. In *FAccT*, 2020.

[37] Alex Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. In *ICML*, 2021.

[38] Alex Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob McGrew, Ilya Sutskever, and Mark Chen. Glide: Towards photorealistic image generation and editing with text-guided diffusion models. *arXiv preprint, arXiv:2112.10741*, 2021.

[39] Nick Pawlowski, Daniel Coelho de Castro, and Ben Glocker. Deep structural causal models for tractable counterfactual inference. In *NeurIPS*, 2020.

[40] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should i trust you?": Explaining the predictions of any classifier. In *KDD*, 2016.

[41] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *MICCAI*, 2015.

[42] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *IJCV*, 2015. License: No license specified.

[43] Pouya Samangouei, Ardavan Saeedi, Liam Nakagawa, and Nathan Silberman. Explaingan: Model explanation via decision boundary crossing transformations. In *ECCV*, 2018.

[44] Shibani Santurkar, Dimitris Tsipras, Brandon Tran, Andrew Ilyas, Logan Engstrom, and Aleksander Madry. Image synthesis with a single (robust) classifier. In *NeurIPS*, 2019.

[45] Lisa Schut, Oscar Key, Rory McGrath, Luca Costabello, Bogdan Sacaleanu, Medb Corcoran, and Yarin Gal. Generating interpretable counterfactual explanations by implicit minimisation of epistemic and aleatoric uncertainties. In *AISTATS*, 2021.

[46] Kathryn Schutte, Olivier Moindrot, Paul Hérent, Jean-Baptiste Schiratti, and Simon Jégou. Using stylegan for visual interpretability of deep learning models on medical images. In *NeurIPS Workshop "Medical Imaging Meets NeurIPS"*, 2020.

[47] Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. *International Journal of Computer Vision*, 2019.

[48] Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. In *ICLR*, 2014.

[49] Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *ICML*, 2015.

[50] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *ICLR*, 2021.

[51] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *ICLR*, 2021.

[52] Suraj Srinivas and François Fleuret. Full-gradient representation for neural network visualization. In *NeurIPS*, 2019.

[53] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

[54] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *ICML*, 2019.

[55] Sahil Verma, John P. Dickerson, and Keegan Hines. Counterfactual explanations for machine learning: A review. *arXiv preprint, arXiv:2010.10596*, 2020.

[56] Sandra Wachter, Brent Mittelstadt, and Chris Russell. Counterfactual explanations without opening the black box: Automated decisions and the GDPR. *Harvard Journal of Law & Technology*, 2018.

[57] Zifan Wang, Haofan Wang, Shakul Ramkumar, Matt Fredrikson, Piotr Mardziel, and Anupam Datta. Smoothed geometry for robust attribution. In *NeurIPS*, 2020.

[58] Qizhe Xie, Minh-Thang Luong, Eduard Hovy, and Quoc V. Le. Self-training with noisy student improves imagenet classification. In *CVPR*, 2020.

[59] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *CVPR*, pages 586–595, 2018.