Does Temporal Encoding Matter? Evidence from GRU-based Clinical Foundation Models

Marco Reed[* 1]   **Thomas Jodrell**[* 1 2]   **Payam Barnaghi**[1 2]

Abstract

Clinical foundation models for structured electronic health records handle temporal irregularity in varied ways, yet the impact of time encoding strategy on downstream performance remains poorly understood. While access to longer patient histories has been shown to improve predictive performance, there is no consensus on the consistent benefit of explicit time encoding in clinical foundation models. We train gated recurrent unit (GRU) models under five temporal encoding conditions, namely no encoding, discrete time tokens, learned projection, fixed sinusoidal encoding, and learned sinusoidal encoding on MIMIC-IV data, and evaluate downstream performance across six clinical prediction tasks. We find that the temporal encoding strategy has no significant impact on downstream performance, even for the patients with the longest sequence lengths and multiple historical visits. This implies that the ordering of data either sufficiently encodes temporal dependencies or that the dataset lacks the temporal diversity to realise the potential improvements from a deeper understanding of time. Our findings caution against assuming that richer time representations improve clinical prediction, and motivate evaluation on datasets with greater temporal heterogeneity.

1. Introduction

Clinical foundation models trained with self-supervised objectives on electronic healthcare record (EHR) data have shown versatility in their performance on a number of downstream prediction tasks, such as hospital readmission and mortality prediction (Steinberg et al., 2021; Renc et al., 2024; Shmatko et al., 2025; Kraljevic et al., 2024). These models are trained on structured medical event sequences including diagnoses, medications, procedures, and laboratory results, embedding clinical information into patient representations that support downstream predictive tasks.

The best performing variants adapt language model architectures to medical event sequences, making use of the sequential and discrete nature of structured medical events. However, unlike natural language, medical events occur at highly irregular intervals spanning minutes to years, the length of which alters the clinical meaning of those events. To address this, early recurrent approaches incorporated time decays based on elapsed time to down-weight old information (Che et al., 2018), while a more recent GRU-based model, CLMBR, concatenated multidimensional temporal features onto input feature vectors (Guo et al., 2023). Similarly, transformer-based architectures have experimented with discrete time gap tokens (Renc et al., 2024), sinusoidal elapsed-time embeddings (Shmatko et al., 2025), and continuous value embeddings (Tipirneni & Reddy, 2022). The incorporation of time in all of these models is motivated by the assumed information content of the irregular intervals.

Despite the proliferation of these methods, there is no consensus on the most effective time condition or whether explicit time encoding is necessary at all. While transformers with extended context windows have shown improvements in downstream predictive tasks (Wornow et al., 2025), recent evidence suggests that explicit temporal tokenisation may be redundant for transformer-based performance on mortality and readmission predictions (Attrach et al., 2025). It remains unclear whether this redundancy is a feature of input sequence length, attention-based approaches, or is inherent to the specific evaluation tasks on EHR data. To disentangle these factors, we employ a GRU architecture, which has been shown to perform within a narrow margin of transformers on clinical prediction tasks (Tipirneni & Reddy, 2022). This allows us to test whether the null result generalises beyond attention-based models, and to systematically vary input sequence length across the full patient timeline, something transformers are poorly suited to given

---
[*]Equal contribution [1]Department of Brain Sciences, Imperial College London, London, UK [2]Care, Research & Technology (CR&T) Centre, UK Dementia Research Institute, London, UK. Correspondence to: Marco Reed <marco.reed24@imperial.ac.uk>, Thomas Jodrell <thomas.jodrell24@imperial.ac.uk>, Payam Barnaghi <p.barnaghi@imperial.ac.uk>.

Proceedings of the Workshop on Structured Data for Health at the 43^{rd} International Conference on Machine Learning, Seoul, South Korea. Copyright 2026 by the author(s).

their practical context window constraints (Vaswani et al., 2017).

2. Methods

2.1. Data and Pre-training

Hospital electronic health record data from MIMIC-IV (Johnson et al., 2024) were used for this study. Data were processed into Medical Event Data Standard (MEDS) (McDermott et al., 2025) using a modified version of the MEDS Transform pipeline (Vector Institute, 2024).

Medical codes at each time step were embedded via a learned embedding layer of dimension $d = 128$ and mean-pooled across codes to produce a single event vector per hour, as in (Tipirneni & Reddy, 2022), and padding tokens were excluded from the pool. In three of the five temporal encoding strategies this event vector was then added to a temporal encoding before being passed to the recurrent encoder. Patients with fewer than five hourly time steps were removed from training.

All models were pre-trained on a next-event prediction objective, structured as a multi-label binary classification task over the entire medical event vocabulary. Given sequences of events up to a randomly sampled anchor point within a patient's record, the models were tasked with predicting the events appearing in the next 24-hour window. During training, five evaluation anchor points were randomly sampled per patient, and were restricted to contain at least five hour-long bins of medical information.

2.2. Model Architecture

The GRU had a hidden dimension of 256, two layers, and a dropout proportion of 0.2. All models were trained for 10 epochs using the AdamW optimiser and a cosine annealing learning rate schedule. The initial learning rate and evaluation window size were selected via 20 trials of hyperparameter tuning (details shown in A.1), with the optimal hyperparameters chosen according to the best precision@10 and recall@10 performance on the validation set.

2.3. Temporal Encoding Strategies

We compared four strategies for explicitly incorporating time into the event representations against a baseline model without time encoding. In all cases, the core architecture was held constant, with only the time encoding module changing.

Discrete time tokens: Taking inspiration from the ETHOS framework (Renc et al., 2024), we encoded temporal gaps directly as events in the patient event stream by inserting discrete `TIME//N` tokens at inter-event gaps. The con-

tinuous inter-event duration was quantised into one of 10 variable-width buckets (Appendix 2).

Sinusoidal encoding: Building on the Delphi architecture (Shmatko et al., 2025), we evaluated sinusoidal time embeddings, extending their work by encoding two temporal features per time step: elapsed hours since the first recorded event (t_{elapsed}) and hours since the previous event (t_δ). These times were mapped to a d-dimensional embedding using a frequency bank initialised geometrically between $2\pi/T_{\max}$ and $2\pi/T_{\min}$ ($T_{\min} = 1$h, $T_{\max} = 87{,}600$h). For a given time t, the d-dimensional embedding $\mathbf{s}(t)$ was constructed as:

$$\mathbf{s}(t) = \big[\sin(\omega_1 t), \ldots, \sin(\omega_{d/2} t),$$
$$\cos(\omega_1 t), \ldots, \cos(\omega_{d/2} t)\big] \in \mathbb{R}^d \tag{1}$$

Embeddings from both features were summed into the token embedding at each time step before being passed to the GRU. We evaluated two variants: *fixed* frequencies, which remained constant throughout training, and *learnable* frequencies following Xu et al. (2019), where the log-frequencies $\mathbf{f} \in \mathbb{R}^{d/2}$, from which $\boldsymbol{\omega} = \exp(\mathbf{f})$, were optimised jointly with the model, allowing it to discover clinically relevant timescales such as circadian ($\sim$24h) or weekly ($\sim$168h) rhythms. In the learnable variant, frequencies were constrained to remain strictly positive by storing them in log-space and applying a softplus transformation at runtime, preventing degenerate zero or negative frequencies during optimisation.

Learned projection encodings: The log-scaled time features were combined $\boldsymbol{\tau} = \big[\log(1 + t_{\text{elapsed}}), \log(1 + t_\delta)\big]$ and projected into the embedding space via a learned linear layer $W \in \mathbb{R}^{d \times 2}$:

$$\mathbf{p}(\boldsymbol{\tau}) = W \, \boldsymbol{\tau}^{\boldsymbol{T}} \tag{2}$$

The resulting projection was added element-wise to the medical event vector.

2.4. Clinical Evaluation

Next-event prediction: Models were evaluated based on their ability to predict a set of clinical codes occurring within a 24-hour window of a randomly sampled anchor point. We report Recall@k and Precision@k, where Recall@k measures the proportion of events in the 24-hour window retrieved in the top k predictions and Precision@k measures the fraction of the top k predictions that occurred in the window.

Downstream clinical tasks: Following the approach of CLIMBR (Steinberg et al., 2021), the final hidden state from the GRU was extracted as a frozen patient representation, and was used as the input to logistic regression (LR) and random forest (RF) models to predict six binary clinical tasks. These tasks included predicting three in-visit

outcomes, namely mortality, emergency department (ED) admission, and intensive care unit (ICU) admission, from the first 48 hours of the data from the current visit and all preceding patient data. The other three tasks considered all the data up to the discharge of the randomly chosen visit and involved predicting either the 30-day readmission to the hospital, ED, or ICU. As an ablation study, all six tasks were additionally re-evaluated using only data from the current visit, and separately using only data from before the current visit.

2.5. Time Token Embedding Analysis

To verify that discrete time tokens had learned meaningful temporal representations, we analysed the geometry of the learned time token embeddings. Principal component analysis (PCA) was applied to the ten 128-dimensional time token embeddings to explore whether the two dimensional representations of these embeddings show a clear temporal ordering. We additionally computed pairwise cosine similarity between all time token embeddings to assess whether tokens representing similar elapsed-time intervals occupied similar regions of the embedding space.

2.6. Statistical Analysis

Statistical significance was assessed using paired two-sided Wilcoxon signed-rank tests comparing each time-aware condition against the time-unaware baseline, with Holm–Bonferroni correction for multiple comparisons across tasks and metrics.

3. Results

3.1. Next-Event Prediction

Performance on the pre-training objective is summarised in Table 1. The no-time baseline achieved the highest recall@10 (37.9%) and precision@10 (38.7%) of all five conditions. This dominance was consistent across all values of k from 1 to 10.

Table 1. **Recall and precision@10 for each time encoding strategy on the next-event prediction task.** The best performing set of hyperparameters was used for each approach.

Model	Recall@10	Precision@10
Baseline (no explicit time)	**37.9%**	**38.7%**
Learned projections	33.6%	35.0%
Time tokens	32.5%	34.9%
Sinusoidal (learnt)	20.8%	20.1%
Sinusoidal (fixed)	19.7%	18.4%

Figure 1. **Time tokens encode ordered representations of time. A)** Principal component analysis projection of time token embeddings coloured by sequence order (purple = shortest interval, yellow = longest interval). Time tokens span intervals from 2 hours to 11 years. Bin time boundaries are given in Appendix A2. **B)** Pairwise cosine similarity between time token embedding vectors. Tokens are ordered by increasing elapsed time interval.

3.2. Exploring Time Token Embedding Properties

To verify that the model was learning meaningful representations of time, we analysed the feature-space geometry of the time token embeddings learned during training.

Figure 1(A) shows that the projection across the two top principal components showed a generally sequential ordering from the shortest (2-5 hours) to the longest (3,600-103,794 hours) bins. The cosine similarity between time token embeddings was highest between temporally adjacent tokens, dropping off beyond immediate neighbours (Figure 1B). Additionally, the first three bins show a high level of cosine similarity, this is explained by these tokens corresponding to event spacings of below 24 hours, a highly clinically meaningful timescale.

Figure 2. **Downstream Performance of GRU foundation model final embeddings on clinical prediction tasks under different time encoding conditions.** Comparison of AUROC and AUPRC (mean across 10 seeds ± 95% confidence interval) across six clinical prediction tasks. All historical events preceding the randomly chosen evaluation visit are included. Prevalences for each task are shown in parentheses following the task name above each collection of Global, Short (first token length quartile) and Long (fourth token length quartile) sequence length results.

3.3. Downstream Clinical Tasks

Figure 2 shows the AUROC (area under the receiver operating characteristic curve) and AUPRC (area under the precision-recall curve) scores for all six clinical tasks stratified by length of sequence. After Holm–Bonferroni correction, all time-aware conditions were statistically indistinguishable to the no-time baseline. This held across all downstream tasks and across both the shortest and longest sequence quartiles.

4. Discussion

Temporal encoding did not show a meaningful improvement on the pre-training objective or downstream clinical prediction performance in this GRU-based EHR foundation model. This result persisted across four time encoding conditions in six clinical prediction tasks, and across sequence length quartiles. The finding is consistent with a prior null result in transformer models (Attrach et al., 2025), and extends to a recurrent architecture, suggesting that the redundancy of temporal encoding is not specific to attention-based models. Additionally, our mechanistic analysis confirms that the

model does successfully learn structured temporal representations, narrowing the explanation to a lack of utilisation rather than an encoding failure.

The no-time baseline outperformed all time conditions on the pre-training objective across all values of k, suggesting that added time features may actively degrade performance on the pre-training task. This may be explained by the dominance in importance of the most recent events in the pre-training task, such that the deeper encoding of historical event timing introduces noise into the hidden state rather than useful context. Given that recent events may dominate the hidden state and mask the utility of temporal encoding, we performed an ablation in which all current-visit data was excluded leaving only pre-admission data (Appendix 6). This found that adding time encoding did not meaningfully improve performance on the clinical prediction tasks, implying that the no-time baseline already captures equally useful medical information from the token order and prevalence alone.

These findings could be partly explained by the dataset characteristics. MIMIC-IV is a high-density critical care

dataset with most events occurring within the one-hour time bin following the previous event (Appendix A.2) meaning the diversity of temporal information is limited to short bursts of activity.

However, despite the limited temporal heterogeneity in the dataset, analysis of discrete time token embeddings confirmed that the model did have sufficient training signal to learn structured temporal representations. There was a clear sequential ordering in the geometry of the embedding PCA projections (Figure 1) and the pairwise cosine similarity analysis showed a similar chronological ordering. Together, these results indicate the failure of temporal encoding to improve model performance is not due to a failure to learn temporal structure, but instead that this structure is not being exploited in downstream tasks.

Whether the lack of utility of explicit temporal encoding reflects a limitation in recurrent architectures in propagating long-range temporal signal or simply that the evaluation tasks do not require such temporal information to perform well remains an open question. Future work should prioritise temporally heterogenous datasets and longer-horizon tasks designed to reward an understanding of time to establish conditions under which time encoding becomes necessary.

Impact Statement

This paper presents work whose goal is to advance the field of EHR based foundation models by exploring the impact that time encodings can have on prediction performance. By identifying the limitations of current approaches, we hope to motivate future work towards more effective use of temporal information in clinical prediction. This work has potential applications in areas outside the healthcare sector, none of which, we feel, must be specifically highlighted here.

Funding Source

The project is funded by the UKRI award for the AI Centre for Doctoral Training in Digital Healthcare (grant number EP/Y030974/1). P.B. is also funded by the Royal Academy of Engineering and Great Ormond Street Hospital (grant number: RCSRF2324-18-69). The funders were not involved in the study design, data collection, data analysis or writing of the manuscript.

Conflicts of Interest

All authors declare no financial or non-financial competing interests.

References

Attrach, R. A., Fani, R., Restrepo, D., Jia, Y., and Schüffler, P. Rethinking Tokenization for Clinical Time Series: When Less is More, December 2025. URL http://arxiv.org/abs/2512.05217. arXiv:2512.05217 [cs].

Che, Z., Purushotham, S., Cho, K., Sontag, D., and Liu, Y. Recurrent Neural Networks for Multivariate Time Series with Missing Values. *Scientific Reports*, 8(1): 6085, April 2018. ISSN 2045-2322. doi: 10.1038/s41598-018-24271-9. URL https://www.nature.com/articles/s41598-018-24271-9.

Guo, L. L., Steinberg, E., Fleming, S. L., Posada, J., Lemmon, J., Pfohl, S. R., Shah, N., Fries, J., and Sung, L. EHR foundation models improve robustness in the presence of temporal distribution shift. *Scientific Reports*, 13 (1):3767, March 2023. ISSN 2045-2322. doi: 10.1038/s41598-023-30820-8. URL https://www.nature.com/articles/s41598-023-30820-8.

Johnson, A., Bulgarelli, L., Pollard, T., Gow, B., Moody, B., Horng, S., Celi, L. A., and Mark, R. MIMIC-IV. *PhysioNet*, October 2024. doi: 10.13026/kpb9-mt58. URL https://doi.org/10.13026/kpb9-mt58. Version 3.1.

Kraljevic, Z., Bean, D., Shek, A., Bendayan, R., Hemingway, H., Yeung, J. A., Deng, A., Balston, A., Ross, J., Idowu, E., Teo, J. T., and Dobson, R. J. B. Foresight—a generative pretrained transformer for modelling of patient timelines using electronic health records: a retrospective modelling study. *The Lancet Digital Health*, 6(4):e281–e290, April 2024. ISSN 2589-7500. doi: 10.1016/S2589-7500(24)00025-6. URL https://www.thelancet.com/journals/landig/article/PIIS2589-7500(24)00025-6/fulltext.

McDermott, M. B. A., Xu, J., Bergamaschi, T. S., Jeong, H., Lee, S. A., Oufattole, N., Rockenschaub, P., Stankevičiūtundefined, K., Steinberg, E., Sun, J., Water, R. P. v. d., Wornow, M., Wu, J., and Wu, Z. Meds: Building models and tools in a reproducible health ai ecosystem. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, KDD '25, pp. 6243–6244, New York, NY, USA, 2025. Association for Computing Machinery. ISBN 9798400714542. doi: 10.1145/3711896.3737608. URL https://doi.org/10.1145/3711896.3737608.

Renc, P., Jia, Y., Samir, A. E., Was, J., Li, Q., Bates, D. W., and Sitek, A. Zero shot health trajectory prediction using transformer. *npj Digital Medicine*, 7(1):

256, September 2024. ISSN 2398-6352. doi: 10.1038/ s41746-024-01235-0. URL https://www.nature. com/articles/s41746-024-01235-0.

Shmatko, A., Jung, A. W., Gaurav, K., Brunak, S., Mortensen, L. H., Birney, E., Fitzgerald, T., and Gerstung, M. Learning the natural history of human disease with generative transformers. *Nature*, 647(8088):248–256, November 2025. ISSN 1476-4687. doi: 10.1038/ s41586-025-09529-3. URL https://www.nature. com/articles/s41586-025-09529-3.

Steinberg, E., Jung, K., Fries, J. A., Corbin, C. K., Pfohl, S. R., and Shah, N. H. Language models are an effective representation learning technique for electronic health record data. *Journal of Biomedical Informatics*, 113:103637, January 2021. ISSN 1532-0464. doi: 10.1016/j.jbi.2020.103637. URL https://www.sciencedirect.com/ science/article/pii/S1532046420302653.

Tipirneni, S. and Reddy, C. K. Self-supervised transformer for sparse and irregularly sampled multivariate clinical time-series. *ACM Trans. Knowl. Discov. Data*, 16(6), July 2022. ISSN 1556-4681. doi: 10.1145/3516367. URL https://doi.org/10.1145/3516367.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Vector Institute. MEDS transform odyssey branch. https://github.com/VectorInstitute/ meds/tree/odyssey, 2024. Accessed: 2026-01-25.

Wornow, M., Bedi, S., Hernandez, M. A. F., Steinberg, E., Fries, J. A., Re, C., Koyejo, S., and Shah, N. H. Context Clues: Evaluating Long Context Models for Clinical Prediction Tasks on EHRs, March 2025. URL http:// arxiv.org/abs/2412.16178. arXiv:2412.16178 [cs].

Xu, D., Ruan, C., Korpeoglu, E., Kumar, S., and Achan, K. Self-attention with functional time representation learning. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

A. Appendix

A.1. Hyperparameter Tuning

Hyperparameter tuning was performed using the Weights and Biases *Sweeps* method. Bayesian optimisation was used to select the next set of hyperparameters to test from a pre-specified range of possible values using validation loss as the performance metric. Twenty hyperparameter combinations were considered for each model. The learning rate range was from 10^{-2} to 10^{-4}, and the size of the prediction window was selected as 24 or 168 hours. Additionally, the weight decay for AdamW was set at 10^{-4}, and the number of evaluation anchors was set at five. For each encoding strategy the best performing model used a window size of 24 hours and the optimal learning rates tended towards the lower end of the learning rate range.

A.2. Distribution of Elapsed Times and Inter-event Time Gaps

Figure 3. **Distribution of temporal characteristics across the MIMIC-IV population.** (Left) Histogram of elapsed time in hours from each medical event to the start of the patient sequence. (Right) Histogram of inter-event gaps plotted on a log scale. Zero-duration intervals are excluded.

A.3. Time Token Binning Strategy

Table 2. Discrete time token bin boundaries. Elapsed time in hours is mapped to one of ten tokens based on the bin in which it falls.

Token	Elapsed time range (hours)
1	$2 - 5$
2	$6 - 11$
3	$12 - 23$
4	$24 - 95$
5	$96 - 215$
6	$216 - 455$
7	$456 - 839$
8	$840 - 1{,}678$
9	$1{,}680 - 3{,}599$
10	$3{,}600 - 103{,}794$

A.4. Recall and Precision @1, 5, and 10

For completeness, we provide the recall and precision @ 1, 5, and 10. As well as reporting the best results for each time encoding strategy, the bottom panels of Figure 4 show the mean and standard deviation of these metrics over all of the hyperparameter tuning runs to give a measure of the variability of the model performance.

Figure 4. **Performance of GRU foundation model for predicting tokens occurring within the next 24 hour window.** Mean and standard deviations (error bars) are reported over the hyperparameter tuning runs.

A.5. Downstream Performance When Truncating Medical History

This ablation study explores the relative performance of the different models when historical data from previous visits is removed. Therefore, the model is only fed the first 48 hours of the current hospital admission. The results are shown in Figure 5.

Figure 5. **Downstream Performance of GRU foundation model final embeddings under different time encoding conditions using only 48 hours of the current visit's data.** Comparison of AUROC and AUPRC (mean across 10 seeds ± 95% confidence interval) across six clinical prediction tasks. All historical events preceding the randomly chosen evaluation visit are removed to emulate the first presentation of the patient to the healthcare service.

Similarly to the results with historical visits included, the inclusion of time does not show a dramatic change in model performance. This is to be expected, as time information is likely most informative to the model when deciding the relevance of historical events, where distant events may be down-weighted, indicating the recovery from a medical condition. To explore this hypothesis a further ablation was considered where the model only receives historical medical data from previous visits, and attempts to predict whether events occur in, or following, the current visit.

A.6. Downstream Performance Only Including Medical History

This ablation study explores the relative performance of the different models when historical data from previous visits is included, but all information from the current visit is removed. This results in a larger cohort of eligible individuals, as there is no truncation due to potential data leakage, producing a much larger prevalence for the in-visit ED and ICU admission tasks. The results are shown in Figure 6.

Figure 6. **Downstream Performance of GRU foundation model final embeddings under different time encoding conditions with only prior-visit data.** Comparison of AUROC and AUPRC (mean across 10 seeds ± 95% confidence interval) across six clinical prediction tasks. All in-visit events within the randomly chosen evaluation visit are removed to emulate the presentation of the patient to the healthcare service with only their historical data available.

A.7. Raw Results

Table 3. Downstream clinical prediction performance (AUROC / AUPRC, mean ± 95% CI across 10 seeds) for all time encoding conditions, stratified by sequence length, using full patient history. Prevalence of the positive class in the global stratum is shown in parentheses.

Task	Condition	Global				Short (Q1)				Long (Q4)			
		AUROC	±	AUPRC	±	AUROC	±	AUPRC	±	AUROC	±	AUPRC	±
Mortality (4.0%)	No encoding	**0.918**	0.006	**0.429**	0.023	0.902	0.030	0.172	0.052	**0.890**	0.010	**0.437**	0.041
	Time tokens	0.917	0.006	0.379	0.035	**0.907**	0.032	0.183	0.058	0.884	0.008	0.388	0.054
	Learned	0.915	0.006	0.362	0.036	0.907	0.030	**0.189**	0.063	0.879	0.011	0.375	0.051
	Sinus. (fixed)	0.910	0.005	0.345	0.025	0.892	0.033	0.130	0.048	0.873	0.009	0.357	0.047
	Sinus. (learned)	0.903	0.006	0.336	0.030	0.862	0.032	0.142	0.070	0.867	0.008	0.358	0.046
ED in visit (0.4%)	No encoding	0.951	0.016	**0.701**	0.068	0.992	0.008	**0.915**	0.047	0.930	0.044	**0.616**	0.204
	Time tokens	0.938	0.022	0.691	0.069	0.985	0.011	0.890	0.056	0.913	0.058	0.586	0.219
	Learned	0.952	0.015	0.662	0.083	**0.995**	0.004	0.894	0.082	0.919	0.057	0.586	0.219
	Sinus. (fixed)	0.948	0.012	0.682	0.067	0.988	0.011	0.869	0.087	0.921	0.046	0.609	0.205
	Sinus. (learned)	**0.953**	0.017	0.680	0.054	0.985	0.011	0.879	0.061	**0.940**	0.035	0.600	0.217
ICU in visit (5.8%)	No encoding	0.867	0.008	0.501	0.029	0.947	0.007	0.733	0.039	0.770	0.026	**0.222**	0.043
	Time tokens	**0.869**	0.008	**0.504**	0.027	**0.957**	0.006	**0.766**	0.033	0.753	0.021	0.187	0.039
	Learned	0.867	0.008	0.489	0.028	0.946	0.011	0.737	0.038	**0.777**	0.024	0.198	0.038
	Sinus. (fixed)	0.860	0.009	0.485	0.030	0.941	0.011	0.718	0.043	0.756	0.020	0.185	0.022
	Sinus. (learned)	0.854	0.007	0.483	0.034	0.937	0.012	0.718	0.045	0.751	0.024	0.200	0.042
Readmission 30d (9.3%)	No encoding	**0.760**	0.059	0.255	0.023	**0.744**	0.047	0.162	0.066	0.686	0.026	0.319	0.049
	Time tokens	0.751	0.060	0.258	0.031	0.717	0.032	0.160	0.067	0.681	0.025	0.324	0.046
	Learned	0.759	0.062	0.251	0.030	0.741	0.066	0.145	0.054	0.694	0.028	0.319	0.044
	Sinus. (fixed)	0.760	0.065	**0.261**	0.033	0.729	0.059	0.148	0.054	**0.697**	0.032	**0.330**	0.052
	Sinus. (learned)	0.757	0.064	0.259	0.030	0.736	0.065	**0.164**	0.071	0.693	0.029	0.323	0.044
ED 30d (10.1%)	No encoding	0.672	0.025	0.186	0.014	0.630	0.016	0.107	0.023	0.627	0.029	0.237	0.028
	Time tokens	0.674	0.025	0.189	0.013	0.625	0.013	0.103	0.020	0.625	0.026	0.236	0.027
	Learned	**0.678**	0.031	**0.193**	0.015	0.633	0.012	0.112	0.024	0.634	0.036	0.245	0.031
	Sinus. (fixed)	0.678	0.029	0.193	0.017	**0.638**	0.018	**0.113**	0.025	**0.637**	0.034	**0.249**	0.033
	Sinus. (learned)	0.675	0.030	0.187	0.013	0.637	0.016	0.110	0.021	0.626	0.037	0.232	0.029
ICU 30d (1.8%)	No encoding	**0.816**	0.037	0.093	0.016	0.823	0.054	0.073	0.057	0.721	0.027	0.117	0.023
	Time tokens	0.816	0.036	0.091	0.016	**0.826**	0.078	0.071	0.050	**0.726**	0.021	0.121	0.029
	Learned	0.811	0.033	**0.098**	0.019	0.825	0.057	0.068	0.054	0.716	0.020	**0.128**	0.031
	Sinus. (fixed)	0.815	0.040	0.090	0.019	0.817	0.089	**0.096**	0.057	0.717	0.025	0.117	0.026
	Sinus. (learned)	0.809	0.037	0.090	0.014	0.804	0.080	0.077	0.052	0.715	0.020	0.121	0.025

Table 4. Downstream clinical prediction performance (AUROC / AUPRC, mean ± 95% CI across 10 seeds) for all time encoding conditions, stratified by sequence length, using only admission data (no prior visit history). Prevalence of the positive class in the global stratum is shown in parentheses.

Task	Condition	Global				Short (Q1)				Long (Q4)			
		AUROC	±	AUPRC	±	AUROC	±	AUPRC	±	AUROC	±	AUPRC	±
Mortality (4.2%)	No encoding	**0.903**	0.007	**0.382**	0.018	0.852	0.053	0.168	0.061	0.869	0.008	**0.491**	0.019
	Time tokens	0.902	0.007	0.379	0.018	**0.860**	0.046	**0.180**	0.096	**0.870**	0.008	0.467	0.024
	Learned	0.896	0.008	0.335	0.016	0.860	0.028	0.095	0.047	0.862	0.009	0.457	0.016
	Sinus. (fixed)	0.887	0.008	0.326	0.013	0.779	0.058	0.094	0.050	0.853	0.007	0.416	0.014
	Sinus. (learned)	0.887	0.010	0.319	0.016	0.818	0.054	0.068	0.035	0.846	0.009	0.392	0.023
ED in visit (0.1%)	No encoding	0.840	0.036	0.007	0.002	0.905	0.070	0.045	0.067	0.744	0.050	0.011	0.005
	Time tokens	**0.872**	0.023	0.008	0.002	**0.939**	0.057	0.047	0.052	**0.823**	0.058	**0.015**	0.009
	Learned	0.856	0.038	**0.011**	0.006	0.923	0.102	**0.094**	0.105	0.771	0.057	0.015	0.012
	Sinus. (fixed)	0.849	0.031	0.010	0.006	0.868	0.071	0.010	0.006	0.776	0.038	0.014	0.008
	Sinus. (learned)	0.853	0.030	0.010	0.004	0.919	0.083	0.072	0.135	0.778	0.072	0.012	0.005
ICU in visit (6.2%)	No encoding	0.824	0.009	0.379	0.012	**0.863**	0.018	0.402	0.045	0.761	0.021	0.359	0.038
	Time tokens	**0.826**	0.008	**0.381**	0.017	0.862	0.015	**0.409**	0.033	**0.764**	0.020	0.358	0.044
	Learned	0.824	0.006	0.365	0.016	0.844	0.022	0.370	0.047	0.757	0.022	0.353	0.037
	Sinus. (fixed)	0.814	0.006	0.362	0.013	0.854	0.014	0.375	0.038	0.754	0.019	**0.363**	0.043
	Sinus. (learned)	0.806	0.007	0.340	0.008	0.830	0.021	0.328	0.032	0.746	0.014	0.334	0.036
Readmission 30d (9.4%)	No encoding	0.699	0.033	0.208	0.018	0.705	0.029	**0.158**	0.017	0.689	0.042	0.221	0.033
	Time tokens	0.695	0.034	0.205	0.018	0.692	0.040	0.155	0.011	0.682	0.040	0.211	0.026
	Learned	**0.716**	0.050	**0.218**	0.014	**0.708**	0.050	0.156	0.010	0.708	0.055	**0.231**	0.016
	Sinus. (fixed)	0.716	0.052	0.209	0.013	0.700	0.046	0.146	0.016	**0.715**	0.057	0.224	0.023
	Sinus. (learned)	0.714	0.051	0.203	0.018	0.700	0.039	0.142	0.023	0.712	0.055	0.224	0.023
ED 30d (10.2%)	No encoding	0.626	0.008	0.159	0.020	0.620	0.020	0.126	0.011	0.647	0.018	0.184	0.027
	Time tokens	0.629	0.010	0.159	0.019	0.609	0.021	0.122	0.012	0.649	0.015	0.186	0.025
	Learned	**0.648**	0.021	**0.167**	0.013	0.628	0.027	**0.135**	0.017	0.661	0.027	0.193	0.010
	Sinus. (fixed)	0.645	0.022	0.163	0.016	**0.638**	0.032	0.131	0.015	0.661	0.028	0.193	0.025
	Sinus. (learned)	0.645	0.017	0.164	0.014	0.632	0.025	0.129	0.013	**0.668**	0.029	**0.199**	0.016
ICU 30d (1.9%)	No encoding	0.781	0.034	0.073	0.010	**0.834**	0.034	**0.090**	0.039	0.706	0.047	0.097	0.015
	Time tokens	0.780	0.033	**0.078**	0.010	0.814	0.051	0.065	0.033	0.712	0.043	**0.104**	0.012
	Learned	0.783	0.040	0.075	0.009	0.816	0.044	0.080	0.041	**0.717**	0.052	0.100	0.017
	Sinus. (fixed)	**0.787**	0.038	0.074	0.009	0.833	0.048	0.086	0.045	0.711	0.047	0.099	0.009
	Sinus. (learned)	0.783	0.038	0.072	0.010	0.809	0.055	0.052	0.023	0.715	0.048	0.097	0.016

Table 5. Downstream clinical prediction performance (AUROC / AUPRC, mean ± 95% CI across 10 seeds) for all time encoding conditions, stratified by sequence length, using only prior visit history. Prevalence of the positive class in the global stratum is shown in parentheses.

Task	Condition	Global				Short (Q1)				Long (Q4)			
		AUROC	±	AUPRC	±	AUROC	±	AUPRC	±	AUROC	±	AUPRC	±
Mortality (2.7%)	No encoding	**0.9056**	0.0061	0.2675	0.0327	0.9190	0.0145	0.3326	0.0635	0.8409	0.0262	**0.2674**	0.0604
	Time tokens	0.9040	0.0066	**0.2725**	0.0264	0.9217	0.0130	**0.3686**	0.0442	0.8394	0.0223	0.2457	0.0457
	Learned	0.9052	0.0076	0.2556	0.0188	**0.9254**	0.0108	0.3364	0.0640	**0.8437**	0.0278	0.2461	0.0598
	Sinus. (fixed)	0.8938	0.0089	0.2569	0.0264	0.9136	0.0115	0.3176	0.0464	0.8265	0.0284	0.2539	0.0517
	Sinus. (learned)	0.8944	0.0069	0.2452	0.0353	0.9183	0.0145	0.2983	0.0481	0.8246	0.0217	0.2326	0.0587
ED in visit (16.3%)	No encoding	**0.9210**	0.0047	**0.7496**	0.0160	**0.9373**	0.0042	**0.8030**	0.0161	**0.8608**	0.0097	0.6045	0.0294
	Time tokens	0.9180	0.0037	0.7376	0.0137	0.9354	0.0045	0.8018	0.0148	0.8567	0.0061	0.6127	0.0324
	Learned	0.9164	0.0034	0.7341	0.0105	0.9303	0.0039	0.7790	0.0173	0.8597	0.0079	**0.6129**	0.0272
	Sinus. (fixed)	0.9022	0.0048	0.6972	0.0185	0.9213	0.0032	0.7559	0.0120	0.8397	0.0080	0.5462	0.0342
	Sinus. (learned)	0.9041	0.0046	0.7012	0.0137	0.9213	0.0041	0.7490	0.0241	0.8425	0.0082	0.5680	0.0349
ICU in visit (14.9%)	No encoding	0.9008	0.0062	0.7506	0.0101	**0.9294**	0.0087	0.8384	0.0124	0.8314	0.0121	**0.6495**	0.0135
	Time tokens	**0.9010**	0.0055	**0.7539**	0.0084	0.9280	0.0080	**0.8386**	0.0112	**0.8342**	0.0129	0.6432	0.0195
	Learned	0.8987	0.0042	0.7527	0.0074	0.9238	0.0089	0.8354	0.0129	0.8332	0.0097	0.6433	0.0181
	Sinus. (fixed)	0.8872	0.0064	0.7278	0.0097	0.9175	0.0099	0.8157	0.0130	0.8240	0.0138	0.6313	0.0205
	Sinus. (learned)	0.8886	0.0064	0.7286	0.0100	0.9173	0.0089	0.8175	0.0131	0.8267	0.0154	0.6310	0.0223