Connection- and Node-Sparse Deep Learning: Statistical Prediction Guarantees

Abstract

Neural networks are becoming increasingly popular in applications, but a comprehensive mathematical understanding of their potentials and limitations is still missing. In this paper, we study the prediction accuracies of neural networks from a statistical point of view. In particular, we establish statistical prediction guarantees for deep learning with different types of sparsity-inducing regularization. Our bounds feature a mild dependence on network widths and depths, and, therefore, support the current trend toward wide and deep networks. The tools that we use in our derivations are uncommon in deep learning and, hence, might be of additional interest.

1 Introduction

Sparsity reduces network complexities and, consequently, lowers the demands on memory and computation, reduces overfitting, and improves interpretability (Changpinyo et al., 2017; Han et al., 2016; Kim et al., 2016; Liu et al., 2015; Wen et al., 2016). Three common notions of sparsity are connection sparsity, which means that there is only a small number of nonzero connections between nodes, node sparsity, which means that there is only a small number of active nodes (Alvarez & Salzmann, 2016; Changpinyo et al., 2017; Feng & Simon, 2017; Kim et al., 2016; Lee et al., 2008; Liu et al., 2015; Nie et al., 2015; Scardapane et al., 2017; Wen et al., 2016), and layer sparsity, which means that there is only a small number of active layers (Hebiri & Lederer, 2020). Approaches to achieving sparsity include augmenting small networks (Ash, 1989; Bello, 1992), pruning large networks (Simonyan & Zisserman, 2015; Han et al., 2016), constraint estimation (Ledent et al., 2019; Neyshabur et al., 2015; Schmidt-Hieber, 2020), and statistical regularization (Taheri et al., 2020).

The many empirical observations of the benefits of sparsity have sparked interest in mathematical support in the form of statistical theories. But such theories are still scarce and, in any case, have severe limitations. For example, statistical prediction guarantees for deep learning with connection-sparse regularization have been established in Taheri et al. (2020), but they do not cover node sparsity, which, in view of the removal of entire nodes, has become especially popular. Moreover, their estimator involves an additional parameter, their theory is limited to a single output node, and their results have a suboptimal dependence on the input vectors. Statistical guarantees for constraint estimation over connection- and node-sparse networks follow from combining results in Neyshabur et al. (2015) and Bartlett & Mendelson (2002). But for computational and practical reasons, regularized estimation is typically preferred over constraint estimation in deep learning as well as in machine learning at large (Hastie et al., 2015). Moreover, their theory is limited to a single output node and ReLU activation, scales exponentially in the number of layers, and, since Bartlett & Mendelson (2002) requires bounded loss functions, does not apply to prediction. Statistical prediction guarantees for constraint estimation over connection-sparse networks have been derived in Schmidt-Hieber (2020), but their theory is limited to a single output node and ReLU activation and assumes bounded weights. In short, there is currently no statistical theory that caters to node sparsity as well as connection sparsity, concerns regularization rather than constraint estimation, allows for multiple output nodes and a range of activation functions, and scales favorably with the networks' widths and depths.

The goal of this paper is to establish such a theory. We focus on prediction in regression-type settings with layered, feedforward neural networks. The estimators under consideration consist of a standard least-squares estimator with additional regularizers that induce connection or node sparsity. We then derive our guarantees by using techniques from high-dimensional statistics (Dalalyan et al., 2017)

and empirical process theory (van de Geer, 2000). In the case of subgaussian noise, we find the rates

$$\sqrt{\frac{l\log[mn\overline{p}]}{n}} \quad \text{and} \quad \sqrt{\frac{ml\underline{p}\log[mn\overline{p}]}{n}}$$

for the connection-sparse and node-sparse estimators, respectively, where l is the number of hidden layers, m the number of output nodes, n the number of samples, $\overline{p}$ the total number of parameters, and $\underline{p}$ the maximal width of the network. The rates suggest that sparsity-inducing approaches can provide accurate prediction even in very wide (with connection sparsity) and very deep (with either type of sparsity) networks while, at the same time, ensuring low network complexities. These findings underpin the current trend toward sparse but wide and especially deep networks from a statistical perspective.

The paper is outlined as follows: Section 2 recapitulates the notions of connection and node sparsity and introduces the corresponding deep learning framework and estimators. Section 3 confirms the empirically-observed accuracies of connection- and node-sparse estimation in theory. Section 4 summarizes the key features and limitations of our work. The Appendix contains all proofs.

2   CONNECTION- AND NODE-SPARSE DEEP LEARNING

We consider data $(\boldsymbol{y}_1, \boldsymbol{x}_1), \dots, (\boldsymbol{y}_n, \boldsymbol{x}_n) \in \mathbb{R}^m \times \mathbb{R}^d$ that are related via

$$\boldsymbol{y}_i = \boldsymbol{g}_*[\boldsymbol{x}_i] + \boldsymbol{u}_i \qquad \text{for } i \in \{1, \dots, n\} \tag{1}$$

for an unknown data-generating function $\boldsymbol{g}_* : \mathbb{R}^d \to \mathbb{R}^m$ and unknown, random noise $\boldsymbol{u}_1, \dots, \boldsymbol{u}_n \in \mathbb{R}^m$. Our goal is to model the data-generating function with a feedforward neural network of the form

$$\boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}] := \Theta^l \boldsymbol{f}^l\big[\Theta^{l-1} \cdots \boldsymbol{f}^1[\Theta^0 \boldsymbol{x}]\big] \qquad \text{for } \boldsymbol{x} \in \mathbb{R}^d \tag{2}$$

indexed by the parameter space $\mathcal{M} := \{\boldsymbol{\Theta} = (\Theta^l, \dots, \Theta^0) : \Theta^j \in \mathbb{R}^{p^{j+1} \times p^j}\}$. The functions $\boldsymbol{f}^j : \mathbb{R}^{p^j} \to \mathbb{R}^{p^j}$ are called the activation functions, and $p^0 := d$ and $p^{l+1} := m$ are called the input and output dimensions, respectively. The depth of the network is l, the maximal width is $\underline{p} := \max_{j \in \{0, \dots, l-1\}} p^{j+1}$, and the total number of parameters is $\overline{p} := \sum_{j=0}^{l} p^{j+1} p^j$.

In practice, the total number of parameters often rivals or exceeds the number of samples: $\overline{p} \approx n$ or $\overline{p} \gg n$. We then speak of high dimensionality. A common technique for avoiding overfitting in high-dimensional settings is regularization that induces additional structures, such as sparsity. Sparsity has the interesting side-effect of reducing the networks' complexities, which can facilitate interpretations and reduce demands on energy and memory. Our first sparse estimator is

$$\widehat{\boldsymbol{\Theta}}_{\text{con}} \in \underset{\boldsymbol{\Theta} \in \mathcal{M}_1}{\arg\min}\left\{\sum_{i=1}^{n} \big\|\boldsymbol{y}_i - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}_i]\big\|_2^2 + r_{\text{con}}\|\!|\Theta^l|\!\|_1\right\} \tag{3}$$

for a tuning parameter $r_{\text{con}} \in [0, \infty)$, a nonempty set of parameters

$$\mathcal{M}_1 \subset \left\{\boldsymbol{\Theta} \in \mathcal{M} : \max_{j \in \{0, \dots, l-1\}} \|\!|\Theta^j|\!\|_1 \leq 1\right\},$$

and the ℓ_1-norm

$$\|\!|\Theta^j|\!\|_1 := \sum_{i=1}^{p^{j+1}} \sum_{k=1}^{p^j} |(\Theta^j)_{ik}| \qquad \text{for } j \in \{0, \dots, l\}, \Theta^j \in \mathbb{R}^{p^{j+1} \times p^j}.$$

This estimator is an analog of the lasso estimator in linear regression (Tibshirani, 1996). It induces sparsity on the level of connections: the larger the tuning parameter r_{con}, the fewer connections among the nodes.

Deep learning with ℓ_1-regularization has become common in theory and practice (Kim et al., 2016; Taheri et al., 2020). Our estimator (3) specifies one way to formulate this type of regularization. The estimator is indeed a regularized estimator (rather than a constraint estimator), because the complexity is regulated entirely through the tuning parameter r_{con} in the objective function (rather than through

Figure 1: exemplary networks produced by the connection-sparse estimator (3) and the node-sparse estimator (6)

a tuning parameter in the set over which the objective function is optimized). But ℓ_1-regularization could also be formulated slightly differently. For example, one could consider the estimators

$$\overline{\boldsymbol{\Theta}}_{\text{con}} \in \underset{\boldsymbol{\Theta} \in \mathcal{M}}{\arg\min}\left\{\sum_{i=1}^{n}\left\|\boldsymbol{y}_i - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}_i]\right\|_2^2 + r_{\text{con}}\prod_{j=0}^{l}\|\Theta^j\|_1\right\} \tag{4}$$

or

$$\widetilde{\boldsymbol{\Theta}}_{\text{con}} \in \underset{\boldsymbol{\Theta} \in \mathcal{M}}{\arg\min}\left\{\sum_{i=1}^{n}\left\|\boldsymbol{y}_i - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}_i]\right\|_2^2 + r_{\text{con}}\sum_{j=0}^{l}\|\Theta^j\|_1\right\}. \tag{5}$$

The differences among the estimators (3)–(5) are small: for example, our theory can be adjusted for (4) with almost no changes of the derivations. The differences among the estimators mainly concern the normalizations of the parameters; we illustrate this in the following proposition.

Proposition 1 (Scaling of Norms). *Assume that the all-zeros parameter* $(\mathbf{0}_{p^{l+1} \times p^l}, \ldots, \mathbf{0}_{p^1 \times p^0}) \in \mathcal{M}_1$ *is neither a solution of* (3) *nor of* (5)*, that* $r_{\text{con}} > 0$*, and that the activation functions are nonnegative homogenous:* $\boldsymbol{f}^j[a\boldsymbol{b}] = a\boldsymbol{f}^j[\boldsymbol{b}]$ *for all* $j \in \{1, \ldots, l\}$*,* $a \in [0, \infty)$*, and* $\boldsymbol{b} \in \mathbb{R}^{p^j}$*. Then,* $\|(\widehat{\Theta}_{\text{con}})^0\|_1, \ldots, \|(\widehat{\Theta}_{\text{con}})^{l-1}\|_1 = 1$ *(concerns the inner layers) for all solutions of* (3)*, while* $\|(\widetilde{\Theta}_{\text{con}})^0\|_1 = \cdots = \|(\widetilde{\Theta}_{\text{con}})^l\|_1$ *(concerns all layers) for at least one solution of* (5)*.*

Another way to formulate ℓ_1-regularization was proposed in Taheri et al. (2020): they reparametrize the networks through a scale parameter and a constraint version of $\mathcal{M}$ and then to focus the regularization on the scale parameter only. Our above-stated estimator (3) is more elegant in that it avoids the reparametrization and the additional parameter.

The factor $\|\Theta^l\|_1$ in the regularization term of (3) measures the complexity of the network over the set $\mathcal{M}_1$, and the factor r_{con} regulates the complexity of the resulting estimator. This provides a convenient lever for data-adaptive complexity regularization through well-established calibration schemes for the tuning parameter, such as cross-validation. This practical aspect is an advantage of regularized formulations like ours as compared to constraint estimation over sets with a predefined complexity.

The constraints in the set $\mathcal{M}_1$ of the estimator (3) can also retain the expressiveness of the full parameterization that corresponds to the set $\mathcal{M}$: for example, assuming again nonnegative-homogeneous activation, one can check that for every $\boldsymbol{\Gamma} \in \mathcal{M}$, there is a $\boldsymbol{\Gamma}' \in \{\boldsymbol{\Theta} \in \mathcal{M} : \max_{j \in \{0,\ldots,l-1\}} \|\Theta^j\|_1 \leq 1\}$ such that $\boldsymbol{g}_{\boldsymbol{\Gamma}} = \boldsymbol{g}_{\boldsymbol{\Gamma}'}$—cf. Taheri et al. (2020, Proposition 1). In contrast, existing theories on neural networks often require the parameter space to be bounded, which limits the expressiveness of the networks.

Our regularization approach is, therefore, closer to practical setups than constraint approaches. The price is that to develop prediction theories, we have to use different tools than those typically used in theoretical deep learning. For example, we cannot use established risk bounds such as Bartlett & Mendelson (2002, Theorem 8) (because Rademacher complexities over classes of unbounded functions are unbounded) or established concentration bounds such as McDiarmid's inequality in McDiarmid (1989, Lemma (3.3)) (because that would require a bounded loss). We instead invoke ideas from high-dimensional statistics, prove Lipschitz properties for neural networks, and use empirical process theory that is based on chaining (see the Appendix).

Our second estimator is

$$\widehat{\boldsymbol{\Theta}}_{\text{node}} \in \underset{\boldsymbol{\Theta} \in \mathcal{M}_{2,1}}{\arg\min}\left\{\sum_{i=1}^{n}\left\|\boldsymbol{y}_i - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}_i]\right\|_2^2 + r_{\text{node}}\|\Theta^l\|_{2,1}\right\} \tag{6}$$

for a tuning parameter $r_{\mathrm{node}} \in [0, \infty)$, a nonempty set of parameters

$$\mathcal{M}_{2,1} \subset \left\{ \boldsymbol{\Theta} \in \mathcal{M} \ : \ \max_{j \in \{0,\dots,l-1\}} \|\Theta^j\|_{2,1} \leq 1 \right\},$$

and the ℓ_2/ℓ_1-norm

$$\|\Theta^j\|_{2,1} := \sum_{k=1}^{p^j} \sqrt{\sum_{i=1}^{p^{j+1}} |(\Theta^j)_{ik}|^2} \qquad \text{for } j \in \{0,\dots,l-1\},\ \Theta^j \in \mathbb{R}^{p^{j+1} \times p^j}\,.$$

This estimator is an analog of the group-lasso estimator in linear regression (Bakin, 1999). Again, to avoid ambiguities in the regularization, our formulation is slightly different from the standard formulations in the literature, but the fact that group-lasso regularizers leads to node-sparse networks has been discussed extensively before (Alvarez & Salzmann, 2016; Liu et al., 2015; Scardapane et al., 2017): the larger the tuning parameter r_{node}, the fewer active nodes in the network.

The above-stated comments about the specific form of the connection-sparse estimator also apply to the node-sparse estimator.

An illustration of connection and node sparsity is given in Figure 1. Connection-sparse networks have only a small number of active connections between nodes (left panel of Figure 1); node-sparse networks have inactive nodes, that is, completely unconnected nodes (right panel of Figure 1). The two notions of sparsity are connected: for example, connection sparsity can render entire nodes inactive "by accident" (see the layer that follows the input layer in the left panel of the figure). In general, node sparsity is the weaker assumption, because it allows for highly connected nodes; this observation is reflected in the theoretical guarantees in the following section.

The optimal network architecture for given data (such as the optimal width) is hardly known beforehand in a data analysis. A main feature of sparsity-inducing regularization is, therefore, that it adjusts parts of the network architecture to the data. In other words, sparsity-inducing regularization is a data-driven approach to adapting the complexity of the network.

While versions of the estimators (3) and (6) are popular in deep learning, statistical analyses, especially of node-sparse deep learning, are scarce. Such a statistical analysis is, therefore, the goal of the following section.

3 STATISTICAL PREDICTION GUARANTEES

We now develop statistical guarantees for the sparse estimators described above. The guarantees are formulated in terms of the squared *average (in-sample) prediction error*

$$\mathrm{err}[\boldsymbol{\Theta}] := \frac{1}{n} \sum_{i=1}^{n} \left\| \boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}_i] \right\|_2^2 \qquad \text{for } \boldsymbol{\Theta} \in \mathcal{M}\,.$$

This is a measure for how well the network $\boldsymbol{g}_{\boldsymbol{\Theta}}$ fits the unknown function $\boldsymbol{g}_*$ (which does not need to be a neural network) on the data at hand. Another popular measure is the expected squared out-of-sample predition error $E\|\boldsymbol{y} - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}]\|_2^2$ for a new sample $(\boldsymbol{y}, \boldsymbol{x})$. The two measures are closely related; in particular, the following guarantees and proofs would remain very similar for the out-of-sample error. But the out-of-sample error would require additional assumptions on the data, so that we opt for the in-sample prediction error for convenience. The important thing is that a small value in either measure means that the network does not only fit the data but also captures the underlying data-generating process.

We now observe that the networks in (2) can be somewhat "linearized:" For every parameter $\boldsymbol{\Theta} \in \mathcal{M}_1$, there is a parameter

$$\overline{\boldsymbol{\Theta}} \in \overline{\mathcal{M}}_1 := \left\{ \overline{\boldsymbol{\Theta}} = (\overline{\Theta}^{l-1}, \dots, \overline{\Theta}^0) \ : \ \overline{\Theta}^j \in \mathbb{R}^{p^{j+1} \times p^j},\ \max_{j \in \{0,\dots,l-1\}} \|\overline{\Theta}^j\|_1 \leq 1 \right\}$$

such that for every $\boldsymbol{x} \in \mathbb{R}^d$

$$\boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}] = \Theta^l \overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Theta}}}[\boldsymbol{x}] \quad \text{with} \quad \overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Theta}}}[\boldsymbol{x}] := \boldsymbol{f}^l\big[\overline{\Theta}^{l-1} \cdots \boldsymbol{f}^1[\overline{\Theta}^0 \boldsymbol{x}]\big] \in \mathbb{R}^{p^l}\,. \tag{7}$$

This additional notation allows us to disentangle the outermost layer (which is regularized directly) from the other layers (which are regularized indirectly). More generally speaking, the additional notation makes a connection to linear regression, where the above holds trivially with $\overline{g}_{\overline{\Theta}}[x] = x$.

We also define

$$\overline{\mathcal{M}}_{2,1} := \left\{ \overline{\Theta} = (\overline{\Theta}^{l-1}, \ldots, \overline{\Theta}^0) : \overline{\Theta}^j \in \mathbb{R}^{p^{j+1} \times p^j}, \max_{j \in \{0, \ldots, l-1\}} \|\overline{\Theta}^j\|_{2,1} \leq 1 \right\}$$

accordingly.

In high-dimensional linear regression, the quantity central to prediction guarantees is the effective noise (Lederer & Vogt, 2020). The effective noise is in our notation (with $l = 0$ and $m = 1$ to describe linear regression) $2\|\sum_{i=1}^n u_i x_i\|_\infty$. The above linearization allows us to generalize the effective noise to our general deep-learning framework:

$$
\begin{aligned}
r^*_{\mathrm{con}} &:= 2 \sup_{\overline{\Psi} \in \overline{\mathcal{M}}_1} \left\| \sum_{i=1}^n u_i \big(\overline{g}_{\overline{\Psi}}[x_i]\big)^\top \right\|_\infty \\
r^*_{\mathrm{node}} &:= 2\sqrt{m} \sup_{\overline{\Psi} \in \overline{\mathcal{M}}_{2,1}} \left\| \sum_{i=1}^n u_i \big(\overline{g}_{\overline{\Psi}}[x_i]\big)^\top \right\|_\infty,
\end{aligned}
\tag{8}
$$

where $\|A\|_\infty := \max_{(i,j) \in \{1, \ldots, m\} \times \{1, \ldots, p^l\}} |A_{ij}|$ for $A \in \mathbb{R}^{m \times p^l}$. The effective noises, as we will see below, are the optimal tuning parameters in our theories; at the same time, the effective noises depend on the noise random variables $u_1, \ldots, u_n$, which are unknown in practice. Accordingly, we call the quantities r^*_{con} and r^*_{node} the *oracle tuning parameters*.

We then find the following result.

Theorem 1 (General Prediction Guarantees)**.** *If $r_{\mathrm{con}} \geq r^*_{\mathrm{con}}$, it holds that*

$$\mathrm{err}[\widehat{\Theta}_{\mathrm{con}}] \leq \inf_{\Theta \in \mathcal{M}_1} \left\{ \mathrm{err}[\Theta] + \frac{2r_{\mathrm{con}}}{n} \|\Theta^l\|_1 \right\}.$$

Similarly, if $r_{\mathrm{node}} \geq r^*_{\mathrm{node}}$, it holds that

$$\mathrm{err}[\widehat{\Theta}_{\mathrm{node}}] \leq \inf_{\Theta \in \mathcal{M}_{2,1}} \left\{ \mathrm{err}[\Theta] + \frac{2r_{\mathrm{node}}}{n} \|\Theta^l\|_1 \right\}.$$

Each bound contains an approximation error $\mathrm{err}[\Theta]$ that captures how well the class of networks can approximate the true data-generating function g_* and a statistical error proportional to r_{con}/n and r_{node}/n, respectively, that captures how well the estimator can select within the class of networks at hand. In other words, Theorem 1 ensures that the estimators (3) and (6) predict—up to the statistical error described by r_{con}/n and r_{node}/n, respectively—as well as the best connection- and node-sparse network. This observation can be illustrated further:

Corollary 1 (Parametric Setting)**.** *If additionally $g_* = g_{\Theta^*}$ for a $\Theta^* \in \mathcal{M}_1$, it holds that*

$$\mathrm{err}[\widehat{\Theta}_{\mathrm{con}}] \leq \frac{2r_{\mathrm{con}}}{n} \|(\Theta^*)^l\|_1.$$

If instead $g_* = g_{\Theta^*}$ for a $\Theta^* \in \mathcal{M}_{2,1}$, it holds that

$$\mathrm{err}[\widehat{\Theta}_{\mathrm{node}}] \leq \frac{2r_{\mathrm{node}}}{n} \|(\Theta^*)^l\|_1.$$

Hence, if the underlying data-generating function is a sparse network itself, the prediction errors of the estimators are essentially bounded by the statistical errors r_{con}/n and r_{node}/n.

The above-stated results also identify the oracle tuning parameters r^*_{con} and r^*_{node} as optimal tuning parameters: they give the best prediction guarantees in Theorem (1). But since the oracle tuning parameters are unknown in practice, the guarantees implicitly presume a calibration scheme that satisfies $r_{\mathrm{con}} \approx r^*_{\mathrm{con}}$ in practice. A natural candidate is cross-validation, but there are no guarantees that cross-validation provides such tuning parameters. This is a limitation that our theories share with all other theories in the field.

Rather than dealing with the practical calibration of the tuning parameters, we exemplify the oracle tuning parameters in a specific setting. This analysis will illustrate the rates of convergences that we can expect from Theorem 1, and it will allow us to compare our theories with other theories in the literature. Assume that the activation functions satisfy $\boldsymbol{f}^j[\boldsymbol{0}_{p^j}] = \boldsymbol{0}_{p^j}$ and are 1-Lipschitz continuous with respect to the Euclidean norms on the functions' input and output spaces $\mathbb{R}^{p^j}$. A popular example is ReLU activation (Nair & Hinton, 2010), but the conditions are met by many other functions as well. Also, assume that the noise vectors $\boldsymbol{u}_1, \ldots, \boldsymbol{u}_n$ are independent and centered and have uniformly subgaussian entries (van de Geer, 2000, Display (8.2) on Page 126). Keep the input vectors fixed and capture their normalizations by

$$\overline{v}_\infty := \sqrt{\frac{1}{n}\sum_{i=1}^n \|\boldsymbol{x}_i\|_\infty^2} \quad \text{and} \quad \overline{v}_2 := \sqrt{\frac{1}{n}\sum_{i=1}^n \|\boldsymbol{x}_i\|_2^2}.$$

Then, we obtain the following bounds for the effective noises.

Proposition 2 (Subgaussian Noise). *There is a constant $c \in (0, \infty)$ that depends only on the subgaussian parameters of the noise such that*

$$P\left\{r_{\text{con}}^* \leq c\overline{v}_\infty\sqrt{nl\log[2mn\overline{p}]}\right\} \geq 1 - \frac{1}{n}$$

and

$$P\left\{r_{\text{node}}^* \leq c\overline{v}_2\sqrt{mnl\underline{p}\log[2mn\overline{p}]}\right\} \geq 1 - \frac{1}{n}.$$

Broadly speaking, this result combined with Theorem 1 illustrates that accurate prediction with connection- and node-sparse estimators is possible even when using very wide and deep networks. Let us analyze the factors one by one and compare them to the factors in the bounds of Taheri et al. (2020) and Neyshabur et al. (2015), which are the two most related papers. The connection-sparse case compares to the results in Taheri et al. (2020), and it compares to the results in Neyshabur et al. (2015) when setting the parameters in that paper to $p = q = 1$ (which gives a setting that is slightly more restrictive than ours) or $p = 1; q = \infty$ (which gives a setting that is slightly less restrictive than ours). The node-sparse case compares to Neyshabur et al. (2015) with $p = 2; q = \infty$ (which gives a setting that is more restrictive than ours, though). Our setup is also more general than the one in Neyshabur et al. (2015) in the sense that it allows for activation other than ReLU.

The dependence on n is, as usual, $1/\sqrt{n}$ up to logarithmic factors.

In the connection-sparse case, our bounds involve $\overline{v}_\infty = \sqrt{\sum_{i=1}^n \|\boldsymbol{x}_i\|_\infty^2/n}$ rather than the factor $v_\infty := \max_{i \in \{1,\ldots,n\}} \|\boldsymbol{x}_i\|_\infty$ of Neyshabur et al. (2015) or the factor $\overline{v}_2 = \sqrt{\sum_{i=1}^n \|\boldsymbol{x}_i\|_2^2/n}$ of Taheri et al. (2020). In principle, the improvements of $\overline{v}_\infty$ over v_∞ and $\overline{v}_2$ can be up to a factor $\sqrt{n}$ and up to a factor $\sqrt{d}$, respectively; in practice, the improvements depend on the specifics on the data. For example, on the training data of `MNIST` (LeCun et al., 1998) and `Fashion-MNIST` (Xiao et al., 2017) ($\sqrt{n} \approx 250; \sqrt{d} = 28$ in both data sets), it holds that $\overline{v}_\infty \approx v_\infty \approx \overline{v}_2/9$ and $\overline{v}_\infty \approx v_\infty \approx \overline{v}_2/12$, respectively. In the node-sparse case, our bounds involve $\overline{v}_2$, which is again somewhat smaller than the factor $v_2 := \max_{i \in \{1,\ldots,n\}} \|\boldsymbol{x}_i\|_2$ in Neyshabur et al. (2015).

The main difference between the bounds for the connection-sparse and node-sparse estimators are their dependencies on the networks' maximal width p. The bound for the connection-sparse estimator (3) depends on the width p only logarithmically (through $\overline{p}$), while the bound for the node-sparse estimator (6) depends on $\overline{p}$ sublinearly. The dependence in the connection-sparse case is the same as in Taheri et al. (2020), while Neyshabur et al. (2015) can avoid even that logarithmic dependence (and, therefore, allow for networks with infinite widths). The node-sparse case in Neyshabur et al. (2015) does not involve our linear dependence on the width, but this difference stems from the fact that they use a more restrictive version of the grouping—we take the maximum over each layer, while they take the maximum over each node— and our results can be readily adjusted to their notion of group sparsity. These observations indicate that node sparsity as formulated above is suitable for slim networks ($p \ll n$) but should be strengthened or complemented with other notions of sparsity otherwise. To give a numeric example, the training data in `MNIST` (LeCun et al., 1998) and `Fashion-MNIST` (Xiao et al., 2017) comprise $n = 60\,000$ samples, which means that the width

should be considerably smaller than $60\,000$ when using node sparsity alone. (Note that the input layer does not take part in $\underline{p}$, which means that d could be larger.)

Both of our bounds have a mild $\sqrt{l}$ dependence on the depth and also a mild $\log[\overline{p}]$ dependence on the total number of parameters. These dependencies considerably improve on the exponentially-increasing dependencies on the depth in Neyshabur et al. (2015) and, therefore, are particularly suited to describe deep network architectures. Replacing the conditions $\max_j \|\!|\Theta^j\|\!|_1 \leq 1$ and $\max_j \|\!|\Theta^j\|\!|_{2,1} \leq 1$ in the definitions of the connection-sparse and node-sparse estimators by the stricter conditions $\sum_j \|\!|\Theta^j\|\!|_1 \leq 1$ and $\sum_j \|\!|\Theta^j\|\!|_{2,1} \leq 1$, respectively (cf. Taheri et al. (2020) and our discussion in Section 2), the dependence on the depth can be improved further from $\sqrt{l}$ to $(2/l)^l\sqrt{l}$ (this only requires a simple adjustment of the last display in the proof of Proposition 3), which is exponentially decreasing in the depth.

Our connection-sparse bounds have a mild $\log[m]$ dependence on the number of output nodes; the node-sparse bound involve an additional factor $\sqrt{m}$. The case of multiple outputs has not been considered in statistical prediction bounds before.

Proposition 2 also highlights another advantage of our regularization approach over theories such as Neyshabur et al. (2015) that apply to constraint estimators. The theories for constraint estimators require bounding the sparsity levels directly, but in practice, suitable values for these bounds are rarely known. In our framework, in contrast, the sparsity is controlled via tuning parameters indirectly, and Proposition 2—although not providing a complete practical calibration scheme—gives insights into how these tuning parameters should scale with n, d, l, and so forth.

We finally note that the bounds in Theorem 1 can be generalized readily to every estimator of the form

$$\widehat{\boldsymbol{\Theta}}_{\text{gen}} \in \underset{\boldsymbol{\Theta}\in\mathcal{M}_{\text{gen}}}{\arg\min}\left\{\sum_{i=1}^{n}\left\|\boldsymbol{y}_i - \boldsymbol{g}_{\boldsymbol{\Theta}}[\boldsymbol{x}_i]\right\|_2^2 + r_{\text{gen}}\|\!|\Theta^l\|\!|\right\},$$

where $r_{\text{gen}} \in [0,\infty)$ is a tuning parameter, $\mathcal{M}_{\text{gen}}$ any nonempty subset of $\mathcal{M}$, and $\|\!| \cdot \|\!|$ any norm. The bound for such an estimator is then

$$\text{err}[\widehat{\boldsymbol{\Theta}}_{\text{gen}}] \leq \inf_{\boldsymbol{\Theta}\in\mathcal{M}_{\text{gen}}}\left\{\text{err}[\boldsymbol{\Theta}] + \frac{2r_{\text{gen}}}{n}\|\!|\Theta^l\|\!|\right\}$$

for $r_{\text{gen}} \geq r_{\text{gen}}^*$, where r_{gen}^* is as r_{con}^* but based on the dual norm of $\|\!| \cdot \|\!|$ instead of the dual norm of $\|\!| \cdot \|\!|_1$. For example, one could impose connection sparsity on some layers and node sparsity on others, or one could impose different regularizations altogether. We omit the details to avoid digression.

4 DISCUSSION

Evidence for the benefits of deep networks has been established in practice (LeCun et al., 2015; Schmidhuber, 2015), approximation theory (Liang & Srikant, 2016; Telgarsky, 2016; Yarotsky, 2017), and statistics (Golowich et al., 2017; Taheri et al., 2020). Since our guarantees scale at most sublinearly in the number of layers, our paper complements these lines of research and shows that sparsity-inducing regularization is an effective approach to coping with the complexity of deep and very deep networks.

Connection sparsity limits the number of nonzero entries in each parameter matrix, while layer sparsity only limits the total number of nonzero rows. Hence, the number of columns in a parameter matrix, that is, the width of the preceding layer, is regularized only in the case of connection sparsity. Our theoretical results reflect this insight in that the bounds for the connection- and node-sparse estimators depend on the networks' width logarithmically and sublinearly, respectively. Practically speaking, our results indicate that connection sparsity is suitable to handle wide networks, but node sparsity is suitable only when complemented by connection sparsity or other strategies.

The mild logarithmic dependence of our connection-sparse bounds on the number of output nodes illustrates that networks with many outputs can be learned in practice. Our prediction theory is the first one that considers multiple output nodes; a classification theory with a logarithmic dependence on the output nodes has been established very recently in Ledent et al. (2019).

The mathematical underpinnings of our theory are very different from those of most other papers in theoretical deep learning. The proof of the main theorem shares similarities with proofs in high-dimensional statistics; to formulate and control the relevant empirical processes, we use the concept of effective noise, chaining, and Lipschitz properties of neural networks. These tools are not standard in deep learning theory and, therefore, might be of more general interest.

Our theory shares some limitations with all other current theories in deep learning: the network architectures are simpler than the ones typically used in practice; the bounds concern global optima rather than the local optima or saddle points provided by many practical algorithms; and the theory does not entail a practical scheme for the calibration of the tuning parameters. Nevertheless, our theory, and mathematical theory in general, provides insights about what accuracies to expect in practice and about what network types and estimators might be suitable for a given problem.

In summary, our paper highlights the benefits of sparsity in deep learning and, more generally, showcases the usefulness of statistical analyses for understanding neural networks.

REFERENCES

J. Alvarez and M. Salzmann. Learning the number of neurons in deep networks. In *Adv. Neural Inf. Process Syst.*, pp. 2270–2278, 2016.

T. Ash. Dynamic node creation in backpropagation networks. *Connect. Sci.*, 1(4):365–375, 1989.

S. Bakin. *Adaptive regression and model selection in data mining problems.* PhD thesis, The Australian National University, 1999.

P. Bartlett and S. Mendelson. Rademacher and Gaussian complexities: Risk bounds and structural results. *J. Mach. Learn. Res.*, 3:463–482, 2002.

M. Bello. Enhanced training algorithms, and integrated training/architecture selection for multilayer perceptron networks. *IEEE Trans. Neural Netw.*, 3(6):864–875, 1992.

B. Carl. Inequalities of Bernstein-Jackson-type and the degree of compactness of operators in Banach spaces. In *Ann. Inst. Fourier*, volume 35, pp. 79–118, 1985.

S. Changpinyo, M. Sandler, and A. Zhmoginov. The power of sparsity in convolutional neural networks. *arXiv:1702.06257*, 2017.

A. Dalalyan, M. Hebiri, and J. Lederer. On the prediction performance of the lasso. *Bernoulli*, 23(1): 552–581, 2017.

J. Feng and N. Simon. Sparse-input neural networks for high-dimensional nonparametric regression and classification. *arXiv:1711.07592*, 2017.

N. Golowich, A. Rakhlin, and O. Shamir. Size-independent sample complexity of neural networks. *arXiv:1712.06541*, 2017.

S. Han, H. Mao, and W. Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. In *Proc. ICML*, 2016.

T. Hastie, R. Tibshirani, and M. Wainwright. *Statistical learning with sparsity: the lasso and generalizations*. CRC press, 2015.

M. Hebiri and J. Lederer. Layer sparsity in neural networks. *arXiv2006.15604*, 2020.

J. Kim, V. Calhoun, E. Shim, and J.-H. Lee. Deep neural network with weight sparsity control and pre-training extracts hierarchical features and enhances classification performance: evidence from whole-brain resting-state functional connectivity patterns of schizophrenia. *Neuroimage*, 124: 127–146, 2016.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Y. LeCun, Y. Bengio, and G. Hinton. Deep learning. *Nature*, 521:436–444, 2015.

A. Ledent, Y. Lei, and M. Kloft. Norm-based generalisation bounds for multi-class convolutional neural networks. *arXiv:1905.12430*, 2019.

J. Lederer. Bounds for rademacher processes via chaining. *arXiv:1010.5626*, 2010.

J. Lederer and M. Vogt. Estimating the lasso's effective noise. *arXiv:2004.11554*, 2020.

H. Lee, C. Ekanadham, and A. Ng. Sparse deep belief net model for visual area V2. In *Adv. Neural Inf. Process. Syst.*, pp. 873–880, 2008.

S. Liang and R. Srikant. Why deep neural networks for function approximation? *arXiv:1610.04161*, 2016.

B. Liu, M. Wang, H. Foroosh, M. Tappen, and M. Pensky. Sparse convolutional neural networks. In *IEEE Int. Conf. Comput. Vis. Pattern Recognit.*, pp. 806–814, 2015.

C. McDiarmid. On the method of bounded differences. *Surv. Comb.*, 141(1):148–188, 1989.

V. Nair and G. Hinton. Rectified linear units improve restricted Boltzmann machines. In *Int. Conf. Mach. Learn.*, pp. 807–814, 2010.

B. Neyshabur, R. Tomioka, and N. Srebro. Norm-based capacity control in neural networks. In *Conf. Learn. Theory*, pp. 1376–1401, 2015.

L. Nie, M. Wang, L. Zhang, S. Yan, B. Zhang, and T.-S. Chua. Disease inference from health-related questions via sparse deep learning. *IEEE Trans. Knowl. Data Eng.*, 27(8):2107–2119, 2015.

S. Scardapane, D. Comminiello, A. Hussain, and A. Uncini. Group sparse regularization for deep neural networks. *Neurocomputing*, 241:81–89, 2017.

J. Schmidhuber. Deep learning in neural networks: An overview. *Neural Networks*, 61:85–117, 2015.

J. Schmidt-Hieber. Nonparametric regression using deep neural networks with ReLU activation function. *Ann. Statist.*, 48(4):1875–1897, 2020.

K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. In *Int. Conf. Learn. Representations*, 2015.

M. Taheri, F. Xie, and J. Lederer. Statistical guarantees for regularized neural networks. *arXiv:2006.00294*, 2020.

M. Telgarsky. Benefits of depth in neural networks. In *Proc. Mach. Learn. Res.*, volume 49, pp. 1517–1539, 2016.

R. Tibshirani. Regression shrinkage and selection via the lasso. *J. R. Stat. Soc. Ser. B. Stat. Methodol.*, 58(1):267–288, 1996.

S. van de Geer. *Empirical processes in M-estimation*. Cambridge Univ. Press, 2000.

A. van der Vaart and J. Wellner. *Weak convergence and empirical processes*. Springer, 1996.

W. Wen, C. Wu, Y. Wang, Y. Chen, and H. Li. Learning structured sparsity in deep neural networks. In *Adv. Neural Inf. Process Syst.*, pp. 2082–2090, 2016.

H. Xiao, K. Rasul, and R. Vollgraf. Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. *arXiv:1708.07747*, 2017.

D. Yarotsky. Error bounds for approximations with deep ReLU networks. *Neural Networks*, 94: 103–114, 2017.

R. Zhuang and J. Lederer. Maximum regularized likelihood estimators: A general prediction theory and applications. *Stat*, 7(1):e186, 2018.

A   APPENDIX

The Appendix consists of two auxiliary results and the proofs of Theorem 1 and Propositions 1 and 2. Our approach combines techniques from high-dimensional statistics and empirical process theory that are very different from the techniques used in most other approaches in the literature.

A.1   LIPSCHITZ PROPERTY

In this section, we prove a Lipschitz property that we use in the proof of Proposition 2.

Proposition 3 (Lipschitz Property). *In the framework of Sections 2 and 3, it holds for all $\overline{\Theta}, \overline{\Gamma} \in \overline{\mathcal{M}}_1$ that*

$$\left\| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \right\|_{\infty} \leq \sqrt{l} \|\boldsymbol{x}\|_{\infty} \|\overline{\Theta} - \overline{\Gamma}\|_{\mathrm{F}}$$

and for all $\overline{\Theta}, \overline{\Gamma} \in \overline{\mathcal{M}}_{2,1}$ that

$$\left\| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \right\|_2 \leq \sqrt{l} \|\boldsymbol{x}\|_2 \|\overline{\Theta} - \overline{\Gamma}\|_{\mathrm{F}} .$$

The Frobenius norm is defined as

$$\|\overline{\Theta}\|_{\mathrm{F}} := \sqrt{\sum_{j=0}^{l-1} \|\overline{\Theta}^j\|_{\mathrm{F}}^2} := \sqrt{\sum_{j=0}^{l-1} \sum_{i=1}^{p^{j+1}} \sum_{k=1}^{p^j} |(\overline{\Theta}^j)_{ik}|^2} \qquad \text{for } \overline{\Theta} \in \overline{\mathcal{M}}_{2,1} = \overline{\mathcal{M}}_1 \cup \overline{\mathcal{M}}_{2,1} .$$

Proposition 3 generalizes (Taheri et al., 2020, Proposition 2) to vector-valued network outputs and to node sparsity, and it replaces their $\|\boldsymbol{x}\|_2$ with the smaller $\|\boldsymbol{x}\|_{\infty}$ in the connection-sparse case.

Proof of Proposition 3. This proof generalizes and sharpens the proof of Taheri et al. (2020), and it simplifies some arguments of that proof. We define the "inner subnetworks" of a network $\overline{\boldsymbol{g}}_{\overline{\Theta}}$ with $\overline{\Theta} \in \overline{\mathcal{M}}_{2,1}$ as the vector-valued functions

$$S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}} \; : \; \mathbb{R}^d \to \mathbb{R}^{p^1}$$
$$\boldsymbol{x} \mapsto S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] := \overline{\Theta}^0 \boldsymbol{x}$$

and

$$S_j \overline{\boldsymbol{g}}_{\overline{\Theta}} \; : \; \mathbb{R}^d \to \mathbb{R}^{p^{j+1}}$$
$$\boldsymbol{x} \mapsto S_j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] := \overline{\Theta}^j \boldsymbol{f}^j \big[\cdots \boldsymbol{f}^1 [\overline{\Theta}^0 \boldsymbol{x}] \big]$$

for $j \in \{1, \dots, l-1\}$. Similarly, we define the "outer subnetworks" of $\overline{\boldsymbol{g}}_{\overline{\Theta}}$ as the real-valued functions

$$S^j \overline{\boldsymbol{g}}_{\overline{\Theta}} \; : \; \mathbb{R}^{p^j} \to \mathbb{R}^{p^l}$$
$$\boldsymbol{z} \mapsto S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{z}] := \boldsymbol{f}^l \big[\overline{\Theta}^{l-1} \cdots \boldsymbol{f}^j[\boldsymbol{z}] \big]$$

for $j \in \{1, \dots, l-1\}$ and

$$S^l \overline{\boldsymbol{g}}_{\overline{\Theta}} \; : \; \mathbb{R}^{p^l} \to \mathbb{R}^{p^l}$$
$$\boldsymbol{z} \mapsto S^l \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{z}] := \boldsymbol{f}^l[\boldsymbol{z}] .$$

The initial network can be split into an inner and an outer network along every layer $j \in \{1, \dots, l\}$:

$$\overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] = S^j \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_{j-1} \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] \big] \qquad \text{for } \boldsymbol{x} \in \mathbb{R}^d .$$

We call this our *splitting argument*.

To exploit the splitting argument, we derive a contraction result for the inner subnetworks and a Lipschitz result for the outer subnetworks. We denote the ℓ_2-operator norm of a matrix A, that is, the largest singular value of A, by $\|A\|_{\mathrm{op}}$. Using then the assumptions that the activation functions are 1-Lipschitz and $\boldsymbol{f}^j[\boldsymbol{0}_{p^j}] = \boldsymbol{0}_{p^j}$, we get for every $\overline{\Theta} = (\overline{\Theta}^{l-1}, \dots, \overline{\Theta}^0) \in \overline{\mathcal{M}}_{2,1}$ and $\boldsymbol{x} \in \mathbb{R}^d$ that

$$\left\| S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] \right\|_2 = \left\| \overline{\Theta}^{j-2} \boldsymbol{f}^{j-2} \big[S_{j-3} \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] \big] \right\|_2$$

$$\leq \|\overline{\Theta}^{j-2}\|_{\mathrm{op}} \|\boldsymbol{f}^{j-2}[S_{j-3}\overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}]]\|_2$$
$$\leq \|\overline{\Theta}^{j-2}\|_{\mathrm{op}} \|S_{j-3}\overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}]\|_2$$
$$\leq \cdots$$
$$\leq \left(\prod_{k=1}^{j-2} \|\overline{\Theta}^k\|_{\mathrm{op}}\right)\|\overline{\Theta}^0 \boldsymbol{x}\|_2$$
$$\leq \left(\prod_{k=0}^{j-2} \|\overline{\Theta}^k\|_{\mathrm{op}}\right)\|\boldsymbol{x}\|_2$$

for all $j \in \{2, \ldots, l\}$. Now, since $\|\overline{\Theta}^k\|_{\mathrm{op}} \leq \|\overline{\Theta}^k\|_{\mathrm{F}} \leq \|\overline{\Theta}^k\|_{2,1}$ and $\overline{\Theta} \in \overline{\mathcal{M}}_{2,1}$, we can deduce from the display that

$$\|S_{j-2}\overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}]\|_2 \leq \left(\prod_{k=0}^{j-2} \|\overline{\Theta}^k\|_{2,1}\right)\|\boldsymbol{x}\|_2 \,.$$

This inequality is our *contraction property*.

By similar arguments, we get for every $\boldsymbol{z}_1, \boldsymbol{z}_2 \in \mathbb{R}^{p^j}$ that

$$\|S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{z}_1] - S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{z}_2]\|_2$$
$$= \|\boldsymbol{f}^l[\overline{\Theta}^{l-1} \cdots \boldsymbol{f}^j[\boldsymbol{z}_1]] - \boldsymbol{f}^l[\overline{\Theta}^{l-1} \cdots \boldsymbol{f}^j[\boldsymbol{z}_2]]\|_2$$
$$\leq \|\overline{\Theta}^{l-1}[\boldsymbol{f}^{l-1} \cdots \boldsymbol{f}^j[\boldsymbol{z}_1]] - \overline{\Theta}^{l-1}[\boldsymbol{f}^{l-1} \cdots \boldsymbol{f}^j[\boldsymbol{z}_2]]\|_2$$
$$\leq \|\overline{\Theta}^{l-1}\|_{\mathrm{op}} \|\boldsymbol{f}^{l-1}[\cdots \boldsymbol{f}^j[\boldsymbol{z}_1]] - \boldsymbol{f}^{l-1}[\cdots \boldsymbol{f}^j[\boldsymbol{z}_2]]\|_2$$
$$\leq \cdots$$
$$\leq \left(\prod_{k=j}^{l-1} \|\overline{\Theta}^k\|_{\mathrm{op}}\right)\|\boldsymbol{z}_1 - \boldsymbol{z}_2\|_2$$

for $j \in \{1, \ldots, l\}$, where $\prod_{k=l}^{l-1} \|\overline{\Theta}^k\|_{\mathrm{op}} := 1$. Hence, similarly as above,

$$\|S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{z}_1] - S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{z}_2]\|_2 \leq \left(\prod_{k=j}^{l-1} \|\overline{\Theta}^k\|_{2,1}\right)\|\boldsymbol{z}_1 - \boldsymbol{z}_2\|_2 \,.$$

This inequality is our *Lipschitz property*.

We now use the contraction and Lipschitz properties of the subnetworks to derive a Lipschitz result for the entire network. We consider two networks $\overline{\boldsymbol{g}}_{\overline{\Theta}}$ and $\overline{\boldsymbol{g}}_{\overline{\Gamma}}$ with parameters $\overline{\Theta} = (\overline{\Theta}^{l-1}, \ldots, \overline{\Theta}^0) \in \overline{\mathcal{M}}_{2,1}$ and $\overline{\Gamma} = (\overline{\Gamma}^{l-1}, \ldots, \overline{\Gamma}^0) \in \overline{\mathcal{M}}_{2,1}$, respectively. Our above-derived splitting argument applied with $j = 1$ and $j = l$, respectively, yields

$$\|\overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]\|_2 = \|S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}]] - S^l \overline{\boldsymbol{g}}_{\overline{\Gamma}}[S_{l-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]\|_2 \,.$$

Elementary algebra and the fact that $S^{j-1}\overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{j-2}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]] = S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[\overline{\Theta}^{j-1}\boldsymbol{f}^{j-1}[S_{j-2}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]$ for $j \in \{2, \ldots, l\}$ then allow us to derive

$$\|\overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]\|_2$$
$$= \left\|S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}]] - \sum_{j=1}^{l}\left(S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{j-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]] - S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{j-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]\right) - S^l \overline{\boldsymbol{g}}_{\overline{\Gamma}}[S_{l-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]\right\|_2$$
$$= \left\|S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}]] - S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_0 \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]\right.$$
$$\left. - \sum_{j=2}^{l}\left(S^j \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{j-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]] - S^{j-1}\overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{j-2}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]\right)\right.$$
$$\left. + S^l \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{l-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]] - S^l \overline{\boldsymbol{g}}_{\overline{\Gamma}}[S_{l-1}\overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]\right\|_2$$

$$
\begin{aligned}
&= \Big\| S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] \big] - S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_0 \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \\
&\quad - \sum_{j=2}^{l} \Big(S^j \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_{j-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] - S^j \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[\overline{\Theta}^{j-1} \boldsymbol{f}^{j-1} \big[S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big] \Big) \\
&\quad + S^l \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_{l-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] - S^l \overline{\boldsymbol{g}}_{\overline{\Gamma}} \big[S_{l-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \Big\|_2 \\
&\leq \big\| S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] \big] - S^1 \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_0 \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big\|_2 \\
&\quad + \sum_{j=2}^{l} \big\| S^j \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_{j-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] - S^j \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[\overline{\Theta}^{j-1} \boldsymbol{f}^{j-1} \big[S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big] \big\|_2 \\
&\quad + \big\| S^l \overline{\boldsymbol{g}}_{\overline{\Theta}} \big[S_{l-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] - S^l \overline{\boldsymbol{g}}_{\overline{\Gamma}} \big[S_{l-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big\|_2 .
\end{aligned}
$$

We bound this further by using the above-derived Lipschitz property of the outer networks and the observation that $S^l \overline{\boldsymbol{g}}_{\overline{\Theta}}[S_{l-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]] = S^l \overline{\boldsymbol{g}}_{\overline{\Gamma}}[S_{l-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}]]$:

$$
\begin{aligned}
\big\| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big\|_2 &\leq \Big(\prod_{k=1}^{l-1} \| \overline{\Theta}^k \|_{2,1} \Big) \big\| S_0 \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - S_0 \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big\|_2 \\
&\quad + \sum_{j=2}^{l} \Big(\prod_{k=j}^{l-1} \| \overline{\Theta}^k \|_{2,1} \Big) \big\| S_{j-1} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] - \overline{\Theta}^{j-1} \boldsymbol{f}^{j-1} \big[S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big\|_2 ,
\end{aligned}
$$

which is by the definition of the inner networks equivalent to

$$
\begin{aligned}
\big\| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big\|_2 &\leq \Big(\prod_{k=1}^{l-1} \| \overline{\Theta}^k \|_{2,1} \Big) \| \overline{\Theta}^0 \boldsymbol{x} - \overline{\Gamma}^0 \boldsymbol{x} \|_2 \\
&\quad + \sum_{j=2}^{l} \Big(\prod_{k=j}^{l-1} \| \overline{\Theta}^k \|_{2,1} \Big) \big\| \overline{\Gamma}^{j-1} \boldsymbol{f}^{j-1} \big[S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] - \overline{\Theta}^{j-1} \boldsymbol{f}^{j-1} \big[S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big\|_2 .
\end{aligned}
$$

Using the properties of the operator norm, we can deduce from this inequality that

$$
\begin{aligned}
\big\| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big\|_2 &\leq \Big(\prod_{k=1}^{l-1} \| \overline{\Theta}^k \|_{2,1} \Big) \| \overline{\Theta}^0 - \overline{\Gamma}^0 \|_{\mathrm{op}} \| \boldsymbol{x} \|_2 \\
&\quad + \sum_{j=2}^{l} \Big(\prod_{k=j}^{l-1} \| \overline{\Theta}^k \|_{2,1} \Big) \| \overline{\Gamma}^{j-1} - \overline{\Theta}^{j-1} \|_{\mathrm{op}} \big\| \boldsymbol{f}^{j-1} \big[S_{j-2} \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big] \big\|_2 .
\end{aligned}
$$

Invoking the mentioned conditions on the activation functions and the contraction property for the inner subnetworks then yields

$$
\begin{aligned}
\big\| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}] \big\|_2 &\leq \Big(\max_{v \in \{0,\dots,l-1\}} \prod_{\substack{k \in \{0,\dots,l-1\} \\ k \neq v}} \max \{ \| \overline{\Theta}^k \|_{2,1}, \| \overline{\Gamma}^k \|_{2,1} \} \Big) \Big(\sum_{j=0}^{l-1} \| \overline{\Gamma}^j - \overline{\Theta}^j \|_{\mathrm{op}} \Big) \| \boldsymbol{x} \|_2 \\
&\leq \sqrt{l} \| \boldsymbol{x} \|_2 \| \overline{\boldsymbol{\Theta}} - \overline{\boldsymbol{\Gamma}} \|_{\mathrm{F}} ,
\end{aligned}
$$

as desired.

The proof for the connection-sparse case is almost the same. The main difference is that one needs to use the $\| \cdot \|_{\infty}$- and $\| \cdot \|_1$-norms (rather than the $\| \cdot \|_2$- and $\| \cdot \|_{\mathrm{op}}$-norms) and the inequality $\| A\boldsymbol{b} \|_{\infty} \leq \| A \|_1 \| \boldsymbol{b} \|_{\infty}$ (rather than the inequality $\| A\boldsymbol{b} \|_2 \leq \| A \|_{\mathrm{op}} \| \boldsymbol{b} \|_2$) to establish suitable contraction and Lipschitz properties. $\qquad\square$

A.2 Entropy Bound

In this section, we establish bounds for the entropies of $\overline{\mathcal{M}}_1$ and $\overline{\mathcal{M}}_{2,1}$. The distance between two networks $\overline{\boldsymbol{g}}_{\overline{\Theta}}$ and $\overline{\boldsymbol{g}}_{\overline{\Gamma}}$ is defined as $\mathrm{dist}[\overline{\boldsymbol{g}}_{\overline{\Theta}}, \overline{\boldsymbol{g}}_{\overline{\Gamma}}] := \sqrt{\sum_{i=1}^n \| \overline{\boldsymbol{g}}_{\overline{\Theta}}[\boldsymbol{x}_i] - \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}_i] \|_\infty^2 / n}$. Given

this distance function and a radius $t \in (0, \infty)$, the metric entropy of a nonempty set $\mathcal{A} \subset \{\overline{\Theta} = (\overline{\Theta}^{l-1}, \ldots, \overline{\Theta}^0) : \overline{\Theta}^j \in \mathbb{R}^{p^{j+1} \times p^j}\}$ is denoted by $H[t, \mathcal{A}]$. We then get the following entropy bounds.

Lemma 1 (Entropy Bounds). *In the framework of Sections 2 and 3, it holds for every $t \in (0, \infty)$ that*

$$H[t, \overline{\mathcal{M}}_1] \leq \left\lceil \frac{4(\overline{v}_\infty)^2 l}{t^2} \right\rceil \log\left[\frac{\overline{v}_\infty \sqrt{l}\, \overline{p}}{t} \right]$$

and

$$H[t, \overline{\mathcal{M}}_{2,1}] \leq \left\lceil \frac{4(\overline{v}_\infty)^2 l \underline{p}}{t^2} \right\rceil \log\left[\frac{\overline{v}_\infty \sqrt{l\underline{p}}\, \overline{p}}{t} \right].$$

Proof of Lemma 1. The first bound can be derived by combining established deterministic and randomization arguments (Carl, 1985);(Lederer, 2010, Proof of Theorem 1.1);(Taheri et al., 2020, Proposition 3).

For the second bound, observe that

$$\|\Theta^j\|_1 = \sum_{i=1}^{p^{j+1}} \sum_{k=1}^{p^j} |(\Theta^j)_{ik}| \leq \sqrt{p^{j+1}} \sum_{k=1}^{p^j} \sqrt{\sum_{i=1}^{p^{j+1}} |(\Theta^j)_{ik}|^2} = \sqrt{p^{j+1}} \|\Theta^j\|_{2,1} = \sqrt{\underline{p}} \|\Theta^j\|_{2,1}$$

for all $j \in \{0, \ldots, l-1\}$ and $\Theta^j \in \mathbb{R}^{p^{j+1} \times p^j}$. We used in turn 1. the definition of the $\|\cdot\|_1$-norm on Page 2, 2. the linearity and interchangeability of finite sums and the inequality $\|\boldsymbol{a}\|_1 \leq \sqrt{b}\|\boldsymbol{a}\|_2$ for all $\boldsymbol{a} \in \mathbb{R}^b$, 3. the definition of the $\|\cdot\|_{2,1}$-norm on Page 4, and 4. the definition of the width $\underline{p}$ on Page 2. Hence, $\overline{\mathcal{M}}_{2,1} \subset \sqrt{\underline{p}}\overline{\mathcal{M}}_1$. A bound for the entropies of $\overline{\mathcal{M}}_{2,1}$ can, therefore, be derived from the first bound by replacing the radii t on the right-hand side by $t/\sqrt{\underline{p}}$. □

A.3 PROOF OF THEOREM 1

In this section, we state a proof for Theorem 1. The proof is inspired by derivations in high-dimensional statistics—see, for example, (Zhuang & Lederer, 2018) and references therein.

Proof of Theorem 1. The main idea of the proof is to contrast the estimators' objective functions evaluated at their minima with the estimators' objective functions at other points. Our first step is to derive what we call a *basic inequality*. By the definition of the estimator in (6), it holds for every $\Theta \in \mathcal{M}_{2,1}$ that

$$\sum_{i=1}^n \left\| \boldsymbol{y}_i - \boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i] \right\|_2^2 + r_{\text{node}} \|\widehat{\Theta}^l\|_{2,1} \leq \sum_{i=1}^n \left\| \boldsymbol{y}_i - \boldsymbol{g}_{\Theta}[\boldsymbol{x}_i] \right\|_2^2 + r_{\text{node}} \|\Theta^l\|_{2,1},$$

where we use the shorthand $\widehat{\Theta} := \widehat{\Theta}_{\text{node}}$. We then invoke the model in (1) to rewrite this inequality as

$$\sum_{i=1}^n \left\| \boldsymbol{g}_*[\boldsymbol{x}_i] + \boldsymbol{u}_i - \boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i] \right\|_2^2 + r_{\text{node}} \|\widehat{\Theta}^l\|_{2,1} \leq \sum_{i=1}^n \left\| \boldsymbol{g}_*[\boldsymbol{x}_i] + \boldsymbol{u}_i - \boldsymbol{g}_{\Theta}[\boldsymbol{x}_i] \right\|_2^2 + r_{\text{node}} \|\Theta^l\|_{2,1}.$$

Expanding the squared terms and rearranging the inequality then yields

$$\sum_{i=1}^n \left\| \boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i] \right\|_2^2 \leq \sum_{i=1}^n \left\| \boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\Theta}[\boldsymbol{x}_i] \right\|_2^2$$

$$+ 2\sum_{i=1}^n \left(\boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i] \right)^\top \boldsymbol{u}_i - 2\sum_{i=1}^n \left(\boldsymbol{g}_{\Theta}[\boldsymbol{x}_i] \right)^\top \boldsymbol{u}_i + r_{\text{node}} \|\Theta^l\|_{2,1} - r_{\text{node}} \|\widehat{\Theta}^l\|_{2,1}.$$

This is our basic inequality.

In the remainder of the proof, we need to bound the first two terms in the last line of the basic inequality. We call these terms the *empirical process terms*. Using the reformulation of the networks in (7), we can write the empirical process term of a general parameter $\Gamma \in \mathcal{M}_{2,1}$ according to

$$2\sum_{i=1}^n \left(\boldsymbol{g}_{\Gamma}[\boldsymbol{x}_i] \right)^\top \boldsymbol{u}_i = 2\sum_{i=1}^n \left(\Gamma^l \overline{\boldsymbol{g}}_{\overline{\Gamma}}[\boldsymbol{x}_i] \right)^\top \boldsymbol{u}_i$$

with $\overline{\Gamma} \in \overline{\mathcal{M}}_{2,1}$. Using the 1. the properties of transpositions, 2. the definition of the trace function, 3. the cyclic property of the trace function, and 4. the linearity of the trace function yields further

$$
\begin{aligned}
2\sum_{i=1}^{n} (\boldsymbol{g}_{\boldsymbol{\Gamma}}[\boldsymbol{x}_i])^{\top}\boldsymbol{u}_i &= 2\sum_{i=1}^{n} (\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}(\Gamma^l)^{\top}\boldsymbol{u}_i \\
&= 2\sum_{i=1}^{n} \operatorname{trace}\Big[(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}(\Gamma^l)^{\top}\boldsymbol{u}_i\Big] \\
&= 2\sum_{i=1}^{n} \operatorname{trace}\Big[\boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}(\Gamma^l)^{\top}\Big] \\
&= 2\operatorname{trace}\Big[\Big(\sum_{i=1}^{n}\boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}\Big)(\Gamma^l)^{\top}\Big].
\end{aligned}
$$

Now, 1. denoting the column-vector that corresponds to the kth column of a matrix A by $A_{\bullet k}$, 2. using Hölder's inequality, 3. using Hölder's inequality again, and 4. again Hölder's inequality and our definitions of the elementwise ℓ_{∞}-and ℓ_1-norms, we find

$$
\begin{aligned}
2\sum_{i=1}^{n} (\boldsymbol{g}_{\boldsymbol{\Gamma}}[\boldsymbol{x}_i])^{\top}\boldsymbol{u}_i &= 2\sum_{k=1}^{p^l} \Big\langle \Big(\sum_{i=1}^{n}\boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}\Big)_{\bullet k}, (\Gamma^l)_{\bullet k}\Big\rangle \\
&\leq 2\sum_{k=1}^{p^l} \Big\| \Big(\sum_{i=1}^{n}\boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}\Big)_{\bullet k}\Big\|_2 \big\|(\Gamma^l)_{\bullet k}\big\|_2 \\
&\leq 2\max_{k\in\{1,\dots,p^l\}} \Big\| \Big(\sum_{i=1}^{n}\boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}\Big)_{\bullet k}\Big\|_2 \sum_{k=1}^{p^l}\big\|(\Gamma^l)_{\bullet k}\big\|_2 \\
&\leq 2\sqrt{m}\Big\| \sum_{i=1}^{n}\boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Gamma}}}[\boldsymbol{x}_i])^{\top}\Big\|_{\infty}\big\|\Gamma^l\big\|_{2,1},
\end{aligned}
$$

which implies in view of the definition of the effective noise in (8)

$$
2\sum_{i=1}^{n} (\boldsymbol{g}_{\boldsymbol{\Gamma}}[\boldsymbol{x}_i])^{\top}\boldsymbol{u}_i \leq r^*_{\text{node}}\big\|\Gamma^l\big\|_{2,1}.
$$

This inequality is our bound on the empirical process terms.

We can combine the bound on the empiricial process term and the basic inequality to find

$$
\begin{aligned}
\sum_{i=1}^{n}\big\|\boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i]\big\|_2^2 \leq{} &\sum_{i=1}^{n}\big\|\boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\Theta}[\boldsymbol{x}_i]\big\|_2^2 \\
&+ r^*_{\text{node}}\|\widehat{\Theta}^l\|_{2,1} + r^*_{\text{node}}\|\Theta^l\|_{2,1} + r_{\text{node}}\|\Theta^l\|_{2,1} - r_{\text{node}}\|\widehat{\Theta}^l\|_{2,1}.
\end{aligned}
$$

Using then the assumption $r_{\text{node}} \geq r^*_{\text{node}}$ yields

$$
\sum_{i=1}^{n}\big\|\boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i]\big\|_2^2 \leq \sum_{i=1}^{n}\big\|\boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\Theta}[\boldsymbol{x}_i]\big\|_2^2 + 2r_{\text{node}}\|\Theta^l\|_{2,1}.
$$

Multiplying both sides by $1/n$ and taking the infimum over $\Theta \in \mathcal{M}_{2,1}$ on the right-hand side then gives

$$
\frac{1}{n}\sum_{i=1}^{n}\big\|\boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\widehat{\Theta}}[\boldsymbol{x}_i]\big\|_2^2 \leq \inf_{\Theta\in\mathcal{M}_{2,1}}\Big\{\frac{1}{n}\sum_{i=1}^{n}\big\|\boldsymbol{g}_*[\boldsymbol{x}_i] - \boldsymbol{g}_{\Theta}[\boldsymbol{x}_i]\big\|_2^2 + \frac{2r_{\text{node}}}{n}\|\Theta^l\|_{2,1}\Big\}.
$$

Invoking the definition of the prediction error on Page 4 gives the desired result.

The proof for the connection-sparse estimator is virtually the same. $\qquad\square$

A.4 PROOF OF PROPOSITION 1

In this section, we give a short proof of Proposition 1.

Proof of Proposition 1. Verify the fact that if the all-zeros parameter is neither a solution of (3) nor of (5), all solutions $\widehat{\boldsymbol{\Theta}}_{\mathrm{con}}$ and $\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}}$ of (3) and (5), respectively, satisfy $(\widehat{\boldsymbol{\Theta}}_{\mathrm{con}})^j, (\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^j \neq \mathbf{0}_{p^{j+1} \times p^j}$ for all $j \in \{0, \ldots, l\}$.

It then follows from the assumed nonnegative homogeneity, $r_{\mathrm{con}} > 0$, and the definition of the estimator in (3) that $\|(\widehat{\boldsymbol{\Theta}}_{\mathrm{con}})^0\|_1, \ldots, \|(\widehat{\boldsymbol{\Theta}}_{\mathrm{con}})^{l-1}\|_1 = 1$ for all solutions $\widehat{\boldsymbol{\Theta}}_{\mathrm{con}}$.

Given a solution $\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}}$ of (5), define $a := \|(\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^0\|_1/(l+1) + \cdots + \|(\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^l\|_1/(l+1)$ and verify the fact that $\boldsymbol{\Gamma} \in \mathcal{M}$ with $\Gamma^0 := a(\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^0/\|(\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^0\|_1, \Gamma^1 := a(\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^1/\|(\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}})^1\|_1, \ldots$ has the same value in the objective function as $\widetilde{\boldsymbol{\Theta}}_{\mathrm{con}}$.

$\square$

A.5 PROOF OF PROPOSITION 2

In this section, we establish a proof of Proposition 2. The key tools are the Lipschitz property of Proposition 3 and the entropy bounds of Lemma 1.

Proof of Proposition 2. The main idea is to rewrite the event under consideration in a form that is amenable to known tail bounds for suprema of empirical processes with subgaussian random variables.

The connection-sparse bound follows from

$$
\begin{aligned}
&P\left\{r^*_{\mathrm{con}} \geq c\overline{v}_\infty \sqrt{nl\log[2mn\overline{p}]}\right\} \\
&= P\left\{2 \sup_{\overline{\boldsymbol{\Psi}} \in \overline{\mathcal{M}}_1} \left\|\sum_{i=1}^n \boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Psi}}}[\boldsymbol{x}_i])^\top\right\|_\infty \geq c\overline{v}_\infty \sqrt{nl\log[2mn\overline{p}]}\right\} \\
&\leq mp^l \max_{\substack{j \in \{1,\ldots,m\} \\ k \in \{1,\ldots,p^l\}}} P\left\{2 \sup_{\overline{\boldsymbol{\Psi}} \in \overline{\mathcal{M}}_1} \left|\left(\sum_{i=1}^n \boldsymbol{u}_i(\overline{\boldsymbol{g}}_{\overline{\boldsymbol{\Psi}}}[\boldsymbol{x}_i])^\top\right)_{jk}\right| \geq c\overline{v}_\infty \sqrt{nl\log[2mn\overline{p}]}\right\} \\
&\leq mp^l \cdot \frac{1}{mn\overline{p}} \\
&\leq \frac{1}{n},
\end{aligned}
$$

where we use in turn 1. the definition of r^*_{con} in (8), 2. the union bound, 3. van de Geer (2000, Corollary 8.3) and our Proposition 3 and Lemma 1, and 4. the inequality $p^l \leq \overline{p} = \sum_{j=0}^l p^{j+1}p^j$ and consolidating the factors. The key concept underlying van de Geer (2000, Corollary 8.3 on Page 128) is chaining (van der Vaart & Wellner, 1996, Page 90).

The same considerations also apply to the node-sparse case, but we get an additional factor $\sqrt{m}$ from the definition of the effective noise in (8) and a factor $\sqrt{\underline{p}}$ from the entropy bound in Lemma 1. The differences between the bounds for the connection- and node-sparse cases in terms of $\overline{v}_\infty$ vs. $\overline{v}_2$ stem from the different Lipschitz constants in Proposition 3. $\square$