Regularized Molecular Conformation Fields

Abstract

Predicting energetically favorable 3-dimensional conformations of organic molecules from molecular graph plays a fundamental role in computer-aided drug discovery research. However, effectively exploring the high-dimensional conformation space to identify (meta) stable conformers is anything but trivial. In this work, we introduce RMCF, a novel framework to generate a diverse set of low-energy molecular conformations through sampling from a regularized molecular conformation field. We develop a data-driven molecular segmentation algorithm to automatically partition each molecule into several structural building blocks to reduce the modeling degrees of freedom. Then, we employ a Markov Random Field to learn the joint probability distribution of fragment configurations and inter-fragment dihedral angles, which enables us to sample from different low-energy regions of a conformation space. Our model constantly outperforms state-of-the-art models for the conformation generation task on the GEOM-Drugs dataset. We attribute the success of RMCF to modeling in a regularized feature space and learning a global fragment configuration distribution for effective sampling. The proposed method could be generalized to deal with larger biomolecular systems.

1   Introduction

The spatial arrangement of atoms within a molecule, also known as molecular conformation, determines the molecular physico-chemical properties, which plays an essential role in downstream computer-aided drug discovery tasks. However, the high-dimensional conformation space spanned by all atomic degrees of freedom (DoF) makes it a great challenge to identify the local minima of the associated *potential energy surface* (PES) of a molecule. Recently, many machine learning (ML) models have achieved remarkable success in molecular conformation generation tasks [Mansimov et al., 2019, Simm and Hernandez-Lobato, 2020, Xu et al., 2021a, Ganea et al., 2021, Xu et al., 2022], exhibiting orders of magnitude faster conformation prediction speed than traditional computational simulation approaches. This makes ML generative models a powerful tool for high-throughput screening in drug discovery, especially large molecules.

To fully exploit the power of ML in molecular conformation generation, we need to tackle a few key challenges. First, a molecule exhibits invariance under SE(3) transformations (i.e., translation and rotation) in 3-dimensional (3D) Euclidean space. In other words, each molecular conformation is uniquely defined up to rigid motion. Hence a single molecule can adopt an infinite set of possible poses. Second, molecules exhibit a variety of dynamics under ambient conditions (e.g., bond rotation, vibration, etc.), leading to a possibly complex PES landscape of high dimension. This makes it particularly challenging for ML models to identify local minima within this space to generate energetically favorable conformations effectively.

Some recently developed ML models tried to solve these problems from different perspectives. For instance, GraphDG[Simm and Hernandez-Lobato, 2020] and CGCF[Xu et al., 2021a] used distance geometry as invariant features for molecular representation learning. The drawbacks of

such representations are that these invariant variables are potentially redundant and exhibit mutual dependency, which may cause numerical instability during training. One can also design equivariant networks to hard-code the invariance/equivariance condition into the model[Satorras et al., 2021, Xu et al., 2022]. These models circumvent using intermediate invariant features, but instead directly learn from the spatial arrangement of atoms. However, some studies[Cohen et al., 2018, Li et al., 2021] have suggested that the specialized equivariant layers may cause some loss in the expressiveness of the neural network. On the other hand, GeoMol[Ganea et al., 2021] predicts a local structure for each atom, followed by assembling these atom-based building blocks to form the molecular conformation. These models have difficulty dealing with cyclic graphs (e.g., benzyl group) and may lead to unreasonable conformation predictions.

In the meantime, we realize that the high-dimensional PES could be described in a reduced basis by considering only a few significant DoF that contribute to the low-energy conformations. Specifically, consider the well-known example of the potential energy diagram of ethane molecule (Figure 1), while the molecule exhibits a total of 18 DoF, we could capture the most significant dynamics using a single variable, i.e., the rotation w.r.t. the carbon-carbon bond, quantified by the H-C-C-H dihedral angle. Other DoF in the ethane molecule, e.g., the stretching and bending of other bonds, do not have significant impact on the potential energy landscape, where they can be treated as small perturbations to the molecular conformation within a potential well. In other words, to serve the purpose of effective sampling local minima for low-energy conformations, we could reduce the dimension of the conformation space by tracking only a few significant DoF, as long as they adequately shape the corresponding energy landscape (e.g., the "ω" shape in Figure 1). It then follows naturally to generate new conformers by sampling from the low-dimensional conformation space, which is physically meaningful.

Figure 1: Schematic of the potential energy diagram of an ethane molecule. The upper panel shows the Newman projection of three degenerate eclipsed conformations, the lower panel shows two energetically-favorable staggered conformations. The H-C-C-H dihedral angle alone is sufficient to describe the potential energy change.

This paper presents Regularized Molecular Conformation Fields (RMCF), a novel framework for 3D molecular conformation generation. The novelty of this work lies in (1) developing a data-driven molecular segmentation algorithm to partition each molecule into fragments with low internal flexibility, which serves as a regularization term for our framework, and (2) employing a Markov Random Field (MRF[Murphy, 2012]) to capture the joint probability distribution of intra-fragment configurations and inter-fragment dihedral angles. Our work is partly inspired by the Ising model[Cipra, 1987] for simulating quantum spin systems, where we make an analogy between the spin state (i.e., spin up or down) and the configuration of each molecular fragment (e.g., chair or boat conformation of cyclohexane). The introduction of molecular fragments effectively reduces the dimension of the conformation space, where we only keep the most significant components (i.e., fragment configuration and inter-fragment dihedral angle) for conformation generation. This molecular segmentation serves as a regularization term for our framework, which is data-driven and has the effect of reducing feature dimensions. Then, we employ MRF as a generalized setting of the Ising model (with more spin states and more coupling terms) to capture the relationship between adjacent fragments and model the uncertainty of conformations. By estimating the parameters of the MRF, we can obtain an energy surface with different conformations. Therefore, we can later sample from the low-energy region of PES, which is implicitly learned by the MRF, to obtain energetically favorable molecular conformations.

We demonstrate the effectiveness of RMCF using the GEOM-Drugs dataset[Axelrod and Gomez-Bombarelli, 2022], where results show that RMCF significantly outperforms state-of-the-art ML models. Specifically, our model can generate a diverse set of low-energy conformations located at distinct local minima of the underlying PES. We attribute the success of our model to the automatic construction of low-dimensional conformation space and learning a joint probability distribution using MRF to achieve effective sampling of new conformations. We argue that capturing the governing

dynamics of molecular systems could significantly improve the performance of learning models for generative purposes.

2 Related Work

Recently, various machine learning models have been proposed for molecular conformation generation. CVGAE [Mansimov et al., 2019] first used a variational autoencoder (VAE) model to generate conformation with atomic coordinates. The model suffers from multi-modality problems due to invariance under SE(3) transformations. Some studies tried to address this problem using two main types of approaches. The first type of approach use intermediate invariant features, such as atomic distance, to encode the system, then leverage geometric algorithms to solve a set of atomic coordinates that match the invariant quantities. For example, GraphDG[Simm and Hernandez-Lobato, 2020] and CGCF [Xu et al., 2021a] proposed to predict the distance matrix by VAE and Flow, respectively, and solve the geometry through the Distance Geometry (DG) method [Liberti et al., 2014]. However, these invariant features are potentially redundant and could exhibit mutual dependency, which makes these methods numerically unstable and could predict unreasonable conformations. Some studies suggest that inconsistencies between training and test are responsible for the poor performance of the models. ConfGF[Shi et al., 2021] passed the gradient of loss to coordinates and ConfVAE [Xu et al., 2021b] used a bilevel optimization to alleviate the inconsistencies. GeoMol[Ganea et al., 2021] defined another set of invariants, which are bond lengths, bond angles, and dihedral angles. Geomol generated multiple conformations by adding noise to the input, which did not learn a global energy function from which to sample the low-energy conformations.

Another type of approach applies equivariant networks or kernels, such that after the input is rotated and translated, the output can be transformed accordingly. Satorras et al. [2021] proposed an equivariant normalizing flow, E(n)-flow, and Xu et al. [2022] proposed GeoDiff, which is a diffusion model [Song and Ermon, 2019] with equivariant Markov kernels. Equivariant methods circumvent intermediate invariants and model the coordinates directly, but require the design of specialized equivariant layers, which some studies have suggested would lose the expressive power of the network.

In addtion, some software for conformation generation are widely used in biochemical research. For instance, RDKit[Riniker and Landrum, 2015] is a popular open-source software generate use ETKDG distance geometry, and OMEGA is a commercial software which assembles the fragments with knowledge-based rules to generate conformations.

3 RMCF: Generating in Regularized Conformation Space

In this section, we present the regularized molecular conformation field RMCF in detail. Generally, RMCF learns the energy landscape of molecular conformations by modeling a joint distribution of fragment states and dihedral angles, from which we can perform inference or draw diverse samples.

We will first give a brief overview of RMCF in Section 3.1. Then we construct and parameterize the RMCF in Section 3.2 and Section 3.3. Later in Section 3.4 and Section 3.5, we describe how to estimate the parameters and draw samples from the RMCF. Finally, we assemble the fragments into a molecule in Section 3.6.

3.1 Formalization

We formally describe the pipeline of our method. Given a molecular graph G, we segment it into fragments and construct a regularized molecular conformation field $\mathcal{G}$. Then, we infer a configuration set $\mathcal{X}$ including the fragment state and the dihedral state from the learned joint probability distribution using MRF. Finally, we assemble the 3D fragments with the predicted inter-fragment dihedral angles to generate the conformation R.

$$G \longrightarrow \mathcal{G} \longrightarrow \mathcal{X} \longrightarrow R$$

A regularized conformation field $\mathcal{G} = (F, D, E)$ is an undirected graph formed by a collection of fragment vertices $F = (f_1, f_2, \cdots, f_{N_F})$, a collection of dihedral vertices $D = (d_1, d_2, \cdots, d_{N_D})$,

| Molecular Graph | RMCF | Assembling | Conformation |

Figure 2: The workflow of RMCF. Starting from a 2D molecular graph, we partition the molecule into fragments with low internal-DoF, and use MRF to model the joint probability distribution of fragment and dihedral configurations. The last step is to assemble the predicted conformation according to the predicted dihedral angles and fragment states.

and a collection of edges $E = (e_1, e_2, \cdots, e_{N_E}) \subset F \times D$, where N_F, N_D, N_E are the size of F, D, E, respectively [Wainwright et al., 2008]. Each edge consists of a pair of vertices $f \in F$ and $d \in D$. We associate with each vertex $f \in F$ a random variable X_f taking values in a set of possible fragment variants, each vertex $d \in D$ a random variable X_d taking values in $\mathbb{R}$. Such a graph is a collection of distributions that factorize as:

$$P(f_1, \cdots, f_{N_F}, d_1, \cdots, d_{N_d}) = \frac{1}{Z} \prod_{C \in \mathcal{C}} \psi_C(f_C, d_C) \tag{1}$$

where Z is the normalizing factor, $\mathcal{C}$ is the maximal cliques of a graph.

A configuration $\mathcal{X} = (\mathcal{X}_f, \mathcal{X}_d)$ of the RMCF contains a state set of fragment nodes $\mathcal{X}_f = \{x_{f_i} | i = 1, 2, \cdots, N_F\}$ and a state set of dihedral nodes $\mathcal{X}_d = \{x_{d_i} | i = 1, 2, \cdots, N_d\}$.

3.2 Graph Construction with Least DoF Principle

To reduce the DoF of the conformation space, we determine which atoms and bonds on the molecular graph to pack into fragments. As a general rule of thumb, we should minimize the *intra*-fragment DoF while capturing the significant dynamic modes using *inter*-fragment dihedral angles. To that end, we design a data-driven fragment segmentation algorithm. Let $\{f_1, f_2, ..., f_n\}$ be a graph partition of a molecular graph G, f_i is one of the corresponding sub-graphs, also called molecular fragments. First, we use existing functional group segmentation methods such as BRICS [Liu et al., 2017] to pre-cut all molecular graphs and their 3d conformations. We keep all rings but remove all the side chains on them.

After obtaining these molecular fragments, a sufficient number of 3D fragments c are sampled for each 2D fragment and clustered using root-mean-square-deviation (RMSD), which measures the average distance between atoms. The set of cluster centroids are used as a vocabulary $\mathcal{V}(f)$ to represent various 3D states of the 2D fragment f. We defined the measurement of the internal DoF as the maximum RMSD between all the 3D fragment pairs in the vocabulary $\mathcal{V}(f)$.

The best segmentation $\mathcal{P}^*$ should exhibit the least sum of the internal DoF on the resulting fragment set. We employ graph dynamic programming to search for the optimal solution.

$$\mathcal{P}^* = \arg\min_{\mathcal{P}} \sum_{f \in \mathcal{P}} \max_{r_i, r_j \in \mathcal{V}(f)} \mathrm{RMSD}(r_i, r_j) \tag{2}$$

Then we can get the fragment set $F = (f_1, f_2, \cdots, f_{N_F})$ and insert the dihedral vertices between connected fragments to construct the RMCF $\mathcal{G}$ on the molecular graph G.

3.3 Parameterization with GNN

Given the RMCF $\mathcal{G}$ constructed from a molecular graph G, we parameterize it with graph neural networks. Let $\mathbf{e}_f$ and $\mathbf{e}_d$ denote the fragment embedding and the dihedral embedding (which is a "dummy" embedding as the network input), we compute the contextualized representations $\mathbf{r}$ by:

$$\{\mathbf{r}_n | n \in F \cup D\} = \text{GNN}(\{\mathbf{e}_n | n \in F \cup D\}; \mathcal{G}) \tag{3}$$

We can also obtain an oracle configuration $\mathcal{X} = (S, \Phi)$ of the RMCF $\mathcal{G}$ based on the conformation R, which is segmented to $(r_1, r_2, \cdots, r_{N_F})$. For a given fragment f, we pick the state r_s as ground truth which has the minimal RMSD to the real fragment r_i.

$$s = \arg\min_s \text{RMSD}(r_i, r_s), r_s \in \mathcal{V}(f) \tag{4}$$

The dihedral angle φ is defined as the angle between half-planes of two connected 3d fragments. Since the dihedral angle depends on the set of the atoms involved in the calculation, for the same type of fragments, we should keep the same set of atoms to calculate.

Figure 3: Dihedral angle

For a system where two fragments contain four consecutively-bonded atoms, two half-planes intersect on a rotatable bond. The angle between them is the *dihedral angle*. If the connected points are sequentially numbered and located at positions $\mathbf{p}_1, \mathbf{p}_2, \mathbf{p}_3, \mathbf{p}_4$ and the corresponding bond vectors are defined as $\mathbf{u}_1 = \mathbf{p}_2 - \mathbf{p}_1, \mathbf{u}_2 = \mathbf{p}_3 - \mathbf{p}_2, \mathbf{u}_3 = \mathbf{p}_4 - \mathbf{p}_3$. Then we have:

$$\varphi(\mathbf{u}_1, \mathbf{u}_2, \mathbf{u}_3) = \text{atan2}\left(|\mathbf{u}_2| \, \mathbf{u}_1 \cdot (\mathbf{u}_2 \times \mathbf{u}_3), (\mathbf{u}_1 \times \mathbf{u}_2) \cdot (\mathbf{u}_2 \times \mathbf{u}_3)\right) \tag{5}$$

In practice, we quantize the angles into a number of evenly divided bins to discretize the continuous angle values.

3.4 Parameter Estimation

The parameter estimation in RMCF is intractable, especially when it is loopy [Murphy, 2012]. Piecewise learning has proven efficient in training graphical models [Sutton and McCallum, 2009, 2012, Lin et al., 2016, Qu et al., 2022], which minimizes a tractable upper bound on the exact log partition function [Sutton and McCallum, 2012]. We train the parameters of each edge independently, and the learned parameters from this local training approach can be used for global inference purposes.

Concretely, for a pair of nodes in the field $e = (f, d) \in \mathcal{G}$, let $|f|$ and $|g|$ denote the cardinality of the state space, $y^f \in \mathbb{I}$ and $y^d \in \mathbb{I}$ indicate the true state from an index set. We calculate the representations of them, $\mathbf{r}_f \in \mathbb{R}^D$ and $\mathbf{r}_d \in \mathbb{R}^D$ from the graph neural networks. The node-wise negative log-likelihood is defined as:

$$\mathcal{L}_n(f) = -\log \text{softmax}\left(\text{out}(\mathbf{r}_f)\right)[y^f] \tag{6}$$

where $\text{out}(\cdot) : \mathbb{R}^D \to \mathbb{R}^{|f|}$ is an operator parameterized by a linear layer. The edge-wise negative log-likelihood is defined as:

$$\mathcal{L}_e(f, d) = -\log \text{softmax}\left(\mathbf{E}_f \mathbf{W}_e \mathbf{E}_d^{\text{T}}\right)[y^f, y^d] \tag{7}$$

where $\mathbf{E}_f \in \mathbb{R}^{|f| \times D}$ and $\mathbf{E}_d \in \mathbb{R}^{|d| \times D}$ are the representations of a set of node states, $\mathbf{W}_e \in \mathbb{R}^{D \times D}$ is a matrix carrying the global information between two nodes. In this study, we use a neural network to parameterize the matrix [Sun et al., 2019]:

$$\mathbf{W}_e = \text{MLP}(\mathbf{r}_f, \mathbf{r}_d)$$

To sum up, the complete training objective is:

$$\mathcal{L} = \sum_{e \in E} \mathcal{L}_e(f, d) + \sum_{n \in F \cup D} \mathcal{L}_n(n)$$

3.5 Inference & Sampling

In this section, we give a brief overview of how we perform inference and sampling in RMCF.

Inference If a RMCF is acyclic (linear- or tree-structured), the max-a-posterior decoding can be done via dynamic programming [Forney, 1973]. Cases are a bit complicated when loops occur in the RMCF. We adopt a more generalized algorithm, namely loopy belief propagation (LBP) [Murphy et al., 2013], to overcome such obstacles. We refer the reader to textbooks for more details about the LBP algorithm [Murphy, 2012].

Sampling Markov Chain Monte Carlo is popular in sampling from graphical models [Andrieu et al., 2003]. We employs an simple variant of it, Gibbs sampling [George and McCulloch, 1993], to draw samples from RMCF. Specifically, we resample each fragment or dihedral individually, keeping all other nodes fixed in each iteration [Murphy, 2012].

Clustering Upon the Markov chain achieves detailed balance, we can draw $1,000$ samples randomly from it. However, these samples can be governed by a few conformations, which means most of them are similar. We measure the distance between two configurations $\mathcal{X}^{(1)}$ and $\mathcal{X}^{(2)}$ by:

$$d(\mathcal{X}^{(1)}, \mathcal{X}^{(2)}) = \|\mathcal{X}_f^{(1)} - \mathcal{X}_f^{(2)}\|_2^2 + \mathbb{H}(\mathcal{X}_d^{(1)}, \mathcal{X}_d^{(2)}) \tag{8}$$

where $\|\cdot\|_2$ is the Euclidean norm measuring the difference between dihedrals, $\mathbb{H}$ is the Hamming distance [Hamming, 1950] counting the number of different fragment states. We further run K-means clustering [MacQueen et al., 1967] based on the pair-wise distance to partition all samples into a fixed number of clusters.

Algorithm 1 Sampling Molecular Conformations From RMCF

Require: an RMCF $\mathcal{G}$, the number of conformations N_C, the number of sampling iterations N_S
Ensure: a set S_C containing N_C conformations

  $S \leftarrow \{\}$
  initialize a configuration $\mathcal{X}$ randomly
  for $i \in [1, 2, \cdots, N_S]$ **do**
    for $n \in F \cup D$ **do**
      $U \leftarrow \{u|(n, u) \in E\}$ $\triangleright$ x_u is fixed in this iteration
      $P \leftarrow \text{softmax} \left\{\sum_{u \in U} \mathbf{E}_u[x_u]\mathbf{W}_{un}\mathbf{E}_n^{\mathrm{T}} + \text{out}(\mathbf{r}_n)\right\}$ $\triangleright$ the value can be pre-computed
      $x_n \sim \text{Cat}(|n|, P)$
    end for
    add $\mathcal{X}$ to S
  end for
  compute the pairwise distance K with Eq.8
  $S_C \leftarrow$ run clustering with $k = N_C$ over S based on K
  return S_C

3.6 Assembling

Once we have predicted the dihedral angle φ between two fragments, we need to compute the transformation matrix $\mathbf{T}$ to align the two fragments in arbitrary position and make their dihedral angle equal to the given value φ and repeat these steps until the whole conformation is assembled.

Given two fragments with six points, located at $\mathbf{p}_1, \mathbf{p}_2, \mathbf{p}_3, \mathbf{p}_4, \mathbf{p}_5, \mathbf{p}_6$, the bond vectors are $\mathbf{u}_1 = \mathbf{p}_2 - \mathbf{p}_1, \mathbf{u}_2 = \mathbf{p}_3 - \mathbf{p}_2, \mathbf{v}_1 = \mathbf{p}_5 - \mathbf{p}_4$, $\mathbf{v}_2 = \mathbf{p}_6 - \mathbf{p}_5$. $\mathbf{u}_2$ and $\mathbf{v}_1$ are the same bond after assembling, so we have $|\mathbf{u}_2| = |\mathbf{v}_1|$.

First we need to rotate the second fragment around some axis so that $\mathbf{u}_2$ and $\mathbf{v}_1$ will be parallel. this axis is the unit normal vector $\mathbf{n}$ towards the plane of $\mathbf{u}_2$ and $\mathbf{v}_1$, and the rotate angle is equal to the cross angle θ.

Figure 4: Transformations for Assembling

$$\cos\theta = \frac{\mathbf{u}_2 \cdot \mathbf{v}_1}{|\mathbf{u}_2| |\mathbf{v}_1|}, \quad \mathbf{n} = \frac{\mathbf{u}_2 \times \mathbf{v}_1}{|\mathbf{u}_2 \times \mathbf{v}_1|}$$

By using the Rodrigues' rotation formula, we can obtain the rotation matrix with unit normal vector $\mathbf{n}$ and rotation angle θ. Next, we rotate the second fragment around $\mathbf{u}_2$ to match with the target dihedral angle. Finally we align the anchor points by calculating the final transformation matrix $\mathbf{T}$ as a composite matrix of two rotations and one translation.

$$\mathbf{R}(\mathbf{n}, \theta) = I \cos\theta + (1 - \cos\theta) \begin{pmatrix} n_x \\ n_y \\ n_z \end{pmatrix} (n_x, n_y, n_z) + \sin\theta \begin{pmatrix} 0 & -n_z & n_y \\ n_z & 0 & -n_x \\ -n_y & n_x & 0 \end{pmatrix} \quad (9)$$

$$\mathbf{R}' = \mathbf{R}(\mathbf{u}_2, \varphi - \varphi') = \mathbf{R}(\mathbf{u}_2, \varphi - \varphi(\mathbf{u}_1, \mathbf{u}_2, \mathbf{R}(n, \theta)\mathbf{v}_2)), \quad \mathbf{t} = (\mathbf{p}_1 - \mathbf{R}'\mathbf{R}\mathbf{p}_4)^{\mathbf{T}}$$

$$\mathbf{T} = \begin{pmatrix} \mathbf{R}'\mathbf{R} & \mathbf{t} \\ 0 & 1 \end{pmatrix} \quad (10)$$

4 Experiment

We now demonstrate the effectiveness of RMCF on the conformation generation task for drug-like molecules.

4.1 Dataset and Baseline

Following previous work on conformation generation, we benchmark our model performance using the GEOM-Drugs dataset, which contains mid-sized organic molecules with high quality conformations. We use the same test set as that in GeoDiff, where the remaining molecules are used for training and validation with a 9:1 ratio. The final training/validation/test set contains 271,539/30,171/1,034 molecules, respectively.

Our molecular segmentation algorithm eventually returned a vocabulary of 9,081 types 2D fragments and 30,408 types of 3D fragments for the GEOM-Drugs dataset. As for the angular discretization of dihedral angles, the 360 degree interval is evenly divided into 72 bins. We adopt the Message-Passing Neural Network (MPNN) [Gilmer et al., 2017] as the framework for implementing our graph neural network. Other implementation details are provided in Appendix A.

We compare our RMCF model with seven recently developed ML models. The performance of CVGAE[Mansimov et al., 2019], GraphDG[Simm and Hernandez-Lobato, 2020], CGCF[Xu et al., 2021a], and ConfVAE[Xu et al., 2021b], ConfGF[Shi et al., 2021] are tabulated as reported in Shi et al. [2021] and Xu et al. [2021b], and we show the metrics of GeoMol[Ganea et al., 2021] and GeoDiff[Xu et al., 2022] as reported in Xu et al. [2022]. We also compare our model with open-source software RDKit and commercial software OMEGA (as reported in Ganea et al. [2021]).

4.2 Evaluation Metrics

To quantitatively measure the quality and diversity of generated molecular conformations, we use the same evaluation metrics as defined in Ganea et al. [2021] and Xu et al. [2022]. Let S_g and S_r denote the set of generated and reference conformations, respectively. The coverage score (COV) and matching score (MAT) following the conventional Recall measurement can be defined as:

$$\text{COV-R}(S_g, S_r) = \frac{1}{|S_r|} \left| \left\{ \mathcal{C} \in S_r \mid \text{RMSD}(\mathcal{C}, \hat{\mathcal{C}}) \leq \delta, \hat{\mathcal{C}} \in S_g \right\} \right|$$

$$\text{MAT-R}(S_g, S_r) = \frac{1}{|S_r|} \sum_{\mathcal{C} \in S_r} \min_{\hat{\mathcal{C}} \in S_g} \text{RMSD}(\mathcal{C}, \hat{\mathcal{C}})$$

where the threshold δ in coverage score is set as 1.25Å for the GEOM-Drugs dataset in our work. The corresponding prediction precision metrics, i.e., COV-P and MAT-P, are defined in a similar

Table 1: Results on the **GEOM-Drugs** dataset, without FF optimization.

Models	COV-R (%) $\downarrow$		MAT-R (Å) $\downarrow$		COV-P (%) $\uparrow$		MAT-P (Å) $\downarrow$	
	Mean	Median	Mean	Median	Mean	Median	Mean	Median
CVGAE	0.00	0.00	3.070	2.994	-	-	-	-
GraphDG	8.27	0.00	1.972	1.985	2.08	0.00	2.434	2.410
CGCF	53.96	57.06	1.249	1.225	21.68	13.72	1.857	1.807
ConfVAE	55.20	59.43	1.238	1.142	22.96	14.05	1.829	1.816
GeoMol	67.16	71.71	1.088	1.059	-	-	-	-
ConfGF	62.15	70.93	1.163	1.160	23.42	15.52	1.722	1.686
GeoDiff	**89.13**	**97.88**	0.863	0.853	61.47	64.55	1.171	1.123
RDKit	60.19	64.28	1.219	1.133	69.23	87.63	1.113	0.963
OMEGA	81.64	97.25	0.851	0.771	77.18	96.15	0.951	0.854
RMCF-R	82.25	90.77	0.839	0.789	**83.02**	**98.50**	**0.812**	**0.722**
RMCF-C	87.12	96.26	**0.749**	**0.709**	82.01	95.91	0.835	0.754

manner, where the set of generated and reference conformations are swapped in the above definition. We set S_g as twice the size of S_r for each molecule for fair comparison with previous work [Ganea et al., 2021, Xu et al., 2022]. The precision-associated metrics focus more on generating accurate conformations that match those in the reference dataset, while the recall-associated metrics emphasize the structural diversity of generated conformations.

4.3 Results and Discussions

The main results are presented in Table 1. We generated conformations by sampling on the RMCF with two strategies: (1) directly sample a specific number of conformations (i.e., S_g), and (2) first generate a sufficient number of conformations (we generate 10,000 conformations in this work), then cluster them into S_g clusters and sample one conformation from each cluster. The model performance associated with the above two strategies are named RMCF-R and RMCF-C, respectively. As shown in the table, RMCF significantly outperforms all other models in all metrics except for the COV-R metric, where our model performance is comparable to that of GeoDiff. In particular, for COV-P and MAT-R metrics, our model shows a significant performance gain compared to others, which means RMCF can generate more accurate and high quality conformations. In addition, we find that the clustering-after-sampling strategy leads to a boost in the structural diversity, while keeping a good quality (i.e., energetically favorable conformations) of the generated conformations.

Since we employ a discretized treatment for the continuous dihedral angle as well as the fragment 3D conformation, the model performance will inevitably have some discrepancy between the predicted and ground truth conformations. To that end, we investigate the upper and lower bound of our model performance to have a better understanding of its predicting power, as shown in Table 2. Specifically, we discretize the ground truth conformations using the molecular segmentation algorithm to obtain the fragment configurations ("gold $\mathcal{X}_f$") and inter-fragment dihedral angles ("gold $\mathcal{X}_d$"), then evaluate the corresponding metrics. On the other hand, we randomly sample some $\mathcal{X}_f$ and $\mathcal{X}_d$, whose evaluation results should indicate the performance lower bound using our fragment representation. Surprisingly, we find that using randomly sampled $\mathcal{X}_f$ and $\mathcal{X}_d$, we can still outperform some previous models. This is an advantage of using molecular fragment as building blocks for conformation generation, since we bypass the need to generate many insignificant variables which may degrade the model performance. We also learn that having accurate dihedral angle predictions (i.e., $\mathcal{X}_d$) is more significant than good fragment configuration predictions (i.e., $\mathcal{X}_f$). These experimental results support our claim that capturing a few significant DoF within a molecule is adequate for generating a diverse set of low-energy conformations, while other DoF could be safely ignored during modeling.

At last, we showcase the generated conformations of two example molecules in Figure 5. For each molecule, we take the first three predicted conformations, and align the non-rigid parts for visualization purposes. From Figure 5(a), we observe a diverse set of conformations mainly driven by the rotation of two single bonds without causing too much steric effect. For the amide bond regions, the model correctly predicts the corresponding dihedral angles to form planar conjugate

Table 2: The empirical upper and lower bound of RMCF performance on the **GEOM-Drugs** dataset.

RMCF Settings	COV-R (%) ↑		MAT-R (Å) ↓		COV-P (%) ↑		MAT-P (Å) ↓	
	Mean	Median	Mean	Median	Mean	Median	Mean	Median
gold $\mathcal{X}_f$,gold $\mathcal{X}_d$	99.16	100.0	0.302	0.242	99.37	100.0	0.290	0.235
rand $\mathcal{X}_f$,gold $\mathcal{X}_d$	96.74	100.0	0.511	0.464	88.93	100.0	0.634	0.561
gold $\mathcal{X}_f$,rand $\mathcal{X}_d$	66.21	77.42	1.125	1.092	40.30	34.25	1.429	1.397
rand $\mathcal{X}_f$,rand $\mathcal{X}_d$	63.60	72.22	1.156	1.135	37.68	31.25	1.463	1.429

* $\mathcal{X}_f$ denotes the fragment configuration set, $\mathcal{X}_d$ denotes the inter-fragment dihedral angle set
* "gold" refers to the ground truth distribution, and "rand" refers to a randomly sampled distribution.

Figure 5: The first three generated conformations of two example molecules. The upper panel shows the 3D atomic arrangement, where the non-rigid fragments are aligned to help visualization. The lower panel indicates where the segmentation has been made for each molecule.

systems. Meanwhile, for Figure 5(b) we see a large planar conjugate system on the left side and a cyclooctane ring on the right. Again, the model accurately captures the conjugate system and only makes variations in the cyclooctane conformations. Interestingly, the segmentation algorithm tends to only preserve the cyclic groups (e.g., benzyl and furan groups), and even cuts through the amide bonds and other acyclic conjugate systems. This behavior is a direct consequence of balancing the vocabulary size and the variety of local chemical environment.

We show that our model performs reasonable segmentation of drug-like molecules into small functional groups with limited internal DoF, and could correctly predict planar conjugate systems. Therefore, we believe that our generative process is essentially sampling from the local-minima of the learned potential energy surface by RMCF, where those non-essential DoF which contribute to local structural perturbations are omitted in our modeling framework. We argue that both the data-driven segmentation and MRF modeling of the joint probability distribution are essential for the success of our model.

5   Conclusion

We introduce RMCF, a novel framework for 3D molecular conformation generation. Our model is physics-motivated, with the central idea to effectively model the joint probability distribution of governing dynamical modes in a reduced conformation space to achieve energetically favorable conformation generation. Experimental results show that RMCF outperforms state-of-the-art models on the GEOM-Drugs dataset to predict a diverse set of conformations located at distinct local minima of the corresponding molecular potential energy surface. Our methodology can be naturally extended to larger biomolecular systems, e.g., proteins, whose conformation prediction is a significant topic in the biological research community. We will address this challenge in our future work.

References

Elman Mansimov, Omar Mahmood, Seokho Kang, and Kyunghyun Cho. Molecular geometry prediction using a deep generative graph neural network. arXiv preprint arXiv:1904.00314, 2019.

Gregor Simm and Jose Miguel Hernandez-Lobato. A generative model for molecular distance geometry. In Hal Daumé III and Aarti Singh, editors, Proceedings of the 37th International Conference on Machine Learning, volume 119, pages 8949–8958. PMLR, 2020.

Minkai Xu, Shitong Luo, Yoshua Bengio, Jian Peng, and Jian Tang. Learning neural generative dynamics for molecular conformation generation. In International Conference on Learning Representations, 2021a.

Octavian-Eugen Ganea, Lagnajit Pattanaik, Connor W Coley, Regina Barzilay, Klavs F Jensen, William H Green, and Tommi S Jaakkola. Geomol: Torsional geometric generation of molecular 3d conformer ensembles. arXiv preprint arXiv:2106.07802, 2021.

Minkai Xu, Lantao Yu, Yang Song, Chence Shi, Stefano Ermon, and Jian Tang. Geodiff: A geometric diffusion model for molecular conformation generation. arXiv preprint arXiv:2203.02923, 2022.

Victor Garcia Satorras, Emiel Hoogeboom, Fabian B Fuchs, Ingmar Posner, and Max Welling. E (n) equivariant normalizing flows for molecule generation in 3d. arXiv preprint arXiv:2105.09016, 2021.

Taco S Cohen, Mario Geiger, Jonas Köhler, and Max Welling. Spherical cnns. arXiv preprint arXiv:1801.10130, 2018.

Xianzhi Li, Ruihui Li, Guangyong Chen, Chi-Wing Fu, Daniel Cohen-Or, and Pheng-Ann Heng. A rotation-invariant framework for deep point cloud analysis. IEEE Transactions on Visualization and Computer Graphics, 2021.

Kevin P Murphy. Machine learning: a probabilistic perspective. MIT press, 2012.

Barry A Cipra. An introduction to the ising model. The American Mathematical Monthly, 94(10): 937–959, 1987.

Simon Axelrod and Rafael Gomez-Bombarelli. Geom, energy-annotated molecular conformations for property prediction and molecular generation. Scientific Data, 9(1):1–14, 2022.

Leo Liberti, Carlile Lavor, Nelson Maculan, and Antonio Mucherino. Euclidean distance geometry and applications. SIAM review, 56(1):3–69, 2014.

Chence Shi, Shitong Luo, Minkai Xu, and Jian Tang. Learning gradient fields for molecular conformation generation. ArXiv, 2021.

Minkai Xu, Wujie Wang, Shitong Luo, Chence Shi, Yoshua Bengio, Rafael Gomez-Bombarelli, and Jian Tang. An end-to-end framework for molecular conformation generation via bilevel programming. arXiv preprint arXiv:2105.07246, 2021b.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In Advances in Neural Information Processing Systems, volume 32, pages 11918–11930. Curran Associates, Inc., 2019.

Sereina Riniker and Gregory A. Landrum. Better informed distance geometry: Using what we know to improve conformation generation. Journal of Chemical Information and Modeling, 55(12): 2562–2574, 2015.

Martin J Wainwright, Michael I Jordan, et al. Graphical models, exponential families, and variational inference. Foundations and Trends® in Machine Learning, 1(1–2):1–305, 2008.

Tairan Liu, Misagh Naderi, Chris Alvin, Supratik Mukhopadhyay, and Michal Brylinski. Break down in order to build up: decomposing small molecules for fragment-based drug design with e molfrag. Journal of chemical information and modeling, 57(4):627–631, 2017.

Charles Sutton and Andrew McCallum. Piecewise training for structured prediction. Machine learning, 77(2):165–194, 2009.

Charles Sutton and Andrew McCallum. Piecewise training for undirected models. arXiv preprint arXiv:1207.1409, 2012.

Guosheng Lin, Chunhua Shen, Anton Van Den Hengel, and Ian Reid. Efficient piecewise training of deep structured models for semantic segmentation. In Proceedings of the IEEE conference on computer vision and pattern recognition, pages 3194–3203, 2016.

Meng Qu, Huiyu Cai, and Jian Tang. Neural structured prediction for inductive node classification. ICLR, 2022.

Zhiqing Sun, Zhuohan Li, Haoqing Wang, Di He, Zi Lin, and Zhihong Deng. Fast structured decoding for sequence models. Advances in Neural Information Processing Systems, 32, 2019.

G David Forney. The viterbi algorithm. Proceedings of the IEEE, 61(3):268–278, 1973.

Kevin Murphy, Yair Weiss, and Michael I Jordan. Loopy belief propagation for approximate inference: An empirical study. arXiv preprint arXiv:1301.6725, 2013.

Christophe Andrieu, Nando De Freitas, Arnaud Doucet, and Michael I Jordan. An introduction to mcmc for machine learning. Machine learning, 50(1):5–43, 2003.

Edward I George and Robert E McCulloch. Variable selection via gibbs sampling. Journal of the American Statistical Association, 88(423):881–889, 1993.

Richard W Hamming. Error detecting and error correcting codes. The Bell system technical journal, 29(2):147–160, 1950.

James MacQueen et al. Some methods for classification and analysis of multivariate observations. In Proceedings of the fifth Berkeley symposium on mathematical statistics and probability, volume 1, pages 281–297. Oakland, CA, USA, 1967.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In Proceedings of the 34th International Conference on Machine Learning-Volume 70, pages 1263–1272. JMLR. org, 2017.