PRUNING EDGES AND GRADIENTS TO LEARN HYPERGRAPHS FROM LARGER SETS

ABSTRACT

This paper aims for set-to-hypergraph prediction, where the goal is to infer the set of relations for a given set of entities. This is a common abstraction for applications in particle physics, biological systems and combinatorial optimization. We address two common scaling problems encountered in set-to-hypergraph tasks that limit the size of the input set: the exponentially growing number of hyperedges and the run-time complexity, both leading to higher memory requirements. We make three contributions. First, we propose to predict and supervise the *positive* edges only, which changes the asymptotic memory scaling from exponential to linear. Second, we introduce a training method that encourages iterative refinement of the predicted hypergraph, which allows us to skip iterations in the backward pass for improved efficiency and constant memory usage. Third, we combine both contributions in a single set-to-hypergraph model that enables us to address problems with larger input set sizes. We provide ablations for our main technical contributions and show that our model outperforms prior state-of-the-art, especially for larger sets.

1 INTRODUCTION

Inferring the relational structure for a given set of entities is a common abstraction for many applications, including vertex reconstruction in particle physics (Shlomi et al., 2020a; Serviansky et al., 2020), inferring higher-order interactions in biological and social systems (Brugere et al., 2018; Battiston et al., 2020) or combinatorial optimization problems, such as finding the convex hull or Delaunay triangulation (Vinyals et al., 2015; Serviansky et al., 2020). The wide spectrum of different application areas underlines the expressivity of this abstract task, which is known in machine learning as set-to-hypergraph prediction (Serviansky et al., 2020). Here, the hypergraph generalizes the pairwise relations in a graph to multi-way relations, a.k.a. hyperedges. We distinguish this task from the related, but different, task of link prediction that aims to discover the missing edges in a graph, given the set of vertices *and a subset of the edges* (Lü & Zhou, 2011). For the set-to-hypergraph problem considered in this paper, we start with a set of nodes without any edges.

A common approach to set-to-hypergraph problems is to decide for *every* edge, whether it exists or not (Serviansky et al., 2020). For a set of n nodes, the number of all possible hyperedges grows in $\mathcal{O}(2^n)$, which already becomes intractable for moderately sized n. This is the *scaling* problem of set-to-hypergraph prediction that we will address in this paper. Combinatorial optimization challenges, like set-to-hypergraph prediction, introduce the additional problem of *complexity*. For example, convex hull finding in d dimensions has a run time complexity of $\mathcal{O}(n \log(n) + n^{\lfloor \frac{d}{2} \rfloor})$ (Chazelle, 1993). This means that larger input sets require more compute regardless of the quality of the hypergraph prediction algorithm. Indeed, it was observed in (Serviansky et al., 2020) that for larger set sizes performance was worse. In this paper we aim to address the scaling and complexity problems in order to predict hypergraphs from larger sets.

We make three contributions in this paper. First, in Section 2 we improve the scalability of hypergraph representations for set-to-hypergraph tasks, by *pruning the non-existing edges*. We prove that during training it suffices to supervise the positive edges only, thus improving the asymptotic memory requirements from $\mathcal{O}(2^n)$ to $\mathcal{O}(kn)$, that is linear in the input set size. Second, to address the complexity problem, we introduce in Section 3 a training method that encourages iterative refinement of the predicted hypergraph with memory requirements scaling constant in the number of

refinement steps. This addresses the need for more compute by complex problems in a scalable manner. Third, we combine in Section 4 the efficient representation from the first contribution with the requirements of the scalable training method from the second contribution in a recurrent model that performs iterative refinement on a pruned hypergraph. Our model handles different input set sizes and varying numbers of edges, while respecting the permutation symmetry of both. In our experiments in Section 5, we provide an in-depth ablation on each of our technical contributions and compare our model against prior work on common set-to-hypergraph benchmarks.

2 SCALING BY PRUNING THE NON-EXISTING EDGES

In this section, we propose a solution for the memory scaling problem encountered in set-to-hypergraph tasks. The goal of set-to-hypergraph tasks is to learn a model $f(\boldsymbol{X}) = \mathcal{H}$ that maps the input set $\boldsymbol{X}$ to its corresponding hypergraph $\mathcal{H}$. The choice on how to *represent* $\mathcal{H}$ can already drastically impact the asymptotic complexity of f. In what follows, we detail necessary properties for the representation of $\mathcal{H}$ that enable learning a pruned incidence matrix and we will motivate why that is a suitable choice.

Nodes. Each element in $\boldsymbol{x}_i \in \boldsymbol{X}$ gets an "identity" as a node $\boldsymbol{v}_i \in \mathcal{V}$ in the hypergraph, meaning if an edge connects every node in $\boldsymbol{V} \subset \mathcal{V}$ then there exists a relation between the input elements $\{\boldsymbol{x}_i \in \boldsymbol{X} | \boldsymbol{v}_i \in \boldsymbol{V}\}$. We differentiate between the input elements and nodes of $\mathcal{H}$, as we expect the latter to be represented as latent vectors of $d_{\mathcal{V}}$ dimensions. The importance of this becomes clear in the discussion on the training objective later on.

Edges. Similar to the nodes, we expect the (hyper)edges $\boldsymbol{e}_i \in \mathcal{E}$ to be represented as vectors of $d_{\mathcal{E}}$ dimensions. Different from the nodes, listing out all the possible edges would require space in $\mathcal{O}(2^n)$, becoming intractable very quickly. However, we observe that in many cases the number of existing edges in a hypergraph is much smaller than the total number of possible edges. We leverage this by specifying a maximum number of edges k that is sufficiently large to cover all (or most) hypergraphs of interest. Thus, we prune all non-existing edges from $\mathcal{E}$, which improves the asymptotic space requirement to $\mathcal{O}(kn)$. In the remaining text, we refer to the non-existing edges as negative and the others as positive. After specifying the training objective, we provide a more formal argument on why pruning the negative edges is sound.

Incidence matrix. Since both the nodes and edges are represented by latent vectors, we require an additional component for specifying the connections between the two. We choose to represent the relational structure using the incidence matrix instead of adjacency tensors (Serviansky et al., 2020; Ouvrard et al., 2017). The two differ in that incidence describes whether an edge is connected to a node, while adjacency states whether an edge between a subset of nodes exists. The rows of the incidence matrix $\boldsymbol{I}$ correspond to the edges and the columns to the nodes. Thus, an entry $\boldsymbol{I}_{i,j} \in [0,1]$ represents the probability of the i-th edge being incident to the j-th node. Theoretically we can express any hypergraph in both representations, but pruning the negative edges becomes especially simple in the incidence matrix, where we just need to remove excess rows.

Loss function. For efficiency purposes, we would like to train each incidence value separately as a binary classification and apply a constant threshold (> 0.5) on $\boldsymbol{I}$ at inference time to get the discrete incidence matrix $\boldsymbol{I}'$. In probabilistic terms, this translates to a factorization of the joint distribution $p(\boldsymbol{I}|\boldsymbol{X})$ as, $\prod_{i,j} p(\boldsymbol{I}_{i,j}|\boldsymbol{X})$. In order to still be able to model interrelations between different incidence probabilities, we impose a requirement on the model f: the probability $\boldsymbol{I}_{i,j}$ produced by f depends on $\boldsymbol{e}_i$ and $\boldsymbol{v}_j$. This highlights the importance of the latent node and edge representations, which enable us to model the dependencies in the output while still being efficient at training and inference time. Furthermore, this changes our assumption on the incidence probabilities from that of independence to *conditional* independence. Thus, we can apply the binary cross-entropy loss to supervise each $\boldsymbol{I}_{i,j}$.

The binary classification highlights another reason for picking the incidence representation over the adjacency. When we prune all negative edges, learning a binary classifier in the adjacency case can no longer work due to the lack of negative examples. In contrast, a positive edge in the incidence matrix contains both zeros and ones, ensuring that the binary classifier sees both positive

and negative examples. However, an adjacency tensor has the advantage that the order of the entries is fully decided by the order of the nodes, which are given by the input in our case. In our case, the row order of the incidence matrix depends on the edges, which are orderless.

When comparing the predicted incidence matrix with a ground-truth matrix, we need to account for the orderless nature of the edges. Hence, we require a loss function that is invariant towards reordering over the rows of the incidence matrix. We achieve this by matching every row in $\boldsymbol{I}$ with a row in the ground-truth $\boldsymbol{I}^*$, such that the binary cross-entropy loss $H(\boldsymbol{I}_{i,j}, \boldsymbol{I}^*_{i,j})$ over all entries is minimal:

$$\mathcal{L}(\boldsymbol{I}, \boldsymbol{I}^*) = \sum_{i,j} H(\boldsymbol{I}_{\pi(i),j}, \boldsymbol{I}^*_{i,j}) \tag{1}$$

Finding a permutation π that minimizes the total loss $\mathcal{L}$ is known as the linear assignment problem and can be solved with the Hungarian matching algorithm (Kuhn, 1955).

Having established the training objective in Equation 1, we can now offer a more formal argument on the soundness of supervising positive edges only while pruning the negative ones:

Proposition 1 (Supervising positive edges only). *Let $\boldsymbol{I}$ be the pruned incidence matrix that contains only the positive edges and $\boldsymbol{J}$ denote the full version that includes the negative edges. The corresponding ground-truth matrices are $\boldsymbol{I}^*$ for the pruned and $\boldsymbol{J}^*$ for the full version. The losses for the full and the pruned incidence matrices are equal up to an additive constant that does not depend on the incidence values:*

$$\mathcal{L}(\boldsymbol{I}, \boldsymbol{I}^*) + c = \mathcal{L}(\boldsymbol{J}, \boldsymbol{J}^*) \tag{2}$$

We provide the proof in Appendix A. Since the losses are equivalent up to an additive constant, the gradients are exactly equal. Thus, pruning the negative edges does not affect learning, while significantly reducing the asymptotic memory requirements.

Summary. In set-to-hypergraph tasks, the number of possible edges in the hypergraph grows exponentially with the input set size. We address this limitation by representing the edge connections with the incidence matrix and pruning all negative edges. We specify properties for f that enable efficient training and inference, while retaining the ability to capture dependencies in the output space. We show that pruning the edges is sound, when the loss function respects the permutation symmetry in the edges.

3 SCALING BY PRUNING THE NON-ESSENTIAL GRADIENTS

Next, we consider how to *learn* the pruned incidence matrix. Some tasks may require more compute than others, which can result in worse performance or intractable models if not properly addressed. A naive approach would increase the number of parameters, either by increasing the number of hidden dimensions or the depth of the neural network, which is clearly not scalable. Furthermore, the memory requirement of backprop would also grow with greater depth. Instead, we would like to increase the amount of sequential computation by reusing parameters. That is, we want the model f to be recurrent, $\mathcal{H}^{t+1} = f(\boldsymbol{X}, \mathcal{H}^t)$. Recurrent models are commonly applied to sequential data, where the input varies for each time step t (Lipton et al., 2015). In our case, we use the same input $\boldsymbol{X}$ at every step. Using a recurrent model, we can increase the total number of iterations – to scale the amount of sequential computation steps – without increasing the number of parameters. However, the recurrency does not address the growing memory requirements of backprop, since the activations of each iteration still need to be kept in memory.

Iterative refinement. In the rest of this section, we present an efficient training algorithm that can scale to any number of iterations at a constant memory cost. We build on the idea that if each iteration applies a small refinement, then it becomes unnecessary to supervise every iteration. We can define an iterative refinement as reducing the loss (by a little) after every iteration, $\mathcal{L}(\boldsymbol{I}^t, \boldsymbol{I}^*) < \mathcal{L}(\boldsymbol{I}^{t-1}, \boldsymbol{I}^*)$. Thus, the long-term dependencies between $\mathcal{H}^t$ for t's that are far apart can also be ignored, since f only needs to improve the current $\mathcal{H}^t$. We can encourage f to iteratively refine the prediction $\mathcal{H}^t$, by applying the loss $\mathcal{L}$ after each iteration. This has the effect that f learns to move the $\mathcal{H}^t$ in the direction of the negative gradient of $\mathcal{L}$, making it similar to a gradient descent update.

Backprop with skips. Similar to previous works that encourage iterative refinement through (indirect) supervision on the intermediate steps (Jastrzebski et al., 2018), we expect the changes of each step to be small. Thus, it stands to reason that supervising *every* step is unnecessary and redundant. This leads us to a more efficient training algorithm that skips iterations in the backward-pass of backprop. Algorithm 1 describes the training procedure in pseudocode (in syntax similar to PyTorch (Paszke et al., 2019)). We perform a total of N gradient updates per mini-batch. Each gradient update consist of two phases, first s iterations without gradient accumulation and then B iterations that add up the losses for

---

Algorithm 1: Backprop with skips

Input: $\boldsymbol{X}, \boldsymbol{I}^*, S, B, N$
$\mathcal{H} \leftarrow \texttt{initialize}(\boldsymbol{X})$
for s **in** S **:**
    with `no_grad()`**:**
        for t **in** `range(s)` **:**
            $\mathcal{H} \leftarrow f(\boldsymbol{X}, \mathcal{H})$
    $l \leftarrow 0$
    for t **in** `range(B)` **:**
        $\mathcal{H} \leftarrow f(\boldsymbol{X}, \mathcal{H})$
        $l \leftarrow l + \mathcal{L}(\mathcal{H}, \boldsymbol{I}^*)$
    `backward(`l`)`
    `gradient_step_and_reset()`

---

backprop. Through these hyperparameters we control the amount of resources used during training. Increasing hyperparameter B allows for models that do not strictly decrease the loss after every step and require supervision over multiple subsequent steps. This training scheme emphasizes the importance of providing $\boldsymbol{X}$ at every refinement step to ensure that the model remembers the initial problem.

Summary. Motivated by the need for more compute to address complex problems, we propose a method that increases the amount of sequential compute of the neural network without increasing the memory requirement at training time. Our training algorithm requires the model f to perform iterative refining of the hypergraph, for which we present a method in the next section.

4 SCALING SET-TO-HYPERGRAPH PREDICTION

In Section 2 and Section 3 we proposed two methods to overcome the memory scaling problems that appear for set-to-hypergraph tasks. To put these methods into practice, we need to specify a model f that fulfills the required properties. In what follows, we propose a specific implementation for each such property.

Initialization. As the starting point for the iterative refinement, we initialize the nodes $\mathcal{V}^0$ from the input set as $\boldsymbol{v}_i^0 = \boldsymbol{W}\boldsymbol{x}_i + \boldsymbol{b}$, where $\boldsymbol{W} \in \mathbb{R}^{d_{\mathcal{V}} \times d_{\boldsymbol{X}}}$, $\boldsymbol{b} \in \mathbb{R}^{d_{\mathcal{V}}}$ are learnable parameters. The affine map allows for hidden dimensions $d_{\mathcal{V}}$ that are different from the input feature dimensions $d_{\boldsymbol{X}}$. An informed initialization similar to the nodes is not available for the edges and the incidence matrix, since these are what we aim to predict. Instead, we choose an initialization scheme that respects the permutation symmetry of a set of edges while also ensuring that each edge starts out differently. The last point is necessary for permutation-equivariant operations to distinguish between different edges. The random initialization $\boldsymbol{e}_i^0 \sim \mathcal{N}(\boldsymbol{\mu}, \mathrm{diag}(\boldsymbol{\sigma}))$, with shared learnable parameters $\boldsymbol{\mu} \in \mathbb{R}^{d_{\boldsymbol{\varepsilon}}}$ and $\boldsymbol{\sigma} \in \mathbb{R}^{d_{\boldsymbol{\varepsilon}}}$ fulfills both these properties, as it is highly unlikely for two samples to be identical.

Conditional independence. We want the incidence probabilities $\boldsymbol{I}_{i,j}$ to be conditionally independent of each other given $\boldsymbol{e}_i$ and $\boldsymbol{v}_j$. A straightforward way to model this is by concatenating both vectors (denoted with $[\cdot]$) and applying an MLP with a sigmoid activation on the scalar output:

$$\boldsymbol{I}_{i,j}^t = \texttt{MLP}\left(\left[e_i^{t-1}, v_j^{t-1}\right]\right) \tag{3}$$

The superscripts point out that we produce a new incidence matrix for step t based on the edge and node vectors from the previous step. Note that we did not specify an initialization for the incidence matrix, since we directly replace it in the first step.

Iterative refinement. The training algorithm in Section 3 assumes that f performs iterative refinement on $\mathcal{H}^t$, but leaves open the question on how to design such a model. Instead of iteratively refining the incidence matrix, i.e., the only term that appears in the loss (Equation 1), we focus on refining the edges and nodes.

A refinement step for some node $\boldsymbol{v}_i \in \mathcal{V}$ needs to account for the rest of the hypergraph, which also changes with each iteration. For this purpose we apply the permutation-equivariant DeepSets

(Zaheer et al., 2017) to produce node updates dependent on the full set of nodes from the previous iteration $\mathcal{V}^{t-1}$. The permutation-equivariance of DeepSets means that the output set retains the input order; thus it is sensible to refer to $\boldsymbol{v}_i^t$ as the updated version of the *same* node $\boldsymbol{v}_i^{t-1}$ from the previous step. Furthermore, we concatenate the aggregated neighboring edges weighted by the incidence probabilities $\rho_{\mathcal{E}\to\mathcal{V}}(j,t) = \sum_{i=1}^{k} \boldsymbol{I}_{i,j}^t e_i^{t-1}$, to incorporate the relational structure between the nodes. This aggregation works akin to message passing in graph neural networks (Gilmer et al., 2017). An indispensable input, required for adding skips in the backward pass during training, are the input features $\boldsymbol{X}$. Instead of directly concatenating the raw features $\boldsymbol{x}_i$, we use the initial nodes $\boldsymbol{v}_i^0$. Finally, we express the refinement part for the nodes as:

$$\mathcal{V}^t = \text{ DeepSets}\left(\left\{\left[\boldsymbol{v}_j^{t-1}, \rho_{\mathcal{E}\to\mathcal{V}}(j,t), \boldsymbol{v}_j^0\right]\middle| j = 1\ldots n\right\}\right) \tag{4}$$

The updates to the edges $\mathcal{E}^t$ mirror that of the nodes, except for the injection of the input set. Together with the aggregation function $\rho_{\mathcal{V}\to\mathcal{E}}(i,t) = \sum_{j=1}^{n} \boldsymbol{I}_{i,j}^t v_j^{t-1}$, we can update the edges as:

$$\mathcal{E}^t = \text{ DeepSets}\left(\left\{\left[e_i^{t-1}, \rho_{\mathcal{V}\to\mathcal{E}}(i,t)\right]\middle| i = 1\ldots k\right\}\right) \tag{5}$$

By sharing the parameters between different refinement steps, we naturally obtain a recurrent model. Previous works on recurrent models (Locatello et al., 2020) saw improvements in training convergence by including layer normalization (Ba et al., 2016) between each iteration. Shortcut connections in ResNets (He et al., 2016) have been shown to encourage iterative refinement of the latent vector (Jastrzebski et al., 2018). We add both shortcut connections and layer normalization to the updates in Equation 4 and Equation 5. Although we prune the negative edges, we still want to predict a variable number thereof. To achieve that we simply extend the incidence model in Equation 3 with an existence indicator:

$$\hat{\boldsymbol{I}}_i^t = \sigma_i^t \boldsymbol{I}_i^t \tag{6}$$

This can be seen as factorizing the probability into "$p(\boldsymbol{e}_i$ incident to $\boldsymbol{v}_j) \cdot p(\boldsymbol{e}_i$ exists)" and replaces the aggregation weights in $\rho_{\mathcal{E}\to\mathcal{V}}$ and $\rho_{\mathcal{V}\to\mathcal{E}}$.

Summary. We propose a model that fulfills the requirements of our scalable set-to-hypergraph training framework from Section 2 and Section 3. By adding shortcut connections, we encourage it to perform iterative refinements on the hypergraph while being permutation equivariant with respect to both the nodes and the edges.

5 EXPERIMENTS

In this section, we evaluate our approach on multiple set-to-hypergraph tasks, in order to compare to prior work and examine the main design choices. We refer to Appendix B for details on the experimental setups and further results. Code is included in the supplementary material.

5.1 SCALING SET-TO-HYPERGRAPH PREDICTION

First, we compare our model from Section 4 on three different set-to-hypergraph tasks against the state-of-the-art model. This allows us to see the difference between predicting the incidence matrix and predicting the adjacency tensors.

Baselines. Our main comparison is against Set2Graph (Serviansky et al., 2020), which is a strong and representative baseline for approaches that predict the adjacency structure, which we generally refer to as adjacency-based approaches. Serviansky et al. (2020) modify the task in two of the benchmarks, to avoid storing an intractably large adjacency tensor. We explain in Appendix B how this affects the comparison. Additionally, we compare to Set Transformer (Lee et al., 2019) and Slot Attention (Locatello et al., 2020), which we adapt to the set-to-hypergraph setting by treating the output as the pruned set of edges and producing the incidence matrix with the MLP from Equation 3. We refer to these two as incidence-based approaches that also include our model.

Particle partitioning. Particle colliders are an important tool for studying the fundamental particles of nature and their interactions. During a collision, several particles are emanated and measured

Table 1: **Particle partitioning results.** On three jet types performance measured in F1 score and adjusted rand index (ARI). Our method outperforms the baselines on bottom and charm jets, while being competitive on light jets.

Model	bottom jets		charm jets		light jets	
	F1	ARI	F1	ARI	F1	ARI
Set2Graph	$0.646_{\pm0.003}$	$0.491_{\pm0.006}$	$0.747_{\pm0.001}$	$0.457_{\pm0.004}$	$0.972_{\pm0.001}$	$0.931_{\pm0.003}$
Set Transformer	$0.630_{\pm0.004}$	$0.464_{\pm0.007}$	$0.747_{\pm0.003}$	$0.466_{\pm0.007}$	$0.970_{\pm0.001}$	$0.922_{\pm0.003}$
Slot Attention	$0.600_{\pm0.012}$	$0.411_{\pm0.021}$	$0.728_{\pm0.008}$	$0.429_{\pm0.016}$	$0.963_{\pm0.002}$	$0.895_{\pm0.009}$
Ours	$0.679_{\pm0.002}$	$0.548_{\pm0.003}$	$0.763_{\pm0.001}$	$0.499_{\pm0.002}$	$0.972_{\pm0.001}$	$0.926_{\pm0.002}$

Table 2: **Convex hull results** measured as F1 score. Our method outperforms all baselines considerably for all settings and set sizes (n).

Model	Spherical			Gaussian		
	$n=30$	$n=50$	$n\in[20..100]$	$n=30$	$n=50$	$n\in[20..100]$
Set2Graph	0.780	0.686	0.535	0.707	0.661	0.552
Set Transformer	0.773	0.752	0.703	0.741	0.727	0.686
Slot Attention	0.668	0.629	0.495	0.662	0.665	0.620
Ours	0.892	0.868	0.823	0.851	0.831	0.809

by nearby detectors, while some particles decay beforehand. Identifying which measured particles share a common progenitor is an important subtask in the context of vertex reconstruction (Shlomi et al., 2020b).

We can treat this as a set-to-hypergraph task: the set of measured particles is the input set and the common progenitors are the edges of the hypergraph. We use a simulated dataset of $0.9M$ data-sample with the default train/validation/test split (Serviansky et al., 2020; Shlomi et al., 2020b). Each data-sample is generated from on one of three different distributions for which we report the results separately: *bottom jets*, *charm jets* and *light jets*. The ground-truth target is the incidence matrix that can also be interpreted as a partitioning of the input elements, since every particle has exactly one progenitor (edge).

In Table 1 we report the performances on each type of jets as the F1 score and Adjusted Rand Index (ARI). Our method outperforms all alternatives on bottom and charm jets, while being competitive on light jets.

Convex hull. The convex hull of a finite set of d-dimensional points can be efficiently represented as the set of simplices that enclose all points. In the 3D case, each simplex consists of 3 points that together form a triangle. For the general d-dimensional case, the valid incidence matrices are limited to those with d incident vertices per edge. Finding the convex hull is an important and well-understood task in computational geometry, with optimal exact solutions (Chazelle, 1993; Preparata & Shamos, 2012). Nonetheless, predicting the convex hull for a given set of points poses a challenging problem for current machine learning methods, especially when the number of points increases (Vinyals et al., 2015; Serviansky et al., 2020). We generate an input set by drawing n 3-dimensional vectors from one of two distributions: Gaussian or spherical. For the Gaussian setting, points are sampled i.i.d. from a standard normal distribution. For the spherical setting, we additionally normalize each point to lie on the unit sphere. Following Serviansky et al. (2020), we use $n=30$, $n=50$ and $n\in[20..100]$, where in the latter case the input set size varies between 20 and 100.

Table 2 shows our results. Our method consistently outperforms all the baselines by a considerable margin. In contrast to Set2Graph, our model does not suffer from a drastic performance decline when increasing the input set size from 30 to 50. Furthermore, based on the results in the Gaussian setting, we also observe that all the incidence-based approaches handle varying input sizes much better than the adjacency-based approach.

Table 3: **Delaunay triangulation results** for different set sizes (n). Our method outperforms Set2Graph on all metrics.

	$n=50$				$n\in[20\,..\,80]$			
Model	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
Set2Graph	0.984	0.927	0.926	0.926	0.947	0.736	0.934	0.799
Ours	0.989	0.953	0.946	0.950	0.987	0.945	0.942	0.943

Delaunay triangulation. A Delaunay triangulation of a finite set of 2D points is a set of triangles for which the circumcircles of all triangles have no point lying inside. When there exists more than one such set, Delaunay triangulation aims to maximize the minimum angle of all triangles. We consider the same learning task and setup as Serviansky et al. (2020), who frame Delaunay triangulation as mapping from a set of 2D points to the set of Delaunay edges, represented by the adjacency matrix. Since this is essentially a set-to-*graph* problem instead of set-to-hypergraph one, we adapt our method for efficiency reasons, as we describe in Appendix B. We generate the input sets of size n, by sampling 2-dimensional vectors uniformly from the unit square, with $n=50$ or $n \in [20\,..\,80]$.

In Table 3, we report the results for Set2Graph (Serviansky et al., 2020) and our adapted method. Our method again outperforms Set2Graph on all metrics.

Summary. By predicting the positive edges only, we can significantly reduce the amount of required memory for set-to-hypergraph tasks. On three different benchmarks, we observe improvements in predictive performance when using this incidence-based approach, compared to the commonly seen adjacency-based method. Interestingly, our method does *not* see a large discrepancy in performance between different input set sizes, both in convex hull finding and Delaunay triangulation. We attribute this to the recurrence of our iterative refinement scheme, which we look into next.

5.2 ABLATIONS

Effects of increasing (time) complexity. The *intrinsic* complexity of finding a convex hull for a d-dimensional set of n points is in $\mathcal{O}(n\log(n) + n^{\lfloor\frac{d}{2}\rfloor})$ (Chazelle, 1993). This scaling behavior offers an interesting opportunity to study the effects of increasing (time) complexity on model performance. The time complexity implies that *any* algorithm for convex hull finding scales super-linearly with the input set size. Since our learned model is not considered an algorithm that (exactly) solves the convex hull problem, the implications become less clear. In order to assess the relevancy of the problem's complexity for our approach, we examine the relation between the number of refining steps and increases in the intrinsic resource requirement. The following experiments are all performed with standard backprop, in order to not introduce additional hyperparameters that may affect the conclusions.

First, we examine the performance of our approach with 3 iterations, trained on increasing set sizes $n\in[10\,..\,50]$. In Figure 1 we observe a monotone drop in performance when training with the same number of iterations. The negative correlation between the set size and the performance confirms a relationship between the computational complexity and the difficulty of the learning task. Next, we examine the performance for varying number of iterations and set sizes. We refer to the setting, where the number of iterations is 3 and set size $n=10$, as the base case. All other set sizes and number of iterations are chosen such that the performance matches the base case as closely as possible. In Figure 1, we observe that the required number of iterations in-

Figure 1: **Performance for increasing complexity.** Increasing the iterations counteracts the performance decline from larger set sizes.

creases with the input set size, further highlighting that an increase in the number of iterations actually suffices in counteracting the performance decrease. Furthermore, we observe that the number of refinement steps scales sub-linearly with the set size, different from what we would expect based on the complexity of the problem. We speculate this is due to the parallelization of our edge finding process, differing from incremental approaches that produce one edge at a time.

Efficiency of backprop with skips. To assess the efficiency of backprop with skips, we compare to truncated backpropagation through time (TBPTT) (Williams & Peng, 1990). We consider two variants of our training algorithm: 1. Skipping iterations at fixed time steps and 2. Skipping randomly sampled time steps. In both the fixed and random skips versions, we skip half of the total iterations. We train all models on convex hull finding in 3-dimensions for 30 spherically distributed points. In addition, we include baselines trained with standard backprop that contingently inform us about performance degradation incurred by our method or TBPTT. Standard backprop increases the memory footprint linearly with the number of iterations T, inevitably exceeding the available memory at some threshold. Hence, we deliberately choose a small set size in order to accommodate training with backprop for $T \in \{4, 16, 32\}$ number of iterations. We illustrate the differences between standard backprop, TBPTT and our backprop with skips in Figure 4 in the Appendix.

Figure 2: **Training time of backprop with skips.** Relative training time and performance for different $T \in \{4, 16, 32\}$. All runs require the same memory, except standard backprop $T \in \{16, 32\}$, which require more.

The results in Figure 2 demonstrate that skipping half of the iterations in the backward-pass, significantly decreases the training time without hurting predictive performance. When the memory budget is constricted to 4 iterations in the backward-pass, both TBPTT and backprop with skips outperform standard backprop considerably.

Recurrent vs. stacked. Recurrence plays a crucial role in enabling more computation without an increase in the number of parameters. By training the recurrent model using backprop with skips, we can further reduce the memory cost during training to a constant amount. Since our proposed training algorithm from Section 3 encourages iterative refinement akin to gradient descent, it is natural to believe that the weight-tying aspect of recurrence is a good inductive bias for modelling this. A reason for thinking so, is that the "gradient" should be the same for the same I, no matter at which iteration it is computed. Hence, we compare the recurrent model against a non-weight-tied (stacked) version that applies different parameters at each iteration. First, we compare the models trained for 3 to 9 refinement steps. In Figure 3a, we show that both cases benefit from increasing the iterations. Adding more iterations beyond 6 only slightly improves the performance of the stacked model, while the recurrent version still benefits, leading to an absolute difference of 0.03 in F1 score for 9 iterations. Next, we train both versions with 15 iterations until they achieve a similar validation performance, by stopping training early on the recurrent model. The results in Figure 3b show that the recurrent variant performs better when tested at larger set sizes than trained, indicating an improved generalization ability.

Learning higher order edges. The particle partitioning experiment exemplifies a case where a single edge can connect up to 14 vertices. Set2Graph (Serviansky et al., 2020) demonstrates that in this specific case it is possible to approximate the hypergraph with a graph. They leverage the fact that any vertex is incident to exactly one edge and apply a post-processing step that constructs the edges from noisy cliques. Instead, we consider a task for which no straightforward graph based approximation exists. Specifically, we consider convex hull finding in 10-dimensional space for 13 standard normal distributed points. We train with $T=32$, $N=4$ and $B=4$. The test performance reaches an F1 score of 0.75, clearly demonstrating that the model managed to learn. This result demonstrates the improved scaling behavior can be leveraged for tasks that are computationally out of reach for adjacency-based approaches.

Figure 3: **Recurrent vs. stacked.** (a) Performance for different numbers of iterations. (b) Extrapolation performance on $n \in [11 . . 20]$ for models trained with set size $n=10$. We stop training the recurrent model early, to match the validation performance of the stacked on $n=10$. The recurrent model derives greater benefits from adding iterations and generalizes better.

6 RELATED WORK

Adjacency prediction. Set2Graph (Serviansky et al., 2020) is a family of maximally expressive permutation equivariant neural networks that map from an input set to (hyper)graphs. They show that their method outperforms many popular alternatives, including Siamese networks (Zagoruyko & Komodakis, 2015) and graph neural networks (Morris et al., 2019) applied to a k-NN induced graph. (Serviansky et al., 2020) extend the general idea, of applying a scalar-valued adjacency indicator function on all pairs of nodes (Kipf & Welling, 2016), to the l-edge case (edges that connect l nodes). In Set2Graph, for each l the adjacency structure is modeled by an l-tensor, requiring memory in $\mathcal{O}(n^l)$. This becomes intractable already for small l and moderate set sizes. By pruning the negative edges, our approach scales in $\mathcal{O}(nk)$, making it applicable even when $l=n$.

Set prediction. Recent works on set prediction map a learned initial set (Zhang et al., 2019; Lee et al., 2019) or a randomly initialized set (Locatello et al., 2020; Carion et al., 2020; Zhang et al., 2021) to the target space. Out of these, the closest one to our hypergraph refining approach is Slot Attention (Locatello et al., 2020), which recurrently applies the Sinkhorn operator (Adams & Zemel, 2011) in order to associate each element in the input set with a single slot (hyperedge). None of the prior works on set prediction consider the set-to-hypergraph task, but some can be naturally extended by mapping the input set to the set of positive edges, an approach similar to ours.

7 CONCLUSION AND FUTURE WORK

By representing and supervising the set of positive edges only, we substantially improve the asymptotic scaling and enable learning tasks with higher-order edges. On common benchmarks, we have demonstrated that our method outperforms previous works, while offering a more favorable asymptotic scaling behavior. In further evaluations, we have highlighted the importance of recurrence for addressing the intrinsic complexity of problems.

Efficient set loss. We identify the Hungarian matching (Kuhn, 1955) as the main computational bottleneck during training. Replacing the Hungarian matched loss with a faster alternative, like a learned energy function (Zhang et al., 2021), would greatly speed up training for tasks with a large maximum number of edges.

Larger input dimensions. Our empirical analysis is limited to datasets on with low dimensional inputs. Learning on higher dimensional input data might require extensions to the model that can make larger changes to the latent hypergraph than is feasible with small iterative refinement steps. The idea here is similar to the observation from Jastrzebski et al. (2018) for ResNets (He et al., 2016) that also encourage iterative refinement: earlier residual blocks apply large changes to the intermediate features while later layers perform (small) iterative refinements.

ETHICS STATEMENT

We propose methods to deal with the scaling issues encountered in set-to-hypergraph tasks and evaluate it largely on synthetic datasets. Our contributions enable larger input set sizes due to better asymptotic memory scaling. This may enable applications on data with many nodes and sparse connections, including amongst others social networks (e.g., clique prediction for a new group of users) or scientific data (e.g., vertex reconstruction for more particles). In the context of applying machine learning methods in social networks, it is good to be mindful about biases relating to human ethnicity, gender or groups that experience frequent discrimination (Torralba & Efros, 2011; Mehrabi et al., 2021).

REPRODUCIBILITY STATEMENT

The proof is included in Appendix A. Additional results and experiment descriptions are in Appendix B. We provide the code for reproducing the experiments in the supplementary material.

REFERENCES

Ryan Prescott Adams and Richard S Zemel. Ranking via sinkhorn propagation. *arXiv preprint arXiv:1106.1925*, 2011.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Federico Battiston, Giulia Cencetti, Iacopo Iacopini, Vito Latora, Maxime Lucas, Alice Patania, Jean-Gabriel Young, and Giovanni Petri. Networks beyond pairwise interactions: structure and dynamics. *Physics Reports*, 2020.

Ivan Brugere, Brian Gallagher, and Tanya Y Berger-Wolf. Network structure inference, a survey: Motivations, methods, and applications. *ACM Computing Surveys*, 51(2):1–39, 2018.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pp. 213–229, 2020.

Bernard Chazelle. An optimal convex hull algorithm in any fixed dimension. *Discrete & Computational Geometry*, 10(4):377–409, 1993.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International Conference on Machine Learning*, pp. 1263–1272. PMLR, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016.

Stanisław Jastrzebski, Devansh Arpit, Nicolas Ballas, Vikas Verma, Tong Che, and Yoshua Bengio. Residual connections encourage iterative inference. In *International Conference on Learning Representations*, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Thomas N Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016.

Harold W Kuhn. The Hungarian method for the assignment problem. *Naval Research Logistics Quarterly*, 2(1-2):83–97, 1955.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International Conference on Machine Learning*, pp. 3744–3753. PMLR, 2019.

Zachary C Lipton, John Berkowitz, and Charles Elkan. A critical review of recurrent neural networks for sequence learning. *arXiv preprint arXiv:1506.00019*, 2015.

Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In *Advances in Neural Information Processing Systems*, pp. 11525–11538, 2020.

Linyuan Lü and Tao Zhou. Link prediction in complex networks: A survey. *Physica A: statistical mechanics and its applications*, 390(6):1150–1170, 2011.

Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A survey on bias and fairness in machine learning. *ACM Comput. Surv.*, 54(6), 2021.

Christopher Morris, Martin Ritzert, Matthias Fey, William L Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 4602–4609, 2019.

Xavier Ouvrard, Jean-Marie Le Goff, and Stéphane Marchand-Maillet. Adjacency and tensor representation in general hypergraphs part 1: e-adjacency tensor uniformisation using homogeneous polynomials. *arXiv preprint arXiv:1712.08189*, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, pp. 8024–8035, 2019.

Franco P Preparata and Michael I Shamos. *Computational geometry: an introduction*. Springer Science & Business Media, 2012.

Stefano Rebay. Efficient unstructured mesh generation by means of delaunay triangulation and bowyer-watson algorithm. *Journal of Computational Physics*, 106(1):125–138, 1993.

Hadar Serviansky, Nimrod Segol, Jonathan Shlomi, Kyle Cranmer, Eilam Gross, Haggai Maron, and Yaron Lipman. Set2graph: Learning graphs from sets. In *Advances in Neural Information Processing Systems*, 2020.

Jonathan Shlomi, Peter Battaglia, and Jean-Roch Vlimant. Graph neural networks in particle physics. *Machine Learning: Science and Technology*, 2(2):021001, 2020a.

Jonathan Shlomi, Sanmay Ganguly, Eilam Gross, Kyle Cranmer, Yaron Lipman, Hadar Serviansky, Haggai Maron, and Nimrod Segol. Secondary vertex finding in jets with neural networks. *arXiv preprint arXiv:2008.02831*, 2020b.

Antonio Torralba and Alexei A. Efros. Unbiased look at dataset bias. In *Conference on Computer Vision and Pattern Recognition*, 2011.

Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In *Advances in Neural Information Processing Systems*, 2015.

Ronald J Williams and Jing Peng. An efficient gradient-based algorithm for on-line training of recurrent network trajectories. *Neural computation*, 2(4):490–501, 1990.

Sergey Zagoruyko and Nikos Komodakis. Learning to compare image patches via convolutional neural networks. In *Conference on Computer Vision and Pattern Recognition*, pp. 4353–4361, 2015.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *Advances in Neural Information Processing Systems*, 2017.

David W Zhang, Gertjan J Burghouts, and Cees G M Snoek. Set prediction without imposing structure as conditional density estimation. In *International Conference on Learning Representations*, 2021.

Yan Zhang, Jonathon Hare, and Adam Prügel-Bennett. Deep set prediction networks. In *Advances in Neural Information Processing Systems*, 2019.

A   PROOF: SUPERVISING POSITIVE EDGES ONLY SUFFICES

Proposition (Supervising positive edges only). *Let $\boldsymbol{I}$ be the pruned incidence matrix that contains only the positive edges and $\boldsymbol{J}$ denote the full version that includes the negative edges. The corresponding ground-truth matrices are $\boldsymbol{I}^*$ for the pruned and $\boldsymbol{J}^*$ for the full version. The losses for the full and the pruned incidence matrices are equal up to an additive constant that does not depend on the incidence values:*

$$\mathcal{L}(\boldsymbol{I}, \boldsymbol{I}^*) + c = \mathcal{L}(\boldsymbol{J}, \boldsymbol{J}^*) \tag{7}$$

Proof. For the sake of rigor, we first summarize the relevant assumptions from **??**. We assume a fixed maximum number k of existing edges, which is determined by the training dataset in practice. Our model predicts an incidence matrix $\boldsymbol{I}$ of size $k \times n$, where n is the input set size. Our proposed method computes the loss based on $\boldsymbol{I}$ and the pruned ground-truth $\boldsymbol{I}^*$. The loss function $\mathcal{L}$ finds a row (edge) wise assignment, that minimizes the total binary cross entropy between the prediction and the ground-truth. This assignment is commonly referred to as Hungarian matching and we denote the assignment as π. The loss is then computed as $\mathcal{L}(\boldsymbol{I}, \boldsymbol{I}^*) = \sum_{i,j} H(\boldsymbol{I}_{\pi(i),j}, \boldsymbol{I}^*_{i,j})$, with H denoting the binary cross-entropy. By denoting the element-wise binary cross-entropy as $\hat{H}$, we can rewrite the loss as, $\mathcal{L}(\boldsymbol{I}, \boldsymbol{I}^*) = \sum_i \hat{H}(\boldsymbol{I}_{\pi(i)}, \boldsymbol{I}^*_i)$, which we will make use of in the following.

In order to compute the loss with respect to the full ground-truth incidence matrix $\boldsymbol{J}^*$, we extend the prediction $\boldsymbol{J}$ to have the same size. In particular, this extension fills the extra rows with non-existing edges, since $\boldsymbol{I}$ is already sufficient to cover all existing edges. We assume w.l.o.g. that the first k rows of the complete incidence matrices are equivalent to their pruned versions. Note that the binary cross entropy is undefined for 0's (corresponding to non-existing edge) in the prediction, and we simply choose an $\epsilon > 0$ that is sufficiently close to 0. This is a mild assumption, since in practice the output of the 'log( )' is lower bounded anyway, e.g., PyTorch lower bounds it at -100.

Next, we prove Equation 7 where c is a (small) constant that depends on ϵ and n, but is independent of the specific prediction and ground-truth values. We differentiate between the assignments (Hungarian matching) for $L(\boldsymbol{I}, \boldsymbol{I}^*)$ and $L(\boldsymbol{J}, \boldsymbol{J}^*)$, by writing π_I and π_J respectively. For any π_J that assigns an $i \leq k$ to $\pi_J(i) > k$, there also exists a $j \leq k$ that is assigned $\pi_J^{-1}(j) > k$, due to bijectivity. We recall that all rows $> k$ are $\boldsymbol{0}$ vectors in $\boldsymbol{J}^*$ and $\boldsymbol{\epsilon}$ vectors in $\boldsymbol{J}$. We refer to these assignments as *mixing*, because the assignment mixes the rows below and above k. The loss terms corresponding to the mentioned rows is lower bounded as follows:

$$\hat{H}(\boldsymbol{I}_i, \boldsymbol{I}^*_{\pi_J(i)}) + \hat{H}(\boldsymbol{I}_{\pi_J^{-1}(j)}, \boldsymbol{I}^*_j) \tag{8}$$

$$= \hat{H}(\boldsymbol{I}_i, \boldsymbol{0}) + \hat{H}(\boldsymbol{\epsilon}, \boldsymbol{I}^*_j) \tag{9}$$

$$= -\sum_{l=1}^{n} \log(1 - \boldsymbol{I}_{i,l}) + \boldsymbol{I}^*_{j,l} \log(\epsilon) + (1 - \boldsymbol{I}^*_{j,l}) \log(1 - \epsilon) \tag{10}$$

$$\geq -\sum_{l=1}^{n} (1 - \boldsymbol{I}^*_{j,l}) \log(1 - \boldsymbol{I}_{i,l}) + \boldsymbol{I}^*_{j,l} \log(\epsilon) + (1 - \boldsymbol{I}^*_{j,l}) \log(1 - \epsilon) \tag{11}$$

$$\geq -\sum_{l=1}^{n} (1 - \boldsymbol{I}^*_{j,l}) \log(1 - \boldsymbol{I}_{i,l}) + \boldsymbol{I}^*_{j,l} \log(\boldsymbol{I}_{i,l}) + (1 - \boldsymbol{I}^*_{j,l}) \log(1 - \epsilon) \tag{12}$$

$$= \hat{H}(\boldsymbol{I}_i, \boldsymbol{I}^*_j) - \sum_{l=1}^{n} (1 - \boldsymbol{I}^*_{j,l}) \log(1 - \epsilon) \tag{13}$$

$$\approx \hat{H}(\boldsymbol{I}_i, \boldsymbol{I}^*_j) - \sum_{l=1}^{n} \log(1 - \epsilon) \tag{14}$$

$$= \hat{H}(\boldsymbol{I}_i, \boldsymbol{I}^*_j) + \hat{H}(\boldsymbol{\epsilon}, \boldsymbol{0}) \tag{15}$$

Equality of Equation 9 holds for mixing assignments. Equality for Equation 12 makes use of the assumption that $-\log(\epsilon) \geq -\log(\boldsymbol{I}_{i,l})$, e.g., in PyTorch we would choose ϵ such that $-\log(\epsilon) =$

100. Equation 14 does not break the inequality, since $\log(1 - \epsilon)$ is orders of magnitude smaller than the other terms. The inequality implies that whenever an assignment π_J mixes the rows below and above k, there exists a non-mixing assignment that is at least as good (in terms of total loss). Any such non-mixing assignment also contains an optimal assignment for the first k rows, implying that $\exists \pi_J : \pi_I(i) = \pi_J(i)$, for $i \leq k$, where π_I is the optimal assignment on the pruned incidence matrices. This further implies that $\mathcal{L}(\boldsymbol{I}, \boldsymbol{I}^*) + g \cdot \hat{H}(\boldsymbol{\epsilon}, \boldsymbol{0}) = \mathcal{L}(\boldsymbol{J}, \boldsymbol{J}^*)$, where $g = 2^n - k$ is the number of non-existing edges. $\qquad\square$

B   EXPERIMENTAL DETAILS

In this section, we provide further details on the experimental setup and additional results.

B.1   PARTICLE PARTITIONING

For the particle partitioning problem, we follow the experimental setup of (Serviansky et al., 2020). The problem considers the case where particles are collided at high energy, resulting in multiple particles shooting out from it. Each example in the dataset consists of the input set, which corresponds to some outgoing particles, and the ground truth partition of the input set. Each element in the partition is a subset of the input set and corresponds to some intermediate particle that was not measured, because it decayed into multiple particles before it could reach the sensors. The learning task consists of inferring which elements in the input set originated from the same intermediate particle. The particle partitioning task bears resemblance to the classical clustering setting. It can be understood as a meta-learning clustering task, where both the number of clusters and the similarity function depend on the context. Thought, clustering algorithms such as k-means, require a priori specification of the number of clusters and use a fixed similarity function and are therefore unsuitable. For more information on how this task fits into the area of particle physics more broadly, we refer to Shlomi et al. (2020a).

Dataset.   We use the publicly available dataset of 0.9M data-sample with the default train/validation/test split (Serviansky et al., 2020; Shlomi et al., 2020b). Each data-sample is The input sets consist of 2 to 14 particles, with each particle represented by 10 features. The target partitioning indicate the common progenitors and restrict the valid incidence matrices to those with a single incident edge per node.

Setup.   While Set2Graph is only one instance of an adjacency-based approach, (Serviansky et al., 2020) show that it outperforms many popular alternatives: Siamese networks, graph neural networks and a non-learnable geometric-based baseline. All adjacency-based approaches incur a prohibitively large memory cost when predicting edges with high connectivity. In the case of particle partitioning, Set2Graph resorts to only predicting edges with at most 2 connecting nodes, followed by an additional heuristic to infer the partitions (Serviansky et al., 2020). In contrast to that, all the incidence-based approaches do not require the additional post-processing step at the end.

We simplify the hyperparameter search by choosing the same number of hidden dimensions d for the latent vector representations of both the nodes $d_{\boldsymbol{\mathcal{V}}}$ and the edges $d_{\boldsymbol{\mathcal{E}}}$. In all runs dedicated to searching d, we set the number of total iterations $T{=}3$ and backpropagate through all iterations. We start with $d{=}32$ and double it, until an increase yields no substantial performance gains on the validation set, resulting in $d{=}128$. In our reported runs, we use $T{=}16$ total iterations, $B{=}4$ backprop iterations, $N{=}2$ gradient updates per mini-batch, and a maximum of 10 edges.

We apply the same $d{=}128$ to both the Slot Attention and Set Transformer baselines. Similar to the original version (Locatello et al., 2020), we train Slot Attention with 3 iterations. Attempts with more than 3 iterations resulted in frequent divergences in the training losses. We attribute this behavior to the recurrent sinkhorn operation, that acts as a contraction map, forcing all slots to the same vector in the limit.

We train all models using the Adam optimizer (Kingma & Ba, 2014) with a learning rate of 0.0003 for 400 epochs and retain the parameters corresponding to the lowest validation loss. All models additionally minimize a soft F1 score (Serviansky et al., 2020). Since each particle can only be part of a single partition, we choose the one with the highest incidence probability at test time. Our

model has 268162 trainable parameters, similar to 251906 for the Slot Attention baseline, but less than 517250 for Set Transformer and 461289 for Set2Graph (Serviansky et al., 2020). The total training time is less than 12 hours on a single GTX 1080 Ti and 10 CPU cores.

Further results. For completeness, we also report the results for the rand index (RI) in Table 4.

Table 4: **Additional particle partitioning results.** On three jet types performance measured as rand index (RI). Our method outperforms the baselines on bottom and charm jets, while being competitive on light jets.

	bottom jets	charm jets	light jets
Model	RI	RI	RI
Set2Graph	$0.736_{\pm 0.004}$	$0.727_{\pm 0.003}$	$0.970_{\pm 0.001}$
Set Transformer	$0.734_{\pm 0.004}$	$0.734_{\pm 0.004}$	$0.967_{\pm 0.002}$
Slot Attention	$0.703_{\pm 0.013}$	$0.714_{\pm 0.009}$	$0.958_{\pm 0.003}$
Ours	$0.781_{\pm 0.002}$	$0.751_{\pm 0.001}$	$0.969_{\pm 0.001}$

B.2 CONVEX HULL FINDING

On convex hull finding in 3D, we compare our method to the same baselines as on the particle partitioning task.

Setup. Set2Graph learns to map the set of 3D points to the 3rd order adjacency tensor. Since storing this tensor in memory is not feasible, they instead concentrate on a local version of the problem, which only considers the k-nearest neighbors for each point (Serviansky et al., 2020). We train our method with $T_{\text{total}}=48$, $T_{\text{BPTT}}=4$, $N_{\text{BPTT}}=6$ and set k equal to the highest number of triangles in the training data. At test time, a prediction admits an edge e_i if its existence indicator $\sigma_i > 0.5$. Each edge is incident to the three nodes with the highest incidence probability. We apply the same hyperparameters, architectures and optimizer as in the particle partitioning experiment, except for: $T=48$, $B=4$, $N=6$. We set the maximum number of edges k equal to the highest number of triangles in the training data. Since we do not change the model, the number of parameters remains at 268162 for our model. This notably differs to Set2Graph, which reports an increased parameter count of 1186689 (Serviansky et al., 2020). We train our method until we observe no improvements on the F1 validation performance for 20 epochs, with a maximum of 1000 epochs. The set-to-set baselines are trained for 4000 epochs, and we retain the parameters resulting in the highest f1 score on the validation set. The total training time is between 14 and 50 hours on a single GTX 1080 Ti and 10 CPU cores.

B.3 DELAUNAY TRIANGULATION

The problem of Delaunay triangulation is, similar to convex hull finding a well-studied problem in computational geometry and has exact solutions in $\mathcal{O}(n \log(n))$ (Rebay, 1993). We consider the same learning task as Serviansky et al. (2020), who frame Delaunay triangulation as mapping from a set of 2D points to the set of Delaunay edges, represented by the adjacency matrix. Note that this differs from finding the set of triangles, as an edge no longer remembers which triangles it is part of. Thus, this reduces to a set-to-graph task, instead of a set-to-hypergraph task.

Model adaptation. The goal in this task is to predict the adjacency matrix of an ordinary graph – a graph consisting of edges that connect two nodes – where the number of edges are greater than the number of nodes. One could recover the adjacency matrix based on the matrix product of $\boldsymbol{I}^T \boldsymbol{I}$, by clipping all values above 1 back to 1 and setting the diagonal to 0. This approach is inefficient, since in this case the incidence matrix is actually larger than the adjacency matrix. Instead of applying our method directly, we consider a simple adaptation of our approach to the graph setting. We replace the initial set of edges with the (smaller) set of nodes and apply the same node refinements on both sets. This change results in $\mathcal{E} = \mathcal{V}$ for the prediction and effectively reduces the incidence matrix to an adjacency matrix, since it is computed based on all pairwise combinations of $\mathcal{E}$ and $\mathcal{V}$. We

further replace the concatenation for the MLP modelling the incidence probability with a sum, to ensure that the predicted adjacency matrix is symmetric and represents an undirected graph. Two of the main design choices of our approach remain in this adaptation: Iterative refining of the complete graph with a recurrent neural network and BPTT with gradient skips. We train our model with $T{=}32$, $B{=}4$ and $N{=}4$. At test-time, an edge between two nodes exists if the adjacency value is greater than 0.5.

Setup. We increase the latent dimensions to $d{=}256$, resulting in 595201 trainable parameters. This notably differs to Set2Graph, which increases the parameter count to 5918742 (Serviansky et al., 2020), an order of magnitude larger. The total training time is less than 9 hours on a single GTX 1080 Ti and 10 CPU cores.

B.4 LEARNING HIGHER ORDER EDGES

In the ablation on *learning higher order edges*, we demonstrate that the improved scaling behavior of our proposed method can be leveraged for tasks that are computationally out of reach for adjacency based approaches. The number of points and dimensions were chosen in conjunction, such that the corresponding adjacency tensor would require more storage than is feasible with current GPUs (available to us). For 13 points in 10 dimensions, explicitly storing the full adjacency tensor using 32-bit floating-point numbers would already require more than 500 GB. We intentionally kept the number of points and dimensions low, to highlight that the asymptotic scaling issue cannot be met by hardware improvements, since small numbers already pose a problem. Note that Set2Graph already struggles with convex hull finding in 3D, where the authors report that storing 3-rd order tensors in memory is not feasible. Instead, they consider a local version of the problem and take the k-Nearest-Neighbors out of the set of points that are part of the convex hull, with $k = 10$. While we limited our calculation of the storage requirement to the adjacency tensor itself, a typical implementation of a neural network also requires storing the intermediate activations, further exacerbating the problem for adjacency based approaches.

B.5 BACKPROP WITH SKIPS

We compare backprop with skips to TBPTT (Williams & Peng, 1990) with $B{=}4$ every 4 iterations, which is the setting that is most similar to ours with regard to training time. In general, TBPTT allows for overlaps between subsequent BPTT applications, as we illustrate in Figure 4. We constrict both TBPTT and backprop with skips to a fixed memory budget, by limiting any backward pass to the most recent $B{=}4$ iterations, for $T{\in}\{16, 32\}$. The standard backprop results serve as a reference point to answer the question: "What if we apply backprop more frequently, resulting in a better approximation to the true gradients?", without necessitating a grid search over all possible hyperparameter combinations for TBPTT. The results on standard backprop appear to indicate that performance worsens when increasing the number of iterations from 16 to 32. We observe that applying backprop on many iterations leads to increasing gradient norms in the course of training, complicating the training process. The memory limited versions did not exhibit a similar behavior, evident from the improved performance, when increasing the iterations from 16 to 32.

Figure 4: **Adding gradient skips to backprop** (a) Standard backprop (b) TBPTT, applying backprop on 4 iterations every 2nd iteration (c) Backprop with skips at iterations 1, 6, 7, 8, which effectively reduces the training time, while retaining the same number of refinement steps.