Monte-Carlo Planning and Learning with Language Action Value Estimates

Abstract

Interactive Fiction (IF) games provide a useful testbed for language-based reinforcement learning agents, posing significant challenges of natural language understanding, commonsense reasoning, and non-myopic planning in the combinatorial search space. Agents based on standard planning algorithms struggle to play IF games due to the massive search space of language actions. Thus, language-grounded planning is a key ability of such agents, since inferring the consequence of language action based on semantic understanding can drastically improve search. In this paper, we introduce Monte-Carlo planning with Language Action Value Estimates (MC-LAVE) that combines a Monte-Carlo tree search with language-driven exploration. MC-LAVE invests more search effort into semantically promising language actions using locally optimistic language value estimates, yielding a significant reduction in the effective search space of language actions. We then present a reinforcement learning approach via MC-LAVE, which alternates between MC-LAVE planning and supervised learning of the self-generated language actions. In the experiments, we demonstrate that our method achieves new high scores in various IF games.

1 Introduction

Building an intelligent goal-oriented agent that can perceive and react via natural language is one of the promising real-world applications of artificial intelligence. As a means of pursuing this, we consider Interactive Fiction (IF) games (Nelson, 2001; Montfort, 2005), text-based simulation environments where the agent interacts with the environment only through natural language. They serve as a useful testbed for developing language-based goal-oriented agents, posing important challenges such as natural language understanding, commonsense reasoning, and non-myopic planning in the combinatorial search space of language actions. IF games naturally have a large branching factor, possessing at least hundreds of natural language actions that can affect the simulation at game states. This renders naive exhaustive search infeasible and raises the strong need for *language-grounded* planning ability, i.e. effective search space is too large to choose an optimal action without inferring the future impact of language action by understanding the environment state described in natural language.

Still, standard planning methods such as Monte-Carlo tree search (MCTS) are language-agnostic and rely only on uncertainty-driven exploration that encourages to search more on less-visited states and actions. This simple uncertainty-based strategy is not sufficient to find an optimal language action within a limited search time, especially when each language action is treated as a discrete token. On the other hand, recent reinforcement learning agents for IF games have started to leverage pre-trained word embeddings for language understanding (He et al., 2016; Fulda et al., 2017; Hausknecht et al., 2019) or knowledge graphs for commonsense reasoning (Ammanabrolu & Hausknecht, 2020), but their exploration strategies are still limited to the ϵ-greedy or the softmax policies, lacking more structured and non-myopic planning ability. As a consequence, current state-of-the-art agents for IF games still have not yet been up to the human-level play.

In this paper, we introduce Monte-Carlo planning with Language Action Value Estimates (MC-LAVE), a planning algorithm for the environments with text-based interactions. MC-LAVE combines Monte-Carlo tree search with *language-driven* exploration, addressing significant search inefficiency attributed to the lack of language understanding. It starts with credit assignment to language

actions via Q-learning of the experiences collected from the past searches. Then, MC-LAVE assigns *non-uniform* search priorities to each language action based on the optimistically aggregated Q-estimates of the past actions that share similar meanings with the candidate action, so as to focus more on the semantically promising actions. This is in contrast to the previous methods that involve language understanding in the form of a knowledge graph, where the insignificant language actions are *uniformly* filtered out by graph mask (Ammanabrolu & Hausknecht, 2020; Ammanabrolu et al., 2020). The non-uniform search empowered by language understanding in MC-LAVE yields better search efficiency while not hurting the asymptotic guarantee of MCTS.

We then present our reinforcement learning approach that uses MC-LAVE as a strong policy improvement operator. Since MCTS explores the combinatorial space of action sequences, its search results can be far better than the simple greedy improvement, as demonstrated in the game of Go (Silver et al., 2017). This final algorithm, MC-LAVE-RL, alternates between planning via MC-LAVE and supervised learning of self-generated language actions. Experimental results demonstrate that MC-LAVE-RL achieves new high scores in various IF games defined in the Jericho framework (Hausknecht et al., 2019), showing the effectiveness of language-grounded MC-LAVE planning.

2 BACKGROUND

2.1 INTERACTIVE FICTION GAME

Interactive Fiction (IF) games are fully text-based environments where the observation and the action spaces are defined as natural language. The game-playing agent observes textual descriptions of the world, selects an language-based action, and receives the associated reward. IF games can be modeled as a special case of partially observable Markov decision processes (POMDPs) defined by tuple $\langle S, A, \Omega, T, O, R, \gamma \rangle$, where S is the set of environment states s, A is the set of language actions a, Ω is the set of text observations o, $T(s'|s, a) = \Pr(s_{t+1} = s'|s_t = s, a_t = a)$ is the transition function, $R(s, a)$ is the reward function for taking action a in state s, $O(s) = o$ is the deterministic observation function in state s, and $\gamma \in (0, 1)$ is the discount factor. The history at time step t, $h_t = \{o_0, a_0, \ldots, o_{t-1}, a_{t-1}, o_t\}$, is a sequence of observations and actions. The goal is to find an optimal policy π^* that maximizes the expected cumulative rewards, i.e. $\pi^* = \arg\max_\pi \mathbb{E}_\pi \left[\sum_{t=0}^\infty \gamma^t R(s_t, a_t) \right]$.

We use the same definition of observation and action space as Hausknecht et al. (2019); Ammanabrolu & Hausknecht (2020); Côté et al. (2018), i.e. An observation is defined by $o_t = (o_{t_{\text{desc}}}, o_{t_{\text{game}}}, o_{t_{\text{inv}}}, a_{t-1})$ where $o_{t_{\text{desc}}}$ is textual description of the current location of agent, $o_{t_{\text{game}}}$ is simulator response to the previous action taken by the agent, $o_{t_{\text{inv}}}$ is information of agent's inventory, and a_{t-1} is the previous action taken by the agent. An action is denoted by a sequence of words $a_t = (a_t^1, a_t^2, \ldots, a_t^{|a_t|})$. Finally, we denote $A_{\text{valid}}(o_t) \subseteq A$ as a set of valid actions with respect to the given observation o_t, which is provided by the Jericho environment interface. Figure 1 shows an example of observation and action in ZORK1 which is one of the most popular IF games.

2.2 CHALLENGES IN INTERACTIVE FICTION GAME

IF games possess important challenges for language-based reinforcement learning agents, requiring natural language understanding, commonsense reasoning, and non-myopic language-grounded planning ability in combinatorial search space of language actions (Hausknecht et al., 2019). More concretely, consider the particular game state of ZORK1 described in Figure 1. In this example situation, a human player would be capable of performing strategic planning based on language understanding and commonsense reasoning as follows: (1) the 'closed trap door' will have to be opened and be explored to proceed with the game, (2) however, acquiring the 'lantern' should precede entering the trap door since the cellar, which is expected to exist below the trap door, could be likely pitch-dark. Without such language-grounded reasoning and planning, the agent may explore the entire action space uniformly, making it vulnerable to being eaten by a monster in the cellar who always appear when there is no light source. As a result, any agent that lacks the ability of long-term planning with language reasoning is prone to be stuck in a suboptimal policy, which enters the cellar to obtain an immediate reward and does nothing further to avoid encountering the monster that kills the agent immediately.

Figure 1: Example of observation and actions from ZORK1

To overcome the bottleneck, the agent should be able to infer that 'take lantern' is worthy enough to be chosen in preference to other actions even though it gives no immediate reward. In this work, we will precisely address such failures of myopic planning that arise from the lack of language-grounded exploration strategy. To this end, we first address the nonmyopic-planning with MCTS-based long-term planning. Then we further improve the search efficiency of MCTS-based planning by incorporating our novel language-grounded exploration strategy based on Language Action Value Estimates, which will be detailed in the subsequent section.

2.3 MONTE-CARLO TREE SEARCH

Monte-Carlo Tree Search (MCTS) (Kocsis & Szepesvári, 2006; Coulom, 2006; Browne et al., 2012) is a generic online planning algorithm that combines random sampling and tree search, and it has been the de-facto standard method for large sequential decision-making problems. Starting from an empty tree, MCTS repeatedly performs the four phases of selection, expansion, rollout, and backpropagation to evaluate the nodes of the search tree more and more accurately. UCT (Kocsis & Szepesvári, 2006) is the standard MCTS method, which adopts UCB (Auer et al., 2002) as an action selection rule at each internal node of the search tree:

$$\arg\max_a \left[Q(h,a) + c\sqrt{\tfrac{\log N(h)}{N(h,a)}} \right] \qquad (1)$$

where h is the history of past observations and actions, $Q(h,a)$ is the average value of sampled returns with taking action a in h, $N(h)$ is the number of simulations performed in h, $N(h,a)$ is the number of times action a is selected in h, and c is a constant that balances exploration and exploitation. However, UCT suffers from severe search inefficiency in the problems with a large action space such as IF games, since it requires to take every action at least once and relies only on *uncertainty-driven* (or visit counts-based) exploration.

PUCT (Silver et al., 2017; 2018) partially addresses the challenges of IF games by adopting PUCB (Rosin, 2011), which involves a prior action distribution $\pi(\cdot|h)$ and eliminates the need for choosing every action at least once. The action selection rule is given by:

$$\arg\max_a \left[Q(h,a) + c_{\text{PUCT}}\pi(a|h)\tfrac{\sqrt{N(h)}}{N(h,a)+1} \right] \qquad (2)$$

The prior distribution $\pi(\cdot|h)$ in Eq. (2) is typically trained by behavioral cloning of $(h_{\text{root}}, a_{\text{root}}^*)$ samples obtained by the result of tree search (Anthony et al., 2017; Silver et al., 2018). However, this procedure not only discards other search information such as abundant (h_t, a_t, r_t, h_{t+1}) samples obtained during the search but also hardly encourages information sharing across the semantically similar actions. Therefore, PUCT is still limited in search efficiency for the tasks with language action space, raising the need for a *language-driven* exploration strategy.

3 MONTE-CARLO PLANNING WITH LANGUAGE ACTION VALUE ESTIMATES

Language-grounded planning ability is essential to address the challenges of IF games. To this end, we need a mechanism to incorporate language understanding and commonsense reasoning into the exploration strategy of search. In this section, we introduce Monte-Carlo planning with Language Action Value Estimates (MC-LAVE), a novel planning algorithm that combines MCTS with

language-driven exploration. MC-LAVE does not rely on any handcrafted heuristic evaluation but starts tabula rasa, based only upon pre-trained word embeddings that can well define the semantic similarities between two language actions. In addition, it only requires a black-box simulator $(r, s', o') \sim \mathcal{G}(s, a)$, which yields (o, a, r, o') samples at each simulator query.

3.1 CREDIT ASSIGNMENT WITH SEARCH EXPERIENCE

Language-driven exploration in MC-LAVE starts by identifying which word sequences of language action are likely to give high long-term rewards. This credit assignment of language action is done by Q-learning using all the experiences $\mathcal{D} = \{(o, a, r, o')\}$ obtained during the past searches. Following the previous work (Hausknecht et al., 2019; Ammanabrolu & Hausknecht, 2020; Ammanabrolu et al., 2020; Madotto et al., 2020), we assume that the current observation captures all the information regarding the latent state, as it is just a text description of the game state. Therefore, we represent the Q-function as a function of the current observation and action, rather than a function of full history and action. Our parameterization of $Q_\phi(o, a)$ basically follows that of Deep Reinforcement Learning Relevance Network (DRRN) (He et al., 2016; Hausknecht et al., 2019), and more details can be found in Appendix A. Finally, the Q_ϕ is trained by minimizing the temporal difference error using $\mathcal{D}$:

$$\arg\min_{\phi} \mathbb{E}_{(o,a,r,o') \sim \mathcal{D}} \left[\left(r + \gamma \max_{a' \in A_{\text{valid}}(o')} Q_{\bar{\phi}}(o', a') - Q_\phi(o, a) \right)^2 \right] \tag{3}$$

where $\bar{\phi}$ is an exponential moving average of ϕ, i.e. soft target update, and $A_{\text{valid}}(o')$ is a set of valid actions in the observation o' provided by Jericho environment. While PUCT of Eq. (2) also uses previous search information to construct a prior policy π, it is typically trained only on planning trajectories $(h_{\text{root}}, a^*_{\text{root}})$ that generally cover very limited regions. Therefore, it can hardly provide informative search guides for areas outside the planning trajectories. In contrast, Q_ϕ of Eq. (3) is trained by using every search experience encountered during search processes, thus it can potentially provide more information over much broader set of states and actions. However, the credit assignment provided by Q_ϕ still struggles to provide useful information for novel language observation-action regions that have never been experienced, making its direct adoption as an exploration strategy inappropriate: the search process necessarily entails visits to novel areas where Q_ϕ does not work properly, and thus Q_ϕ may instead promote exploitation.

3.2 LANGUAGE-DRIVEN EXPLORATION VIA LANGUAGE ACTION VALUE ESTIMATES

The key to generalizing existing experiences to novel situations is context-agnostic information sharing between language actions based on their semantic similarities. For example, if an action of 'take something' has ever been useful in the past, we may expect that the action of 'take something else' can also be worthy in other situations. Motivated by such instances, we introduce Language Action Value Estimates (LAVE), which assigns *non-uniform* search priorities to each language action by examining whether its semantic neighborhood actions have been beneficial in the past.

As the first step for LAVE, we define a *semantic neighborhood* of action a, a set of the past experiences whose actions share similar semantics with action a by:

$$\mathcal{N}(a) = \{ (\bar{o}, \bar{a}) \mid d(a, \bar{a}) < \delta \text{ where } (\bar{o}, \bar{a}, \bar{r}, \bar{o}') \in \mathcal{D} \} \tag{4}$$

where δ is a hyperparameter that controls a proximity threshold, and $d(a, \bar{a})$ is a distance measure between two actions a and $\bar{a}$ in language embedding space represented by the pre-trained word embeddings $e(\cdot)$:

$$d(a, \bar{a}) = 1 - \frac{\psi(a) \cdot \psi(\bar{a})}{\|\psi(a)\|\|\psi(\bar{a})\|} \text{ where } \psi(a) = \frac{1}{|a|} \sum_{i=1}^{|a|} e(a^i)$$

For simplicity, we use the average of the word embeddings $\psi(a)$ as the language action (or sentence) embedding, where the semantic similarity can be well-measured by the cosine similarity in the embedding space.

Figure 2: Overall architecture of policy improvement via MC-LAVE.

Then, the LAVE exploration bonus for the action a is estimated through a soft maximum over the Q-values of a's semantic neighborhood actions in order to encourage optimistic exploration.

$$L_\phi(a) = \log \frac{1}{|\mathcal{N}(a)|} \sum_{(\bar{o},\bar{a}) \in \mathcal{N}(a)} \exp[Q_\phi(\bar{o},\bar{a})] \quad (5)$$

Note that $L_\phi(a)$ in Eq. (5) relies only on the Q-values of $(\bar{o}, \bar{a})$ samples experienced in the past, thus can be reliably estimated. Also, it is context-agnostic in which the action a is taken, thus circumvents the challenge of measuring the similarity between the very long textual observations, while promoting active information sharing between affordable language actions.

Finally, MC-LAVE encourages the *language-driven* exploration in the selection phase of MCTS via LAVE $L_\phi(a)$, which selects actions at each intermediate nodes by the following rule:

$$\underset{a \in A_{\text{valid}}(o)}{\arg\max} \left[Q(h,a) + \underbrace{\frac{\sqrt{N(h)}}{N(h,a)+1}}_{\substack{\text{uncertainty-driven} \\ \text{exploration}}} \left(\underbrace{c_{\text{PUCT}} \pi_\theta(a|o)}_{\substack{\text{prior knowledge} \\ \text{encoding}}} + \underbrace{c_{\text{LAVE}} L_\phi(a)}_{\substack{\text{language-driven} \\ \text{exploration}}} \right) \right] \quad (6)$$

where $\pi_\theta(a|o)$ is a prior policy trained by behavior cloning of past planning results, $L_\phi(a)$ is a language-driven exploration bonus, c_{LAVE} is an exploration constant. MC-LAVE uses the policy π_θ for incorporating prior knowledge of the past planning trajectories, as well as the language-driven bonus $L_\phi(a)$ for facilitating information sharing between semantic neighborhood actions. MC-LAVE initially encourages to explore the actions with high language-driven exploration bonuses and low visit count, but it does not hurt the asymptotic behavior of MCTS (Theorem 2 in Appendix C). The full pseudocode for the MC-LAVE is provided in Appendix D.

4 REINFORCEMENT LEARNING VIA MC-LAVE

As shown in (Silver et al., 2017), MCTS can be used as a strong policy improvement operator for reinforcement learning. Similarly, we use MC-LAVE as a policy improvement operator for learning the IF game. As a result, our reinforcement learning algorithm, MC-LAVE-RL, alternates between MC-LAVE planning and supervised learning of self-generated actions:

1. **Planning** Use the MC-LAVE with current policy π_θ and Q-function Q_ϕ to collect the n planning trajectories $\mathcal{T} = \bigcup_i \tau^{(i)}$ and experience replay $\mathcal{D}$:

$$\tau^{(i)} = \{(o_1^{(i)}, a_1^{*(i)}), \ldots, (o_T^{(i)}, a_T^{*(i)})\}, \mathcal{D} = \{(o, a, r, o')\}$$

where $a_t^{*(i)}$ is selected action at i-th trajectory t-th timestep by MCTS and T denotes a episode length. (For the first iteration, MC-LAVE uses uniform policy and randomly initialized Q-function.)

	Algorithms	DRRN[†]	TDQN[†]	KG-A2C[‡]	MC!Q*BERT[§]	PUCT-RL	MC-LAVE-RL
Requirements	*Valid Action*	Hard	Soft	Soft	Soft	Hard	Hard
	Resettable	-	-	-	✓	✓	✓
	External Info	-	-	-	ALBERT & Jericho-QA	-	Word Embedding
Difficult Games	ZORK1	32.6	9.9	34	41.6	38.2	**45.2**
	DEEPHOME	1	1	1	8	17.4	**35**
	LUDICORP	13.8	6	17.8	**22.8**	18	**22.8**
Possible Games	PENTARI	27.2	17.4	50.7	58	64	**68**
	DETECTIVE	197.8	169	207.9	**330**	322	**330**
	LIBRARY	17	6.3	14.3	**19**	**19**	**19**
	BALANCES	**10**	4.8	**10**	**10**	**10**	**10**
	TEMPLE	7.4	7.9	**8**	**8**	**8**	**8**
	ZTUU	**21.6**	4.9	9.2	11.8	5	7

Table 1: Performance evaluation of various approaches for IF games in Jericho (Hausknecht et al., 2019). Handicaps leveraged in each algorithm are described in the table. *Valid Action* indicates whether an algorithm uses valid action handicap provided by Jericho as a hard constraint for the effective action space or as a soft constraint via entropy loss over the valid actions (Ammanabrolu & Hausknecht, 2020). *Resettable* indicates whether an algorithm requires a resettable simulator, i.e. the previously visited state can be restored. ZORK1, DEEPHOME, LUDICORP are categorized as *difficult games* and the other games are categorized as *possible games* by Hausknecht et al. (2019). The results of other algorithms are from Hausknecht et al. (2019)[†], Ammanabrolu & Hausknecht (2020)[‡], and Ammanabrolu et al. (2020)[§] respectively. All our results (PUCT-RL, MC-LAVE-RL) indicate averages over 5 independent runs, and their standard errors are provided in Appendix E due to space limit.

2. **Policy training** Update the policy network parameter θ by minimizing the negative log-likelihood with using collected planning trajectories $\mathcal{T}$, i.e. supervised learning with cross-entropy loss:

$$\arg\min_\theta \mathbb{E}_{(o_t^{(i)}, a_t^{*(i)}) \sim \mathcal{T}} \left[-\log \pi_\theta(a_t^{*(i)}|o_t^{(i)}) \right]$$

3. **Q-learning** Update the Q-function parameter ϕ by minimizing the temporal difference error from experience replay $\mathcal{D}$:

$$\arg\min_\phi \mathbb{E}_{(o,a,r,o') \sim \mathcal{D}} \left[\left(r + \gamma \max_{a' \in A_{\text{valid}}(o')} Q_{\bar{\phi}}(o', a') - Q_\phi(o, a) \right)^2 \right]$$

We continue to update the policy through the above policy iteration with MC-LAVE operator until the policy performance converges.

5 EXPERIMENTS

In this section, we show experimental results of our approach on IF games included in Jericho environment (Hausknecht et al., 2019). The action spaces of IF games in Jericho environment are defined by the sequences of the game-dependent input vocabulary whose size is roughly from 500 to 2000. While the size of the vocabulary is limited compared to large-scale open domain dialogues, it still serves as a useful testbed to demonstrate the effectiveness of semantic-based information sharing of MC-LAVE[1]. First, we evaluate performances of MC-LAVE-RL comparing with baseline methods. Second, we compare intermediate scores of MC-LAVE-RL on ZORK1 with a baseline, PUCT-RL that uses PUCT as a policy improvement operator, to show that MC-LAVE is the more effective for IF games than PUCT. Third, we investigate the effectiveness of semantic neighborhood by comparing the planning performance of MC-LAVE with varying the size of semantic neighborhood. Finally, we give a qualitative analysis of our approach by providing a representative example,

---

[1]For example, the ZORK1 environment produces identical observations for taking the actions `take lantern` and `get lantern`, where MC-LAVE can readily take advantage by exploiting the information sharing across those semantically similar actions (Appendix H).

Methods	PUCT-RL		MC-LAVE-RL	
	Planning	Learning	Planning	Learning
Iteration 1	31.9 ± 1.4	36.6 ± 1.0	30.4 ± 2.0	36.6 ± 1.0
Iteration 2	35.8 ± 0.0	37.4 ± 1.0	36.1 ± 0.1	38.2 ± 0.8
Iteration 3	35.3 ± 0.2	39.0 ± 0.0	41.2 ± 0.5	43.0 ± 1.0
Iteration 4	35.2 ± 0.4	38.2 ± 0.8	43.8 ± 0.1	45.2 ± 1.2

Table 2: Experimental results of the policy improvement with PUCT and MC-LAVE on ZORK1. For each iteration, we perform the 25 planning with PUCT and MC-LAVE to collect planning trajectories and experience replay. All results indicate averages and standard errors over 5 trials.

which shows how MC-LAVE focuses on semantically promising actions during search. Detailed configurations of our experiments are described in Appendix B.

5.1 EVALUATION ON INTERACTIVE FICTION GAMES

First, we compare the performance of MC-LAVE-RL with the following algorithms: (1) DRRN (Hausknecht et al., 2019), a variant of DQN algorithm (Mnih et al., 2013) for natural language action space, (2) TDQN (Hausknecht et al., 2019), an extension of LSTM-DQN algorithm (Narasimhan et al., 2015) incorporating with template-based action generation, (3) KG-A2C (Ammanabrolu & Hausknecht, 2020), actor-critic method with knowledge graph state representation, (4) MC!Q*BERT (Ammanabrolu et al., 2020), an extension of KG-A2C with BERT-based knowledge graph construction and knowledge-graph-based intrinsic reward. In addition, we also compare MC-LAVE-RL with our baseline called PUCT-RL, which uses PUCT as a policy improvement operator.

Table 1 summarizes handicaps leveraged in each algorithm and the performance of MC-LAVE-RL and baseline algorithms across 9 IF games included in Jericho environment. The results show that MC-LAVE-RL outperforms or matches the state-of-the-art results on 8 out of 9 games. Although MC-LAVE-RL requires more handicap or assumption, it performs the same or better than strong baseline MC!Q*BERT which requires similar assumptions and more requirements. In addition, MC-LAVE-RL achieves higher game scores on overall games compared to PUCT-RL, which is a baseline algorithm that only excludes language-driven exploration strategy from MC-LAVE-RL. Furthermore, MC-LAVE-RL performs significantly better than other methods on *difficult games* such as ZORK1, DEEPHOME, and LUDICORP, which are categorized by Hausknecht et al. (2019) as a relatively challenging game due to the large action space and sparse rewards.

In the case of ZORK1, as described in Section 2.2, other algorithms (except MC!Q*BERT, which is concurrent work by Ammanabrolu et al. (2020)) fail to overcome the bottleneck and are stuck into the suboptimal policy, which leaves the agent being eaten by a monster in the dark without a light source. On the other hand, MC-LAVE-RL successfully finds the optimal action (i.e. `take lantern`) on the bottleneck state by using the exploration strategy suitable for natural language spaces and obtains additional rewards by discovering novel states that cannot be reached with other methods. For instance, trajectories of MC-LAVE-RL agent frequently show that the agent overcomes bottlenecks and behaves crucial actions to complete the game, such as `killing the monster with sword` and `putting the painting in the trophy case`. Further illustrative examples of trajectories are provided in Appendix F.

5.2 REINFORCEMENT LEARNING VIA MC-LAVE

In order to understand the effectiveness of MC-LAVE as a policy improvement operator, we compare the performances of PUCT-RL and MC-LAVE-RL in ZORK1. Table 2 reports the intermediate results of planning and supervised learning in each iteration of the policy iteration. In each iteration, the policy and the Q-function are trained using planning trajectories and experience replay collected from 25 independent planning agents. As can be seen in Table 2, the performance of MC-LAVE-RL is improved more consistently than PUCT-RL, both in planning and learning. At the beginning of the policy iteration, PUCT-RL improves the performance, but it fails to overcome bottleneck and converges to a suboptimal policy: PUCT utilizes the prior policy learned by imitating the planning results of the previous iteration to estimate the exploration bonus, but this uncertainty-based method is not much effective to encourage the agent to explore the action space that is not sufficiently covered. On the other hand, MC-LAVE-RL not only uses the prior policy, but also uses Q-Network

PUCT	east	open case	open trap door	take all	take lantern	take sword	turn on lantern
$Q(h, a)$	2.65	6.80	**13.81**	2.03	11.34	0.22	9.00
$\pi_\theta(a\|o)$	0.08	0.08	0.50	0.08	0.08	0.08	0.08
$N(h, a)$	38	39	105	37	52	37	42

MC-LAVE	east	open case	open trap door	take all	take lantern	take sword	turn on lantern
$Q(h, a)$	7.86	10.59	14.10	2.30	**14.23**	-1.33	13.11
$\pi_\theta(a\|o)$	0.08	0.08	0.50	0.08	0.08	0.08	0.08
$N(h, a)$	23	58	85	47	67	7	63
$L_\phi(a)$	13.21	35.55	25.35	38.21	49.81	2.25	34.72

Table 3: Illustrative examples of search results of PUCT and MC-LAVE on bottleneck state in ZORK1 (see Figure 1). $Q(h, a)$ denotes the average of Monte-Carlo returns, $\pi_\theta(a|o)$ represents policy prior, $N(h, a)$ represents visit count of each action, $L_\phi(a)$ represents language-driven exploration bonus of MC-LAVE. $c_{\text{PUCT}} = 200$ and $c_{\text{LAVE}} = 0.1$ are used for the exploration constants.

for credit assignment to language actions. This allows a more focused exploration on semantically promising actions and consequently overcomes the bottleneck to further improve the performance.

5.3 THE EFFECT OF THE SIZE OF SEMANTIC NEIGHBORHOOD

The size of semantic neighborhood is particularly crucial for the performance of MC-LAVE planning. To see this, we conducted a simple ablation experiment in ZORK1 on the effect of varying proximity threshold δ, which controls the size of the semantic neighborhood of action $\mathcal{N}(a)$ in Eq. (4). Moreover, to demonstrate that the LAVE exploration bonus works as a meaningful exploration bonus beyond simple random noise injection, we also present the result of a simple baseline PUCT+RANDOM, which uses MC-LAVE action selection rule of Eq. (6) with the neighborhood given by 10 randomly sampled actions. This baseline can be understood as performing the search with noise injection via the randomly chosen neighborhood, while not considering information sharing between semantically similar actions. As shown in Figure 3, the performance of PUCT+RANDOM is almost identical to PUCT, which supports that random noise injection alone does not lead to

Figure 3: Performance of MC-LAVE planning on ZORK1 for varying δ. The results are averaged over 100 trials, and error bars indicate the standard errors.

improving search efficiency. Moreover, the results of MC-LAVE shows that too small or too large δ are not effective, which can be naturally explained as follows: (1) when $\delta = 0$, no sample in the replay buffer is considered as neighborhood, leading LAVE exploration bonus to always zero, (2) when $\delta = 2$ (the largest possible value), every sample in the replay buffer is considered as neighborhood, yielding LAVE exploration bonus to a constant value for all a. Therefore, with either two extremes of δ, the MC-LAVE action selection rule of Eq. (6) is reduced to the PUCT action selection rule of Eq. (2). Finally, the moderately small $\delta = 0.3$ works the best, which highlights the importance of information sharing between *meaningfully defined* semantic neighborhoods to solve IF games efficiently.

5.4 QUALITATIVE ANALYSIS

In this section, we provide a qualitative analysis on the effectiveness of language-driven exploration in MC-LAVE. We show an illustrative example in Table 3 that demonstrates how MC-LAVE focuses more on the semantically promising actions. Table 3 shows search results of PUCT and MC-LAVE in the bottleneck state of ZORK1, described in Figure 1. In this example, the 'open trap door' is a suboptimal action that obtains an immediate reward, while 'take lantern' gives no immediate reward, but it is an optimal action when considering long-term dependency. As can be seen in Table 3, PUCT cannot effectively explore because of an evenly search based on uncertainty, and converges into suboptimal action (i.e. 'open trap door') that obtains an immediate reward. On the other hand, MC-LAVE assigns search priorities to actions based on the optimistically aggregated

Q-estimates of the past actions. As a result of focusing on semantically promising actions, MC-LAVE selects the optimal action (i.e. 'take lantern') even though it does not give any immediate reward. PUCT also performs non-uniform search based on prior policy, but this only encourages to explore the actions of previous behavior and does not focus on semantically promising actions.

6 RELATED WORK

Variants of Monte-Carlo tree search. Leveraging prior knowledge for MCTS has been one of the most important direction for improving MCTS (Gelly & Silver, 2007; Silver et al., 2016; 2017; 2018; Gelly & Silver, 2011). PUCT (Rosin, 2011; Silver et al., 2017; 2018) is one of the most popular MCTS algorithms, which incorporates prior knowledge as a policy. The prior policy in PUCT is typically trained by imitation learning of past behavior; other search information, such as transition tuples and inferred Q-values, is discarded. To address this limitation, Hamrick et al. (2019) presents Search with Amortized Value Estimates (SAVE), which incorporates Q-based prior knowledge into MCTS. In SAVE, Q-function is fit by inferred Q-values and transition tuples from search, then is used as a prior into MCTS. Although SAVE improves sample efficiency in MCTS, it lacks a language-grounded exploration strategy. Rapid Action Value Estimation (RAVE) (Gelly & Silver, 2011) is another notable method that addresses information sharing, which allows sharing action values in the search tree. However, RAVE is designed especially for the game of Go and cannot be straightforwardly applied to IF games. Furthermore, to leverage the prior knowledge given as textual information, Branavan et al. (2011) present a method which extracts the most relevant information to current state and incorporates linguistic information into the Monte-Carlo search framework. However, they assume natural language documents that contain domain knowledge of the task.

Reinforcement Learning via Monte-Carlo tree search. There are a number of recent work on using MCTS for reinforcement learning. Silver et al. (2017) achieved successful results with MCTS as a policy improvement operator in the game of Go. Also, in the negotiation dialogue domain, Jang et al. (2020) used Bayes-adaptive Monte-Carlo planning as a policy improvement operator to prevent the issue of diverging from human language. Inspired by these successes, we use MC-LAVE algorithm as a policy improvement operator which effectively works on IF games.

Deep Reinforcement Learning for Interactive Fiction Games. IF games have attracted a lot of interest from the RL research since the introduction of Jericho (Hausknecht et al., 2019), an OpenAI Gym-like (Brockman et al., 2016) learning environment for IF games. Jericho includes baseline RL agents such as DRRN and TDQN. DRRN is a variant of deep Q-Network architecture for handling natural language actions in text-based decision making tasks. TDQN is an extension of LSTM-DQN (Narasimhan et al., 2015) utilizing predefined templates in order to reduce effective search spaces of combinatorial language action space. More recently, knowledge-graph-based approaches have been introduced to address the issues of partial observability and commonsense reasoning (Ammanabrolu & Riedl, 2019; Ammanabrolu & Hausknecht, 2020; Ammanabrolu et al., 2020). KG-A2C (Ammanabrolu & Hausknecht, 2020) is an actor-critic algorithm that leverages knowledge graph state representation for commonsense reasoning. Ammanabrolu et al. (2020) introduce Q*BERT, an extension of KG-A2C, which updates the knowledge graph by using pre-trained language model ALBERT (Lan et al., 2020), a variant of BERT (Devlin et al., 2019). To encourage better exploration and overcome the bottleneck state in IF games, they introduce MC!Q*BERT that additionally uses intrinsic motivation based on changes of the knowledge graphs.

7 CONCLUSION

We presented Monte-Carlo planning with Language Action Value Estimates (MC-LAVE), an MCTS-based algorithm for language action space, which combines MCTS with language-driven exploration strategy. MC-LAVE assigns search priorities to each language action based on Q-values of previously executed actions that share similar meanings, then invests more search effort into semantically promising actions. We then incorporated MC-LAVE into reinforcement learning by using MC-LAVE as a policy improvement operator. Our approach achieved remarkable results in difficult games that feature large action space and sparse reward and outperforms or matches the state-of-the-art on the various IF games.

REFERENCES

Prithviraj Ammanabrolu and Matthew Hausknecht. Graph constrained reinforcement learning for natural language action spaces. In *International Conference on Learning Representations*, 2020.

Prithviraj Ammanabrolu and Mark Riedl. Playing text-adventure games with graph-based deep reinforcement learning. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 3557–3565, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1358.

Prithviraj Ammanabrolu, Ethan Tien, Matthew Hausknecht, and Mark O. Riedl. How to avoid being eaten by a grue: Structured exploration strategies for textual worlds. *CoRR*, abs/2006.07409, 2020.

Thomas Anthony, Zheng Tian, and David Barber. Thinking fast and slow with deep learning and tree search. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 5366–5376, 2017.

Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 2002.

S.R.K. Branavan, David Silver, and Regina Barzilay. Learning to win by reading manuals in a Monte-Carlo framework. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pp. 268–277, Portland, Oregon, USA, June 2011. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P11-1028.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *CoRR*, abs/1606.01540, 2016.

Cameron Browne, Edward Powley, Daniel Whitehouse, Simon Lucas, Peter I. Cowling, Stephen Tavener, Diego Perez, Spyridon Samothrakis, and Simon Colton. A survey of Monte Carlo tree search methods. *IEEE Transactions on Computational Intelligence and AI in Games*, 4:1–49, 2012.

Rémi Coulom. Efficient selectivity and backup operators in Monte-Carlo tree search. In *Proceedings of the 5th International Conference on Computers and Games*, pp. 72–83, 2006.

Marc-Alexandre Côté, Ákos Kádár, Xingdi (Eric) Yuan, Ben Kybartas, Tavian Barnes, Emery Fine, James Moore, Matthew Hausknecht, Layla El Asri, Mahmoud Adada, Wendy Tay, and Adam Trischler. Textworld: A learning environment for text-based games. In *Computer Games Workshop at ICML/IJCAI 2018*, pp. 1–29, June 2018.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Nancy Fulda, Daniel Ricks, Ben Murdoch, and David Wingate. What can you do with a rock? affordance extraction via word embeddings. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*, pp. 1039–1045, 2017.

Sylvain Gelly and David Silver. Combining online and offline knowledge in uct. In *ICML*, pp. 273–280, 2007.

Sylvain Gelly and David Silver. Monte-carlo tree search and rapid action value estimation in computer go. *Artificial Intelligence*, 175(11):1856–1875, 2011.

Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Tobias Pfaff, Theophane Weber, Lars Buesing, and Peter W Battaglia. Combining q-learning and search with amortized value estimates. In *International Conference on Learning Representations*, 2019.

Matthew Hausknecht, Prithviraj Ammanabrolu, Marc-Alexandre Côté, and Xingdi (Eric) Yuan. Interactive fiction games: A colossal adventure. In *AAAI 2020*, October 2019. ArXiv.

Ji He, Jianshu Chen, Xiaodong He, Jianfeng Gao, Lihong Li, Li Deng, and Mari Ostendorf. Deep reinforcement learning with a natural language action space. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1621–1630, 2016.

Youngsoo Jang, Jongmin Lee, and Kee-Eung Kim. Bayes-adaptive monte-carlo planning and learning for goal-oriented dialogues. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2020.

Levente Kocsis and Csaba Szepesvári. Bandit based Monte-Carlo planning. In *Proceedings of the Seventeenth European Conference on Machine Learning*, 2006.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. In *International Conference on Learning Representations*, 2020.

Andrea Madotto, Mahdi Namazifar, Joost Huizinga, Piero Molino, Adrien Ecoffet, Huaixiu Zheng, Alexandros Papangelis, Dian Yu, Chandra Khatri, and Gokhan Tur. Exploration based language learning for text-based games. In Christian Bessiere (ed.), *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20*, pp. 1488–1494. International Joint Conferences on Artificial Intelligence Organization, 7 2020. Main track.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Nick Montfort. *Twisty Little Passages: An Approach to Interactive Fiction*. 2005.

Karthik Narasimhan, Tejas Kulkarni, and Regina Barzilay. Language understanding for text-based games using deep reinforcement learning. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 1–11, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1001.

Graham Nelson. *The Inform Designer's Manual*. 2001.

Christopher D Rosin. Multi-armed bandits with episode context. *Annals of Mathematics and Artificial Intelligence*, 61(3):203–230, 2011.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of go without human knowledge. *Nature*, 2017.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

A IMPLEMENTATION DETAILS

As discussed in section 4, MC-LAVE-RL alternates (1) planning, (2) supervised learning and Q-learning. In the planning phase, multiple planning workers are run in parallel on a distributed computing system to collect various planning trajectories and experience replay. After planning, we merge collected trajectories and experience replay and train the policy network and Q-Network using merged trajectories and experience replay respectively. For Q-Network, we exploit the same architecture used in DRRN (He et al., 2016) illustrated as Figure 5, which takes an observation o_t, an action a_t as an input and outputs $Q_\phi(o_t, a_t)$. For the policy network, we use a network architecture similar with DRRN as described in Figure 4, which directly outputs $f_\theta(a_t|o_t)$, an unnormalized probability of an action a_t given an observation o_t, i.e. $\pi_\theta(a_t|o_t) \propto f_\theta(a_t|o_t)$.

Figure 4: Policy network   Figure 5: Q-Network

B EXPERIMENTS DETAILS

Hyperparameters	ZORK1	DEEPHOME	LUDICORP	PENTARI	DETECTIVE	LIBRARY	BALANCES	TEMPLE	ZTUU
λ (discount factor)	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
# of max iterations	4	4	4	4	4	4	4	4	4
δ (neighborhood threshold)	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
Max search depth	10	10	20	10	10	15	15	10	15
Max episode length	35	35	50	35	50	35	35	35	35
# of simulations per action	50	50	50	50	50	50	50	50	50
# of planning workers	25	25	25	25	25	25	25	25	25
c_{LAVE}	1.0	1.0	2.0	1.0	0.1	1.0	1.0	1.0	1.0
c_{PUCT}	50	20	50	50	200	20	50	50	50

Table 4: Configurations of MC-LAVE-RL used in our experimental results. Hyperparameters in upside of the table were globally adapted in the planning-learning framework and the other hyperparameters are used only in MCTS planning phase.

C ASYMPTOTIC OPTIMALITY OF MC-LAVE

In this section, we show that the asymptotic optimality of PUCB (Rosin, 2011) is still held after the introduction of the language-driven exploration bonus in Eq. (5). We start by restating the theoretical result for PUCB.

Lemma 1. *(Theorem 1 in (Rosin, 2011)) For any stochastic policy $\pi(a) > 0$ with $\sum_a \pi(a) = 1$, $c_1 > 0$, and $c_2 > 0$, **PUCB action selection rule** at trial t is defined as:*

$$\arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2 \frac{1}{\pi(a)} \sqrt{\frac{\log t}{t}} \right]$$

where $N(a)$ is the number of simulations action a is taken in the past, $r(t, a)$ is an empirical average reward of action a at the start of trial t., Then, expected regret of PUCB action selection rule is bounded by $O(\sqrt{n \log n})$ $\forall n > 1$.

Note that the prior policy π in the PUCB rule encourages the actions that have a high value of $\pi(a)$ to be selected more often. In this work, we use a variant of PUCB as in (Silver et al., 2017).

Theorem 2. *MC-LAVE action selection rule at trial t is defined as:*

$$\arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2 \frac{1}{\pi(a)} \sqrt{\frac{\log t}{t}} - c_3 \frac{1}{L(a)} \sqrt{\frac{\log t}{t}} \right]$$

where $N(a)$ is the number of simulations action a is taken in the past, $r(t, a)$ is an empirical average reward of action a at the start of trial t, $\pi(a) > 0$ is a stochastic policy with $\sum_a \pi(a) = 1$, $c_1 > 0$, $c_2 > 0$, $c_3 > 0$ and $L(a) > 0$ is a bonus of action a. Then MC-LAVE action selection rule also achieves expected regret bounded by $O(\sqrt{n \log n})$ $\forall n > 1$.

Proof. The theorem can be proved by showing that MC-LAVE action selection rule can be represented as PUCB action selection rule with another policy. MC-LAVE action selection rule is defined as

$$\arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2 \frac{1}{\pi(a)} \sqrt{\frac{\log t}{t}} - c_3 \frac{1}{L(a)} \sqrt{\frac{\log t}{t}} \right]$$

$$= \arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2 \left(\frac{1}{\pi(a)} + \frac{c_3}{c_2} \frac{1}{L(a)} \right) \sqrt{\frac{\log t}{t}} \right]$$

Define $p(a)$, $\pi'(a)$, c_2' as follows:

$$p(a) := \frac{1}{\left(\frac{1}{\pi(a)} + \frac{c_3}{c_2} \frac{1}{L(a)} \right)}, \quad \pi'(a) := \frac{p(a)}{\sum_a p(a)}, \quad c_2' := c_2 \frac{1}{\sum_a p(a)}$$

Then MC-LAVE action selection rule can be represented as follows:

$$\arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2 \frac{1}{p(a)} \sqrt{\frac{\log t}{t}} \right]$$

$$= \arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2 \frac{1}{\sum_a p(a)} \cdot \frac{1}{\frac{p(a)}{\sum_a p(a)}} \sqrt{\frac{\log t}{t}} \right]$$

$$= \arg\max_a \left[r(t, a) + c_1 \sqrt{\frac{\log t}{N(a)}} - c_2' \frac{1}{\pi'(a)} \sqrt{\frac{\log t}{t}} \right]$$

which induces PUCB action selection rule with another policy π' and coefficient c_2'. Hence, by Lemma 1, MC-LAVE achieves expected regret bounded by the same order with PUCB, which is $O(\sqrt{n \log(n)})$ $\forall n > 1$. $\square$

Thus, in the same manner we obtain the analysis of UCT from that of UCB, i.e. induction with a mild assumption on the drift-condition of the inherent non-stationary bandit problem, we can obtain the analysis of MCTS using MC-LAVE using the above result.

D PSEUDOCODE OF MC-LAVE

Algorithm 1 Monte-Carlo Planning with Language Action Value Estimates (MC-LAVE)

---

procedure SEARCH(s_0)
    $o_0 \leftarrow O(s_0)$
    $h_0 \leftarrow o_0$
    repeat
        SIMULATE $(s_0, h_0, 0)$
    until TIMEOUT ()
    return $\arg\max\limits_{a \in A_{\text{valid}}(o_0)} Q(h_0, a)$
end procedure

procedure SIMULATE(s, h, t)
    if $t = $ (planning horizon T) **then**
        return 0
    end if
    $[a, \text{rollout}] \leftarrow$ SELECTACTION(h)
    $[r, s', o'] \leftarrow \mathcal{G}(s, a)$
    $h' \leftarrow hao'$
    if rollout **then**
        $R' \leftarrow$ ROLLOUT($s', t+1$)
    else
        $R' \leftarrow$ SIMULATE($s', h', t+1$)
    end if
    $N(h) \leftarrow N(h) + 1$
    $N(h, a) \leftarrow N(h, a) + 1$
    $Q(h, a) \leftarrow Q(h, a) + \frac{R - Q(h,a)}{N(h,a)}$
    return $r + R'$
end procedure

procedure SELECTACTION(h)
$$a \leftarrow \arg\max_{a \in A_{\text{valid}}(o)} \left[Q(h, a) + c_{\text{PUCT}} \pi_\theta(a|o) \frac{\sqrt{N(h)}}{N(h,a)+1} \right.$$
$$\left. + c_{\text{LAVE}} L_\phi(a) \frac{\sqrt{N(h)}}{N(h,a)+1} \right]$$
    if $N(h, a) = 0$ **then**
        rollout $\leftarrow$ true
    else
        rollout $\leftarrow$ false
    end if
    return $[a, \text{rollout}]$
end procedure

procedure ROLLOUT(s, t)
    if $t = $ (planning horizon T) **then**
        return 0
    end if
    $o \leftarrow O(s)$
    $a \sim \pi_\theta(\cdot|o)$
    $[r, s', o'] \leftarrow \mathcal{G}(s, a)$
    return $r +$ ROLLOUT($s', t+1$)
end procedure

E COMPARISON RESULTS OF SOFT AND HARD CONSTRAINTS

	Algorithms	KG-A2C (Soft)	KG-A2C (Hard)	PUCT-RL	MC-LAVE-RL
Difficult Games	ZORK1	34 ± 2.2	40.2 ± 0.4	38.2 ± 0.8	$\mathbf{45.2 \pm 1.2}$
	DEEPHOME	1 ± 0.0	20 ± 2.1	28.6 ± 2.9	$\mathbf{35 \pm 0.6}$
	LUDICORP	18.6 ± 0.5	19.8 ± 1.0	18 ± 0.0	$\mathbf{22.8 \pm 0.2}$
Possible Games	PENTARI	41 ± 0.9	44 ± 0.9	64 ± 2.4	$\mathbf{68 \pm 2.0}$
	DETECTIVE	318 ± 5.2	$\mathbf{338 \pm 3.4}$	322 ± 2.0	330 ± 0.0
	LIBRARY	15.8 ± 0.5	17 ± 0.0	$\mathbf{19 \pm 0.0}$	$\mathbf{19 \pm 0.0}$
	BALANCES	$\mathbf{10 \pm 0.0}$	$\mathbf{10 \pm 0.0}$	$\mathbf{10 \pm 0.0}$	$\mathbf{10 \pm 0.0}$
	TEMPLE	$\mathbf{8 \pm 0.0}$	$\mathbf{8 \pm 0.0}$	$\mathbf{8 \pm 0.0}$	$\mathbf{8 \pm 0.0}$
	ZTUU	5 ± 0.0	5 ± 0.0	5 ± 0.0	$\mathbf{7 \pm 2.7}$

Table 5: Experimental results comparing soft and hard constraints of valid action handicap. KG-A2C (Soft/Hard) indicates the use of valid action handicap as a (soft constraint via entropy loss over the valid actions/hard constraint for the effective action space). All results indicate averages and standard errors over 5 independent runs.

For an equivalent comparison in terms of valid action handicap, we also re-implemented KG-A2C (published state-of-the-art) in both ways that the valid action handicap are used as a soft constraint via entropy loss over valid actions and as a hard constraint for the effective action space. The results show MC-LAVE-RL still significantly outperforms or matches the both of KG-A2C with using soft and hard constraints on the 8 out of 9 games.

F ILLUSTRATIVE BEHAVIOR EXAMPLES

To understand how MC-LAVE-RL discovers more novel states than other reinforcement learning agents, we provide illustrative examples that represent the behavior of each agent playing ZORK1.

Figure 6: Illustrative examples on ZORK1 that represents the behavior of learned policy by baselines and our algorithms.

G ILLUSTRATIVE EXAMPLES FOR LANGUAGE-ACTION EMBEDDING

We present the t-SNE visualization for the language-action embedding and the (semantic) neighborhood of the action 'take lantern' on ZORK1. In the following figures, the color of points indicates the observation-marginalized Q-value of each action with respect to the replay buffer, which is defined as:

$$\mathbb{E}_{(\bar{o},\bar{a})\sim\mathcal{D}(a)}[Q(\bar{o},\bar{a})] \text{ s.t. } \mathcal{D}(a) = \{(\bar{o},\bar{a}) : a = \bar{a} \text{ where } (\bar{o},\bar{a},\bar{r},\bar{o}') \in \mathcal{D}\}$$

Only a subset of the entire language actions is presented in the figures to prevent the cluttered presentation. The bold font with cyan and yellow indicate the (semantic) neighborhood of the action 'take lantern' and 'open trap door', and the bold font with magenta indicates the common neighborhood of them. As shown in Figure 7, the semantic neighborhood of language actions defined by the pre-trained word embedding is composed of semantically similar actions. However, as shown in Figure 7, when using the word embedding fine-tuned by Q_ϕ training, semantic neighborhood includes a number of irrelevant actions. This result highlights the importance of word embedding for effective information sharing in MC-LAVE-RL.

Figure 7: (Left) The t-SNE visualization for semantic neighborhood of language actions defined by the pre-trained word embedding. The language-actions sharing similar meanings are located at similar points in the embedding space. (Right) The t-SNE visualization for neighborhood of language actions defined by the word embedding fine-tuned by Q_ϕ training. The training objective of Q_ϕ does not account for the semantics of language actions but only considers rewards, thus the resulting embedding loses the linguistic semantics of words.

H ILLUSTRATIVE EXAMPLE FOR SEMANTIC-BASED INFORMATION SHARING

MC-LAVE	east	open case	open trap door	take all	take lantern	take sword	turn on lantern
$Q(h,a)$	7.86	10.59	14.10	2.30	**14.23**	-1.33	13.11
$\pi_\theta(a|o)$	0.08	0.08	0.50	0.08	0.08	0.08	0.08
$N(h,a)$	23	58	85	47	67	7	63
$L_\phi(a)$	13.21	35.55	25.35	38.21	49.81	2.25	34.72

MC-LAVE	east	open case	open trap door	take all	**get lantern**	take sword	turn on lantern
$Q(h,a)$	6.22	11.37	14.29	4.05	**15.31**	-0.82	13.88
$\pi_\theta(a|o)$	0.08	0.08	0.50	0.08	0.08	0.08	0.08
$N(h,a)$	21	47	125	35	57	11	54
$L_\phi(a)$	13.21	35.55	25.35	38.21	41.43	2.25	34.72

Table 6: Illustrative example of search results of MC-LAVE on bottleneck state in ZORK1 (see Figure 1) with modifying the action 'take lantern' to 'get lantern'. The above result with the action 'take lantern' is the same as in Table 3. $Q(h,a)$ denotes the average of Monte-Carlo returns, $\pi_\theta(a|o)$ represents policy prior, $N(h,a)$ represents visit count of each action, $L_\phi(a)$ represents language-driven exploration bonus of MC-LAVE. Note that some differences in $Q(h,a)$ and $N(h,a)$ between results are due to two independent simulation runs.

In order to show the effectiveness of language-action embedding, we further investigate MC-LAVE planning on the bottleneck state presented in Figure 1 and Table 3. Specifically, in the bottleneck state, we artificially modified the action 'take lantern' to 'get lantern' within the valid action set which is used for MC-LAVE planning. As shown in Table 6, MC-LAVE still can successfully select the modified 'get lantern' over 'open trap door' as a final action, even though 'get lantern' had never seen by the agent before. This *generalization* property of MC-LAVE is due to the effect of pre-trained embedding, which shows the importance of language-action embedding for information sharing across semantic space.