Benchmark and Boosted Segmentation on Dental Panoramic Radiographs

[1] *Address withheld*

Abstract

Panoramic radiographs, also known as orthopantomograms, are routinely used by dentists to get a better understanding of the patient's oral condition and perform orthodontics; however, most dentists' use of them is rough which may cause medical negligence due to physician burnout and time limitation. To reduce the dentists' workflow, we define a mission to segment five orals structures including Alveolarcrest, Condyle, Neuraltube, Sinusmaxillaris, and Teeth on Panoramic radiographs. A Cascaded Multi-scale Mask2former(CMMask2former) method is proposed for this task. For the small objects, we specially design multi-scale masked attention for the mask area. Overall, the whole structure is designed in a cascade way of two stages for localization and prediction. Our results demonstrate a superior prediction performance compared to other methods.

Keywords: Panoramic radiographs, Orthodontic, Segmentation, Mask2former.

1. Introduction

Physician burnout is a serious issue that affects all dentists due to the overwhelming patient data for dentists to review and complex workflows.(Yates, 2020) Panoramic radiographs, as a way to visualize patients' oral condition; most dentists' use tends to be rough. The quality of care is often sub-optimal, and some preventable medical errors may happen. Meanwhile, patients are also dissatisfied with limited interactions and attention from doctors during their short clinical visits. Segmentation models for the analysis of Panoramic radiographs data is a challenging task that helps to uncover different oral structures which can reduce the workflow of dentists and give both dentists and patients a clearer visualization of their oral condition for orthodontic treatment plans.(Wu et al., 2018) In this context, we propose a mission to do segmentation on the Panoramic radiographs for five oral structures: Alveolarcrest, Condyle, Neuraltube, Sinusmaxillaris, and Teeth. Considering the Independence between teeth and overlap area with other structures, an instance segmentation is applied for the teeth class.(Lee et al., 2020) For the other four structures, we detect them with a semantic segmentation way.(Koch et al., 2019) Recently, a new deep learning paradigm that is compatible with both two segmentation methods was introduced: Masked-attention Mask Transformer (Mask2former)(Cheng et al., 2022), which could be applied to this mission. It is a transformer-based encoder-decoder framework for Universal Image Segmentation. The semantic segmentation for Alveolarcrest, Condyle, Neuraltube, and Sinusmaxillaris is still a challenging task, especially for Neuraltube which is slender. To improve segmentation results for small object Neuraltube, we specially designed a Cascaded structure based on Mask2former with Multi-scale Masked attention for its segmentation on Panoramic radiographs. The proposed framework Cascaded Multi-scale Mask2former(CMMask2former) offers state-of-the-art performance in the segmentation of Panoramic radiographs.

2. Methods

Figure 1: CMMask2former Framework: Two stages of Multi-scale Masked attention Mask-former (MMask2former) in a cascaded way. MMask2former adopts the same meta-architecture as Mask2Former except for the attention module.

The schematic overview of our CMMask2former framework is shown in Figure 1. Our framework is built based on Mask2former(Cheng et al., 2022). For the slender and small characteristics of Neuraltube, it will be hard to learn the features of the object and find the boundary distinction, hence we first design a Multi-scale Masked attention to localize the object region and import more surrounding information of the object. Based on the Masked attention(Cheng et al., 2022), we adjust the masked attention map to the bounding box of predicted area and use all of the previous masked attention maps to generate the attention map for the next layer. Our Multi-scale masked attention modulates the attention matrix via:

$$X_l = softmax(\frac{1}{l}\sum_{i=0}^{l-1} BOX(M_i) + Q_l K_l^T)V_l + X_{l-1}. \tag{1}$$

Here, l is the layer index, $X_l \in R^{NC}$ refers to NC-dimensional query features at the lth layer and Q_l. $Q_l \in R^{NC}$ is the query feature. $K_l, V_l \in R^{H_l W_l C}$ are the image features respectively, and H_l and W_l are the spatial resolution of image features. $M_{l-1} \in \{0,1\}^{NH_l W_l}$ is the binarized prediction output (thresholded at 0.5) from the previous layer. BOX is the function to fill the prediction of binary mask M_i to a shape of its bounding box area.

Overall, we use two Mask2formers with Multi-scale masked attention to build a cascaded structure. The first MMask2former is used to localize the object region. We crop the predicted region from the original image after enlarging the range by 10 percent of its width and high with the center fixed. The new cropped image will be sent to the next MMask2former for prediction.

3. Experiments and conclusion

Data Set We analyze Panoramic radiographs from 466 patients who received orthodontics service from Angelalign. The data set is randomly separated into three data sets for train-

ing, validation, and testing with a ratio of 7:1:2. All patients' Panoramic radiographs are manually annotated with five classes including Alveolarcrest, Condyle, Neuraltube, Sinusmaxillaris, and Teeth (each tooth is independent).

Semantic segmentation We compare CMMask2former with state-of-the-art models on our dataset in Table 1. The comparation models include Unet++(Zhou et al., 2020), MedT(Valanarasu et al., 2021), UCTransNet(Wang et al., 2022) and Mask2former(Cheng et al., 2022). Moreover, we also show the result of our method without Multi-scale masked attention(MMA) or Cascaded structure(CS) over CMMask2former. It also demonstrates the effectiveness of our modules.

Table 1: Semantic segmentation on our data set with four classes

Model	$IoU_{Alveolarcrest}$	$IoU_{Condyle}$	$IoU_{Neuraltube}$	$IoU_{Sinusmaxillaris}$	$mIoU$
Unet++	72.731	29.732	17.036	48.754	42.063
MedT	88.089	72.885	35.316	79.493	68.946
UCTransNet	91.472	83.236	59.666	85.601	79.994
Mask2former	92.566	89.276	62.457	87.575	82.968
Ours(w/o CS)	92.840	88.071	64.863	88.021	83.449
Ours(w/o MMA)	92.902	89.413	66.144	88.047	84.127
Ours	92.654	89.902	67.537	87.589	84.421

Instance segmentation We compare CMMask2former with Mask R-CNN(He et al., 2018) on our data set in Table 2. For this part, we do not import our modules, hence, the results of Mask2former and our model are close.

Table 2: Instance segmentation on our data set with teeth class

Model	AP_{Teeth}
Mask R-CNN	52.034
Mask2former	74.345
Ours	74.381

Conclusion In conclusion, this paper provides a first insight into the segmentation task of five oral structures on Panoramic radiographs. We propose a Cascaded Multi-scale Mask2former(CMMask2former) method for this segmentation task. Experimental results on our data set demonstrate the effectiveness of our modules.

References

Bowen Cheng, Ishan Misra, Alexander G. Schwing, Alexander Kirillov, and Rohit Girdhar. Masked-attention mask transformer for universal image segmentation, 2022.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn, 2018.

Thorbjørn Louring Koch, Mathias Perslev, Christian Igel, and Sami Sebastian Brandt. Accurate segmentation of dental panoramic radiographs with u-nets. In *2019 IEEE 16th International Symposium on Biomedical Imaging (ISBI 2019)*, pages 15–19, 2019.

Jeong-Hee Lee, Sang-Sun Han, Young Hyun Kim, Chena Lee, and Inhyeok Kim. Application of a fully deep convolutional neural network to the automation of tooth segmentation on panoramic radiographs. *Oral Surgery, Oral Medicine, Oral Pathology and Oral Radiology*, 129(6):635–642, 2020.

Jeya Maria Jose Valanarasu, Poojan Oza, Ilker Hacihaliloglu, and Vishal M. Patel. Medical transformer: Gated axial-attention for medical image segmentation, 2021.

Haonan Wang, Peng Cao, Jiaqi Wang, and Osmar R. Zaiane. Uctransnet: Rethinking the skip connections in u-net from a channel-wise perspective with transformer, 2022.

Chia-Hsiang Wu, Wan-Hua Tsai, Ying-Hui Chen, Jia-Kuang Liu, and Yung-Nien Sun. Model-based orthodontic assessments for dental panoramic radiographs. *IEEE Journal of Biomedical and Health Informatics*, 22(2):545–551, March 2018.

Scott W. Yates. Physician stress and burnout. *The American Journal of Medicine*, 133(2): 160–164, 2020.

Zongwei Zhou, Md Mahfuzur Rahman Siddiquee, Nima Tajbakhsh, and Jianming Liang. Unet++: Redesigning skip connections to exploit multiscale features in image segmentation, 2020.