Meta-Learning for Fast Model Recommendation in Unsupervised Multivariate Time Series Anomaly Detection

Anonymous[1]

[1]Anonymous Institution

Abstract Unsupervised model recommendation for anomaly detection is a recent discipline for which there is no existing work that focuses on multivariate time series data. This paper studies that problem under real-world restrictions, most notably: (i) a limited time to issue a recommendation, which renders existing methods based around the testing of a large pool of models unusable; (ii) the need for generalization to previously unseen data sources, which is seldom factored in the experimental evaluation. We turn to meta-learning and propose Hydra, the first meta-recommender for anomaly detection in literature that we especially analyze in the context of multivariate times series. We conduct our experiments using 94 public datasets from 4 different data sources. Our ablation study testifies that our meta-recommender achieves a higher performance than the current state of the art, including in difficult scenarios in which data similarity is minimal: our proposal is able to recommend a model in the top 10% (13%) of the algorithmic pool for known (unseen) sources of data.

1 Introduction

Unsurprisingly, there is no single anomaly detection algorithm that is optimal for every realistic situation. Thus, the task of automatic model selection (i.e., correctly choosing which algorithm and hyper-parameters to use, jointly known as a *configuration* or a *model*) is crucial when working on new data. In a supervised learning setting, in which there is available ground truth, this problem has been extensively studied (see He et al. [2021], Karmaker et al. [2021] and references therein). However, model selection becomes especially difficult in an unsupervised setting, given the lack of an objective method for comparing and ranking different algorithmic configurations.

This paper investigates meta-learners for automating anomaly detection on multivariate time series. We consider constraints of a practical scenario, in which model recommendation needs to be as fast as possible and the recommender might work with new datasets from known sources (e.g., sources it has been fed at training time) or with previously unseen and radically different sources (so that generalization ability is particularly important). In particular, we design Hydra, a two-headed meta-recommender, that attains performance superior to the state of the art not only for known sources, but especially for radically different sources: our ablation study shows that (i) a meta-recommender is needed to disambiguate the cases of known/unknown data sources, (ii) a hierarchical organization of the recommenders through clustering improves performance for the known sources case and (iii) the use of well-known time series features (i.e., catch22 Lubba et al. [2019]) is both faster and more accurate than current ad hoc features.

We evaluate our contributions with the largest set of real data ever tested on this discipline to date, combining four different public data sources. On this benchmark, Hydra selects models in the top 10% of all tested configurations for known data, and is able to internally adapt to novel data sources with limited performance loss (top 13%) . We open source the software library we developed[1] to carry out our experiments, including pre-computed performance and meta-feature matrices as well as our recommenders, with the objective of easing reproducibility and fostering research in the area.

---

[1]https://figshare.com/s/f0bf74405fb4462de65b

Submitted to AutoML 2023

Table 1: Comparison of meta-learning methods in literature.

Work	Method	Data used	Code
MetaOD	Performance estimation from meta-features	Synthetic groups, independent, non temporal	✓
ELECT	Nearest Neighbor in performance space	Synthetic groups, independent, non temporal	
LOTUS	Nearest Neighbor in Gromov-Wasserstein space	Independent, non temporal	
Ours	Adaptive performance estimation from meta-features	Real grouped, multivariate, temporal	✓

2 State of the Art

Meta-learning is a family of methods based on the mapping between algorithmic performance and any information that can be extracted in an unsupervised fashion from datasets, called meta-features, which allows it to be applied on a new dataset (Vanschoren [2018]). These require a large computational effort beforehand in order to train the model recommender but tend to have a small computational footprint in application and are thus fit for our settings. While meta-learning works are varied for areas as supervised learning (Dyrmishi et al. [2019]) and neural networks (Hospedales et al. [2021]), the problem has only recently started being tackled for unsupervised anomaly detection, as summarized in Table 1.

MetaOD by Zhao et al. [2021] is the first meta-learning scheme in literature directly tailored to unsupervised outlier detection. It is based on collaborative filtering: C configurations are tested over N different datasets, and a matrix factorization process approximates the performance of all configurations based on a projected matrix of meta-features extracted from the datasets. A multivariate random forest regressor is trained to transform the original projected meta-features matrix into the optimized one. Given a new dataset, X_{new}, its meta-features are extracted, projected and transformed by the random forest regressor, which allows it to be multiplied by the other matrix factorization component, yielding a performance prediction for every configuration. With respect to MetaOD, Hydra (i) includes a meta-recommender to explicitly account for the novelty of X_{new} (see Section 3.3.1), (ii) differs in the design of the mapping methods (iterative factorization versus singular value decomposition), including the optimization of the normalized discounted cumulative gain versus the mean root squared error, which allows us to perform more complex recommendations (Section 3.3.3), and finally (iii) on the addition and use of time-series specific meta-features (Section 3.4).

A second branch of approaches includes ELECT (Zhao et al. [2022]) and LOTUS (Singh and Vanschoren [2022]). The former is based on establishing distances in the performance space and finding the closest neighbors to X_{new}. As new datasets are unlabelled, ELECT estimates performance with a subset of the unsupervised metrics compiled by Ma et al. [2021]. LOTUS searches for nearest neighbors according to the Gromov-Wasserstein distance, for which they propose a low rank approximation. Additionally, as direct comparison is not possible since code for ELECT and LOTUS is not available, we implement a nearest neighbor baseline as a proxy of ELECT/LOTUS, that we include in our experimental study.

3 Unsupervised Model Recommendation through Meta-Learning

This section expands the basic details of model recommendation through meta-learning and outlines our novel proposals. Every recommender we present will follow the same scheme, divided in an offline training phase, in which the mapper between unsupervised dataset meta-features is trained, and an online application phase, in which a new dataset is issued an appropriate model recommendation.

3.1 Offline Training

Starting from (i) an available collection of datasets $D = \{X_1, X_2, ..., X_n\}$ for which ground truth labels about anomalies are available and (ii) a collection of algorithmic configurations C, this collection is applied and evaluated over D using a suitable metric. This yields P, a performance matrix of dimensions $n \times |C|$. In parallel, a set of meta-features, M is extracted for all X_i in D, a meta-feature being any numeric value that's extracted from a whole dataset. While a comprehensive set of meta-features is presented by Vanschoren [2018], the first set custom tailored to unsupervised outlier detection was presented in Zhao et al. [2021], which we will call M_{MetaOD}. The only task left in this phase is to build an estimator, f, to predict the values in P based on M, defined as $\hat{P}$:

$$\hat{P} = f(M). \tag{1}$$

3.2 Online Application

Once a new dataset X_{new} is received, for which no ground truth labels are available, this phase's objective is to issue a configuration recommendation. Extracting the same meta-feature set as employed in the offline training, a meta-feature vector M_{new} is obtained, through which a performance estimation $\hat{P}_{\text{new}} \in \mathbb{R}^{1 \times |C|}$ is obtained as $f(M_{\text{new}})$. As this vector contains the performance estimation of all the configurations in C, issuing a model recommendation entails only the selection of the one with maximum estimated performance:

$$c_{opt} = \arg\max \hat{P}_{\text{new}}. \tag{2}$$

3.3 Hydra design

Our proposed meta-recommender, Hydra, is composed of three components: a novelty detection mechanism and two model recommenders, specialized to each of the two possible situations (novel / known data). Thus, during fitting, Hydra's novelty lies in its model recommenders, whereas during recommendation, its innovative component is its ability to dynamically select which model recommender to use. We describe each step in detail in the following subsections.

3.3.1 Meta-recommendation based on data novelty.
An important component of deploying a model recommender in real-world scenarios setting is its ability to not only perform well with datasets similar to the ones seen during fitting, but especially its ability to also perform well with novel and radically dissimilar datasets. Recognizing this need, a novel contribution in Hydra is to propose a mechanism for novelty detection, wich is used to create a meta-recommender that detects whether datasets are novel or not, and then can dispatch different recommenders to be applied in each case. The process is simple: during application, new data points are projected using Uniform Manifold Approximation and Projection (UMAP)McInnes et al. [2018] in the meta-feature space and clustered alongside the previous datasets in M. The decision of what recommender to used can be taken based on whether the new points belong to clusters with points seen during fitting or not using any off-the-shelf clustering algorithm, like DBSCAN. This usage of the meta-feature space is similar to the one presented by Kadioglu et al. [2010], but we use it to perform meta-recommendation instead of default recommendation.

3.3.2 Recommender for novel data: U Regression (UReg).
In case data radically differs from the one seen at training, Hydra next uses Singular Value Decomposition ($P \approx UDV$) and trains a multi-regressor Random Forest to predict U from M, $\hat{U}(M)$:

$$\hat{P} = f_{\text{UReg}}(M) := \hat{U}(M)DV. \tag{3}$$

Internally, the Random Forest is optimizing the mean squared error of the solution, so the estimations obtained by f_{URegr} can guide the end user in understanding not only which model is

recommended but also its expected performance. As the number of singular vectors calculated in the SVD is a user defined parameter, this method complexity can be tuned by reducing or increasing the number of Random Forests to train. Additionally, it can be expected that for novel data the a highly summarized description (i.e., a low number of components) can be enough to guide model recommendation.

3.3.3 Recommender for known data: Clustered Factorization (CFact).

In case data is similar to the one seen during training, Hydra uses a more refined recommender. Given the inherent variety in the potential input datasets we could find, it's reasonable to assume that existing patterns between the meta-features and performance matrices can vary across the meta-feature space. Otherwise stated, we expect that datasets that fall in close region of the meta-feature can provide a better input for recommendation than farway datasets. To address this assumption, *CFact* performs a UMAP projection of M and a subsequent clustering of the datasets in the projected space. A *UReg* recommender is fit for each cluster, corresponding to subsets of rows of P, obtaining a set of recommenders, $R = \{r_1, r_2, ..., r_{cl}\}$, where cl is equal to the number of determined clusters. As the output of each recommender can be expressed as a configuration and its predicted performance pair (c_i, p_i), when a new dataset is received *CFact* will produce n tuples of the aforementioned form, with the recommended option being the one that maximizes p_i.

3.4 Time-series Meta-features (catch22)

Finally, we observe that current work Zhao et al. [2021, 2022], Singh and Vanschoren [2022] employs generic meta-features for dataset summarization. For instance, M_{MetaOD} uses a set of 200 features, some of which requires the application of four anomaly detection methods already (HBOS, Isolation Forest, LODA and PCA) and are as such computationally intensive; additionally, such meta-features do not properly account for the temporal dimension of the data. We therefore set to investigate if, for time-series meta-recommendation, meta-features that are naturally used in the time-series domain provide a competitive advantage: we turn to *Catch22*, a set of 22 univariate time series meta-features that have been selected out of a set of over 4000 for their effectiveness when used as features for Machine Learning tasks in time series. As *Catch22* is extracted from a single series, we define M_{Catch22} as the 110 meta-features created by summarizing each of the set of values for each meta-feature by its *{minimum, first quartile, average value, third quartile, maximum}*.

4 Methodology

Our objective in the rest of the paper is to compare the performance of anomaly detection model recommenders for time series data, that we collect from quite heterogeneous publicly available sources (Section. 4.1). On these datasets, we train model recommenders using a representative selection of anomaly detection algorithms, spanning over 500 individual algorithmic configurations (Section. 4.2). As for recommenders, we contrast Hydra to the current state of the art, and additionally include relevant methods as a baseline (Section. 4.3). In particular our evaluation aims at assessing the generalization abilities of the recommender to unseen data source, for which we devise two evaluation scenarios (Section. 4.4).

To address the above questions, we designed a software framework that we open source to simplify reproducibility of this paper. For convenience, the software package includes pre-computed M and P matrices and every recommender analyzed in this paper.

4.1 Data

We used four public data sources of multivariate, numeric time series. They are (i) Server Machine Dataset (SMD), by Su et al. [2019], containing datasets of server metrics, like CPU, memory or network usage; (ii) BGP, by Putina et al. [2018], datasets representing devices deployed on a testbed on which BGP anomalies were manually injected and the features are related to the network

Table 2: Data sources summary. Number of row, columns and anomaly duration are expressed in median ± median absolute deviation.

Name	Ref.	Datasets	Rows	Columns	Anomaly Length (samples)
BGP	Putina et al. [2018]	39	1437 ± 31	214 ± 70	54 ± 1
Benchmark	Lai et al. [2021]	19	400 ± 0	5 ± 0	1 ± 0
SMD	Su et al. [2019]	28	47405 ± 37	31 ± 1	11 ± 11
Water	HAI	8	113401 ± 81393	58 ± 3	258 ± 159
Total		94	3264992	10262	92768

Figure 1: UMAP projection of the datasets in the $M_{Catch22}$ space. Benchmark and SMD are the only data sources with apparent overlap in the formed clusters. Large intra-cluster similarity and inter-cluster dissimilarity are expected when performing model recommendation in an industrial application.

control and data planes; (iii) Benchmark, by Lai et al. [2021], a collection of synthetic and realistic datasets for Time Series Outlier Detection; and (iv) Water, HAI; a collection of sensor features from a water-treatment plant devices. Table 2 presents a summary of the number of datasets per source, their size in rows and columns as well as the duration of the anomalies on each of them. To further detail their variety, Fig. 1 displays the 2D UMAP projection of the datasets in the meta-feature space, showing that there is barely no overlap in similarity between sources and that datasets within sources are similar between each other, which is the scenario we expect in practice and that makes generalization abilities especially important.

4.2 Anomaly detection algorithms in P

Regarding anomaly detection algorithms, we aimed for completeness in terms of different algorithmic families. Additionally, in order to capture the potential time series specific anomalies we previously mentioned, we created P with a combination of six among *batch* and *streaming* anomaly detection algorithms: (i) the batch case, we employed Local Outlier Factor (Breunig et al. [2000]), Isolation Forest (Liu et al. [2008]), Random Histogram Forest (Putina et al. [2020]) and LODA (Pevný [2016]), (ii) whereas for streaming algorithms, we opted for Half-Space Trees (Tan et al. [2011]) and xStream (Manzoor et al. [2018]). As for their hyper-parameters, we tested a total of 507 combinations, to ensure a good coverage of their performance space[2].

Each algorithm's output is evaluated using the Area Under the Precision Recall Curve (PRAUC), a common metric for anomaly detection. Then, each PRAUC value was transformed into a value in a 1-100 scale, as the percentile it represents in the possible performance distribution, to ensure all values are comparable across datasets.

4.3 Recommenders

In terms of recommenders, we consider **Hydra** (as well as serveral variations in the ablation study where we also consider each individual building block, such as **URegr** and **CFact**) and contrast it to the current state of the art represented by **MetaOD** Zhao et al. [2021]. We consider several

---

[2]Detailed further on supplemental material.

Table 3: Hyper-parameter set used to test the recommenders in the experiments.

Recommender	Hyperparameters	Recommender	Hyperparameters
Hydra	SVD factors: UReg = 2, CFact = 5
UMAP components = 10
DBSCAN ϵ = 1	MetaOD	{PCA factors, iterations} = 40, 10
{Min, max} learning rate = 1.05, 0.1
Learning rate steps = 10
kNN	Neighbors k = 1	Regression	Number of trees = 500

additional baselines: **Global Best**, which selects the configuration with best median performance in the training data; **Nearest Neighbor (kNN)** Nikolić et al. [2013], which recommends the model that worked best in the dataset most similar in the meta-feature space to X_{new} and a **Regression** method which builds Random Forest regression models between P and M directlyXu et al. [2012]. The parameters used for their comparison are summarized in Table 3.

4.4 Experiments

We define two scenarios in terms of the data splitting strategy employed. In *Scenario I*, we perform Stratified Repeated 10-folds Cross Validation with 3 repetitions, ensuring that datasets from every source are present on each fold: this scenario is the one typically considered in the literature, where therefore as per Figure.1 we can expect recommenders to be able to readily leverage information from previous datasets, and that constitutes an optimistic scenario in which the recommender has been trained to also include data from the source where it is applied to.

Additionally, we consider a *Scenario II*, in which we split the data in a Leave One Source Out fashion, creating 4 folds, ensuring in each of them that each data source is *not* present. For each experiment, we fit every recommender with the training data in a single fold and predict the anomaly detection model for corresponding test data of the left-out source. In this case, models have been exposed to a variety of training data, which can be expected however to be quite different from the data where the recommender is applied to, and corresponds to a stress test of the generalization capabilities.

We repeat each experiment five times with different random seeds, so that presented results aggregated these different repetitions, treating them as different studies in a meta-analysis as per Lipsey and Wilson [2001]. For all reported metrics of interest, we measure their effect size by pooling over the repetitions, estimating its average and its 95% confidence interval (CI).

5 Results

We preliminary restrain the set of meta-features (Section 5.1), based on which we report an exhaustive comparison of the recommender performance (Section 5.2). We conclude with an ablation study of our proposal (Section 5.3) and some consideration on computational requirements (Section 5.4).

5.1 Preliminary selection of meta-feature sets

To compare the two meta-feature sets we measure, for each recommender, the proportions of cases in which the better performance are obtained using M_{MetaOD} or M_{C22}. To be conservative, we consider that recommender performance are different only whenever for a dataset d in a scenario s and recommender r, the performance difference between the two meta-features set exceeds $|p_{\text{MetaOD}} - p_{\text{C22}}| > \sigma_{d,s,r}^+$, where $\sigma_{d,s,r}^+$ is the maximum of the standard deviation of the performance obtained across seeds for $\{d, s, r\}$ for M_{MetaOD} and M_{C22}. With this conservative definition, we capture only macroscopic differences and account for the potential variability in recommender behavior across seeds and dataset difficulty.

Meta-features	Recommender			
	Hydra	MetaOD	kNN	Regression
Equal	72 ± 2	58 ± 3	43 ± 2.5	69 ± 2.5
$M_{Catch22}$	16 ± 2	17 ± 2	31 ± 2.5	18 ± 2
M_{MetaOD}	12 ± 2	15 ± 2	25 ± 2.5	14 ± 2

Figure 2: Percentage of tests in which the performance of methods selected by each recommender is equal, better for M_{MetaOD} or $M_{Catch22}$. Estimates and 95% confidence interval across five different random seeds.

Results are reported on Fig. 2. Briefly, we gather that for all recommenders, performance are similar for the majority of the cases with either M_{C22} and M_{MetaOD} meta-feature sets. Additionally, it appears that M_{C22} is slightly better than M_{MetaOD}, except for the MetaOD recommender itself. Finally, we observe that M_{C22} features are almost 4× faster to compute with respect to than M_{MetaOD}. In what follows, we limited report results using M_{C22} and point out that qualitative considerations reported hereafter also holds when using M_{MetaOD} (detailed results in the supplementary material).

5.2 Comparison of Recommender Performance

We consider all recommenders at a glance, on both mild (I) and hard (II) generalization scenarios. Considering the stratified cross validation scenario (I) first, we observe that most approaches appear to have close performance: notice that Hydra recommends on average a model close to the top-10% (89.8). Also, while the differences are statistically significant, we observe that Hydra is only marginally improving over a simple regression (88.7) or global best (84.5) baselines, or over the Meta-OD state of the art (83.7). This confirms previous findings in Zhao et al. [2021] that were indeed showing a naïve solution to provide satisfactory results and under mild generalization settings there would be no obvious reasons to suggest for more complex recommender than simple baselines.

At the same time, a completely different picture emerges from the hard generalization scenario (II): in particular, we see in this case that Global best (64.3) and kNN (52.5) approaches, along with state of the art MetaOD (59.7), incur a dramatic performance drop. In this case, simply recommending what worked best in the datasets observed at training time is not useful for the novel data. While direct regression (75.0) is in this case able to interpolate a better recommmendation (at the cost of building one random forest per each of the 507 algorithmic configurations), it is still far lower than Hydra (86.9), whose performance is only minimally affected and thus is able to meet its generalization goal with a top-13% recommendation also in harder settings. We now dissect the fundamental reasons of this performance difference.

Figure 3: *Recommender comparison*: Average performance percentile obtained by each recommender across five random seeds, expressed as average estimate and 95% confidence intervals.

Figure 4: *Ablation study*: UReg performance as a function of the number of SVD factors for Scenario I (stratified cross validation) and II (leave-one-source-out cross validation). Average and 95%CI performance using 5 different random seeds.

5.3 Ablation study

5.3.1 Novel vs known data. Among the fundamental reasons of the early observed performance difference is the novelty of the data: i.e., recommender strategies that work well with when the recommender is exposed to a sample of the data where it is expected to actuate, no longer apply when the actuation scenario changes drastically. We illustrate this by showing a sensitivity analysis of a building block of Hydra: specifically, URegression internally uses a Singular Value Decomposition of P, where the number of SVD factors is a free hyper-parameter.

Intuitively, for a sufficiently high number of factors, URegression would be equivalent to the Regression recommender we utilize for baseline: hence, as early observed for the Regression recommender, we expect that for growing number of SVD factors the performance of UReg should diverge in the Scenario I and Scenario II. In particular, in the stratified cross validation, scenario I, we expect performance (and computation time) to increase with the number of SVD factors, while the same does not necessarily hold for the leave-one-source-out scenario II.

Figure 4 shows the average percentile of UReg for varying number of SVD factors, with 95% CI computed across five random seeds. In practice, (i) we observe a sharp difference between the use of 2 SVD factors and a relatively flat behavior otherwise; (ii) as expected, performance in the stratified validation case improve for growing number of SVD factors; (iii) also, we gather that a larger number of factors than 2 is counter-productive for leave-one-source-out scenario II; (iv) finally, it is worth stressing that UReg with 2 SVD factors seems to capture some fundamental dataset properties, with recommendations that are structurally different, and significantly better with respect to those of a global baseline.

This suggests the existence of some broad scoped global trends that is applicable across sources and is well captured by few SVD factors, whereas more specific patterns captured by higher dimensionality SVD vectors are not exportable: while this seems a reasonable explanation, further analysis on a broader set of data sources is needed to confirm the generality of the phenomenon to an even broader set of sources than those considered here.

5.3.2 Performance of individual building blocks. As the main idea in Hydra is, based on the meta-feature projection, to select a recommender that is better suited to handle novel (UReg) or known (CFact) data, we finally contrast Hydra with simpler alternatives where only some of its individual building blocks are used. We fit the internal recommenders to the same scenarios as Hydra and tabulate their average performance percentile with 95% CI and report a rank test for the individual building blocks versus Hydra in Figure 5. The picture confirms that, as expected (i) the CFact recommender is the best choice for Scenario I, where CFact clustering allows for a finer-tuned performance prediction in known data, (ii) the UReg recommender with 2 factors (UReg(2)) is the best choice for Scenario II as it captures global patterns that are applicable across unseen sources and (iii) Hydra is able to seamlessly meta-recommend the correct one among CFact/UReg(2) based on its novelty estimation capability. Overall, all building blocks are therefore necessary to get accurate recommendations in cases where training and test data are similar, as well as robust recommendations that are able to go beyond recommending a simple default configuration when dealing with radically different data.

Figure 5: *Ablation study*: Average rank comparison and average performance percentile obtained by Hydra and its individual building blocks, with 95% confidence interval. CD equals the critical distance in average ranking at which recommenders can be considered significantly different.

5.4 Computational requirements

Whereas due to lack of space it is out of the scope of this paper to present a fully fledged comparison of computational costs, we wish to remark here that Hydra's requirements are fairly lightweight. On one core of an Intel Xeon E5-4627 CPU, the cost for meta-feature summarization per column is 25 ms for M_{C22} (90 for M_{MetaOD}) on a 150 row dataset. UReg fitting costs are in the range of 100ms (500ms) for 2 (20) SVD factors, and UReg recommendation costs 25ms (200ms) for 2 (20) factors. The dominant cost in Hydra is represented by the UMAP projection and clustering of the points when a new dataset is received, which takes about 5 seconds in our experiments. We remark, though, that Hydra's fitting / recommendation times are lower than / equal to the second recommender in terms of performance, the Regression baseline. Overall, the largest cost during training is the one-time cost incurred by evaluating the 507 combinations of algorithms across all datasets, which take several hours in our setup. In reason of its extreme lightweight and parsimonious computation requirement, we believe that Hydra has a limited negative effect to, e.g., societal impacts such as global warming.

6 Conclusion

This paper tackles the problem of automatic model recommendation for anomaly detection in a realistic setting applied to multivariate time series. We introduce Hydra, (i) a meta-recommender able to seamlessly combine two new base recommenders, (ii) UReg and (iii) CFact –that leverage respectively a Singular Value Decomposition of the performance matrix and a clustering of it– and that are designed to respectively provide (ii) general recommendation for novel data, as well as (iii) more accurate recommendation for known data. Results of a reproducible campaign show that Hydra is able to recommend model configurations close to the top 10% of available models both in mild and hard generalization scenarios.

At the same time, many interesting research questions remain open. First, while Hydra provides better generalization capabilities than the state of the art, a broader study on a much larger set of (unfortunately not publicly available) datasets would be necessary. Second, while we have shown that time series meta-features (e.g. Catch22) is a valid substitute for custom meta-features set tailored for outlier detection, the meta-feature design space is far from being fully explored. Finally, while Hydra is limited to model recommendation, a natural extension would be to combine model outputs, as done in supervised learning area Tornede et al. [2022]. Regarding Hydra societal impacts, we have determined that this work presents no notable negative impacts to society, and even less to the environment, thanks to its low computational footprint.

References

HAI 1.0: HIL-based Augmented ICS Security Dataset | USENIX. URL https://www.usenix.org/conference/cset20/presentation/shin.

Markus M Breunig, Hans-Peter Kriegel, Raymond T Ng, and Jörg Sander. Lof: identifying density-based local outliers. In *Proceedings of the 2000 ACM SIGMOD international conference on Management of data*, pages 93–104, 2000.

Salijona Dyrmishi, Radwa Elshawi, and Sherif Sakr. A decision support framework for automl systems: A meta-learning approach. In *2019 International Conference on Data Mining Workshops (ICDMW)*, pages 97–106. IEEE, 2019.

Xin He, Kaiyong Zhao, and Xiaowen Chu. Automl: A survey of the state-of-the-art. *Knowledge-Based Systems*, 212:106622, 2021.

Timothy Hospedales, Antreas Antoniou, Paul Micaelli, and Amos Storkey. Meta-learning in neural networks: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 44(9): 5149–5169, 2021.

Serdar Kadioglu, Yuri Malitsky, Meinolf Sellmann, and Kevin Tierney. Isac–instance-specific algorithm configuration. In *ECAI 2010*, pages 751–756. IOS Press, 2010.

Shubhra Kanti Karmaker, Md Mahadi Hassan, Micah J Smith, Lei Xu, Chengxiang Zhai, and Kalyan Veeramachaneni. Automl to date and beyond: Challenges and opportunities. *ACM Computing Surveys (CSUR)*, 54(8):1–36, 2021.

Kwei-Herng Lai, Daochen Zha, Junjie Xu, Yue Zhao, Guanchu Wang, and Xia Hu. Revisiting Time Series Outlier Detection: Definitions and Benchmarks. June 2021. URL `https://openreview.net/forum?id=r8IvOsnHchr`.

Mark W Lipsey and David B Wilson. *Practical meta-analysis.* SAGE publications, Inc, 2001.

Fei Tony Liu, Kai Ming Ting, and Zhi-Hua Zhou. Isolation forest. In *2008 eighth ieee international conference on data mining*, pages 413–422. IEEE, 2008.

Carl H Lubba, Sarab S Sethi, Philip Knaute, Simon R Schultz, Ben D Fulcher, and Nick S Jones. catch22: Canonical time-series characteristics: Selected through highly comparative time-series analysis. *Data Mining and Knowledge Discovery*, 33(6):1821–1852, 2019.

Martin Q. Ma, Yue Zhao, Xiaorong Zhang, and Leman Akoglu. A Large-scale Study on Unsupervised Outlier Model Selection: Do Internal Strategies Suffice? *arxiv*, 2021. URL `https://arxiv.org/abs/2104.01422v2`.

Emaad Manzoor, Hemank Lamba, and Leman Akoglu. xstream: Outlier detection in feature-evolving data streams. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1963–1972, 2018.

Leland McInnes, John Healy, and James Melville. Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

Mladen Nikolić, Filip Marić, and Predrag Janičić. Simple algorithm portfolio for sat. *Artificial Intelligence Review*, 40(4):457–465, 2013.

Tomáš Pevnỳ. Loda: Lightweight on-line detector of anomalies. *Machine Learning*, 102:275–304, 2016.

Andrian Putina, Dario Rossi, Albert Bifet, Steven Barth, Drew Pletcher, Cristina Precup, and Patrice Nivaggioli. Telemetry-based stream-learning of BGP anomalies. In *Proceedings of the 2018 Workshop on Big Data Analytics and Machine Learning for Data Communication Networks*, Big-DAMA '18, pages 15–20, New York, NY, USA, August 2018. Association for Computing Machinery. ISBN 978-1-4503-5904-7. doi: 10.1145/3229607.3229611. URL `https://doi.org/10.1145/3229607.3229611`.

Andrian Putina, Mauro Sozio, Dario Rossi, and José Manuel Navarro. Random histogram forest for unsupervised anomaly detection. In *2020 IEEE International Conference on Data Mining (ICDM)*, pages 1226–1231. IEEE, 2020.

Prabhant Singh and Joaquin Vanschoren. Meta-Learning for Unsupervised Outlier Detection with Optimal Transport, November 2022. URL `http://arxiv.org/abs/2211.00372`. arXiv:2211.00372 [cs].

Ya Su, Youjian Zhao, Chenhao Niu, Rong Liu, Wei Sun, and Dan Pei. Robust Anomaly Detection for Multivariate Time Series through Stochastic Recurrent Neural Network. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '19, pages 2828–2837, New York, NY, USA, July 2019. Association for Computing Machinery. ISBN 978-1-4503-6201-6. doi: 10.1145/3292500.3330672. URL `https://doi.org/10.1145/3292500.3330672`.

Swee Chuan Tan, Kai Ming Ting, and Tony Fei Liu. Fast anomaly detection for streaming data. In *Twenty-second international joint conference on artificial intelligence*. Citeseer, 2011.

Alexander Tornede, Lukas Gehring, Tanja Tornede, Marcel Wever, and Eyke Hüllermeier. Algorithm selection on a meta level. *Machine Learning*, pages 1–34, 2022.

Joaquin Vanschoren. Meta-Learning: A Survey. *arXiv*, October 2018. URL `http://arxiv.org/abs/1810.03548`. arXiv: 1810.03548.

Lin Xu, Frank Hutter, Jonathan Shen, Holger H Hoos, and Kevin Leyton-Brown. SATzilla2012: Improved Algorithm Selection Based on Cost-sensitive Classification Models. *SAT*, page 2, 2012.

Yue Zhao, Ryan A Rossi, and Leman Akoglu. Automatic Unsupervised Outlier Model Selection. *NeurIPS*, page 14, 2021.

Yue Zhao, Sean Zhang, and Leman Akoglu. Toward Unsupervised Outlier Model Selection. *ICDM2022*, page 10, 2022.