# Adversarial Attack on Attackers: Post-Process to Mitigate Black-Box Score-Based Query Attacks

## Abstract

The score-based query attacks (SQAs) pose practical threats to deep neural networks by crafting adversarial perturbations within dozens of queries, only using the model's output scores. Nonetheless, we note that if the loss trend of the outputs is slightly perturbed, SQAs could be easily misled and thereby become much less effective. Following this idea, we propose a novel defense, namely Adversarial Attack on Attackers (AAA), to confound SQAs towards incorrect attack directions by slightly modifying the output logits. In this way, (1) SQAs are prevented regardless of the model's worst-case robustness; (2) the original model predictions are hardly changed, *i.e.*, no degradation on clean accuracy; (3) the calibration of confidence scores can be improved simultaneously. Extensive experiments are provided to verify the above advantages. For example, by setting $\ell_\infty = 8/255$ on CIFAR-10, our proposed AAA helps WideResNet-28 secure $80.59\%$ accuracy under Square attack (2500 queries), while the best prior defense (*i.e.*, adversarial training) only attains $67.44\%$. Since AAA attacks SQA's general greedy strategy, such advantages of AAA over 8 defenses can be consistently observed on 8 CIFAR-10/ImageNet models under 6 SQAs, using different attack targets and bounds. Moreover, AAA calibrates better without hurting the accuracy. Our code would be released.

## 1 Introduction

Deep Neural Networks (DNNs) are vulnerable to adversarial examples (AEs), where human-imperceptible perturbations added to clean samples can fool DNNs to give wrong predictions [1, 2]. Recently, such a threat is made practically feasible by the black-box score-based query attacks (SQAs) [3, 4, 5], as they only require the same information as users to craft efficient AEs. Users, for better judgments, need the model's prediction confidence indicated by DNNs' output scores, which is the only knowledge needed by SQAs to perform attacks. In contrast, white-box attacks [6, 7, 8] or transfer-based attacks [9, 10] require the gradients or training data of DNNs. Moreover, it has been shown that SQAs can achieve a non-trivial attack success rate by a reasonable number of queries, *e.g.*, dozens, compared to thousands of queries for decision-based query attacks [11, 12, 13]. Thus, such feasibility and effectiveness of SQAs are attracting increasing attention from defenders [14].

Defending against SQAs is a different goal compared to improving the *worst-case* robustness as commonly studied [15, 16, 17]. Because in *real-world scenarios* which SQAs are designed for, DNNs are treated as black boxes, in which the only interaction between models and users/attackers is the model's output scores. Thus, altering the scores is all defenders could do here, either in direct or indirect ways. Most existing defenses indirectly change outputs by optimizing the model [8, 18, 19] or pre-processing the inputs [14, 20], which, however, severely affect models' normal performance for different reasons. Training a robust model, *e.g.*, by adversarial training [8, 21], diverts the model's attention to learning AEs, yielding the so-called accuracy-robustness trade-off [22]. Randomizing

Figure 1: Compared to existing defenses on inputs or models, AAA post-processes to avoid SQAs as in (a). Our main idea is to show attackers the incorrect attack direction as illustrated in (b). Specifically, if we perturb the original blue loss curve to the orange one, then attackers that trying to decrease the loss would be mostly cheated away from their true destiny, *i.e.*, the adversarial direction.

[14, 23, 24, 25, 26] and blurring [20, 27, 28, 29] inputs reduce the signal-noise ratio, inevitably hurdling accurate decision. Dynamic inference [19, 30] is time-consuming due to the test-time optimization on model. Thus, it is imperative to develop a user-friendly defense against SQAs. In this paper, we hereby consider a post-processing defense as demonstrated in Fig. 1 (a), which naturally enjoys the benefits as follows: (1) model's decision is hardly affected since good predictions have already been obtained; (2) model calibration can be simultaneously improved via post-processing [31, 32] to output accurate prediction confidence; (3) it can be flexibly used as a plug-in module for pre-trained models with negligible test-time computation overhead. Despite these merits, it remains unexplored that by post-processing,

*How to serve users while avoiding SQA attackers when they access the same output information?*

Since SQAs are black-box attacks that find the adversarial direction to update AEs by observing the loss change indicated by DNN's output scores, we can perturb such scores directly to fool attackers into incorrect attack tracks. Following this idea, we propose the adversarial attack on attackers (AAA), which reverses the loss trend so that attackers, trying to greedily update AEs following the original trend, are led to the non-adversarial path farther away from the decision boundary as shown in Fig. 1 (b). Specifically, AAA directly optimizes DNN's logits to control the output loss to approximate the reversed curve, which is orange in Fig. 1 (b), where one could see that attackers that are threatening to the undefended model (going adversarial by reducing loss) would be attacked to help the defended DNN predict (going non-adversarial by reducing loss). Now that a post-processing module is adopted here, we could simultaneously use it to calibrate the model as commonly proposed [31, 33]. Thus, a simple plug-in post-module is all you need to both fool attackers and offer users accurate confidence.

By post-processing, AAA not only lowers the calibration error without hurting accuracy in all cases, but also efficiently prevents SQAs, *e.g.*, helping a WideResNet-28 [34] on CIFAR-10 [35] secure $80.59\%$ accuracy under Square attack [5] (2500 queries), while the best prior defense (*i.e.*, adversarial training [36]) only attains $67.44\%$. Because AAA attacks the general greedy update of SQAs, such advantages of AAA over 8 baseline defenses can be consistently observed on 8 CIFAR-10/ImageNet models under 6 SQAs, using different attack targets, norms, bounds, and losses, verifying AAA a user-friendly, effective, and generalizable defense.

**Contributions**

- We analyze current defenses from the view of SQA defenders and point out that a post-processing module forms not only effective but also user-friendly and plug-in defenses.
- We design a novel adversarial attack on attackers (AAA) defense that fools SQA attackers to incorrect attack directions by slightly perturbing the DNN output scores.
- We conduct comprehensive experiments showing that AAA outperforms the other 8 defenses in the accuracy, calibration, and protection from all tested 6 SQAs under various settings.

## 2   Related work

**Query attacks**   are black-box attacks that only require the model's output information. Query attacks can be divided into score-based query attacks (SQAs) [3, 4, 5, 37, 38, 39, 40] and decision-based query attacks (DQAs) [11, 12, 13, 41]. SQAs greedily update AEs from original samples by

observing the loss change indicated by DNN's output scores, *i.e.*, logits or probabilities. Early SQAs try to estimate DNN's gradients by additional queries around the sample [38, 42]. Recently, it is validated query-efficient to perform fast pure random-search SQAs [4, 5]. It has also been proposed to use pre-trained surrogate models in SQAs [39, 43], which, however, demands unfeasible access to DNN's training sample as in transfer-based attacks [9, 10]. Thus, we do not focus on defending such SQAs as also in [14]. Besides SQAs, DQAs rely only on DNN's decisions, *e.g.*, the top-1 predictions, to generate AEs. Since DQAs could not perform the greedy update, they start crafting the AE from a different sample and keep DNN's prediction wrong during the attack. Currently, DQAs need thousands of queries to reach a non-trivial attack success rate [44] compared to dozens of times for SQAs [5] as compared in Appendix A, limiting their threats. Additionally, SQAs are mostly applicable and attackers do not have to resort to DQAs because, in the real world, DNNs must not only be accurate but also indicate when they tend to be incorrect [31] by outputting confidence scores.

**Adversarial defense**    mainly has two different goals. The first goal is to improve DNN's worst-case robustness [17], which demands DNNs to have no AE around clean samples bounded by a norm ball. Such robustness is originally evaluated by gradient-based white-box attacks [6, 7], but later, gradient obfuscation phenomenon is discovered [15], motivating evaluations to incorporate random noise and black-box attacks [16] in adaptive methods [16, 45, 46]. In this assessment, adversarial training (AT) [8, 21] is validated as the most effective defense, and other methods, *e.g.*, using more or augmented data [47, 48], designing special architecture [18, 49, 50], and inducing randomness in training [51, 52], all need collaborations with AT to achieve good performance. Another defense goal is to mitigate real-case adversarial threats, and the defense performance is evaluated by the feasible and query-efficient SQAs. A more robust model in the worst cases certainly protects itself in real cases. Besides, it is also possible to defend by dynamic inference [19, 30], and randomizing [14, 23, 24, 25], denoising [20, 27] or quantifying [28, 29] inputs. However, all aforementioned defenses on inputs or models exert a non-negligible impact on accuracy, calibration, or inference speed due to the focus on learning AEs in AT, the reduction of signal-noise ratio in pre-processing, or the costly test-time optimization in dynamic inference as compared meticulously in Section 3.

**Model calibration**    performance is a higher demand for a good model besides high accuracy. Besides correct predictions, model calibration additionally requires DNNs to produce accurate confidence in their predictions [53]. For instance, exactly $80\%$ of the samples predicted with $80\%$ confidence should be correctly predicted. In this point of view, the expected calibration error (ECE) [32] is widely used to quantify the error between accuracy and confidence. Various methods have been proposed to improve DNN's calibration in training [33, 54, 55, 56] or by a post-processing module after training [31, 32, 57]. Among them, temperature scaling [32] is a simple but effective method [31], which divides all output logits by a single scalar tuned by a validation set so that the ECE in testing samples would be significantly reduced. Since division is a simple post-processing operation, calibration could be simultaneously achieved by AAA, the first post-processing defense. There have been methods to avoid attacks by calibration [56] or calibrate by attack [33], but the simultaneous improvement of defense and calibration has not been reported to the best of our knowledge.

# 3   Preliminaries and motivation

Before presenting the proposed method, we first introduce the key ideas of SQAs and analyze existing defenses. For a clean sample $\boldsymbol{x}$ labelled by $y$, an SQA on a DNN $f$ generates an AE $\boldsymbol{x}'$ by minimizing the margin between logits [4, 5, 40, 58] as

$$\mathcal{L}(f(\boldsymbol{x}), y) = f_y(\boldsymbol{x}) - \max_{k \neq y} f_k(\boldsymbol{x}), \tag{1}$$

namely the margin loss [7]. For defenders without the label $y$, it is possible to calculate the unsupervised margin loss based only on the logits vector $\boldsymbol{z} = f(\boldsymbol{x})$ as

$$\mathcal{L}_{\mathrm{u}}(\boldsymbol{z}) \triangleq \mathcal{L}(\boldsymbol{z}, \hat{y}) = \mathcal{L}\left(f(\boldsymbol{x}), \arg\max f(\boldsymbol{x})\right) \tag{2}$$

by assuming the model prediction $\hat{y}$ to be correct, since handling originally misclassified samples falls beyond the scope of defense [17]. For attackers with label $y$, it can be known that the attack succeeds if $\mathcal{L}(f(\boldsymbol{x}), y) < 0$. To quickly realize this, SQAs only update AEs if a query $\boldsymbol{x}_{\mathrm{q}}$ has a lower margin loss compared to the current best query $\boldsymbol{x}_k$, *i.e.*,

$$\boldsymbol{x}_{k+1} = \left\{ \begin{array}{ll} \boldsymbol{x}_{\mathrm{q}}, & \mathcal{L}(f(\boldsymbol{x}_{\mathrm{q}}), y) < \mathcal{L}(f(\boldsymbol{x}_k), y), \\ \boldsymbol{x}_k, & \mathcal{L}(f(\boldsymbol{x}_{\mathrm{q}}), y) \geq \mathcal{L}(f(\boldsymbol{x}_k), y). \end{array} \right. \tag{3}$$

125 Existing SQAs [4, 5, 40] are quite effective, capable of halving the accuracy within 100 queries on
126 CIFAR-10 when $\ell_\infty = 8/255$, posing significant and practical threats. Aware of this, the first defense
127 specifically against SQAs has been recently proposed [14] to pre-process inputs by random noise.
128 Besides, other existing defenses are also useful to avoid SQAs, among which the most representative
129 ones are adversarial training (AT) [8, 21], dynamic inference [19, 30], and pre-processing [14, 28].
130 These defenses work in different mechanisms as illustrated in Fig. 1 (a) and Section 2. Here in Table
131 1, we present a comparison of their key characteristics related to the defense performance.

Table 1: Expectation and effects of current defenses (unpreferable effects are marked in red)

|  | expectation | AT [8, 21] | pre-pro [14, 28] | dyn-inf [19, 30] | AAA (ours) |
|---|---|---|---|---|---|
| accuracy | = | ↓↓ | ↓ | = | = |
| calibration | ↑ | / | ↓ | ↓ | ↑ |
| testing cost | = | = | = | ↑↑↑ | = |
| training cost | = | ↑↑↑ | = | = | = |
| acc under SQA | ↑ | ↑↑ | ↑ | ↑ | ↑↑↑ |

132 Real-case defenders are expected to serve users and meanwhile avoid SQA attackers. The former
133 demands good accuracy, calibration, and inference speed. While the latter requires good protection,
134 and preferably, no additional training (denoted as "="). As a training-time defense on model, AT
135 exerts a significant impact on accuracy [22], *e.g.*, >10% accuracy drop on ImageNet [49], with several-
136 fold training computation and an indefinite impact (denoted as "/") on calibration. Pre-processing
137 is a test-time defense on input, which avoids SQAs by reducing the input's signal-noise ratio but
138 inevitably hurts normal performance. Recently, the dynamic inference is proposed as a test-time
139 defense by optimizing the model, which shows no accuracy drop but dramatically increases the
140 computation, *e.g.*, DENT [19] consumes >700% test-time calculation. Given the above discussion, it
141 is imperative to develop a user-friendly and efficient method to effectively defend against SQAs.

## 4  Adversarial attack on attackers

143 Defending by post-processing naturally carries the advantages of good accuracy and calibration
144 [31], no additional training and negligible test-time computation. Although it does not improve the
145 commonly-studied worst-case robustness [16], its potential to defeat SQAs in real cases has not been
146 explored yet to the best of our knowledge. By investigating current defenses from the perspective of
147 SQA defenders in Sec. 3, it is interesting to find that in the real world, no matter whether defenders
148 alter inputs, models, or outputs, what users/attackers get are just the changes in outputs, *i.e.*, the
149 black-box setting. Thus, it is reasonable and preferable for SQA defenders to directly manipulate
150 DNN's output scores, which has already become a standard practice in model calibration [31].

151 But how? Now that attackers conduct the adversarial attack on the model, why cannot we defenders
152 actively perform an adversarial attack on attackers? If attackers search for the adversarial direction
153 by scores, we can manipulate such scores to cheat them into an incorrect attack path. Following this
154 idea, we develop the adversarial attack on attackers (AAA) to control what the SQA attackers base
155 their actions on, *i.e.*, the loss (1) indicated by the DNN's output scores. Under such direct misleading,
156 SQA attackers, following their original policy, would be guided to wherever we want them to go
157 due to their greediness, seeing (3). Therefore, we can adopt the extreme fooling that leads attackers
158 to walk opposite towards their destiny, *i.e.*, the non-adversarial direction. In this way, attackers are
159 attacked to actually help DNNs become more confident in predictions.

160 Reversing the attacker's path by directly altering outputs is simple. Since SQA attackers observe the
161 margin loss (1), what we should do is force the modified loss to increase when the original unmodified
162 loss actually decreases. This can be achieved by a one-to-one mapping between unmodified and
163 modified loss values, *e.g.*, outputting large margin loss (high confidence) when the original margin
164 is small (model is not confident). However, this naive method prevents users from getting accurate
165 prediction confidence since it greatly changes scores to reverse the overall loss trend along the
166 adversarial direction. Thus, we alternatively reverse the loss in a small interval while keeping the
167 overall trend unchanged as in Fig. 1 (b). This design cheats attackers in most cases, but only requires
168 slight modifications on scores so that the precision of confidence is largely preserved.

169 Specifically, we periodically set *loss attractors* and encourage the DNN's unsupervised margin loss
170 (2) to move towards its closest attractor

$$l_a = (\text{ceil}\,(l_0/t) - 1/2) \times t, \tag{4}$$

171 where $l_0 = \mathcal{L}_u(z_0)$ is the unmodified loss. $t$ is the period, and "ceil" denotes rounding up decimals
172 to integers. For example, if $t = 4$, then according to (4), the closest loss attractor of logits with
173 $l_0 = 0 \rightarrow 4$ is $l_a = 2$. As we can see, the $1/2$ bias is necessary to avoid setting an attractor on $l_a = 0$,
174 *i.e.*, the decision boundary, because approximating the logits to it tends to flip the model's decision.

175 Periodically-set loss attractors divide logits with different $l_0$ into intervals, so that we could reverse
176 the loss trend in each of the interval to cheat attackers into the opposite attack direction as in Fig. 1
177 (b). However, reversing the trend demands more than mapping in-interval losses to a fixed value $l_a$. It
178 requires mapping a small loss with a large one. Thus, we set the target loss value $l_t$ for logits as

$$l_t = l_a - \alpha \times (l_0 - l_a). \tag{5}$$

179 That is, if the unmodified loss $l_0$ is larger than $l_a$ by $l_{\text{diff}}$, we hope the modified loss $l_t$ to be smaller
180 than $l_a$ by $\alpha \times l_{\text{diff}}$. In this way, as a sample is actually close to the decision boundary ($l_0$ decreases),
181 AAA outputs an increasing $l_t$ to mislead attackers away from this adversarial direction.

182 Although the periodic design has already altered output confidence very slightly, we could also step
183 further to improve the precision of confidence because post-processing logits is a standard practice in
184 model calibration [32, 57]. Thus, simultaneous defense and calibration is obtainable in a single AAA
185 module by controlling the loss while encouraging the output confidence $\sigma(z) = \max(\text{softmax}(z))$
186 to approach the calibrated one $p_t$ as

$$\min_z \quad \|\,\mathcal{L}_u(z) - l_t\,\|_1 + \beta \cdot \|\,\sigma(z) - p_t\,\|_1, \tag{6}$$

187 where the first item requires the output loss to form the reversed curve so that attackers would be
188 cheated to non-adversarial directions, while the second item motivates the output confidence to be
189 accurate, and $\beta$ controls the balance between them. Through this design, DNN's output could be both
190 accurate and misleading, achieving two seemingly contradictory goals at the same time.

191 The calibrated confidence $p_t$ is obtainable by various model calibration methods [32, 57]. Among
192 them, temperature scaling [32] is simple but effective [31], which divides all logits by a scalar $T$ as
193 $p_t = \sigma(z_0/T)$. The temperature $T$ is tuned by a validation set to minimize the calibration error, and
194 here, such tuning is conducted when the optimization (6) is also performed so that we can find the
195 temperature that suits AAA best. After that, $T$ is fixed for inference in AAA post-processing module.

196 We summarize our algorithm in Alg. 1. AAA first
197 calculates the original loss $l_0$, according to which
198 sets the target loss $l_t$ that forms the reversed loss
199 curve. Then AAA optimizes the logits to reach the
200 target loss, and also the target confidence $p_t$, which
201 is obtained by dividing the original logits using a
202 pre-tuned temperature $T$. The overall procedure is
203 conducted in test-time with only optimization on
204 the logits, making AAA a computation-efficient,
205 plug-in, and model-agnostic method with good
206 accuracy, calibration, and defense against SQAs.

---

**Algorithm 1** Adversarial Attack on Attackers

**Input:** the logits $z_0$, model's temperature $T$,
    AAA hyper-parameters.
**Output:** post-processed logits $z$
 1: calculate original loss $l_0 = \mathcal{L}_u(z_0)$ by (2)
 2: set target loss $l_t$ by (5)
 3: set target confidence $p_t = \sigma(z_0/T)$
 4: initialize $z = z_0$ and optimize it for (6)
 5: **return** $z$

---

## 5 Experiments

### 5.1 Setup

209 We evaluate AAA along with 8 defense baselines, including random noise defense (RND [33]),
210 adversarial training (AT [36, 59, 49]), dynamic inference (DENT [19]), training randomness (PNI
211 [51]), and ensemble (TRS [60]). Results of AT with extra data [22]) are in Appendix A. AAA
212 uses hyper-parameters $\alpha = 1, t = 6, \beta = 5$, and an Adam optimizer [61] with learning rate
213 $0.1, \beta_1 = 0.9, \beta_2 = 0.999$, and the iteration of optimization 100. To calibrate simultaneously by
214 AAA, we perform temperature scaling using 1K/5K samples for CIFAR-10 testing set / ImageNet
215 validation set respectively to and make them disjoint with the testing samples in attack as much as
216 possible. Detailed hyper-parameters of other defenses and attacks are in Appendix E.

The defenses are assessed by 6 state-of-the-art SQAs, which are random search methods including Square [5], SignHunter [40], and SimBA [4], and gradient estimation methods including NES [58], and Bandits [3]. They are effective and applicable in various settings. Some SQAs use pre-trained models [39, 43], which, however, demands unfeasible access to DNN's training sample. To evaluate real-case defenses against training-based attacks, we alternatively consider a practical SQA QueryNet [62] based on model stealing. Results of DQAs and SQAs using other than margin loss are put in Appendix A. Since AAA aims to defend in real cases without resorting to randomness, it would be unsuitable to evaluate AAA by the common adaptive or white-box attacks [16], e.g., EOT [15]. We mostly perform untargeted $\ell_\infty$ attacks, but we also test the targeted and $\ell_2$ attacks under different bounds to observe the generalization of defenses.

We use 8 DNNs, which are mostly WideResNets [34] as in [17]. The pre-trained models of PNI [51] / TRS [60] are ResNet-20 [63], and we also test ResNeXt-101 [64] in ImageNet. Other studied DNNs come from RobustBench [17] and torchvision [65] as specified in Appendix E. AT models are tested using the same bound as in AT, if not otherwise stated. We use all 10K CIFAR-10 testing samples. For ImageNet, we randomly-select 1K validation samples from all 1K classes respectively (1 image in 1 class) to eliminate the class bias as in [62]. All images are rescaled to $[0, 1]$, and the ImageNet ones are resized to $224 \times 224$. Before feeding them to DNNs, we quantify images to 8-bit, imitating the real-case 8-bit image setting as in [62]. Experiments are performed on an NVIDIA Tesla A100 GPU but could be run on any GPU with over 4GB memory.

As defenders, we are concerned about DNN's remaining accuracy after it being attacked by SQAs for a certain query times. Thus, we report such *SQA adversarial accuracy* after 100 and 2500 queries, reflecting DNN's performance under mild and extreme SQAs. We include the average query times, another metric commonly used by attackers, in Appendix C. To measure the calibration, the expected calibration error (ECE) [32] is commonly used. ECE divides all $N$ testing samples into $M$ bins, and each bin contains samples with confidence ranging from the $m^{\text{th}}$ quantile to the $(m + 1)^{\text{th}}$ quantile of $[0, 1]$. Then ECE is calculated by the difference between accuracy and confidence as $\frac{1}{N} \sum_{m=1}^{M} \left| \sum_{i \in B_m} \mathbf{1}(\hat{y}_i = y_i) - \sum_{i \in B_m} \hat{p}_i^{\hat{y}_i} \right|$, where $\hat{y}_i$ is the predicted label of the $i^{\text{th}}$ sample in the $m^{\text{th}}$ bin $B_m$, and $\hat{p}_i^{\hat{y}_i}$ represents the probability confidence of this prediction.

Figure 2: The AAA-defended (with the above hyper-parametes) and undefended margin loss value when attacking the undefended WideResNet-28 [34] in RobustBench [17] by Square attack [5] ($\ell_\infty = 8/255$) using the $9952^{\text{th}}$ CIFAR-10 test sample (other samples have similar trends as in Appendix B). AAA fools attackers precisely as shown by the tiny symmetric oscillations of two lines.

## 5.2 Visual illustration of AAA

We first visually illustrate the mechanism and effects of AAA. AAA, besides fooling attackers, also calibrates the model, forming the loss curve as in Fig. 2. Slightly different from the ideal defense in Fig. 1 (b) is that the orange curve is lowered for calibration. However, calibration does not hurdle fooling attackers, *i.e.*, the orange line is mostly going opposite to the blue line in a precisely symmetric manner. Also, two lines cross the decision boundary at the same time, meaning that AAA does not change the decision.

Besides the loss, it is also necessary to observe the output probabilities of AAA, which is displayed in Fig. 3 (left). AAA, indicated by the orange lines, changes the scores slightly without hurting accuracy (dotted lines) compared to RND [33] and AT [36]. By such small modifications, AAA not only improves the calibration but also prevents SQAs by misleading them into incorrect directions. As displayed by the right part of Fig. 3, AAA is super effective in avoiding SQAs, even if it is a query-efficient attack working at a large bound. Specifically, AAA preserves a standard trained DNN to have >60% accuracy after 2500 queries, doubling the performance of AT and tripling that for RND.

Figure 3: The left figure illustrates the change of output scores for different defenses. We first sort 10K testing samples in ascending order according to their ground-truth-class probability predicted by the undefended model (blue line), and then divide them into 100 bins, so that the left bins in the figure stand for low-confidence or misclassified samples, and vice versa. Then for samples in each bin, we plot the confidence (solid lines) and accuracy (dotted line) for AT [36], RND [33], and AAA. Compared to AT and RND, AAA alters scores most slightly without influencing the accuracy curve. The right figure shows DNN's accuracy under Square attack [5] when $\ell_2 = 2.5$, indicating that AAA outperforms alternatives in defending SQAs by a large margin with also the highest clean accuracy.

Table 2: The defense performance under attacks (#query = $100/2500$)

| Model | Metric / Attack | None | AT [36, 59, 49] | RND [14] | AAA (ours) |
|---|---|---|---|---|---|
| CIFAR-10 $\ell_\infty = \frac{8}{255}$ | ECE (%) | 3.52 | 11.00 | 6.32 | **2.46** |
| | Acc (%) | 94.78 | 87.02 | 91.05 | **94.84** |
| Wide-ResNet-28 [34] | Square [5] | 39.38 / 00.09 | 78.30 / 67.44 | 60.83 / 49.15 | **81.36 / 80.59** |
| | SignHunter [40] | 41.14 / 00.04 | 78.87 / 66.79 | 61.02 / 47.82 | **79.41 / 76.71** |
| | SimBA [4] | 53.04 / 03.95 | 84.21 / 75.85 | 76.39 / 64.34 | **88.86 / 83.36** |
| | NES [58] | 83.42 / 12.24 | 85.92 / 81.01 | 86.23 / 68.19 | **90.62 / 85.95** |
| | Bandit [3] | 69.86 / 41.03 | **83.62** / 76.25 | 70.44 / 41.65 | 80.86 / **78.36** |
| ImageNet $\ell_\infty = \frac{4}{255}$ | ECE (%) | 5.42 | 5.03 | 5.79 | **4.30** |
| | Acc (%) | 77.11 | 66.30 | 75.32 | **77.17** |
| Wide-ResNet-50 [34] | Square [5] | 52.27 / 09.25 | 59.20 / 51.11 | 58.67 / 50.54 | **63.13 / 62.51** |
| | SignHunter [40] | 53.05 / 13.88 | 59.47 / 56.22 | 59.36 / 52.98 | **62.35 / 56.80** |
| | SimBA [4] | 71.79 / 20.90 | 65.64 / 47.60 | 66.36 / 63.27 | **74.16 / 67.14** |
| | NES [58] | 77.11 / 64.93 | 66.30 / 64.38 | 71.33 / 66.05 | **77.12 / 67.06** |
| | Bandit [3] | 71.33 / 65.77 | 65.30 / 63.98 | 65.15 / 61.38 | **72.15/ 70.53** |
| ImageNet $\ell_\infty = \frac{4}{255}$ | ECE (%) | 8.37 | **5.74** | 8.93 | 7.38 |
| | Acc (%) | **78.21** | 63.94 | 76.75 | **78.21** |
| Res-NeXt-101 [64] | Square [5] | 54.51 / 11.73 | 57.99 / 51.47 | 58.56 / 48.20 | **66.32 / 65.77** |
| | SignHunter [40] | 54.12 / 13.30 | 59.14 / 56.49 | 58.02 / 52.50 | **62.72 / 59.60** |
| | SimBA [4] | 70.86 / 24.64 | 59.40 / 57.53 | 68.31 / 66.16 | **74.06 / 67.26** |
| | NES [58] | **78.21** / 66.24 | 63.94 / 62.51 | 73.37 / 69.30 | **78.21 / 68.51** |
| | Bandit [3] | 72.19 / 67.73 | 63.18 / 62.26 | 67.69 / 64.62 | **72.91 / 71.48** |

## 5.3 Numerical results of AAA

We report the main numerical results in Table 2, where RND and AAA are directly implemented in the undefended model denoted as "None". The AT method for the three models are PSSiLU [36], vanilla AT [59], and feature denoising [49], respectively. According to Table 2, AAA not only consistently reduces ECE by >12%, but also does not hurt clean accuracy. In contrast, the AT models lose >7% accuracy and RND also endures a drop in accuracy and calibration. Under SQAs, AAA

preserves a significantly higher accuracy than the undefended model, which is totally destroyed. The most threatening SQAs in two datasets more than halve the CIFAR-10 model's accuracy within 100 queries and degrade ImageNet ones to <15% by 2500 times. However, the AAA model remains >75% and >55% accuracy in extreme cases. AT and RND are useful in mitigating SQAs, but it is AAA that tops the defense performance in almost all cases.

Besides AT and RND, diverse defenses have also been proposed, and it would be interesting to see their results. DENT [19] optimizes the model in test-time, trying to learn the AE distribution. PNI [51] injects noise during training, making the learned weights less sensitive to input perturbations. TRS [60] ensembles three models with low attack transferability between each other. They are originally developed for gradient-based attacks, but also provide some protection against SQAs. As displayed in Table 3, however, they are not comparable to AAA in real cases regarding the accuracy, calibration, and defense performance. Here, we also test a strong SQA QueryNet, which uses three architecture-alterable models to steal the DNN. Due to its utilization of large-scale testing samples, QueryNet greatly hurts DNNs, but AAA is still the defense that protects the model best.

Table 3: Various defenses under strong attacks (#query $= 100/2500$, CIFAR-10, $\ell_\infty = 8/255$)

| Metric / Attack | None | DENT [19] | PNI [51] | TRS [60] | AAA (ours) |
|---|---|---|---|---|---|
| ECE (%) | 3.52 | 5.20 | 3.09 | 3.64 | **2.46** |
| Acc (%) | 94.78 | 94.80 | 81.91 | 88.64 | **94.84** |
| Square [5] | 39.38 / 00.09 | 62.01 / 35.07 | 57.69 / 45.47 | 56.26 / 23.91 | **81.36 / 80.59** |
| QueryNet [40] | 13.50 / 00.03 | 39.35 / 20.75 | 44.06 / 34.69 | 16.43 / 08.49 | **50.01 / 49.63** |

## 5.4 Generalization of AAA

Aside from the untargeted $\ell_\infty$ attacks, we also conduct targeted attacks, $\ell_2$ attacks under different bounds to study the generalization of AAA. A targeted attack is successful only if an AE is mispredicted as a pre-set class, which, is randomly chosen from incorrect classes for each sample here. And $\ell_2$ attacks bound the perturbations by $\ell_2$ norm, which is reported to fool DNNs better [10]. Here we additionally validate AAA's plug-in advantage by combining it with AT. Note that what differs from AAA and most existing defenses [49, 50, 51] combined with AT is that AAA has already achieved excellent defense performance, so such a combination is feasible but not necessary. We choose Square attack [5] to perform the above evaluations because it is the most effective SQA as tested in Table 2. The results are presented in Table 4, where all models are exactly the same as in Table 2 (CIFAR-10) without tuning hyper-parameters of defense to fairly evaluate the generalization of different methods. The results of $\ell_2$ AT model and other $\ell_\infty$ AT models are put in Appendix A.

In the difficult targeted attack setting, the undefended model remains only 2.84% accuracy after 2500 queries, which is approximately just the accuracy drop of the AAA model. For $\ell_2$ attacks, AAA is still capable of mitigating threats without hurting users, and its superiority is more outstanding as the attack bound becomes larger. AT models, although robust, suffer from attacks under a large or different norm ball [56]. Thus, its defense effects decrease as SQA alters the setting, seeing the bottom line. Defended by AAA, however, this drawback would be greatly avoided. An $\ell_\infty$ AT model, even under $\ell_2 = 2.5$ attack after 2500 queries, is hardly influenced, *i.e.*, increasing query times after 100 queries hardly better the attack performance, discouraging SQA attackers.

Table 4: Generalization of AAA tested by Square attack [5] (#query $= 100/2500$, CIFAR-10)

| Metric / Attack | None | AAA (ours) | AT [36] | AT-AAA |
|---|---|---|---|---|
| ECE (%) | 3.52 | **2.46** | 11.00 | **10.56** |
| Acc (%) | 94.78 | **94.84** | **87.02** | **87.02** |
| untargeted $\ell_\infty = 8/255$ | 39.38 / 00.09 | **81.36 / 80.59** | 78.30 / 67.44 | **80.80 / 80.13** |
| targeted $\ell_\infty = 8/255$ | 75.59 / 02.84 | **92.05 / 91.62** | 85.75 / 82.72 | **86.22 / 86.13** |
| untargeted $\ell_2 = 0.5$ | 81.53 / 18.75 | **92.66 / 92.63** | 84.26 / 78.97 | **85.12 / 84.31** |
| untargeted $\ell_2 = 2.5$ | 12.77 / 00.01 | **70.35 / 63.46** | 57.88 / 25.19 | **74.03 / 73.72** |

Figure 4: The influence of AAA hyper-parameters (the attractor interval $t$ in (4), the reverse step $\alpha$ in (5), and the calibration loss weight $\beta$ in (6)) to accuracy (left axis), ECE (right axis), SQA adversarial accuracy (left axis), and temperature (right axis). The dashed ECE (ref) means the undefended model.

## 5.5 Hyper-parameters of AAA

The above amazing results in various settings are all obtained using fixed parameters that are heuristically selected, and it would be necessary to see how each of them affects the results. The attractor interval $t$ in (4) decides the period of the margin loss attractors, and a larger $t$ divides the losses into fewer intervals so that attackers are harder to jump out of one of them. The reverse step $\alpha$ in (5) controls the reverse degree, and if it increases, the modified loss curve would be steeper oppositely along the adversarial direction, emphasizing the defense. The calibration loss weight $\beta$ in (6) directly balances defense and calibration in optimization. Here we still consider the accuracy, ECE, and SQA adversarial accuracy (under 100 queries). Plus, we study an additional metric, the temperature $T$ of logits rescaling tuned with AAA.

The results are shown in Fig. 4. The adversarial accuracy far exceeds the undefended model ($39.38\%$) and mostly surpasses AT ($67.44\%$). The clean accuracy is hardly impacted and the ECE is mostly below the undefended model (the green dashed line). Thus, AAA's good performance is insensitive to hyper-parameters, even if tuned in logarithmic scale. Regarding the trend, an intuitive conclusion is that a larger $\alpha$, a larger $t$, or a smaller $\beta$ that highlights defense more v.s. calibration would thereby increase the adversarial accuracy and ECE. Interestingly, the temperature mostly decreases as the defense is emphasized (the logits are divided by a smaller value), indicating that the model tends to output lower confidence to defend, consistent with the situation in AT [17].

## 6 Conclusion, impacts and limitations

We develop a novel defense against score-based query attacks (SQAs). Our main idea is to actively attack the attackers (AAA), misleading them into incorrect attack directions. AAA achieves that by post-processing DNN's logits while enforcing the new output confidence to be calibrated, making AAA a deterministic plug-in test-time defense with improvements in calibration and accuracy by costing negligible computation overhead. Compared to alternative defenses, AAA is effective in mitigating SQAs according to our study on 8 defenses, 6 SQAs, and 8 DNNs under various settings.

As a defense in real-world applications, AAA greatly mitigates the adversarial threat without requiring huge computational burden. For example, in autonomous driving or supervision systems, the post-processing defense module could be directly implemented in pre-trained models. Despite the low cost, the benefits of adopting AAA are profound. In most cases, users would be provided with a more accurate confidence score so that they know better when the model tends to fail. In adversarial cases, SQAs, the most threatening attack in real cases, would be effectively prevented.

AAA is developed to especially prevent SQAs. Thus, defending our types of attacks is beyond our scope. For example, AAA does not improve the worst-case robustness evaluated in white-box settings [16, 46] where attackers have complete knowledge of the model (the AutoAttack [16] robust accuracy would be increased in an undesirable manner by AAA). Also, AAA is not applicable to avoiding transfer-based attacks and decision-based query attacks, which are either unfeasible or inefficient in the real world, because AAA induces only a negligible impact on the decision boundary by perturbing the output scores very slightly.

# References

[1] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. J. Goodfellow, and R. Fergus, "Intriguing properties of neural networks," in *International Conference on Learning Representations (ICLR)*, 2014.

[2] I. J. Goodfellow, J. Shlens, and C. Szegedy, "Explaining and harnessing adversarial examples," in *International Conference on Learning Representations (ICLR)*, 2015.

[3] A. Ilyas, L. Engstrom, and A. Madry, "Prior convictions: Black-box adversarial attacks with bandits and priors," in *International Conference on Learning Representations (ICLR)*, 2019.

[4] C. Guo, J. Gardner, Y. You, A. G. Wilson, and K. Weinberger, "Simple black-box adversarial attacks," in *International Conference on Machine Learning (ICML)*, 2019, pp. 2484–2493.

[5] M. Andriushchenko, F. Croce, N. Flammarion, and M. Hein, "Square attack: A query-efficient black-box adversarial attack via random search," in *the European Conference on Computer Vision (ECCV)*, 2020, pp. 484–501.

[6] S.-M. Moosavi-Dezfooli, A. Fawzi, and P. Frossard, "Deepfool: A simple and accurate method to fool deep neural networks," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 2574–2582.

[7] N. Carlini and D. Wagner, "Towards evaluating the robustness of neural networks," in *the IEEE Symposium on Security and Privacy (SP)*, 2017, pp. 39–57.

[8] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, "Towards deep learning models resistant to adversarial attacks," in *International Conference on Learning Representations (ICLR)*, 2018.

[9] C. Xie, Z. Zhang, Y. Zhou, S. Bai, J. Wang, Z. Ren, and A. L. Yuille, "Improving transferability of adversarial examples with input diversity," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 2730–2739.

[10] S. Chen, Z. He, C. Sun, and X. Huang, "Universal adversarial attack on attention and the resulting dataset DAmageNet," in *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 2022, pp. 2188–2197.

[11] W. Brendel, J. Rauber, and M. Bethge, "Decision-based adversarial attacks: Reliable attacks against black-box machine learning models," in *International Conference on Learning Representations (ICLR)*, 2018.

[12] M. Cheng, T. Le, P.-Y. Chen, H. Zhang, J. Yi, and C.-J. Hsieh, "Query-efficient hard-label black-box attack: An optimization-based approach," in *International Conference on Learning Representations (ICLR)*, 2018.

[13] J. Chen, M. I. Jordan, and M. J. Wainwright, "HopSkipJumpAttack: A query-efficient decision-based attack," in *the IEEE Symposium on Security and Privacy (SP)*, 2020, pp. 1277–1294.

[14] Z. Qin, Y. Fan, H. Zha, and B. Wu, "Random noise defense against query-based black-box attacks," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 7650–7663.

[15] A. Athalye, N. Carlini, and D. Wagner, "Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples," in *International Conference on Machine Learning (ICML)*, 2018, pp. 274–283.

[16] F. Croce and M. Hein, "Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks," in *International Conference on Machine Learning (ICML)*, 2020, pp. 2206–2216.

[17] F. Croce, M. Andriushchenko, V. Sehwag, E. Debenedetti, N. Flammarion, M. Chiang, P. Mittal, and M. Hein, "Robustbench: a standardized adversarial robustness benchmark," in *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2021.

[18] Y. Li, Z. Yang, Y. Wang, and C. Xu, "Neural architecture dilation for adversarial robustness," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 29 578–29 589.

[19] D. Wang, A. Ju, E. Shelhamer, D. Wagner, and T. Darrell, "Fighting gradients with gradients: Dynamic defenses against adversarial attacks," *arXiv preprint arXiv:2105.08714*, 2021.

[20] A. Prakash, N. Moran, S. Garber, A. DiLillo, and J. Storer, "Deflecting adversarial attacks with pixel deflection," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018, pp. 8571–8580.

[21] F. Tramèr, A. Kurakin, N. Papernot, I. J. Goodfellow, D. Boneh, and P. D. McDaniel, "Ensemble adversarial training: Attacks and defenses," in *6th International Conference on Learning Representations (ICLR)*, 2018.

[22] R. Rade and S.-M. Moosavi-Dezfooli, "Helper-based adversarial training: Reducing excessive margin to achieve a better accuracy vs. robustness trade-off," in *ICML 2021 Workshop on Adversarial Machine Learning*, 2021.

[23] H. Salman, M. Sun, G. Yang, A. Kapoor, and J. Z. Kolter, "Denoised smoothing: A provable defense for pretrained classifiers," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2020, pp. 21 945–21 957.

[24] C. Xie, J. Wang, Z. Zhang, Z. Ren, and A. L. Yuille, "Mitigating adversarial effects through randomization," in *International Conference on Learning Representations (ICLR)*, 2018.

[25] X. Liu, M. Cheng, H. Zhang, and C.-J. Hsieh, "Towards robust neural networks via random self-ensemble," in *the European Conference on Computer Vision (ECCV)*, 2018, pp. 369–385.

[26] M. Lecuyer, V. Atlidakis, R. Geambasu, D. Hsu, and S. Jana, "Certified robustness to adversarial examples with differential privacy," in *the IEEE Symposium on Security and Privacy (SP)*, 2019, pp. 656–672.

[27] Z. Liu, Q. Liu, T. Liu, N. Xu, X. Lin, Y. Wang, and W. Wen, "Feature distillation: Dnn-oriented JPEG compression against adversarial examples," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 860–868.

[28] J. Buckman, A. Roy, C. Raffel, and I. Goodfellow, "Thermometer encoding: One hot way to resist adversarial examples," in *International Conference on Learning Representations (ICLR)*, 2018.

[29] C. Guo, M. Rana, M. Cisse, and L. van der Maaten, "Countering adversarial images using input transformations," in *International Conference on Learning Representations (ICLR)*, 2018.

[30] Y.-H. Wu, C.-H. Yuan, and S.-H. Wu, "Adversarial robustness via runtime masking and cleansing," in *International Conference on Machine Learning (ICML)*, 2020, pp. 10 399–10 409.

[31] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in *International Conference on Machine Learning (ICML)*, 2017, pp. 1321–1330.

[32] M. P. Naeini, G. Cooper, and M. Hauskrecht, "Obtaining well calibrated probabilities using bayesian binning," in *the AAAI conference on Artificial Intelligence (AAAI)*, 2015, pp. 2901–2907.

[33] Y. Qin, X. Wang, A. Beutel, and E. Chi, "Improving calibration through the relationship with adversarial robustness," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 14 358–14 369.

[34] S. Zagoruyko and N. Komodakis, "Wide residual networks," in *British Machine Vision Conference (BMVC)*, 2016, pp. 87.1–87.12.

[35] A. Krizhevsky *et al.*, "Learning multiple layers of features from tiny images," 2009.

[36] S. Dai, S. Mahloujifar, and P. Mittal, "Parameterizing activation functions for adversarial robustness," *arXiv preprint arXiv:2110.05626*, 2021.

[37] N. Papernot, P. McDaniel, I. Goodfellow, S. Jha, Z. B. Celik, and A. Swami, "Practical black-box attacks against machine learning," in *the ACM on Asia Conference on Computer and Communications Security*, 2017, pp. 506–519.

[38] P.-Y. Chen, H. Zhang, Y. Sharma, J. Yi, and C.-J. Hsieh, "Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models," in *the 10th ACM workshop on artificial intelligence and security*, 2017, pp. 15–26.

[39] S. Cheng, Y. Dong, T. Pang, H. Su, and J. Zhu, "Improving black-box adversarial attacks with a transfer-based prior," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, pp. 10 934–10 944.

[40] A. Al-Dujaili and U.-M. O'Reilly, "Sign bits are all you need for black-box attacks," in *International Conference on Learning Representations (ICLR)*, 2019.

[41] M. Cheng, S. Singh, P. H. Chen, P.-Y. Chen, S. Liu, and C.-J. Hsieh, "Sign-opt: A query-efficient hard-label adversarial attack," in *International Conference on Learning Representations (ICLR)*, 2019.

[42] A. N. Bhagoji, W. He, B. Li, and D. Song, "Practical black-box attacks on deep neural networks using efficient query mechanisms," in *the European Conference on Computer Vision (ECCV)*, 2018, pp. 154–169.

[43] Y. Guo, Z. Yan, and C. Zhang, "Subspace attack: Exploiting promising subspaces for query-efficient black-box attacks," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, pp. 3820–3829.

[44] D. C. R. Viet Quoc Vo, Ehsan Abbasnejad, "Ramboattack: A robust query efficient deep neural network decision exploit," *Network and Distributed Systems Security (NDSS) Symposium*, 2022.

[45] C. Yao, P. Bielik, P. Tsankov, and M. Vechev, "Automated discovery of adaptive attacks on adversarial defenses," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 26 858–26 870.

[46] F. Tramer, N. Carlini, W. Brendel, and A. Madry, "On adaptive attacks to adversarial example defenses," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2020, pp. 1633–1645.

[47] S. Gowal, S.-A. Rebuffi, O. Wiles, F. Stimberg, D. A. Calian, and T. A. Mann, "Improving robustness using generated data," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 4218–4233.

[48] S.-A. Rebuffi, S. Gowal, D. A. Calian, F. Stimberg, O. Wiles, and T. A. Mann, "Data augmentation can improve robustness," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 29 935–29 948.

[49] C. Xie, Y. Wu, L. v. d. Maaten, A. L. Yuille, and K. He, "Feature denoising for improving adversarial robustness," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 501–509.

[50] Y. Fu, Q. Yu, Y. Zhang, S. Wu, X. Ouyang, D. Cox, and Y. Lin, "Drawing robust scratch tickets: Subnetworks with inborn robustness are found within randomly initialized networks," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 13 059–13 072.

[51] Z. He, A. S. Rakin, and D. Fan, "Parametric noise injection: Trainable randomness to improve deep neural network robustness against adversarial attack," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 588–597.

[52] H. Salman, J. Li, I. Razenshteyn, P. Zhang, H. Zhang, S. Bubeck, and G. Yang, "Provably robust deep learning via adversarially trained smoothed classifiers," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, pp. 11 292–11 303.

[53] A. Niculescu-Mizil and R. Caruana, "Predicting good probabilities with supervised learning," in *International Conference on Machine learning (ICML)*, 2005, pp. 625–632.

[54] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, "Rethinking the inception architecture for computer vision," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 2818–2826.

[55] S. Thulasidasan, G. Chennupati, J. A. Bilmes, T. Bhattacharya, and S. Michalak, "On mixup training: Improved calibration and predictive uncertainty for deep neural networks," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, pp. 13 911–13 922.

[56] D. Stutz, M. Hein, and B. Schiele, "Confidence-calibrated adversarial training: Generalizing to unseen attacks," in *International Conference on Machine Learning (ICML)*, 2020, pp. 9155–9166.

[57] B. Zadrozny and C. Elkan, "Obtaining calibrated probability estimates from decision trees and naive bayesian classifiers," in *the AAAI conference on Artificial Intelligence (AAAI)*, 2001, pp. 609–616.

[58] A. Ilyas, L. Engstrom, A. Athalye, and J. Lin, "Black-box adversarial attacks with limited queries and information," in *International Conference on Machine Learning (ICML)*, 2018, pp. 2142–2151.

[59] H. Salman, A. Ilyas, L. Engstrom, A. Kapoor, and A. Madry, "Do adversarially robust imagenet models transfer better?" in *Advances in Neural Information Processing Systems (NeurIPS)*, 2020, pp. 3533–3545.

[60] Z. Yang, L. Li, X. Xu, S. Zuo, Q. Chen, P. Zhou, B. Rubinstein, C. Zhang, and B. Li, "TRS: Transferability reduced ensemble via promoting gradient diversity and model smoothness," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 17 642–17 655.

[61] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *International Conference on Learning Representations (ICLR)*, 2015.

[62] S. Chen, Z. Huang, Q. Tao, and X. Huang, "Querynet: Attack by multi-identity surrogates," *arXiv preprint arXiv:2105.15010*, 2021.

[63] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778.

[64] S. Xie, R. Girshick, P. Dollár, Z. Tu, and K. He, "Aggregated residual transformations for deep neural networks," in *the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 1492–1500.

[65] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga *et al.*, "Pytorch: An imperative style, high-performance deep learning library," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, pp. 8024–8035.