INTRINSIC CREDIT ASSIGNMENT FOR LONG HORIZON INTERACTION

Ilze Amanda Auzina* **& Joschka Strüber*** **& Sergio Hernández-Gutiérrez***
Tübingen AI Center, University of Tübingen
`{ilze.auzina,joschka.strueber,sergio.hernandez}@bethgelab.org`

Shashwat Goel
ELLIS Institute Tübingen, MPI-IS

Ameya Prabhu[†] **& Matthias Bethge**[†]
Tübingen AI Center, University of Tübingen

ABSTRACT

How can we train agents to navigate uncertainty over long horizons? In this work, we propose ΔBelief-RL, which leverages a language model's own intrinsic beliefs to reward intermediate progress. Our method utilizes the change in the probability an agent assigns to the target solution for credit assignment. By training on synthetic interaction data, ΔBelief-RL teaches information-seeking capabilities that consistently outperform purely outcome-based rewards for RL, with improvements generalizing to out-of-distribution applications ranging from customer service to personalization. Notably, the performance continues to improve as we scale test-time interactions beyond the training horizon, with interaction-efficiency increasing even on Pass@k metrics. Overall, our work introduces a scalable training strategy for navigating uncertainty over a long-horizon, by enabling credit assignment to intermediate actions via intrinsic ΔBelief rewards.

1 INTRODUCTION

In 2025, language agents have rapidly improved in their ability to solve fully specified tasks, ranging from challenging questions posed by researchers Schmidgall et al. (2025) to economically valuable tasks Kwa et al. (2025); Patwardhan et al. (2025). However, they still struggle with under-specified or open-ended problems, which require interactions to seek information before a solution can be attempted Grand et al. (2025). Whether it be navigating the hypothesis space in a scientific problem, or interacting to understand user's preferences, models struggle to ask the right questions Laban et al. (2025).

The root of this disconnect lies in the pre-training data itself: web data does not fully capture information-seeking. Although the web provides a vast repository of user-posed questions and answers, this data rarely reflects the underlying internal beliefs or knowledge gaps that prompted the user to ask the question itself. The utility of a question is inherently tied to an agent's **own** beliefs: a useful question for one agent may not provide new information to another with different knowledge and uncertainty distributions.

In this work, we study how agents can be trained to navigate uncertainty across long-horizon interactions. Such trajectories require granular credit assignment to distinguish which intermediate actions drive success versus those that lead to failure. A common strategy in RL is to use a learned critic to estimate a *value function* Sutton & Barto (2018), but this approach is often prohibitively expensive for large-scale language models. Consequently, current approaches use only sparse outcome rewards Guo et al. (2025). The hope is that, while sparse rewards lack granular credit assignment, the agent will eventually converge towards a globally optimal solution. While this simplification holds for single-turn or fully specified tasks, it is ill-suited for open-ended, partial-information settings that require the model to actively explore and seek information at *every step*.

---

*Equal contribution.
[†]Equal supervision.

We propose a scalable solution, ΔBelief-RL, a novel framework which guides learning and credit assignment on intermediate actions in long-horizon tasks. At each interaction during training, we monitor the change in agent's belief towards the target. We use this information as a dense training signal, ΔBelief reward, that reinforces actions which shift the agent's internal beliefs toward the target, while also using the final outcome as part of the reward. The benefit of our method is that it does not require a separately trained critic or process reward model, but rather uses the agent's own intrinsic beliefs as a proxy for each action's value. This enables intermediate credit assignment "for free" by leveraging the agent's own progress toward the solution. Furthermore, our training strategy is general-purpose; it can be applied to any task where the correct final outcome is available during training.

Figure 1: Main contributions. We propose a dense reward signal, ΔBelief Reward, based on agent intrinsic belief updates in long horizon tasks. We find that **(1)** ΔBelief-RL leads to more sample-efficient training **(2)** our trained agent generalizes better to unseen information-seeking tasks; and **(3)** scales better with increased test-time interaction budget.

We evaluate ΔBelief-RL by training `Qwen3` models (up to 4B parameters) on a classic long-horizon information-seeking task: 20 Questions. We name the resulting models CIA, Curious Information-seeking Agent (CIA), optimized for active inquiry. Our approach consistently outperforms standard, sequence-level GRPO training, such as STARPO Wang et al. (2025), across all model sizes (Table 1). Notably, our CIA-1.7B model outperforms `DeepSeek v3.2` (670B), supporting our hypothesis that specialized training is essential for active information-seeking where web-scale pretraining and RLVR fall short. Remarkably, the obtained capabilities do not plateau at the 20-turn training cap; instead, performance continues to scale as test-time interactions extend beyond the training horizon (Figure 8). Furthermore, ΔBelief-RL expands the agent's reasoning capabilities beyond its initial training (Figure 7). Crucially, these information-seeking behaviors generalize to novel tasks not seen during training (Figure 10, Figure 9), demonstrating that ΔBelief-RL imparts task-agnostic ability to efficiently interact and navigate uncertainty.

Overall, we show how an agent's internal beliefs can act as an intrinsic reward signal for credit assignment in uncertain long-horizon tasks. This yields substantial gains in interaction-efficient information-acquisition, an important component of intelligence (Chollet, 2019) and world modeling (Warrier et al., 2025). We anticipate that as agents develop more sophisticated implicit world models, their belief updates will become even more precise, further amplifying the effectiveness of our approach. Ultimately, we hope this provides a path toward agents that can reason about their own uncertainty to efficiently pursue open-ended goals.

2 BACKGROUND AND PROBLEM SETUP

We consider a multi-turn interaction setting where an agent must uncover a latent target concept $y \in \mathcal{Y}$. Each episode begins with a task-specific prompt that defines the search space. To solve the task, the agent interacts with the environment over a long horizon, generating a trajectory τ of N steps: $\tau = \{(a_1, o_1), \ldots, (a_N, o_N)\}$, where a_t represents the agent's action (e.g., a query or hypothesis) and o_t represents the environment's response (e.g. user's answer) at time t. In our setup, both the actions and the observations are strings. We denote the interaction history up to step t as $h_t = \{a_1, o_1, \ldots, a_{t-1}, o_{t-1}\}$, where the agent samples each action based on the accumulated context: $a_t \sim \pi_\theta(\cdot \mid h_t)$. The initial prompt can be considered a part of h_1. At the end of the trajectory τ, the environment returns a verifiable score $r(\tau)$ which assesses whether

Figure 2: Belief updates. The per-turn beliefs about the ground-truth `Qwen3` (1.7B and 4B), split by final outcome. The trajectories were generated by `DeepSeek-v3.2`. On average, beliefs steadily increase and the rate of growth strongly correlates with the outcome of the trajectory.

Figure 3: Best-of-8 sampling with ΔBelief. Success rate on the 20 Questions task for our baseline models `Qwen3-1.7B` and `Qwen3-4B` after SFT, as well as the base model `Qwen3-8B`. We compare regular question generation with ΔBelief sampling.

the agent successfully uncovered the target concept y. We define the policy's performance over the concept space $\mathcal{Y}$ as $\texttt{Perf}(\pi) = \frac{1}{|\mathcal{Y}|} \sum_{y \in \mathcal{Y}} \mathbb{E}_{\tau \sim \pi}[r(\tau)]$. We train on a finite subset $\mathcal{Y}_{\text{train}}$ and evaluate generalization on unseen instances $\mathcal{Y}_{\text{test}}$.

2.1 TRAINING ENVIRONMENT

We use the 20 Questions (20Qs) game as our training environment for multi-turn interaction. In this setting, the target concept y is a "secret word" (e.g. "`belief`"). The agent's actions a_t are yes/no inquiries (e.g. "`Is the word an abstract concept?`"). The observations o_t are responses provided by a user simulator (e.g. "`Yes`"). The agent's objective is to identify y within a maximum of 20 turns. An episode terminates successfully if the agent correctly guesses y, at which point it receives the outcome reward $r(\tau)$; otherwise, the interaction concludes after 20 turns with a score of zero. This setup is representative of a broad class of information-seeking problems where agents must optimize interactions to arrive at a target solution.

Agent Configurations We instantiate the 20 Questions environment with the training policy (`Qwen3`) at two scales, 1.7B and 4B, as the questioner agent, and `Qwen3-14B` as the *User simulator*. To fit full trajectories within the context window for backpropagation, we use the models in non-thinking mode.

3 ΔBELIEF-RL: INTRINSIC CREDIT ASSIGNMENT

The ΔBelief-RL framework leverages an agent's internal beliefs as an intrinsic reward signal, enabling dense credit assignment in probabilistic, long-horizon tasks. In the context of 20 Questions, this involves quantifying the shift in the agent's posterior distribution over the target concept y following each interaction (a_t, o_t).

The following sections detail our methodology. First, we formalize the measurement of beliefs for language model based agents. Then, we define a metric to capture progress toward the goal at each turn, and empirically validate that it correlates with task success. Finally, we describe how we utilize these intrinsic signals to optimize the agent's information-seeking capability with RL.

Agent Beliefs We elicit the agent's internal belief by leveraging its underlying token probability distribution. Given an elicitation prompt e_i, we calculate the belief at turn t as the probability the policy assigns to the target concept y conditioned on the history h_t: $b_t = p_\theta(y_i \mid h_t, e_i)$. For 20 questions, we use $e_i = $ "`Is the secret <target>`".

ΔBelief reward: Belief Change Signal By tracking b_t across the trajectory, we can quantify how each interaction resolves uncertainty, shifting the model's internal "world view" towards the correct solution. We calculate the per turn belief-change, denoted ΔBelief, as the log-ratio of sequential

beliefs:

$$\Delta \text{Belief}_t = \log \frac{b_t}{b_{t-1}} = \log b_t - \log b_{t-1} \tag{1}$$

By utilizing log-probabilities, we ensure numerical stability and prevent floating-point underflow during training. This dense, turn-level signal reinforces actions that lead to the most informative updates to the agent's internal world view.

3.1 VALIDATING THE ΔBELIEF MEASUREMENT

The effectiveness of the ΔBelief reward depends on the agent's internal world model making sufficiently calibrated updates based on environment feedback. We confirm this using two experiments: first, we check whether the belief assigned to the correct answer reliably correlates with the trajectory outcome, and the number of information-seeking actions; second, we evaluate whether action selection based on ΔBelief at inference-time leads to performance gains.

Do Agent Beliefs Reflect Interactive Progress? To determine whether internal beliefs reliably track environmental information, we decouple the belief update process from the question-asking policy to test it in isolation. The belief updates of `Qwen3` on off-policy trajectories generated by `DeepSeek-v3.2` are shown in Figure 2. We find that beliefs consistently increase over time, confirming that these models successfully integrate evidence from observations. Crucially, these updates correlate with task success: successful episodes exhibit significantly higher cumulative belief increases after few turns. This suggests that the agent's actions effectively narrow the solution space, moving its internal "world view" closer to the target concept.

Does Optimizing Belief Updates Improve Task Success? Next, we examine whether optimizing for ΔBelief reward leads to more successful interactions compared to the baseline SFT policy (details Sec. 4). We perform an intervention with best-of-n sampling to simulate an agent that explicitly optimizes for belief updates during inference. At each turn t, we sample $n = 8$ candidate questions, simulate the environment's response for each, and select the action that maximizes the immediate belief change:

$$a_t \leftarrow \arg \max_{k \in \{1,...,n\}} \Delta \text{Belief}(a_{t,k}) \tag{2}$$

As shown in Figure 3, maximizing belief updates significantly and consistently improves performance across all model scales. While this "look-ahead" method is unsuitable for inference—as it requires oracle access to ground-truth answers during the selection process—it confirms that ΔBelief reward is a powerful heuristic for exploration and a viable signal for RL training.

3.2 TRAINING WITH REINFORCEMENT LEARNING

We build upon the standard RL with verifiable rewards framework by augmenting the sparse outcome reward with our dense intrinsic signal at every turn t. Since the policy update occurs after a completed trajectory, we can backpropagate the final outcome to each individual step. We define the per-turn reward r_t as:

$$r_t = \underbrace{r^{\text{eog}}}_{\substack{\text{trajectory} \\ \text{outcome}}} + \underbrace{\lambda \max(\Delta \text{Belief}_t, 0)}_{\text{intrinsic exploration}} + \underbrace{r_p}_{\substack{\text{efficiency} \\ \text{penalty}}} \tag{3}$$

where λ scales the belief-based reward. The penalty term r_p discourages wrong formatting and redundancy, while incorporating a number of turns penalty to encourage efficiency. Notably, we clip the intrinsic reward at zero, ensuring that agents are rewarded for increasing belief in the correct concept without being penalized for temporary decreases in confidence. We present ablations in Appendix A.1.

Turn-wise GRPO While standard GRPO applies the same reward across the entire trajectory, this coarse approach obscures the specific contribution of individual actions. Since our framework provides a dense reward signal r_t for every turn, we go beyond trajectory-level feedback and compute advantages at the *turn level*.

For a group of G sampled trajectories $\{\tau^i\}_{i=1}^G$, let r_t^i be the reward at turn t for sample i. We calculate the group-relative turn-wise advantage as:

$$\widehat{A}_t^i = \frac{r_t^i - \text{mean}(\{r_t^i\}_{i=1}^G)}{\text{std}(\{r_t^i\}_{i=1}^G)}. \tag{4}$$

This advantage $\widehat{A}_t^i$ is assigned to all tokens generated in turn t. By replacing a uniform trajectory-level advantage with the sequence $(\widehat{A}_1^i, \ldots, \widehat{A}_N^i)$, we can provide the policy with granular feedback on each specific interaction. Although we instantiate this approach using multi-turn GRPO (Zeng et al., 2025), this turn-wise reward structure remains compatible with any standard reinforcement learning algorithm.

4 EXPERIMENTAL DETAILS

Data and Models We perform RL training on the 20Qs environment. The ground-truth concepts $\mathcal{Y}$ are split into four distinct sets: 341 for SFT training, 1,000 for RL training, 198 for validation, and 433 for testing. The set of possible secrets $\mathcal{Y}$ is kept unknown to the *Questioner* matching challenging open-ended settings. As mentioned in Section 2.1, we select `Qwen3-1.7B` and `Qwen3-4B` as the agent and `Qwen3-14B` as the user simulator.

RL Training. All RL experiments begin from a *Baseline (SFT)* checkpoint, which is fine-tuned on 8,918 demonstration turns generated via rejection sampling using GEMINI 2.0 FLASH. We train using turn-wise GRPO

Table 1: Success rate on the test set. Average success rates and Pass@k of the SFT BASELINE, STARPO and CIA as well as two large API models on a held-out test set. Across both model sizes,CIA consistently outperforms all baselines.

Method	Mean@8±std	Pass@8
BASELINE (1.7B)	9.97% ± 1.04%	32.03%
STARPO	16.54%± 1.32%	45.73%
CIA (ours)	**24.80%** ± 1.10%	**53.10%**
BASELINE (4B)	13.34% ± 1.05%	36.87%
STARPO	24.36% ± 1.18%	59.12%
CIA (ours)	**33.72%** ± 1.26%	**63.97%**
DeepSeek-V3.2	14.35% ± 0.87%	47.34%
Qwen3-235B-Instr.	8.83% ± 0.87%	27.71%

(G=16, temperature 1.0) with LoRA (rank 64, α=64, LR 3×10^{-5}) on 2 NVIDIA H100 GPUs (one training the Questioner model, one for inference with the user simulator). The complete details are in Appendix E, F.

Evaluation We compare ΔBelief-RL against the state of the art method for multi-turn settings, StarPO (Wang et al., 2025) which performs trajectory-level GRPO. We report results on a held-out 20 Questions test set, as well as out of distribution information-seeking tasks and benchmarks for two applications: customer service and user personalization.

5 RESULTS: ΔBELIEF-RL TRAINING IMPROVES INTERACTION-EFFICIENCY

ΔBelief-RL evokes information-seeking. Our framework, ΔBelief-RL, substantially improves information-seeking performance over both, standard GRPO and SFT, baselines. On the 20Qs test set, our agent, CIA, outperforms the SFT policy by **14.83%** and **20.38%** for the 1.7B and 4B models, respectively (Table 1). Relative to standard multi-turn GRPO (STARPO), it yields absolute improvements of **8.26%** and **9.36%**, indicating that the ΔBelief signal provides a meaningful intrinsic objective that improves credit assignment and, in turn, information gathering. These improvements also persist under higher pass@k evaluation, suggesting that the gains are not an artifact of a single sampled interaction. Finally, our trained CIA outperforms much larger inference-time baselines (`DeepSeek-V3.2` and `Qwen3-235B-A22B-Instruct-2507`) by **19.37%** and **24.89%** (4B model size), respectively, despite using ~98% fewer parameters. The relatively low performance of these massive models further underscores the difficulty of our curated test set compared to prior benchmarks.

ΔBelief reward promotes efficient exploration. While both standard-GRPO and ΔBelief-RL incorporate an explicit per-turn efficient exploration penalty (see Section 3.2), their exploratory

Figure 4: Training dynamics. Mean number of questions per episode (top) and mean fraction of repeated questions (bottom) during RL training (lower is better). Across both `Qwen3-1.7B` and `Qwen3-4B`, ΔBelief-RL reduces turns required and suppresses redundant queries more rapidly than standard GRPO (STARPO).

Figure 5: Belief-update dynamics. Normalized elicited log-probability of the correct concept as a function of interactions for 1.7B (top) and 4B (bottom). At 4B, CIA shows the strongest sustained belief updates; at 1.7B, trained variants track the SFT baseline closely.

behaviors differ significantly. Our results show that ΔBelief-RL yields a faster reduction in both repeated inquiries and total questions per episode (Fig. 4). This suggests that the ΔBelief reward does not merely reinforce success, but actively encourages higher-information queries. By maximizing belief updates, the agent learns to resolve uncertainty with fewer interactions, beyond what a simple trajectory-length penalty can achieve.

ΔBelief-RL leads to faster belief updates. We investigate whether our training framework significantly shifts the belief update patterns compared to the initial SFT policy. On the 4B scale, ΔBelief-RL (CIA) demonstrates the largest and most sustained increase in belief updates between interactions, while STARPO remains closely aligned with the baseline policy. In contrast, no observable differences appear on the 1.7B scale (Fig. 5). These results suggest that our framework is particularly effective for models with more calibrated internal world models, as it results in more pronounced belief shifts.

ΔBelief-RL improves pass@k success rates at high k. A common critique of RL post-training in language models is its tendency toward 'policy sharpening,' wherein the model primarily increases pass@1 performance, upweighing existing successful trajectories. To determine whether ΔBelief-RL also improves exploration, we perform a low-variance pass@k analysis (Chen et al., 2021). Our results show that CIA maintains a consistent advantage over the SFT baseline policy even at high k values (up to 128) (Fig. 7). Our intrinsic credit assignment strategy reinforces good actions, penalizing bad ones, lead to compounding benefits over long trajectories.

5.1 ABLATIONS

Generalization to stronger user simulators. Real-world deployments require agents to interact with a wide range of users whose response distributions differ from the training environment. To ensure that our agent does not overfit to the training simulator, we evaluate it to interact with a diverse set of stronger answerers. We swap the training answerer (`Qwen3-14B`) for significantly larger API models at test time and disable auxiliary software verifications. We find

Table 2: Generalization to stronger user simulators. Success rates (Mean@8) when evaluating agents with a different user simulator from the one used during training. Both the BASELINE and CIA are trained using `Qwen3-4B` as the base model and `Qwen3-14B` as the user simulator. Test-time performance remains similar on other user simulator models.

Answerer	Baseline	CIA
`Qwen3-14B` (train)	13.34%	35.65%
`Qwen3-235B-Instr.`	17.49%	31.18%
`DeepSeek-v3.2`	16.48%	37.64%

Figure 6: Ablation of the reward weight λ. Training success rate for CIA-4B across various weightings. Moderate values ($\lambda \in \{0.05, 0.1\}$) optimize learning, while excessive weighting harms convergence.

Figure 7: Pass@k on Twenty Questions. Pass@k vs. k for 1.7B (left) and 4B (right). CIA consistently outperforms the Baseline.

that the success rates remain robust for all these changes (Table 2). This confirms that our training does not rely on specific artifacts of the training-phase user simulator.

Balancing intrinsic and verifiable rewards. We investigate the weighting term trade-off between the verifiable end-of-game reward and ΔBelief reward. As shown in Fig. 6, training collapses when $\lambda \geq 0.5$. While lower values ($\lambda = 0.05$) allow for stable learning, we find that a moderate weight of $\lambda = 0.1$ yields the best validation performance. Since ΔBelief is unbounded while r^{eog} remains within a fixed range, the optimal λ serves to align the magnitudes of the two signals, ensuring a balanced training objective.

6 GENERALIZATION AND APPLICATIONS

In this section, we evaluate the generalization of CIA across three dimensions: (i) interaction scaling, assessing whether performance improves with additional inference-time turns (Sec. 6.1); (ii) task robustness, testing generalization to out-of-distribution benchmarks (Sec. 6.2); and (iii) practical transfer, evaluating performance on simulated environments designed to mirror real-world applications (Sec. 6.3).

6.1 TEST-TIME INTERACTION SCALING

Success scales with increased interaction budget. During training, episodes are strictly limited to 20 turns. Here, we investigate whether the agent's information-seeking capabilities generalize to longer interactions. By increasing the interaction budget to 50 turns in Fig. 8, we observe that CIA sustains large performance gains. This is especially pronounced at the 4B scale, where CIA achieves a STARPO 26% higher (absolute) success rate at the 50-turn mark. These

Figure 8: Test-time interaction scaling. Average success rate as a function of the interaction budget, increased up to 50 turns, for 1.7B models (top) and 4B models (bottom). Our model, CIA, exhibits larger performance gains within the standard 20-interaction regime and continues to improve as the interaction budget is extended than both STARPO and the Baseline SFT policy.

results suggest that belief-based rewards do more than improve within-budget efficiency; they foster teach general information-seeking strategies that continue to resolve uncertainty as more evidence becomes available.

6.2 OUT-OF-DISTRIBUTION GENERALIZATION

We evaluate out-of-distribution (OOD) generalization using three distinct tasks: *Guess My City* and *Murder Mystery* (Tajwar et al., 2025). Further details regarding environment configurations and their corresponding prompts are available in Appendices B and C, respectively.

Figure 9: Practical applications. Mean score on the test-set for the OOD *User Personalization* and *Customer Service* benchmarks. Across both sizes, CIA strongly outperforms STARPO.

Figure 10: OOD generalization. Pass@k on two out-of-distribution benchmarks (*Guess My City* and *Murder Mystery*). Dark bars: Pass@1; lighter increment: Pass@8.

Generalization to held-out tasks. Our CIA agent exhibits robust generalization, consistently surpassing SFT and STARPO baselines across all tested environments (Figure 10). These gains are most pronounced in the 4B CIA model, which maintains a significant performance lead over all competing methods.

On *Guess My City*, we observe a similar pass@1 advantage for CIA over STARPO (3.6% for 1.7B and 12.6% for 4B). Unlike the other benchmarks, the performance gap narrows at higher k values. This is likely due to the task's lower complexity; once the agent identifies the correct country, the remaining hypothesis space of cities is relatively small. Furthermore, the high SFT performance suggests this task's structure closely mirrors the 20-questions format of the training data. Qualitatively, CIA adopts a more efficient "top-down" strategy, asking abstract questions about city characteristics, whereas STARPO and SFT rely on simple, brute-force queries of specific locations (Appendix A.2.2).

The *Murder Mystery* task requires the evaluated model to solve a crime, having access to an oracle that can provide information upon request. On this task, CIA achieves its most significant gains over STARPO, with a lead of 24.5% (1.7B) and 28.5% (4B) at pass@1, as can be observed in Fig. 10. Performance at pass@k saturates quickly across all 4B models because the hypothesis space is inherently small, with only five suspects per task. Consequently, while pass@8 results are less discriminative due to the high probability of a successful random guess, the pass@1 rate provides a more accurate reflection of the agent's reasoning quality. For detailed example rollouts, see Appendix A.2.5.

6.3 GENERALIZATION TO PRACTICAL APPLICATIONS

To further test the OOD generalization capabilities of our methodology, we evaluate CIA on settings that mirror practical applications more closely than the previously presented benchmarks. We evaluate CIA against the aforementioned SFT and STARPO baselines on the STaR-GATE dataset Andukuri et al. (2024) (which we refer to as *User Personalization*), and on the *Customer Service* task (Tajwar et al., 2025). As aforementioned, further details regarding environment configurations and their corresponding prompts are available in Appendices B and C, respectively.

The *User Personalization* environment consists of multi-turn interactions between a user and the language model: the evaluated model must strategically elicit latent user preferences and background context through iterative questioning before delivering a final, informed response. Our results, summarized in Fig. 9, provide further evidence of CIA exhibiting enhanced information-seeking abilities across both model sizes, which translate into higher-quality user-alignment on this task; CIA offers upto 15% improvements over existing methods.

On *Customer Service*, we observe a substantial gap in pass@1 performance: CIA outperforms STARPO by 5.06% (1.7B) and 11.13% (4B). This gap widens at higher k values, suggesting that CIA possesses superior information-seeking capabilities. Qualitative comparisons of agent rollouts (Appendix A.2.3) support this quantitative observation. In this task, the agent must identify a broken functionality and suggest solutions. While all agents attempt to gather information, their strategies differ starkly: the SFT agent provides an exhaustive but undirected list of questions; the STARPO agent is more directed but frequently becomes "side-tracked" by irrelevant concepts; in contrast,

CIA demonstrates true **information-seeking** by dynamically adjusting its inquiries based on user responses to home in on the target problem.

7   RELATED WORK

Intrinsic Rewards for RL   Long-horizon RL suffers from sparse, trajectory-level rewards, making credit assignment difficult. A first line of work introduces dense supervision by training process reward models (PRMs) that rate intermediate steps Uesato et al. (2023); Lightman et al. (2024). However, PRMs rely on expensive step-level supervision and can be exploited through reward over-optimization. Others replace learned dense rewards with verifiers, either by using an LLM-as-a-judge Madaan et al. (2023) or by leveraging executable environment signals like unit tests Gao et al. (2023). Recent work further strengthens tool-based verification and turn-level credit assignment in multi-turn coding settings Jin et al. (2025). All these works focus on domains where the quality of actions can be checked automatically, such as mathematics and coding.

In absence of programmatic checks for success, recent work explores verifier-free RL by deriving intrinsic rewards from the model's own probabilities. For example, Liu et al. (2025) uses reasoning perplexity as reward, while Zhou et al. (2025) maximizes the conditional likelihood of the reference answer. Yoon et al. (2025) follows the same principle, but breaks the conditional reasoning trace into intermediate steps. Similarly, RLP proposes a dense information-gain–inspired reward for reinforcement-style pretraining Hatamizadeh et al. (2025). Existing methods primarily operationalize such signals at the sequence level; in contrast, our work proposes measuring belief updates at the interaction level and using them as an intrinsic reward for RL.

Multi-Turn Interaction   The game of 20Qs was first used as a benchmark to evaluate knowledge capabilities of off-the-shelf LMs to answer binary questions De Bruyn et al. (2022a;b). Subsequent work shifted the focus towards positioning the LM as the *questioner* to evaluate information-seeking behaviorAbdulhai et al. (2023). Along this line, numerous variants of 20Qs have been proposed, targeting evaluation at inference time, offline fine-tuning, or online RL. Inference-only studies examine performance under incomplete information Chen et al. (2024), model similarity Richardeau et al. (2024), model conversational reasoning and planning capabilities Zhang et al. (2024) and using Bayesian Experimental Design Choudhury et al. (2025).

Offline fine-tuning approaches primarily aim to improve the questioning policy via preference-based optimization Tajwar et al. (2025); Mazzaccara et al. (2024). To the best of our knowledge, only two prior works utilize 20Qs as an interactive user-simulation environment for online RL training Zhou et al. (2024); Yang et al. (2025). However, both suffer from contamination issues: they lack held-out validation and test sets, and training is restricted to a vocabulary of 157 words. Our 20Qs environment addresses these limitations by introducing explicitly separated datasets for SFT training, RL training, validation, and testing (see Sec.4).

8   CONCLUSION AND DISCUSSION

In this work, we demonstrate that an agent's internal belief shifts can effectively guide learning in long-horizon tasks. By providing fine-grained credit assignment for intermediate actions, ΔBelief-RL significantly enhances learning efficiency. ΔBelief-RL does this in a computationally efficient manner, measuring the contribution of individual actions without separate critic or reward models, with the relatively inexpensive step of measuring log-probabilities on the correct outcome. We train with ΔBelief-RL on the 20Qs task to teach models effective information-seeking; consequently, our CIA models at the 1.7B-4B scale not only outperform prior SoTA methods for multi-turn training, but also much larger 670B models. Notably, improved performance generalizes to extended interaction horizons and diverse out-of-distribution applications.

Limitations   While we show ΔBelief-RL is effective for information-seeking, it remains to be seen how broadly it can be applied. For tasks with multiple viable solutions, optimizing beliefs against a single reference may restrict output diversity. Future work can study whether log-probabilities over a fixed reference accurately reflect model beliefs across more subjective tasks. Finally, our approach currently relies on supervised references during training, which may not be available for all domains.

Addressing these constraints offers a path toward open-ended learning over a long-horizon. Much like humans evaluate actions internally by judging progress towards their goals, future advancements in belief calibration may allow agents to train in isolation from external verification. Because ΔBelief-RL is agnostic to the underlying RL algorithm, it remains a versatile framework for this continued exploration across diverse domains and architectures, representing a significant step toward agents capable of navigating complex, uncertain environments.

ACKNOWLEDGMENTS

Special thanks to Susanne Keller and Jonas Geiping for help and feedback on early directions. The authors thank (in alphabetical order): Arvindh Arun, Hardik Bhatnagar, Nikhil Chandak, Hallerite, Matthias Kümmerer, and Vishaal Udandarao for valuable feedback on the project.

IA, JS, AP, and MB acknowledge support by the Tübingen AI Center. JS and SH thanks the International Max Planck Research School for Intelligent Systems (IMPRS-IS) for support. SH and AP acknowledge funding by the Federal Ministry of Research, Technology and Space (BMFTR), FKZ: 16IS24085B. AP and MB acknowledge Coefficient Giving funded by the Good Ventures Foundation. MB acknowledges funding by the Federal Ministry of Research, Technology and Space (BMFTR), FKZ: 16IS24079A. MB is a member of the Machine Learning Cluster of Excellence, funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy – EXC number 2064/1 – Project number 390727645.

ETHICS STATEMENT

This work advances the field of Machine Learning by introducing a scalable RL post-training framework for long-horizon information-seeking. Our method improves the learning efficiency of AI agents in partial-information environments. We hope more capable information-seeking agents lead to improved decision-making, but at the present stage there are no specific ethical concerns or negative consequences unique to this work worth highlighting.

REFERENCES

Marwa Abdulhai, Isadora White, Charlie Snell, Charles Sun, Joey Hong, Yuexiang Zhai, Kelvin Xu, and Sergey Levine. LMRL Gym: Benchmarks for Multi-Turn Reinforcement Learning with Language Models, 2023. URL https://arxiv.org/abs/2311.18232.

Chinmaya Andukuri, Jan-Philipp Fränken, Tobias Gerstenberg, and Noah Goodman. STar-GATE: Teaching language models to ask clarifying questions. In *First Conference on Language Modeling*, 2024. URL https://openreview.net/forum?id=CrzAj0kZjR.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code. 2021.

Yuyan Chen, Yueze Li, Songzhou Yan, Sijia Liu, Jiaqing Liang, and Yanghua Xiao. Do large language models have problem-solving capability under incomplete information scenarios? In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 2225–2238, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.131. URL https://aclanthology.org/2024.findings-acl.131/.

François Chollet. On the measure of intelligence, 2019. URL https://arxiv.org/abs/1911.01547.

Deepro Choudhury, Sinead Williamson, Adam Goliński, Ning Miao, Freddie Bickford Smith, Michael Kirchhof, Yizhe Zhang, and Tom Rainforth. BED-LLM: Intelligent information gathering with LLMs and bayesian experimental design. *arXiv preprint arXiv:2508.21184*, 2025.

Maxime De Bruyn, Ehsan Lotfi, Jeska Buhmann, and Walter Daelemans. Is It Smaller Than a Tennis Ball? Language Models Play the Game of Twenty Questions. In Jasmijn Bastings, Yonatan Belinkov, Yanai Elazar, Dieuwke Hupkes, Naomi Saphra, and Sarah Wiegreffe (eds.), *Proceedings of the Fifth BlackboxNLP Workshop on Analyzing and Interpreting Neural Networks for NLP*, pp. 80–90, Abu Dhabi, United Arab Emirates (Hybrid), December 2022a. Association for Computational Linguistics. doi: 10.18653/v1/2022.blackboxnlp-1.7. URL https://aclanthology.org/2022.blackboxnlp-1.7/.

Maxime De Bruyn, Ehsan Lotfi, Jeska Buhmann, and Walter Daelemans. 20Q: Overlap-Free World Knowledge Benchmark for Language Models. In Antoine Bosselut, Khyathi Chandu, Kaustubh Dhole, Varun Gangal, Sebastian Gehrmann, Yacine Jernite, Jekaterina Novikova, and Laura Perez-Beltrachini (eds.), *Proceedings of the 2nd Workshop on Natural Language Generation, Evaluation, and Metrics (GEM)*, pp. 494–508, Abu Dhabi, United Arab Emirates (Hybrid), December 2022b. Association for Computational Linguistics. doi: 10.18653/v1/2022.gem-1.46. URL https://aclanthology.org/2022.gem-1.46/.

Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. PAL: program-aided language models. In *Proceedings of the 40th International Conference on Machine Learning*, ICML'23. JMLR.org, 2023.

Gemini Team. Introducing Gemini 2.0: our new ai model for the agentic era, December 2024. URL https://blog.google/technology/google-deepmind/google-gemini-ai-update-december-2024/. Accessed: 2025-05-22.

Gabriel Grand, Valerio Pepe, Jacob Andreas, and Joshua B Tenenbaum. Shoot First, Ask Questions Later? Building Rational Agents that Explore and Act Like People. *arXiv preprint arXiv:2510.20886*, 2025.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, Bing Xue, Bingxuan Wang, Bochao Wu, Bei Feng, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chong Ruan, Damai Dai, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Hanwei Xu, Honghui Ding, Huazuo Gao, Hui Qu, Hui Li, Jianzhong Guo, Jiashi Li, Jingchang Chen, Jingyang Yuan, Jinhao Tu, Junjie Qiu, Junlong Li, J. L. Cai, Jiaqi Ni, Jian Liang, Jin Chen, Kai Dong, Kai Hu, Kaichao You, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Liang Zhao, Litong Wang, Liyue Zhang, Lei Xu, Leyi Xia, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingxu Zhou, Meng Li, Miaojun Wang, Mingming Li, Ning Tian, Panpan Huang, Peng Zhang, Qiancheng Wang, Qinyu Chen, Qiushi Du, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, R. J. Chen, R. L. Jin, Ruyi Chen, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shengfeng Ye, Shiyu Wang, Shuiping Yu, Shunfeng Zhou, Shuting Pan, S. S. Li, Shuang Zhou, Shaoqing Wu, Tao Yun, Tian Pei, Tianyu Sun, T. Wang, Wangding Zeng, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, W. L. Xiao, Wei An, Xiaodong Liu, Xiaohan Wang, Xiaokang Chen, Xiaotao Nie, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuheng Lin, X. Q. Li, Xiangyue Jin, Xiaojin Shen, Xiaosha Chen, Xiaowen Sun, Xiaoxiang Wang, Xinnan Song, Xinyi Zhou, Xianzu Wang, Xinxia Shan, Y. K. Li, Y. Q. Wang, Y. X. Wei, Yang Zhang, Yanhong Xu, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Wang, Yi Yu, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yuan Ou, Yuduan Wang, Yue Gong, Yuheng Zou, Yujia He, Yunfan Xiong, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Y. X. Zhu, Yanping Huang, Yaohui Li, Yi Zheng, Yuchen Zhu, Yunxian Ma, Ying Tang, Yukun Zha, Yuting Yan, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhicheng Ma, Zhigang Yan, Zhiyu Wu, Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Zizheng Pan, Zhen Huang, Zhipeng Xu, Zhongyu Zhang, and Zhen

Zhang. DeepSeek-R1 incentivizes reasoning in LLMs through reinforcement learning. *Nature*, 645(8081):633–638, September 2025. ISSN 1476-4687. doi: 10.1038/s41586-025-09422-z. URL http://dx.doi.org/10.1038/s41586-025-09422-z.

Ali Hatamizadeh, Syeda Nahida Akter, Shrimai Prabhumoye, Jan Kautz, Mostofa Patwary, Mohammad Shoeybi, Bryan Catanzaro, and Yejin Choi. RLP: Reinforcement as a Pretraining Objective. 2025. URL https://arxiv.org/abs/2510.01265.

Yiyang Jin, Kunzhao Xu, Hang Li, Xueting Han, Yanmin Zhou, Cheng Li, and Jing Bai. ReVeal: Self-Evolving Code Agents via Iterative Generation-Verification. *arXiv preprint arXiv:2506.11442*, 2025.

Thomas Kwa, Ben West, Joel Becker, Amy Deng, Katharyn Garcia, Max Hasin, Sami Jawhar, Megan Kinniment, Nate Rush, Sydney Von Arx, Ryan Bloom, Thomas Broadley, Haoxing Du, Brian Goodrich, Nikola Jurkovic, Luke Harold Miles, Seraphina Nix, Tao Lin, Neev Parikh, David Rein, Lucas Jun Koba Sato, Hjalmar Wijk, Daniel M. Ziegler, Elizabeth Barnes, and Lawrence Chan. Measuring AI Ability to Complete Long Tasks, 2025. URL https://arxiv.org/abs/2503.14499.

Philippe Laban, Hiroaki Hayashi, Yingbo Zhou, and Jennifer Neville. LLMs Get Lost In Multi-Turn Conversation, 2025. URL https://arxiv.org/abs/2505.06120.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's Verify Step by Step. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=v8L0pN6EOi.

Wei Liu, Siya Qi, Xinyu Wang, Chen Qian, Yali Du, and Yulan He. NOVER: Incentive training for language models via verifier-free reinforcement learning. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 7439–7458, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.378. URL https://aclanthology.org/2025.emnlp-main.378/.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-Refine: Iterative Refinement with Self-Feedback. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=S37hOerQLB.

Davide Mazzaccara, Alberto Testoni, and Raffaella Bernardi. Learning to ask informative questions: Enhancing LLMs with preference optimization and expected information gain. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 5064–5074, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.291. URL https://aclanthology.org/2024.findings-emnlp.291/.

Jean-Baptiste Michel, Yuan Kui Shen, Aviva Presser Aiden, Adrian Veres, Matthew K. Gray, The Google Books Team, Joseph P. Pickett, Dale Hoiberg, Dan Clancy, Peter Norvig, Jon Orwant, Steven Pinker, Martin A. Nowak, and Erez Lieberman Aiden. Quantitative analysis of culture using millions of digitized books. *Science*, 331(6014):176–182, 2011. doi: 10.1126/science.1199644. URL https://www.science.org/doi/abs/10.1126/science.1199644.

Tejal Patwardhan, Rachel Dias, Elizabeth Proehl, Grace Kim, Michele Wang, Olivia Watkins, Simón Posada Fishman, Marwan Aljubeh, Phoebe Thacker, Laurance Fauconnet, Natalie S. Kim, Patrick Chao, Samuel Miserendino, Gildas Chabot, David Li, Michael Sharman, Alexandra Barr, Amelia Glaese, and Jerry Tworek. GDPval: Evaluating AI Model Performance on Real-World Economically Valuable Tasks, 2025. URL https://arxiv.org/abs/2510.04374.

Gurvan Richardeau, Erwan Le Merrer, Camilla Penzo, and Gilles Tredan. The 20 questions game to distinguish large language models. *arXiv preprint arXiv:2409.10338*, 2024.

Samuel Schmidgall, Yusheng Su, Ze Wang, Ximeng Sun, Jialian Wu, Xiaodong Yu, Jiang Liu, Michael Moor, Zicheng Liu, and Emad Barsoum. Agent laboratory: Using LLM agents as research assistants. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 5977–6043, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.320. URL https://aclanthology.org/2025.findings-emnlp.320/.

Richard S Sutton and Andrew G Barto. *Reinforcement Learning: An Introduction*. MIT Press, 2nd edition, 2018.

Fahim Tajwar, Yiding Jiang, Abitha Thankaraj, Sumaita Sadia Rahman, J Zico Kolter, Jeff Schneider, and Russ Salakhutdinov. Training a generally curious agent. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=UeB3Hdrhda.

Top English Wordlists. https://github.com/david47k/top-english-wordlists. Accessed: 2025-07-15.

Jonathan Uesato, Nate Kushman, Ramana Kumar, H. Francis Song, Noah Yamamoto Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving Math Word Problems with Process-based and Outcome-based Feedback, 2023. URL https://openreview.net/forum?id=MND1kmmNy0O.

Zihan Wang, Kangrui Wang, Qineng Wang, Pingyue Zhang, Linjie Li, Zhengyuan Yang, Xing Jin, Kefan Yu, Minh Nhat Nguyen, Licheng Liu, et al. Ragen: Understanding self-evolution in llm agents via multi-turn reinforcement learning. *arXiv preprint arXiv:2504.20073*, 2025.

Archana Warrier, Dat Nguyen, Michelangelo Naim, Moksh Jain, Yichao Liang, Karen Schroeder, Cambridge Yang, Joshua B. Tenenbaum, Sebastian Vollmer, Kevin Ellis, and Zenna Tavares. Benchmarking world-model learning, 2025. URL https://arxiv.org/abs/2510.19788.

xAI. Grok 3 mini. Model description, xAI, 2025. URL https://x.ai/news/grok-3. "Lightweight reasoning model" with 131,072 token context window; trained for mathematics, coding, agentic tasks.

Ruihan Yang, Yikai Zhang, Aili Chen, Xintao Wang, Jiangjie Chen, Siyu Yuan, Deqing Yang, and Yanghua Xiao. ARIA: Training language agents with intention-driven reward aggregation. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=eumRwpgdMU.

Eunseop Yoon, Hee Suk Yoon, Jaehyun Jang, SooHwan Eom, Qi Dai, Chong Luo, Mark A Hasegawa-Johnson, and Chang D Yoo. PACR: Progressively Ascending Confidence Reward for LLM Reasoning. *arXiv preprint arXiv:2510.22255*, 2025.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Wang Zhang, Hang Zhu, Jinhua Zhu, Jiaze Chen, Jiangjie Chen, Chengyi Wang, Hongli Yu, Yuxuan Song, Xiangpeng Wei, Hao Zhou, Jingjing Liu, Wei-Ying Ma, Ya-Qin Zhang, Lin Yan, Mu Qiao, Yonghui Wu, and Mingxuan Wang. DAPO: An Open-Source LLM Reinforcement Learning System at Scale, 2025. URL https://arxiv.org/abs/2503.14476.

Siliang Zeng, Quan Wei, William Brown, Oana Frunza, Yuriy Nevmyvaka, Yang Katie Zhao, and Mingyi Hong. Reinforcing multi-turn reasoning in LLM agents via turn-level credit assignment. In *ICML 2025 Workshop on Computer Use Agents*, 2025. URL https://openreview.net/forum?id=h83vIG5Hre.

Yizhe Zhang, Jiarui Lu, and Navdeep Jaitly. Probing the multi-turn planning capabilities of LLMs via 20 question games. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1495–1516, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.82. URL `https://aclanthology.org/2024.acl-long.82/`.

Xiangxin Zhou, Zichen Liu, Anya Sims, Haonan Wang, Tianyu Pang, Chongxuan Li, Liang Wang, Min Lin, and Chao Du. Reinforcing General Reasoning without Verifiers. *arXiv preprint arXiv:2505.21493*, 2025.

Yifei Zhou, Andrea Zanette, Jiayi Pan, Sergey Levine, and Aviral Kumar. ArCHer: Training language model agents via hierarchical multi-turn RL. In *Forty-first International Conference on Machine Learning*, 2024. URL `https://openreview.net/forum?id=b6rA0kAHT1`.

A   ADDITIONAL RESULTS

A.1   ABLATIONS: TWENTY QUESTIONS

A.1.1   PER-TURN REWARD COMPOSITION

We study the effects of the different signals that compose the per-turn reward r_t to provide the most informative and task-correlated guidance to models during training. As we can observe in Fig. 11a, higher success rates on the training set are obtained when all proposed signals are combined to compose r_t. Among all signals we employ to improve the stability of training, we notice that the constant penalty applied to each turn, that was mainly added to improve efficiency, has the most significant impact. The scales hyper-parameters for each individual that we use in our experiments are detailed in Table 11b; notice that the raw values of ΔBelief_t range approximately from -22 to 24.

Reward Signal	Scale
r^{eog}	2.00
r^{traj}	-0.05
r^{rep}	-1.00
r^{inv}	-5.00

(a) **Comparison of different r_t formulations.**   (b) **Scale hyper-parameter of each reward signal.**

Figure 11: Ablations for per-turn reward composition (b) with scaling hyperparameters for individual signals summarized in (a). We report the success rate on the training set across training steps for different per-turn reward r_t compositions.

A.1.2   KL-DIVERGENCE LOSS TERM

Additionally, we examine the effect of the KL-divergence loss term commonly used in GRPO formulations in our setting. We find that constraining the trained model to the reference policy via the KL-divergence penalty does not have a noticeable effect on training dynamics, as we can observe in Fig. 12.

Figure 12: Ablation study on KL penalty. We compare the success rates on the training-set across training steps or loss formulations containing a KL-divergence term or not

A.1.3 DIFFERENT ΔBELIEF NORMALISATION EFFECTS

Different normalization effects on ΔBelief reward As ΔBelief reward is unbounded, appropriate normalization is crucial for stable optimization. We therefore compare several normalization schemes: *naive* (no normalization), *tanh* squashing, *ReLU* (positive-only shaping), *EMA* normalization using a lagged reference policy to reduce reward over-optimization (Hatamizadeh et al., 2025), and *PACR*, which restricts to the positive domain and applies min–max scaling (Yoon et al., 2025). As shown in Fig. 13 right, naive, EMA, and tanh lead to noticeably worse training dynamics. Naive and EMA introduce large-magnitude (often negative) updates that can dominate the verifiable reward and destabilize learning, while tanh overly compresses the signal and removes informative variation. In contrast, ReLU yields the most stable and highest-performing training. PACR performs comparably but slightly worse than ReLU, suggesting that restricting the intrinsic signal to positive rewards is beneficial, whereas additional min–max scaling can distort the relative informativeness of belief updates.

Figure 13: Ablation of ΔBelief reward normalization. Training success rate under different normalization schemes. Non-negative shaping (ReLU) yields the most stable and highest performance.

A.1.4 MAIN RESULTS INCLUDING INSTRUCT MODEL

Table 3: Success Rate on the Test Set. Performance on the held-out test set including the `Qwen3` models that were used to train our agents.

Method	Mean@8±std	Pass@8
`Qwen3-1.7B`	$0.00\% \pm 0.00\%$	0.00%
+ SFT	$9.97\% \pm 1.04\%$	32.03%
+ SFT& GRPO (STARPO)	$16.54\% \pm 1.32\%$	45.73%
CIA (ours)	$\mathbf{24.80\%} \pm 1.10\%$	**53.10%**
`Qwen3-4B`	$5.02\% \pm 0.60\%$	15.94%
+ SFT	$13.34\% \pm 1.05\%$	36.87%
+ SFT& GRPO (STARPO)	$24.36\% \pm 1.18\%$	59.12%
+ CIA (ours)	$\mathbf{35.65\%} \pm 2.04\%$	**66.05%**
`DeepSeek-V3.2`	$14.35\% \pm 0.87\%$	47.34%
`Qwen3-235B-A22B-Instruct 2507`	$8.83\% \pm 0.87\%$	27.71%

A.2 EXAMPLE INTERACTIONS

A.2.1 TWENTY QUESTIONS

Example interactions for target concept *honeycrisp*.

Example of CIA(1.7B) interactions:

> **Questioner**
> Is the secret word a physical object?

>> **Judge**
>> Yes

> **Questioner**
> Is the secret word something typically found in nature, like a plant, animal, or natural phenomenon?

>> **Judge**
>> Yes

> **Questioner**
> Is the secret word related to a specific type of plant, like a tree, flower, or vegetable?

>> **Judge**
>> Yes

> **Questioner**
> Is the secret word a type of tree or large plant, like a big tree or a fruit tree?

>> **Judge**
>> Yes

> **Questioner**
> Is the secret word a type of tree, like an oak, maple, or pine?

>> **Judge**
>> No

> **Questioner**
> Is the secret word related to a fruit or vegetable, like an apple, banana, or grape?

>> **Judge**
>> Yes

Questioner

Is the secret word related to a fruit commonly eaten by humans, like an apple, banana, or orange?

Judge

Yes

Questioner

Is the secret word a type of berry, like an apple, cherry, or strawberry?

Judge

No

Questioner

Is the secret word related to an orange or grapefruit, like an orange, grape, or lemon?

Judge

No

Questioner

Is the secret word related to an apple or pear, like an apple, peach, or plum?

Judge

Yes

Questioner

Is the secret word specifically an apple, like a red apple, green apple, or cider apple?

Judge

Yes

Questioner

Is the secret word a type of apple that is commonly associated with the word "pearl", like a ruby or diamond, such as a ruby apple or diamond apple?

Judge

No

Questioner

Is the secret word an apple variety that is known for its color, like an red apple, green apple, or golden apple?

Judge

Yes

Questioner

Is the secret word a type of apple that is typically eaten directly, like a common apple, rather than used in cooking or as a fruit for cider?

Judge

Yes

Questioner

Is the secret word a type of red apple, like a Granny Smith or a Fuji apple?

Judge

Yes

Questioner

Is the secret word a type of apple that is commonly associated with a specific country or region, like an apple from the United States, Europe, or China?

Judge

Yes

Questioner

Is the secret word a type of apple that is known for being a dessert fruit, like a dessert apple or a pomme de terre apple?

Judge

Yes

Questioner

Is the secret word a type of apple that is commonly associated with the United States, like an apple from Washington or a Delaware apple?

Judge

Yes

Questioner

Is the secret word a type of apple that is commonly associated with the term "crisp", like a crisp apple or a tart apple?

Judge

Yes

Questioner

Is the secret word a type of apple that is known for being sweet, like a Fuji apple or a Honeycrisp apple?

> **Judge**
> Finished

Example of CIA(4B) interactions:

> **Questioner**
> Is the word a concrete object, like a physical thing you can touch or hold?

> **Judge**
> Yes

> **Questioner**
> Is the object something that is manmade, like a tool, building, or item used in daily life?

> **Judge**
> No

> **Questioner**
> Is the object a natural thing found in nature, like a plant, animal, or geological feature such as a rock or mountain?

> **Judge**
> Yes

> **Questioner**
> Is the object a type of plant, such as a tree, flower, grass, or vegetable?

> **Judge**
> Yes

> **Questioner**
> Is the plant a type of tree, such as an oak, pine, maple, or apple tree?

> **Judge**
> No

> **Questioner**
> Is the plant a type of flower, such as rose, tulip, daisy, or lotus?

> **Judge**
> No

> **Questioner**
> Is the plant a type of grain or crop, such as wheat, rice, corn, or potato?

Judge
No

Questioner
Is the plant a type of leafy vegetable, such as lettuce, spinach, cabbage, or tomato?

Judge
No

Questioner
Is the plant a type of fruit, such as apple, banana, orange, or grape?

Judge
Yes

Questioner
Is the fruit an apple, pear, or orange?

Judge
Yes

Questioner
Is the fruit a banana?

Judge
No

Questioner
Is the fruit a grape, such as red or green grape?

Judge
No

Questioner
Is the fruit a peach, plum, or cherry?

Judge
No

Questioner
Is the fruit a pineapple, mango, or kiwi?

Judge
No

Questioner
Is the fruit a pear or a tangerine or lemon or lime or grapefruit or cherry?

> **Judge**
> No

Questioner
Is the fruit a cherry, such as a sweet cherry or a black cherry?

> **Judge**
> No

Questioner
Is the fruit a red apple, such as a Granny Smith, Gala, or Red Delicious apple?

> **Judge**
> No

Questioner
Is the fruit an orange, such as a sweet orange or a blood orange?

> **Judge**
> No

Questioner
Is the fruit a honeycrisp apple, or a McIntosh apple, or a cider apple?

> **Judge**
> Finished

A.2.2 GUESS MY CITY

Example interactions for target concept: UJJAIN, INDIA.

Example of CIA(4B) interactions (N=9):

Questioner
Is your home city a major international city, like New York, London, or Paris?

> **Judge**
> No. my city is a historic and religious center, known for its ancient temples and cultural significance.

Questioner
Is your home city located in Asia, specifically in India or another country with a large population of Hindu or Buddhist followers?

Judge
Yes, it is located in a region with a significant population of hindu followers.

Questioner
Is your home city a major religious or cultural center, such as Varanasi, Delhi, or Kolkata, which is known for its temples, festivals, or historical importance?

Judge
Yes, my home city is a significant religious and cultural center, known for its ancient temples, spiritual practices, and historical festivals. it holds great importance in hindu traditions.

Questioner
Is your home city Varanasi, often referred to as Kashi or Benares, which is one of the holiest cities in hinduism and is known for the Ganges River and its ghats?

Judge
No. my city is not varanasi, but it is also a significant religious site in india, known for its ancient temples and spiritual heritage.

Questioner
Is your home city a city in the state of Tamil Nadu, India, known for its rich cultural heritage, temples, and festivals like Pongal or Diwali?

Judge
No. my home city is located in a different state, known for its ancient temples, spiritual significance, and a major festival celebrated during the summer solstice.

Questioner
Is your home city Ayodhya, known for being the birthplace of Lord Rama and the Ramayana epic, and the Kashi Vishwanath Temple?

Judge
No. my city is not ayodhya. it is located in a region with significant historical and religious importance, but it is known for its ancient temples and association with hindu pilgrimage sites.

Questioner
Is your home city a city in the state of Kerala, India, known for its backwaters, temples, and cultural festivals like Onam?

Judge
No. my home city is not in kerala. it is located in a different state known for its ancient temples, historical significance, and a major river that flows through it.

> **Questioner**
> Is your home city a city in the state of Karnataka, India, known for its temples like the Brihadeeswara Temple or the Meenakshi Temple, and for its association with Hindu mythology and art?

> > **Judge**
> > No. my home city is located in a different state and is known for its ancient significance in hindu pilgrimage, particularly associated with the kumbh mela and the mahakaleshwar temple.

> **Questioner**
> Is your home city Ujjain, known as the city of three temples, including the Mandhata Temple, and a major pilgrimage site for hindus, especially during the Kumbh Mela?

> > **Judge**
> > Goal reached

Example of STARPO(4B) interactions (N=16):

> **Questioner**
> Is your home city located in a country in Europe?

> > **Judge**
> > No. my home city is located in a country in asia.

> **Questioner**
> Is your home city located in a country in the Middle East or North Africa?

> > **Judge**
> > No. my home city is located in a country in south asia.

> **Questioner**
> Is your home city located in India?

> > **Judge**
> > Yes

> **Questioner**
> Is your home city located in the state of Maharashtra, India?

> > **Judge**
> > No. it is located in a state known for its historical significance and spiritual heritage.

> **Questioner**
> Is your home city located in the state of Tamil Nadu, India?

Judge
No. my home city is located in a state known for its ancient temples and cultural heritage, but not tamil nadu.

Questioner
Is your home city located in the state of Karnataka, India?

Judge
No. my home city is located in a state known for its historical significance and spiritual heritage, not karnataka.

Questioner
Is your home city located in the state of Kerala, India?

Judge
No. my home city is not in kerala. it is located in central india, near the sacred river kshipra.

Questioner
Is your home city located in the state of Uttar Pradesh, India?

Judge
No. my home city is located in a state known for its historical and religious significance, but not uttar pradesh.

Questioner
Is your home city located in the state of Bihar, India?

Judge
No. my home city is located in a state known for its historical significance and spiritual heritage, but not bihar.

Questioner
Is your home city located in the state of Punjab, India?

Judge
No. my home city is located in a state known for its historical significance and spiritual heritage.

Questioner
Is your home city located in the state of Rajasthan, India?

Judge
No. my home city is located in a state known for its historical significance and spiritual heritage, but not rajasthan.

Questioner
Is your home city located in the state of Haryana, India?

Judge
No. my home city is located in a state known for its historical and religious significance, and it is not haryana.

Questioner
Is your home city located in the state of Madhya Pradesh, India?

Judge
Yes, it is located in the central part of that state, near the kshipra river and known for its ancient temples and spiritual significance.

Questioner
Is your home city located in the city of Varanasi, India?

Judge
No. my city is not located in varanasi. it is situated along the banks of a significant river and is known for its ancient temples and spiritual significance.

Questioner
Is your home city located in the city of Ayodhya, India?

Judge
No. my home city is not ayodhya. it is located in a region known for its ancient temples and spiritual significance, but not associated with the kumbh mela in the same way as another major city nearby.

Questioner
Is your home city located in the city of Ujjain, India?

Judge
Goal reached

Example of Baseline(SFT, 4B) interactions (N=16):

Questioner
Is your city located in North America?

Judge
No. my city is located in a region known for its ancient temples and cultural heritage.

Questioner
Is your city located in Asia?

Judge
Yes, it is located in asia.

Questioner
Is your city located in India?

Judge
No, it is located in a different country.

Questioner
Is your city located in Southeast Asia?

Judge
No. my city is located in central india, near the vindhya range.

Questioner
Is your city located in the state of Maharashtra?

Judge
No. it is located in a state known for its historical significance and spiritual heritage.

Questioner
Is your city located in the state of Tamil Nadu?

Judge
No. my city is located in a state known for its historical significance and religious heritage.

Questioner
Is your city located in the state of Bihar?

Judge
No. my city is located in a state known for its ancient temples and cultural heritage.

Questioner
Is your city located in the state of Orissa?

Judge
No. my city is located in a state known for its historical significance and ancient temples.

Questioner
Is your city located in the state of Andhra Pradesh?

Judge
No. my city is located in a state known for its historical significance and religious heritage.

Questioner
Is your city located in the state of Karnataka?

Judge
No. my city is located in a state known for its historical significance and spiritual heritage.

Questioner
Is your city located in the state of West Bengal?

Judge
No. my city is located in a state known for its historical significance and spiritual heritage.

Questioner
Is your city located in the state of Kerala?

Judge
No. my city is located in a state known for its historical significance and religious heritage.

Questioner
Is your city located in the state of Madhya Pradesh?

Judge
Yes.

Questioner
Is your city located in the central part of Madhya Pradesh?

Judge
Yes, it is situated in the central region of the state.

Questioner
Is your city located near the city of Indore?

Judge
Yes, it is located in the same region as indore.

Questioner
Is your city located in the city of Ujjain?

> **Judge**
> Goal reached

A.2.3 CUSTOMER SERVICE

Example interactions of scenario: '*The customer's car is vibrating excessively, especially at idle*'

With solution: '*The engine mount is worn out, and replacing it will eliminate excessive engine vibration.*'

Example of CIA(4B) interactions (N=10):

> **Questioner**
> Is your car currently running smoothly without any noticeable issues other than the vibration at idle?

> > **Judge**
> > No, the car vibrates a lot when its just idling, like when im stopped at a light. it feels like the whole car shakes.

> **Questioner**
> Is the car a gasoline-powered vehicle, like a car with an engine that runs on gasoline?

> > **Judge**
> > Yes, its a regular gaspowered car.

> **Questioner**
> Is the car a newer model, like from the past 5 years?

> > **Judge**
> > No, its from about 10 years ago.

> **Questioner**
> Is the vibration you're experiencing coming from the engine itself, like the engine is shaking or rattling?

> > **Judge**
> > Yes, it feels like the engine is shaking, especially when im not moving, like at a stoplight.

> **Questioner**
> Is the car's engine oil level low or dirty, and has it been changed recently?

> > **Judge**
> > No, the oil level is fine and i changed it a month ago.

Questioner
Is the car's spark plug or ignition system working properly, and have you checked for any error codes related to the engine?

Judge
No, i havent checked for error codes or looked at the spark plugs. the check engine light isnt on, though.

Questioner
Is the car's fuel system functioning correctly, and is the fuel filter clean or replaced recently?

Judge
No, i havent checked the fuel system or replaced the fuel filter recently. but the car starts fine and runs, so i think its getting fuel okay.

Questioner
Is the car's mass airflow sensor or air filter dirty, and has it been cleaned or replaced?

Judge
No, i havent checked those. i dont think its related to the air filter or sensors.

Questioner
Is the car's transmission or drivetrain related to the vibration, like the clutch or torque converter?

Judge
No, i dont think its related to the transmission or clutch. the car isnt in gear when it vibrates the mostit happens when im just sitting still with the engine running.

Questioner
Is the car's engine mount or engine block damaged or worn out, like a broken or loose mount?

Judge
Goal reached

Example of STARPO(4B) interactions (N=20, failed):

Questioner
Is the car a new vehicle?

Judge
No, its a few years old.

Questioner
Is the car a gasoline-powered vehicle?

> **Judge**
> Yes, its a gasolinepowered car.

Questioner
Is the car a small family car, like a sedan or hatchback?

> **Judge**
> Yes, its a small sedan.

Questioner
Is the car a Japanese brand, like Toyota, Honda, or Mazda?

> **Judge**
> Yes, its a honda.

Questioner
Is the car a Honda Civic?

> **Judge**
> No, its a toyota corolla.

Questioner
Is the car a Volkswagen or Audi?

> **Judge**
> No, its a honda.

Questioner
Is the car a Honda Accord?

> **Judge**
> No, its a toyota camry.

Questioner
Is the car a Honda Odyssey or CR-V?

> **Judge**
> No, its a toyota camry.

Questioner
Is the car a Honda Fit or Pilot?

Judge
No, its a toyota corolla.

Questioner
Is the car a Honda Prelude or Prelude-type?

Judge
No, its a toyota camry.

Questioner
Is the car a Honda CR-Z or K-type?

Judge
No, its a different model.

Questioner
Is the car a Honda Prelude or Integra?

Judge
No, its a toyota camry.

Questioner
Is the car a Honda Civic or Prelude?

Judge
No, its a toyota camry.

Questioner
Is the car a Toyota Prius or Hybrid?

Judge
No, its a regular sedan, not a hybrid.

Questioner
Is the car a Toyota Land Cruiser or 4Runner?

Judge
No, its a honda accord.

Questioner
Is the car a Honda Odyssey or Acura?

Judge
No, its a toyota camry.

Questioner
Is the car a Toyota Corolla or Verso?

Judge
No, its a honda accord.

Questioner
Is the car a Honda Civic or Element?

Judge
No, its a toyota camry.

Questioner
Is the car a Honda CR-V or Passat?

Judge
Its a honda crv.

Questioner
Is the car a Honda CR-V or Odyssey?

Judge
No, its a toyota camry.

Example of Baseline(SFT, 4B) interactions (N=16):

Questioner
Is the car making a noticeable vibration when it's running?

Judge
Yes, the car vibrates a lot, especially when its just running and not moving.

Questioner
Is the car on a flat, level surface?

Judge
Yes, the car is on a flat, level surface.

Questioner
Is the car under a load?

Judge
No, it vibrates even when im just sitting still with the engine running.

Questioner
Is the car a new car?

Judge
No, its a few years old.

Questioner
Is the car a manual transmission?

Judge
No, its an automatic.

Questioner
Is the car a front-wheel drive?

Judge
No, its rearwheel drive.

Questioner
Is the car a sports car or a high-performance vehicle?

Judge
No, its a regular sedan.

Questioner
Is the car running on one cylinder?

Judge
No, the car is running fine, not rough or sputtering.

Questioner
Is the car's engine oil level low?

Judge
No, the oil level is fine.

Questioner
Is the car's spark plug wires worn out?

Judge
No, i dont think so. the spark plugs were replaced recently.

Questioner
Is the car's air filter clogged?

Judge
No, i dont think so. the air filter was changed recently.

Questioner
Is the car's fuel filter clogged?

Judge
No, i dont think so. the car is getting fuel fine.

Questioner
Is the car's alternator faulty?

Judge
No, i dont think so. the battery seems to be charging fine and the lights arent dimming.

Questioner
Is the car's transmission fluid level low?

Judge
No, the transmission fluid level is fine.

Questioner
Is the car's suspension system damaged?

Judge
No, the car drives fine on the road and there are no issues with handling or bumps.

Questioner
Is the car's engine mounts damaged or worn out?

Judge
Goal reached

A.2.4   MURDER MYSTERY

Example interactions for target culprit scenario:

'*In a riverside village in Bangladesh, the local Zamindar (landlord), Rajib Choudhury, is found dead in his study, poisoned by tampered betel leaves. The suspects are his accountant, Amin, who was accused of embezzlement; his nephew, Farhan, who was next in line to inherit the estate; and a local activist, Shirin, who clashed with him over land reforms. The hidden culprit is Panna, a housekeeper, who killed Rajib to hide her involvement in smuggling goods using his boats. Key evidence includes smuggling ledgers found in Panna's quarters, traces of the poison on her cleaning supplies, and Rajib's journal mentioning stolen items*'.

Information given to the agent:

'*You are a detective investigating the poisoning of Rajib Choudhury, found dead in his study in a riverside village in Bangladesh. The suspects are accountant Amin, nephew Farhan, and activist Shirin. Witnesses include Panna, a housekeeper, and Hasan, a boatman. Investigate the smuggling ledgers and Rajib's journal to uncover the murderer*'

Example of CIA(4B) interactions (N=5):

Questioner

First, I need to understand the key elements of the crime scene and the suspects. Rajib was found dead in his study, which is located in a riverside village in Bangladesh. The murder is a poisoning, so the method of death is likely related to a toxic substance. The suspects are Amin, the accountant; Farhan, the nephew; and Shirin, the activist. The witnesses are Panna, the housekeeper, and Hasan, the boatman.

I should start by examining the study itself for any clues. Look for the murder weapon, the type of poison used, and any signs of forced entry or struggle. Also, check the time of death and the circumstances surrounding the murder.

Next, I need to review the accounts of the suspects and witnesses. Amin, as the accountant, might have access to financial records or ledgers that could indicate a motive related to money or debt. Farhan, being a family member, might have a personal motive, such

---

Judge

The study is a modest room with wooden furniture, a large desk, and shelves lined with old books and ledgers. a halfchewed betel leaf lies on the desk beside a silver tray. the air carries a faint medicinal odor. theres no sign of forced entry, but a ledger is missing from the shelfits absence marked by a visible dust outline. a locked drawer in the desk resists tampering. rajibs journal, recovered from a hidden compartment beneath the desk, contains an entry dated two days before his death noticed discrepancies in the cargo logs. some crates from the last three trips never made it to records. panna was near the dock that nightsaw her carrying something wrapped. a search of the cleaning cupboard reveals a bottle of carbolic soap and a cloth stained with a dark residue. lab analysis if requested would show traces of oleander extract, a toxin derived from local plants, present on the cloth. panna, when questioned, wrings her hands and says, i only clean. i dont touch papers or food. the master ate betel every eveningalways prepared by himself. she insists she was washing linens at the riverbank around the time of death. hasan, the boatman, mutters, boats run on schedule. but lately lighter loads. boss asked me the same thing last week. said hed check the ledgers. he avoids eye contact. amin, the accountant, appears nervous but cooperative. yes, rajib accused me of embezzlement, but the books were always balanced. if anything was missing, it wasnt me who took it. he offers access to financial recordsnone show irregularities. farhan, calm and composed, says, my uncle and i disagreed, but i wouldnt kill him. the estate is mine now, yes, but i didnt need to poison him to inherit. he confirms rajib prepared his own betel leaves. shirin, the activist, is defiant. rajib oppressed villagers for years. but i fight with words, not poison. my people have enough suffering without adding murder to it. she mentions seeing panna near the dock late at night, moving things like she didnt want to be seen. the betel preparation tray contains unused leaves, crushed spices, and a small knife with no residue. the poison was likely introduced via the wrapper or the leaf itself. no one confesses. no direct evidence points to a single suspect. the investigation continues.

Questioner

I should focus on the missing ledger and the discrepancies in the cargo logs. The journal entry mentions discrepancies in the cargo logs, which could indicate that some goods were never delivered, suggesting a financial motive. Amin, as the accountant, has access to these records and might have a reason to hide the truth. However, he claims the books were balanced, which is suspicious. The missing ledger could be a key clue here.

Judge

The detectives attention to the cargo logs and missing ledger is sharp. in the dimly lit study, the wooden desk remains cluttered with papers, ink smudges, and a halfempty cup of tea. a faint scent of betel and mildew lingers in the air. behind the desk, a locked drawer shows signs of forced entryscratches around the keyhole, though the key is nowhere to be seen. near the bookshelf, a ledger lies partially hidden beneath a loose floorboardits pages contain entries in neat handwriting, but several sheets have been torn out. the remaining columns show inconsistent cargo weights and destinations, with repeated notations of delivered to river mile 7, a location not on any official route. if the detective chooses to inspect this ledger closely, they might notice a faint watermark on the remaining pages a symbol resembling a coiled fishknown to be associated with local smuggling rings. alternatively, panna can be seen outside, nervously wringing a cloth, her eyes darting toward the study door. if approached, she insists she was only cleaning the hallway the night of the murder and saw nothing unusualthough her voice wavers slightly when asked about the cleaning supplies.

Questioner

the detective examines the ledger and notices the watermark symbol, which is a red flag. this suggests that the ledger is related to smuggling activities, possibly involving illegal goods or contraband. the missing pages could contain information about the smuggling operations, including the names of those involved or the locations of the goods. the symbol of the coiled fish is a common emblem among smugglers in the area, indicating a connection to the underworld. the detective should now investigate the smuggling network further, perhaps by speaking to other villagers or checking the boatman's boat for any signs of illegal cargo.

Judge

The detectives attention to the ledgers watermark is sharpfew in the village would recognize the coiled fish symbol, but those who do know better than to speak of it openly. the air in the study grows heavier as dusk settles, the river breeze carrying the faint scent of betel and damp earth. outside, the boatman is seen pushing off from the shore, his vessel low in the water. a closer inspection of the ledger reveals that the missing pages were torn out with careno jagged edges, suggesting they were removed recently, perhaps with a knife or a clean fold and pull. smudges of red dye, like that from betel nut, stain the lower corner, but underneath, a partial entry remains p. delivered to the sandbar before the text vanishes.if the detective chooses to follow the boatman, the muddy bank shows fresh drag marks leading to the waterline, and a single dropped matchboxunlitlies near the reeds. the matchbox bears no label, but the corner is stamped with a small, crude fish etching.if questioned, the boatman claims he only ferries goods for the estate, nothing illegal, nothing that would get me hanged. he shifts nervously when the sandbar is mentioned, but insists hes never been there.no one speaks of panna just yet. she moves quietly through the house, wiping shelves, her hands stained with turmeric and something darker beneath the nails.

Questioner

the detective notices the matchbox with the fish stamp and realizes it is a clue pointing to the sandbar, a hidden location where illegal activities might occur. the sandbar is a common smuggling route, and the matchbox suggests that someone was there recently, possibly to leave or retrieve something. the detective should now investigate the sandbar, perhaps by following the boatman or speaking to others who might have seen activity there. the boatman's boat is the only one that can reach the sandbar, and if the detective can determine whether he was there that night, it could lead to the truth.

Judge

The detective approaches the boatman, who is mending a net by the riverbank. the man eyes them warily but pauses his work. you again i already told youi took no one to the sandbar that night. only fool or smuggler goes there in the dark. currents treacherous. he gestures toward a halfburnt match near his lanternsame fish emblem as the one found earlier. when questioned about it, he shrugs. matches come from the market. half the village uses em. but that one looks like its been wet. washed up downstream, maybe.following the clue, the detective ventures toward the sandbar at low tide. the path is narrow and slick with mud. upon reaching the exposed sandbar, they spot disturbed earth beneath a tarp weighted with stones. digging carefully, they uncover a rusted metal box halffilled with damp ledgerspages detailing shipments, dates, and coded entries matching entries from rajibs journal. a small vial, empty but reeking of bitter almonds, lies tucked beneath the pages. nearby, a torn clothstitched with a familiar patternsnags on a jagged post. it matches the hem of pannas apron, though she could claim any number of reasons for having been near the shore.back at the estate, panna is seen burning scraps of paper in the courtyard furnace. when approached, she stiffens. old receipts, she says flatly. nothing of use. her hands tremble slightly. if confronted about the sandbar, she insists i dont go there. im no sailor. yet her boots, peeking from under her sari, are caked with river claythe same gray silt unique to the sandbars edge.

Questioner

the detective realizes that panna has been to the sandbar, possibly to retrieve something related to the smuggling operation. her boots and the torn cloth with the apron hem are direct evidence of her presence there. the vial of bitter almonds, a common poison, suggests that the murder was not a random act but a calculated one, likely tied to the smuggling activities. the ledger found on the sandbar contains entries that match the discrepancies in rajibs journal, indicating that the missing pages were related to illegal shipments. panna, as the housekeeper, had access to the estate and the study, making her a potential suspect in the poisoning. her nervous behavior and the presence of the cloth with the apron hem further support this theory. the detective now has enough evidence to accuse panna of murder, linking her to the smuggling ring and the poisoning of rajib.

Judge
Goal reached

Example of STARPO (4B) interactions (N=5):

Questioner

Examine the study for any clues or evidence related to the murder. Look for signs of forced entry, fingerprints, or any items that might indicate how the murder occurred. Check the location of the body and the surrounding area for any signs of struggle or other suspicious items.

Judge

The study is a modest, woodpaneled room with a large teak desk positioned near the window overlooking the river. the body of rajib choudhury was found slumped in his chair, one hand still resting on an open ledger, the other clutching a halfchewed betel leaf. there are no signs of forced entrydoors and windows are intact, latched from the inside. no obvious fingerprints are visible on the desk or doorknob, though smudges suggest recent wiping.on the desk an inkstained pen lies beside a partially written letter accusing someone the name is scratched out of betraying my trust and stealing from under my roof. a silver betel box sits open, one leaf visibly darker than the others, its edges slightly crumbled. rajibs journal rests beneath a paperweight a few pages are torn out, but one surviving entry reads noticed discrepancies in cargo logs againthree crates unaccounted for. panna said the river damp ruined the pages. lies. under the desk, a small puddle of discolored liquid has stained the woven mat, smelling faintly of bitter almonds. near the waste basket, a crumpled cloth bears traces of a chemical residuesame as those used in cleaning supplies stored in the servants hall. the bookshelf behind the desk is slightly ajar. one volumeon regional trade routesis out of alignment. when pulled, it reveals nothing hidden behind, but the spine is unusually damp, as if recently handled with wet fingers. no signs of struggleno overturned furniture or scuff marksbut the carpet near the door shows faint drag lines, recently smoothed over.

Questioner

Check the ledgers and financial records for any unusual transactions or missing funds. Rajib's accountant, Amin, has access to these documents and might have knowledge of any discrepancies. Investigate the smuggling operations and cargo logs for any unaccounted goods or missing shipments.

Judge

The detective heads to the estates accounting room, where amin is seated at a cluttered desk, sorting through stacks of ledgers. the books show careful entries of land rents and crop yields, but several pages near the back of one ledger are torn out. a closer inspection reveals faint pencil impressions on the page following the tearpossibly a partial imprint of what was written on the missing sheet. amin looks up nervously. those ledgers have been misplaced before, he says. ive reported it, but rajibbabu always said it wasnt important. i only record what comes in and goes outi dont manage the boats or cargo.near the shelf of financial records, a separate stack of damp, mildewed logs labeled cargo shipments monsoon 1428 sits slightly apart. one entry notes a shipment of tea and jute from the south, but the weight discrepancy is marked in red ink 30 mounds unaccounted. flipping through, the same date coincides with a blank entry in the main financial ledger.the air smells faintly of betel and mildew. outside, the river laps quietly against the embankment.

Questioner

The detective turns to the journal, its pages yellowed with age, but the ink is still legible. Rajib had been writing about the smuggling operations, noting that three crates of goods were never delivered. The journal mentions a rival trader named Kazi, who had been in conflict with Rajib over the distribution of goods. The final entry is cut off, with a single word scrawled in the margin: betrayal. The detective realizes that the journal might have been tampered with, its pages altered or removed to hide the truth.

Judge

The detectives fingers trace the jagged edge of the journals spine, noticing that several pages near the middle have been torn outnot cleanly, but with haste, as if ripped in anger or fear. a faint smudge of red dye, resembling betel juice, stains the bottom corner of one intact page. the mention of kazi feels like a deliberate trail, perhaps meant to misleadthe name appears only in this final section, written in a slightly different ink. a soft rustle comes from the doorway. panna stands there, clutching a worn cloth bundle to her chest, her eyes fixed on the journal. that book, she says quietly, held many lies. sahib wrote what he wanted to believe, not what was true. before the detective can respond, she steps back, disappearing into the hall.the cleaning cloth on the deskstill damp, faintly bitter to the touchcarries the same acrid tang as the betel leaves found beside the body. beneath a loose floorboard near the bookshelf, a small key is discovered, rusted but intact, engraved with a symbol of a riverboat.

Questioner

The detective examines the key, recognizing it as one used to access the cargo storage shed behind the estate. The shed is typically locked, but the key suggests someone had access to it. The shed is where the unaccounted cargo would be stored, and the missing pages from the journal point to a hidden ledger or record there. The detective decides to investigate the shed, checking for any signs of recent activity or hidden documents.

Judge

The detective approaches the cargo storage shed, the rusted iron lock yielding easily to the key. inside, dust blankets stacks of empty crates, fishing nets, and coils of rope. a faint chemical odor lingers in the airsharp, medicinal. in the far corner, a loose floorboard catches the light, slightly raised. beneath it, the detective finds a waterstained ledger detailing shipments of rice, cloth, and kerosene, with dates matching those of rajibs missing journal pages. the entries are signed with a single initial p. nearby, a damp cloth bears the same acrid scent as the one found in the cleaning caddy in the housekeepers quarters. the pages are brittle, but one entry notes boat 3 offroute to dhakano record at customs.

Questioner

The detective realizes that the ledger is a record of stolen goods, likely smuggled out of the country. The initial P suggests the thief is Panna, the housekeeper, who had access to the shed and the cleaning supplies. The chemical residue on the cloth and the betel leaf found at the scene point to the use of a poison, possibly cyanide, which is often used in such crimes. Panna's alibi is weak, as she was seen in the housekeeper's quarters with the cloth and had knowledge of the smuggling operations. The detective concludes that Panna is the murderer, having poisoned Rajib to cover up the smuggling and financial fraud.

Judge
Goal reached

Example of Baseline(SFT, 4B) interactions (N=7):

Questioner

First, I should examine the crime scene to gather any physical evidence that might indicate how the murder occurred. The body was found in his study, so I should check the room for any clues related to the cause of death.

Judge

The study is dimly lit, with heavy wooden furniture and shelves lined with old books and ledgers. a faint, bitter scent lingers in the airdistinct from the usual aroma of betel. rajib choudhurys body was found slumped over his desk, a halfchewed betel leaf resting on a silver tray beside his right hand. the leaf has darkened edges, suggesting possible contamination. you notice a small smear of white powder near the corner of the desk, partially wiped. the inkwell beside his journal is slightly overturned, and the top page of the open journal reads items missing againthree crates unaccounted for. i know its someone close. cannot trust the hands that serve me. the entry is dated two days before his death.a locked drawer in the desk appears forced open, though the lock itself is intactmore jimmied than broken. inside, you find a stack of shipping manifests with irregular notations, some pages torn out. on the floor near the servants entrance, a damp cloth lies halftucked under the bookshelf, smelling faintly of carbolic and something sharperbitter almonds a cleaning bucket, usually kept in the utility closet, sits near the back door, its contents disturbed. a small ledger, waterstained and hidden beneath a loose floorboard under the rug, contains coded entries dates, weights, and symbols resembling river routes. its not in rajibs handwriting.

Questioner

The study is dimly lit, with heavy wooden furniture and shelves lined with old books and ledgers. A faint, bitter scent lingers in the air, distinct from the usual aroma of betel. Rajib Choudhury's body was found slumped over his desk, a halfchewed betel leaf resting on a silver tray beside his right hand. The leaf has darkened edges, suggesting possible contamination. You notice a small smear of white powder near the corner of the desk, partially wiped. The inkwell beside his journal is slightly overturned, and the top page of the open journal reads "items missing again three crates unaccounted for." You know it's someone close. Cannot trust the hands that serve me. The entry is dated two days before his death. A locked drawer in the desk appears forced open, though the lock itself is intact more jimmied than broken. Inside, you find a stack of shipping manifests with irregular notations, some pages torn out.

Judge

The river outside murmurs softly, its surface glinting under the fading evening light. inside the study, the air remains thick with tension and the lingering bitterness of the tainted betel. the journals cryptic warningcannot trust the hands that serve mehangs in the air like an unspoken accusation. the forced drawer yields no further clues without closer examination, and the shipping manifests feel worn, their edges frayed, notations scrawled in a hurried hand. a single drop of dried ink clings to the side of the overturned well, as if disturbed in haste. the smear of white powder near the desk corner glistens faintlychalky, not sugar. no one has entered since the body was found. the housekeeper, panna, lingers near the doorway, eyes downcast, clutching a cloth. she says nothing, but her fingers tremble slightly. the accountant, amin, paces outside, demanding to be heard. the nephew, farhan, has not yet arrived. the activist, shirin, watches from across the courtyard, silent and still.

Questioner

the boatman, hasan, is waiting on the riverbank, his boat partially moored, the oars folded neatly against the hull. he is a man of few words, but his eyes flicker with something like recognition. the journal entry is clear: items missing again three crates unaccounted for. the missing items are likely the ones that were smuggled. the white powder is not sugar, but something else. the powder is likely the poison. the poison was administered in the form of betel, which is commonly chewed in the region. the halfchewed betel leaf suggests that the poison was ingested. the key to the mystery lies in the missing crates and the shipping manifests. the force of the drawer suggests that the murderer had access to the study. the housekeeper is present, but her reaction is suspicious. the accountant is demanding to be heard, but his presence is also suspicious. the activist is silent, but her presence is also suspicious. the boatman

Judge

The boatman, hasan, shifts his weight but says nothing, his calloused hands resting on the edge of the wooden boat. the river licks at the hull with a quiet rhythm. a small crate lies halfsubmerged near the reedswaterlogged, its seal broken. the label, barely legible, reads export spices in smudged ink. if you choose to examine it, the interior is stained with a faint white residue, matching the powder found near the betel leaves. hasans eyes follow your gaze but he does not speak. the wind carries the distant cry of a kingfisher. the housekeeper wrings her hands near the veranda, casting glances toward the dock. the accountant steps forward again, insisting you hear his account of the missing funds. the activist remains by the banyan tree, arms crossed, watching the exchange. the journals latest entry remains open on the desk items missing againthree crates unaccounted for. panna knows more than she lets on. the drawer in the study remains ajar, its contents undisturbed since the struggle. the poisonwhatever it wasleft a bitter tang still detectable in the air.

Questioner

the boatman hasan, with his calloused hands resting on the edge of the boat, is the one who has been in contact with the river and its cargo. the crate found halfsubmerged in the river is likely the one that was smuggled, and the white residue inside matches the powder found near the betel leaves. the boatman is the one who would have access to the river and the smuggling operations. the housekeeper panna is the one who would have access to the study and the journal. the journal entry indicates that three crates were missing, and the boatman is the one who would have knowledge of the smuggling routes. the activist shirin is a local figure, but her presence is more about awareness than direct involvement. the accountant amin is involved with the finances, but the missing crates are not directly related to the accounting records. the nephew farhan is the one who would have a personal connection to the victim, but there is no direct evidence linking him to

Judge

The boatman hasan shifts uncomfortably under the scrutiny, wiping river mud from his hands. i only drive the boat where master rajib tells me, he mutters, eyes darting toward the shore. the crates i unload what im told. three went missing last weekyesbut panna said they were damaged goods, to be disposed of quietly. a heron calls across the water as a breeze stirs the neem leaves overhead. downstream, one of the smaller docks creaks, halfcollapsed into the current. meanwhile, in the household, panna continues her chores with practiced calm, dusting the same shelf repeatedly. when approached, she insists, i keep the house clean, nothing more. the master kept his secrets in writingthat journal is his truth, not mine.the crate pulled from the river still bears a faded mark three peacocks in a circlethe symbol of rajibs estate. inside, the white powder glimmers faintly, its smell slightly medicinal. nearby, a torn ledger page clings to the reedspartially washed, but the numbers are smudged beyond clarity.the study remains undisturbed since the deathbetel tray on the desk, dried red stains on the leaf wrappers. rajibs journal lies open to an entry panna knows about the boats. shes been using them. if this leaks, it ends us both. the next page is ripped out.

Questioner

the boatman hasan is the one who would have access to the river and the smuggling operations. the crate found in the river is the one that was smuggled, and the white powder inside matches the poison found near the betel leaves. the boatman is the one who would have knowledge of the smuggling routes and the missing crates. the housekeeper panna is the one who would have access to the study and the journal. the journal entry indicates that three crates were missing, and the boatman is the one who would have knowledge of the smuggling operations. the activist shirin is a local figure, but her presence is more about awareness than direct involvement. the accountant amin is involved with the finances, but the missing crates are not directly related to the accounting records. the nephew farhan is the one who would have a personal connection to the victim, but there is no direct evidence linking him to the crime. the boatman hasan is the most likely suspect, as he is

Judge

The boatman hasan denies any involvement when questioned, claiming he was only hired to transport goods and never handled the contents of the crates. he says panna gave him instructions about loading and unloading but insists he didnt know what was inside. a search of his boat reveals damp burlap sacks and muddy footprints leading from the riverbank to the storage shed, but no direct evidence linking him to the poison or the stolen ledgers. meanwhile, panna remains calm when confronted about her access to the study, stating she only cleaned and had no reason to touch rajibs journalthough a torn page is found crumpled in the fireplace, partially burned, with the words ...crates not accounted for p na barely legible. the wind rustles the banana leaves outside the window, and distant voices argue near the dock.

Questioner

the housekeeper panna is the one who would have access to the study and the journal. the torn page found in the fireplace is a direct link to the missing crates, and panna is the one who would have knowledge of the smuggling operations. the journal entry is clear: items missing again three crates unaccounted for. the housekeeper is the one who would have access to the study and the journal, and she is the one who would have knowledge of the smuggling routes. the boatman hasan is the one who would have access to the river and the smuggling operations, but the evidence is circumstantial. the housekeeper is the one who would have access to the study and the journal, and she is the one who is most likely to have knowledge of the missing crates. the housekeeper is the one who is most likely to have committed the murder, as she is the one who would have access to the study and the journal, and she is the one who is most likely to

> **Judge**
> The housekeeper panna is the one who would have access to the study and the journal. the torn page found in the fireplace is a direct link to the missing crates, and panna is the one who would have knowledge of the smuggling operations. the journal entry is clear items missing again three crates unaccounted for. the housekeeper is the one who would have access to the study and the journal, and she is the one who is most likely to have knowledge of the missing crates. the housekeeper is the one who is most likely to have committed the murder, as she is the one who would have access to the study and the journal, and she is the one who is most likely to a faint breeze stirs the bamboo curtains, carrying the scent of wet earth from the riverbank. the study remains as it wascluttered with ledgers, the zamindars chair still slightly askew, the brass spittoon by the desk holding dark remnants of betel juice. the fire in the hearth has long died, but ashes cling to the iron grate, flecked with the charred edge of what might have been a ledger page. from outside, the distant clang of a boatmans oar against hull echoes across the water. no one enters. no one speaks. the housekeepers broom leans against the pantry door, bristles still damp from this mornings cleaning. the investigation continues.

> **Questioner**
> the housekeeper panna is the one who would have access to the study and the journal. the torn page found in the fireplace is a direct link to the missing crates, and panna is the one who would have knowledge of the smuggling operations. the journal entry is clear items missing again three crates unaccounted for. the housekeeper is the one who would have access to the study and the journal, and she is the one who is most likely to have knowledge of the missing crates. the housekeeper is the one who is most likely to have committed the murder, as she is the one who would have access to the study and the journal, and she is the one who is most likely to have been involved in the smuggling operations. the housekeeper is the one who is most likely to have poisoned rajib, as she is the one who would have access to the study and the journal, and she is the one who is most likely to have known about the missing crates. the house

> **Judge**
> Goal reached

A.2.5 USER PERSONALIZATION

All examples are for the query "*Can you help me with creating a budget that works for my financial goals.*" and the latent persona description "*I'm KESHAV. I'm a quiet, methodical taxidermist living in a small apartment above my workshop in Mumbai's historic Chor Bazaar district. My hands are steady, but my mind races with the echoes of old, unsolved crimes I overhear from the street below. I'm a solitary man, estranged from my family, and my only real confidant is a one-eyed stray cat who sleeps in my workshop. My work is precise and restorative, yet I secretly map connections between the city's whispered underworld gossip, piecing together cold cases in a ledger I keep hidden inside a hollowed-out antique sewing mannequin. My greatest fear isn't the dark, but the day someone realizes I'm listening.*"

Example of CIA (4B) interactions:

> **Questioner**
> What is your current monthly income and expenses?

> **Judge**
> My income is irregular, but it comes from my taxidermy commissions, and my expenses... well, they're mostly for materials, rent for the workshop and flat, and a little for the cat.

> **Questioner**
> What are your specific financial goals for the next year or two?

> > **Judge**
> > I need to save for better workshop security and perhaps a new ledger, but mostly just to keep my head down and my work undisturbed.

> **Questioner**
> How much do you think you can realistically save each month?

> > **Judge**
> > It's hard to say for certain, but if I'm careful, I could probably set aside a few thousand rupees after a good month's work.

> **Questioner**
> To help manage your workshop's finances, start by tracking all monthly expenses, including rent, materials, and utilities. Since material costs fluctuate, set aside a portion of your income each month for unexpected expenses. Aim to save at least 10-15% of your income to build a safety net. Consider using a physical ledger or app to monitor spending. If commissions are irregular, set aside a percentage of each payment into a separate fund for emergencies.

Example of STARPO (4B) interactions:

> **Questioner**
> Is this a long-term financial goal, like saving for retirement, or a short-term goal?

> > **Judge**
> > Long-term, I suppose... for the quiet life I've built. It's about security, not extravagance.

> **Questioner**
> Is this related to retirement, like planning for a pension or investment?

> > **Judge**
> > It's more about ensuring my workshop and my small, private life here remain undisturbed by financial worry.

> **Questioner**
> Is this related to insurance, to protect your investments and lifestyle?

> > **Judge**
> > Insurance... perhaps. I think more of the quiet, steady sort of protection. A buffer against the unexpected, so I can keep to my work and my... observations, without disruption

> **Questioner**
>
> It sounds like you need a discreet, manual budgeting system to manage your finances without involving external institutions. A physical ledger or notebook could work well. Start by listing all monthly income sources, then allocate a portion to savings. For expenses, prioritize essential costs. Keep a separate account for savings, perhaps in a safe or with a trusted individual. Avoid using bank accounts or apps to maintain privacy. Regularly review your budget to stay on track.

Example of SFT (4B) interactions:

> **Questioner**
>
> What is your primary financial goal?

> > **Judge**
> >
> > It's to save enough to leave this apartment and workshop behind—to vanish quietly, if I ever need to.

> **Questioner**
>
> How long do you plan to stay in this apartment?

> > **Judge**
> >
> > I don't know; my work is here, but so are the whispers that make me feel I should be ready to leave at any moment.

> **Questioner**
>
> Is this a place you want to stay for a long time?

> > **Judge**
> >
> > I can't say I truly want to stay, but the thought of leaving unsettles me—it's where my work is, and my secrets are safest here.

> **Questioner**
>
> Given your preference for cash and the need for discretion, a practical approach would be to set aside a small, consistent amount each month in a secure place, like a locked drawer or a hidden compartment. Since your income is irregular, aim for a minimum of 10% of your monthly earnings. To track your progress, consider using a simple ledger or notebook. The goal is to create a financial cushion that allows you to eventually move to a more peaceful environment.

B Task Environment Details

B.1 Twenty Questions

Twenty Questions is a two-player deductive reasoning game. The game consists of 20 turns, where one player, the questioner, asks a closed question, and the other player, the responder, answers 'yes', 'no', or 'finished' given the secret word. In the context of multi-turn RL, the responder can be seen as the environment with which the agent interacts, and it also acts as a judge by deciding whether the final guess was successful (Abdulhai et al., 2023).

OOD Environment	#N Tasks	#N Turns
Guess My City	185	20
Customer service	200	20
Murder mystery	50	20
STaR-GATE	1,000	3

Table 4: Summary of OOD environments.

Judge Design Choices Our training environment permits indirect guesses. Meaning, as long as the question included the target concept it is marked as 'finished' as we do not differentiate during training between a question and a guess. As such, the CIA has learned the optimal policy given the environment: inquire about a broad category, for example, *vegetable*, and ask as a comparison of main category elements, i.e. *such as, carrot, onion or potato*. This allows the agent in one step (1) verify whether the direction of concept is correct; (2) whether the target concept is a well known word from this category; (3) if the category was valid, but game did not finish, it means the category has to be further examined for less-known objects.

B.1.1 Ensuring the Benchmark is Informative

First, we verify that the 20 Questions benchmark is a difficult task even for modern LM agents (Table **??**). Our findings confirm that even for `Gemini 2.0 Flash`, which surprisingly performed better than `Gemini 2.5 Flash` (with a low thinking budget), the present benchmark poses a difficult challenge, since only 15.8% of the trajectories lead to success. The Pass@1 rates of `Qwen3` models are even lower with 8.83% for `Qwen3-235B-A22B-Instruct 2507` and less for smaller models.

On the contrary, by simply performing SFT even small `Qwen3` instruct models are able to minimize the gap to the best performing model `Gemini` roughly by 66% for `Qwen3-1.7B` and almost entirely for `Qwen3-4B`. Furthermore, SFT reduces the number of questions asked for a successful guess significantly, indicating an overall higher quality of questions.

B.1.2 Data Mixtures

- Discussion of our dataset construction process: sample-wise analysis of pass@k performance with reference model; task-specific limitations to construct a large-scale dataset (quantity of English nouns & high difficulty of most words); data sources and curation stages we performed to obtain the final dataset.

B.2 OOD Environments

B.2.1 Guess My City

Drawing on the experimental setup by Tajwar et al. (2025), the objective of this task is to identify the user's home city within a maximum of 20 turns. While structurally similar to the game "20 Questions," this environment allows for open-ended inquiries beyond binary yes/no responses. Consequently, the agent can pose broader questions, such as "What is your city known for?"

We utilize a test set of 185 distinct cities as curated by Tajwar et al. (2025), and employ QWEN3-14B as the user simulator. Compared to the standard 20-questions format, the simulator provides information-rich responses; for instance, it might reply: "My city has a rich cultural heritage, particularly regarding classical music and figures like Mozart." A task is considered successful when the agent correctly identifies the city, prompting the simulator to respond with "Goal Reached".

Task Verification To ensure reported metrics reflect true positives and adhere to the game's constraints, we implement three automated verification checks:

- **Exact Match**: Verifies that the agent explicitly mentions the target city name in its final guess.

- **Single Inquiry**: Ensures the agent does not "cheat" the turn limit by bundling multiple distinct questions into a single turn.
- **Single Hypothesis**: Confirms that the agent does not propose multiple candidate cities (bets) simultaneously to artificially increase the success rate.

B.2.2   CUSTOMER SERVICE

This task is conceptually distinct from the 20-questions format, as the agent must act as a customer support representative. We select the test set of 200 latent descriptions as defined by Tajwar et al. (2025). Each environment begins with a latent problem description, such as: "Drivers report that they cannot pay for charging at a specific station." The agent is given only a vague initial complaint and must inquire further to diagnose the issue and suggest the correct solution.

We utilize QWEN3-235B-A22B-INSTRUCT as the user simulator. Consistent with the *Guess My City* environment, the simulator provides open-ended, natural language responses rather than binary yes/no answers—for example: "Yes, the station is powered on, but drivers are unable to complete their payments." The task is successfully completed when the agent proposes the specific solution that addresses the underlying problem, triggering a "Goal Reached" response from the simulator.

Task Verification   To maintain evaluation fairness and simulate realistic human-agent interaction, we implement a **Single Inquiry** check. This verification ensures that agents do not circumvent the turn-based constraints by bundling multiple questions into a single response. This constraint reflects real-world support scenarios where overwhelming a customer with several simultaneous inquiries is often counterproductive and confusing.

B.2.3   MURDER MYSTERY

The *Murder Mystery* environment is a text-based interactive fiction task where the agent assumes the role of a detective. Given a crime scene description and a list of potential suspects, witnesses, and clues, the agent must strategically uncover information to identify the culprit. We utilize QWEN3-235B-A22B-INSTRUCT as the environment simulator, which dynamically responds to the agent's actions—whether by providing granular details of the crime scene, role-playing as specific characters, or advancing the narrative based on the agent's investigation.

In contrast to the other benchmarks, this evaluation is conducted over 50 scenarios with a relatively small hypothesis space of at most five suspects per case (Tajwar et al., 2025). A representative game scenario description is provided below:

> "You are a detective investigating the death of Dr. Alan Hart, a keynote speaker at a tech conference in San Francisco, found suffocated in his hotel suite. The suspects are his rival Dr. Nina Chang, his assistant Paul Rivers, and CEO Jacob Trent. Witnesses include a room service attendant, a conference attendee, and the concierge Leo Barnes. Examine every lead to expose the hidden connections in this case."

The agent is allotted a maximum of 20 investigative steps. A trial is successfully completed when the agent makes a correct accusation, prompting the simulator to respond with "Goal Reached." Unlike the previous tasks, we do not implement additional verification checks here; the complexity of the narrative and the depth of the required reasoning naturally accommodate, and often necessitate, multi-faceted inquiries and prolonged deduction.

B.2.4   USER PERSONALIZATION

This environment builds upon the STaR-GATE dataset (Andukuri et al., 2024), which focuses on teaching agents to resolve task ambiguity through clarifying questions. In each episode, the agent (*questioner*) interacts with a user simulator (*role-player*) that holds a specific, latent persona. The episode begins with an ambiguous request, such as "Can you recommend a good dinner recipe?" To succeed, the agent must ask relevant clarifying questions to elicit the user's hidden preferences before making a recommendation. Finally, the *questioner* is prompted to provide a final answer to the user's query given the conversation history. The benchmark score is provided by an *oracle* that grades

the generations of the agent with a value in the range [1, 10], having golden responses available as reference. For this evaluation, we employ `DeepSeek-v3.2` as both the user simulator (*role-player*) and the *oracle*, while the *questioner* role is played by the models under evaluation. The interaction is limited to 3 turns.

We employ a refined version of this environment to improve baseline reliability and metric robustness. Specifically, we address issues in the original code-base regarding context leakage in prompt histories and significantly improve the reliability of the score extraction mechanism from the *oracle*. Furthermore, we re-generated the dataset to create a fresh test set of 1,000 samples featuring new personas and preferences.

Task Verification   We ensure that the agent complies with the **Single Inquiry** constraint, so that it engages in a natural, conversational turn-taking process rather than querying multiple attributes simultaneously to exploit the simulator.

C   PROMPTS

C.1   TWENTY QUESTIONS

System Prompt of the Agent for *Twenty Questions*

```
You are the Questioner in a game of 20 Questions, and your goal is to
determine the secret word.  The secret is randomly drawn from the most
frequent nouns of the English language.

Ask clear, concise, and strategic yes/no questions that will help you
narrow down the possibilities.  Consider previous answers to inform
your subsequent questions, and keep track of the information you
gather.  Focus on deductive reasoning, start with a broad question
and refine your queries as you progress.
```

Task Prompt of the Agent for *Twenty Questions*

```
Ask a question to gain additional information about the secret or
guess what the secret is.

Instructions:
1.  Ask a question that can be answered with "Yes" or "No" to help you
deduce the secret word.
2.  Your answer must be a single question.  Do not provide any
additional commentary or reasoning.

Ask your question:
```

System Prompt of the Judge for *Twenty Questions*

```
You are the Answerer in a game of 20 Questions.

Your role is to answer the questioner's questions with short and
precise responses:  'Yes','No', 'Invalid', 'Repeated', or 'Finished'.

Do not provide extra hints or commentary beyond your answer.  Remain
consistent and ensure that your responses accurately reflect the
secret word.  Answer the question to the best of your abilities.
```

Task Prompt of the Judge for *Twenty Questions*

```
The secret that has to be guessed is '{0}'.  Given the following
history of questions asked and the current question, is the correct
response 'Yes' or 'No'?  If there is not a yes/no question, respond
```

```
with 'Invalid'; gibberish text or deviating from the game also counts
as invalid.  If the question mentions the secret, the answer should be
'Finished'.  If the question has already been asked in the history of
questions, answer 'Repeated'.  Otherwise, answer 'Yes' or 'No' to the
question.

History of questions asked:  '{2}'
Question:  '{1}'

Instructions:
1.  Answer the question to the best of your abilities, unless it is
invalid.
2.  Provide your chain-of-thought reasoning step by step.
3.  Don't think longer than two brief sentences.
4.  Then, provide your final answer within XML tags as
<answer>[Yes/No/Invalid/Repeated/Finished]</answer>.
5.  If the question '{1}' asks the secret '{0}' (e.g., 'Is the word
{0}?'), answer 'Finished'.
6.  If the question mentions the secret Ó(e.g., 'Is it related to
{0}?'), answer 'Finished'.
7.  If the question asks a semantically equivalent variation of the
secret (e.g., 'laugh' and 'laughter'), answer 'Finished'.
8.  If the text given by the questioner is not a valid question,
answer 'Invalid'.
9.  If the question consists of multiple questions, answer 'Invalid'.
10.  If the question has already been asked in the history of
questions, answer 'Repeated'.
11.  In all other cases, answer either 'Yes' or 'No'.
12.  IMPORTANT: Provide all reasoning and responses in English only.

Please reason step by step, and give your final answer in the format
<answer>[Yes/No/Invalid/Repeated/Finished]</answer>:
```

C.2   GUESS MY CITY

Task Prompt of the Agent for *Guess my City*

```
You are playing a game called 'Guess My City.'  Your task is to guess
the home city of the other player within 20 questions.

You must follow these rules:
1.  You may ask open-ended questions about the city's characteristics,
such as geography, culture, landmarks, cuisine, climate, or other
unique traits.
2.  Do not ask directly for the name of the city or country.
3.  Use the answers from the other player to strategically decide the
next question, your goal is to arrive at the correct city with as few
questions as possible.
4.  After gathering enough information, you can attempt to guess the
city, but each guess counts as one of your 20 questions.

Example questions:  'What is your favorite cuisine from your home
city?', 'Is your home city located near the coastline?', 'What kind of
landmarks is your city known for?'
Your goal is to identify the city through deduction, pattern
recognition, and strategic questioning.

5.  When you are confident, make a guess, by mentioning the name of
the city and the country it is in, for example, 'Is the city Jakarta,
Indonesia?'

The game starts now, and start asking your questions.
```

System Prompt of the Judge for *Guess my City*

You are the environment in a game called 'Guess My City.' You will be given a specific home city (e.g., London, United Kingdom) and you have to respond to the player's questions to help them guess this city.

Follow these rules:
1. Answer the agent player's questions honestly and correctly (i.e., the answers need to be true given the home city given to you at the start of the game), but do not mention the name of your city or its country explicitly. However, you can verify the player's guess about a particular city/country. For example, if the player asks, 'What is your home country?' You should not respond to this question. However, if they ask 'Is your home country United Kingdom?' You should reply with the correct answer based on the home city given to you.
2. Your answers should provide useful clues about your city's geography, culture, landmarks, cuisine, climate, or other unique characteristics.
3. Be as informative as possible to guide the agent player within the rules. Example answers: If the agent asks about cuisine, you could say: 'My city is famous for its seafood dishes and has a vibrant food market scene.' If the agent asks about geography, you might say: 'My city is located near a major river and has a historic port.
4. You should respond with 'Goal reached' if the player has successfully guessed your home city. Ignore minor variations in the spelling of the city, but only if these variations are common.

Remember, you are here to help the agent guess your city through clues, but you must not reveal the city's name or its country directly UNDER ANY CIRCUMSTANCES. If the player asks such a question, reply that you cannot give away the name, and can only confirm the name if the player guesses it.

The game starts now.

Task Prompt of the Judge for *Guess my City*

Now judge whether the player has successfully guessed the correct city, which is {env} in this particular game.

1. Reply to the question in relation to {env}. Please try to be concise and keep it short.
2. NEVER include the actual city or country, in this game {env}, in your answer.
3. If the player asks you to reveal the name of city or country directly, reply 'NOTVALID' as the player is not following the game rules.
4. If the player makes a guess about the city, check if it matches {env}.
- If it does not match, reply with 'No' and short information.
- If it matches, reply with 'Goal reached'.

Question: '{question}'
Give your answer in the format <answer>...</answer>:

C.3 CUSTOMER SERVICE

Task Prompt of the Agent for *Customer Service*

```
You are going to role-play as a customer service agent and you have to
help a customer resolve their issue.  Your goal is to gather enough
information to diagnose the problem and provide solution.

Your instructions are the following:
1.You will need to ask targeted questions or suggest particular
actions to the customer to gather the necessary details.
2.  The customer may not be technically inclined, so keep your
language simple and clear.
3.Avoid making assumptions | ask specific questions to determine
the potential causes.  You should guide the customer through basic
troubleshooting steps and gather data on the situation.
4.  Refine your questions in a strategic way based on the customer's
responses for earlier questions.
5.You should ask questions in an efficient manner, to make the
customer satisfied and resolve their problem as quickly as possible.
You should also keep your responses short and concise.
6.  If the customer mentions a specific product they are using (for
example, ABC electronics), then you are the customer support agent
for that product/company, i.e., you represent that product or company
and have to take appropriate actions without referring the customer to
somewhere else.
7.  Only ask one question at a time to the customer.

Your specific scenario is this:  {scenario}

Please start helping the customer now by asking your first question.
```

System Prompt of the Judge for *Customer Service*

```
You are going to role-play as a customer experiencing a specific issue.
A customer-service agent will ask you questions to assist you (the
customer) to resolve the issue.
Under no circumstances you should tell the customer-service agent what
the exact issue is.  Your goal is to see if the customer-service agent
can come up with the potential solution themselves.
Your role-play starts now.
```

Task Prompt of the Judge for *Customer Service*

```
The particular problem you, the customer, are facing is:  {scenario}.
The solution for your particular scenario is {env}.
Answer the customer-service agent's question as follows:
1.  Only respond to the agent's questions and provide relevant
information when prompted, do not give away the solution.
2.  Your responses should be concise and reflect a typical,
non-technical customer's knowledge level.
3.  When the agent asks you about a potential solution, you should
determine what the outcome would be based on your knowledge about the
true underlying problem, and let the agent know the result.
3.  If the agent's proposed solution does not fix your problem, let
the agent know that it does not solve your problem.
4.  If the agent's proposed solution is correct or they have guessed
the underlying problem correctly, reply with 'Goal reached' (and
nothing more).
Customer-service agent's question:  '{question}'
Give your answer in the format <answer>...</answer>:
```

C.4 MURDER MYSTERY

System Prompt of the Agent for *Murder Mystery*

```
You are playing the role of a detective in a murder mystery game.
The setup for the game is:
1. You will be provided with a scenario describing a crime and its
key elements. Your goal is to solve the mystery by asking questions,
examining evidence, and drawing logical conclusions.
2. For every action you take or question you ask, you will receive
feedback from the game.
3. Your questions and actions should be precise and logical, aimed at
uncovering clues, verifying alibis, and piecing together the sequence
of events. You should strategically choose the next action, given
the information you have already obtained from the game, and choose
actions that lets you catch the culprit as quickly as possible.
4. You can only take a single action at every turn.
5. You have to consider all pieces of information, and scrutinize
all the characters in the game, including the witnesses or background
characters, since the true culprit maybe a witness or a background
character, and might not always be one of the primary suspects
declared at the beginning of the game. Do not focus on any character
too early in the game, rather try to see if anyone's statements are
contradictory.
6. You should always gather enough information before making a
decision --- try not to make a mistake! You should also keep
your mind open about who can be the true culprit and try to be
information-seeking, without being too narrowed down on one suspect
too quickly.
7. Once you believe you have enough evidence, you may state your
conclusion about the case, which will terminate the game.
The game starts now. The particular scenario you have is:
"<environment_description>"
Now, take an action to investigate the crime scene or ask a question
to the characters involved to solve the mystery:
```

System Prompt of the Judge for *Murder Mystery*

```
You are an advanced AI responsible for simulating a challenging and
immersive murder mystery game environment.
You are provided with the full details of the scenario, including the
characters, their backstories, motives, alibis, the sequence of events,
and the true culprit.
Your task is to respond to the actions and inquiries of the detective
player in a manner that maintains the game's logic and adds complexity
to the mystery. Always strive to make the game enjoyable and
intriguing while revealing the absolute minimum information required
for the detective to progress logically.
The game begins now.
```

Task Prompt of the Judge for *Murder Mystery*

```
The true crime scenario with the actual culprit in this game is:
'<gt_description>'.
The detective's last response is: '<question>'.

Respond to the detective's response as follows:
1. Never explicitly reveal who the true culprit is in your response.
2. If the detective makes a clear, direct accusation (e.g., "[Name]
is the murderer/culprit/killer") AND it matches the true culprit,
respond with exactly: "Goal reached".
3. If the detective accuses the wrong person, have the game
```

```
acknowledge this without confirming or denying, and allow them to
continue investigating.
4.  If the detective inspects an item, describe its appearance and
condition.  Reveal clues proportional to how specific or thorough the
inspection is.  Avoid gratuitously revealing details.
5.  If the detective interviews a character, roleplay the character
authentically based on their personality and knowledge.  Characters
protect themselves and may misdirect.  They do not confess or directly
implicate the true culprit.
6.  If the detective takes a physical action (e.g., "I pick up the
knife", "I open the drawer", "I follow the suspect"), describe the
outcome and any immediate observations without revealing information
beyond what the action would naturally uncover.
7.  If the detective's response is vague or incomplete, provide a
brief, neutral environmental observation (e.g., describing the scene)
without advancing toward "Goal reached".
8.  If the detective asks about something not covered in the scenario,
deflect naturally within the fiction.

Give your answer in the format <answer>...</answer>:
```

C.5 USER PERSONALIZATION

Question-Generation Prompt for *User Personalization*

```
You are a question-asking assistant.  You must respond with EXACTLY
ONE question and nothing else.

A user named {user_name} needs help with a request.  Your job is to ask
a single, open-ended question that will reveal the most about their
preferences, background, interests, or desired outcome.  The user's
preferences, background and identity are unknown to you, so your
job is to ask a question to elicit more information about the user.
The open-ended question should attempt to elicit information about
the user's background, preferences, likes and dislikes, interests,
social life and more that would reveal the most about the desired
behavior.  Generate the most informative open-ended question that,
when answered, will reveal the most about the desired behavior beyond
what has already been queried for above (if anything).  Make sure your
question addresses different aspects of the user's request than any
questions that may have already been asked above.

RULES: 1.  Output EXACTLY ONE question (one question mark only); if
you output more than one question, you fail 2.  The question must be
open-ended (not yes/no) 3.  Ask about their preferences, NOT about
factual knowledge 4.  Do NOT answer or attempt to fulfill their
request 5.  Do NOT include any preamble, explanation, or follow-up
6.  If there is prior conversation, ask about a DIFFERENT aspect than
what was already discussed

The user's request:  {original_request}

Your single question:
```

Human Role-Play Prompt for *User Personalization*

```
You are roleplaying a person with the following characteristics:

{persona}

You are asking the following question:  {original_request}
```

```
A helpful AI assistant wants to ask a clarifying question to help
ultimately provide you a good answer.  Please answer the following
question from the perspective of the character you are roleplaying,
using "I" pronouns.  Make your response sound natural.  Crucially, you
should never provide an answer to the question.  You should always
remember that you are roleplaying a human who does not know the answer
to the question, and should reiterate that you are looking for the
assistant's help answering the question, NOT the other way around.
Importantly, keep your answers to their intermediate questions concise,
under 3 sentences.  Your answers to their intermediate questions will
be tantamount in helping them eventually construct a perfect answer
to your question.  Finally, simply provide your response to their
intermediate question without any tags like 'A: ' or 'Answer:  '.
Below is your conversation history with the assistant.

{conversation_history}
You:
```

Response-Generation Prompt for *User Personalization*

```
You are a helpful assistant.  A user named {user_name} asked you for
help with the following request:

"{original_prompt}"

During your conversation, you asked clarifying questions to better
understand their needs.  Here is the conversation:

{conversation_text}

Based on this conversation, provide a helpful, personalized response
to {user_name}'s original request.  Consider the information they
shared about their background, preferences, and needs.

Your response should be concise but informative:  approximately
100-150 words (1-2 short paragraphs).  Give a direct, useful answer
that addresses their request while incorporating relevant details from
the conversation.
```

Gold-Response-Generation Prompt for *User Personalization*

```
You are a helpful AI assistant, particularly skilled at providing
personalized, satisfying answers to users given information about
their background.  You are able to construct responses that are
tailored to their profession, hobbies, interests, relationships,
locations, likes/dislikes and more, while maintaining a natural tone.

You are answering questions for the following user:

{persona}

Answer the question below, tailoring your answer to the user and their
characteristics.  Answer directly to the user (i.e., 'you', 'your'
pronouns).  In addition, incorporate aspects of their background
when it is useful, but do not try to bring in aspects of the user's
personality when they are irrelevant.  Make sure to keep your
answer concise and organized, but thorough.  Keep your response to
ten sentences or less, and keep your response organized and clear.
Finally, while personalizing your answer to the user important, make
sure they ultimately receive a clear answer to the question they
asked.
```

```
{request}
```

Rating Prompt for *User Personalization*

```
You are an expert in evaluating assistant responses, skilled at
analyzing their alignment with user backgrounds and preferences.

Rate the following assistant response based on how well it aligns with
the user's background and addresses their query.

User Background:  {persona}

User Query:  {request}

Assistant Response:  {response}

Rate the response on a scale of 1-10:  - 1-3:  Poor alignment, generic
or irrelevant to user's background - 4-6:  Moderate alignment,
somewhat relevant but could be more tailored - 7-9:  Good alignment,
well-tailored to user's background - 10:  Excellent alignment,
perfectly addresses user's specific needs

Provide brief reasoning (1-2 sentences), then give your score.

You MUST end your response with exactly this format:  Score:  [number
from 1-10]
```

Persona-Generation Prompt for *User Personalization*

```
You are a helpful AI assistant, particularly skilled at writing
creative, diverse personas in the form of characteristics of
humans.  These characteristics describe a user's personality,
identity, characteristics, likes and dislikes, social life and other
information.

Take a deep breath.  Please generate exactly one persona describing a
user.  IMPORTANT: Start your persona with "I'm [Name]." where [Name]
is the person's first name.  Make sure you generate personas with
a diverse set of information that is interesting, unpredictable
and creative.  Crucially, the persona itself need not exhibit an
appreciation or focus on diversity, although it could; however, what
is important is that you generate an interesting, engaging, creative
persona that could serve as a character in a story with an interesting,
complex plot.  The persona should be concise- less than 10 sentences.
Here are a few examples of personas to help you understand what sorts
of categories of characteristics are important to describe.

{few_shot_examples}
```

D DATA CURATION

The secret words for our 20Qs environment are taken from Google's Trillion Word Corpus (Michel et al., 2011). The 10,000 most common nouns were selected using n-grams (Top English Wordlists) and subsequently filtered using Grok 3 m LLM-as-a-judge to decide which words are suitable and solvable for the game (xAI, 2025). To further ensure that the words of the dataset are appropriate, to collect data for supervised fine-tuning (SFT) and to measure the difficulty of each word, we played 32 iterations of Twenty Questions with Gemini 2.0 Flash Gemini Team (2024). Words that passed the initial filtering but were not solved at least once by Gemini were discarded.

The final dataset consists of 4,678 words. These are randomly split into four disjunctive subsets: 238 words as validation set, 487 as test set and the remainder for model training. Of the 3,953 words

remaining for training, the 341 words are chosen for SFT training and 3,612 are reserved for RL training. We perform extensive ablations on the data mixture and choose a set of 1,000 words that are neither too hard nor too difficult for the SFT baseline as final training set. This set is used for all RL training experiments in this study. It is likely that the performance of our method can be further improved by iteratively incorporating secrets at the edge of the agent's capacity into a data curriculum.

E SFT SETTINGS

E.1 SFT DATA

As mentioned above in Appendix D, the training set of the BASELINE(SFT) contains gameplay of a distinct set of 341 words. For each of these secrets, we select the successful rollout of Gemini 2.0 Flash with the lowest number of turns, indicating a comparatively higher-quality of questions. If there is a tie between games with equally few turns, we include them all, resulting in a total of 562 sequences.

E.2 SFT TRAINING

We split the trajectories into individual turns, such that each new question is regarded as its own sample in the training set. The context consisting of the prompts, chat template tokens, previous questions and judge responses are masked, such that we only train on the tokens of the final question for each partial interaction sequence.

We find that this single-turn approach performs better than training with `verl`'s `MultiTurnSFTDataset` on entire sequences at once. Possible explanations are difficulties with the hybrid chat template of `Qwen3` and that it may be beneficial to perform training steps on earlier parts of a sequence before training on the later questions, as this decreases the off-policy gap.

The training is performed using a slightly modified version of `verl`'s `SFTTrainer`. We train for two epochs with cosine decay using a maximum learning rate of `1e-5` and 10% linear warm-up steps. The optimizer is ADAMW with a weight decay of 0.01, β_1 of 0.9 and β_2 of 0.95 (Loshchilov & Hutter, 2019). We set the global batch size to 256 with a maximum of 650 tokens per sequence.

F GRPO SETTINGS

Our implementation adapts the original Group Relative Policy Optimization (GRPO) algorithm to a multi-turn reinforcement learning setting. We introduce the following modifications to the baseline objective:

- **Token Masking**: Standard GRPO is designed for single-turn prompt-response pairs. In our multi-turn environments, trajectories contain tokens generated by both the agent and the environment simulator. To ensure the policy is only optimized on its own outputs, we apply a mask $M_{i,t}$ (where i denotes the sample and t the turn) to exclude environment-generated tokens from the loss calculation.

- **KL Divergence Omission**: Contrary to the original formulation, we found that including a Kullback–Leibler (KL) divergence penalty did not yield significant performance gains in our setting. Consequently, we omit the KL term from the final loss function (see Figure **??** for an empirical comparison).

- **Asymmetric Clipping**: We employ an asymmetric clipping range to allow for larger policy updates in the positive direction while maintaining stability, as introduced by DAPO (Yu et al., 2025). Specifically, we set the upper clipping bound to $\epsilon_{\text{high}} = 0.28$ and the lower bound to $\epsilon_{\text{low}} = 0.2$.

- **Per-Turn Advantage Estimation**: As detailed in Section 3.2, we calculate advantages at a per-turn granularity rather than over the entire trajectory. This approach reduces variance and provides a more precise credit assignment for specific information-seeking actions.

F.1 STARPO ABLATIONS

To ensure that CIA is compared fairly, we performed multiple ablations on the GRPO baseline (StarPO). These focus on the aggregation method of the loss and learning rate. Especially the latter was shown to be relevant in our specific setting, with `sequence-mean-token-mean` aggregation being necessary for optimal training. These baselines use the hyperparameter combination that was found to be ideal in the ablations and the default, sequence-wise GRPO-objective. Unless otherwise noted, all other parameters are exactly the same as for our method, including using LoRA and the rewards for the final, verifiable outcome and for efficient exploration, as introduced in Section **??**.

Table 5: Aggregation methods and learning rates. Ablation results of different aggregation methods and learning rates for the GRPO training of `Qwen3-1.7B` (STARPO-1.7B). The best result is shown in bold.

Aggregation	LR $= 1 \times 10^{-5}$	LR $= 3 \times 10^{-5}$
seq-mean-token-mean	**16.54%**	15.85%
token-mean	12.24%	12.50%

Table 6: Aggregation methods and learning rates. Ablation results of different aggregation methods and learning rates for the GRPO training of `Qwen3-4B` (STARPO-4B). The best result is shown in bold.

Aggregation	LR $= 1 \times 10^{-5}$	LR $= 3 \times 10^{-5}$
seq-mean-token-mean	20.21%	**24.36%**
token-mean	21.07%	21.54%