EXPLORING VULNERABILITIES OF BERT-BASED APIS

ABSTRACT

Natural language processing (NLP) tasks, ranging from text classification to text generation, have been revolutionised by pretrained BERT models. This allows corporations to easily build powerful APIs by encapsulating fine-tuned BERT models. These BERT-based APIs are often designed to not only provide reliable service but also protect intellectual properties or privacy-sensitive information of the training data. However, a series of privacy and robustness issues may still exist when a fine-tuned BERT model is deployed as a service. In this work, we first present an effective model extraction attack, where the adversary can steal a BERT-based API (the victim model), without knowing the victim model's architecture, parameters or the training data distribution. We then demonstrate how the extracted model can be exploited to develop effective attribute inference attack to expose sensitive information of the training data. We also show that the extracted model can lead to highly transferable adversarial attacks against the original model. Extensive experiments on multiple benchmark datasets under various settings validate the potential privacy issues and adversarial vulnerabilities of BERT-based APIs.

1 INTRODUCTION

The emergence of **B**idirectional **E**ncoder **R**epresentations from **T**ransformers (BERT) (Devlin et al., 2018) has revolutionised the natural language processing (NLP) field, leading to state-of-the-art performance on a wide range of NLP tasks with minimal task-specific supervision. In the meantime, with the increasing success of contextualised pretrained representations for transfer learning, powerful NLP models can be easily built by fine-tuning the pretrained models like BERT or XLNet (Yang et al., 2019). Building NLP models on pretrained representations typically only require several task-specific layers or just a single feedforward layer on top of BERT. To protect data privacy, system integrity and Intellectual Property (IP), commercial NLP models such as Google's BERT and OpenAI's GPT-2 (Radford et al., 2019) are often made indirectly accessible through pay-per-query prediction APIs. This leaves model prediction the only information an attacker can access.

Prior works have found that existing NLP APIs are still vulnerable to model extraction attack, which reconstructs a copy of the remote NLP model based on carefully-designed queries and the outputs of the API (Krishna et al., 2019; Wallace et al., 2020). Pretrained BERT models further make it easier to apply model extraction attack to specialised NLP models obtained by fine-tuning pretrained BERT models (Krishna et al., 2019). It is thus of paramount importance to ask the following two questions: 1) what sensitive information will be exposed by the extracted model; and 2) whether the extracted model can cause more vulnerabilities of the target/victim model (i.e. the black-box API).

To answer the above two questions, in this work, we first launch a model extraction attack, where the adversary queries the target model with the goal to steal it and turn it into a white-box model. With the extracted model, we further demonstrate that: 1) it is possible to infer sensitive information about the training data; and 2) the extracted model can be exploited to generate highly transferable adversarial attacks against the remote victim model behind the API. Our results highlight the risks of publicly-hosted NLP APIs being stolen and attacked if they are trained by fine-tuning BERT.

Contributions: First, we demonstrate that the extracted model can be exploited by an attribute inference attack to expose more sensitive information about the original training data, leading to a significant privacy leakage. Second, we show that adversarial examples crafted on the extracted model are highly transferable to the target model, exposing more adversarial vulnerabilities of the

target model. Third, extensive experiments with the extracted model on benchmark NLP datasets highlight the potential privacy issues and adversarial vulnerabilities of BERT-based APIs. We also show that both attacks developed on the extracted model can evade existing defence strategies.

2   RELATED WORK

2.1   MODEL EXTRACTION ATTACK (MEA)

Model extraction attacks (also referred to as "stealing" or "reverse-engineering") have been studied both empirically and theoretically, for simple classification tasks (Tramèr et al., 2016), vision tasks (Orekondy et al., 2019), and NLP tasks (Chandrasekaran et al., 2020). As opposed to stealing parameters (Tramèr et al., 2016), hyperparameters (Wang & Gong, 2018), architectures (Oh et al., 2019), training data information (Shokri et al., 2017) and decision boundaries (Tramèr et al., 2016; Papernot et al., 2017), in this work, we attempt to create a local copy or steal the functionality of a black-box victim model (Krishna et al., 2019; Orekondy et al., 2019), that is a model that replicates the performance of the victim model as closely as possible. If reconstruction is successful, the attacker has effectively stolen the intellectual property.

Furthermore, this extracted model could be used as a reconnaissance step to facilitate later attacks (Krishna et al., 2019). For instance, the adversary could use the extracted model to facilitate private information inference about the training data of the victim model, or to construct adversarial examples that will force the victim model to make incorrect predictions.

Comparison to Knowledge Distillation (KD). Model extraction is closely related to KD approaches (Hinton et al., 2015): training a student model to imitate the predictions of a teacher. However, model extraction differs from KD in the following three important aspects: (1) Goal: Distillation aims to transfer knowledge from a large model to a small model. This compression is not needed in model extraction. Instead, the adversary is primarily interested in the functionality of the victim model; (2) Data distribution: KD usually assumes access to the original training dataset or a different dataset sampled from the same distribution as the original training data's distribution. In model extraction, the training data is often unknown to the attacker; (3) True labels for supervision: the true labels are usually necessary for KD as well, while they are missing from model extraction.

2.2   ATTRIBUTE INFERENCE ATTACK

Fredrikson et al. (2014) first proposed *model inversion attack* on biomedical data. The goal is to infer some missing attributes of an input feature vector based on the interaction with a trained ML model. Since deep neural networks have the ability to memorise arbitrary information (Zhang et al., 2017), the private information can be memorised by BERT as well, which poses a threat of information leakage (Krishna et al., 2019). In NLP application, the input text often provides sufficient clues to portray the author, such as gender, age, and other important attributes. For example, sentiment analysis tasks often have privacy implications for authors whose text is used to train models. Prior works (Coavoux et al., 2018) have shown that user attributes can be easily detectable from online review data, as used extensively in sentiment analysis results (Hovy et al., 2015). One might argue that sensitive information like gender, age, location and password are all not explicitly included in model predictions. Nonetheless, model predictions are produced from the input text, it can meanwhile encode personal information which might be exploited for adversarial usages, especially a modern deep learning model owns more capacity than they need to perform well on their tasks (Zhang et al., 2017). The naive solution of removing protected attributes is insufficient: other features may be highly correlated with, and thus predictive of, the protected attributes (Pedreshi et al., 2008).

2.3   ADVERSARIAL TRANSFERABILITY AGAINST NLP SYSTEM

An important property of adversarial examples is their transferability (Szegedy et al., 2014; Goodfellow et al., 2015; Papernot et al., 2017). It has been shown that adversarial examples generated against one network can also successfully fool other networks (Liu et al., 2016; Papernot et al., 2017), especially the adversarial image examples in computer vision. Similarly, in NLP domain, adversarial examples that are designed to manipulate the substitute model can also be misclassified by the target model are considered transferable (Papernot et al., 2017; Ebrahimi et al., 2018). Ad-

Figure 1: The workflow of the proposed attacks. Phase 1 (model extraction attack): we first sample queries, label them using the victim API, and then train an extracted model on the resulting data. Phase 2: we mount attribute inference attack (bottom left) and transfer adversarial attack (bottom right) based on the extracted model. For attribute inference attack, we train an extra attack model to infer the demographic attributes from BERT representation on any input text, causing privacy leakage of sensitive attributes. For transferred adversarial attack, we first generate adversarial typo examples on the extracted model, then apply them to attack the victim API.

versarial transferability against NLP system remains largely unexplored. Few recent works have attempted to transfer adversarial examples to the NLP systems (Sun et al., 2020; Wallace et al., 2020), however, it remains unknown how the transferability works against BERT-based APIs, and whether the transferability would succeed when the victim model and the substitute (extracted) model have different architectures.

3 ATTACKING BERT-BASED API

In this work, we consider an adversary looking to steal or attack BERT-based APIs, either for financial gain or to exploit private information or model errors. As shown in Figure 1, the whole attack pipeline against BERT-based APIs can be summarised into two phases. In phase one (*model extraction attack* (MEA)), we first sample queries, label them using the victim API, and then train an extracted model on the resulting data. In phase two, we conduct *attribute inference attack* (AIA) and *adversarial example transfer* (AET) based on the extracted model. We empirically validate that the extracted model can help *enhance* privacy attack and adversarial example transferability in Section 4.3 and Section 4.4.

We remark that our attack pipeline is applicable to many remote BERT-based APIs, as we assume: (a) the capabilities required are limited to observing model output by the APIs; (b) the number of queries is limited.

3.1 VICTIM MODEL: BERT-BASED API

Modern NLP systems are typically based on a pretrained BERT. BERT produces rich natural language representations which transfer well to most downstream NLP tasks (sentiment analysis, topic classification, etc.). Modern NLP systems typically leverage the fine-tuning methodology by adding a few task-specific layers on top of the publicly available BERT base,[1] and fine-tune the whole model.

3.2 MODEL EXTRACTION ATTACK (MEA)

Model extraction attack aims to steal an intellectual model from cloud services. In this attack, we assume a "victim model" g_V is a commercially available black-box API for task T, *i.e.,* the model architecture, hyperparameters, or training data are not publicly available, and an adversary with

---

[1] https://github.com/google-research/bert

Dataset	Private Variable	#Train	#Dev	#Test	Category
TP-US	age, gender	22,142	2,767	2,767	sentiment analysis
AG	entity	11,657	1,457	1,457	topic classification
AG full	-	112k	1,457	1,457	topic classification
Blog	age, gender	7,098	887	887	topic classification
Yelp	-	520k	40,000	1,000	sentiment analysis

Table 1: Summary of NLP datasets.

black-box query access to g_V attempts to reconstruct a local copy g'_V ("extracted model") of the victim model. In a nutshell, we perform model extraction attack in a transfer learning setting, where both the adversary and the victim model fine-tune a pretrained BERT. The goal is to extract a model with comparable accuracy to the victim model. Generally, MEA can be formulated as a two-step approach, as illustrated by the top figure in Figure 1:

1. Attacker crafts a set of inputs as queries (transfer set), then sends them to the victim model (BERT-based API) to obtain predictions;

2. Attacker reconstructs a copy of the victim model as an "extracted model" using the queried query-prediction pairs.

Since the attacker does not have training data for g_V, we apply a task-specific query generator to construct m queries $\{x_i\}_1^m$ to the victim model. For each x_i, g_V returns a K-dim posterior probability vector $y_i \in [0, 1]^k$, $\sum_k y_i^k = 1$. The resulting dataset $\{x_i, y_i\}_1^m$ is used to train g'_V. Specifically, we assume that the attacker fine-tunes the public release of $f_{\text{bert}, \theta^*}$ on this dataset to obtain g'_V, which mimics the behaviour of g_V. Once the local copy g'_V is obtained, the attacker does not have to pay the provider of the original API anymore for predicting on new data points.

3.3 ATTRIBUTE INFERENCE ATTACK (AIA)

Next, we investigate how to use the extracted model to aid the attribute inference of the private training data of the victim model, *i.e., attribute inference attack* (AIA) (Song & Raghunathan, 2020). We remark that AIA is different from inferring attribute distribution as in model inversion attack (Yeom et al., 2018). The intuition behind AIA is that the BERT representation generated by the extracted model can be used to infer the sensitive information of the private training data of the victim model (Li et al., 2018b; Coavoux et al., 2018). Note that in our work, the only explicit information that is accessible to the attacker is model prediction given by the victim model to the chosen inputs, rather than the original BERT representation. We specifically exploit BERT representation of the extracted model, as it encodes the most useful information for the follow-up classification. A more detailed description can be referred to Appendix B.

3.4 ADVERSARIAL EXAMPLE TRANSFER (AET)

Most existing adversarial attacks on BERT are white-box settings, requiring knowledge of either the model internals (*e.g.,* model architecture, hyperparameters) or training data. However, based on our knowledge, only recent works start to study the black-box settings. Most of them require many queries since their target is each sample instead of the whole model (Zhang et al., 2020; Tan et al., 2020; Zang et al., 2020). To circumvent this issue, we leverage the transferability of adversarial examples: we first generate adversarial examples for our extracted model, then transfer them to the BERT-based APIs. The intuition lies in the fact that the similarity of our extracted model and the victim model allows for direct transfer of adversarial examples obtained via gradient-based attacks. Here the extracted model serves as a surrogate to craft adversarial examples in a white-box manner.

4 EXPERIMENTS AND ANALYSIS

4.1 NLP TASKS AND DATASETS

We extract models on four diverse NLP datasets that focus on two main tasks: sentiment analysis and topic classification. The four NLP datasets include TP-US from Trustpilot Sentiment dataset (Hovy

Model		AG news	AG news (full)	Blog	TP-US	Yelp
Victim model / API		79.99	94.47	97.07	85.53	95.57
All Same		**80.83**	**94.54**	**96.77**	**86.48**	**95.72**
Data Different (review)	1x	69.94	88.63	88.16	85.15	94.06
	5x	75.29	91.27	92.75	85.82	94.95
Data Different (news)	1x	71.95	90.47	83.13	84.15	91.06
	5x	75.82	92.26	87.64	85.46	93.13

Table 2: Accuracy [%] of the victim models and the extracted models among different datasets in terms of domains and sizes.

et al., 2015), AG news corpus (Del Corso et al., 2005), Blog posts dataset from the blog authorship corpus (Schler et al., 2006), and YELP dataset (Zhang et al., 2015). Table 1 summarises the statistics of the used datasets. A more detailed description can be referred to Appendix A.

4.2 MEA

We measure the accuracy (on the same held-out test set for evaluation purposes) between the outputs of the victim model and the extracted model to assess their functional similarity. In line with prior work (Krishna et al., 2019), we first choose the size of the resulting transfer set (queries) to be comparable (e.g., 1x) to the size of victim's training set, then scale up to 5x.

Attack Strategies We first study model extraction through simulated experiments: we train victim models, query them as if they are black-box APIs, and then train the extracted model to mimic the victim model. We assume that the attacker has access to the freely available pretrained BERT model used by the victim model.

Query Distribution To investigate how the data distribution of queries (P_A) may impact the attack on the victim model trained on data from P_V (*c.f.,* Table 1), we experiment with the following experiments (architectural difference can be found in Appendix D):

1. We use the same architecture, hyperparameters, and the original data as the victim (All Same).

2. We use the same architecture and hyperparameters as the victim, but sample queries from different distribution (Data Different).

The second scenario makes fewer assumptions and is more realistic and challenging, as the attacker may not know the target data distribution as a prior. Therefore, in addition to the same data distribution as the victim, we additionally investigate the query distribution P_A sourced from the following corpora:

- Reviews data: Yelp and Amazon reviews dataset (Zhang et al., 2015)
- News data: CNN/DailyMail dataset (Hermann et al., 2015)

Regarding the experiments of MEA, our general findings from Table 2 include: (1) using same data (All Same) as queries achieves the best extraction performance, validating that the closeness of the domain between the victim training data and queries is positively correlated to the extraction; (2) using same data can achieve comparable accuracies, even outperform the victim models, we hypothesise this is due to the regularising effect of training on soft-labels (Hinton et al., 2015); (3) our MEA is effective despite the fact that queries may come from different distributions. Using samples from different corpora (review and news) as queries, our MEA can still achieve 0.85-0.99$\times$ victim models' accuracies when the number of queries varies in {1x,5x}, and the extraction is more successful with 5x queries. This facilitates the follow-up AIA and AET. Even with small query budgets (0.1x and 0.5x), extraction is often successful. More results are available in Appendix C. From now, unless otherwise mentioned, because of their effectiveness (*c.f.,* Table 2), we will use *news* data for AG news, and *reviews* data for TP-US, Blog and Yelp.[2]

---

[2]Empirically, we do not have access to the training data of the victim model.

4.3 AIA

For AIA, we conduct our studies on TP-US, AG news and Blog datasets, as there is no matching demographic information for Yelp. AIA is appraised via the following metrics:

- For demographic variables (*i.e.,* gender and age): $1 - X$, where X is the average over the accuracies of the prediction by the attackers on these two variables.
- For named entities: $1 - F$, where F is the F1 score between the ground truths and the prediction by the attackers on the presence of all named entities.

We denote the value of $1 - X$ or $1 - F$ as *empirical privacy*, *i.e.,* the inverse accuracy or F1 score of the attacker, higher means better empirical privacy, *i.e.,* lower attack performance.

We first randomly split each dataset in Table 1 into two halves. The first half $\mathcal{D}_V$ is used to train a victim model, whereas the second half $\mathcal{D}_A$ is specifically reserved for the training of AIA attack model. On the extracted model from MEA, attackers can determine how to infer the private attributes from the BERT representation h of the extracted model over $\mathcal{D}_A$. Each attacker consists of a multi-layer feed forward network and a binary classifier, which takes the h as the inputs and emits the predicted private attributes. Once the attackers are obtained, we measure the empirical privacy of the target model by the ability of an attacker to predict accurately the specific private information of $\mathcal{D}_V$.

Apart from the standard three corpora used for MEA (*c.f.,* Section 4.2), in AIA, we also consider $\mathcal{D}_A$ (2nd half) as queries, which is derived from the same distribution of $\mathcal{D}_V$. It is worth noting that for AG news, we use the filtered AG news (*c.f.,* Appendix A) with sensitive entity information for AIA.

To gauge the private information leakage, we consider a majority class prediction of each attribute as a baseline. To evaluate whether our extracted model can help enhance AIA, we also take the pretrained BERT without (w/o) fine-tuning as a baseline. Table 3 shows that compared to the pretrained only BERT, the attack model built on the BERT representation of the extracted model indeed largely enhances the attribute inference of the training data of the victim model — more than 4x effective for AG news compared with the majority baseline, even though MEA is based on the queries from different data distribution. This implies that target model predictions inadvertently capture sensitive information about users, such as their gender, age, and other important attributes, apart from the useful information for the main task (*c.f.,* Table 2).

Interestingly, compared with queries from the same distribution, Table 3 shows that queries from different distributions make AIA easier (see the best results corresponding to the lower privacy protections in bold in Table 3). We believe this anti-intuitive phenomenon is caused by the posterior probability, as the posterior probability of the same distribution is sharper than that of the different distribution.[3] This argument can be also confirmed from Section 5, where we use a temperature coefficient τ at the softmax layer to control the sharpness of the posterior probability.

We speculate that the effectiveness of AIA is related to the undesired deep model memorisation of the victim model, which can be spread to the extracted model through model prediction, incurring information leakage.

We further investigate which kind of attribute is more vulnerable, *i.e.,* the relationship between attribute distribution (histogram variance) and privacy leakage. We empirically found that, compared with the attribute with higher variance, attribute with lower variance is harder to attack.[4]

4.4 AET

Since we have access to the parameters of the locally extracted model, we craft white-box adversarial examples on it and test whether such examples are transferable to the target model. We evaluate sample crafting using the metric of transferability, which refers to the victim API misclassification rate of adversarial samples. We use Blog, TP-US, AG news (full) and Yelp for AET.

How We Generate Natural Adversarial Examples? Following Sun et al. (2020), we first leverage the gradients of the gold labels w.r.t the embeddings of the input tokens to find the most informative tokens. Then we corrupt the selected tokens with the following six sources of typos: 1) Insertion; 2) Deletion;

---

[3]Please refer to the Appendix C for the detailed analysis.
[4]Please refer to the Appendix C for the detail.

	AG news	Blog	TP-US
Majority class	49.94	49.57	38.15
BERT (w/o fine-tuning)	69.39	44.03	49.38
All Same	22.74	36.37	36.76
Data Different (2nd half)			
1x	21.01	35.98	37.34
Data Different (review)			
1x	17.93	34.34	**35.97**
5x	18.31	34.45	36.82
Data Different (news)			
1x	**15.76**	**33.88**	36.92
5x	17.91	35.39	37.68

Table 3: Privacy protection of attribute inference over different data sets. Note higher privacy means better empirical privacy, *i.e.,* lower attack performance. (2nd half: $\mathcal{D}_A$ reserved for the training of AIA attack model.)

3) Swap; 4) Mistype: Mistyping a word though keyboard, such as "oh" → "0h"; 5) Pronounce: Wrongly typing due to the close pronounce of the word, such as "egg" → "agg"; 6) Replace-W: Replace the word by the frequent human behavioural keyboard typo based on the statistics.[5] Note that the above operations are constrained by the character distribution on the keyboard.

To evaluate whether our extracted model is needed to mount transferable attacks, we also attack it by using black-box adversarial examples. Compared with the black-box adversarial examples, Table 4 shows that the adversarial examples crafted on our extracted model via the white-box attack make the target model more vulnerable to adversarial examples in terms of transferability — more than twice effective in the best case. This validates that our extracted model, which is designed to be a high-fidelity imitation of the victim model, considerably enhances the adversarial example transferability, thus severely damaging the output integrity of the victim model.

We examine potential factors that contribute to the successful transferability. We found that collecting a larger number of queries contributes to a better attack performance, *i.e.,* 5x queries generally results in much better transferability compared with 1x.

		AG news (full)	Yelp	TP-US	Blog
		transferability			
black-box	deepwordbug				
	1x	25.6	13.5	18.4	52.9
	5x	35.3	20.7	18.2	67.8
	textbugger				
	1x	16.1	11.3	21.3	41.2
	5x	24.7	16.3	21.1	62.7
	textfooler				
	1x	18.5	12.3	27.5	34.7
	5x	24.9	16.9	27.1	64.4
w-box (ours)	adv-bert				
	1x	46.2	17.8	**43.4**	64.9
	5x	**52.6**	**25.2**	41.3	**76.5**

Table 4: Transferability is the ratio of adversarial examples transferring from the extracted model to the victim model. Higher is better. deepwordbug (Gao et al., 2018); textbugger (Li et al., 2018a); textfooler (Jin et al., 2019); adv-bert (Sun et al., 2020). w-box: white-box attack.

This implies that the extracted model with higher fidelity (closer to the victim model, *c.f.,* Table 2) can considerably enhance the adversarial example transferability.

5 DEFENCE

Although we primarily focus on the vulnerabilities of BERT-based APIs in this work, we briefly discuss several counter strategies the victim model may adopt to reduce the informativeness of prediction while minimising the overall drop in API performance (Shokri et al., 2017).

---

[5]https://en.wikipedia.org/wiki/Wikipedia:Lists_of_common_misspellings

	TP-US			AG news		AG news (full)	
	MEA	AIA	AET	MEA	AIA	MEA	AET
ND	85.15	36.92	43.4	71.95	15.76	90.47	46.2
SOFTENING ($\tau = 0.5$)	85.10	**37.69**	50.9	72.32	20.78	90.29	33.1
SOFTENING ($\tau = 5$)	85.33	33.17	58.7	72.48	11.32	90.87	53.3
HARD LABEL	**84.60**	37.62	**40.2**	**69.11**	**22.47**	**89.98**	**33.0**

Table 5: Attack performance under different defences and datasets. ND: no defence; τ: temperature on softmax. For MEA and AET, **lower** scores indicate better defences, conversely for AIA. All experiments are conducted with 1x queries.

Hard label only. The posterior probability usually leaks more information from the victim model, thus victim model can choose to only return the hard label.

Softening predictions. A temperature coefficient τ on softmax layer manipulates the distribution of the posterior probability. A higher τ leads to smoother probability, whereas a lower one produces a sharper distribution. When τ is approaching 0, the posterior probability becomes a hard label.

Table 5 indicates that although varying temperature on softmax cannot defend the victim model against MEA, it is an effective defensive approach to AIA when $\tau = 0.5$. Similarly, compared with ND, hard label can help mitigate all attacks to some extent.[6]

Overall, there is no defence that is effective against all our attacks (*c.f.,* Table 2, Table 3, Table 4), as all these defences preserve the rank of the most confident label. Models can still be effectively stolen and exploited using just the hard label or the smoothed predictions returned by the black-box API. This further validates that the adversary only needs to have access to the victim model's hard label, and does not always need to have access to the confidence scores for our attacks to be successful.

6 DISCUSSION

Understanding how well our attacks work in various settings is important for defenders to know how vulnerable their systems are. Extensive experiments in this paper indicate that the privacy and robustness of an NLP system depend on the model complexity as well as the task. For example, the privacy leakage of the victim model becomes more serious by inferring from the extracted model for AG news and Blog, while this phenomenon is less obvious for TP-US dataset (*c.f.,* Table 3). In terms of robustness against adversarial example transferability, Blog is more vulnerable (*c.f.,* Table 4).

Defence against all our investigated attacks in this work is a hard and open problem. An ideal defence should resist against all the possible attacks while striving to have a minimal impact on legitimate users of the model (Orekondy et al., 2019). While current defences are marginally effective, they may fail when adversaries adapt to the defence — sophisticated adversaries might anticipate these defences and develop simple modifications to their attacks to circumvent these defences (Krishna et al., 2019). We hope that this work highlights the need for more research in the development of effective countermeasures to defend against these attacks, or at least to increase the cost of adversaries.

7 CONCLUSIONS

This work goes far beyond only model extraction from BERT-based APIs, we also identified that the extracted model can largely enhance the privacy leakage and adversarial example transferability even in difficult scenarios (*e.g.,* limited query budget, queries from different distributions). Extensive experiments based on representative NLP datasets and tasks under various settings demonstrate the effectiveness of our attacks against BERT-based APIs. We hope that our in-depth investigation can provide new insights, and arouse the awareness of the community for building more trustworthy BERT-based API. A number of avenues for further work are attractive. More broadly, we expect to extend our work to more complex NLP tasks, and develop defences that can ensure privacy, robustness, and accuracy simultaneously.

---

[6]We observe the similar behaviours for Yelp and Blog.

REFERENCES

Varun Chandrasekaran, Kamalika Chaudhuri, Irene Giacomelli, Somesh Jha, and Songbai Yan. Exploring connections between active learning and model extraction. In *29th {USENIX} Security Symposium ({USENIX} Security 20)*, pp. 1309–1326, 2020.

Maximin Coavoux, Shashi Narayan, and Shay B. Cohen. Privacy-preserving neural representations of text. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 1–10, 2018.

Gianna M Del Corso, Antonio Gulli, and Francesco Romani. Ranking a stream of news. In *Proceedings of the 14th international conference on World Wide Web*, pp. 97–106, 2005.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Javid Ebrahimi, Anyi Rao, Daniel Lowd, and Dejing Dou. Hotflip: White-box adversarial examples for text classification. In *ACL*, 2018.

Matthew Fredrikson, Eric Lantz, Somesh Jha, Simon Lin, David Page, and Thomas Ristenpart. Privacy in pharmacogenetics: An end-to-end case study of personalized warfarin dosing. In *23rd {USENIX} Security Symposium ({USENIX} Security 14)*, pp. 17–32, 2014.

Ji Gao, Jack Lanchantin, Mary Lou Soffa, and Yanjun Qi. Black-box generation of adversarial text sequences to evade deep learning classifiers. In *2018 IEEE Security and Privacy Workshops (SPW)*, pp. 50–56. IEEE, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

Karl Moritz Hermann, Tomas Kocisky, Edward Grefenstette, Lasse Espeholt, Will Kay, Mustafa Suleyman, and Phil Blunsom. Teaching machines to read and comprehend. In *Advances in neural information processing systems*, pp. 1693–1701, 2015.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Dirk Hovy, Anders Johannsen, and Anders Søgaard. User review sites as a resource for large-scale sociolinguistic studies. In *Proceedings of WWW*, pp. 452–461, 2015.

Di Jin, Zhijing Jin, Joey Tianyi Zhou, and Peter Szolovits. Is bert really robust? a strong baseline for natural language attack on text classification and entailment. *arXiv*, pp. arXiv–1907, 2019.

Kalpesh Krishna, Gaurav Singh Tomar, Ankur P Parikh, Nicolas Papernot, and Mohit Iyyer. Thieves on sesame street! model extraction of bert-based apis. *arXiv preprint arXiv:1910.12366*, 2019.

Jinfeng Li, Shouling Ji, Tianyu Du, Bo Li, and Ting Wang. Textbugger: Generating adversarial text against real-world applications. *arXiv preprint arXiv:1812.05271*, 2018a.

Yitong Li, Timothy Baldwin, and Trevor Cohn. Towards robust and privacy-preserving text representations. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pp. 25–30, 2018b.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. *arXiv preprint arXiv:1611.02770*, 2016.

Seong Joon Oh, Bernt Schiele, and Mario Fritz. Towards reverse-engineering black-box neural networks. In *Explainable AI: Interpreting, Explaining and Visualizing Deep Learning*, pp. 121–144. Springer, 2019.

Tribhuvanesh Orekondy, Bernt Schiele, and Mario Fritz. Knockoff nets: Stealing functionality of black-box models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4954–4963, 2019.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia conference on computer and communications security*, pp. 506–519, 2017.

Dino Pedreshi, Salvatore Ruggieri, and Franco Turini. Discrimination-aware data mining. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 560–568, 2008.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8):9, 2019.

Jonathan Schler, Moshe Koppel, Shlomo Argamon, and James W Pennebaker. Effects of age and gender on blogging. In *AAAI spring symposium: Computational approaches to analyzing weblogs*, volume 6, pp. 199–205, 2006.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18. IEEE, 2017.

Congzheng Song and Ananth Raghunathan. Information leakage in embedding models. *arXiv preprint arXiv:2004.00053*, 2020.

Lichao Sun, Kazuma Hashimoto, Wenpeng Yin, Akari Asai, Jia Li, Philip Yu, and Caiming Xiong. Adv-bert: Bert is not robust on misspellings! generating nature adversarial samples on bert. *arXiv preprint arXiv:2003.04985*, 2020.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

Samson Tan, Shafiq Joty, Min-Yen Kan, and Richard Socher. It's morphin'time! combating linguistic discrimination with inflectional perturbations. *arXiv preprint arXiv:2005.04364*, 2020.

Florian Tramèr, Fan Zhang, Ari Juels, Michael K Reiter, and Thomas Ristenpart. Stealing machine learning models via prediction apis. In *25th {USENIX} Security Symposium ({USENIX} Security 16)*, pp. 601–618, 2016.

Eric Wallace, Mitchell Stern, and Dawn Song. Imitation attacks and defenses for black-box machine translation systems. *arXiv preprint arXiv:2004.15015*, 2020.

Binghui Wang and Neil Zhenqiang Gong. Stealing hyperparameters in machine learning. In *2018 IEEE Symposium on Security and Privacy (SP)*, pp. 36–52. IEEE, 2018.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. In *Advances in neural information processing systems*, pp. 5753–5763, 2019.

Samuel Yeom, Irene Giacomelli, Matt Fredrikson, and Somesh Jha. Privacy risk in machine learning: Analyzing the connection to overfitting. In *2018 IEEE 31st Computer Security Foundations Symposium (CSF)*, pp. 268–282. IEEE, 2018.

Yuan Zang, Fanchao Qi, Chenghao Yang, Zhiyuan Liu, Meng Zhang, Qun Liu, and Maosong Sun. Word-level textual adversarial attacking as combinatorial optimization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 6066–6080, 2020.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In *ICLR*, 2017.

Huangzhao Zhang, Hao Zhou, Ning Miao, and Lei Li. Generating fluent adversarial examples for natural languages. *arXiv preprint arXiv:2007.06174*, 2020.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in neural information processing systems*, pp. 649–657, 2015.

APPENDIX

A   DATASET DESCRIPTION

Trustpilot (TP)   Trustpilot Sentiment dataset (Hovy et al., 2015) contains reviews associated with a sentiment score on a five point scale, and each review is associated with 3 attributes: gender, age and location, which are self-reported by users. The original dataset is comprised of reviews from different locations, however in this paper, we only derive TP-US for study. Following Coavoux et al. (2018), we extract examples containing information of both gender and age, and treat them as the private information. We categorise "age" into two groups: "under 34" (U34) and "over 45" (O45).

AG news   We use AG news corpus (Del Corso et al., 2005). This task is to predict the topic label of the document, with four different topics in total. Following (Zhang et al., 2015; Jin et al., 2019), we use both "title" and "description" fields as the input document.

We use full AG news dataset for MEA and AET, which we call AG news (full). As AIA requires entity information, we use the corpus filtered by Coavoux et al. (2018)[7], which we call AG news. The resultant AG news merely includes sentences with the five most frequent person entities, and each sentence contains at least one of these named entities. Thus, the attacker aims to identify these five entities as 5 independent binary classification tasks.

Blog posts (Blog)   We derive a blog posts dataset (Blog) from the blog authorship corpus presented (Schler et al., 2006). We recycle the corpus preprocessed by Coavoux et al. (2018), which covers 10 different topics. Similar to TP-US, the private variables are comprised of the age and gender of the author. And the age attribute is binned into two categories, "under 20" (U20) and "over 30" (O30).

Yelp Polarity (Yelp)   Yelp dataset is a document-level sentiment classification (Zhang et al., 2015). The original dataset is in a five point scale (1-5), while the polarised version assigns negative labels to the rating of 1 and 2 and positive ones to 4 and 5.

B   AIA ALGORITHM

The main algorithm for *Attribute Inference Attack* (AIA) is shown in Algorithm 1. For each dataset, once the extracted model g'_V is built, we query g'_V with D_A to collect the BERT representation $\boldsymbol{h}(x_i)$ for each $x_i \in D_A$. For each sensitive attribute s, a specific attacker (*c.f.,* Section 4.3) is trained on $\{(\boldsymbol{h}(x_i), s_i)\}$, in order to infer the private attributes of the interest; in our case, they are gender, age and named entities (*c.f.,* Table 1).

In more detail, in Algorithm 1, given D_A, we take the non-sensitive attributes x_i as input, and the sensitive attribute s_i as label to train an AIA attack model. During test time, attacker could feed the non-sensitive attributes of any input into the trained model to infer the sensitive attribute. In the case when the attacker gets the non-sensitive attributes of any victim training record, the attacker can successfully infer its sensitive attributes, thus causing privacy leakage of the victim training data (*c.f.,* Table 3, we use the non-sensitive attributes of D_V as test data, and demonstrate the sensitive attribute privacy leakage of D_V). Note that the non-sensitive attributes of the victim training data could be accessible to any attacker.

C   ABLATION STUDY

Query Size   Due to the budget limit, malicious users cannot issues massive requests. To investigate the attack performance of model extraction under the low-resource setting, we conduct two additional experiments, which only utilise 0.1x and 0.5x of the training data of the victim models respectively. According to Table 6, although some dataset such as Blog suffers from a drastic drop, the overall performance of extracted models is comparable to the victim models. In addition, distant domains

---

[7]https://github.com/mcoavoux/pnet/tree/master/datasets.

Algorithm 1 Attribute inference attack

1: **Input:** extracted model g'_V, labelled auxiliary data $D_A = (x_i, s_i)$, BERT representation $\boldsymbol{h}$, sensitive input x^*
2: Query g'_V with D_A and collect $\{(\boldsymbol{h}(x_i), s_i) | (x_i, s_i) \in D_A\}$.
3: Train a classifier f that predicts s on $\{(\boldsymbol{h}(x_i), s_i)\}$.
4: Query g'_V with x^* to get the target BERT representation $\boldsymbol{h}(x^*)$
5: **return** $f(\boldsymbol{h}(x^*))$

	AG news	AG news (full)	Blog	TP-US	Yelp
victim model	79.99	94.47	97.07	85.53	95.57
All Same	80.83	94.54	96.77	86.48	95.72
Data Different (review)					
0.1x	50.90	86.57	36.83	79.95	92.39
0.5x	68.13	87.31	84.59	84.21	93.25
1x	69.94	88.63	88.16	85.15	94.06
5x	75.29	91.27	92.75	85.82	94.95
Data Different (news)					
0.1x	61.70	89.13	18.04	79.20	88.24
0.5x	70.56	89.84	32.92	84.18	89.76
1x	71.95	90.47	83.13	84.15	91.06
5x	75.82	92.26	87.64	85.46	93.13

Table 6: The accuracy of victim models and extracted models among different datasets in terms of domains and sizes.

exhibit significant degradation, when compared to the close ones. For example, sampling 0.1x-5x queries from news data present a more stable attack performance against the victim model trained with AG news than Blog.

AIA Impact Factor In Section 6, we found that there is a correlation between the success of AIA and temperature τ on the softmax layer. We conjecture that the causal factor is the sharpness of the posterior probability, *i.e.,* if the model is less confident on its most probable prediction, then AIA is more likely to be successful. This speculation is confirmed by Figure 2, where the higher posterior probability leads to a higher empirical privacy.

Figure 3 and Table 7 indicate that the attribute inference is also affected by the distribution of these attributes. Attributes with higher variances cause more information leakage or a lower empirical privacy. For example, for AG-news, entity 2-4 with higher variances result in lower empirical privacy, while entity 0-1 are more resistant to AIA. For TP-US and Blog, as age and gender exhibit similar distribution, AIA performance gap across these two attributes is less obvious, as evidenced by the last two rows in Table 7.

D ARCHITECTURE MISMATCH

In practice, the adversary may not know the victim's model architecture. A natural question is whether model extraction is still possible even when the extracted models and the victim models have different architectures. We study the influence of the architectural choice by using a different architecture, either (1) the victim is a BERT-large and the extracted is BERT-base or (2) the victim is BERT-base and the extracted is a BERT-large. According to Table 8, if both the victim and the extracted models adopt BERT-large architecture, then the vulnerability of the victim is magnified in all attacks. When there exist an architectural mismatch, the efficacy of AIA and AET can be alleviated.

(a) AG news

(b) TP-US

(c) Blog

Figure 2: The correlation between the empirical privacy of AIA and the maximum posterior probability. AG news uses news data as queries, while Blog and TP-US query the victim models with reviews data. **mean** and **median** denote the mean and median of the maximum posterior probability of the queries.

(a) AG news

(b) TP-US

(c) Blog

Figure 3: The distribution of different datasets grouped by private attributes.

AG news					
	entity 0	entity 1	entity 2	entity 3	entity 4
All Same	15.61	15.10	7.71	6.95	5.49
Data Diff. (news)	14.79	12.38	3.84	5.33	2.02

TP-US			Blog		
	gender	age		age	gender
All Same	36.40	37.12	All Same	32.18	39.02
Data Diff. (reviews)	36.44	37.40	Data Diff. (reviews)	31.20	38.01

Table 7: AIA performance on individual attributes of different datasets. All experiments are conducted with 1x queries.

Victim	Extracted	TP-US		AG news (full)	
		MEA	AIA	MEA	AET
BERT-large	BERT-large	**86.42**	**35.08**	**91.01**	**59.3**
BERT-base	BERT-large	85.89	36.89	90.68	37.2
BERT-base	BERT-base	85.15	35.97	90.47	46.2
BERT-large	BERT-base	85.36	36.65	89.88	42.7

Table 8: Attack performance on TP-US and AG news (full) with mismatched BERT architectures between the victim and the extracted model. (·, ·) refers to (victim, extracted) pretraining.