IMPROVING GENERATIVE FLOW NETWORKS WITH PATH REGULARIZATION

ABSTRACT

Generative Flow Networks (GFlowNets) are recently proposed models for learning stochastic policies that generate compositional objects by sequences of actions with the probability proportional to a given reward function. The central problem of GFlowNets is to improve their exploration and generalization. In this work, we propose a novel path regularization method based on optimal transport theory that places prior constraints on the underlying structure of the GFlowNets. The prior is designed to help the GFlowNets better discover the latent structure of the target distribution or enhance its ability to explore the environment in the context of active learning. The path regularization controls the flow in GFlowNets to generate more diverse and novel candidates via maximizing the optimal transport distances between two forward policies or to improve the generalization via minimizing the optimal transport distances. In addition, we derive an efficient implementation of the regularization by finding its closed form solutions in specific cases and a meaningful upper bound that can be used as an approximation to minimize the regularization term. We empirically demonstrate the advantage of our path regularization on a wide range of tasks, including synthetic hypergrid environment modeling, discrete probabilistic modeling, and biological sequence design.

1 INTRODUCTION

Recently proposed by (Bengio et al., 2021), Generative Flow Networks (GFlowNets) are generative models for compositional objects, which learn a stochastic policy that sequentially modifies a temporarily constructed object through a sequence of actions to make the generating likelihood proportional to a given reward function. Specifically, GFlowNets aims to solve the problem of generating a diverse set of good candidates. In biological sequence design, diversity is a key consideration because of improving the chance of discovering candidates that can satisfy many evaluation criteria later in downstream phases. Especially, in the multi-round active learning setting, where the generator was iteratively improved by receiving feedback from an oracle on their proposed candidates, the effect of diverse generation becomes apparent because more diversity means more exploration and knowledge gained. Besides, the generalization ability of GFlowNets over structured data makes them a good framework for discrete probabilistic modeling.

The central problems of GFlowNets are improving exploration and generalization. In this work, we propose to *train GFlowNets with an additional path regularization via optimal transport* (Villani, 2003)), which acts as a prior on the underlying structures of GFlowNets. The prior is designed to help the GFlowNets better discover the latent structure of the target distribution or enhance its ability to explore the environment in the context of active learning. Precisely, the path regularization via OT can help GFlowNets generate more diverse and novel candidates via maximizing OT distances between two forward policies or improving generalization via minimizing the OT distances.

For generalization: To improve GFlownets' generalization, we propose the following prior constraints: (i) Forward policies at nearby states along trajectories with high flow should be similar so they will prefer certain directions leading to high rewards. For example, in discrete image probabilistic modeling, the modes concentrate in a small region of space, so the policy must focus on some specific directions ; (ii) Trajectories related to positive objects (both have high rewards) must share their paths. As a result, the similarity of states along trajectories with high flow is higher than in other places. From a probabilistic perspective, we propose to measure the similarity of states s and s' in GFlowNets by the transition probability from s to s' ; (iii) When a GFlowNet learns something,

the flow of the GFlowNet must be sparse. Thus, our proposal priors encourage GFlowNets to refine their flow, i.e., enhance flow on high flow trajectories and vice versa.

For diversity and exploration: To encourage GFlowNets' policy to generate more diverse candidates, such as in the multi-round active learning setting, we propose to put a prior on two neighbor forward policies, such that the prior encourages the dissimilarity of the forward policies. For example, in biological sequence design, each action adds a fragment or an amino acid, and the dissimilarity prior makes the policies biased toward adding more distinct elements to a molecule, making the molecules more diverse.

Why optimal transport is a good solution? First, for the similarity prior, we need a measure of "distance" between pairs of probability distributions. The Optimal Transport (OT) theory (Villani (2003)) studies how probabilistic mass can be optimally transported from the support of one probabilistic distribution to others of another distribution given a cost function. The minimum transportation cost, called OT distance, can be used as a metric that quantifies the distance between two probability distributions. In the context of GFlowNets, we want the regularization effect on nearby states so we apply optimal transport distance for forward policies $P_F(\cdot|s)$ and $P_F(\cdot|s')$ at two neighbor states s and s'. In which, to compute the distance we solve an optimal transport problem from support points u_i (children of s) to v_j (children of s') given a cost $c(u_i, v_j)$. The cost $c(u_i, v_j)$ is a distance between u_i and v_i. Compared with KL divergence, the biggest problem of KL divergence is that it was infinite for a variety of distributions with unequal support. And in GFlowNet, the support of $P_F(\cdot|s)$ and $P_F(\cdot|s')$ are usually not equal. As a result, minimizing the optimal transport distances encourages the similarity of the forward policies making GFlowNets prefer certain directions and improving the generalization, whereas maximizing the optimal transport distances between two forward policies makes GFlowNets generate more diverse and novel candidates. Moving to the second prior, we need a loss to measure the expectation of the transition probabilities from one state to another. In terms of probabilistic interpretation, we can rewrite the OT distance as the minimum expectation of the transport cost

$$d(\alpha, \beta) = \min_{\gamma \sim \Pi(\alpha, \beta)} \mathbb{E}_{u,v \sim \gamma} c(u, v) \tag{1}$$

where $\alpha := P_F(\cdot|s)$, $\beta := P_F(\cdot|s')$ and $\Pi(\alpha, \beta)$ is the set of all joint distributions $\gamma(u, v)$ with marginals $\alpha(u), \beta(v)$. We propose to use $c(u, v) = \min_{\tau = u \to \cdots \to v} -\log(P(\tau|u))$ which can be natural interpreted as the directed distance between two states in GFlowNet. Then minimizing optimal transport distance corresponds to maximizing the transition probability from children u of s to children v of s'. Finally, the proposed cost $c(u, v)$ also links the path regularization to entropy and cross-entropy terms, which encourages sparsity of GFlowNets' flow when minimizing the optimal transport distance while encouraging exploration when maximizing the optimal transport distance.

Contributions. In this work, we develop a novel path regularization to increase the mode diversity and generalization of the generative flow network. Our contributions can be summarized as follows:

1. We propose to train GFlowNets with an additional path regularization via optimal transport, which acts as a prior on the underlying structures of GFlowNets to improve the generalization and exploration of GFlowNets.

2. We define a new directed distance between two states in GFlowNets. The distance not only is the natural choice for optimal transport distance in GFlowNet but also links the path regularization via optimal transport to entropy and cross-entropy.

3. We derive an efficient implementation of the regularization by finding its closed-form solutions in specific cases and a meaningful upper bound that can be used as an approximation when we want to minimize the regularization term.

Organization. The paper is organized as follows. In Section 2, we provide backgrounds on GFlowNets and optimal transport. In Section 3, we propose a new directed distance between two states in GFlowNets and then derive the formulation of path regularization via optimal transport. We will explain why this is the natural and optimal choice. Then we derive the upper bound and efficient implementation of the path regularization. We provide extensive experiment results of path regularization via Optimal Transport in Section 4 and conclude the paper with a few discussions in Section 5. Extra experimental and theoretical results and settings are deferred to the Appendix.

2 BACKGROUND

2.1 GFLOWNETS

Preliminaries Given a *compositional* space $\mathcal{X}$, where each object $x \in \mathcal{X}$ can be constructed by taking a sequence of discrete *actions* from the action space $\mathcal{A}$. Incrementally, the generation process modifies a temporarily constructed object, which is called a *state* $s \in \mathcal{S}$. In addition, a special action indicates that the object is completely constructed and represents a *terminal state*, such that $s = x \in \mathcal{X}$. These states and actions correspond to the vertices and edges of a directed acyclic graph $G = (\mathcal{S}, \mathcal{A})$. The construction of an object $x \in \mathcal{X}$ defines a *complete trajectory*, which is a sequence of transitions $\tau = (s_0 \to s_1 \to \ldots \to s_n = x \to s_f)$ beginning from the *initial state* s_0 and ending in the *final state* s_f. Let $\mathcal{T}$ be the set of all complete trajectories. Without loss of generality, we may assume that each terminal state $s \in \mathcal{X}$ has only one outgoing edge, which is $s \to s_f$. This can be easily achieved by augmenting every terminal state s with more outgoing edges by a new terminal state s^{T} and a stop action $s \to s^{\mathrm{T}}$.

Flows A *trajectory flow* (Bengio et al.) is a nonnegative function $F : \mathcal{T} \mapsto \mathbb{R}^+$. The flow $F(\tau)$ can be interpreted as the probability mass associated with trajectory τ. As an analogy with water flow, the flow $F(\tau)$ is the number of water particles sharing the same path τ. As a results we can define the state flow via $F(s) = \sum_{s \in \tau} F(\tau)$, and the edge flow via $F(s \to s') = \sum_{s \to s' \in \tau} F(\tau)$. We can associate a probability measure P with the trajectory flow F. In which, there are two important conditional probabilities, the forward transition probabilities (forward policy) $P_F(s'|s) := F(s \to s')/F(s)$ is related to adding an element to build the objects, and the backward transition probabilities (backward policy) $P_B(s|s') := F(s \to s')/F(s')$ is related to moving an element.

Learning GFlowNets Theoretically, Bengio et al. has shown that if the training objective such as flow-matching objective (Bengio et al., 2021) or trajectory balanced objective (Malkin et al., 2022)) is achieved on all states and possible trajectories respectively, then GFlowNets can be trained to completion, i.e., perfectly generating objects proportional to their rewards. In this paper, we use Trajectory Balance Objective because it brings more efficient credit assignment and faster convergence (Malkin et al. (2022)). We provide more background of GFLowNets in Appendix B.

2.2 OPTIMAL TRANSPORT DISTANCE

Transportation plans and joint probabilities For two discrete probability measures $\boldsymbol{\alpha}$ and $\boldsymbol{\beta}$ over some space $\mathcal{X}$, the admissible couplings set, which can be interpreted as the set of transportation plans or joint probability distributions, is defined as:

$$\Pi(\boldsymbol{\alpha}, \boldsymbol{\beta}) = \left\{ \pi \in \mathbb{R}_+^{k \times l} : \pi \mathbb{1}_l = \boldsymbol{\alpha}, \pi^\top \mathbb{1}_k = \boldsymbol{\beta} \right\}. \tag{2}$$

Optimal transportation The Kantorovich optimal transport (Peyré & Cuturi (2019)) between $\boldsymbol{\alpha}$ and $\boldsymbol{\beta}$ is defined as follows:

$$\mathrm{OT}_{\mathbf{C}}(\boldsymbol{\alpha}, \boldsymbol{\beta}) := \min_{\pi \in \Pi(\boldsymbol{\alpha}, \boldsymbol{\beta})} \langle \mathbf{C}, \pi \rangle \tag{3}$$

where $\mathbf{C}$ is the cost matrix and $\mathbf{C}_{ij}$ describes the cost of transport mass from the support i^{th} of $\boldsymbol{\alpha}$ toward the support j^{th} of $\boldsymbol{\beta}$. Whenever the matrix $\mathbf{C}$ is itself a metric matrix, the optimum of this problem, $\mathrm{OT}_{\mathbf{C}}(\boldsymbol{\alpha}, \boldsymbol{\beta})$, can be proved to be also a distance. Assuming that $k = l = d$, the worst-case complexity of computing that optimum with any of the algorithms known so far scales in $O(d^3 \log d)$ and turns out to be super-cubic in practice (Pele & Werman (2009), §2.1).

3 PATH REGULARIZATION VIA OPTIMAL TRANSPORT

3.1 OPTIMAL TRANSPORT FORMULATION OF THE PATH REGULARIZATION

Turn transition probability into directed distance We define a new directed distance between two states in GFlowNets, which is used as transport cost to compute OT distance.

Definition 3.1 (Directed Distance in GFlowNets) *Let $\tau = s \to \ldots \to s'$ be the transition from state s to state s' either via backward or forward policy. The length of τ and the Directed Distance from s to s' are defined as follows:*

$$Len(\tau) := -\log(P(\tau \mid s)) \tag{4}$$

$$d(s, s') := \min_{\tau = (s \to \ldots \to s')} -\log(P(\tau \mid s)) \tag{5}$$

Where $d(s, s') = 0$ when $s \equiv s'$. Intuitively, $d(s, s')$ is the length of the shortage path from s to s'.

The proposed Directed Distance is the natural choice for distance in GFlowNets. Firstly, let consider two states s and s'. They can be seen as the equivalent of one another, and have zero distance, if $P(s'|s)$, the probability of transitioning from state s to state s', is equal to 1. In contrast, if the transition probability is equal to 0, we cannot reach s' from s by following GFlowNets policy, then the distance must be infinite. Beside, it is obvious that $-\log(1) = 0$ and $-\log(0) = \infty$. Another reason is that distances are additive, whereas probabilities are multiplicative. As a result, if we want the probability of a trajectory to be naturally related to its length, the transition probabilities between states should be changed to their distance by a "negative" logarithmic scale.

Why do we use the proposed directed distance as transport cost to compute OT distance? There are several reasons for using the directed distance as transport cost to compute OT distance. First, as discussed above, it is the natural choice to turn a transition probability into a distance. Second, with the transport cost as the directed distance, the OT distance can be decomposed into cross-entropy, entropy, and other negative terms. This gives us an upper bound for optimal transport distance and imposes sparsity prior for GFlowNets' structures when minimizing the OT distance or exploration when maximizing the OT distance. Besides, the choosing of cost function makes minimizing optimal transport distance correspond to maximizing the transition probability between children of neighbor states. Using the directed distance as transport cost allows us to derive closed-form solutions for optimal transport distance under some conditions. In contrast, if we use optimal transport distance with another transport cost, such as the shortage path in the graph, we only archive the first prior.

Optimal transport formulation of the path regularization Once we have defined the directed distance between two states in GFlowNets, we can define the optimal transport distance between two forward policies of neighbor states. Consider two neighbor states $s < s'$ in trajectory τ. The forward policy $P_F(\cdot|s)$ is a discrete probability measure supported by $\text{Child}(s) = \{u_1, ..., u_m\}$ and $P_F(\cdot|s')$ is a discrete probability measure supported by $\text{Child}(s') = \{v_1, ..., v_m\}$.

The optimal transport (OT) distance between $P_F(\cdot|s)$ and $P_F(\cdot|s')$ can be define as:

$$\text{OT}_{\mathbf{C}}\left(P_F(\cdot|s), P_F(\cdot|s')\right) := \min_{\pi \in \prod(P_F(\cdot|s), P_F(\cdot|s'))} \langle \mathbf{C}, \pi \rangle \tag{6}$$

where the admissible couplings set is defined as:

$$\Pi(P_F(\cdot|s), P_F(\cdot|s')) := \left\{\pi \in \mathbb{R}_+^{k \times l} : \pi \mathbb{1}_l = P_F(\cdot|s), \pi^\top \mathbb{1}_k = P_F(\cdot|s')\right\} \tag{7}$$

and $\mathbf{C}$ is a cost matrix whose each entry is the length of a shortage path from u_i to v_j

$$\mathbf{C}_{ij} = c(u_i, v_j) := d(u_i, v_j) = \min_{\tau=(u_i \to ... \to v_j)} -\log(P(\tau \mid u_i)). \tag{8}$$

Because we cannot access the full graph during training progress so the shortage path from u_i to v_i can only be constructed from the sub-graph containing s_t, s_{t+1}, their children states, and the edges that connecting them. Rather than going directly from u_i to v_j if this edge exists, we can always move from u_i to v_j along a back-and-forth trajectory, i.e., $u_i \to s \to s' \to v_j$, with the probability $P_B(s|u_i)P_F(s'|s)P_F(v_j|s')$. Because transport cost from u_i to v_i is the length of the shortage path from u_i to v_i, it is reasonable to have a minimum operator in the following formulation:

$$\mathbf{C}_{ij} = \begin{cases} 0, & \text{if} \quad u_i \equiv v_j \\ \min\left(-\log(P_B(s \mid u_i)P_F(s' \mid s)P_F(v_j \mid s')), -\log(P(v_j \mid u_i))\right), & \text{else if} \quad u_i \to v_j \in \mathcal{A} \\ -\log(P_B(s \mid u_i)P_F(s' \mid s)P_F(v_j \mid s')), & \text{otherwise.} \end{cases} \tag{9}$$

Definition 3.2 (Optimal Transport Formulation of the Path Regularization) *For any complete trajectory $\tau = (s_0 \to s_1 \to ... \to s_n)$, we define the path regularization via optimal transport as follows:*

$$\mathcal{L}_{OT}(\tau) := \sum_{t=0}^{n-1} OT_{\mathbf{C}_{t;\theta}}\left(P_F(\cdot|s_t; \theta), P_F(\cdot|s_{t+1}; \theta)\right) \tag{10}$$

where $\mathbf{C}_{t;\theta}$ is the directed distance in GFlowNets (see Definition 3.1), with the formulation in Eqn. 9.

If $\overline{\pi}_\theta$ is a training policy – usually that given by $P_F(\cdot|\cdot; \theta)$ or a tempered version of it – then the trajectory loss is updated along trajectories sampled from $\overline{\pi}_\theta$, i.e., with stochastic gradient:

$$\mathbb{E}_{\tau \sim \overline{\pi}_\theta} \nabla_\theta(\mathcal{L}_{\text{TB}}(\tau) + \lambda \mathcal{L}_{\text{OT}}(\tau)). \tag{11}$$

Figure 1: Optimal transport distance between $P_F(\cdot|s)$ and $P_F(\cdot|s')$. The forward policy $P_F(\cdot|s)$ is a discrete probability measure supported by $\text{Child}(s) = \{u_1, u_2 := s', u_3\}$. Similarly, $P_F(\cdot|s')$ is supported by $\text{Child}(s') = \{v_1 \equiv u_1, v_2, v_3\}$. The cost matrix is a 3×3 matrix. For example, $c_{11} = d(u_1, v_1) = 0$ (because $u_1 \equiv v_1$). There are many possible paths to move from u_3 to v_3. First, going directly from u_3 to v_3 with a distance is equal to $\text{len}(u_3 \rightarrow v_3) = -\log(P_F(v_3|u_3))$. Second, we can move from u_3 to v_3 along a back-and-forth trajectory, i.e., $u_3 \rightarrow s \rightarrow s' \rightarrow v_3$, with a distance $-\log(P_B(s|u_3)) - \log(P_F(s'|s)P_F) - \log(P(v_3|s'))$. Because transport cost from u_3 to v_3 is the length of the shortage path from u_3 to v_3, $c_{33} = d(u_3, v_3) = \min(-\log(P_B(s|u_3)P_F(s'|s)P_F(v_3|s')), -\log(P_F(v_3|u_3)))$.

The effects of minimizing the path regularization: Remind that the optimal transport (OT) distance between $P_F(\cdot|s)$ and $P_F(\cdot|s')$ is defined as follows:

$$\text{OT}_{\mathbf{C}}\left(P_F(\cdot|s), P_F(\cdot|s')\right) := \min_{\pi \in \prod(P_F(\cdot|s), P_F(\cdot|s'))} \langle \mathbf{C}, \pi \rangle. \tag{12}$$

Minimizing $\text{OT}_{\mathbf{C}}\left(P_F(\cdot|s), P_F(\cdot|s')\right)$ makes $P_F(v|s')$ closed to $P_F(u|s)$, where $c(u, v)$ small. This is because all probability mass form u can be transferred to v with a smaller cost than to other places, so the total transport cost reduces. Also, $P_F(v|s')$ and $P_F(u|s)$ will be increased, where $c(u, v)$ small. This induces the similarity of the forward policies and makes the flow focus on specific directions. It should be noticed that the matrix cost $\mathbf{C}$ is not a constant but depends on the forward policies. Therefore, minimizing the optimal transport distance affects not only the forward policies but also the cost. However, the effect on the forward policies is also consistent with the effects on the cost. As in E.q 20 of theorem 3.2 increasing $P_F(u|s)$ leads to increase $P_B^*(u|s)$. Besides, $-\log(P_B(s|u)P_F(s'|s)P_F(v|s'))$ is an upper bound of $c(u, v)$, so increasing $P_F(u|s)$ and $P_F(v|s')$ also make $c(u, v)$ smaller. We have $\mathbf{C} \geq 0$ so $\text{OT}_{\mathbf{C}}\left(P_F(\cdot|s), P_F(\cdot|s')\right) \geq 0$. Also, the optimal transport distance is equal to zero when all probability mass $P_F(v|s') = P_F(u|s)$ concentrate on u, v where $c(u, v) = 0$. For examples, $P_F(s_t|s_{t-1}) = 1$ and $P_F(s_{t+1}|s_t) = 1$ is a special case. When GFlowNets visit a high reward object, the prior by designed helps GFlowNets quickly adapt their flow to this high reward terminal state. More discussion about entropy and cross-entropy is in Theorem 3.1.

The effects of maximizing the path regularization: In contrast to minimizing the optimal transport distance, maximizing makes the forward policies different, so more diverse actions are chosen, leading to more diverse and novel candidates. As in the theorem 3.1, the upper-bound of the optimal transport distance is the entropy of forward policy $\mathbf{H}(P_F(\cdot|s))$ and the entropy of the path $\mathbf{H}(P(\tau))$. Thus, maximizing the OT distance means maximizing the upper bound, which increases the entropy. This means more diversity and exploration. Remind that in terms of probabilistic interpretation, we can rewrite the OT distance as the minimum expectation of the transport cost

$$\min_{\gamma \sim \Pi(\alpha, \beta)} \mathbb{E}_{u, v \sim \gamma} c(u, v). \tag{13}$$

Thus, maximizing the OT distance means maximizing the cost $c(u, v)$. Because $c(u, v)$ is an inverse function of transition probability from u to v, maximizing the OT distance means minimizing $P(u \rightarrow v)$. As a result, the flow was distributed to more states, so more diverse action was chosen.

3.2 Upper Bound and Efficient Implementation of the Path Regularization

The cost of computing optimal transport distance $\text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right)$ scales at least in $\mathcal{O}(d^3 log(d))$, where d is the number of support points. By using the Sinkhorn algorithm (Cuturi, 2013), which solves optimal transport with entropic regularization, we can reduce computing costs to $\mathcal{O}(d^2)$ (Altschuler et al., 2017; Lin et al., 2019; 2022). However, the implementation of the path regularization requires the computation of the optimal transport distances for all edges in the trajectory τ. This is a significant burden on computing resources and capacity. To overcome this problem, in Theorem 3.1 we propose an upper bound of optimal transport distance $\text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right)$. The upper bound not only provides an efficient implementation but also can explain the behaviors of the path regularization. This is because the optimal transport distance can be decomposed into cross-entropy, entropy, and other negative terms. These negative terms are the total cost of an optimal transport problem with a negative sparse cost matrix, which can be solved completely in the hypergrid environment and EB-GFN experiments or other GflowNet settings under certain conditions (Section 3.3).

Definition 3.3 (Pseudo backward policy) *Let s be a state on trajectory τ, which has its children set: $Child(s) = \{u_1, ..., u_k\}$, then the "pseudo backward policy" at state s is defined as:*

$$P_B^*(\cdot|s)) = (P_B^*(u_1|s), \ldots, P_B^*(u_k|s)) \tag{14}$$

where we have

$$P_B^*(u_i|s) = P_B(s|u_i) \quad \forall 1 \le i \le k. \tag{15}$$

Theorem 3.1 (Upper bound of optimal transport distance) *For any trajectory $\tau = (s_0 \to s_1 \to \ldots \to s_n)$. The path regularization via optimal transport can be upper-bound by:*

$$\mathcal{L}_{OT}(\tau) \le \mathcal{L}_{UB}(\tau), \tag{16}$$

where:

$$\mathcal{L}_{UB}(\tau) := \sum_{t=0}^{n-1} \left[\mathbf{H}(P_F(\cdot|s_t), P_B^*(\cdot|s_t)) - \log(P_F(s_{t+1}|s_t)) + \mathbf{H}(P_F(\cdot|s_{t+1})) \right]. \tag{17}$$

The proof of Theorem 3.1 is in Appendix D.1. The cross-entropy and entropy terms in the upper-bound $\mathcal{L}_{UB}(\tau)$ encourage the sparsity of GFlowNets' flow. When we minimizes the upper-bound $\mathcal{L}_{UB}(\tau)$, the cross-entropy terms $\mathbf{H}(P_F(.|s_t), P_B^*(.|s_t))$ try to match the Forward policy and the Pseudo backward policy at s_t. For example, consider a children state u of s_t, if $P_F(u|s_t)$ is high, then $P_B(s_t|u)$ is also high. As a result, increasing $P_B(s_t|u)$ makes other flows leading to u pruned. While the meanings of cross-entropy and entropy terms are clear, we now would like to explain the meaning of regularization terms $-\log(P_F(s_{t+1}|s_t))$. Direct calculations indicate that:

$$\sum_{t=0}^{n-1} -\log(P_F(s_{t+1}|s_t)) = -\log\left(\prod_{t=0}^{n-1} P_F(s_{t+1}|s_t)\right) = -\log(P(\tau)), \tag{18}$$

$$\mathbb{E}_{\tau \sim \pi_\theta}(-\log(P(\tau))) = \mathbf{H}(P(\tau)). \tag{19}$$

By taking this approach, the upper-bound not only regularizes the policies via $\mathbf{H}(P_F(\cdot|s_{t+1}))$ but also more importantly the path via $\mathbf{H}(P(\tau))$. Besides, we can think $-\log(P(\tau)) = -\log(P(\tau|s_0).P(s_0)) = -\log(P(\tau|s_0))$ as the length of τ. Thus the effect of minimizing path regularization also is biasing to shorter paths in terms of the direct distance and equivalently to small numbers of paths with high flows.

3.3 CLOSED FORM FORMULATION FOR THE PATH REGULARIZATION

In the case of the hypergrid environment (Bengio et al. (2021)) and EB-GFN experiments (Zhang et al. (2022)), Protein and DNA design or other GflowNet settings with certain conditions, theorem 3.2 allows us to compute optimal transport loss from a closed form formulation rather than using the Sinkhorn Algorithm. The closed form formulation was derived by taking advantage of the following observations. For the first observation, any two neighbor states $s < s'$ do not have the same child state. The reason is that there is not exist an action a_k such that a_k can decompose into others actions, i.e, $a_k = a_i + a_j$. For the second observation, there is an action a^* moving from a child $u \ne s'$ of s to a child v of s', if and only if these children are achieved by taking the same action both at s and s'. Moreover, a^* is the action moving from s to s'. Without loss of generality, we can denote a_i as an action so that the state-action pair (s, a_i) leads to u_i and (s', a_i) leads to v_i. Let denote A_s^* as the set of valid non-terminal actions at state s. If the state-action pair (s, a) leads to s', and the state-action pair (s', a') leads to s", Let denote $s' = s + a$ and $s" = s + a + a'$. Moreover, if exist an action a^* so that $s" = s + a^*$ then we denote $a^* = a + a'$.

Theorem 3.2 (Closed form solution for optimal transport distance) *For any non-terminal neighbor states $s < s'$, let denote a_i as an action so that the state-action pair (s, a_i) leads to u_i and (s', a_i) leads to v_i, where $u_i \in Child(s)$ and $v_i \in Child(s')$. Let A_s^* as the set of non-terminal valid actions at state s. Let a_s^* is the action moving from s to s'. If $a_i \ne a_k + a_h \quad \forall a_i, a_k, a_h \in \mathcal{A}$ and $a_i + a_h = a_m + a_n, a_i \ne a_m \iff a_i = a_n, a_h = a_m, a_i \ne a_m$ then:*

$$OT(P_F(\cdot|s), P_F(\cdot|s')) = \mathbf{H}(P_F(\cdot|s), P_B^*(\cdot|s)) - \log(P_F(s'|s)) + \mathbf{H}(P_F(\cdot|s'))$$
$$+ P_F(s'|s).(\log(P_B(s'|s)) + \log(P_F(s'|s)))$$
$$+ \sum_{i \in A_s^* \bigcap A_{s'}^*} \min(P_F(u_i|s), P_F(v_i|s'))c_i', \tag{20}$$
$$u_i \ne s' \implies u_i + a_s^* = v_i. \tag{21}$$

where we define

$$c_i' = \begin{cases} \min(0, \log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_i|s')) - \log(P_F(v_i|u_i))), & \text{if } u_i \neq s' \\ 0, & \text{if } u_i = s' \end{cases}$$

(22)

The proof of Theorem 3.2 and the closed form solution for optimal transport distance at terminal state are in Appendix D.2. These close forms of the optimal transport distance will be used in our experiments in Section 4 (see Appendix D.2 for the reasons why we can apply the Theorem).

4 EXPERIMENTAL RESULTS

In this section, we numerically justify the advantage of OT regularization over the baseline GFlowNet model only trained with trajectory balance loss on a wide range of tasks: hypergrid environment, discrete probabilistic modeling, and biological sequence design tasks. We aim to show that: (i) Minimizing the path regularization via OT improves the GFlowNets' generalization, and the upper bound can be used as an efficient approximation when we want to minimize the regularization term (hyper-grid environment, discrete probabilistic modeling); while (ii) Maximizing path regularization via OT enhances the exploration ability of GFlowNets (biological sequence tasks).

4.1 HYPER-GRID ENVIRONMENT

Task We follow the framework of Malkin et al. (2022) with slight changes to study a hyper-grid environment, which evaluates the generalization ability of the GFlowNet to guess and sample unvisited modes of the interested distribution. Consider a D-dimensional hyper-grid environment with length of each side is H, where each cell represents non-terminal state of the given DAG: $s = (s_1, \ldots, s_D)$ where $s_d \in \{0, 1, \ldots, H-1\}$ for $d \in \{1, \ldots, D\}$. The source state is $(0, 0, ..., 0)$. For any non-terminal state, the available actions are operations of increasing coordinate i by 1 that still satisfies $s_i \leq H-1$ and a terminating action that moves to a corresponding terminal state s^T, which has its reward:

$$R\left(s^\top\right) = R_0 + 0.5 \prod_{d=1}^{D} \mathbb{I}\left[|s_d/(H-1) - 0.5| \in (0.25, 0.5]\right] + 2 \prod_{d=1}^{D} \mathbb{I}\left[|s_d/(H-1) - 0.5| \in (0.3, 0.4)\right]$$

(23)

where R_0 is the constant that controls the discovery challenge and $\mathbb{I}$ is the indicator function. This reward function indicates that only considerable rewards exist at the environment's corners, and there are correct 2^D modes. The experiment is conducted for two hyper-grid environments with the number of dimensions 4 and 7 (a higher number of dimensions means more challenging). We consider the same side length $H = 8$ and $R_0 = 10^{-3}$ for both environments. To evaluate the performance on this task, we use KL divergence and the number of modes found during training as the main evaluation metrics. More details about architectures, hyper-parameters, and evaluation criteria are provided in Appendix E.1.

Results We plot the mean results over 10 runs for each configuration in Fig. 2. Although recovering full modes and achieving the same stable minimum of KL divergence, the GFlowNet model trained by minimizing the path regularization via OT discovers modes faster than the baseline, which indicates its focus on finding directions leading to states with high rewards during the training progress rather than spend time exploring the environment. This also helps the model better discover the latent structures of the interested distribution and achieve some level of low KL error faster. We can also see that the upper bound is an efficient approximation in terms of complexity when using a positive regularization coefficient, whose performance is even better.

4.2 BIOLOGICAL SEQUENCE DESIGN

Task We follow the framework of Jain et al. (2022) to simulate the process of designing biological sequences, such as anti-microbial peptides (AMP), DNA and protein sequences (TF Bind 8, GFP). The experiments are conducted in the multi-round active learning setting, with the goal of generating a diverse set of useful candidates after evaluation rounds. We report the performance score, diversity score, and novelty score of the TopK scoring candidates to evaluate the performance of each method. More details about task description, datasets, hyper-parameters, and evaluation criteria are provided in Appendix E.2.

AMP The results for AMP design task is shown in Table 1. We see that the GFlowNet-AL model trained by maximizing the regularization via OT performs better than other baselines in terms of diversity and novelty. In addition, the TopK performance of the GFLowNet-AL baseline also increases

Figure 2: Results on the $4 - D$ (upper) and $7 - D$ (lower) hyper-grid environment. Left: Number of modes found during training. Right: KL divergence between the true and empirical distribution.

	Performance	Diversity	Novelty
DynaPPO	$\mathbf{0.938 \pm 0.009}$	12.12 ± 1.71	9.31 ± 0.69
COMs	0.761 ± 0.009	19.38 ± 0.14	26.47 ± 1.30
GFlowNet-AL (paper)	0.932 ± 0.002	22.34 ± 1.24	28.44 ± 1.32
GFlowNet-AL	0.874 ± 0.022	$\mathbf{31.98 \pm 2.27}$	23.91 ± 1.87
GFlowNet+Min OT-AL	0.847 ± 0.033	20.32 ± 7.38	23.63 ± 1.66
GFlowNet+UB OT-AL	0.828 ± 0.022	29.89 ± 2.80	24.16 ± 1.75
GFlowNet+Max OT-AL	0.917 ± 0.003	31.56 ± 2.43	$\mathbf{28.86 \pm 0.96}$

Table 1: Results on the AMP task with $K = 100$.

from 0.874 to 0.917 when we maximize the OT regularization and is only lower than the reported performance of DynaPPO. However, DynaPPO has a much lower diversity and novelty score, which implies that it mostly generates similar candidates from the training dataset.

TF Bind 8 An interesting observation here is that initial dataset $\mathcal{D}_0$ contains only half of all possible DNA sequences of length 8 having lower scores. Specifically, low-quality data is very common in practice, and in this task, it poses a big challenge for all the methods to have good results. From Table 2, we can see that MINs have the highest diversity compared to the other methods. However, this method has a much lower TopK performance and novelty score, which indicates its generated samples are very similar to the low-quality training dataset. Moreover, although having slightly lower diversity, the GFlowNet-AL model trained by maximizing the path regularization via OT performs better than the others when looking at all metrics - it outperforms other baselines in terms of performance and novelty score.

	Performance	Diversity	Novelty
DynaPPO	0.58 ± 0.02	5.18 ± 0.04	0.83 ± 0.03
COMs	0.74 ± 0.04	4.36 ± 0.24	1.16 ± 0.11
BO-qEI	0.44 ± 0.05	4.78 ± 0.17	0.62 ± 0.23
CbAS	0.45 ± 0.14	5.35 ± 0.16	0.46 ± 0.04
MINs	0.40 ± 0.14	$\mathbf{5.57 \pm 0.15}$	0.36 ± 0.00
CMA-ES	0.47 ± 0.12	4.89 ± 0.01	0.64 ± 0.21
AmortizedBO	0.62 ± 0.01	4.97 ± 0.06	1.00 ± 0.57
GFlowNet-AL (paper)	0.84 ± 0.05	4.53 ± 0.46	2.12 ± 0.04
GFlowNet-AL	0.83 ± 0.01	4.66 ± 0.08	1.14 ± 0.03
GFlowNet+Min OT-AL	0.82 ± 0.01	4.72 ± 0.10	1.13 ± 0.04
GFlowNet+UB OT-AL	0.83 ± 0.01	4.68 ± 0.10	1.14 ± 0.05
GFlowNet+Max OT-AL	$\mathbf{0.85 \pm 0.02}$	4.52 ± 0.18	$\mathbf{1.21 \pm 0.10}$

Table 2: Results on the TF Bind 8 task with $K = 128$.

GFP Lastly, the results for the GFP task are shown in Table 3, where the objective is to find protein sequences having high fluorescence. We observe that the GFlowNet-AL model trained by maximizing OT regularization generates more diverse and novel candidates than other methods. In addition, its performance score is only lower than the best one achieved by COMs and higher than

the GFlowNet-AL baseline. However, when looking at all metrics, the GFlowNet-AL model trained by maximizing the path regularization via OT still outperforms all other baselines.

	Performance	Diversity	Novelty
DynaPPO	0.794 ± 0.002	206.19 ± 0.19	203.20 ± 0.47
COMs	$\mathbf{0.831 \pm 0.003}$	204.14 ± 0.14	201.64 ± 0.42
BO-qEI	0.045 ± 0.003	139.89 ± 0.18	203.60 ± 0.06
CbAS	0.817 ± 0.012	5.42 ± 0.18	1.81 ± 0.16
MINs	0.761 ± 0.007	5.39 ± 0.00	2.42 ± 0.00
CMA-ES	0.063 ± 0.003	201.43 ± 0.12	203.82 ± 0.09
AmortizedBO	0.051 ± 0.001	205.32 ± 0.12	202.34 ± 0.25
GFlowNet-AL (paper)	0.853 ± 0.004	211.51 ± 0.73	210.56 ± 0.82
GFlowNet-AL	0.82318 ± 0.00005	218.54 ± 7.88	222.05 ± 5.49
GFlowNet+Min OT-AL	0.82311 ± 0.00009	182.03 ± 0.25	220.56 ± 2.02
GFlowNet+UB OT-AL	0.82316 ± 0.00009	221.64 ± 0.11	218.02 ± 0.79
GFlowNet+Max OT-AL	0.82326 ± 0.00009	$\mathbf{225.00 \pm 3.76}$	$\mathbf{242.11 \pm 1.44}$

Table 3: Results on the GFP task with $K = 128$.

4.3 SYNTHETIC DISCRETE PROBABILISTIC MODELING TASKS

Task We follow the framework of Zhang et al. (2022), Energy-based Generative Flow Networks (EB-GFN), to model seven different distributions over 32-dimensional binary data that are discretizations of continuous distributions over the plane. The state space $\mathcal{S}$ of the GFlowNet consists of vectors of length $D = 32$ with with entries in $\{0; 1; \oslash\}$. The source state is $s_0 = (\oslash, \oslash, ..., \oslash)$. For any non-terminal state, the available actions are turning a void entry $\oslash$ to 0 or 1. After D actions, we reach the terminal states having all entries in $\{0; 1\}$. The main evaluation metrics are NLL score and MMD score. The detailed settings about architectures, hyper-parameters, and evaluation criteria are provided in Appendix E.3.

Results The results for synthetic discrete probabilistic modeling tasks (Synthetic EB-GFN) are shown in Table 4. Training GFlowNets with either minimizing the path regularization via OT (Min OT) or via the Upper-bound (UB OT) gains the better NLL and MMD scores than the baseline. We also observe that the performance of training EB-GFN with Min OT and UB OT are quite similar.

Metrix	Method	2spirals	8gaussians	circles	moons	pinwheel	swissroll	checkerboard
NLL ↓	PCD	20.094	19.991	20.565	19.763	19.593	20.172	21.214
	ALOE	20.295	20.350	20.565	19.287	19.821	20.160	54.653
	ALOE +	**20.062**	19.984	20.570	19.743	19.576	20.170	21.142
	EB-GFN (paper)	20.050	19.982	20.546	19.732	19.554	20.146	20.696
	EB-GFN	20.0679	19.9862	**20.5598**	19.7324	19.5735	20.1599	20.6839
	EB-GFN + Min OT	20.0640	19.9855	**20.5598**	19.7308	**19.5699**	20.1595	**20.6831**
	EB-GFN + UB OT	20.0651	**19.9854**	20.5600	**19.7305**	19.5707	20.1596	20.6836
MMD ↓	PCD	2.160	0.954	0.188	0.962	0.505	1.382	2.831
	ALOE	21.926	107.320	0.497	26.894	39.091	0.471	61.562
	ALOE +	**0.149**	0.078	0.636	0.516	1.746	0.718	12.138
	EB-GFN (paper)	0.583	0.531	0.305	0.121	0.492	0.274	1.206
	EB-GFN	0.3012	0.0408	-0.1724	-0.1744	0.2056	0.1555	-0.0986
	EB-GFN + Min OT	0.1816	0.0343	$\mathbf{-0.2775}$	$\mathbf{-0.1966}$	**0.1220**	0.1334	$\mathbf{-0.1071}$
	EB-GFN + UB OT	0.2902	**0.0102**	0.2819	-0.1253	0.1561	**0.0257**	-0.0923

Table 4: Results on the Synthetic EB-GFN tasks. We display the negative log-likelihood (NLL) and MMD (in units of 1×10^{-4}). Note that ALOE+ uses a thirty times larger parametrization than ALOE and EB-GFN.

5 CONCLUDING REMARKS

In this paper, we propose to train GFlowNets with an additional path regularization via Optimal Transport that places prior constraints on the underlying structure of the GFlowNets. We have empirically shown that minimizing the path regularization via OT improves the GFlowNet's generalization while maximizing path regularization via OT enhances the exploration ability of GFlowNets. In addition, we derive an efficient implementation of the regularization by finding its closed form solutions in specific cases and a meaningful upper bound that can be used as an approximation when we want to minimize the regularization term. A limitation of the current method is computing the optimal transport distances for all couples of nearest neighbor states. Our proposed Dropout OT (see in Appendix C) might be a solution. In future works, we aim to develop a more efficient path regularization for high dimensional discrete data or propose a new cost function to compute the optimal transport distances.

REFERENCES

Jason Altschuler, Jonathan Niles-Weed, and Philippe Rigollet. Near-linear time approximation algorithms for optimal transport via Sinkhorn iteration. In *Advances in Neural Information Processing Systems*, pp. 1964–1974, 2017.

Christof Angermueller, David Dohan, David Belanger, Ramya Deshpande, Kevin Murphy, and Lucy J. Colwell. Model-based reinforcement learning for biological sequence design. In *ICLR*, 2020.

Michal Arbel, Liang Zhou, and Arthur Gretton. Generalized energy based models. *arXiv: Machine Learning*, 2021.

Luis A. Barrera, Anastasia Vedenko, Jesse V. Kurland, Julia M. Rogers, Stephen S. Gisselbrecht, Elizabeth J. Rossin, Jaie Woodard, Luca Mariani, Kian Hong Kock, Sachi Inukai, Trevor Siggers, Leila Shokri, Raluca Gordân, Nidhi Sahni, Chris Cotsapas, Tong Hao, Song Yi, Manolis Kellis, Mark J. Daly, Marc Vidal, David E. Hill, and Martha L. Bulyk. Survey of variation in human transcription factors reveals prevalent dna binding changes. *Science*, 351(6280):1450–1454, 2016. doi: 10.1126/science.aad2257. URL https://www.science.org/doi/abs/10.1126/science.aad2257.

David Belanger, Suhani Vora, Zelda E. Mariet, Ramya Deshpande, David Dohan, Christof Angermueller, Kevin Murphy, Olivier Chapelle, and Lucy J. Colwell. Biological sequence design using batched bayesian optimization. 2019.

Emmanuel Bengio, Moksh Jain, Maksym Korablyov, Doina Precup, and Yoshua Bengio. Flow network based generative models for non-iterative diverse candidate generation. *CoRR*, abs/2106.04399, 2021. URL https://arxiv.org/abs/2106.04399.

Yoshua Bengio, Tristan Deleu, Edward J. Hu, Salem Lahlou, Mo Tiwari, and Emmanuel Bengio. Gflownet foundations. URL https://arxiv.org/abs/2111.09266.

Nicolas Bonneel, Michiel van de Panne, Sylvain Paris, and Wolfgang Heidrich. Displacement interpolation using lagrangian mass transport. 2011.

Charlotte Bunne, David Alvarez-Melis, Andreas Krause, and Stefanie Jegelka. Learning generative models across incomparable spaces. In *ICML*, 2019.

Nicolas Courty, Rémi Flamary, and Devis Tuia. Domain adaptation with regularized optimal transport. In *ECML/PKDD*, 2014.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transportation distances. *arXiv: Machine Learning*, 2013.

Bo Dai, Z. Liu, Hanjun Dai, Niao He, Arthur Gretton, Le Song, and Dale Schuurmans. Exponential family estimation via adversarial dynamics embedding. In *NeurIPS*, 2019.

Hanjun Dai, Rishabh Singh, Bo Dai, Charles Sutton, and Dale Schuurmans. Learning discrete energy-based models via auxiliary-variable local exploration. *ArXiv*, 2020.

Tristan Deleu, Ant'onio G'ois, Chris C. Emezue, Mansi Rankawat, Simon Lacoste-Julien, Stefan Bauer, and Yoshua Bengio. Bayesian structure learning with generative flow networks. *ArXiv*, abs/2202.13903, 2022.

Yilun Du, Shuang Li, Joshua B. Tenenbaum, and Igor Mordatch. Improved contrastive divergence training of energy based models. In *ICML*, 2021.

Aude Genevay, Gabriel Peyré, and Marco Cuturi. Learning generative models with sinkhorn divergences. In *AISTATS*, 2018.

Will Grathwohl, Kevin Swersky, Milad Hashemi, David Kristjanson Duvenaud, and Chris J. Maddison. Oops i took a gradient: Scalable sampling for discrete distributions. *ArXiv*, abs/2102.04509, 2021.

Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *Journal of Machine Learning Research*, 13(25):723–773, 2012. URL http://jmlr.org/papers/v13/gretton12a.html.

Nikolaus Hansen. The cma evolution strategy: A comparing review. In *Towards a New Evolutionary Computation*, 2006.

Geoffrey E. Hinton. Training products of experts by minimizing contrastive divergence. *Neural Computation*, 14:1771–1800, 2002.

Geoffrey E. Hinton, Simon Osindero, and Yee Whye Teh. A fast learning algorithm for deep belief nets. *Neural Computation*, 18:1527–1554, 2006.

Nhat Ho, XuanLong Nguyen, Mikhail Yurochkin, Hung Hai Bui, Viet Huynh, and Dinh Phung. Multilevel clustering via Wasserstein means. In *International Conference on Machine Learning*, pp. 1501–1509, 2017.

Moksh Jain, Emmanuel Bengio, Alex García, Jarrid Rector-Brooks, Bonaventure F. P. Dossou, Chanakya Ajit Ekbote, Jie Fu, Tianyu Zhang, Micheal Kilgour, Dinghuai Zhang, Lena Simine, Payel Das, and Yoshua Bengio. Biological sequence design with gflownets. In *ICML*, 2022.

Tianyi Lin, Nhat Ho, and Michael Jordan. On efficient optimal transport: An analysis of greedy and accelerated mirror descent algorithms. In *International Conference on Machine Learning*, pp. 3982–3991, 2019.

Tianyi Lin, Nhat Ho, and Michael I. Jordan. On the efficiency of entropic regularized algorithms for optimal transport. *Journal of Machine Learning Research*, 2022.

Nikolay Malkin, Moksh Jain, Emmanuel Bengio, Chen Sun, and Yoshua Bengio. Trajectory balance: Improved credit assignment in gflownets. *ArXiv*, abs/2201.13259, 2022.

Frederic P. Miller, Agnes F. Vandome, and John McBrewster. *Levenshtein Distance: Information Theory, Computer Science, String (Computer Science), String Metric, Damerau?Levenshtein Distance, Spell Checker, Hamming Distance*. Alpha Press, 2009. ISBN 6130216904.

T. Nguyen, Q.-H. Pham, T. Le, T. Pham, N. Ho, and B.-S. Hua. Point-set distances for learning representations of 3D point clouds. In *ICCV*, 2021.

Ofir Pele and Michael Werman. Fast and robust earth mover's distances. *2009 IEEE 12th International Conference on Computer Vision*, pp. 460–467, 2009.

Gabriel Peyré and Marco Cuturi. Computational optimal transport. *Found. Trends Mach. Learn.*, 11:355–607, 2019.

Malak Pirtskhalava, Anthony A. Amstrong, Maia Grigolava, Mindia Chubinidze, Evgenia Alimbarashvili, Boris Vishnepolsky, Andrei E. Gabrielian, Alex Rosenthal, Darrell E. Hurt, and Michael Tartakovsky. DBAASP v3: database of antimicrobial/cytotoxic activity and structure of peptides as a resource for development of new therapeutics. *Nucleic Acids Res.*, 49(Database-Issue):D288–D297, 2021. doi: 10.1093/nar/gkaa991. URL https://doi.org/10.1093/nar/gkaa991.

Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Xi Chen, John F. Canny, P. Abbeel, and Yun S. Song. Evaluating protein transfer learning with tape. *bioRxiv*, 2019.

Ruslan Salakhutdinov and Geoffrey E. Hinton. Deep boltzmann machines. In *AISTATS*, 2009.

Karen S. Sarkisyan, Dmitry Bolotin, Margarita V. Meer, Dinara R. Usmanova, Alexander S. Mishin, George V. Sharonov, Dmitry N. Ivankov, Nina G. Bozhanova, Mikhail S. Baranov, Onuralp Soylemez, Natalya S. Bogatyreva, Peter K. Vlasov, Evgeny S. Egorov, Maria D. Logacheva, Alexey S. Kondrashov, Dmitry M. Chudakov, Ekaterina V. Putintseva, Ilgar Z. Mamedov, Dan S. Tawfik, Konstantin A. Lukyanov, and Fyodor A. Kondrashov. Local fitness landscape of the green fluorescent protein. *Nature*, 533:397 – 401, 2016.

Sam Sinai, Richard Wang, Alexander Whatley, Stewart Slocum, Elina Locane, and Eric D. Kelsic. Adalead: A simple and robust adaptive greedy search algorithm for sequence design. *ArXiv*, abs/2010.02141, 2020.

Kevin Swersky, Yulia Rubanova, David Dohan, and Kevin P. Murphy. Amortized bayesian optimization over discrete spaces. In *UAI*, 2020.

Tijmen Tieleman. Training restricted boltzmann machines using approximations to the likelihood gradient. In *ICML '08*, 2008.

Brandon Trabucco, Aviral Kumar, Xinyang Geng, and Sergey Levine. Conservative objective models for effective offline model-based optimization. In *ICML*, 2021.

Cédric Villani. Topics in optimal transportation. 2003.

Gui-Song Xia, Sira Ferradans, Gabriel Peyré, and Jean-François Aujol. Synthesizing and mixing stationary gaussian texture models. *SIAM J. Imaging Sci.*, 7:476–508, 2014.

Dinghuai Zhang, Nikolay Malkin, Zhen Liu, Alexandra Volokhova, Aaron Courville, and Yoshua Bengio. Generative flow networks for discrete probabilistic modeling. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 26412–26428. PMLR, 17–23 Jul 2022. URL `https://proceedings.mlr.press/v162/zhang22v.html`.

Supplement to "Improving Generative Flow Networks with Path Regularization"

A RELATED WORK

GFlowNets The objective of GFlowNets is related to MCMC methods for sampling from a given unnormalized density function, especially in discrete spaces where exact sampling is intractable (Dai et al. (2020); Grathwohl et al. (2021)). However, GFlowNets amortize the complexity of iterative sampling by a training procedure that implies the data's compositional structure as its learning problem. Empirically, GFlowNets' performance is better than other earlier methods in a wide variety of tasks: small molecules generation (Bengio et al. (2021)), discrete probabilistic modeling (Zhang et al. (2022)), Bayesian structure learning (Deleu et al. (2022)) and biological sequence design (Jain et al. (2022)). On the theoretical side, definitions and properties of GFlowNets are more investigated in Bengio et al..

Optimal Transport The optimal transport theory (OT) (Villani (2003)) has established a natural and useful geometric tool for comparing measures supported on metric probability spaces. The development of OT theory has a long history, where it has been discovered in many settings and under different forms. And in recent years, another revolution in the spread of OT has been witnessed, thanks to the emergence of approximate solvers that can scale to the problem of large dimensions. As a consequence, OT is being widely used to solve various problems in computer graphics (Bonneel et al. (2011),Nguyen et al. (2021)), image processing (Xia et al. (2014)), and machine learning (Courty et al. (2014), Ho et al. (2017) Genevay et al. (2018), Bunne et al. (2019)).

Energy-based models EBMs, or energy functions parameterized by deep neural networks, have demonstrated effectiveness in generative modeling (Salakhutdinov & Hinton (2009); Hinton et al. (2006)). Contrastive divergence methods (Hinton (2002); Tieleman (2008); Du et al. (2021)) have been proposed to handle costly MCMC processes by approximating energy gradient. Recently, it has been shown that simultaneous learning of the proposal distribution can also be helpful (Dai et al. (2019); Arbel et al. (2021)). Then this finding has been extended to discrete spaces by using GFlowNets in Zhang et al. (2022).

Biological sequence design Various methods have been proposed to handle the biological sequence design tasks: deep model-based optimization (Trabucco et al. (2021)), Bayesian optimization (Belanger et al. (2019); Swersky et al. (2020)), reinforcement learning (Angermueller et al. (2020)), adaptive evolutionary methods (Hansen (2006); Sinai et al. (2020)), and so on. Recently, GFlowNets also have been proposed as a useful generator of diverse candidates for this problem in Jain et al. (2022).

B BACKGROUND OF GFLOWNETS

Generative Flow Networks (GFlowNets) are a class of generative model learning to sample a compositional object $\mathbf{x}$ with probability in proportion to a given reward function $R(\mathbf{x})$. From a reinforcement learning viewpoint, GFlowNets learn a stochastic policy to generate object $\mathbf{x} \in \mathcal{X}$ by applying a sequence of discrete actions $a \in \mathcal{A}$. After an action, we might have an object or partially constructed object, which is described by a state $s \in \mathcal{S}$. The sequence of actions forms a complete trajectory $\tau = (s_0, s_1, ..., s_n, s_f)$ specifies how the object was build from scratch. The trajectory starting from an initial empty state s_0, going through a sequence of partially constructed object s and terminating at constructed object $s_n = x$ to a special final state s_f. The fully constructed objects in $\mathcal{X} \subset \mathcal{S}$ are called terminating states. From a probabilistic modeling viewpoint, GFlowNets can be seen as the flows of unnormalized probabilities in a directed acyclic graph $G = (\mathcal{S}, \mathcal{A})$ from a source s_0 to sinks $\mathbf{x} \in \mathcal{X}$, which then flows to the final single sink state s_f. The stochastic policy in GFlowNets acts as the gates to control the flows of unnormalized probabilities. If GFlowNets modify the gates so that the flow of unnormalized probabilities leading to the sink $\mathbf{x}$ is equals to the given reward $R(\mathbf{x})$, they can sample object $\mathbf{x}$ with probability in proportion to $R(\mathbf{x})$.

A *complete trajectory* is a sequence of states $\tau = (s_0, s_1, ..., s_n, s_f)$, where each transition $s_t \rightarrow s_{t+1}$ is an action in $\mathcal{A}$. For each transition $s \rightarrow s' \in \mathcal{A}$, we call s is a parent of s' and s' is a child of s. Let $\mathcal{T}$ be the set of complete trajectories.

Flows A *trajectory flow* (Bengio et al.) is a nonnegative function $F : \mathcal{T} \mapsto \mathbb{R}^+$. The flow $F(\tau)$ can be interpreted as the probability mass associated with trajectory τ. As an analogy with water flow, the flow $F(\tau)$ is the number of water particles sharing the same path τ.

The flow through a state (state flow) is defined as follows:

$$F(s) = \sum_{s \in \tau} F(\tau). \tag{24}$$

The flow through a edge (edge flow) is defined as follows:

$$F(s \to s') = \sum_{s \to s' \in \tau} F(\tau). \tag{25}$$

Trajectory flow is a measure on the set of all complete trajectories $\mathcal{T}$. Thus we can associate a probability measure P with the trajectory flow F:

$$P(\tau) := \frac{F(\tau)}{\sum_{\tau \in \mathcal{T}} F(\tau)} = \frac{F(\tau)}{Z}. \tag{26}$$

We can also define the probability $P_T(x)$ of visiting a terminal state x as follows:

$$P_T(x) := \frac{\sum_{\tau : x \in \tau} F(\tau)}{Z} = \frac{F(x)}{Z}. \tag{27}$$

The probability of an event $A \subseteq \mathcal{T}$ is defined as follows:

$$P(A) := \frac{F(A)}{Z} \tag{28}$$

where $F(A) = \sum_{\tau \in A} F(\tau)$.

The conditional probability of an event A given another event B is defined as follows:

$$P(A|B) := \frac{P(A, B)}{P(B)} = \frac{F(A \cap B)}{F(B)}. \tag{29}$$

The forward transition probabilities (forward policy) P_F and the backward transition probabilities (backward policy) are special cases of conditional probability, which are defined as follows:

$$P_F(s'|s) := P(s \to s'|s) = \frac{F(s \to s')}{F(s)}, \tag{30}$$

$$P_B(s|s') := P(s \to s'|s') = \frac{F(s \to s')}{F(s')}. \tag{31}$$

Markovian Flow Trajectory flow F is Markovian Flow if, for any state s, outgoing edge $s \to s'$, and for any trajectory $\tau = (s_1, \ldots, s)$ ending in s:

$$P(s \to s'|\tau) = P(s \to s'|s) = P_F(s'|s). \tag{32}$$

Equivalently (Bengio et al. (2021), Prop. 3)

$$P(\tau = (s_0 \to \ldots \to s_n)) = \prod_{t=1}^{n} P_F(s_t \mid s_{t-1}), \tag{33}$$

or equivalently

$$P(\tau = (s_0 \to \ldots \to s_n \mid s_n = x)) = \prod_{t=1}^{n} P_B(s_{t-1} \mid s_t). \tag{34}$$

Because each trajectory in GFlowNets was generate by policy $\pi(s'|s) = P_F(s'|s)$ via Eq. 33, as in Corollary 2 (Bengio et al. (2021)), if a GFlowNet yields a flow, then it is a Markovian flow. Learning a GFlowNet is considered the problem of fitting a Markovian flow to a fixed reward function on $\mathcal{X}$ as below.

Learning GFlowNets (Bengio et al. (2021)) Suppose that a nontrivial nonnegative reward function $R : \mathcal{X} \to \mathbb{R}_{\geq 0}$ is given on the set of terminal states. GFlowNets aim to approximate a Markovian flow F on $G = (\mathcal{S}, \mathcal{A})$ such that the likelihood of a trajectory sampled from F terminating in a given $x \in \mathcal{X}$ is proportional to $R(x)$, i.e. $P_T(x) \propto R(x)$. This is accomplished by the reward matching condition:

$$R(x) = \sum_{\tau : x \in \tau} F(\tau) = F(x) \quad \forall x \in \mathcal{X}. \tag{35}$$

If $R(x) = \sum_{\tau:x\in\tau} F(\tau) = F(x)$ then $P_T(x) = \frac{F(x)}{Z} \propto R(x)$, i.e. the likelihood of a trajectory sampled from F terminating in a given $x \in \mathcal{X}$ is proportional to $R(x)$. GFlowNet has several training objectives which were proven to satisfy 35.

Flow matching objective (Bengio et al. (2021)):

$$\sum_{s'} F(s' \to s) = \sum_{s''} F(s \to s''). \tag{36}$$

This is the conservation law, i.e., the total flow into a state is equal to the total flow moving out of it. We can parameterize GFlowNets with the edge flow function $F_\theta(\cdot, \cdot)$, and sample object x via the policy as the forward transition probabilities defined by this flow:

$$\pi(s'|s) = P_{F_\theta}(s'|s) = \frac{F_\theta(s \to s')}{\sum_{s''} F_\theta(s \to s'')}. \tag{37}$$

Bengio et al. (2021) shows that if the flow matching objective obtains a global minimum over a full-support training distribution $\overline{\pi}_\theta$, the policy $\pi(s'|s)$ would sample each object x with a probability $P_T(x)$ proportional to its reward R(x).

$$\mathcal{L}_{FM} = \left(\log(\sum_{s'} F_\theta(s' \to s)) - \log(\sum_{s''} F_\theta(s \to s'')) \right)^2. \tag{38}$$

Detailed balance objective:

$$F(s)P_F(s'|s) = P_B(s|s')F(s'). \tag{39}$$

This is because both sides of the term equal $F(s \to s')$. The detailed balance condition has a close relation with the flow matching condition, where the sum of flow is implicitly included in P_F and P_B. We can parameterize GFlowNets with $F_\theta(s)$, $P_F(\cdot|s;\theta)$, and $P_B(\cdot|s';\theta)$. As flow matching condition, we can turn detailed balance condition into a training objective:

$$\mathcal{L}_{DB} = (\log(F_\theta(s)P_F(\cdot|s;\theta)) - \log(F_\theta(s')P_B(\cdot|s';\theta)))^2. \tag{40}$$

Trajectory balance objective For any trajectory $\tau = (s_0, s_1, ...s_n = x)$

$$F(s_0) \prod_{t=1}^{n} P_F(s_t|s_{t-1}) = R(x) \prod_{t=1}^{n} P_B(s_{t-1}|s_t). \tag{41}$$

This is because both sides of the term equal $F(\tau)$. We can parameterize GFlowNets with $Z_\theta = F(s_0)$, $P_F(\cdot|s;\theta)$, and $P_B(\cdot|s';\theta)$. As flow matching condition, we can turn trajectory balance condition into a training objective:

$$\mathcal{L}_{TB} = \left(\log(Z_\theta \prod_{t=1}^{n} P_F(s_t|s_{t-1};\theta)) - \log(R(x) \prod_{t=1}^{n} P_B(s_{t-1}|s_t;\theta)) \right)^2. \tag{42}$$

Trajectory balance objective brings more efficient credit assignment and faster convergence (Malkin et al. (2022)).

GFlowNets can be trained offline This means we can use any train policy $\overline{\pi}$ of sampling trajectories τ to minimize the training objective $\mathbb{E}(\mathcal{L}(\tau))$ so long as it can sample all the possible trajectories with non-zero probability.

Usually, training policy $\overline{\pi}$ was chosen as a mixing of GFLowNets policy $\pi(s'|s)$ with α percentage of exploration by a uniform distribution:

$$\overline{\pi} = (1 - \alpha)\pi(s'|s) + \alpha\text{Uniform}. \tag{43}$$

C   DROPOUT OPTIMAL TRANSPORT

A limitation of the current method is computing the optimal transport distances for all couples of nearest neighbor states, especially in high dimensional discrete data. Our proposed Dropout OT might be a solution. This is because rather than sampling trajectories τ and using all edges from them, we can separately sample edges $s \to s'$ proportional to edge flows, allowing us to efficiently compute path regularization.

Theorem C.1 *For any complete trajectory* $\tau = (s_0 \rightarrow s_1 \rightarrow ... \rightarrow s_n)$ *sampled from the training policy* π_θ

$$\mathbb{E}_{\tau \sim \pi_\theta}(\mathcal{L}_{OT}(\tau)) \propto \mathbb{E}_{s \rightarrow s' \sim \pi_\theta}(OT(P_F(\cdot|s), P_F(\cdot|s'))). \tag{44}$$

The proof of Theorem C.1 is in Appendix D.3. Here we train GFlowNets with Trajectory Balance Objective. Therefore, when sampling a trajectory τ, we get a set of edges from τ. We just sample uniformly a p percentage of edges to compute OT loss.

To sample p percentage of edges, let sample $r_s \sim Ber(p)$.

$$\mathbb{E}_{s \rightarrow s' \sim \pi_\theta}(OT(P_F(\cdot|s), P_F(\cdot|s'))) = \frac{1}{p}\mathbb{E}_{r_s \sim Ber(p)}\mathbb{E}_{s \rightarrow s' \sim \pi_\theta}(r_s.OT(P_F(\cdot|s), P_F(\cdot|s'))). \tag{45}$$

We approximate the path regularization loss via:

$$\mathcal{L}_{\text{OT}}(\tau) \simeq \frac{1}{p}\sum_{t=0}^{n-1} x_t\text{OT}(P_F(.|s_t), P_F(.|s_{t+1})) \tag{46}$$

with x_t drawn independently from $\text{Ber}(p)$ for all $0 \le t \le n-1$. Intuitively, if $x_t = 0$ then we don't need to calculate the corresponding optimal transport cost anymore, which reduces a considerable amount of computing time and memory down to p percentage.

D PROOFS

D.1 PROOF OF THEOREM 3.1

For any trajectory $\tau = (s_0 \rightarrow s_1 \rightarrow ... \rightarrow s_n)$, we first prove that for any $t \in \overline{0, n-1}$

$$\text{OT}(P_F(\cdot|s_t), P_F(\cdot|s_{t+1})) \le \mathbf{H}(P_F(\cdot|s_t), P_B^*(\cdot|s_t)) - \log(P_F(s_{t+1}|s_t)) + \mathbf{H}(P_F(\cdot|s_{t+1})). \tag{47}$$

Consider two neigboor states s_t and s_{t+1} with the children sets: $\text{Child}(s_t) = \{u_1, ..., u_k\}$ and $\text{Child}(s_{t+1}) = \{v_1, ..., v_l\}$. By definition 6, the optimal transportation distance between two distributions $P_F(.|s_t)$ and $P_F(.|s_{t+1})$ is defined as:

$$\text{OT}_{\mathbf{C}}(P_F(\cdot|s_t), P_F(\cdot|s_{t+1})) := \min_{\pi \in \prod(P_F(\cdot|s_t), P_F(\cdot|s_{t+1}))} \langle \mathbf{C}, \pi \rangle, \tag{48}$$

where the admissible couplings set is defined as:

$$\Pi(P_F(.|s_t), P_F(.|s_{t+1})) = \left\{\pi \in \mathbb{R}_+^{k \times l} : \pi \mathbb{1}_l = P_F(\cdot|s_t), \pi^{\mathsf{T}}\mathbb{1}_k = P_F(\cdot|s_{t+1})\right\}. \tag{49}$$

We have,

$$\text{OT}(P_F(.|s_t), P_F(.|s_{t+1}))$$

$$\le \sum_i \sum_j \pi_{ij}\mathbf{C}_{ij}$$

$$\le -\sum_i \sum_j \pi_{ij}\log\left(P_B(s_t|u_i)P_F(s_{t+1}|s_t)P_F(v_j|s_{t+1})\right)$$

$$= -\sum_i \sum_j \pi_{ij}\log\left(P_B(s_t|u_i)\right) - \sum_i \sum_j \pi_{ij}\log\left(P_F(s_{t+1}|s_t)\right) - \sum_i \sum_j \pi_{ij}\log\left(P_F(v_j|s_{t+1})\right))$$

$$= -\sum_i \log\left(P_B(s_t|u_i)\right)\sum_j \pi_{ij} - \log\left(P_F(s_{t+1}|s_t)\right)\sum_i \sum_j \pi_{ij} - \sum_i \log\left(P_F(v_j|s_{t+1})\right)\sum_j \pi_{ij}$$

$$= -\sum_i \log\left(P_B(s_t|u_i)\right)P_F(u_i|s_t) - \log\left(P_F(s_{t+1}|s_t)\right) - \sum_j \log\left(P_F(v_j|s_{t+1})\right))P_F(v_j|s_{t+1})$$

$$= -\sum_i \log\left(P_B^*(u_i|s_t)\right)P_F(u_i|s_t) - \log\left(P_F(s_{t+1}|s_t)\right) + \mathbf{H}(P_F(.|s_{t+1})$$

$$= \mathbf{H}(P_F(.|s_t), P_B^*(.|s_t)) - \log(P_F(s_{t+1}|s_t)) + \mathbf{H}(P_F(.|s_{t+1})). \tag{50}$$

The first inequality obtained by the definition of optimal transport distance in Eq. 48, the second inequality comes from Eq. 9, the fifth equality is due to the constraints of admissible couplings in Eq. 49.

As a consequence, the upper-bound loss is obtained by summing up all inequality 47 for all t.

D.2 PROOF OF THEOREM 3.2

Recall from definition 6 the optimal transportation distance between two distributions $P_F(.|s)$ and $P_F(.|s')$ is defined as:

$$\text{OT}_{\mathbf{C}}\left(P_F(\cdot|s), P_F(\cdot|s')\right) := \min_{\pi \in \Pi(P_F(\cdot|s), P_F(\cdot|s'))} \langle \mathbf{C}, \pi \rangle. \tag{51}$$

Let decompose the total cost $\langle \mathbf{C}, \pi \rangle$

$$
\begin{aligned}
\langle \mathbf{C}, \pi \rangle &= \sum_{i,j} \pi_{ij} \mathbf{C}_{ij} \\
&= \sum_{i,j} \pi_{ij}(-\log(P_B(s|u_i)) - \log(P_F(s'|s)) - \log(P_F(v_j|s'))) \\
&+ \sum_{u_i=s',j} \pi_{ij}(\log(P_B(s|s')) + \log(P_F(s'|s))) \\
&+ \sum_{u_i \neq s', v_j \in Child(u_i), a_i \neq a^\top} \pi_{ij}(\log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_j|s') + \mathbf{C}_{ij}) \\
&+ \sum_{u_i=v_j} \pi_{ij}(\log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_j|s'))).
\end{aligned}
\tag{52}
$$

We will prove that $u_i \neq v_j \quad \forall i, j$, i.e, Child$(s) \cap$ Child$(s') = \varnothing$, indeed,

$$a_i \neq a_k + a_h \quad \forall a_i, a_k, a_h \in \mathcal{A} \implies a_i \neq a_s^* + a_j \implies s + a_i \neq s + a_s^* + a_j \implies u_i \neq v_j. \quad \forall i, j \tag{53}$$

We have

$$
\begin{aligned}
& u_i \neq s', \quad v_j \in Child(u_i), \quad a_i \neq a^\top \\
\iff\ & a_i \neq a_s^*, \quad s + a_i + a_{u_i}^* = s + a_s^* + a_j, \quad a_i \neq a^\top \\
\iff\ & a_i \neq a_s^*, \quad a_i + a_{u_i}^* = a_s^* + a_j, \quad a_i \neq a^\top \\
\iff\ & a_i \neq a_s^*, \quad a_i = a_j \neq a^\top, \quad a_{u_i}^* = a_s^*.
\end{aligned}
\tag{54}
$$

As a result, we can rewrite Eq. 52 as:

$$
\begin{aligned}
\langle \mathbf{C}, \pi \rangle &= \sum_{i,j} \pi_{ij}(-\log(P_B(s|u_i)) - \log(P_F(s'|s)) - \log(P_F(v_j|s'))) \\
&+ \sum_{u_i=s',j} \pi_{ij}(\log(P_B(s|s')) + \log(P_F(s'|s))) \\
&+ \sum_{u_i \neq s', a_i = a_j \neq a^\top} \pi_{ij}(\log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_j|s') + \mathbf{C}_{ii})).
\end{aligned}
\tag{55}
$$

The first term of above equation actually is the upper-bound of the optimal transport distance. Therefore, we can rewrite the total transport cost as:

$$
\begin{aligned}
\langle \mathbf{C}, \pi \rangle &= \mathbf{H}(P_F(\cdot|s), P_B^*(\cdot|s)) - \log(P_F(s'|s)) + \mathbf{H}(P_F(\cdot|s') \\
&+ P_F(s'|s).(\log(P_B(s'|s)) + \log(P_F(s'|s))) \\
&+ \sum_{u_i \neq s', a_i = a_j \neq a^\top} \pi_{ij}(\log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_j|s') + \mathbf{C}_{ii})).
\end{aligned}
\tag{56}
$$

From the definition of c_i' in Eq. 22, we have

$$c_i' = \begin{cases} \log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_j|s') + \mathbf{C}_{ii}), & \text{if } u_i \neq s', a_i = a_j \neq a^\top \\ 0 & \text{if } u_i = s' \text{ or } a_i = a^\top. \end{cases} \tag{57}$$

From Eq. 56 and Eq. 57, we have

$$\sum_{u_i \neq s', a_i = a_j \neq a^\top} \pi_{ij}(\log(P_B(s|u_i)) + \log(P_F(s'|s)) + \log(P_F(v_j|s') + \mathbf{C}_{ii}) = \sum_i \pi_{ij}.c_i'. \tag{58}$$

Thus, we find that

$$\underset{\pi \in \prod(P_F(\cdot|s), P_F(\cdot|s'))}{\arg\min} \langle \mathbf{C}, \pi \rangle = \underset{\pi \in \prod(P_F(\cdot|s), P_F(\cdot|s'))}{\arg\min} \langle \mathbf{C}', \pi \rangle \tag{59}$$

where, $\mathbf{C}'$ is a diagonal matrix with the diagonal $c_i' \leq 0$. For convenience, if action a_i is invalid at state s, we assign $P_F(u_i \mid s) := 0$, so the cost matrix of the optimal transport distance still is a square matrix with the zero cost a invalid actions, then applying the Lemma 1, we have:

$$\min_{\pi \in \prod(P_F(\cdot|s), P_F(\cdot|s'))} \langle \mathbf{C}', \pi \rangle = \sum_i \min(P_F(u_i|s), P_F(v_i|s))\mathbf{C}_{ii}'. \tag{60}$$

We obtain the closed form formulation for optimal transport distance

$$\begin{aligned} \mathrm{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right) &= \mathbf{H}(P_F(\cdot|s), P_B^*(\cdot|s)) - \log(P_F(s'|s)) + \mathbf{H}(P_F(\cdot|s')) \\ &\quad + P_F(s'|s).(\log(P_B(s'|s)) + \log(P_F(s'|s))) \\ &\quad + \sum_{i \in A_s^* \cap A_{s'}^*} \min(P_F(u_i|s), P_F(v_i|s'))c_i'. \end{aligned} \tag{61}$$

Lemma 1 *Given a squared diagonal cost matrix $\mathbf{C}'$ with non-positive entities in the diagonal, the solution of optimal transport problem between two distribution $P_F(\cdot|s)$ and $P_F(\cdot|s')$, which has the same number of support points, given cost matrix $\mathbf{C}'$ is given by:*

$$\min_{\pi \in \Pi(P_F(\cdot|s), P_F(\cdot|s'))} \langle \mathbf{C}', \pi \rangle = \sum_i \min(P_F(u_i|s), P_F(v_i|s))\mathbf{C}_{ii}'. \tag{62}$$

Proof of Lemma 1: Let define
$$F(\pi) = \langle \mathbf{C}', \pi \rangle,$$

$$\overline{p}_{ij} = \begin{cases} \min(p_s^i, p_{s'}^i), & \text{if } i = j \\ \dfrac{\left(p_s^i - \min(p_s^i, p_{s'}^i)\right)\left(p_{s'}^j - \min(p_s^j, p_{s'}^j)\right)}{1 - \sum_k \min(p_s^k, p_{s'}^k)} & \text{if } i \neq j. \end{cases}$$

where $p_s^i := P_F(u_i|s)$ and $p_{s'}^j := P_F(v_j|s')$.

We will prove that $\overline{\pi} \in \Pi\left(P_F(\cdot|s), P_F(\cdot|s')\right)$ and $F(\pi) \geq F(\overline{\pi}) \quad \forall \pi \in \Pi\left(P_F(\cdot|s), P_F(\cdot|s')\right)$.

It is not difficult to show that $\overline{\pi}_{ij} \geq 0$. From the definition of $\overline{\pi}$, we have

$$\sum_j^n \overline{\pi}_{ij} = \sum_{j \neq i} \overline{\pi}_{ij} + \overline{\pi}_{ii} = \sum_{j \neq i} \frac{\left(p_s^i - \min(p_s^i, p_{s'}^i)\right)\left(p_{s'}^j - \min(p_s^j, p_{s'}^j)\right)}{1 - \sum_k \min(p_s^k, p_{s'}^k)} + \min(p_s^i, p_{s'}^i). \tag{63}$$

If $\min(p_s^i, p_{s'}^i) = p_s^i$ then

$$\sum_j^n \overline{\pi}_{ij} = 0 + \min(p_s^i, p_{s'}^i) = p_s^i. \tag{64}$$

else $\min(p_s^i, p_{s'}^i) = p_{s'}^i$ then

$$\sum_{j \neq i} \left(p_{s'}^j - \min(p_s^j, p_{s'}^j)\right) = \sum_j \left(p_{s'}^j - \min(p_s^j, p_{s'}^j)\right) = 1 - \sum_k \min(p_s^k, p_{s'}^k)$$

$$\implies \sum_j^n \overline{\pi}_{ij} = \left(p_s^i - \min(p_s^i, p_{s'}^i)\right) \frac{\sum_{j \neq i} \left(p_{s'}^j - \min(p_s^j, p_{s'}^j)\right)}{1 - \sum_k \min(p_s^k, p_{s'}^k)} + \min(p_s^i, p_{s'}^i) = p_s^i. \tag{65}$$

Therefore $\sum_j^n \overline{\pi}_{ij} = p_s^i = P_F(u_i|s)$. Similarly, $\sum_i^n \overline{\pi}_{ij} = p_s^j = P_F(v_j|s')$, combining with $\overline{\pi}_{ij} \geq 0$, we have

$$\overline{\pi} \in \Pi\left(P_F(\cdot|s), P_F(\cdot|s')\right). \tag{66}$$

Moreover

$$F(\pi) = \langle \mathbf{C}', \pi \rangle = \sum_i \pi_{ii}\mathbf{C}_{ii}' \geq \sum_i \min(p_s^i, p_{s'}^i)\mathbf{C}_{ii}' = \langle \mathbf{C}', \overline{\pi} \rangle = F(\overline{\pi}) \quad \forall \pi \in \Pi\left(P_F(\cdot|s), P_F(\cdot|s')\right).$$
$$\tag{67}$$

As a consequence, we obtained the solution of optimal transport problem.

Closed form solution for optimal transport distance at terminal state. We will derive the closed form solution for optimal transport distance in case of two neighbor states $s < s'$, in which s'

is a terminal state. In the case of Hyper-grid environment, EB-GFN experiments, and Biological Sequence Design, all terminal state x have only one child that is the final state s_f, and $P_F(s_f|x) = 1 \quad \forall x$. Thus, the admissible couplings set $\prod(P_F(\cdot|s), P_F(\cdot|s'))$ has only one element. That is $\pi^* = P_F(\cdot|s)$. As a result, the optimal transportation distance between $P_F(.|s)$ and $P_F(.|s')$ is:

$$\text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right) = \min_{\pi \in \prod(P_F(\cdot|s), P_F(\cdot|s'))} \langle \mathbf{C}, \pi \rangle = \langle \mathbf{C}, \pi^* \rangle. \tag{68}$$

Specially, in EB-GFN experiments, all children u_i of s is a terminal state so $d(u_i, s_f) = -\log(1) = 0$. This makes $\mathbf{C} = 0$ and $\text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right) = 0$. In Hyper-grid environment experiment, for terminal sate s' because $c'_i = 0$, we have:

$$\text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right) = \mathbf{H}(P_F(\cdot|s), P_B^*(\cdot|s)) - \log(P_F(s'|s))$$
$$+ P_F(s'|s).(\log(P_B(s'|s)) + \log(P_F(s'|s))). \tag{69}$$

The Hyper-grid environment (Bengio et al., 2021) (in section 4.1) and EB-GFN experiments (Zhang et al., 2022) (in section 4.3) satisfy two condition in Theorem 3.2. In Biological Sequence Design (Jain et al., 2022) (in section 4.2) such as protein and DNA sequences, the action space consists of actions adding a nucleic acid in $\{A, T, G, U\}$ and a amino acid respectively. Such settings satisfy former condition $a_i \neq a_k + a_h \quad \forall a_i, a_k, a_h \in \mathcal{A}$. However, the later condition $a_i + a_h = a_m + a_n, a_i \neq a_m \iff a_i = a_n, a_h = a_m, a_i \neq a_m$ is no longer true because the order property of action space, i.e, $a_i + a_j \neq a_j + a_i$. In this situation, the third terms in Eq. 20 is zero and we can still using the formulation in Eq. 20. Generally, the action space is independence and unique factorization.

D.3 PROOF OF THEOREM C.1

By definition of the edge flow we have

$$\sum_{\tau: s \to s' \in \tau} P(\tau) = \sum_{\tau: s \to s' \in \tau} \frac{F(\tau)}{Z} = \frac{F(s \to s')}{Z} = P(s \to s'). \tag{70}$$

From that equation, we find that

$$\begin{aligned}
\mathbb{E}_{\tau \sim \pi_\theta}(\mathcal{L}_{\text{OT}}(\tau)) &= \mathbb{E}_{\tau \sim \pi_\theta}\left(\sum_{s \to s' \in \tau} \text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right)\right) \\
&= \sum_{\tau} \sum_{s \to s' \in \tau} \text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right).P(\tau) \\
&= \sum_{s \to s'} \sum_{\tau: s \to s' \in \tau} \text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right).P(\tau) \\
&= \sum_{s \to s'} \text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right) \sum_{\tau: s \to s' \in \tau} P(\tau) \\
&= \sum_{s \to s'} \text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right).P(s \to s') \\
&\propto \mathbb{E}_{s \to s' \sim \pi_\theta}(\text{OT}\left(P_F(\cdot|s), P_F(\cdot|s')\right)).
\end{aligned} \tag{71}$$

$\square$

E EXPERIMENT SETTINGS

In this part, we report experiment settings, including evaluation metrics for comparing the methods, hyper-parameter choices, and neural network architectures for all experiments. For biological sequence design tasks, we also give more details about the task description and datasets used for training.

E.1 HYPER-GRID ENVIRONMENT

E.1.1 EVALUATION CRITERIA

To evaluate the performance, we measure the KL divergence between the actual and empirical distribution of the last 2×10^5 visited states. The number of modes found during the training progress is also used to measure the learned models' performance.

E.1.2 IMPLEMENTATION DETAILS

GFlowNet: For the implementation of the GFlowNet model, we also follow the framework of Malkin et al. (2022): an MLP with two hidden layers of 256 dimensions each. The GFlowNet policy model, which includes both P_F and P_B, is trained with a learning rate of 0.001 while the learning rate for total flow Z_θ is 0.1. We use a mini-batch size of 16 and 62500 training steps with the trajectory balance objective.

Proposed OT regularization The regularization coefficient is 0.02 for both Min OT, UB OT, and Max OT in our $4 - D$ and $7 - D$ hypergrid environment.

E.2 BIOLOGICAL SEQUENCE DESIGN

E.2.1 TASK DESCRIPTION & DATASETS

These experiments simulate the process of designing biological sequences, such as anti-microbial peptides, DNA, and protein sequences..., in drug discovery applications. This process often consists of an active loop with several rounds of ideating molecules and multiple-stage evaluations for filtering candidates, with rising levels of precision and cost. This characteristic makes the diversity of proposed candidates a considerable concern in the ideation phase because many similar candidates can all fail in the later phases.

Specifically, we consider the problem of finding objects x in the space of discrete objects $\mathcal{X}$, that maximize a given oracle $f : \mathcal{X} \mapsto \mathbb{R}^+$. Here, we can only query this oracle N times, each with an input batch of fixed size b. This can form N rounds of evaluation in the active learning setting, where the generative policy is initially given a dataset $D_0 = \left\{ \left(x_1^0, y_1^0 \right), \ldots, \left(x_n^0, y_n^0 \right) \right\}$ collected from the oracle, where $y_i^0 = f(x_i^0)$ for $1 \leq i \leq n$.

Because the oracle can only be called limited, we also train a supervised proxy model M that predicts y from x to approximate the oracle f. Specifically, in i-th round, given the current dataset $\mathcal{D}_i$, this proxy model can be used as a reward function R to collect additional observations to train our generative policy to propose a batch of candidates $\mathcal{B}_i = \left\{ x_1^i, \ldots, x_b^i \right\}$. Then the current dataset $\mathcal{D}_i$ is updated for the next round of evaluation as $\mathcal{D}_{i+1} = \mathcal{D}_i \cup \left\{ \left(x_1^i, y_1^i \right), \ldots, \left(x_b^i, y_b^i \right) \right\}$ where $y_j^i = f\left(x_j^i \right)$.

Following the framework of Jain et al. (2022), we will conduct experiments on the biological sequence design tasks:

Anti-Microbial Peptide Design: This task aims to generate short amino-acid sequences of length lower than 51, which have anti-microbial properties. The vocabulary has 20 amino-acids $[A, C, D, E, F, G, H, I, K, L, M, N, P, Q, R, S, T, V, W, Y]$. The active learning algorithm is evaluated for $N = 10$ rounds, with the number of candidates generated each round $b = 1000$. The initial dataset $\mathcal{D}_0$ contains 3219 AMPs and 4611 non-AMP sequences, which is collected from the DBAASP database Pirtskhalava et al. (2021).

TFBind 8: The goal of this task is to generate DNA sequences of length 8, which have high binding activity with human transcription factors. The vocabulary has 4 nucleobases $[A, C, T, G]$. The active learning algorithm is evaluated for $N = 10$ round, with the number of candidates generated each round $b = 128$. The initial dataset $\mathcal{D}_0$ contains $32, 898$ samples, which is half of all possible DNA sequences of length 8 having lower scores. The data and the oracle used are from Barrera et al. (2016).

GFP: The objective of this task is to generate protein sequences of length 237 that have high fluorescence. The vocabulary is similar to the one of the AMP task (size 20). The active learning algorithm is evaluated for $N = 10$ round, with the number of candidates generated each round $b = 128$. The initial dataset $\mathcal{D}_0$ contains $5, 000$ samples, which is from Rao et al. (2019); Sarkisyan et al. (2016) together with the oracle.

E.2.2 EVALUATION CRITERIA

To evaluate the performance, we also use the metrics as in Jain et al. (2022). Specifically, considering a set of candidates $\mathcal{D}$, we have the following metrics:

Performance score: mean score of the candidates in the set

$$\text{Mean}(\mathcal{D}) = \frac{\sum_{(x_i, y_i) \in \mathcal{D}} y_i}{|\mathcal{D}|}, \tag{72}$$

Diversity: a measurement of how well the generated candidates can capture the modes of the distribution implied by the oracle

$$\text{Diversity}(\mathcal{D}) = \frac{\sum_{(x_i,y_i)\in\mathcal{D}} \sum_{(x_j,y_j)\in\mathcal{D}\setminus\{(x_i,y_i)\}} d\left(x_i, x_j\right)}{|\mathcal{D}|(|\mathcal{D}|-1)}, \tag{73}$$

where d is a distance defined over $\mathcal{X}$, such as Levenshtein distance Miller et al. (2009).

Novelty: a measure of the difference between the candidates in $\mathcal{D}$ and $\mathcal{D}_0$

$$\text{Novelty}(\mathcal{D}) = \frac{\sum_{(x_i,y_i)\in\mathcal{D}} \min_{s_j\in\mathcal{D}_0} d\left(x_i, s_j\right)}{|\mathcal{D}|}. \tag{74}$$

These metrics will be evaluated on the set of candidates that have top K scores $\mathcal{D} = \text{TopK}(\mathcal{D}_N \setminus \mathcal{D}_0)$.

E.2.3 IMPLEMENTATION DETAILS

For the implementation of the GFlowNet-AL baseline model, we use the previously published implementation with slight changes, which follows the training setups of Jain et al. (2022):

Proxy model: We parameterize it as an MLP with two hidden layers, each having 2048 hidden units, and use ReLU activation. We also use ensembles of 5 models with same architecture for uncertainty estimation. For the acquisition function, we use UCB ($\mu + \kappa\sigma$) with $\kappa = 0.1$. The proxy is trained with MSE loss using mini-batch of size 256 and Adam optimizer with $(\beta_0, \beta_1) = (0.9, 0.999)$ and learning rate 10^{-4}. During training, early stopping is also used by evaluating the validation set containing 10% of the data.

GFlowNet generator: We use an MLP with 2 hidden layers of 2048 hidden units each. The model is trained with trajectory balance objective as the main loss function, by using Adam optimizer with $(\beta_0, \beta_1) = (0.9, 0.999)$. Additionally, $\log Z$ is trained with a learning rate of 10^{-3} for AMP, TF Bind 8 task, and 5×10^{-3} for GFP task. Other hyper-parameters are shown in the following table:

Hyper-parameter	AMP	TF Bind 8	GFP
δ : Uniform Policy Coefficient	0.001	0.001	0.05
Learning rate	5×10^{-4}	10^{-5}	10^{-3}
m : Minibatch size	32	32	32
β : Reward Exponent $R(x)^\beta$	3	3	3
T : Training steps	10,000	5,000	50,000

Table 5: Hyper-parameters for the GFlowNet.

There are some changes in hyper-parameter choices and the number of active learning rounds in the TF Bind 8 task and the GFP task compared to the original training setups of Jain et al. (2022). However, during the experiment, we observed that these settings helped us get the closest results to the reported one in Jain et al. (2022).

Proposed OT regularization The regularization coefficients for Min OT, UB OT, and Max OT are the same for each biological sequence design task. Specifically, the coefficients for the AMP, TF Bind 8, and GFP task are 0.025, 0.1, and 0.02 correspondingly.

E.3 SYNTHETIC DISCRETE PROBABILISTIC MODELING TASKS

E.3.1 EVALUATION CRITERIA

To evaluate the performance, we keep the same evaluation criteria in Zhang et al. (2022), where they use the NLL of a large independent sample of ground truth data and the exponential Hamming MMD (Gretton et al. (2012)) between ground truth data and generated samples as performance metrics. To measure NNL and MMD, we use 10 fixed sets, and each set consists of 4000 ground truth data samples.

E.3.2 IMPLEMENTATION DETAILS

GFlowNet: For the implementation of the GFlowNet model, we use an MLP with 2 hidden layers of 512 dimensions each. The GFlowNet policy model, which includes both P_F and P_B, is trained

with a learning rate of 0.001. We use a mini-batch size of 128 and $1e5$ training steps with the trajectory balance objective.

EBMs: For the implementation of the Energy-Based Model, we use an MLP with 3 hidden layers of 256 dimensions each. The learning rate is 0.001.

Proposed OT regularization: The regularization coefficient is 0.001 for both Min OT and UB OT and is the same for all tasks.