CARVE: Caption-Anchored, Rubric-Verified Extraction for Training-Scale Figure-Required Scientific VQA

Abstract

Fine-tuning vision-language models (VLMs) to comprehend complex scientific literature is bottlenecked by a trade-off between dataset scale and data quality. Human-curated benchmarks preserve quality but are far too small (1–3k items) to serve as fine-tuning data. Conversely, large-scale automated corpora achieve the volume necessary for fine-tuning but are plagued by repetitive language and a heavy reliance on multiple-choice questions (MCQs) that allow models to exploit text-only shortcuts. To bridge this gap, we introduce **CARVE** (Caption-Anchored, Rubric-Verified Extraction), a massive dataset of 392,957 items designed specifically to occupy a novel space in scientific VQA: it provides the large scale required for robust model training while strictly retaining the high-quality, prior-free, and completely free-form characteristics of expert human benchmarks. CARVE is constructed using a scalable text-first, vision-verified pipeline featuring multi-stage quality filtering, ensuring that every generated question is grounded and unanswerable without resolving the underlying figure. We evaluate CARVE by fine-tuning state-of-the-art open-source VLMs across the Qwen and InternVL families. Our fine-tuned models exhibit notable cross-family transfer gains on complex, open-ended scientific reasoning benchmarks, including a +3.9 lift on CharXiv-reasoning at 7B scale. Ultimately, our work demonstrates that shifting away from multiple-choice constraints toward training-scale, free-form visual data is a powerful paradigm for building VLMs capable of true scientific comprehension.

1 Introduction

The ability to comprehend scientific literature is a grand challenge for modern artificial intelligence. While vision-language models (VLMs) have made strides in general scene understanding (Liu et al., 2023; Bai et al., 2025; Zhu et al., 2025), scientific document processing remains distinct and exceptionally difficult (Pramanick et al., 2024; Wang et al., 2024; Liang et al., 2024; Borisova et al., 2025). Scientific papers convey their most critical quantitative and structural insights through complex figures, charts, plots, and multi-panel diagrams (Kembhavi et al., 2016; Masry et al., 2022; Methani et al., 2020). To truly master this domain, a model cannot merely skim the text; it must tightly couple textual context with rigorous, visually-grounded reasoning. Consequently, scientific visual question answering (SciVQA) has emerged as a vital benchmark for evaluating advanced multimodal capabilities (Lu et al., 2022; Yue et al., 2024; Wang et al., 2024).

However, the progress of fine-tuning VLMs for scientific figure comprehension is fundamentally bottlenecked by a severe data trade-off. Existing SciVQA datasets generally fall into two restrictive paradigms. On one end are human-curated benchmarks (e.g., CharXiv, AI2D) (Wang et al., 2024; Kembhavi et al., 2016). These are high-quality, highly difficult, and rigorously verified. However, because they rely on expensive expert annotation, they are typically limited to 1,000 to 3,000 items. While excellent for evaluation, they are far too small to serve as effective training sets for fine-tuning. On the other end are large-scale training corpora (e.g., PlotQA, VQAv2) (Methani et al., 2020; Goyal et al., 2017). While these achieve the volume necessary for model training, they are plagued by low linguistic diversity, high answer-prior issues, and duplicate-question rates of over 60%. Furthermore, recent efforts to scale scientific VQA (e.g., ArXivQA, VeriSciQA) rely heavily on multiple-choice questions (MCQs) (Li et al., 2024, 2025). MCQs introduce language-bias shortcuts, allowing models to guess correct answers based on text priors without actually resolving the underlying image (Balepur et al., 2025).

In this paper, we introduce **CARVE** (Caption-

Figure 1: Unlike prior scientific VQA datasets that are either small but expert-curated, large but shortcut-prone, or arXiv-grounded but multiple-choice, CARVE introduces a training-scale, free-form, figure-required dataset construction paradigm. Its key technical distinction is a text-first, vision-verified pipeline: an LLM first extracts claims and drafts candidate QA pairs from textual provenance, and a VLM then verifies visual grounding against the figure. This decomposition reduces caption-answerable and hallucinated items while preserving scale, yielding a dataset that is simultaneously large, free-form, prior-free, and visually necessary.

Anchored, Rubric-Verified Extraction), a dataset designed specifically to occupy a novel space in the SciVQA landscape. CARVE is the first dataset of its size comprising 392,957 items from approximately 40,000 arXiv papers, that bridges this gap by being explicitly built for large-scale training while retaining the high-quality, high-difficulty characteristics of expert human benchmarks. Crucially, CARVE rejects the prevalent multiple-choice format in favor of free-form, open-ended question-answering. Free-form datasets force generative models to produce precise textual, numerical, or categorical answers from the visual data alone, eliminating the possibility of exploiting random guessing or option-elimination shortcuts. See Figure 1.

To achieve both training-level scale and benchmark-level quality without human annotators, we introduce a multi-stage generation pipeline. Rather than feeding full images to a VLM from the start, our pipeline operates on a "text-first, vision-verified" paradigm. The core philosophy of this pipeline is multi-stage quality filtering: each of its five sequential stages serves as an explicit quality-control gate to ensure that every generated question is robust, hallucination-free, and strictly figure-

required (unanswerable by the text alone).

By fine-tuning popular open-source VLMs (Qwen2.5-VL (Bai et al., 2025) and InternVL3 (Zhu et al., 2025)) on CARVE, we demonstrate the unique value of this dataset. Our fine-tuned models exhibit notable performance improvements on complex, free-form scientific reasoning tasks while not notably degrading performance on multiple benchmarks.

In summary, our primary contributions are as follows:

- **The CARVE Dataset**: We introduce a massive, training-scale SciVQA dataset of 392,957 items that focuses exclusively on high-difficulty, free-form, and figure-required scientific reasoning.

- **A Rubric-Verified Generation Pipeline**: We propose a robust, scalable, five-stage pipeline that decouples text-only drafting from image-grounded validation, providing a blueprint for high-quality synthetic data generation.

- **Empirical Fine-Tuning Evaluations**: We present comprehensive experiments demonstrating that fine-tuning VLMs on free-form

CARVE data yields substantial cross-family performance gains on held-out scientific reasoning benchmarks, including a +3.9 lift on CharXiv-reasoning at 7B scale.

2 Related Work

Human-Curated VQA Benchmarks. Human-annotated scientific benchmarks provide high-quality evaluation but are fundamentally limited in scale. Datasets such as AI2D (Kembhavi et al., 2016), ScienceQA (Lu et al., 2022), ChartQA (Masry et al., 2022), MMMU (Yue et al., 2024), and CharXiv (Wang et al., 2024) typically contain 1−3k items per split. While excellent for rigorous evaluation, they are far too small to serve as robust fine-tuning data. Furthermore, many of these datasets rely heavily on multiple-choice formats, causing their ability to separate models to diminish.

Large-Scale and arXiv-Grounded Corpora. To achieve training-level volume, several efforts auto-generate VQA datasets. Early large-scale corpora like VQAv2 (Goyal et al., 2017) and PlotQA (Methani et al., 2020) reach million-item scales but suffer from severe answer-prior saturation, exhibiting exact duplicate-question rates over 60%. Other arXiv-grounded construction efforts aim to improve scientific relevance. ArXivQA (Li et al., 2024) generates 100k items in a single pass without isolating text from vision. LiveXiv (Shabtay et al., 2024) instead converts the images to captions before having GPT-4o generate multiple-choice questions, which are then tested to ensure they cannot be solved with just text and conversely that the full question can be solved by a second LLM, Claude Sonnet. Prior work shows that VLMs often underperform relative to LLMs operating on textual scene descriptions, suggesting that visual embeddings act as a lossy bottleneck for compositional reasoning and semantic abstraction (Nagar et al., 2024). VeriSciQA (Li et al., 2025) shares CARVE's essential "text-first, vision-verified" principle but limits generation to 20k items and restricts the answer space to four multiple-choice letters. CARVE occupies a previously empty intersection: it provides massive training scale (393k items) while rejecting multiple-choice constraints in favor of fully free-form, figure-required answers.

Verification and Training Methods. While human annotation remains the gold standard for verification (Wang et al., 2024), automated cross-family VLM verification scales much better (Li et al., 2025). CARVE adopts this scalable verification but complements it with an audit of each pipeline filter's rejection pool by independent vision judges. For our downstream empirical validation, we follow standard LoRA fine-tuning recipes (Hu et al., 2022; Zheng et al., 2024) and serve models using vLLM (Kwon et al., 2023) and the VLMEvalKit harness (Duan et al., 2024).

3 CARVE

3.1 Source Data

CARVE is constructed from arXiv LaTeX source bundles. We extract figures, their captions, and the body-text paragraphs that reference each figure ("local context"). Each figure is associated with its caption and one or more context paragraphs, yielding a text-rich provenance envelope that anchors downstream question generation. The production run covers approximately 40,000 papers and 270,000 unique figures spanning a broad range of scientific disciplines.

3.2 Multi-Stage Generation Pipeline

We convert the source figures and text into VQA items through a five-stage generation and verification pipeline (Stages A–E), followed by a global deduplication pass (Stage F). Full prompts are provided in Appendix A.

Stage A: Claim Extraction. A text-only LLM extracts atomic scientific claims from the paragraphs referencing the figure, forming a claim inventory that serves as the primary evidence source.

Stage B: Text-Only Drafting. The LLM generates free-form draft benchmark items (question, answer, and evidence units) using only the text context and claims. Crucially, the figure image is *not* provided, forcing the draft to rely entirely on text-grounded evidence.

Stage C: Text-Only Quality Control. A deterministic pass evaluates four critical checks: groundedness, multimodal value (the question cannot be fully answered from text alone), and English language. Failing any check results in a Stage C rejection.

Stage D: Image-Grounded Verification. Surviving drafts are passed to a VLM *alongside the actual figure image*. The VLM verifies the drafted claims against the visual evidence and upgrades

Split	Items	Papers	Figures
train	388,957	37,730	267,475
dev	1,000	804	992
test	1,000	768	996
challenge	2,000	520	1,971
total	**392,957**	**39,822**	**∼270k**

Table 1: CARVE split sizes. Held-out splits are capped at fixed sizes with paper-exclusive assignment (seed-deterministic). Zero paper or figure overlap exists across all six split pairs.

Stage E: Verified Quality Control. A final deterministic pass re-evaluates the criteria from Stage C. The multimodal value check now strictly requires at least one evidence unit to be grounded in the figure. If the VLM fails to establish visual grounding, the item is rejected.

Stage F: Global Deduplication and Assembly. Verified items are collected across all papers, and duplicate questions are filtered out to ensure dataset-wide uniqueness. The final dataset is split by paper into train, dev, test, and challenge sets (see Table 1). That final challenge split is not i.i.d with the others, but heuristically chosen to be more challenging, drawn from questions tagged by the drafter with "mechanism", "anomaly analysis", "synthesis", or "multi-hop reasoning"; or which involve at least five claims.

3.3 Intrinsic Dataset Quality

We measure CARVE's intrinsic properties against eight existing VQA datasets, including the two closest sibling sci-figure-VQA datasets (ArXivQA, VeriSciQA), using identical metric definitions (Table 2). CARVE uniquely combines three properties: **(i)** a prior-free answer distribution (majority-answer ceiling 0.0% vs. 25.7–29.0% for the MCQ sibling sets and 27–36% for the MCQ benchmarks); **(ii)** a rich free-form answer space (median 392 characters and 18.6-bit answer entropy vs. a 1-character single-letter answer at 2.0–3.9 bits of entropy for every MCQ comparator, including the otherwise diverse VeriSciQA); **(iii)** an almost-saturating unique-answer fraction (0.996 vs. at most 0.105 for any MCQ set). VeriSciQA reaches a duplicate-question rate of 0.2% via DeepSeek-v3 generation but the answer space remains constrained to four

Dataset	N	Maj	Uniq	H	Dup-Q
Free-form sci-figure VQA					
CARVE (ours)	389k	**.000**	**.996**	**18.6**	**.000**
CharXiv-r	1k	.057	.643	8.4	.000
ChartQA	2.5k	.022	.639	10.1	.016
Multiple-choice sci-figure VQA					
ArXivQA (sibling)	100k	.290	.105	3.9	.125
VeriSciQA (sibling)	20k	.257	.000	2.0	.002
AI2D	3.1k	.269	.001	2.0	.072
ScienceQA	2.0k	.360	.003	1.9	.641
MMMU	1.1k	.270	.059	2.7	.020
Other large-scale VQA					
VQAv2	214k	.190	.065	7.4	.620
PlotQA	1.2M	.154	.203	9.6	.677

Table 2: Intrinsic quality comparison. **Maj**: majority-answer accuracy ceiling (no-model prior). **Uniq**: unique-answer fraction. **H**: answer entropy (bits). **Dup-Q**: exact duplicate-question rate. Sibling sci-figure-VQA datasets ArXivQA (Li et al., 2024) and VeriSciQA (Li et al., 2025) both inherit the MCQ 4-letter answer space, capping their entropy at 2 bits and their majority-answer ceiling at the per-option floor. CARVE is the only dataset that is simultaneously prior-free, answer-rich, and non-repeating.

letters; CARVE keeps the question-side diversity *and* extends the answer space by approximately five orders of magnitude (4 unique answers in VeriSciQA versus 386k unique answers in CARVE-train). We verify zero cross-dataset contamination between CARVE and CharXiv-reasoning (Wang et al., 2024): the two corpora draw from disjoint arXiv eras and share no source papers.

4 Pipeline-Stage Validation

Complementary to the previous section is whether the pipeline filters are over-exclusive, e.g., mistakenly throwing away items which can actually be answered with the figure. We address that question with a held-out vision-aware judge that was not used at any stage of the pipeline, and report formal tests of two falsifiable claims about the design.

Validation at a glance. On 5,000-item samples of each rejection pool, a held-out vision judge confirms 94.5–97.2% of Stage C/D/E rejects are figure-unanswerable; a second cross-judge (Gemini-2.5-flash) agrees with the first on Stage C to within 2 points (96.6% vs. 94.5%, binary agreement 95.9%). Stage F deduplication drops have an $18.5\times$ higher clearly-answerable rate than Stage E rejects ($p \approx 0$). The remainder of this section reports the per-stage rates and the two tests in full.

ArXivQA *Multiple choice, single-pass*

Q: What is the trend of the blue line in the first panel of the figure as the value of log d increases?
MC Answers:
 (a) It remains constant throughout.
 (b) It increases.
 (c) **It decreases.**
 (d) It shows a cyclical pattern.

VeriSciQA *Multiple choice, text-first verify*

Q: In the extended phase shown in the figure, what is the relationship between the even-odd (ln $\delta^{\{e\text{-}o\}}$) and odd-even (ln $\delta^{\{o\text{-}e\}}$) level spacings?
MC Answers:
 (a) The odd-even level spacing is always larger
 (b) They are identical
 (c) The even-odd level spacing oscillates while the odd-even level spacing remains constant
 (d) **There is a gap between them**

CARVE (ours) *Free-form, text-first verify*

Q: Based on the tensor representation in the figure, calculate the total mass (sum of counts) for the subtensor defined by users {Alice, Bob}, pages {A, B}, and date {May-29}.
Answer: The total mass is 19. This is the sum of the values in the highlighted 2x2 block of the tensor: Alice/A (4) + Alice/B (5) + Bob/A (7) + Bob/B (3) = 19.

Figure 2: **Single-sample comparison of CARVE against the two closest arXiv-grounded sci-figure VQA datasets, ArXivQA (Li et al., 2024) and VeriSciQA (Li et al., 2025).** All three corpora are built from arXiv papers and ground questions in scientific figures. Both siblings restrict the answer space to four letters {A,B,C,D} (2 bits of entropy); their typical question form is a single-bit trend or categorical relationship. CARVE emits free-form answers (mean 18.6 bits of entropy, median 392 characters) that articulate the figure's specific quantitative content. CARVE shares the text-first-then-image-verify construction style with VeriSciQA; the answer space is the differentiation.

Held-out judge. We re-score samples of each rejection pool with Qwen3.6-35B-A3B-FP8, a multimodal mixture-of-experts model independent of the LLMs used at Stages A, B, and D. The judge receives the figure image, the question, and the gold reference answer, and returns a 0–3 score: 0 (unanswerable from the figure alone), 1 (ambiguous), 2 (mostly answerable), 3 (clearly answerable). We sample 5,000 train-paper rejects per stage for Stage C and Stage D, all 32,651 train-paper rejects for Stage E, and all 30,139 train-paper deduplication drops for Stage F.

Per-stage agreement. Table 3 reports the score distribution per stage. Stages C, D, and E reject items with 94.5%, 95.0%, and 97.2% score=0 rates respectively; only 1.2–1.8% of each rejection pool clears the score=3 threshold.

Claim 1: Stage C is a quality filter (cross-judge). Stage C is the largest filter (358,090 train-paper rejects, 4.2× Stage E's pool size) and the most consequential test of the design. We cross-validate the Stage C 5,000-item sample with a second judge, Gemini-2.5-flash, under the identical rubric, and recover **96.6%** score=0 (4,788/4,959 valid; 95% CI [96.07, 97.03]). Binary agreement (score=0 vs. ≥1) between Qwen3.6 and Gemini on the 4,949 joint items is **95.9%**.

Stage	Pool	N	s=0	s=3
C reject (mm-value)	358,090	5,000	**94.5**	1.6
D loss (VLM-missing)	88,795	5,000	**95.0**	1.2
E reject (post-verify QC)	24,955	32,651	**97.2**	1.8
Stage F dedup drop	30,171	30,139	61.8	**33.2**

Table 3: Held-out vision judge (Qwen3.6-35B-A3B-FP8) score distribution per rejection pool. **Pool**: total train-paper items the stage rejects. **N**: sampled. **s=0**: figure-unanswerable rate (%); higher means the filter is well-calibrated. **s=3**: clearly-answerable rate (%); lower means the filter is not over-zealous. Stage F's high s=3 rate is expected because it removes redundancy, not low quality.

Claim 2: Stage D losses are quality-correlated, not random noise. A natural concern is that Stage D losses might be random parser or network failures rather than quality-driven drops. We test this with a two-proportion z-test on the score=0 rates of Stage C explicit rejects and Stage D losses: Stage C 94.69% (4724/4989; 95% CI [94.03, 95.28]), Stage D 95.32% (4749/4982; 95% CI [94.70, 95.88]), $z=-1.46$, $p=0.146$ (two-sided). The two pools are statistically indistinguishable; Stage D losses look identical to items rejected by an explicit quality check, which supports treating them as quality-correlated rather than noise.

	AI2D	SciQA	ChQA	MMMU	ChXiv
3B-Inst	78.0	82.0	84.0	48.6	33.5
3B-CARVE	78.4	81.3	83.2	48.0	34.8
Δ	+0.4	−0.7	−0.8	−0.6	**+1.3**
7B-Inst	81.6	87.3	86.8	51.9	40.6
7B-CARVE	81.7	87.6	87.3	52.3	44.5
Δ	+0.1	+0.3	+0.6	+0.4	**+3.9**

Table 4: Downstream transfer: Qwen2.5-VL Instruct vs. CARVE. ChQA = ChartQA (format-aware regraded). ChXiv = CharXiv-reasoning (local-judge graded). All under the forced-terse protocol.

	AI2D	SciQA	ChQA	MMMU	ChXiv
Δ (1B)	−3.2	−4.0	−3.6	+1.4	**+0.8**
Δ (2B)	−1.4	−5.1	−2.8	+1.0	**+1.7**
Δ (8B)	−1.7	−0.7	−1.7	−1.2	**+0.2**

Table 5: Cross-family transfer deltas: InternVL3 Instruct-NoCoT vs. CARVE. ChartQA cells are format-aware regraded.

Model	Size	Test	Chal.
Zero-shot (not trained on CARVE)			
InternVL3	1B	38.1	42.1
Qwen2-VL-2B-Inst	2B	39.0	40.2
InternVL3	2B	42.0	44.4
Qwen2.5-VL-3B-Inst	3B	51.9	51.7
InternVL3	8B	52.4	54.0
Qwen2.5-VL-7B-Inst	7B	**60.7**	59.6
CARVE-finetuned (in-domain)			
InternVL3-CARVE	1B	41.8	47.9
InternVL3-CARVE	2B	53.7	57.3
Qwen2.5-VL-CARVE	3B	59.8	58.9
InternVL3-CARVE	8B	65.0	65.4
Qwen2.5-VL-CARVE	7B	**66.7**	**65.8**
Proprietary (zero-shot)			
GPT-4o-mini	–	61.0	62.6
Gemini-2.5-flash	–	75.4	74.1

Table 6: In-domain held-out benchmark (partial-credit 0–100, local judge). *Chal.* = challenge split.

Reading. The held-out judge agrees with Stages C, D, and E on 94–97% of their rejected items, and an independent second vision judge confirms Stage C's rate to within 2 points.

5 Experimental Setup

We fine-tune five models across two families using the standard LoRA recipe (Hu et al., 2022; Zheng et al., 2024): Qwen2.5-VL (Bai et al., 2025) at 3B and 7B parameters, and InternVL3 (Zhu et al., 2025) at 1B, 2B, and 8B. All models are trained for 2 epochs on the full 388k-item CARVE train split using rank-8 attention-only adapters.

For evaluation, models are tested on five established transfer benchmarks (AI2D, ScienceQA, ChartQA, MMMU, and CharXiv-reasoning) using a uniform *forced-terse* system prompt to prevent answer-format differences from confounding results. We also evaluate in-domain on the CARVE test (1,000 items) and challenge (2,000 items) splits. All free-form grading uses a single self-hosted judge (Qwen2.5-32B-Instruct-AWQ) on a partial-credit 0–100 rubric for CARVE and a binary 0/1 rubric for CharXiv.

6 Results and Analysis

6.1 Downstream Transfer (Qwen2.5-VL)

Table 4 presents transfer results for Qwen2.5-VL. CARVE finetuning preserves general competence across all four non-target benchmarks (all deltas within ±0.8 points) while delivering a meaningful gain on the in-domain transfer benchmark CharXiv-r: +3.9 at 7B and +1.3 at 3B.

6.2 Cross-Family Transfer (InternVL3)

To test whether the CARVE signal generalizes beyond the Qwen family, we apply the identical LoRA recipe to InternVL3 at 1B, 2B, and 8B (Table 5).

InternVL3-CARVE shows measurable but bounded transfer regressions on MCQ benchmarks (3–5 points at 1B/2B, within ±1.7 at 8B), while consistently gaining on CharXiv-r. We identify two distinct mechanisms behind the regressions. First, ChartQA losses are predominantly matcher-format leakage: CARVE-trained models append the chart's natural unit suffix (e.g., %), which the default matcher penalizes asymmetrically, and a format-aware regrade recovers 7–9 points at 1B/2B. Second, AI2D, ScienceQA, and MMMU losses are where CARVE genuinely picks incorrect multiple-choice responses.

6.3 In-Domain Benchmark

Table 6 shows all sub-10B models on CARVE's held-out splits, plus two proprietary anchors graded by the same local judge.

Key findings. (**1**) The zero-shot rows form a clean monotonic capability curve (1B → 7B); the best zero-shot score is approximately 60/100, leaving approximately 40 points of headroom that could potentially be saturated. (**2**) Test and challenge scores are comparable within a model. (**3**) In-domain CARVE lifts are positive across

Configuration	Test	Chal.
Gemini-2.5-flash *(with figure)*	**79.3**	**78.0**
− figure; keep caption + paragraphs	29.7	26.0
− figure; keep question only	2.4	2.3
Δ figure vs. caption+context	+49.7	+52.0
Δ figure vs. question only	+76.9	+75.7

Table 7: Within-model self-ablation of Gemini-2.5-flash on the held-out splits. Removing the figure (while keeping caption and paper paragraphs that cite the figure—exactly the text the Stage B drafter saw) collapses scores by approximately 50 points; removing all context leaves under 3 points. Judge is Qwen3.6-35B-A3B-FP8 (vision-aware), identical to Table 6.

Training data	CharXiv-r	Δ
Qwen2.5-VL-7B-Instruct	40.6	—
+ VeriSciQA-5k (reported)	—	+1.70
+ CARVE-5k (this work)	43.0	+**2.4**
+ CARVE-388k (Table 4)	44.5	+3.9

Table 8: Matched-scale lift on CharXiv-reasoning. Same base model, same LoRA recipe, varying only the training corpus. At identical 5,000-item scale CARVE-5k exceeds VeriSciQA's reported lift by 0.7 points. The remaining gap to CARVE-388k is the volume contribution.

both families: Qwen2.5-VL gains +7.9 / +7.2 (test/challenge) at 3B and +6.0 / +6.2 at 7B; InternVL3 shows large, monotonically growing lift (+3.7 / +5.8 at 1B, +11.7 / +12.9 at 2B, +12.6 / +11.4 at 8B). InternVL3 models in our setting can still learn well from synthetic answers generated by a Qwen model. **(4)** Both Qwen-7B-CARVE (65.8) and InternVL3-8B-CARVE (65.4) clear GPT-4o-mini (62.6) on the challenge split by ∼3 points, while remaining ∼9 points below Gemini-2.5-flash (74.1).

6.4 Text-Only Ablation: does CARVE require the figures?

To verify that CARVE items genuinely require the figure rather than being recoverable from the source paper's text, we ablate Gemini-2.5-flash—the strongest off-the-shelf model in Table 6—by removing its image access while keeping the same Qwen3.6-35B-A3B-FP8 vision-aware judge used for every row of Table 6. Two text-only configurations: **q-only** sees only the question; **q+cap+ctx** additionally sees the figure caption and the source paper paragraphs that cite the figure—exactly the text that the Stage B drafter consumed.

Reading. Even granted the caption *and* every paragraph of the source paper that cites the figure, a frontier text-only configuration of Gemini-2.5-flash scores approximately 30/100 on test and 26/100 on challenge—approximately 33–40 points below the in-domain CARVE-finetuned 7–8B models and approximately 50 points below the same model with the figure. The within-model drop from 79.3 to 29.7 is a clean self-ablation under a single judge, so there is no generator/judge bias confound. The +3 to +6 lift from q-only to q+cap+ctx isolates the small marginal value of the surrounding text; the bulk of the signal is the figure.

6.5 Matched-Scale Comparison vs. Concurrent Work

The headline +3.9 lift on Qwen2.5-VL-7B (Table 4) trains on the full 388,957-item CARVE-train. To control for scale and isolate the per-item signal, we compare against VeriSciQA's (Li et al., 2025) reported +1.70 CharXiv-r lift on the same base model with a 5,000-item finetune set. We train Qwen2.5-VL-7B on a random 5,000-item subsample of CARVE-train under the identical LoRA recipe (rank 8, $\alpha=16$, attention projections, 2 epochs, forced-terse evaluation, same judge).

CARVE-5k yields +**2.4** on CharXiv-r (40.6 → 43.0), exceeding VeriSciQA's reported +1.70 by 0.7 points at identical scale and base model (Table 8). The matched comparison isolates a per-item signal advantage from the pipeline itself, separate from the aggregate-volume contribution: CARVE's 5k subsample already exceeds the lift from a same-size sibling corpus generated with a much stronger LLM (DeepSeek-v3 vs. our Qwen3-4B drafter).

6.6 Paraphrase Robustness

A natural concern with any finetuned model is whether the lift reflects figure-grounded reasoning or absorption of surface phrasing patterns from the training distribution. To test this we sample 500 items from CARVE-test, generate 3 paraphrases per item with a held-out LLM rewriter that preserves meaning while varying syntax and lexical choices, and evaluate both Qwen2.5-VL-7B-Instruct and the CARVE-finetuned counterpart on all 4 phrasings of each item under the same Qwen3.6-35B-A3B-FP8 vision-aware judge used throughout §6.3. Per-item consistency is the fraction of phrasings the model answers correctly.

CARVE finetuning raises mean per-item accuracy by +9.3 points and *simultaneously* raises the

Model	mean	all-4	$\geq$3-of-4
Qwen2.5-VL-7B-Inst	65.3	41.4	60.4
Qwen2.5-VL-7B-CARVE	**74.6**	**54.2**	**72.4**
Δ	+9.3	+**12.8**	+12.0

Table 9: Paraphrase consistency on 500 CARVE-test items $\times$ 4 phrasings. **mean**: average per-paraphrase correctness; **all-4**: items correct on every paraphrase; $\geq$**3-of-4**: items correct on at least three. Stability rises faster than mean accuracy.

all-4-paraphrases-stable rate by $+12.8$ points (Table 9). A model picking up phrasing-specific cues would gain mean accuracy without becoming more paraphrase-stable; the observed pattern is consistent with the model reading the figure and producing the same answer across syntactic variants of the same question.

7 Conclusion

We introduce CARVE, a 392,957-item scientific-figure VQA corpus drawn from approximately 40,000 arXiv papers. By replacing the standard single-pass VLM generation with a structured, multi-phase pipeline that strictly decouples text-only drafting from image-required verification, we eliminate the text-prior shortcuts that plague existing large-scale datasets. Our post-hoc audit confirms the rigor of this pipeline: 94–97% of items rejected by our automated filters are independently judged as figure-unanswerable by held-out vision models, demonstrating that CARVE enforces visual necessity at scale.

The resulting dataset is completely free of multiple-choice constraints, featuring a 0.0% majority-answer ceiling and 18.6-bit answer entropy. Fine-tuning on CARVE drives substantial performance gains across multiple open-source VLMs, yielding $+6$ to $+13$ point lifts on our in-domain challenge split and $+3.9$ points on the held-out CharXiv-reasoning benchmark at 7B scale. Ultimately, CARVE demonstrates that shifting from multiple-choice formats to training-scale, free-form visual data is a highly effective paradigm for teaching VLMs rigorous scientific comprehension.

8 Limitations

We identify the following limitations that should accompany any claims about CARVE, which also serve as direct avenues for future work:

Question-stem templating. Approximately 92.6% of CARVE questions begin with "Based on the provided. . .", an artifact of the fixed generation prompt. While question *phrasing* is highly templated, question *identity* is not: zero questions are duplicated across the 389k-item dataset. A paraphrase-diversification pass is straightforward future work.

Sub-10B scope. All reported numbers exclude 32B-class subjects because the local judge (Qwen2.5-32B-Instruct-AWQ) shares their base parameter class. Whether CARVE's benefits saturate above 10B is left to future work with a parameter-disjoint judge.

Judge validation. The local judge is validated to ± 0.02 against GPT-4o-mini on CharXiv-r's binary rubric, but the CARVE partial-credit 0–10 rubric is *not yet human-validated*. Relative cross-model rankings are robust (judge and rubric held fixed), but absolute score calibration is provisional. A human-agreement spot-check is a necessary pre-camera-ready step.

Visual resolution. All CARVE checkpoints use modest visual resolution ($\sim$300–700 image tokens). Whether higher-resolution inputs raise the ceiling is an untested lever held fixed for a clean comparison.

Family-dependent transfer. Qwen2.5-VL preserves general competence under CARVE finetuning ($\leq \pm 0.8$ on all transfer benchmarks at $\leq$7B). InternVL3 shows bounded regressions (3–5 points at 1B/2B, $\leq$1.7 at 8B), attributable to real MCQ content drift under attention-only LoRA at low rank. Higher-rank LoRA and mixed-format training are natural mitigations.

Construction compute and licensing. The CARVE pipeline runs entirely on self-hosted open-source models served via vLLM (Kwon et al., 2023): a text-only LLM (Qwen3-4B-Instruct-2507) drives Stages A and B, a vision-language model (Qwen3.5-9B) drives Stage D, and a separate text-only LLM (Qwen2.5-32B-Instruct-AWQ) drives evaluation grading and the held-out validation in §4. No proprietary VLM or LLM API was used at any stage of construction or downstream evaluation. The released corpus and per-stage rejection pools are unencumbered by per-call licensing constraints, the same pipeline is reproducible on

local hardware with comparable open-source models, and the total open-source compute footprint for CARVE construction plus the five sub-10B LoRA finetunes (§5) fits within a few hundred GPU-hours of A100/H200-class compute.

9 AI Assistance

AI is integral to the creation of CARVE. AI has been extensively used in the design and implementation of the pipeline and in the writing of this paper, but all substantive content originates from the authors.

References

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, and 1 others. 2025. Qwen2.5-VL technical report. *arXiv preprint arXiv:2502.13923*.

Nishant Balepur, Rachel Rudinger, and Jordan Lee Boyd-Graber. 2025. Which of these best describes multiple choice evaluation with llms? a) forced b) flawed c) fixable d) all of the above. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3394–3418.

Ekaterina Borisova, Nikolas Rauscher, and Georg Rehm. 2025. SciVQA 2025: Overview of the first scientific visual question answering shared task. In *Proceedings of the Fifth Workshop on Scholarly Document Processing (SDP 2025)*, pages 182–210.

Haodong Duan, Xinyu Fang, Junming Yang, Xiangyu Zhao, Yuxuan Qiao, Mo Li, Amit Agarwal, Zhe Chen, Lin Chen, Yuan Liu, and 1 others. 2024. VLMEvalKit: An open-source toolkit for evaluating large multi-modality models. In *Proceedings of the 32nd ACM International Conference on Multimedia*.

Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daumé Iii, and Kate Crawford. 2021. Datasheets for datasets. *Communications of the ACM*, 64(12):86–92.

Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. 2017. Making the V in VQA matter: Elevating the role of image understanding in visual question answering. In *CVPR*.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *ICLR*.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. 2016. A diagram is worth a dozen images. In *ECCV*.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*.

Lei Li, Yuqi Wang, Runxin Xu, Peiyi Wang, Xiachong Feng, Lingpeng Kong, and Qi Liu. 2024. Multimodal arxiv: A dataset for improving scientific comprehension of large vision-language models. *Preprint*, arXiv:2403.00231.

Yuyi Li, Daoyuan Chen, Zhen Wang, Yutong Lu, and Yaliang Li. 2025. Verisciqa: An auto-verified dataset for scientific visual question answering. *arXiv preprint arXiv:2511.19899*.

Zhenwen Liang, Kehan Guo, Gang Liu, Taicheng Guo, Yujun Zhou, Tianyu Yang, Jiajun Jiao, Renjie Pi, Jipeng Zhang, and Xiangliang Zhang. 2024. SceMQA: A scientific college entrance level multimodal question answering benchmark. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 109–119.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916.

Pan Lu, Swaroop Mishra, Tony Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. 2022. Learn to explain: Multimodal reasoning via thought chains for science question answering. In *The 36th Conference on Neural Information Processing Systems (NeurIPS)*.

Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. 2022. ChartQA: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of ACL*.

Nitesh Methani, Pritha Ganguly, Mitesh M. Khapra, and Pratyush Kumar. 2020. PlotQA: Reasoning over scientific plots. In *WACV*.

Aishik Nagar, Shantanu Jaiswal, and Cheston Tan. 2024. Zero-shot visual reasoning by vision-language models: Benchmarking and analysis. In *2024 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8.

Shraman Pramanick, Rama Chellappa, and Subhashini Venugopalan. 2024. SPIQA: A dataset for multimodal question answering on scientific papers. *Advances in Neural Information Processing Systems*, 37:118807–118833.

Nimrod Shabtay, Felipe Maia Polo, Sivan Doveh, Wei Lin, M. Jehanzeb Mirza, Leshem Chosen, Mikhail Yurochkin, Yuekai Sun, Assaf Arbelle, Leonid Karlinsky, and Raja Giryes. 2024. LiveXiv: A multi-modal live benchmark based on arxiv papers content. *arXiv preprint arXiv:2410.10783*.

Zirui Wang, Mengzhou Xia, Luxi He, Howard Chen, Yitao Liu, Richard Zhu, Kaiqu Liang, Xindi Wu, Haotian Liu, Sadhika Malladi, and 1 others. 2024. Charxiv: Charting gaps in realistic chart understanding in multimodal llms. *Advances in Neural Information Processing Systems*, 37:113569–113697.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, and 1 others. 2024. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9556–9567.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyan Luo, Zhangchi Feng, and Yongqiang Ma. 2024. LlamaFactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of ACL: System Demonstrations*.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, and 1 others. 2025. InternVL3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*.

A Generation Prompts and Quality Checks

We reproduce the full prompts used in each LLM/VLM stage of the CARVE pipeline, together with the deterministic repair-and-QC passes applied immediately after the LLM stages. All prompts are transcribed verbatim from `src/processing/claim_extraction.py` (Stage A) and `src/models/prompts.py` (Stages B and D); QC pseudocode mirrors `src/benchmarking/qc.py`. Template fields shown as {name} are filled at runtime.

A.1 Stage A: Claim Extraction

System prompt.

```
You extract atomic scientific
claims from paper context.
Use only the local context
text provided.  Do not invent
claims, do not merge unrelated
statements, and do not use the
figure or caption.
```

User prompt.

```
Extract atomic claims from the
LOCAL_CONTEXT only.

Rules:
- Output valid JSON only.
- Return a JSON array.
- Each object must contain
exactly these fields:
"text", "claim_type",
"source_index",
"source_sentence"
- Allowed claim_type values:
observation, comparison,
interpretation, mechanism,
conclusion.
- Keep claims short, atomic, and
entailed by the context.
- source_index must match the
[Context i] block number when
multiple blocks are given.
- Context block numbering is
1-based:  [Context 1], [Context
2], ...
- source_sentence must quote
or closely paraphrase the
originating sentence from
LOCAL_CONTEXT.
- Ignore boilerplate, citations,
and statements unrelated to
figure evidence.

LOCAL_CONTEXT:
{context_text}

OPTIONAL_METADATA:
{metadata_text}

Return JSON only.
```

A.2 Stage B: Text-Only Benchmark Drafting

System prompt.

```
You are an expert
benchmark-construction system
for multimodal scientific
reasoning.  You are drafting one
structured benchmark item using
only the figure caption and
local paper context.  The figure
image is NOT provided.  Do not
claim direct visual inspection.
Keep every claim grounded in the
text you were given or clearly
mark it as scientific prior or
unsupported.
```

User prompt (full).

```
Construct exactly {num_items}
distinct benchmark draft
items for free-form scientific
reasoning.

Return a JSON array of benchmark
items.
Each item must ask a
meaningfully different question
about the same figure context.
Do not produce near-duplicate
questions, near-duplicate
answers, or repeated evidence
decompositions.
Prefer diversity across
question_type and reasoning
target when the text supports
it.

Important constraints:
- The figure image is not
available in this stage.
- Generate the question using
only the caption and local
context.
- Do not say you inspected the
figure directly.
- Do not use grounding_source
values 'figure_only',
'figure_plus_caption', or
'figure_plus_context'.
- Use 'caption_only',
'local_context_only',
'caption_plus_context',
'scientific_prior', or
'unsupported'.
- Produce a useful future
multimodal benchmark draft, but
keep the draft honest about its
text-only evidence.
- Output valid JSON only.

CAPTION:
{caption}

LOCAL_CONTEXT:
{local_context_text}

NORMALIZED_CLAIMS:
{claims_text}

OPTIONAL_METADATA:
{metadata_text}
```

```
Requirements:
- Use the normalized claims as
the primary textual evidence
inventory.
- Every evidence unit must
include explicit claim
provenance in 'notes', citing
one or more supporting claim
ids such as 'claims: c1' or
'claims: c2,c4'.
- Do not leave claim provenance
implicit or omit it for
convenience.
- Write exactly {num_items}
free-form question(s) in total.
- Write exactly {num_items}
concise free-form reference
answer(s) in total.
- Include latent_reasoning_plan,
evidence_units,
dependency_graph, leakage_audit,
quality_control, and
final_status.
- Keep evidence units atomic.
- Make parent_units and
dependency_graph consistent.
- Make importance_weight values
sum to 1.0.
- If uncertainty exists, mark it
explicitly.

Use this JSON schema exactly:
```json
{schema_text}
```

When generating multiple items,
return a JSON array where every
element matches the schema
above.
```

A.3 Stage C: Deterministic Repair and QC for Text-Only Drafts

After Stage B, every draft is passed through a deterministic repair-and-QC pass implemented in `src/benchmarking/qc.py` (`repair_text_only_benchmark_draft`). The pass first normalizes the schema and then runs seven structural checks; four of these are designated *critical* and any failure causes the draft to be rejected.

Critical checks. The set of critical checks is `CRITICAL_QUALITY_CONTROL_KEYS` = (`groundedness_check`, `multimodal_value_check`, `hallucination_check`, `language_check`).

Repair and QC pipeline.

1. **Schema normalization.** The repair pass deep-merges the model output into the canonical `draft_benchmark_v1` template, fills

any missing `benchmark_id`, `question`, `question_type`, `difficulty_level`, `multimodal_requirement_level`, and `provenance` fields, and replaces invalid enum values with inferred defaults. For each evidence unit it canonicalizes `unit_id`, `unit_type`, `support_strength`, `ambiguity_level`, `scientific_confidence`, `importance_level` (clipped to `[1,5]`), and renormalizes `importance_weights` to sum to 1.0. Critically, any unit whose `grounding_source` matches a "figure*" value (`figure_only`, `figure_plus_caption`, or `figure_plus_context`) is downgraded to the best available text-only grounding (`caption_plus_context` when both are present, otherwise `caption_only`, `local_context_only`, or `unsupported`); the unit's `notes` is appended with "Grounding was downgraded during text-only QC because the figure image was not available."

2. **Groundedness check (critical).** The check fails if either (a) the draft has no evidence units after repair, or (b) at least one evidence unit has `grounding_source = unsupported` and `importance_level` ≥ 4. Otherwise the check passes with the explanation "All critical units are grounded in caption/context, scientific prior, or marked uncertainty."

3. **Multimodal-value check (critical).** A heuristic `visual_necessity` score is recomputed from the question type and unit count: it is set to `medium` when `question_type` is in {`comparison`, `multi_hop_reasoning`, `anomaly_analysis`, `synthesis`} or when the draft contains at least four evidence units, and otherwise `low`. The check fails when `visual_necessity == low`, i.e. the draft appears answerable from text alone with weak future visual value.

4. **Hallucination check (critical).** Fails if any evidence unit has `grounding_source = unsupported` *and* `importance_level` ≥ 4. (Low-importance unsupported claims are permitted

because they may be used as distractors or be downgraded by Stage D.)

5. **Language check (critical).** The repair pass concatenates the question and reference answer and runs `detect_language` (a lightweight n-gram detector). The check passes when the detected code is in {`en`, `unknown`} and fails otherwise. This is the primary filter that removed non-English residue in the shards-derived pool.

6. **Non-critical checks.** Three additional checks (`nontriviality_check`, `dependency_coherence_check`, `ambiguity_handling_check`) are recorded for diagnostics but do not by themselves cause rejection. `nontriviality_check` fails when the question has fewer than six tokens or only a single evidence unit. `dependency_coherence_check` fails if validation still reports `parent_units` or `dependency_graph` errors after repair. `ambiguity_handling_check` fails when no uncertainty notes are attached to the reasoning plan; in that case the repair pass auto-fills a generic note that the figure has not yet been reviewed.

7. **Leakage audit re-computation.** The repair pass recomputes `leakage_audit` from scratch: `caption_leakage_risk` is `high` when every unit is `caption_only`; `context_leakage_risk` is `high` when every unit is `local_context_only`; otherwise both are `medium` (mixed text) or `low`. `lexical_overlap_risk` uses the Jaccard-style token overlap between the reference answer and the caption+context: `high` when overlap ≥ 0.80, `medium` when ≥ 0.55, else `low`.

8. **Final status.** If any critical check failed, the draft is marked `rejected` with an explanation enumerating the failing keys, and `provenance.review_status` is set to `rejected`. Otherwise the draft is marked `accepted_with_ambiguity` with `review_status = needs_figure_review`, deferring the figure grounding decision to Stage D.

A.4 Stage D: Figure Verification

System prompt.

```
You are a scientific benchmark
verification system.  You are
given a figure image, its
caption, local paper context,
extracted textual claims, and a
text-only draft benchmark item.
Your job is to revise the draft
into a figure-verified benchmark
item.  Only mark claims as
figure-grounded when the image
actually supports them.
```

User prompt (full).

```
Verify and revise the benchmark
draft against the provided
FIGURE image.

Rules:
- The figure image IS available
in this stage.
- Use the draft item only as a
starting point, not as ground
truth.
- Preserve the draft
'benchmark_id' exactly.
- Preserve the draft question
and question intent unless the
question is clearly invalid,
ungrounded, or too shallow.
- If you revise the question,
keep the same scientific target
and explain the repair in
provenance.notes.
- Check observations against the
image.
- Convert draft-only grounding
to figure-aware grounding when
justified.
- Do not use
'caption_plus_context' in the
final output.
- Allowed grounding_source
values are 'figure_only',
'caption_only',
'local_context_only',
'figure_plus_caption',
'figure_plus_context',
'scientific_prior', and
'unsupported'.
- Set 'schema_version' to
'verified_benchmark_v1'.
- Set provenance.construction_stage
to 'figure_verified'.
- Set provenance.review_status
to 'figure_verified' unless the
item must be rejected.
- Include 'figure' in
provenance.source_modalities.
- Keep accepted_paraphrases
lists.
- Output valid JSON only.
```

Leakage audit rubric (embedded in the user prompt).

```
HOW TO SCORE leakage_audit
(be critical - most items have
NON-zero risk):

caption_leakage_risk:
high   - reference_answer
paraphrases or copies the
caption verbatim;
the question can be answered
from caption alone.
medium - reference_answer reuses
substantive phrasing from the
caption,
but adds figure-grounded detail
or interpretation.
low    - reference_answer relies
on figure content not present in
the caption.

context_leakage_risk: same
scale, but vs. LOCAL_CONTEXT
paragraphs.

lexical_overlap_risk:
high   - >60% of
reference_answer n-grams appear
verbatim in caption+context.
medium - 30%-60% overlap.
low    - <30% overlap.

visual_necessity:
high   - answering REQUIRES
inspecting the figure (reads off
axis values,
counts elements, identifies
spatial relationships, compares
regions).
medium - figure helps
disambiguate but the answer
is largely derivable from text.
low    - answer is fully
derivable from caption+context;
the figure is decorative
for this question.

Do NOT default everything
to {low, low, low, high}.
If the reference_answer
reuses caption phrasing, mark
caption_leakage_risk medium
or high.  If the question
could be answered without the
figure, visual_necessity is not
high.  Provide a 1-2 sentence
audit_notes explaining your
scoring.
```

Context block. The user prompt closes with four context blocks and the verified schema:

```
CAPTION:
{caption}

LOCAL_CONTEXT:
{local_context_text}

NORMALIZED_CLAIMS:
{claim_text}

DRAFT_ITEM:
```json
{draft_text}
```
```

```
OPTIONAL_METADATA:
{metadata_text}

Return JSON in exactly this
verified schema:
```json
{verified_schema_text}
```
```

A.5 Stage E: Deterministic Repair and QC for Verified Items

After Stage D, every verified item is passed through a second deterministic repair-and-QC pass (`repair_verified_benchmark_item`). It runs the same seven structural checks as Stage C, but the *groundedness* criterion is upgraded to require at least one figure-grounded evidence unit and the LLM-emitted leakage audit is trusted when its values are in vocabulary.

Repair and QC pipeline.

1. **Schema normalization.** The pass deep-merges the model output into the `verified_benchmark_v1` template and inherits any missing top-level fields (`benchmark_id`, `question`, `question_type`, `difficulty_level`, `multimodal_requirement_level`, `reference_answer`, `semantic_matching_rules`, `quality_control`) from the Stage B draft. `provenance.construction_stage` is forced to `figure_verified`, `review_status` is normalized to one of {`figure_verified`, `human_adjudicated`, `rejected`}, and `figure` is unconditionally inserted into `provenance.source_modalities`. Each unit's `grounding_source` is mapped through `_repair_verified_grounding_source`: `caption_plus_context` values from the draft are upgraded to `figure_plus_context`; out-of-vocabulary or empty values become `unsupported`. This is the step that promotes a successfully-verified draft into the figure-grounded vocabulary required for Stage E.

2. **Groundedness check (critical, upgraded).** As in Stage C, the check fails if any unit has `grounding_source = unsupported` with `importance_level` ≥ 4.

3. **Multimodal-value check (critical, upgraded).** This is the Stage E-specific change: the check passes *iff at least one evidence unit has* `grounding_source` *in {`figure_only`, `figure_plus_caption`, `figure_plus_context`}.* Otherwise the check fails with the explanation "Verification did not establish figure-grounded evidence." This is the gate that enforces the figure-grounding requirement for the verified pool, and the dominant source of Stage E rejections.

4. **Hallucination check (critical).** Same as Stage C: fails if any unit has `grounding_source = unsupported` with `importance_level` ≥ 4.

5. **Language check (critical).** Same as Stage C: runs `detect_language` on the question and reference answer; fails when the detected code is not in {`en`, `unknown`}.

6. **Non-critical checks.** `nontriviality_check`, `dependency_coherence_check`, and `ambiguity_handling_check` are computed exactly as in Stage C, except that `ambiguity_handling_check` always passes after verification (uncertainty is allowed to be empty when the figure resolves the question).

7. **Leakage audit (trusted-with-fallback).** Unlike Stage C, the Stage E pass *preserves* the LLM-emitted leakage audit when its values are in the valid vocabulary {`low`, `medium`, `high`}, and only falls back to a heuristic when the LLM omitted a field or returned an out-of-vocabulary value. The heuristic fallback is: `caption_leakage_risk` and `context_leakage_risk` default to `low` when at least one unit is figure-supported and otherwise to `medium`; `lexical_overlap_risk` defaults to `low`; `visual_necessity` defaults to `high` when at least one unit is figure-supported and otherwise to the Stage-C heuristic. This change prevents the uniform (`low`, `low`, `low`, `high`) distribution that appeared when the leakage audit was

always recomputed from grounding sources alone.

8. **Final status.** If any critical check failed, the verified item is marked `rejected` with an explanation listing the failing keys, and `provenance.review_status` becomes `rejected`. Otherwise, the item is marked `accepted_with_ambiguity` when any evidence unit has `ambiguity_level` $\neq$ `low`, `scientific_confidence == low`, or the reasoning plan still contains uncertainty notes; otherwise it is marked `accepted`. Only items in the `accepted` or `accepted_with_ambiguity` buckets enter the published CARVE pool.

B Dataset Composition: Distributional Breakdowns

This appendix reports the distributional shape of CARVE-train along four axes: items per source paper, items per source figure, image-file format, and arXiv release month. All counts are computed directly from the released training file (`partialcredit_verified_train.json`, 388,957 items; the full corpus of 392,957 items adds the 1,000/1,000/2,000 dev/test/challenge splits as reported in Table 1). The `benchmark_id` field for each item is of the form `<arxiv_id>_fig_<n>_q<m>`, which we parse to recover the source paper, the source figure within that paper, and the question index; two items fail to parse and are excluded from the per-paper / per-figure histograms below. The slight difference between the 38,884 unique parsed paper IDs in this appendix and the 37,730 figure quoted in Table 1 reflects a handful of papers whose canonical arXiv ID in the split-assignment metadata differs by formatting (zero-padding) from the form embedded in `benchmark_id`; the distributional summaries below are unaffected.

B.1 Items per Paper

CARVE-train draws on 38,884 unique arXiv source papers; each paper contributes a median of 6 items and a mean of 10.0 items (Table 10). The distribution is right-skewed: the 25th and 75th percentiles span 3 to 12 items, the 90th percentile is at 22 items, and a long tail extends to a single paper contributing 572 items (a survey-style paper

Statistic	Value
Unique papers (CARVE-train)	38,884
Min items per paper	1
25th percentile	3
Median	6
75th percentile	12
90th percentile	22
Max items per paper	572
Mean items per paper	10.0

Table 10: Items-per-paper summary statistics for CARVE-train.

Items / paper	Papers	Share
1	3,813	9.8%
2	4,255	10.9%
3–5	10,007	25.7%
6–10	9,609	24.7%
11–20	6,968	17.9%
21–50	3,558	9.2%
51–100	546	1.4%
> 100	128	0.3%
total	38,884	100.0%

Table 11: Distribution of CARVE-train papers by item count. No paper exceeds the corpus by more than three orders of magnitude, and 89% of papers contribute 20 or fewer items.

with many distinct figures, each producing multiple verified questions). The bucketed breakdown in Table 11 shows that 9.8% of papers contribute exactly one item, 50.4% contribute between 3 and 10 items (the densest band), and only 1.7% of papers contribute more than 50 items. The figure-level upstream cap means even heavy-contributor papers produce at most a bounded number of items per figure (Section B.2), so individual papers do not dominate the corpus.

B.2 Items per Figure

CARVE-train covers 271,052 unique figures across the 38,884 source papers, for a mean of 7.0 figures per paper. Within each figure, the pipeline draws at most two surviving items: 56.5% of figures contribute a single item and the remaining 43.5% contribute exactly two (Table 12). The hard cap at two items per figure is a deliberate Stage B configuration choice that bounds intra- figure redundancy; the further drop from the configured ceiling is attributable to Stage C/D/E rejections and Stage F deduplication, which remove duplicate or text-answerable variants of the second item more often than the first.

Items / figure	Figures	Share
1	153,149	56.5%
2	117,903	43.5%
total	271,052	100.0%

Table 12: Distribution of CARVE-train figures by item count. Stage B draws at most two items per figure by configuration; the residual single-item majority reflects downstream filtering of the second draft.

Format	Image refs	Share
`.png`	365,916	94.1%
`.jpg`	21,733	5.6%
`.jpeg`	1,306	0.3%
total	388,955	100.0%

Table 13: CARVE-train image-file format breakdown. Two items omit an `images` field and are excluded from the total. Vector sources (SVG, EPS) are rasterized to PNG at ingest.

B.3 Image-File Format

The figure images bundled with CARVE-train are stored in three raster formats (Table 13). PNG dominates at 94.1% of item-level image references; the upstream arXiv source distribution and the PDF-figure extraction pipeline both default to PNG. JPEG-family variants (`.jpg` and `.jpeg`) account for the remaining 5.9%, all of which originate from author-supplied bitmap figures. No vector formats appear at the item level: SVG and EPS sources are rasterized to PNG during pipeline ingestion to support uniform VLM processing across stages.

B.4 arXiv Release Month

The 38,884 source papers cluster in two arXiv release windows (Table 14). The first window (Jan–June 2018) contributes 97.1% of items (377,784 items from ~37,500 papers across six consecutive monthly snapshots); the second window (January 2024) contributes the remaining 2.9% (11,171 items). The 2018 window is the production-scale build, drawn from the dense arXiv LaTeX-bundle dumps that CARVE was originally constructed against; the January 2024 papers are a contamination-control supplement, drawn from the post-cutoff arXiv stream after January 2024 to provide papers that no proprietary model in the comparison set could have seen during pre-training. CARVE-train therefore mixes a dense historical window with a small recent window. CharXiv-reasoning, our primary held-out trans-

Year-Month	Items	Share
2018-01	57,916	14.9%
2018-02	58,443	15.0%
2018-03	59,335	15.3%
2018-04	64,369	16.5%
2018-05	71,924	18.5%
2018-06	65,797	16.9%
2024-01	11,171	2.9%
total	388,955	100.0%

Table 14: CARVE-train item counts by arXiv release month, recovered from the `YYMM` prefix of each item's arXiv identifier. Two items with unparseable identifiers are excluded; row shares sum to 100.0% up to rounding.

fer target (Wang et al., 2024), draws from a disjoint arXiv era and shares zero source papers with CARVE-train (§3.3).

B.5 arXiv Discipline Coverage

We resolve each paper's primary arXiv subject class against the OAI metadata snapshot (5.2 GB JSONL, 99.86% ID-match against the 36,743 unique papers that contribute items to any split) and group top-level archives into coarse domains (Table 15).

The challenge split is notably more CS-heavy (46.2% CS papers vs. 29.4% in the full corpus); the challenge-priority filter (metadata: question types in {`mechanism`, `anomaly_analysis`, `synthesis`, `multi_hop_reasoning`}) selects for items that require synthesizing across panels or steps, which the Stage-B drafter emits more often on CS / ML diagrams than on observational physics plots. The compositional consequence is that challenge-split benchmark numbers should be read as informative about *algorithmic-figure* understanding more than about cross-domain generalization.

B.6 Question Type, Difficulty, and Multimodal Requirement

The Stage-B drafter assigns each item three categorical attributes, which are preserved through Stages C–E and survive into the released splits. We report the distributions on test (1,000 items, 99.6% recovered) and challenge (2,000 items, 99.9% recovered); distributions on dev mirror test within ± 2 pp on every cell.

B.7 Summary

CARVE-train's composition is structurally bounded along every axis we report: no paper dominates (max 572 items, 99.6% of papers under

Domain	Papers	%
Computer Science (cs. *)	10,799	29.4
Astrophysics (astro-ph)	5,164	14.1
Condensed Matter (cond-mat)	4,660	12.7
Mathematics (math. *)	3,497	9.5
Physics, general (physics. *)	3,324	9.0
High-Energy Physics (hep-*)	2,786	7.6
Statistics (stat. *)	1,714	4.7
Quantum Physics (quant-ph)	1,650	4.5
Gen. Relativity (gr-qc)	773	2.1
EE / Signal Proc. (eess. *)	624	1.7
Nuclear Physics (nucl-*)	622	1.7
Quantitative Biology (q-bio. *)	440	1.2
Nonlinear Sciences (nlin. *)	231	0.6
Quantitative Finance (q-fin. *)	182	0.5
Mathematical Physics (math-ph)	153	0.4
Economics (econ. *)	71	0.2
unknown (no OAI match)	53	0.1
Total	36,743	100.0

Table 15: Coverage of arXiv disciplines across the 36,743 unique papers that contribute at least one item to CARVE (test+challenge+dev+train). Categories are arXiv top-level archive prefixes; sub-categories (e.g., `cs.CV`, `physics.flu-dyn`) are merged into their parent. Each paper's *primary* archive (first listed in OAI metadata) is counted exactly once. Aggregated, physics-flavored archives (astro-ph, cond-mat, physics, hep-*, gr-qc, quant-ph, nucl-*, nlin, math-ph) account for $\approx 53\%$ of the corpus; computer science alone is the largest single archive at 29.4%.

Question type	Test (%)	Challenge (%)
Observation	82.4	85.6
Interpretation	8.1	6.5
Comparison	7.5	5.2
Mechanism	1.4	2.7
Conclusion	0.5	0.2

Table 16: Item-type distribution on the released splits. *Observation* items ask the model to read off a value or label from the figure; *interpretation* items ask what a visual pattern means; *comparison* items contrast two or more figure elements; *mechanism* items ask how a depicted process works; *conclusion* items ask the model to draw a takeaway from the figure. CARVE skews heavily toward observation ($\sim 85\%$), a known property of caption-anchored construction: the Stage-A claim inventory most often surfaces single-fact observations from the caption, and the Stage-B drafter consequently produces matching question forms.

Difficulty	Test (%)	Challenge (%)
Easy	26.7	37.4
Medium	73.2	62.6
Hard	0.1	0.1

Table 17: Self-reported difficulty (Stage-B-emitted, Stage-D-verified) on the released splits. The Stage-B drafter is conservative in assigning `hard`: under 0.1% of items receive it. Challenge's "harder" character does *not* come from this field; it derives from (i) paper-exclusive split assignment (challenge papers contribute no items to train) and (ii) the question-type priority filter described in §B.5 (mechanism / anomaly / synthesis / multi-hop reasoning).

100 items), no figure produces more than two items by construction, image formats reduce to a single rasterization choice (PNG-dominant), and the source-paper time window is explicitly split between a dense production build and a smaller contamination-controlled supplement. None of these distributional facts conflict with the headline counts in the main paper (Table 1); they describe the shape of the 388,957 items that headline summary aggregates.

C Datasheet for CARVE

We follow the datasheet template of Gebru et al. (2021). Section headers match the template; answers are intentionally terse and reuse the quantities established in the main paper.

C.1 Motivation

For what purpose was the dataset created? CARVE was created to fill an empty operating point in scientific-figure VQA: training scale (hundreds of thousands of items) combined with a free-form answer space and audited figure-required grounding. Existing options force a tradeoff be-

tween scale and rigor—auto-generated million-item corpora saturate at 15–36% majority-answer ceilings with 62–68% duplicate questions, while human-curated benchmarks at 1–3k items are too small for finetuning (§2, Table 2). CARVE targets the intersection of those two regimes.

Who created the dataset? The authors of this paper. Author identities and affiliations are withheld during anonymous review and will be disclosed in the camera-ready version.

Who funded the dataset? Funding sources are withheld during anonymous review and will be disclosed in the camera-ready version. All construction compute was satisfied by self-hosted open-source models on local A100/H200-class GPUs; no proprietary VLM or LLM API was used at any stage of construction (§8).

Multimodal requirement	Test (%)	Challenge (%)
figure_context_fusion	85.0	85.9
figure_caption_fusion	15.0	14.1

Table 18: Stage-D-assigned multimodal-evidence requirement on the released splits. *figure_context_fusion* items require the figure plus surrounding paper text; *figure_caption_fusion* items require the figure plus its caption. The text-only ablation in §6.4 shows that for both classes, removing the figure collapses scores by ≈ 50 points, confirming the figure-required label is load-bearing.

C.2 Composition

What do instances represent? Each instance is a single scientific-figure VQA item consisting of a free-form question, a free-form reference answer, the figure image, identifiers that locate the figure within its source arXiv paper, and provenance metadata describing the construction pipeline's leakage-audit scores and the kept evidence units.

How many instances are there in total? 392,957 items derived from 39,822 arXiv papers and approximately 270,000 unique figures (Table 1).

Does the dataset contain all possible instances or is it a sample? A sample. The pool of figure-bearing arXiv papers is much larger than 40k. The 40k papers were drawn from a fixed snapshot of arXiv LaTeX source bundles and processed through the five-stage pipeline; only items that survived all filters were retained. The pipeline rejects 358,090 text-answerable drafts at Stage C, 88,795 at Stage D, 24,955 at Stage E, and 30,171 at Stage F deduplication (Table 3). The retained corpus is therefore not a representative cross-section of arXiv figures but a quality-filtered subset biased toward items that a held-out vision judge would call figure-answerable (§4).

What data does each instance consist of?

- `question`: free-form English question.

- `answer`: free-form reference answer (mean 18.6 bits of entropy, median 392 characters; Table 2).

- `grading_query`: judge-formatted prompt used by the local Qwen2.5-32B-Instruct-AWQ judge under the 0–10 partial-credit rubric (§5).

- `figure_path`: relative path to the figure image bundled with the release.

- `arxiv_id`: source arXiv identifier of the paper from which the figure was extracted.

- `figure_id` and `paper_id`: stable internal identifiers used for the paper-exclusive split assignment.

- Provenance fields: per-item leakage-audit scores (`caption_leakage_risk`, `context_leakage_risk`, `lexical_overlap`, `visual_necessity`), the kept evidence units with grounding-source labels, and the QC status (`accepted` or `accepted_with_ambiguity`).

The construction pipeline also retains the figure caption and the local context paragraphs used at Stages A and B; these are released alongside the items so that downstream users can reconstruct the text-only ablation in Table 7.

Is there a label or target associated with each instance? Yes: the free-form reference answer is the target. Grading is performed by a self-hosted judge LLM under a documented rubric rather than by exact string match (§5).

Is any information missing from individual instances? Items emitted under the `accepted_with_ambiguity` status carry one or more partially-grounded evidence units; these are retained because at least one evidence unit is figure-grounded but the verifier flagged residual ambiguity in another. Users who require fully unambiguous items can filter on `qc_status == accepted`. No required field is missing from any released item.

Are relationships between individual instances made explicit? Yes. Each item exposes its `arxiv_id`, `paper_id`, and `figure_id`; multiple items may share a figure (the pipeline emits one or more items per figure), and multiple figures share a paper. The splits enforce paper-exclusive assignment, so two items in distinct splits never share a source paper.

Are there recommended data splits? Yes (Table 1): train (388,957 items / 37,730 papers), dev (1,000 / 804), test (1,000 / 768), challenge

(2,000 / 520). Splits are paper-exclusive and seed-deterministic; zero paper or figure overlap exists across all six split pairs. The held-out test and challenge splits are MD5-pinned in VLMEvalKit's `vlmeval/dataset/carve.py` so that downstream evaluations against those splits are reproducible.

Are there any errors, sources of noise, or redundancies? Yes, and they are quantified rather than hidden:

- **Filter false negatives (over-rejection).** The independent Qwen3.6-35B-A3B-FP8 judge agrees with the pipeline on 94–97% of each stage's rejected items (Table 3); the remaining 1.2–1.8% are score=3 items that the held-out judge calls clearly answerable. We do not attempt to recover these into the released corpus.

- **Filter false positives (over-acceptance).** The pipeline's audit (§4) measures rejection-pool quality, not keep-pool quality; the rate at which incorrectly-grounded items survive every filter is bounded by the leakage-audit scores recorded per item but is not given a single headline number in this release.

- **Stem templating.** Approximately 92.6% of questions begin "Based on the provided. . . ", an artifact of the fixed Stage B prompt (§8). Question *identity* is not duplicated (0.0% duplicate-question rate, Table 2).

- **Hard-tail errors.** The qualitative analysis in §D documents shared-misperception failures and dense-grid counting failures on the challenge split that both Instruct and CARVE-finetuned 7B checkpoints exhibit.

Is the dataset self-contained, or does it link to or otherwise rely on external resources? Self-contained at release time for the held-out splits: the OSF deposit ships the test and challenge figures alongside their JSONL records, plus a 5k-item clean train sample. The full 389k train split, by contrast, ships only the JSONL records plus `arxiv_id`; full-train users reconstitute the figure images from a matching arXiv source snapshot or download the per-figure images from the planned HuggingFace mirror. arXiv itself is the canonical external dependency and is expected to remain available; the per-paper `arxiv_id` is the stable handle.

Does the dataset contain confidential, sensitive, or offensive content? Source data is arXiv preprints, which pass arXiv's own moderation prior to public posting. The released corpus has not been independently audited for personally identifiable information, biased language, or offensive content beyond what arXiv's preprint moderation already applies. Scientific figures occasionally include human faces (e.g., facial-recognition or medical-imaging papers); the qualitative example in §D explicitly references a face-bearing figure. Users who require an additional content audit should run one before deploying CARVE in downstream products.

C.3 Collection Process

How was the data acquired? The source data is arXiv LaTeX source bundles. The pipeline extracts figures, their captions, and the body-text paragraphs that reference each figure ("local context") from each paper's source archive (§3).

What mechanisms or procedures were used to collect the data? A five-stage open-source pipeline reproduced in Figure **??**:

1. **Stage A:** Qwen3-4B-Instruct-2507 extracts atomic scientific claims from local context.

2. **Stage B:** The same text LLM drafts a structured (question, answer, evidence) tuple from caption, context, and claims, with no figure access.

3. **Stage C:** A deterministic repair pass enforces text-only grounding labels and four quality checks (groundedness, multimodal value, hallucination, language).

4. **Stage D:** Qwen3.5-9B (vision-language) receives the figure image and re-scores the draft, reassigning grounding-source labels and completing a leakage audit.

5. **Stage E:** A second deterministic pass requires at least one figure-grounded evidence unit to accept the item.

Survivors enter Stage F (cross-pool deduplication and paper-exclusive split assignment). The full prompts are reproduced in Appendix A.

Was the dataset sampled or did it use the full population? A sampled population of approximately 40,000 arXiv papers drawn from a fixed source snapshot, processed in full through the

pipeline. The acceptance rate from drafts to released items is approximately 392k / 892k ≈ 44% across all four filter stages combined (Table 3 reports the four rejection pools).

Who collected the data? The authors, using fully automated self-hosted pipelines. No crowdworkers or paid annotators were involved in the construction of train, dev, test, or challenge splits. Held-out validation in §4 uses two independent automated judges (Qwen3.6-35B-A3B-FP8 self-hosted and Gemini-2.5-flash via API).

Over what timeframe was the data collected? The arXiv snapshot used as input was collected during 2024 (specific cutoff withheld during anonymous review for non-deanonymizing reasons of contamination control against CharXiv-r). The pipeline runs and the held-out validation in §4 were executed across 2025–2026. The pipeline is deterministic given fixed seeds and frozen model checkpoints; rerunning it on the same snapshot reproduces the same item set.

Were any ethical-review processes conducted? The construction relies on publicly posted arXiv preprints and on self-hosted open-source models. No human-subjects approval is applicable. No paid annotation labour was used. No personal data was collected from users.

C.4 Preprocessing / Cleaning / Labeling

Was any preprocessing or cleaning of the data done? Yes; cleaning is the pipeline. The five stages are described in §3 and audited in §4. Additionally:

- Question text is deduplicated case-insensitively with punctuation stripped before split assignment.

- Schema-invalid items (missing required fields, malformed JSON) are dropped before split assignment.

- Held-out splits enforce paper-exclusive assignment under a fixed seed, with zero overlap across the six split pairs verified post-hoc.

Was the raw data saved in addition to the cleaned data? Yes. The per-stage rejection pools used in §4 (Stage C reject, Stage D loss, Stage E reject, Stage F dedup drop) are retained alongside the released items and ship with their per-item judge scores so that the validation tables can be

reproduced. The original arXiv source bundles are not re-redistributed (arXiv remains the canonical source); the per-item `arxiv_id` lets a user fetch them.

Is the software used to preprocess / clean / label the data available? Yes. The pipeline source, the held-out test and challenge splits, the LoRA recipe (§5), and the VLMEvalKit integration (Duan et al., 2024) are released alongside the corpus. The construction pipeline depends on vLLM (Kwon et al., 2023) and the self-hosted Qwen3-4B-Instruct-2507 and Qwen3.5-9B checkpoints; both are fetched at standard HuggingFace identifiers.

C.5 Uses

Has the dataset been used for any tasks already? Yes. This paper uses CARVE for LoRA finetuning of Qwen2.5-VL (3B, 7B) and InternVL3 (1B, 2B, 8B), with downstream transfer evaluation on AI2D, ScienceQA, ChartQA, MMMU, and CharXiv-reasoning, and in-domain evaluation on the held-out test and challenge splits (§6). Pipeline-stage rejection pools are used for the held-out validation in §4.

Is there a repository that links to any or all papers or systems that use the dataset? At review time, no; the OSF deposit and any future HuggingFace mirror linked from the camera-ready paper are the canonical entry points and will track downstream uses.

What (other) tasks could the dataset be used for?

- Scientific-figure VQA finetuning and evaluation beyond the model families reported here.

- Filter-calibration meta-research: the released rejection pools plus the held-out judge scores support follow-up work on automated quality filtering of VQA construction pipelines.

- Caption-figure leakage measurement: the per-item leakage audit scores plus the text-only ablation protocol (Table 7) provide a reusable testbed.

- Caption-grounded retrieval and figure-citation alignment, by treating the (`question`, `caption`, `figure`) triple as a retrieval signal.

Is there anything about the composition of the dataset or the way it was collected and preprocessed / cleaned / labeled that might impact future uses? Two items merit explicit caution:

- **Question-stem templating.** 92.6% of questions share a fixed opening (§8); models fine-tuned on CARVE may overfit the stem regardless of the question identity beneath it. Downstream users targeting stem-diverse downstream evaluation should plan for paraphrase augmentation.

- **Domain bias.** The 40k-paper sample is drawn from arXiv, so physics, computer science, mathematics, and quantitative biology are over-represented relative to the natural sciences taken as a whole. Conclusions drawn on CARVE do not automatically transfer to scientific figures in chemistry journals, clinical case reports, or earth-science publications outside arXiv.

Are there tasks for which the dataset should not be used?

- Production grading of student or clinical exams: the partial-credit judge rubric is not yet human-validated (§8) and is calibrated to relative rankings, not absolute scores.

- Identity-sensitive applications targeting people depicted in figures: faces appear occasionally in source figures, and the corpus has not been audited for personally identifiable information.

- Commercial repurposing of bundled figures without checking each paper's individual licence: figure copyright follows the per-paper arXiv submission licence, which varies (see §C.6).

C.6 Distribution

Will the dataset be distributed to third parties outside of the entity on behalf of which the dataset was created? Yes. The corpus is released for unrestricted academic use under the licensing terms in §C.6.

How will the dataset be distributed? For peer review: an anonymous OSF deposit containing the held-out test and challenge splits, a 5k-item clean sample of train, and the referenced figures (deposit tarball $\approx$ 821 MB compressed). The view-only OSF URL is at https://osf.io/nwtqe/?view_only= 4c1b3784094c4189970122a4a49ff194. For post-acceptance public release: the full 392,957-item corpus on HuggingFace Datasets, plus a release tag on the pipeline source repository. Held-out test and challenge splits are MD5-pinned in VLMEvalKit's vlmeval/dataset/carve.py, so reproducibility against the held-out numbers in Tables 6–7 is independent of any single hosting service.

When will the dataset be distributed? Held-out splits and a 5k-item train sample are available via the anonymous OSF deposit during peer review. Full distribution (full train split, public mirror, version tagging) follows acceptance.

Will the dataset be distributed under a copyright or other intellectual property (IP) licence, and/or under applicable terms of use (ToU)? The dataset metadata—the (question, answer, grading_query, per-item provenance) tuple authored by this work—is released under **CC-BY-4.0**. The bundled figure images inherit the licence under which each source arXiv paper was submitted; this is most commonly arXiv's non-exclusive licence to distribute, but a subset of papers submit under CC-BY, CC-BY-SA, CC-BY-NC, or arXiv's perpetual-licence option. The per-item arxiv_id field is exposed so that downstream users can verify the source licence of any figure they intend to redistribute. Users wishing to repackage CARVE figures into a derived dataset are responsible for checking each arxiv_id's submission licence before doing so.

Have any third parties imposed IP-based or other restrictions on the data associated with the instances? arXiv's terms of use govern the redistribution of figure images; we comply with arXiv's bulk-access policy for the source snapshot used in construction. No additional third-party restrictions apply to the authored metadata.

Do any export controls or other regulatory restrictions apply? None known.

C.7 Maintenance

Who will be supporting / hosting / maintaining the dataset? The authors. Specific maintainer affiliations and the canonical hosting endpoint will

be disclosed in the camera-ready paper. The MD5-pinned held-out splits are a hosting-agnostic anchor: any future mirror that matches the pinned hashes is a valid distribution endpoint regardless of which service it sits behind.

How can the owner / curator / manager of the dataset be contacted? Anonymous during review. The camera-ready version will list a corresponding author email and the GitHub Issues page on the pipeline source repository as the two contact channels.

Is there an erratum? No erratum exists at the time of submission. If errors are found, they will be tracked on the pipeline source repository's Issues page and referenced from the HuggingFace dataset card.

Will the dataset be updated? The 392,957-item v1 corpus and the MD5-pinned held-out splits are treated as a frozen artefact—downstream comparability requires that v1 not silently change. Future versions (e.g., a paraphrase-diversified v2 addressing the 92.6% stem-templating limitation in §8) will ship as additive, separately-tagged releases that do not overwrite v1.

If the dataset relates to people, are there applicable limits on the retention of the data associated with the instances? Not applicable: instances describe scientific figures, not people. Where figures incidentally depict human faces, the underlying arXiv paper is the canonical source and any takedown request should be routed to arXiv in the first instance; we will mirror takedowns in CARVE upon notice.

Will older versions of the dataset continue to be supported / hosted / maintained? Yes; the held-out v1 splits remain pinned and available indefinitely through any mirror matching the published MD5 hashes. Pipeline source tags marking v1 will not be deleted.

If others want to extend / augment / build on / contribute to the dataset, is there a mechanism for them to do so? Yes. The pipeline source is released alongside the corpus; downstream contributors can rerun it on additional arXiv snapshots, on alternative text/vision-language backbones, or with modified Stage B and Stage D prompts. The recommended path is a separately-tagged release (e.g., CARVE-paraphrase) that links back to the

canonical v1 rather than a modification of v1 in place, preserving the comparability of published benchmark numbers.

D Qualitative Examples

We provide 15 representative single-column example cards (Figures 3–16), pre-rendered with the full question text, gold reference answer, both Instruct and CARVE predictions with their partial-credit judge scores, and a one-line "Read" commentary. Cards are bucketed into five filtered sets selected by score disagreement on CARVE-challenge between 7B-CARVE and 7B-Instruct (both Qwen2.5-VL); counts in parentheses are the size of the filtered set, and examples are sampled within each set.

D.1 In-Domain Wins on CARVE-challenge (91 / 2,000 with CARVE ≥ 8, Inst ≤ 3)

Q: Based on the provided plot for the m-ELL-SS method, what is the approximate peak value of the estimated process (black line) and the corresponding x-axis coordinate?

Gold: Peak at x ≈ 6, y ≈ 11.

Inst: ✗ [3/10] Peak ≈ 25, x ≈ 6.

CARVE: ✓ [9/10] Peak at x ≈ 5.5, y ≈ 11.

Read: Instruct mis-reads y-axis (25 vs 11); CARVE reads it correctly.

Figure 3: In-domain win: chart value reading. Instruct mis-reads the y-axis (25 vs. 11); CARVE reads the chart correctly.

W I N

Q: Based on the provided figure, identify the distinct color-coded trajectories representing the different network models and describe their spatial relationship.

Gold: The figure displays three distinct trajectories colored red, green, and blue. The red trajectory is located on the left side, the green trajectory is in the center, and the blue trajectory is on the right side. The green and red trajectories intersect at a single point, while the blue trajectory remains separate from the others.

Inst: ✗ [4/10] The figure shows three distinct color-coded trajectories: red, green, and blue. The red trajectory is the shortest and appears to be the most direct, while the blue trajectory is the longest and most

CARVE: ✓ [9/10] The figure displays three distinct trajectories: a red trajectory on the left, a green trajectory in the center, and a blue trajectory on the right. The red and green trajectories intersect at a centr

Read: CARVE recovers the figure-grounded answer (9/10) where Instruct (4/10) missed it.

Figure 4: In-domain win: conclusion reversal. Both models read the legend; only CARVE follows the figure evidence.

WIN

Q: Based on the provided plot, how does the solid curve (representing the Stefan-Boltzmann law) compare to the dashed curve (linear approximation) across the temperature range of 275 K to 375 K?

Gold: Nearly indistinguishable; only slight deviation.

Inst: ✗ [3/10] Solid curve consistently above dashed curve.

CARVE: ✓ [9/10] Nearly indistinguishable; linear approximation is a very close fit.

Read: Instruct invents a non-existent relationship; CARVE reports the overlap.

Figure 5: In-domain win: curve identity. Instruct invents a non-existent relationship; CARVE reports the actual overlap.

WIN

Q: Based on the simulation result shown in the bar chart, what is the probability value associated with the single outcome observed for the classical bit 0 (cbit0)?

Gold: The probability value is 1.000. The bar chart in Figure (b) shows a single orange bar reaching the maximum value on the y-axis, which corresponds to a probability of 1.000 for the outcome where the classical bit is 0.

Inst: ✗ [0/10] 0.000

CARVE: ✓ [10/10] The probability value associated with the single outcome observed for the classical bit 0 (cbit0) is 1.000.

Read: CARVE recovers the figure-grounded answer (10/10) where Instruct (0/10) missed it.

Figure 6: Cross-family win on CARVE-challenge: InternVL3-CARVE corrects a quantitative reading the Instruct base mis-extracted.

Q: Based on the visual evidence in the figure, what specific type of scene analysis is being demonstrated, and what are the primary dynamic elements visible?

Gold: The figure demonstrates a highway scene analysis. The primary dynamic elements visible are multiple vehicles traveling in lanes on a multi-lane road, with a solid barrier on the right and vegetation on the left.

Inst: ✗ [3/10] Traffic flow analysis

CARVE: ✓ [6/10] The figure demonstrates a scene analysis of a highway or road environment. The primary dynamic elements visible are multiple vehicles (cars) traveling in a single lane, with some vehicles appearing to

Read: CARVE recovers the figure-grounded answer (6/10) where Instruct (3/10) missed it.

Figure 7: Cross-family win: InternVL3-CARVE identifies a specific figure element the base misclassifies.

| Batch-size | 5 Dimension | | | | |
| | Time (Sec) | | | Speed-up w.r.t. GLPK | |
	GLPK	BLPG	BLPG-SM	Vs BLPG	Vs BLPG-SM
1	0.0000	0.0000	0.0000	0.00	0.00
50	0.0010	0.0000	0.0002	0.00	5.00
100	0.0012	0.0001	0.0011	12.00	1.09
500	0.0094	0.0010	0.0021	9.40	4.48
1000	0.0163	0.0030	0.0033	5.43	4.94
1500	0.0310	0.0090	0.0040	3.44	7.75
2000	0.0410	0.0050	0.0060	8.20	6.83
5000	0.1040	0.0130	0.0140	8.00	7.43
10000	0.1660	0.0250	0.0250	6.64	6.64
20000	0.3170	0.0490	0.0480	6.47	6.60
50000	0.7750	0.1220	0.1200	6.35	6.46
100000	1.6630	0.2420	0.2390	6.87	6.96

Q: Based on the provided table for 5-dimensional LPs, what is the minimum batch size required for the BLPG solver to outperform the GLPK solver, and what is the corresponding speed-up factor?

Gold: The minimum batch size required for BLPG to outperform GLPK in 5-dimensional LPs is 100. At this batch size, the speed-up factor of BLPG relative to GLPK is 12.00.

Inst: ✗ [0/10] 50, 5.00

CARVE: ✓ [10/10] The minimum batch size required for BLPG to outperform GLPK is 100. At this batch size, the speed-up factor is 12.00.

Read: CARVE recovers the figure-grounded answer (10/10) where Instruct (0/10) missed it.

Figure 8: Cross-family win: directional comparison the base reverses.

Q: For which category of ancestors is the standard deviation of its expected number of ancestors generally greater?

Rubric: Your final answer must be grounded to some text that is explicitly written and relevant to the question in the chart.

Gold: African ancestors

Inst: ✗ [0/1] African

CARVE: ✓ [1/1] African ancestors

Read: CARVE matches the chart's exact text; Instruct's short form fails strict-grounding judge.

Figure 9: CharXiv-r transfer win: CARVE-finetuned model recovers a value the base zero-shot misreads.

Q: In how many plots does config_A have the tallest peak?

Rubric: Your final answer must be an exact integer.

Gold: 2

Inst: ✗ [0/1] 1

CARVE: ✓ [1/1] 2

Figure 10: CharXiv-r transfer win: multi-panel chart with quantitative comparison only the CARVE checkpoint resolves.

Q: In subplot (b), under how many selection strength groups does the point with the highest log_K value also exhibit the highest slope value?

Rubric: Your final answer must be an exact integer.

Gold: 2

Inst: ✗ [0/1] 1

CARVE: ✓ [1/1] 2

Read: Cross-family transfer: CARVE training on Qwen recipe ports to InternVL3.

Figure 11: CharXiv-r transfer win: figure-grounded reading where text-prior shortcuts fail.

Q: What is one change to this ecosystem that would increase the number of mouse?

A: A decrease in grass
B: An increase in the number of snakes
C: Snakes would decrease
D: A decrease in the amount of trees

Gold: B

Inst: ✓ [1/1] B

CARVE: ✗ [0/1] A. A decrease in grass

Read: AI2D source has option-text bleed across B/C/D; gold 'increase snakes' is also biologically counter-intuitive.

Figure 12: MCQ loss: InternVL3-CARVE picks a different letter on an item the Instruct base gets right.

Q: Parabolic-arch influence line — shear at D for P=3 kips at B.

A: −1.84k compr
B: −1.94k compr
C: −1.74k compr

Gold: C (−1.74k compr)

Inst: ✓ [1/1] C

CARVE: ✗ [0/1] B. −1.94k compr

Figure 13: MCQ loss: ScienceQA item where CARVE finetuning shifts the answer letter.

Q: Based on the corner plot for the high-energy model OG, what are the median (μ) and standard deviation (σ) values for the parameter f_γ?

Gold: For the parameter f_γ, the median (μ) is 0.015 and the standard deviation (σ) is 0.004.

Inst: ✓ [10/10] The median (μ) for the parameter f_γ is approximately 0.015, and the standard deviation (σ) is approximately 0.004.

CARVE: ✗ [0/10] The median (μ) is 0.696 and the standard deviation (σ) is 0.223.

Read: Instruct (10/10) reads the figure correctly; CARVE (0/10) hallucinates a different claim.

Figure 14: In-domain loss: CARVE over-attributes a property not present in the figure; Instruct is correct.

Q: Of the left, middle, and right plots, which has the least number of triangles as formed by ridges in the plot of t vs. x along the x=0.5 line?

Rubric: Your final answer must be grounded to some text that is explicitly written and relevant to the question in the chart.

Gold: left

Inst: ✓ [1/1] Left plot

CARVE: ✗ [0/1] right

Figure 15: Transfer loss: CARVE selects the wrong network branch where the base zero-shot is correct.

Q: Based on the provided image, what anatomical view of the brain phantom is depicted?

Gold: Sagittal slice (side-on view).

Inst: ✗ [0/10] Axial view.

CARVE: ✗ [0/10] Axial view.

Read: Shared misperception of a standard medical-imaging view (sagittal vs axial). Both models default to 'axial' regardless of orientation.

Figure 16: Hard-tail item: a dense, multi-element figure where both models share a training-prior default.