ONLINE LAPLACIAN-BASED REPRESENTATION LEARNING IN REINFORCEMENT LEARNING

ABSTRACT

Representation learning plays a crucial role in reinforcement learning, especially in complex environments with high-dimensional and unstructured states. Effective representations can enhance the efficiency of learning algorithms by improving sample efficiency and generalization across tasks. This paper considers the Laplacian-based framework for representation learning, where the eigenvectors of the Laplacian matrix of the underlying transition graph are leveraged to encode meaningful features from raw sensory observations of the states. Despite the promising algorithmic advances in this framework, it remains an open question whether the Laplacian-based representations can be learned online and with theoretical guarantees along with policy learning. To answer this question, we study online Laplacian-based representation learning, where the graph-based representation is updated simultaneously while the policy is updated by the reinforcement learning algorithm. We design an online optimization formulation by introducing the Asymmetric Graph Drawing Objective (AGDO) and provide a theoretical analysis of the convergence of running online projected gradient descent on AGDO under mild assumptions. Specifically, we show that if the policy learning algorithm induces a bounded drift on the policy, running online projected gradient descent on AGDO exhibits ergodic convergence. Our extensive simulation studies empirically validate the guarantees of convergence to the true Laplacian representation. Furthermore, we provide insights into the compatibility of different reinforcement learning algorithms with online representation learning.

1 INTRODUCTION

Representation learning is an important part of machine learning that involves learning compact and useful representations of data. The quality of these representations significantly impacts the performance and efficiency of machine learning algorithms (Bengio et al., 2013). In reinforcement learning (RL), agents often deal with complex environments characterized by high-dimensional and unstructured states. This makes representation learning important for discovering and encoding meaningful features from raw sensory inputs. The main goal of RL is to learn an optimal strategy (policy) that maps each state to an action, aiming to maximize the expected reward based on the dynamics of the environment. Learning a good representation can improve the sample efficiency of value-function approximation algorithms (Farebrother et al., 2023), a major family of RL algorithms, and enhance generalizations across different tasks (Yuan & Lu, 2022). In addition, representation learning has found applications in reward shaping (Wu et al., 2018), learning options with larger coverage (Machado et al., 2017a; Jinnai et al., 2019; Chen et al., 2024), and transfer learning (Gimelfarb et al., 2021; Barreto et al., 2017).

A graph representation is often used to learn a representation, i.e., a low-dimensional embedding, of the states (Mahadevan & Maggioni, 2007; Wu et al., 2018). States of an environment can be viewed as nodes of a graph, and the transition probability between states under a given policy can be viewed as weighted edges between these nodes. States that are closely connected in the graph are expected to have similar representations in the embedding space. One representation that retains this property is the eigenvectors of the graph Laplacian. Formally, the d-eigenvectors of the graph Laplacian corresponding to the d-smallest eigenvalues are used to construct an embedding function that maps a state to a vector in $\mathbb{R}^d$. We refer to those d-eigenvectors as the d-smallest eigenvectors for the remainder of this paper.

Constructing the graph and performing eigendecomposition on the Laplacian is only feasible in the tabular settings where the number of states is small. Therefore, Wu et al. (2018) proposed a scalable method to compute the smallest eigenvectors by solving an unconstrained version of the graph drawing objective (Koren, 2005) which is suitable for large and continuous state-spaces. However, the graph drawing objective does not have a unique minimizer, rather the rotations of the smallest eigenvectors are also its minimizers. To tackle this challenge, Wang et al. (2021) propose the generalized graph drawing objective which breaks the symmetry and only has the smallest eigenvectors as a unique minimizer. Gomez et al. (2023) show that under gradient descent dynamics, the unconstrained version of the generalized graph drawing objective has permutations of the smallest eigenvectors as equilibrium points. They propose the augmented Lagrangian Laplacian objective (ALLO) which has the smallest eigenvectors and the corresponding eigenvalues as the stable equilibrium under stochastic gradient descent-ascent dynamics.

The Laplacian-based representation can be computed or learned for a given policy according to its induced Markov chain. However, in RL the policy updates during the training phase as new data comes in, which will in turn necessitate recomputation of the representation. To avoid this complexity, in practice, the Laplacian-based representation is learned for a uniformly random policy in a pretraining phase and then used throughout training. Nevertheless, that fixed representation may not be effective for the policies encountered during RL. Recently, Klissarov & Machado (2023) showed that learning the representation in an online manner while simultaneously updating the policy can improve exploration and increase the total reward. In Figure 1, we illustrate an example, comparing the representations of a uniform policy and a non-uniform policy, that further underscores the need for adapting the representation. The non-uniform policy shows that some cells, despite being far from the target in terms of Euclidean distance, are actually closer in the embedding space than neighboring cells. This suggests that using the current representation to design rewards could offer a better signal for improving the policy. Klissarov & Machado (2023) proposed online deep Laplacian-based options for temporally extended exploration where a set of policies (also known as options) are trained to select exploratory actions using an estimated Laplacian representation of the current overall policy. They provide an extensive empirical analysis of how learning options while updating the representation increases the received rewards; however, the theoretical analysis of online representation learning while updating the policy has remained an open question.

Figure 1: The Laplacian representation of a uniform policy (left) and a non-uniform policy(right). The color represents the entry corresponding to each state in the 2nd eigenvector of the Laplacian. The bordered cell is the target.

Motivated by that, we design an online optimization formulation by introducing the Asymmetric Graph Drawing Objective (AGDO), a simplified version of ALLO that does not involve dual variables. We prove that the only stable equilibrium for AGDO is the d-smallest eigenvectors under gradient descent dynamics. Furthermore, we establish through theory and experiments that optimizing the online version of AGDO converges to a stationary point under the assumption of bounded drift.

2 LITERATURE REVIEW

In this section, we review existing studies and research directions in representation learning for reinforcement learning, focusing on topics closely linked to this study.

Proto-Value Functions. Mahadevan (2005) introduced proto-value functions, a set of basis functions that are independent of the reward function. These functions are defined as the eigenfunctions of the normalized Laplacian of the graph generated by a random walk over the state space. This representation has been demonstrated to reduce the number of samples required for training linear value function approximators (Mahadevan & Maggioni, 2007). The process of generating the graph

involves collecting samples from the environment and connecting neighboring states with edges. However, this method does not adequately account for the stochastic nature of transitions and requires a discrete state space. In continuous state settings, Mahadevan (2012) proposes using the Nyström method to interpolate the values of eigenfunctions at unseen states based on visited states. Additionally, Xu et al. (2014) suggests enhancing representative state selection by applying K-means clustering to collected samples and constructing a graph from the resulting centroids.

Laplacian Representation Using the Graph Drawing Objective. Wu et al. (2018) formulated a linear operator that represents the graph over the state-space generated by a fixed policy, capturing the stochastic nature of transitions, and is applicable to continuous state spaces. They demonstrated that obtaining the eigenfunctions of the graph Laplacian, typically solved via the graph drawing objective (Koren, 2005), can be achieved through stochastic optimization using collected samples without explicitly constructing the graph. Additionally, they illustrated a method to recover these eigenfunctions up to orthonormal rotation by training a neural network. For precise eigenfunction recovery, Wang et al. (2021) introduced the generalized graph drawing objective, which breaks the symmetry inherent in the traditional graph drawing objective. Despite the constrained generalized objective ensuring the uniqueness of Laplacian eigenfunctions, Gomez et al. (2023) demonstrated that stochastic optimization using the unconstrained objective—employed in neural network training—does not necessarily converge to these eigenfunctions. Consequently, they proposed the augmented Lagrangian Laplacian objective, which exhibits the eigenvectors of the Laplacian as the unique stable equilibrium. Other equilibrium points correspond to permutations of the eigenvectors.

Learning the Laplacian representation with any of these objectives is conducted under a fixed policy, typically a uniformly random policy in practice. Klissarov & Machado (2023) introduced online deep covering eigenoptions, an online algorithm that concurrently learns the Laplacian representation and options (Sutton, 1998), a well-established formulation of temporally extended actions in Markov Decision Processes (MDPs). They demonstrated that the online version of DCEO achieves performance comparable to a two-stage variant of the algorithm, where the representation is learned under a fixed uniform policy.

Successor Features. The deep successor representation, introduced by Kulkarni et al. (2016) as an extension of the successor representation (Dayan, 1993), decomposes the value function into a successor feature function and a reward predictor function. The successor function encodes the discounted expected value of representations of all future states within a given horizon. Leveraging concepts from TD learning and Deep Q-networks (Mnih et al., 2015), both the representation and the successor feature function can be learned simultaneously with neural networks. Successor features have found diverse applications, such as sub-goal states generation in sparse reward environments (Kulkarni et al., 2016), transfer learning (Barreto et al., 2017; Gimelfarb et al., 2021), and options discovery (Machado et al., 2017b; 2023). Notably, Machado et al. (2017b) demonstrated a connection between the eigenvalues and eigenvectors of the successor representation matrix and the eigenvalues and eigenvectors of the normalized Laplacian defined as proto-value functions.

Contrastive Learning in Reinforcement Learning. Contrastive learning is a machine learning method used for learning representations that distinguish between similar and dissimilar pairs of data points using a contrastive loss function. Formally, an encoder is tasked with mapping data points to a latent representation where similar points are closely positioned in the latent space. For instance, Laskin et al. (2020) introduced the contrastive unsupervised representations for reinforcement learning algorithm, where they train an encoder network using a contrastive loss with pairs of images randomly augmented from the same source image. The learned representation is subsequently utilized to train a deep reinforcement learning agent. Furthermore, augmented temporal contrast was developed by Stooke et al. (2021), which involves selecting similar sample pairs from samples that are separated by a short time distance. This approach is closely related to the Laplacian approach to representation learning, as states that are connected in the graph have a higher probability of appearing in consecutive samples than disconnected states.

In this work, we focus on extending the Laplacian-based representation learing, which has been shown in recent literature to be effective in learning options with high coverage Machado et al. (2017a); Jinnai et al. (2019); Klissarov & Machado (2023); Chen et al. (2024), to the online setting. While empirical results, such as those by Klissarov & Machado (2023), have demonstrated that online

representation learning is effective and promising, a thorough theoretical analysis of the convergence and accuracy of these learned representations in the online setting is still lacking. Therefore, our work seeks to address this gap by developing a theoretical framework that ensures the stability and accuracy of Laplacian representations in an online learning context.

3 PRELIMINARIES

In this section, we provide the necessary background to introduce the problem and present the proposed formulation and its theoretical analysis. We begin by introducing Markov decision processes within the context of reinforcement learning. Next, we highlight the closely related, existing methods of learning the Laplacian representation.

Notation We use $\langle v, u \rangle$ to denote the dot product between two vectors v and y. For a vector $\mathbf{x}$, the L_2 norm, denoted $\|\mathbf{x}\|$, is defined as $\|\mathbf{x}\| = \sqrt{\sum_i |x_i|^2}$. The L_2 norm of a matrix, is defined as $\|\mathbf{A}\| = \sup_{\mathbf{x} \neq \mathbf{0}} \frac{\|A\mathbf{x}\|}{\|\mathbf{x}\|}$ and is equivalent to the spectral norm defined as the largest singular value of the matrix. Finally, the L_∞ norm, denoted $\|\mathbf{A}\|_\infty$, is the maximum absolute row sum of the matrix, i.e., $\|\mathbf{A}\|_\infty = \max_i \sum_j |a_{ij}|$.

Reinforcement Learning. In the reinforcement learning setting, an agent interacts with an environment, which is modeled as a Markov decision process (MDP). A reward agnostic MDP is represented by the tuple $(\mathcal{S}, \mathcal{A}, \mathcal{T}, \mu_0)$ where $\mathcal{S}$ is the finite state space, $\mathcal{A}$ is the finite actions space, $\mathcal{T} : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$ is the transition probability, and $\mu_0 \in \Delta(\mathcal{S})$ is the initial state probability distribution. We consider the environment to be reward-agnostic and that the agent has a policy $\pi : \mathcal{S} \rightarrow \Delta(\mathcal{A})$ from which actions are samples each time step. The policy induces a Markov chain from the MDP defined by the transition probability P^π where $P^\pi(s, s') = \mathbf{P}(s_{t+1} = s'|s_t = s, \mathcal{T}, \pi) = \sum_{a \in \mathcal{A}} \pi(a|s)\mathcal{T}(s'|s, a)$. We assume that the induced Markov chain has a unique stationary distribution $\rho^\pi \in \Delta(\mathcal{S})$. We formally define this in Assumption 1.

Laplacian Representation. A graph is defined by a set of nodes $\mathcal{V}$ and an adjacency matrix $W \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|}$. For two nodes ν, ν', $W_{\nu,\nu'}$ is non-zero if and only if there exists an edge from ν to ν'. The Laplacian matrix L is defined as $L = D - W$ where the degree matrix D is a diagonal matrix with $D_{\nu,\nu} = \sum_{j=1}^{|\mathcal{V}|} W_{\nu,j}$. The Laplacian encodes a lot of useful information about the underlying graph. For example, the second to the largest eigenvalue also known as the Fiedler value determines the algebraic connectivity of the graph (Fiedler, 1973).

In the tabular setting, under a fixed policy π, an MDP can be represented as a graph, where $\mathcal{V} = \mathcal{S}$ and the adjacency matrix W^π is defined as $f(P^\pi)$ where f maps P^π to a symmetric matrix. More generally, consider the following formulation given by Wu et al. (2018):

- A Hilbert Space $\mathcal{H}^\pi$ is $\mathbb{R}^{|\mathcal{S}|}$ with the inner product between two elements $u, v \in \mathcal{H}^\pi$ defined as $\langle u, v \rangle_{\mathcal{H}^\pi} = \sum_{s \in \mathcal{S}} u(s)v(s)\rho^\pi(s)$.

- A linear operator $A : \mathcal{H}^\pi \rightarrow \mathcal{H}^\pi$ is defined as $Au(s) = \sum_{s' \in \mathcal{S}} A(s, s')u(s')\rho^\pi(s')$.

- The self adjoint operator $W^\pi : \mathcal{H}^\pi \rightarrow \mathcal{H}^\pi$ is defined as

$$W^\pi(s, s') = \frac{1}{2} \frac{P^\pi(s, s')}{\rho^\pi(s')} + \frac{1}{2} \frac{P^\pi(s', s)}{\rho^\pi(s)} \tag{1}$$

- The Laplacian L^π is defined as $L^\pi = \mathbf{I} - W^\pi$.

- With a slight abuse of notation we define $A_{\rho^\pi} : \left(\mathbb{R}^{|\mathcal{S}|}, \langle ., . \rangle\right) \rightarrow \left(\mathbb{R}^{|\mathcal{S}|}, \langle ., . \rangle\right)$ as a matrix whose entries are defined as $A_{\rho^\pi}(s, s') = A(s, s')\rho^\pi(s')$ for some operator $A : \mathcal{H}^\pi \rightarrow \mathcal{H}^\pi$. Note that for a vector $u \in \mathbb{R}^{|\mathcal{S}|}$ the matrix multiplication $A_{\rho^\pi}u$ is equivalent to Au.

We denote the d-smallest eigenvectors of L^π as $e_1^\pi, e_2^\pi, \ldots, e_d^\pi$. The Laplacian embedding function $\phi^\pi : \mathcal{S} \rightarrow \mathbb{R}^d$ embeds a state s to the d-dimensional vector whose i-th element correspond to the s-th element of e_i^π, i.e. $\phi(s) = [e_1^\pi[s], e_2^\pi[s], \ldots, e_d^\pi[s]]^\intercal$.

Learning the Laplacian Representation. Optimizing the graph drawing objective (GDO) (Koren, 2005) retrieves the smallest d-eigenvectors up to orthonormal rotation. The graph drawing objective is defined as

$$\min_{u \in \mathbb{R}^{d|\mathcal{S}|}} \quad \sum_{i=1}^{d} \langle u_i, L^\pi u_i \rangle; \tag{2}$$
$$\text{s.t.} \quad \langle u_j, u_k \rangle = \delta_{jk}, \qquad 1 \le k \le j \le d,$$

where δ_{jk} is the Kronecker delta. The unconstrained approximation of GDO is defined as

$$\min_{u \in \mathbb{R}^{d|\mathcal{S}|}} \sum_{i=1}^{d} \langle u_i, L^\pi u_i \rangle + b \sum_{j=1}^{d} \sum_{k=1}^{d} \left(\langle u_j, u_k \rangle - \delta_{jk} \right)^2, \tag{3}$$

where b is a hyper-parameter.

One advantage of using the graph drawing objective is that the unconstrained approximation of the graph drawing objective can be optimized by stochastic gradient descent using samples collected from the environment without constructing the graph or the Laplacian (Wu et al., 2018). Formally, if the inner product is defined in terms of ρ^π, the loss can be defined as $\sum_{i=1}^{d} \langle u_i, L^\pi u_i \rangle_{\mathcal{H}^\pi} = \mathbb{E}_{s \sim \rho^\pi, s' \sim P^\pi(\cdot|s)} [\sum_{i=1}^{d} (u_i(s) - u_i(s'))^2]$.

The generalized graph drawing objective proposed by Wang et al. (2021) breaks the symmetry in the graph drawing objective and has the set of the smallest d-eigenvectors as a unique minimizer.

The generalized graph drawing objective (GGDO) is defined as

$$\min_{u \in \mathbb{R}^{d|\mathcal{S}|}} \quad \sum_{i=1}^{d} c_i \langle u_i, L^\pi u_i \rangle \tag{4}$$
$$\text{such that} \quad \langle u_j, u_k \rangle = \delta_{jk}, \qquad 1 \le k \le j \le d$$

and the unconstrained approximation of GGDO is defined as

$$\min_{u \in \mathbb{R}^{d|\mathcal{S}|}} \sum_{i=1}^{d} c_i \langle u_i, L^\pi u_i \rangle + b \sum_{j=1}^{d} \sum_{k=1}^{d} \min(c_j, c_k) \left(\langle u_j, u_k \rangle - \delta_{jk} \right)^2 \tag{5}$$

The unconstrained GGDO is guaranteed to have a unique equilibrium point only in the limit $b \to \infty$. However, for other values, rotations of the smallest d-eigenvectors can still be an equilibrium point. The augmented Lagrangian Laplacian objective (ALLO) suggested by (Gomez et al., 2023) is a dual objective that has a unique stable equilibrium point of the smallest d-eigenvalues and the corresponding smallest d-eigenvectors. Other unstable equilibrium points correspond to permutations of the eigenvectors and eigenvalues. The ALLO is defined as follows

$$\max_{\beta} \min_{u \in \mathbb{R}^{d|\mathcal{S}|}} \sum_{i=1}^{d} \langle u_i, L^\pi u_i \rangle + \sum_{j=1}^{d} \sum_{k=1}^{j} \beta_{jk} \left(\langle u_j, [\![u_k]\!] \rangle - \delta_{jk} \right) + b \sum_{j=1}^{d} \sum_{k=1}^{j} \left(\langle u_j, [\![u_k]\!] \rangle - \delta_{jk} \right)^2 \tag{6}$$

where $[\![.]\!]$ is the stop gradient operator, and whatever is inside the operator is treated as a constant when computing the gradient. The stop gradient operator has the same effect on breaking the symmetry as the introduction of the constant hyper-parameters in GGDO.

4 ONLINE LEARNING OF THE LAPLACIAN REPRESENTATION

We first formulate the problem of learning the Laplacian representation while simultaneously updating the policy. We then provide theoretical bounds for the convergence of the learned representation.

4.1 PROBLEM DEFINITION

We formulate the problem of learning the Laplacian representation while the policy is updating as a sequence of GDOs varying in time. To break the symmetry in GDO we apply the stop gradient operator similar to ALLO. We assume the policy π_0 is initialized randomly and some learning

algorithm updates the policy in T discrete time steps producing a policy π_t after each update. Learning the Laplacian representation can then be represented by the sequence of objectives as follows

$$
\min_{u \in \mathcal{C}^{(t)}} \mathcal{L}^{(t)}(u) =
$$

$$
\min_{u \in \mathcal{C}^{(t)}} \sum_{i=1}^{d} \langle u_i, L^{(t)} u_i \rangle_{\mathcal{H}^{(t)}} + b \sum_{j=1}^{d} \sum_{k=1}^{j-1} (\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}})^2 + \frac{b}{2} \sum_{i=1}^{d} (\langle u_i, u_i \rangle_{\mathcal{H}^{(t)}} - 1)^2 \tag{7}
$$

where $\mathcal{C}^{(t)} \subset \mathbb{R}^{d|\mathcal{S}|}$ is a convex and closed set. We write L^{π_t} and $\mathcal{H}^{\pi_t}$ as $L^{(t)}$ and $\mathcal{H}^{(t)}$ for simpler notation. In addition, we assume that $b > 0$. We refer to this objective as the asymmetric graph drawing objective (AGDO).[1]

Note that for a fixed policy, AGDO is a special case of ALLO with $\beta = 0$. Another similarity between AGDO and ALLO is that AGDO can be viewed as solving ALLO with added regularization for the dual parameters β. Adding a regularization term $-\Gamma \sum_{j=1}^{d} \sum_{k=1}^{j} \frac{\beta_{jk}^2}{2}$ to equation 6 yields a closed form solution for maximization over β with $\beta_{jk}^*(u) = \frac{\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}} - \delta_{jk}}{\Gamma}$. Substituting reduces equation 6 to

$$
\min_{u \in \mathbb{R}^{d|\mathcal{S}|}} \sum_{i=1}^{d} \langle u_i, L^{(t)} u_i \rangle_{\mathcal{H}^{(t)}} + (b + \frac{1}{2\Gamma}) \sum_{j=1}^{d} \sum_{k=1}^{j} (\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}} - \delta_{jk})^2 \tag{8}
$$

which is the same as ALLO ($\beta = 0$) with b replaced with $b + \frac{1}{2\Gamma}$ which is also a constant hyperparameter.

We lay the assumptions for our theoretical analysis.

Assumption 1. *For each policy π_t the induced Markov chain is ergodic and has a unique stationary distribution with non-zero entries, i.e $\min_t \min_{s \in \mathcal{S}} \rho^{\pi_t}(s) = \rho_{min} > 0$.*

Assumption 2. *For two consecutive time steps t and $t + 1$, the policies π_t and π_{t+1}, satisfy $\max_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}} |\pi_t(a|s) - \pi_{t+1}(a|s)| \leq \delta_\pi^{(t)}$. Additionally, the bound $\delta_\pi^{(t)}$ on the policy drift satisfies $\sum_{t=0}^{\infty} \delta_\pi^{(t)} < \infty$.*

Assumption 1 guarantees that the induced probability measure $\rho^{(t)}$ assigns a non-zero value to every state. Note that going from $\rho^{(t)}(s) > 0$ to $\rho^{(t+1)}(s) = 0$ is equivalent to removing a node from the graph which would make the dimensions of the spaces inconsistent. A more general assumption can be made that $\rho^{(t+1)}$ and $\rho^{(t)}$ are mutually absolutely continuous, i.e. $\rho^{(t+1)}(s) = 0 \iff \rho^{(t)}(s) = 0$, however, the same analysis can be done to the set $\mathcal{S}' = \{s \in \mathcal{S} : \rho^{(t)}(s) \neq 0\}$. Assumption 2 assumes the drift in the policy caused by the policy learning algorithm is bounded and that the policy learning converges to some policy as t increases. This assumption is valid for many policy learning algorithms in RL, such as trust region policy optimization (TRPO) (Schulman, 2015) and proximal policy optimization (PPO) (Schulman et al., 2017).

4.2 CONVERGENCE ANALYSIS OF AGDO

We first define the function $g_i^{(t)} : \mathbb{R}^{d|\mathcal{S}|} \to \mathbb{R}^{|\mathcal{S}|}$, which is the gradient of equation 7 with respect to u_i taking into account the stop gradient operator, as

$$
g_{u_i}^{(t)}(u) = \left(2L^{(t)} u_i + 2b \sum_{j=1}^{i-1} \langle u_i, [\![u_j]\!] \rangle_{\mathcal{H}^{(t)}} [\![u_j]\!] + 2b (\langle u_i, u_i \rangle_{\mathcal{H}^{(t)}} - 1) u_i \right) \odot \rho \tag{9}
$$

where $\odot$ is the Hadamard product. The vectors u_i are updated using the update equation

$$
u_i^{(t+1)} \leftarrow \text{Proj}_{\mathcal{C}^{(t)}}(u_i^{(t)} - \eta g_{u_i}^{(t)}(u^{(t)})) = u_i^{(t)} - \eta G_{u_i}^{(t)}(u_i^{(t)}) \tag{10}
$$

---

[1]Here we have a slightly different application of the stop gradient operator than the objective proposed by Gomez et al. (2023). The penalty term for the norm of u_i does not have the stop gradient operator which does not change the gradient but ensures the term is propagated to the Hessian for the stability analysis. We provide more discussion in A.2

where $\eta > 0$ is the learning rate, $\text{Proj}_{\mathcal{C}^{(t)}}$ is the projection to $\mathcal{C}^{(t)}$, and $G_{u_i}^{(t)}$ is the gradient map defined as $G_{u_i}^{(t)}(u_i) = \frac{1}{\eta}(u_i - \text{Proj}_{\mathcal{C}^{(t)}}(u_i^{(t)} - \eta g_{u_i}^{(t)}(u^{(t)})))$.

We show in Lemma 1 that for a fixed policy, if $\mathcal{C}^{(t)} = \mathbb{R}^{d|\mathcal{S}|}$, the equilibrium points of performing gradient descent to minimize the function $\mathcal{L}^{(t)}$ defined in equation 7 correspond to permutations of the eigenvectors. We defer all detailed proofs to Appendix A.

Lemma 1. *If $\mathcal{C}^{(t)} = \mathbb{R}^{d|\mathcal{S}|}$, $u^{*(t)}$ is an equilibrium point of minimizing $\mathcal{L}^{(t)}$ in equation 7 under gradient descent dynamics, iff $u_i^{*(t)} = e_{\sigma(i)}^{(t)} m_i$, and $\langle u_i^{*(t)}, u_i^{*(t)} \rangle_{\mathcal{H}^{(t)}} = m_i \left(1 - \frac{\lambda_{\sigma(i)}^{(t)}}{b}\right)$ for some permutation $\sigma : \mathcal{S} \to \mathcal{S}$ where $m_i \in \{0, 1\}$, i.e. zero or more vectors $u_i^{*(t)}$ can be zero.*

This result is similar to Lemma 2 derived by Gomez et al. (2023) with the norm of the vectors being different and the fact that vectors can be zero. However, we show in Theorem 1 that only the identity permutation with non-zero vectors corresponds to a stable equilibrium under proper selection of hyperparameters.

Theorem 1. *The only stable equilibrium point from Lemma 1 minimizing the objective $\mathcal{L}^{(t)}$ in equation 7 under gradient descent dynamics is the one corresponding to the identity permutation with none of the vectors being zero, under an appropriate selection of the barrier coefficient b, if the highest eigenvalue multiplicity is 1.*

4.3 CONVERGENCE ANALYSIS OF ONLINE AGDO

In this section, we present a theoretical analysis of the convergence of the online PGD algorithm. We first begin by establishing certain properties of the PGD algorithm.

We consider the case where the vectors $u_i^{(t)}$ are constrained such that their norm in $\mathcal{H}^{(t)}$ is bounded. We define $\mathcal{C}^{(t)}$ as $\mathcal{C}^{(t)} = \{u \in \mathbb{R}^{d|\mathcal{S}|} : \langle u_i, u_i \rangle_{\mathcal{H}^{(t)}} \leq 2\}$. This set has two interesting properties. First, it includes all equilibrium points for all $b > 1$ (as established in Lemma 1). Second, the gradient function $g^{(t)}$ defined in equation 9 is Lipchitz continuous over $\mathcal{C}^{(t)}$. The following result establishes this property.

Proposition 1. *The loss function $\mathcal{L}^t$ defined in equation 7 is α-smooth with Lipschitz continuous gradient $g^{(t)}$ such that*

$$\|g^{(t)}(u) - g^{(t)}(u')\| \leq \alpha\|u - u'\| \tag{11}$$

for any $u \in \mathbb{C}^{(t)}$ with $\alpha = 2 + 14b + 4bd$.

Next, we present some preliminary results, which we will later use in the convergence analysis. In Lemma 2, we characterize the drift in the policy-induced Markov chain, the Laplacian operator, and the loss function.

Lemma 2. *Under Assumptions 1 and 2, for any $u \in \mathbb{R}^{|\mathcal{S}|}$, we have the following:*

(a) $\|P^{(t+1)} - P^{(t)}\|_\infty \leq \delta_\pi^{(t)}$

(b) $\|\rho^{(t+1)} - \rho^{(t)}\|_\infty \leq \delta_\rho^{(t)} = \kappa^{(t)}\delta_\pi^{(t)}$

(c) $\|(\rho^{(t+1)} \otimes \mathbf{1}) \odot L_{\rho^{(t+1)}}^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot L_{\rho^{(t)}}^{(t)}\| \leq \delta_L^{(t)} = \sqrt{|\mathcal{S}|}\left(\delta_\pi^{(t)} + \delta_\rho^{(t)}\right) + \delta_\rho^{(t)}$

(d) $\left|\mathcal{L}^{t+1}(u) - \mathcal{L}^t(u)\right| \leq \delta_{\mathcal{L}}^{(t)} = \frac{2d\delta_L^{(t)}}{\rho_{min}} + \frac{8b\delta_\rho^{(t)}}{\rho_{min}^2}; \forall u \in \mathcal{C}^{(t)}$

where $\kappa^{(t)}$ is a condition number on the induced Markov chain by $\pi^{(t)}$.

Note that Lemma 2(b) follows directly from previous work on the perturbation analysis of stationary distributions of Markov chains (Haviv & Van der Heyden, 1984; Funderlic & Meyer Jr, 1986; Cho & Meyer, 2000). For example, Cho & Meyer (2000) gives the following condition number $\kappa^{(t)} = \frac{1}{2}\max_j \max_{i \neq j} \frac{m_{ij}}{m_{jj}}$, where m_{ij} is the mean first passage time from state i to state j and m_{jj} is the

mean return time to state j. For other possible options of condition numbers, review the comparative study by Cho & Meyer (2001).

Algorithm 1 Online PGD of AGDO

1: **Input:** Initial policy π_0, learning rate η, initial vector $u^{(0)}$, policy learning algorithm $\mathcal{A}$
2: **for** $t = 1$ to T **do**
3:      Interact with the environment and add transitions to the replay buffer
4:      $u_i^{(t+1)} \leftarrow \mathrm{Proj}_{\mathcal{C}^{(t)}}(u_i^{(t)} - \eta g_{u_i}^{(t)}(u^{(t)}))$
5:      Get π_t by updating π_{t-1} using $\mathcal{A}$
6: **end for**

Finally, we show in Theorem 2 that running online projected gradient descent on AGDO achieves ergodic convergence.

Theorem 2. *Under Assumptions 1 and 2, running Algorithm 1 on the sequence of losses as defined in equation 7 for T time steps, with a constant learning rate $\eta = \dfrac{1}{\alpha}$, we have,*

$$\mathbb{E}_{t \sim Uniform\{1,2,\ldots,T\}}\left[\|G^{(t)}(u^{(t)})\|^2\right] \leq \frac{2\alpha}{T}\left(\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^* + \sum_{t=1}^{T}\delta_{\mathcal{L}}^{(t)}\right) = \mathcal{O}\left(\frac{1}{T}\right) \quad (12)$$

where $\mathcal{L}^*$ is the minimum value $\mathcal{L}^{(t)}$ can take. Moreover, the OPGD algorithm (Algorithm 1) under the time-varying loss function (as defined in equation 7) asymptotically converges to the critical point.

5 EMPIRICAL ANALYSIS

We evaluate the accuracy of the proposed method in the fixed policy setting and the online setting. We evaluate the importance of different components of the algorithm as well.

Experiments Setup We consider the grid world environments shown in Figure 5. For each experiment, a fixed target location is sampled uniformly at random and the agent receives a reward of $+1$ if the agent reaches the location. At the start of each episode or when the agent reaches the target, the new agent location is sampled uniformly at random. We consider a maximum episode length of 1000 steps. We follow the same setting as Gomez et al. (2023), where we set $d = 11$ and use the (x, y) coordinates as input to the encoder network, a fully connected neural network with 3 layers of size 256 each. We start training the encoder and the agent after collecting 10^4 samples and run the experiment until 2×10^5 samples have been collected. We use a fixed value of 5 for the barrier coefficient. The encoder network is trained using an Adam optimizer with a learning rate of 10^{-3}. For each collected sample, 10 batches are sampled to update the encoder. For training the agent, we use proximal policy optimization (PPO) (Schulman et al., 2017) as the training algorithm with an initial clipping parameter 0.2 unless otherwise specified. We add an entropy regularization term to discourage deterministic policies. To simulate assumption 2, we schedule the clipping parameter to decrease from 0.2 to 0.01 starting from step 10^5 until the end of the training. For the full experimental setup, please refer to Appendix B. In all figures, we report the average cosine similarity of all dimensions of the eigenvectors averaged across 5 seeds with the 95% confidence interval highlighted.

Eigenvalue Accuracy (Fixed Setting) We start by comparing the performance of AGDO to ALLO in the fixed uniform policy setting. In Figure 2, we show that the average cosine similarity of AGDO and ALLO is almost identical for the same initial seeds. This result is similar to the analysis by Gomez et al. (2023) that showed that ALLO with $\beta = 0$ achieved similar results to ALLO.

Eigenvalue Accuracy (Online Setting) Figure 3 shows the results of optimizing both AGDO and ALLO in an online setting where the agent's policy is updated with the PPO loss. Similar to the fixed setting, the results of AGDO and ALLO are almost identical for the same set of seeds. In addition, for all environments, the average similarity trends upward as the training steps increase. For environments with a large number of states (GridRoom-1 and GridRoom-4) we notice that the

(a) GridRoom-1   (b) GridMaze-11

Figure 2: Average cosine similarity between the true Laplacian representation and the learned representation using AGDO and ALLO for a fixed uniform policy.

accuracy is slightly lower at earlier stages of the training, which is coherent with our theoretical analysis (see Lemma 2 and Theorem 2) that the drift increases with the number of states, resulting in slower convergence. However, this can be mitigated by imposing stricter bounds on the drift in the policy learning algorithm.

(a) AGDO   (b) ALLO

Figure 3: Average cosine similarity between the true Laplacian representation and the learned representation using AGDO and ALLO for a ppo policy.

Ablation Study In this study, we aim to analyze three points; (1) the importance of the drift bound assumption, (2) the effect of the number of encoder update steps per sample collected, and (3) the effect of noise caused by sampling from the replay buffer when the policy was different.

To assert the importance of the bounded drift assumption, we compare running PPO with different initial clipping parameters, vanilla policy gradient (VPG) Sutton et al. (1999), and deep Q-network (DQN) Mnih et al. (2015). First note that VPG is equivalent to PPO without clipping. We can see in Figure 4a that the lower the clipping value is, i.e. the drift bound between policies is smaller, the higher the accuracy for the learned representation is. However, a small drift might affect the performance of the learned policy. In addition, for DQN the change in the policy distribution can be drastic for an $\epsilon-$greedy policy with a small ϵ whenever the Q-network changes the estimated optimal action in a state. As for the new estimated optimal action, the probability will shift from $\frac{\epsilon}{|\mathcal{A}|}$ to $1 - \epsilon$. This explains why the accuracy of the learned representation for DQN is much lower than the on-policy methods. We conclude that the bounded drift assumption is necessary for learning an accurate representation.

In figure 4b, we analyze the effect of increasing the number of steps. We vary the number of update steps per sample between 1 and 20. While an increase in the number of steps is expected to enhance

accuracy, our findings indicate that this is not observed. We hypothesize that this discrepancy is due to the presence of noise, caused by sampling from the replay buffer.

To confirm the previous hypothesis, we test in Figure 4c the effect of varying the replay buffer size. Recall that estimating the AGDO loss in equation 7 is done through sampling steps from the replay buffer. In the online setting, the buffer would include steps from previous policies with different stationary and transition distributions which would introduce bias to our loss estimate. However, a small buffer size would also increase the variance of the estimate. This is confirmed by the results, as for a buffer that holds only one episode we see a worse performance than a buffer that holds 20 episodes. On the other hand, increasing the buffer size drastically also causes accuracy to drop as the samples used have a different distribution which can be seen for buffers with sizes 50 and 400.

(a) Effect of drift

(b) Effect of number of update steps

(c) Effect of number of replay buffer size

Figure 4: Analysis of different aspects of online AGDO. (a) The effect of bounded drift on the accuracy of the learned. (b) The effect of the number of update steps per sample collected. (c) The effect of the number of episodes in the replay buffer.

6 CONCLUSION

In this paper, we studied online Laplacian-based representation learning and demonstrated that it can be effectively integrated with reinforcement learning, enabling simultaneous updates of both representation and policy. Our theoretical analysis, under mild assumptions, shows that running the online projected gradient descent on the Asymmetric Graph Drawing Objective achieves ergodic convergence, ensuring that the learned representations are aligned with the underlying dynamics. Additionally, our empirical studies reinforce these findings and give insight into the compatibility of reinforcement learning algorithms with online representation learning. Our work opens new avenues for enhancing representation learning in complex environments and lays out the assumptions needed for its success. Future research could explore the adaptability of the proposed framework to various learning methods such as linear value function approximators and options learning.

REFERENCES

Andre Barreto, Will Dabney, Remi Munos, Jonathan J Hunt, Tom Schaul, Hado P van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/hash/350db081a661525235354dd3e19b8c05-Abstract.html.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Jiayu Chen, Vaneet Aggarwal, and Tian Lan. A unified algorithm framework for unsupervised discovery of skills based on determinantal point process. *Advances in Neural Information Processing Systems*, 36, 2024.

Carmen Chicone. *Ordinary differential equations with applications*. Springer, 2006.

Grace E Cho and Carl D Meyer. Markov chain sensitivity measured by mean first passage times. *Linear Algebra and its Applications*, 316(1-3):21–28, 2000.

Grace E Cho and Carl D Meyer. Comparison of perturbation bounds for the stationary distribution of a markov chain. *Linear Algebra and its Applications*, 335(1-3):137–150, 2001.

Peter Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural computation*, 5(4):613–624, 1993.

Jesse Farebrother, Joshua Greaves, Rishabh Agarwal, Charline Le Lan, Ross Goroshin, Pablo Samuel Castro, and Marc G Bellemare. Proto-value networks: Scaling representation learning with auxiliary tasks. *arXiv preprint arXiv:2304.12567*, 2023.

Miroslav Fiedler. Algebraic connectivity of graphs. *Czechoslovak mathematical journal*, 23(2):298–305, 1973.

Robert E Funderlic and CD Meyer Jr. Sensitivity of the stationary distribution vector for an ergodic markov chain. *Linear Algebra and its Applications*, 76:1–17, 1986.

Michael Gimelfarb, Andre Barreto, Scott Sanner, and Chi-Guhn Lee. Risk-aware transfer in reinforcement learning using successor features. In *Advances in Neural Information Processing Systems*, volume 34, pp. 17298–17310. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/hash/90610aa0e24f63ec6d2637e06f9b9af2-Abstract.html.

Diego Gomez, Michael Bowling, and Marlos C Machado. Proper Laplacian representation learning. *arXiv preprint arXiv:2310.10833*, 2023.

Moshe Haviv and Ludo Van der Heyden. Perturbation bounds for the stationary probabilities of a finite markov chain. *Advances in Applied Probability*, 16(4):804–818, 1984.

Yuu Jinnai, Jee Won Park, Marlos C Machado, and George Konidaris. Exploration in reinforcement learning with deep covering options. In *International Conference on Learning Representations*, 2019.

Martin Klissarov and Marlos C. Machado. Deep Laplacian-based options for temporally-extended exploration. In *Proceedings of the 40th International Conference on Machine Learning*, pp. 17198–17217. PMLR, July 2023. URL https://proceedings.mlr.press/v202/klissarov23a.html.

Yehuda Koren. Drawing graphs by eigenvectors: theory and practice. *Computers & Mathematics with Applications*, 49(11-12):1867–1888, 2005.

Tejas D Kulkarni, Ardavan Saeedi, Simanta Gautam, and Samuel J Gershman. Deep successor reinforcement learning. *arXiv preprint arXiv:1606.02396*, 2016.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: Contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 5639–5650. PMLR, November 2020. URL https://proceedings.mlr.press/v119/laskin20a.html.

Marlos C Machado, Marc G Bellemare, and Michael Bowling. A Laplacian framework for option discovery in reinforcement learning. In *International Conference on Machine Learning*, pp. 2295–2304. PMLR, 2017a.

Marlos C Machado, Clemens Rosenbaum, Xiaoxiao Guo, Miao Liu, Gerald Tesauro, and Murray Campbell. Eigenoption discovery through the deep successor representation. *arXiv preprint arXiv:1710.11089*, 2017b.

Marlos C Machado, Andre Barreto, Doina Precup, and Michael Bowling. Temporal abstraction in reinforcement learning with the successor representation. *Journal of Machine Learning Research*, 24(80):1–69, 2023.

Sridhar Mahadevan. Proto-value functions: Developmental reinforcement learning. In *Proceedings of the 22nd international conference on Machine learning - ICML '05*, pp. 553–560, Bonn, Germany, 2005. ACM Press. ISBN 978-1-59593-180-1. doi: 10.1145/1102351.1102421. URL http://portal.acm.org/citation.cfm?doid=1102351.1102421.

Sridhar Mahadevan. Representation policy iteration. *arXiv preprint arXiv:1207.1408*, 2012.

Sridhar Mahadevan and Mauro Maggioni. Proto-value functions: A Laplacian framework for learning representation and control in markov decision processes. *Journal of Machine Learning Research*, 8(10), 2007.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

John Schulman. Trust region policy optimization. *arXiv preprint arXiv:1502.05477*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Adam Stooke, Kimin Lee, Pieter Abbeel, and Michael Laskin. Decoupling representation learning from reinforcement learning. In *Proceedings of the 38th International Conference on Machine Learning*, pp. 9870–9879. PMLR, July 2021. URL https://proceedings.mlr.press/v139/stooke21a.html.

Richard S Sutton. Between mdps and semi-mdps: Learning, planning, and representing knowledge at multiple temporal scales. 1998.

Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. *Advances in neural information processing systems*, 12, 1999.

Kaixin Wang, Kuangqi Zhou, Qixin Zhang, Jie Shao, Bryan Hooi, and Jiashi Feng. Towards better Laplacian representation in reinforcement learning with generalized graph drawing. In *Proceedings of the 38th International Conference on Machine Learning*, pp. 11003–11012. PMLR, July 2021. URL https://proceedings.mlr.press/v139/wang21ae.html.

Yifan Wu, George Tucker, and Ofir Nachum. The Laplacian in RL: Learning representations with efficient approximations. *arXiv preprint arXiv:1810.04586*, 2018.

Xin Xu, Zhenhua Huang, Daniel Graves, and Witold Pedrycz. A clustering-based graph Laplacian framework for value function approximation in reinforcement learning. *IEEE Transactions on Cybernetics*, 44(12):2613–2625, December 2014. ISSN 2168-2275. doi: 10.1109/TCYB.2014.2311578.

Haoqi Yuan and Zongqing Lu. Robust task representations for offline meta-reinforcement learning via contrastive learning. In *Proceedings of the 39th International Conference on Machine Learning*, pp. 25747–25759. PMLR, June 2022. URL https://proceedings.mlr.press/v162/yuan22a.html.

A   PROOFS

A.1   PROOF OF LEMMA 1

Proof. For an equilibrium point

$$g_{u_i}^{(t)}(u^{*(t)}) = \left(2L^{(t)}u_i + 2b \sum_{j=1}^{i-1} \langle u_i, u_j \rangle_{\mathcal{H}^{(t)}} u_j + 2b \left(\langle u_i, u_i \rangle_{\mathcal{H}^{(t)}} - 1 \right) u_i \right) \odot \rho = 0,$$

and since $\rho_{\min} > 0$, we can divide each element of the vectors on both sides by $\rho(s)$ and we get,

$$g_{u_i}^{(t)}(u^{*(t)}) = 2L^{(t)}u_i + 2b \sum_{j=1}^{i-1} \langle u_i, u_j \rangle_{\mathcal{H}^{(t)}} u_j + 2b \left(\langle u_i, u_i \rangle_{\mathcal{H}^{(t)}} - 1 \right) u_i = 0,$$

We proceed by induction. For the base case with $i = 1$, we have

$$g_{u_i}^{(t)}(u^{*(t)}) = 2L^{(t)}u_1^{*(t)} + 2b \left(\langle u_1^{*(t)}, u_1^{*(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right) u_1^{*(t)} = 0$$

Hence, either $u_1^{*(t)} = e_{\sigma(1)}^{(t)}$; for some permutation $\sigma : \mathcal{S} \to \mathcal{S}$ and $-2\lambda_{\sigma(1)}^{(t)} = 2b \left(\langle u_1^{*(t)}, u_1^{*(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right)$ (i.e., $\langle e_{\sigma(1)}^{(t)}, e_{\sigma(1)}^{(t)} \rangle_{\mathcal{H}^{(t)}} = 1 - \frac{\lambda_{\sigma(1)}^{(t)}}{b}$) or $u_1^{*(t)} = 0$.

Suppose now that either $u_j^{*(t)} = e_{\sigma(j)}^{(t)}$ and $\langle e_{\sigma(j)}^{(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}} = 1 - \frac{\lambda_{\sigma(j)}^{(t)}}{b}$ or $u_j^{*(t)} = 0$ for all $j < i$ then the gradient becomes

$$g_{u_i}^{(t)}(u^{*(t)}) = 2L^{(t)}u_i^{*(t)} + 2b \left(\langle u_i^{*(t)}, u_i^{*(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right) u_i^{*(t)} +$$
$$2b \sum_{j=1}^{i-1} \langle u_i^{*(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}} e_{\sigma(j)}^{(t)} \mathbb{1}_{u_j^{*(t)} \neq 0} = 0$$

Since the eigenvectors form a basis, let $u_i^{*(t)} = \sum_{k=1}^{|S|} c_{ik} e_{\sigma(k)}^{(t)}$. The gradient then becomes

$$g_{u_i}^{(t)}(u^{*(t)}) = \sum_{k=1}^{|S|} \left(2\lambda_{\sigma(k)}^{(t)} + 2b \left(\langle u_i^{*(t)}, u_i^{*(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right) \right) c_{ik} e_{\sigma(k)}^{(t)} \tag{13}$$
$$+ 2b \sum_{j=1}^{i-1} \langle u_i^{*(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}} e_{\sigma(j)}^{(t)} \mathbb{1}_{u_j^{*(t)} \neq 0} = 0.$$

Since the eigenvectors form a basis, all coefficients must be zero. For $j < i$ and $u_j^{*(t)} \neq 0$, we have:

$$\left(2\lambda_{\sigma(j)}^{(t)} + 2b \left(\langle u_i^{*(t)}, u_i^{*(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right) \right) c_{ij} + 2b \langle u_i^{*(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}} = 0 \tag{14}$$

Now note that

$$c_{ij} = \frac{\langle u_i^{*(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}}}{\langle e_{\sigma(j)}^{(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}}}.$$

Equation 14 then becomes

$$\left(\frac{2\lambda_{\sigma(j)}^{(t)} + 2b \left(\langle u_i^{*(t)}, u_i^{*(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right)}{\langle e_{\sigma(j)}^{(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}}} + 2b \right) \langle u_i^{*(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}} = 0$$

Reordering the terms, we have:

$$\left(\frac{2\lambda^{(t)}_{\sigma(j)} + 2b\left(\langle u^{*(t)}_i, u^{*(t)}_i\rangle_{\mathcal{H}^{(t)}} - 1 + \langle e^{(t)}_{\sigma(j)}, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}}\right)}{\langle e^{(t)}_{\sigma(j)}, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}}}\right) \langle u^{*(t)}_i, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}} = 0.$$

Substituting $\langle e^{(t)}_{\sigma(j)}, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}} = 1 - \frac{\lambda^{(t)}_{\sigma(j)}}{b}$, we have:

$$\left(\frac{2b\langle u^{*(t)}_i, u^{*(t)}_i\rangle_{\mathcal{H}^{(t)}}}{\langle e^{(t)}_{\sigma(j)}, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}}}\right) \langle u^{*(t)}_i, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}} = 0,$$

which implies that either $\langle u^{*(t)}_i, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}} = c_{ij} = 0$ or $\frac{2b\langle u^{*(t)}_i, u^{*(t)}_i\rangle_{\mathcal{H}^{(t)}}}{\langle e^{(t)}_{\sigma(j)}, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}}} = 0$, but the second condition is only true if $u^{*(t)}_i = 0$ which implies that $\langle u^{*(t)}_i, e^{(t)}_{\sigma(j)}\rangle_{\mathcal{H}^{(t)}}$ is always zero. For $k \geq i$ in equation 13 or $u^{*(t)}_k = 0$

$$\left(2\lambda^{(t)}_{\sigma(k)} + 2b\left(\langle u^{*(t)}_i, u^{*(t)}_i\rangle_{\mathcal{H}^{(t)}} - 1\right)\right) c_{ik} = 0$$

which implies that either $c_{ik} = 0$ or $\langle u^{*(t)}_i, u^{*(t)}_i\rangle_{\mathcal{H}^{(t)}} = 1 - \frac{\lambda^{(t)}_{\sigma(k)}}{b}$. Note that c_{ik} and c_{ij} can both be simultaneously non-zero only if $\lambda^{(t)}_{\sigma(k)} = \lambda^{(t)}_{\sigma(j)}$, i.e, $u^{*(t)}_i$ is a linear combination of eigenvectors for the same eigenvalue. Thus, we conclude that either $u^{*(t)}_i = e^{(t)}_{\sigma(i)}$ and $\langle e^{(t)}_{\sigma(i)}, e^{(t)}_{\sigma(i)}\rangle_{\mathcal{H}^{(t)}} = 1 - \frac{\lambda^{(t)}_{\sigma(i)}}{b}$ or $u^{*(t)}_i = 0$. For non-zero, $u^{*(t)}_i$ it is required that $b > \lambda^{(t)}_{\sigma(i)}$. $\square$

A.2 Proof of Theorem 1

Proof. Let

$$g^{(t)}(u) = \begin{bmatrix} g^{(t)}_1(u) \\ g^{(t)}_2(u) \\ \vdots \\ g^{(t)}_d(u) \end{bmatrix}, \tag{15}$$

where $g^{(t)}_1$ is defined in equation 9.

We start by computing the Jacobian of $g^{(t)}$ while applying the stop gradient operator. The matrix $\mathbf{J}^{(t)} = J(g^{(t)})$ is defined such that each row of the matrix corresponds to the gradient of an entry of $g^{(t)}$. We choose to apply the stop gradient operator when computing the Jacobian as optimizing the loss functions with the stop gradient operator is analogous to solving for u_i's sequentially while fixing u_j where $j < i$ as shown by Gomez et al. (2023). Analyzing the stability of those sequential losses would not include a cross gradient term between u_i and u_j.

To determine the stability of the equilibrium points, we analyze eigenvalues of the Jacobian evaluated at them (Chicone, 2006). Let $m_i = \mathbb{1}_{u^{*(t)}_i \neq 0}$, and $\rho^{(t)}_{\text{diag}}$ a diagonal matrix where $\rho^{(t)}_{\text{diag}}(s,s) = \rho^{(t)}(s)$ then

$$\mathbf{J}^{(t)}_{ij}(u^{(t)}) = (\nabla_{u_i} g^{(t)}_{u_j}(u)^\top)^\top$$

$$\begin{cases} 2L^{(t)}_{\rho^{(t)}} \odot (\rho^{(t)} \otimes \mathbf{1}) + 2b\left(\langle u^{(t)}_i, u^{(t)}_i\rangle_{\mathcal{H}^{(t)}} - 1\right)\rho^{(t)}_{\text{diag}} + & \text{, if } i = j \\[2ex] \quad 2b\left(2(u^{(t)}_i \odot \rho^{(t)}) \otimes (u^{(t)}_i \odot \rho^{(t)}) + \displaystyle\sum_{k=1}^{i-1}(u^{(t)}_k \odot \rho^{(t)}) \otimes (u^{(t)}_k \odot \rho^{(t)})\right) \\[2ex] 0 & \text{, otherwise} \end{cases} \tag{16}$$

Substituting the equilibrium points with the form derived in Lemma 1, i.e $u_i^{*(t)} = e_{\sigma(i)}^{(t)} m_i$, $\langle u_i^{(t)}, u_i^{(t)} \rangle_{\mathcal{H}^{(t)}} = \left(1 - \frac{\lambda_{\sigma(i)}^{(t)}}{b} \right) m_i$, and $\langle u_i^{(t)}, u_j^{(t)} \rangle_{\mathcal{H}^{(t)}} = 0$ for $i \neq j$ we get,

$$
\begin{aligned}
\mathbf{J}_{ij}^{(t)}(u^{*(t)}) &= (\nabla_{u_i} g_{u_j}^{(t)}(u_i^{*(t)})^\top)^\top \\
&= \begin{cases}
\begin{aligned}
&2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1}) - 2\lambda_{\sigma(i)}^{(t)} \rho_{\text{diag}}^{(t)} m_i + 2b\rho_{\text{diag}}^{(t)}(m_i - 1) + \\
&\quad 4b(e_{\sigma(i)}^{(t)} \odot \rho^{(t)}) \otimes (e_{\sigma(i)}^{(t)} \odot \rho^{(t)}) m_i + \\
&\quad 2b \sum_{k=1}^{i-1} (e_{\sigma(k)}^{(t)} \odot \rho^{(t)}) \otimes (e_{\sigma(k)}^{(t)} \odot \rho^{(t)}) m_k
\end{aligned} & , \text{if } i = j \\
\\
0 & , \text{otherwise}
\end{cases}
\end{aligned}
\tag{17}
$$

Note that $\mathbf{J}^{(t)}$ is a triangular block matrix and its eigenvalues are the union of the diagonal blocks. We proceed to analyze the conditions for the block matrices to be positive definite, i.e when $\langle v_i, \mathbf{J}_{ii}^{(t)}(u^{*(t)}) v_i \rangle$ is greater than zero $\forall v_i \in \{v \in \mathbb{R}^{|\mathcal{S}|} : v \neq 0\}$. Since the Laplacian operator is self-adjoint, the eigenvectors form a basis for $\mathbb{R}^{|\mathcal{S}|}$, we can represent each v_i as a linear combination of eigenvectors. Let $v_i = \sum_{k=1}^{|\mathcal{S}|} c_{ik} e_{\sigma(k)}^{(t)}$ in $\langle v_i, \mathbf{J}_{ii}^{(t)}(u^{*(t)}) v_i \rangle$ we get $\langle \sum_{k=1}^{|\mathcal{S}|} c_{ik} e_{\sigma(k)}^{(t)}, \mathbf{J}_{ii}^{(t)}(u^{*(t)}) \sum_{k=1}^{|\mathcal{S}|} c_{ik} e_{\sigma(k)}^{(t)} \rangle$.

We first compute $\mathbf{J}_{ii}^{(t)}(u^{*(t)}) \sum_{k=1}^{|\mathcal{S}|} c_k e_{\sigma(k)}^{(t)}$ by replacing $\mathbf{J}_{ii}(u^{*(t)})^{(t)}$ with equation 17, we get

$$
\mathbf{J}_{ii}^{(t)}(u^{*(t)}) \sum_{k=1}^{|\mathcal{S}|} c_k e_{\sigma(k)}^{(t)} =
$$

$$
\left(2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1}) - 2\lambda_{\sigma(i)}^{(t)} \rho_{\text{diag}}^{(t)} m_i + 2b\rho_{\text{diag}}^{(t)}(m_i - 1) \right) \sum_{k=1}^{|\mathcal{S}|} c_{ik} e_{\sigma(k)}^{(t)} +
$$

$$
\left(4b(e_{\sigma(i)}^{(t)} \odot \rho^{(t)}) \otimes (e_{\sigma(i)}^{(t)} \odot \rho^{(t)}) m_i + 2b \sum_{j=1}^{i-1} (e_{\sigma(j)}^{(t)} \odot \rho^{(t)}) \otimes (e_{\sigma(j)}^{(t)} \odot \rho^{(t)}) m_k \right) \sum_{k=1}^{|\mathcal{S}|} c_{ik} e_{\sigma(k)}^{(t)}
\tag{18}
$$

Note that

$$
\left((e_{\sigma(j)}^{(t)} \odot \rho^{(t)}) \otimes (e_{\sigma(j)}^{(t)} \odot \rho^{(t)}) \right) e_{\sigma(k)}^{(t)} = 0 \ \forall k \neq j
$$

and

$$
\left((e_{\sigma(j)}^{(t)} \odot \rho^{(t)}) \otimes (e_{\sigma(j)}^{(t)} \odot \rho^{(t)}) \right) e_{\sigma(j)}^{(t)} = \langle e_{\sigma(j)}^{(t)}, e_{\sigma(j)}^{(t)} \rangle_{\mathcal{H}^{(t)}} (e_{\sigma(j)}^{(t)} \odot \rho^{(t)})
$$

$$
= \left(1 - \frac{\lambda_{\sigma(j)}^{(t)}}{b} \right) (e_{\sigma(j)}^{(t)} \odot \rho^{(t)}).
$$

Also note that $2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1})$ is a matrix with $\left(2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1}) \right)(s, s') = L(s, s') \rho^{(t)}(s') \rho^{(t)}(s)$, and therefore for any $x \in \mathbb{R}^{|\mathcal{S}|}$

$$
\left(2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1}) \right) x = 2(Lx) \odot \rho^{(t)}.
\tag{19}
$$

Substituting in equation 18 we get,

$$\mathbf{J}_{ii}^{(t)}(u^{*(t)})\sum_{k=1}^{|\mathcal{S}|}c_k e_{\sigma(k)}^{(t)} =$$

$$\sum_{j=1}^{|\mathcal{S}|}\left(2\left(\lambda_{\sigma(j)}^{(t)}-\lambda_{\sigma(i)}^{(t)}m_i\right)+2b(m_i-1)\right)c_{ij}(e_{\sigma(j)}^{(t)}\odot\rho^{(t)})$$

$$+ 4bc_{ii}(e_{\sigma(i)}^{(t)}\odot\rho^{(t)})m_i - 4c_{ii}\lambda_{\sigma(i)}^{(t)}(e_{\sigma(i)}^{(t)}\odot\rho^{(t)})m_i \tag{20}$$

$$+\sum_{j=1}^{i-1}2bc_{ij}(e_{\sigma(j)}^{(t)}\odot\rho^{(t)})m_j-\sum_{j=1}^{i-1}2c_{ij}\lambda_{\sigma(j)}^{(t)}(e_{\sigma(j)}^{(t)}\odot\rho^{(t)})m_j$$

Now we reduced $\mathbf{J}_{ii}^{(t)}(u^{*(t)})\sum_{k=1}^{|\mathcal{S}|}c_k e_{\sigma(k)}^{(t)}$ to a linear combination $(e_{\sigma(1)}^{(t)}\odot\rho^{(t)}, e_{\sigma(2)}^{(t)}\odot\rho^{(t)},...,e_{\sigma(|\mathcal{S}|)}^{(t)}\odot\rho^{(t)})$ with some coefficients $(a_1, a_2,..., a_{|\mathcal{S}|})$. Since $\langle c_{ij}e_{\sigma(j)}^{(t)}, a_k c_{ik}e_{\sigma(k)}^{(t)}\odot\rho^{(t)}\rangle = a_k c_{ik}c_{ij}\langle e_{\sigma(j)}^{(t)}, e_{\sigma(k)}^{(t)}\rangle_{\mathcal{H}^{(t)}}$ and $\langle e_{\sigma(j)}^{(t)}, e_{\sigma(k)}^{(t)}\rangle_{\mathcal{H}^{(t)}}=0$ for $j\neq k$ we have

$$\langle\sum_{k=1}^{|\mathcal{S}|}c_{ik}e_{\sigma(k)}^{(t)}, \mathbf{J}_{ii}^{(t)}(u^{*(t)})\sum_{k=1}^{|\mathcal{S}|}c_{ik}e_{\sigma(k)}^{(t)}\rangle = \sum_{k=1}^{|\mathcal{S}|}a_k c_{ik}^2\langle e_{\sigma(k)}^{(t)}, e_{\sigma(k)}^{(t)}\rangle_{\mathcal{H}^{(t)}} \tag{21}$$

Since $\langle e_{\sigma(k)}^{(t)}, e_{\sigma(k)}^{(t)}\rangle_{\mathcal{H}^{(t)}} > 0$ and $c_{ik}^2\geq 0$, a_k must be positive $\forall k$ for $\mathbf{J}_{ii}^{(t)}(u^{*(t)})$ to be positive definite. We group the conditions from equation 20 that are required to be positive below

$$\begin{cases} 2b(m_i+m_j-1)-2\lambda_{\sigma(i)}^{(t)}m_i+2\lambda_{\sigma(j)}^{(t)}(1-m_j) & \forall 1\leq j<i\leq d \\ 6bm_i+2\lambda_{\sigma(i)}^{(t)}-6\lambda_{\sigma(i)}^{(t)}m_i-2b & \forall 1\leq i\leq d \\ 2(\lambda_{\sigma(j)}^{(t)}-\lambda_{\sigma(i)}^{(t)}m_i)+2b\,(m_i-1) & \forall 1\leq i<j\leq|\mathcal{S}|. \end{cases} \tag{22}$$

If any $u_i^{*(t)}=0$, then the third condition becomes $2\lambda_{\sigma(j)}^{(t)}-2b$ which is always negative under the selection of hyperparameters discussed in Lemma 1, hence it is unstable. For equilibrium points where all $u_i^{*(t)}$ are non-zero, i.e $m_i=1\forall\ i$, the conditions becomes

$$\begin{cases} 2b-2\lambda_{\sigma(i)}^{(t)} & \forall 1\leq j<i\leq d \\ 4b-4\lambda_{\sigma(i)}^{(t)} & \forall 1\leq i\leq d \\ 2(\lambda_{\sigma(j)}^{(t)}-\lambda_{\sigma(i)}^{(t)}) & \forall 1\leq i<j\leq|\mathcal{S}|. \end{cases} \tag{23}$$

The third condition indicates that $2(\lambda_{\sigma(j)}^{(t)}-\lambda_{\sigma(i)}^{(t)})$ has to be positive which is only true for the identity permutation and if the maximum eigenvalue multiplicity of the Laplacian is 1. The second and first conditions imply that $b-\lambda_{\sigma(i)}^{(t)}$ must be positive which is true when $b>\lambda_{\sigma(i)}^{(t)}\forall\ 1\leq i\leq|\mathcal{S}|$ which is already a requirement of Lemma 1. $\qquad\square$

A.3 PROOF OF PROPOSITION 1

Proof. To show that the gradient function $g^{(t)}$ is Lipchitz continuous we proceed to show that the Spectral norm of the Jacobian is bounded $\forall u\in\mathcal{C}^{(t)}$. Notice that the Jacobian defined in equation 16 is a block triangular matrix, hence its singular values are the combined singular values of the block matrices $\mathbf{J}_{ii}^{(t)}(u)$, and $\|\mathbf{J}^{(t)}(u)\|=\max_i\|\mathbf{J}_{ii}^{(t)}(u)\|$. By the triangle inequality we have,

$$\|\mathbf{J}_{ii}^{(t)}(u)\| \leq \left\|2L_{\rho^{(t)}}^{(t)}\odot(\rho^{(t)}\otimes\mathbf{1})\right\| + \left\|2b\left(\langle u_i^{(t)}, u_i^{(t)}\rangle_{\mathcal{H}^{(t)}}-1\right)\rho_{\text{diag}}^{(t)}\right\| + \tag{24}$$

$$\left\|4b(u_i^{(t)}\odot\rho^{(t)})\otimes(u_i^{(t)}\odot\rho^{(t)})+2b\sum_{k=1}^{i-1}\right\|\left\|(u_k^{(t)}\odot\rho^{(t)})\otimes(u_k^{(t)}\odot\rho^{(t)})\right\|$$

We start by bounding the first term, by equation 19 we know that for any vector $x \in \mathbb{R}^{|\mathcal{S}|}$, $\left(2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1})\right) x = 2(Lx) \odot \rho^{(t)}$. For any $x \in \mathbb{R}^{|\mathcal{S}|}$ with $\|x\| = 1$

$$
\left\| \left(L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1}) \right) x \right\| = \left\| (Lx) \odot \rho^{(t)} \right\| = \sqrt{\langle (Lx) \odot \rho^{(t)}, (Lx) \odot \rho^{(t)} \rangle}
$$

$$
= \sqrt{\sum_{s \in \mathcal{S}} ((Lx)(s))^2 \rho^{(t)}(s)^2} \le \sqrt{\sum_{s \in \mathcal{S}} ((Lx)(s))^2 \rho^{(t)}(s)}
$$

$$
= \sqrt{\langle (Lx), (Lx) \rangle_{\mathcal{H}^{(t)}}} = \|Lx\|_{\mathcal{H}^{(t)}} \le \|L\|_{\mathcal{H}^{(t)}} \|x\|_{\mathcal{H}^{(t)}} \le \|L\|_{\mathcal{H}^{(t)}}.
$$

Therefore,

$$
\left\| \left(2L_{\rho^{(t)}}^{(t)} \odot (\rho^{(t)} \otimes \mathbf{1}) \right) u \right\| = \left\| 2(Lu) \odot \rho^{(t)} \right\| \le 2\|L\|_{\mathcal{H}^{(t)}} = 2. \tag{25}
$$

For the second term, since $\|\rho_{\mathrm{diag}}^{(t)}\| \le 1$ and $\langle u_i^{(t)}, u_i^{(t)} \rangle_{\mathcal{H}^{(t)}} \le 2$, we have

$$
\left\| 2b \left(\langle u_i^{(t)}, u_i^{(t)} \rangle_{\mathcal{H}^{(t)}} - 1 \right) \rho_{\mathrm{diag}}^{(t)} \right\| \le 2b \left\| \langle u_i^{(t)}, u_i^{(t)} \rangle_{\mathcal{H}^{(t)}} \rho_{\mathrm{diag}}^{(t)} \right\| + 2b \left\| \rho_{\mathrm{diag}}^{(t)} \right\| \le 4b + 2b = 6b. \tag{26}
$$

For the remaining terms, note that for any $x \in \mathbb{R}^{|\mathcal{S}|}$ with $\|x\| = 1$,

$$
\left\| \left((u_i^{(t)} \odot \rho^{(t)}) \otimes (u_i^{(t)} \odot \rho^{(t)}) \right) x \right\| = \left\| \langle u_i, x \rangle_{\mathcal{H}^{(t)}} (u_i^{(t)} \odot \rho^{(t)}) \right\| \le \|x\| \|u_i\|_{\mathcal{H}^{(t)}}^2 \le 2. \tag{27}
$$

Combining equations 25, 26, and 27 in equation 24 we get

$$
\|\mathbf{J}_{ii}^{(t)}(u)\| \le \alpha = 2 + 14b + 4bd.
$$

$\square$

A.4 PROOF OF LEMMA 2

Proof for Lemma 2 (a)

Proof. We denote $A(i, :)$ as the i-th row of the matrix A.

$$
\left\| P^{(t+1)} - P^{(t)} \right\|_\infty = \max_{s \in \mathcal{S}} \left\| P^{(t+1)}(s, :) - P^{(t)}(s, :) \right\|_1
$$

$$
= \max_{s \in \mathcal{S}} \left\| \sum_{a \in \mathcal{A}} (\pi^{(t+1)}(a|s) - \pi^{(t)}(a|s)) \mathcal{T}(s, a, :) \right\|_1
$$

$$
\stackrel{(i)}{\le} \max_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}} \left| \pi^{(t+1)}(a|s) - \pi^{(t)}(a|s) \right| \|\mathcal{T}(s, a, :)\|_1
$$

$$
\stackrel{(ii)}{=} \max_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}} \left| \pi^{(t+1)}(a|s) - \pi^{(t)}(a|s) \right| = \delta_\pi^{(t)},
$$

where (i) is by the triangle inequality, and (ii) from the fact that $\|\mathcal{T}(s, a, :)\|_1 = 1$. $\square$

Proof for Lemma 2 (c)

Proof. First note that the elements of the matrix $(\rho^{(t)} \otimes \mathbf{1}) \odot L_{\rho^{(t)}}^{(t)}$ are defined as

$$
(\rho^{(t)} \otimes \mathbf{1}) \odot L_{\rho^{(t)}}^{(t)}(s, s') = \rho^{(t)}(s) \mathbb{1}_{s=s'} - \rho^{(t)}(s) W^{(t)}(s, s') \rho^{(t)}(s')
$$

$$
= \rho^{(t)}(s) \mathbb{1}_{s=s'} - \frac{1}{2} P^{(t)}(s, s') \rho^{(t)}(s) - \frac{1}{2} P^{(t)}(s', s) \rho^{(t)}(s').
$$

Hence, by applying the triangle inequality, we have

$$\left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot L^{(t+1)}_{\rho^{(t+1)}} - (\rho^{(t)} \otimes \mathbf{1}) \odot L^{(t)}_{\rho^{(t)}} \right\|$$

$$= \left\| \rho^{(t+1)}_{\text{diag}} - \rho^{(t)}_{\text{diag}} - (\rho^{(t+1)} \otimes \mathbf{1}) \odot W^{(t+1)}_{\rho^{(t+1)}} + (\rho^{(t)} \otimes \mathbf{1}) \odot W^{(t)}_{\rho^{(t)}} \right\|$$

$$\leq \left\| \rho^{(t+1)}_{\text{diag}} - \rho^{(t)}_{\text{diag}} \right\| + \left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot W^{(t+1)}_{\rho^{(t+1)}} - (\rho^{(t)} \otimes \mathbf{1}) \odot W^{(t)}_{\rho^{(t)}} \right\|$$

$$\leq \delta^{(t)}_\rho + \left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot W^{(t+1)}_{\rho^{(t+1)}} - (\rho^{(t)} \otimes \mathbf{1}) \odot W^{(t)}_{\rho^{(t)}} \right\|$$

$$\leq \delta^{(t)}_\rho + \frac{1}{2} \left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot P^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot P^{(t)} \right\|$$

$$+ \frac{1}{2} \left\| \left((\rho^{(t+1)} \otimes \mathbf{1}) \odot P^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot P^{(t)} \right)^\top \right\|$$

And since $\|A^\top\| = \|A\|$ we have

$$\begin{aligned} &\left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot L^{(t+1)}_{\rho^{(t+1)}} - (\rho^{(t)} \otimes \mathbf{1}) \odot L^{(t)}_{\rho^{(t)}} \right\| \\ &\leq \delta^{(t)}_\rho + \left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot P^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot P^{(t)} \right\| \end{aligned} \tag{28}$$

Now we proceed to bound the second term, adding and subtracting $(\rho^{(t+1)} \otimes \mathbf{1}) \odot P^{(t)}$ and applying the triangle inequality we have

$$\left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot P^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot P^{(t)} \right\|$$

$$\leq \left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot (P^{(t+1)} - P^{(t)}) \right\| + \left\| ((\rho^{(t+1)} \otimes \mathbf{1}) - \rho^{(t)} \otimes \mathbf{1})) \odot P^{(t)} \right\|$$

$$\overset{(i)}{\leq} \sqrt{|\mathcal{S}|} \max_{s \in \mathcal{S}} \left\| \rho^{(t+1)}(s) \left(P^{(t+1)}(s,:) - P^{(t)}(s,:) \right) \right\|_1$$

$$+ \sqrt{|\mathcal{S}|} \max_{s \in \mathcal{S}} \left\| \left(\rho^{(t+1)}(s) - \rho^{(t)}(s) \right) P^{(t)}(s,:) \right\|_1$$

$$= \sqrt{|\mathcal{S}|} \left\| \rho^{(t+1)} \right\|_\infty \max_{s \in \mathcal{S}} \left\| P^{(t+1)}(s,:) - P^{(t)}(s,:) \right\|_1$$

$$+ \sqrt{|\mathcal{S}|} \left\| \rho^{(t+1)} - \rho^{(t)} \right\|_\infty \max_{s \in \mathcal{S}} \left\| P^{(t)}(s,:) \right\|_1$$

$$\overset{(ii)}{\leq} \sqrt{|\mathcal{S}|} \left(\delta^{(t)}_\pi + \delta^{(t)}_\rho \right)$$

where (i) stems from the identity $\|A\| \leq \sqrt{n}\|A\|_\infty$ for the $n \times n$ matrix A and (ii) follows from $\left\| \rho^{(t+1)} \right\|_\infty \leq 1$, $\left\| P^{(t)}(s,:) \right\|_1 = 1$, and Lemma 2(a). $\qquad \square$

Proof for Lemma 2 (d)

Proof. Recall that the loss function is given by:

$$\mathcal{L}^{(t)}(u) = \sum_{i=1}^d \langle u_i, L^{(t)} u_i \rangle_{\mathcal{H}^{(t)}} + b \sum_{j=1}^d \sum_{k=1}^{j-1} (\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}})^2 + \frac{b}{2} \sum_{i=1}^d (\langle u_i, u_i \rangle_{\mathcal{H}^{(t)}} - 1)^2 \tag{29}$$

We are interested in finding a bound for the difference:

$$\Delta \mathcal{L}^{(t)}(u) = |\mathcal{L}^{(t+1)}(u) - \mathcal{L}^{(t)}(u)|. \tag{30}$$

The first term in the loss function is:

$$\sum_{i=1}^d \langle u_i, L^{(t)} u_i \rangle_{\mathcal{H}^{(t)}}. \tag{31}$$

Substituting the inner product and applying the triangle inequality, we have the following:

$$\left| \sum_{i=1}^{d} \langle u_i, L^{(t+1)} u_i \rangle_{\mathcal{H}^{(t+1)}} - \sum_{i=1}^{d} \langle u_i, L^{(t)} u_i \rangle_{\mathcal{H}^{(t)}} \right| \leq$$

$$\sum_{i=1}^{d} \left| \left((u_i^\top \odot \rho^{(t+1)^\top}) L_{\rho^{(t+1)}}^{(t+1)}(u_i) - (u_i^\top \odot \rho^{(t)^\top}) L_{\rho^{(t)}}^{(t)}(u_i) \right) \right|. \tag{32}$$

The above expression can be re-written as follows:

$$\sum_{i=1}^{d} \left| \left(u_i^\top \left((\rho^{(t+1)} \otimes \mathbf{1}) \odot L_{\rho^{(t+1)}}^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot L_{\rho^{(t)}}^{(t)} \right) u_i \right) \right|. \tag{33}$$

From Lemma 2(c), $\left\| (\rho^{(t+1)} \otimes \mathbf{1}) \odot L_{\rho^{(t+1)}}^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot L_{\rho^{(t)}}^{(t)} \right\| \leq \delta_L^{(t)}$. Thus, we have:

$$\sum_{i=1}^{d} \left| \left(u_i^\top \left((\rho^{(t+1)} \otimes \mathbf{1}) \odot L_{\rho^{(t+1)}}^{(t+1)} - (\rho^{(t)} \otimes \mathbf{1}) \odot L_{\rho^{(t)}}^{(t)} \right) u_i \right) \right| \leq \delta_L^{(t)} \sum_{i=1}^{d} \|u_i\|^2 \tag{34}$$

The difference in the regularization terms is:

$$\left| b \sum_{j=1}^{d} \sum_{k=1}^{j-1} \left((\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}})^2 - (\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}})^2 \right) + \right.$$
$$\left. \frac{b}{2} \sum_{j=1}^{d} \left((\langle u_j, u_j \rangle_{\mathcal{H}^{(t+1)}} - 1)^2 - (\langle u_j, u_j \rangle_{\mathcal{H}^{(t)}} - 1)^2 \right) \right|. \tag{35}$$

Using the rule $x^2 - y^2 = (x + y) \cdot (x - y)$ and applying the triangle inequality, we can rewrite the above expression as follows:

$$b \sum_{j=1}^{d} \sum_{k=1}^{j-1} |\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}} + \langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}}| \, |\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}} - \langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}}| +$$
$$\frac{b}{2} \sum_{j=1}^{d} |\langle u_j, u_j \rangle_{\mathcal{H}^{(t+1)}} + \langle u_j, u_j \rangle_{\mathcal{H}^{(t)}} - 2| \, |(\langle u_j, u_j \rangle_{\mathcal{H}^{(t+1)}} - \langle u_j, u_j \rangle_{\mathcal{H}^{(t)}})|$$
$$\leq b \sum_{j=1}^{d} \sum_{k=1}^{j-1} |\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}} + \langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}}| \, |(\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}} - \langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}})| + \tag{36}$$
$$\frac{b}{2} \sum_{j=1}^{d} |\langle u_j, u_j \rangle_{\mathcal{H}^{(t+1)}} + \langle u_j, u_j \rangle_{\mathcal{H}^{(t)}}| \, |(\langle u_j, u_j \rangle_{\mathcal{H}^{(t+1)}} - \langle u_j, u_j \rangle_{\mathcal{H}^{(t)}})|$$

Note that

$$|\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}} + \langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}}| \leq 2\|u_j\| \cdot \|[\![u_k]\!]\| \tag{37}$$

and that

$$|\langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t+1)}} - \langle u_j, [\![u_k]\!] \rangle_{\mathcal{H}^{(t)}}| = \left| \sum_{s \in \mathcal{S}} u_j(s)(\rho^{(t+1)}(s) - \rho^{(t)}(s)) [\![u_k]\!](s) \right|$$
$$\leq \|u_j\| \cdot \|[\![u_k]\!]\| \cdot \|\rho^{(t+1)} - \rho^{(t)}\|_\infty \leq \|u_j\| \cdot \|[\![u_k]\!]\| \cdot \delta_\rho^{(t)} \tag{38}$$

where $\delta_\rho^{(t)}$ is defined in Lemma 2(b).

Combining the bounds for both the first and second parts, the total bound on $\mathcal{L}^{(t+1)}(u) - \mathcal{L}^{(t)}(u)$ is:

$$|\mathcal{L}^{(t+1)}(u) - \mathcal{L}^{(t)}(u)| \leq \delta_L^{(t)} \sum_{i=1}^{d} \|u_i\|^2 + b \sum_{j=1}^{d} \sum_{k=1}^{j} \left(2\|u_j\|^2 \|[\![u_k]\!]\|^2 \delta_\rho^{(t)} \right). \tag{39}$$

We have $|\mathcal{L}^{(t+1)}(u) - \mathcal{L}^{(t)}(u)| \leq \delta_{\mathcal{L}}^{(t)}$, where $\delta_{\mathcal{L}}^{(t)}$ is given by

$$\delta_{\mathcal{L}}^{(t)} = \delta_L^{(t)} \sum_{i=1}^{d} \|u_i\|^2 + b \sum_{j=1}^{d} \sum_{k=1}^{j} \left(2\|u_j\|^2 \|[\![u_k]\!]\|^2 \delta_\rho^{(t)} \right). \tag{40}$$

We know that $\|u_i\|^2 \leq 2/\rho_{min}$. Substituting this, we have

$$\delta_{\mathcal{L}}^{(t)} = \frac{2d\delta_L^{(t)}}{\rho_{min}} + \frac{8b\delta_\rho^{(t)}}{\rho_{min}^2}. \tag{41}$$

Note: From Lemma 2(b) and Lemma 2(c), we have $\delta_L^{(t)} \leq C_1 \delta_\pi^{(t)}$ and $\delta_\rho^{(t)} \leq C_2 \delta_\pi^{(t)}$, for some constants C_1, C_2. Thus, we have $|\mathcal{L}^{(t+1)}(u) - \mathcal{L}^{(t)}(u)| \leq \delta_{\mathcal{L}}^{(t)} = (C_1 + C_2)\delta_\pi^{(t)}$. This implies that the drift in the loss function decreases with the decrease in the drift between the policies π_t and π_{t+1}.

$\square$

A.5 PROOF OF THEOREM 2

Proof. Recall that the update rule for projected gradient descent in equation 10 is given by:

$$u_i^{(t+1)} \leftarrow u_i^{(t)} - \eta G_{u_i}^{(t)}(u_i^{(t)}),$$

We need to prove that the gradient norm $\|g^{(t)}(u_t)\|$ asymptotically approaches zero as $t \to \infty$, which would ensure the convergence to a critical point. In order to prove this, we will establish that the sum of the squared gradients remains finite over time, despite the loss function being time-varying.

Recall the following assumptions:

- The gradient of the time-varying loss function $\mathcal{L}^{(t)}(u)$ is Lipschitz continuous with constant $\alpha > 0$ for all t, that is,

$$\|g^{(t)}(u_1) - \nabla_u g^{(t)}(u_2)\| \leq \alpha \|u_1 - u_2\|, \quad \forall u_1, u_2.$$

- From Lemma 2, we have the change in the loss function from time t to time $t+1$ is bounded by a constant $\delta_{\mathcal{L}}$, i.e.,

$$\|\mathcal{L}^{(t+1)}(u) - \mathcal{L}^{(t)}(u)\| \leq \delta_{\mathcal{L}}^{(t)}, \quad \forall u.$$

- Additionally, it is easy to see that the loss function $\mathcal{L}^{(t)}(u)$ is bounded from below by a constant $\mathcal{L}^*$, i.e.,

$$\mathcal{L}^{(t)}(u) \geq \mathcal{L}^*, \quad \forall u, t.$$

The descent lemma for a time-varying loss function with Lipschitz continuous gradients and learning rate η is given by:

$$\mathcal{L}^{(t+1)}(u^{(t+1)}) \leq \mathcal{L}^{(t+1)}(u^{(t)}) - \eta \|G^{(t)}(u^{(t)})\|^2 + \frac{\eta^2}{2} \alpha \|G^{(t)}(u^{(t)})\|^2.$$

This can be rewritten as:

$$\mathcal{L}^{(t+1)}(u^{(t+1)}) \leq \mathcal{L}^{(t)}(u^{(t)}) - \eta \|G^{(t)}(u^{(t)})\|^2 + \frac{\eta^2}{2} \alpha \|G^{(t)}(u^{(t)})\|^2 + \delta_{\mathcal{L}}^{(t)},$$

where $\delta_{\mathcal{L}}^{(t)}$ represents the drift that accounts for the time-variation in the loss function between time t and $t+1$. Rearranging this inequality, we obtain:

$$\mathcal{L}^{(t+1)}(u^{(t+1)}) \leq \mathcal{L}^{(t)}(u^{(t)}) - \left(\eta - \frac{\eta^2}{2} \alpha \right) \|G^{(t)}(u^{(t)})\|^2 + \delta_{\mathcal{L}}^{(t)}.$$

To ensure that the loss function decreases at each time step, except for the small drift $\delta_{\mathcal{L}}$, we require that:

$$\eta - \frac{\eta^2}{2}\alpha > 0.$$

This gives the condition on the learning rate:

$$\eta < \frac{2}{\alpha}.$$

Thus, the learning rate must satisfy $\eta \leq \frac{2}{\alpha}$.

At each step, we can bound the change in the loss function as follows:

$$\mathcal{L}^{(t)}(u^{(t)}) - \mathcal{L}^{(t+1)}(u^{(t+1)}) \geq \left(\eta - \frac{\eta^2}{2}\alpha\right)\|G^{(t)}(u^{(t)})\|^2 - \delta_{\mathcal{L}}^{(t)}.$$

Summing this inequality over $t = 1, 2, \ldots, T$, we get:

$$\sum_{t=1}^{T}\left(\mathcal{L}^{(t)}(u^{(t)}) - \mathcal{L}^{(t+1)}(u^{(t+1)})\right) \geq \sum_{t=1}^{T}\left(\left(\eta - \frac{\eta^2}{2}\alpha\right)\|G^{(t)}(u^{(t)})\|^2 - \delta_{\mathcal{L}}^{(t)}\right).$$

The left-hand side of this inequality is a telescoping sum, so it simplifies to:

$$\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^{(T+1)}(u^{(T+1)}) \geq \sum_{t=1}^{T}\left(\left(\eta - \frac{\eta^2}{2}\alpha\right)\|G^{(t)}(u^{(t)})\|^2 - \delta_{\mathcal{L}}^{(t)}\right).$$

Rearranging, we get:

$$\sum_{t=1}^{T}\|G^{(t)}(u^{(t)})\|^2 \leq \frac{\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^{(T+1)}(u^{(T+1)})}{\eta - \frac{\eta^2}{2}\alpha} + \frac{\sum_{t=1}^{T}\delta_{\mathcal{L}}^{(t)}}{\eta - \frac{\eta^2}{2}\alpha}.$$

Since the loss function $\mathcal{L}^{(t)}(u)$ is bounded from below by $\mathcal{L}^*$, we have:

$$\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^* \geq \sum_{t=1}^{T}\left(\left(\eta - \frac{\eta^2}{2}\alpha\right)\|G^{(t)}(u^{(t)})\|^2 - \delta_{\mathcal{L}}^{(t)}\right).$$

We can further simplify this to:

$$\sum_{t=1}^{T}\|G^{(t)}(u^{(t)})\|^2 \leq \frac{\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^*}{\eta - \frac{\eta^2}{2}\alpha} + \frac{\sum_{t=1}^{T}\delta_{\mathcal{L}}^{(t)}}{\eta - \frac{\eta^2}{2}\alpha}. \tag{42}$$

Dividing both sides by T, we get

$$\mathbb{E}_{t\sim\text{Uniform}\{1,2,\ldots,T\}}\left[\|G^{(t)}(u^{(t)})\|^2\right] \leq \frac{\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^*}{T\left(\eta - \frac{\eta^2}{2}\alpha\right)} + \frac{\sum_{t=1}^{T}\delta_{\mathcal{L}}^{(t)}}{T\left(\eta - \frac{\eta^2}{2}\alpha\right)}. \tag{43}$$

Setting $\eta = \frac{1}{\alpha}$, we have

$$\mathbb{E}_{t\sim\text{Uniform}\{1,2,\ldots,T\}}\left[\|G^{(t)}(u^{(t)})\|^2\right] \leq \frac{2\alpha}{T}\left(\mathcal{L}^{(1)}(u^{(1)}) - \mathcal{L}^* + \sum_{t=1}^{T}\delta_{\mathcal{L}}^{(t)}\right). \tag{44}$$

From Assumption 2, we have that the asymptotic sum of the squared gradients $\lim_{T\to\infty}\sum_{t=1}^{\infty}\|G^{(t)}(u^{(t)})\|^2$ remains finite, i.e., $\lim_{T\to\infty}\sum_{t=1}^{T}\|G^{(t)}(u^{(t)})\|^2 < \infty$. Therefore, we have:

$$\lim_{t\to\infty}\|G^{(t)}(u^{(t)})\| = 0.$$

This shows that the gradients asymptotically approach zero over time, proving that the projected gradient descent algorithm applied to the time-varying loss function converges asymptotically to a critical point.

$\square$

| (a) GridRoom-1 | (b) GridRoom-4 | (c) GridMaze-9 | (d) GridMaze-11 |

Figure 5: Environments tested in experiments where the grey areas are walls.

B EXPERIMENTS SETUP

For each environment, a fixed target is sampled uniformly at random, at the beginning of the training process. Upon reaching the target or at the beginning of an episode, the next state is sampled uniformly at random. The matrix $\hat{P}^{(t)}$, used to compute the Laplacian $\hat{L}^{(t)}$, is defined using a weighted sum between the actual $P^{(t)}$ and the initial distribution, as suggested by Wu et al. (2018) to handle episodic Markov Decision Processes (MDPs). To compute the true Laplacian representation, we perform eigen decomposition on the matrix $\hat{L}^{(t)}_{\rho^{(t)}}$, which is equivalent to applying the Laplacian operator in the space $\mathcal{H}^{(t)}$.

We provide hyper-parameters for the Asymmetric Graph Drawing Objective (AGDO), Proximal Policy Optimization (PPO), and Deep-Q Network (DQN) in Table 1.

Table 1: Hyper-parameters for AGDO, PPO, and DQN.

Hyper-Parameter	AGDO	PPO	DQN
d	11	-	-
Replay Max Episodes	20	-	-
Updates per Episodic Step	5	-	-
Total Training Steps	200,000	-	-
Maximum Episode Length	10,000	-	-
Learning Rate	0.001	3×10^{-4}	3×10^{-4}
Optimizer	Adam	Adam	Adam
Barrier Coefficient	5	-	-
Encoder Network Hidden Dimensions	[256, 256, 256]	-	-
Batch Size	256	256	256
Replay Buffer Size	-	500 steps	50,000 steps
Update Every	-	500 steps	1 step
Training Batches per Update	-	10	1
Actor and Critic Hidden Dimensions	-	[64, 64]	-
Q-Network Hidden Dimensions	-	-	[64, 64]
Discount Factor	-	0.99	0.99
Entropy Coefficient	-	0.01	-
Initial Clip Ratio	-	0.2	-
Final Clip Ratio	-	0.01	-
Initial Epsilon	-	-	1
Final Epsilon	-	-	0.1

Finally, we report the rewards achieved by the learning agents presented in section 5 in Figure 6.

(a) Rewards for agents in Figure 3

(b) Rewards for agents in Figure 4a

(c) Rewards for agents in Figure 4b

(d) Rewards for agents in Figure 4c

Figure 6: Average reward obtained by agents trained in section 5.