TAME the BALROG: Task-Adaptive Modular Evolution framework for Game Agents

Ola Aleksandra Pasieka[* 1 2]   Dominika Woszczyk[1]   Antoine Cully[2]   Borja G. León[1]

Abstract

Interactive games have proven to be key benchmarks for advancing Artificial Intelligence (AI), requiring capabilities like long-term planning, exploration, and adaptation to stochastic environments. While Large Language Models (LLMs) have achieved notable results across many domains, they struggle in complex gaming environments like those presented in the BALROG leaderboard. The absence of adaptive frameworks that can dynamically configure themselves based on environmental characteristics, limits the progress of AI in games. To this end, we introduce Task-Adaptive Modular Evolution (TAME) framework, which employs genetic algorithms to evolve environment-specific structures from modular components, enabling significant performance improvements of LLMs across diverse domains. TAME discovers high-performing configurations by selecting between baseline and hierarchical structures, selectively incorporating specialised modules, and fine-tuning each component through systematic mutations. Evaluating TAME across 6 varying games, TAME discovers high-performing architectures that deliver substantial gains: Gemini-3.1-Flash-Lite improves on average from 34.5% to 42.8%, GPT5-Minimal-Thinking from 32.8% to 44.8%, and Claude-Haiku-4.5 from 27.4% to 35.0%. Moreover, these structures demonstrate strong transferability for larger models of the same family. Transferring TAME-discovered architectures to Gemini-3.1-Pro, we achieve state-of-art performance on the BALROG leaderboard.

---

[*]This work was developed during an internship at Iconic. [1]Iconic, United Kingdom [2]Department of Computing, Imperial College London, London, United Kingdom. Correspondence to: Ola Aleksandra Pasieka <aleksandra.pasieka32@gmail.com>, Borja G. León <borja@iconicgames.ai>.

Accepted to the 2nd Workshop on Compositional Learning at ICML 2026, Seoul, South Korea. Copyright 2026 by the author(s).

1. Introduction

Large language models (LLMs) have achieved remarkable growth across a wide range of tasks, from general language understanding (Hendrycks et al., 2020) and code generation (Wang et al., 2024a; Pan et al., 2025; Hong et al., 2024), to recent breakthroughs including mastering the ARC reasoning benchmark (Chollet, 2024; Chollet et al., 2024) and performing at gold-medal level on International Mathematical Olympiad (Chervonyi et al., 2025). However, these models struggle significantly in interactive decision-making environments that require sequential actions, state awareness, and long-term planning (Liu et al., 2024; Klissarov et al., 2025).

Games have historically served as major testbeds for Artificial Intelligence, with examples including Atari (Mnih et al., 2013), Starcraft (Team, 2019), and GrantTurismo (León et al., 2024). Those successes predominantly emerged from reinforcement learning (RL) approaches specifically engineered for each domain, often requiring millions of training episodes and domain-specific reward shaping. While LLMs hold considerable promise on the possibility of zero-shot generalisation across games through their vast pretraining experience, e.g., game wikis, strategy guides, and gameplay discussions, they fail to translate this latent knowledge effectively. This performance gap is clearly illustrated in the BALROG leaderboard (Paglieri et al., 2025), a suite of diverse games traditionally employed in RL research, where even state-of-the-art LLMs achieve only partial success in the simpler games and barely progress with more challenging ones.

Notably, agentic frameworks have emerged as a dominant approach to enhancing LLM capabilities in other complex domains, including software development (Yang et al., 2024; Hong et al., 2024; Pan et al., 2025) or scientific research (Bran et al., 2023; Wang et al., 2024a; Lu et al., 2024). There are also recurrent efforts to improve long-term memory management in agentic frameworks, with solutions that prioritise either speed and cost efficiency, such as Jarvis-1 (Wang et al., 2024b), or performance, such as A-mem (Xu et al., 2025). Yet, despite presenting similar challenges, no agentic framework has been applied to games, which requires to handle challenges such as partially observability

Figure 1. TAME evolutionary framework overview. TAME runs a genetic algorithm to generate a population of genomes representing different module combinations, hyperparameters, and prompts, tunes them through a series of genetic operation, and selects the genome achieving the highest score. Icons were generated with Google Gemini Pro 2.5, 2025.

or exploration that are not as critical in most math or coding applications.

To address this gap, we introduce the TAME (Task-Adaptive Modular Evolution) framework, a genetic framework for LLMs to evolve agent architectures for diverse games. TAME consists of a series of basic game skill modules that enable different capabilities that might be relevant in games, e.g., hierarchical planning and memory. However, unlike in other domains, games can encode very diverse dynamics, e.g., Nethack is a game where exploration, long-term planning and memory are of paramount importance, while none of those skills help in a game like TextWorld. Thus, TAME undergoes an evolutionary process, iteratively exploring both the best modules for a specific game and enhancing the modules to work better in that game. Figure 1 illustrates this process. Each candidate structure is encoded through a vector that represents which modules are activated, along with the hyperparameters and the prompt discovered for this candidate. Through successive generations balancing diversity and performance, TAME employs mutation and cross-over operations on the genomes of the selected candidates to discover increasingly effective structures, i.e., module activation, and refines such modules adapting hyperparameters, prompts and inputs.

We validate TAME through extensive experiments across the six games used to evaluate foundational models in the BALROG leaderboard. We find that TAME-discovered configurations achieve relative score improvement of 24%, 28% and 37% on average compared to the baseline LLM performance, using Gemini-3.1-Flash-Lite, Claude-Haiku-4.5, and GPT5-Minimal Thinking respectively. Moreover, we show that architectures discovered by TAME exhibit strong transferability across the same family of models: genomes evolved using Gemini-3.1-Flash-Lite directly enhance the performance of Gemini-3.1-Pro without additional adapta-

tion, and same pattern repeats on other families of models. In the case of Gemini-3.1-Pro, we achieve new state-of-the-art results on BALROG leaderboard.

Thus, our contributions can be summarised as follows: (1) We introduce TAME, the first game-agentic framework that enables LLMs to evolve modular structures tailored to gaming environments and achieve state-of-the-art performance in the BALROG leaderboard, showing improved performance across 6 varying environments; (2) We present a genetic approach, which is the key for the functioning of this framework, introducing a set of modules for general gaming capabilities and a genome that captures modules, hyperparameters and prompts enabling TAME to adapt the agent to the game with a low evolutionary budget; (3) We demonstrate that TAME can be used to find effective agentic configurations with smaller models that directly transfer and improve the performance of larger and more complex, reasoning models of the same family; (4) We propose a novel and effective long-term memory system that combines embedding-based retrieval with LLM-augmented semantic memory matching the performance of state-of-the-art memory methods requiring three times less LLM calls.

2. Related work

Prompting and Memory. Hallucinations remain a key challenge for LLMs (Kalai et al., 2025), which can be mitigated through prompting techniques like chain-of-thought (Wei et al., 2022) and step-by-step reasoning. Limited context windows (Brown et al., 2020) is another limitation, driving development of memory systems. Retrieval-Augmented Generation (RAG) (Lewis et al., 2021) combines LLMs with external document retrieval to reduce hallucinations without retraining. HiAgent (Hu et al., 2024a) manages hierarchical memory using subgoals, dividing into "working memory" and "cross-trial memory" with LLM-based ob-

servation summarisation, while (Park et al., 2023) balance memory retrieval using recency, importance, and relevance scores. Jarvis1 (Wang et al., 2024b) stores task names, plans, and observation sequences using embedding (CLIP) for encoding and retrieval. A-mem (Xu et al., 2025) introduces structured memory notes with timestamps, keywords, and embeddings, establishing inter-memory connections through LLM calls.

LLMs as hierarchical planners. In TWOSOME (Tan et al., 2024), LLMs score actions based on observations, allowing RL agents to leverage world knowledge for improved decisions. MaestroMotif (Klissarov et al., 2024) uses LLMs to generate reward functions for skills, while LLM-Augmented Hierarchical Agents (Prakash et al., 2023) use LLMs to inject commonsense priors for more efficient policy learning. Jarvis1 (Wang et al., 2024b), consists of planner and controller, enhanced by multimodal memory system. An important limitation of Jarvis-1 is the necessity of human-crafted goals based on specific skills, limiting its application in games with emerging tasks.

Agentic frameworks. Agentic frameworks are systems that enable Large Language Models to act as autonomous agents capable of reasoning, planning, and interacting with external tools and environments. Recent work, such as AGENTBREEDER (Rosser and Foerster, 2025), shows that optimising frameworks provides superior multi-agent performance on reasoning, mathematics, and safety benchmarks. Moreover, multiple works show improvements in scientific discovery (Lu et al., 2024) and software development (Yang et al., 2024) through these structured frameworks. Related research like AFLOW (Zhang et al., 2024) and ADAS (Hu et al., 2024b) focus on optimising agent workflows, i.e. the sequential flow and coordination of processing steps. Other frameworks (Yuan et al., 2024; Zhang et al., 2025) use evolutionary search to construct multi-agent systems, where multiple distinct agents are coordinated with specialised roles. Different from these works, we present a single-agent system operating on a fixed workflow architecture and evolves the internal implementations. Closer to our work, AgentSquare (Shang et al., 2024) proposes a single-agent framework but with several key shortcomings over our approach when applied to games. Unlike AgentSquare, which relies on manual tool definitions and a restricted module set, TAME does not require additional user input to adapt to different games. TAME also expands the search space to include critical gaming skills—such as exploration, loop detection, and survival (see Figure 2) and introduces a novel, more effective long-term memory system.

Evolutionary Strategies. While earlier work in Evolutionary Hyperparameter Optimization (EHO) focused on optimising over numerical hyperparameters (Vincent and Jidesh, 2023) and neural network topologies (Lu et al., 2019;

Stanley et al., 2019), recent literature has also explored combining LLMs and evolutionary frameworks. Genetic algorithms are a common choice due to easy parallelisation across hardware (Ma et al., 2024; Rosser and Foerster, 2025; Sarkar et al., 2025).(Lehman et al., 2022) propose "evolution through large models" using LLMs as evolutionary operators. EvoPrompt (Guo et al., 2025) employs LLMs for crossover and mutation in genetic algorithms to discover diverse prompts, while Rainbow Teaming (Samvelyan et al., 2024) mutates adversarial prompts to populate MAP-Elites archives systematically. DOMiNO (Zahavy et al., 2022) balances quality-diversity trade-offs using Lagrange multipliers. Eureka (Ma et al., 2024) shows evolutionary optimisation over reward code benefits from human initialisation.

Options. We propose a hierarchical structure for decision-making, a method common in robotics (Wohlke et al., 2021), autonomous driving (Duan et al., 2020), and games (Lin et al., 2021). Following the Options Framework (Sutton et al., 1999), we use the term options to denote manageable subtasks that decompose the main objective.

3. TAME Framework

We introduce TAME (Task-Adaptive Modular Evolution framework), a novel agentic framework designed for dynamic LLM adaptation across diverse gaming environments. Inspired by Eureka (Ma et al., 2024), which shows that human priors significantly improve LLM-based evolutionary optimisation performance, TAME begins with an initial population $\mathcal{P}_0$ comprising diverse modular structure configurations, each encoding different combinations of human-crafted modules and hyperparameters. The framework's modular architecture consists of six core components illustrated in Figure 2: hierarchical goal decomposition (comprising a Meta-Controller, Low-Level Executor, and Completion Validator), Long-Term Memory, Critic, Loop Detector, Amygdala, and Explorer. TAME's evolutionary process operates iteratively: in each generation, the framework evaluates all new members $p \in \mathcal{P}_i$ on the target game and selects candidates for the next generation based on two criteria: (1) the top N performers by absolute score, and (2) M additional diverse solutions that achieve at least a fraction α of the best performer's score. This dual selection strategy balances exploitation of successful structures with exploration of the relevant solution space. Each candidate's genome is represented as a vector encoding active modules, hyperparameters (e.g., memory decay rates, exploration-exploitation trade-offs), and module-specific prompts. After every iteration, the genomes of the selected candidates undergo mutation and crossover operations to generate the new members of the subsequent population $\mathcal{P}_{i+1}$. Through successive generations, TAME discovers increasingly effective structures tailored to each game's requirements. The

Figure 2. Fully enabled TAME modular architecture: an epsilon-greedy mechanism selects between Meta-controller (providing options toward game objectives) and Explorer (options towards exploring the environment). Low-level Executor proposes actions, while Amygdala checks for danger and prioritises survival. Completion Validator checks option completion while the Loop Detector identifies stuck states, and the Critic summarises key actions that led to the outcome of the option. Long-term memory saves successful and failed trajectories and adds them to LLM context. The details of each module can be found in the Appendix G.

remaining of this section details the genetic algorithm and the design and functionality of each modular component in TAME.

3.1. Notation and Functional Inputs

Let $\mathcal{G} = \{g_1, \ldots, g_n\}$ be the set of decomposed options towards the game objective, A the action space, O the observation space, S the state space, H the set of option summaries, and $\mathcal{T}$, space of natural text. Each state $s_t \in S$ at time t is defined as:

$$s_t = (o_t, I, h_{i-1}, g_i, \tau_i, M_i^{\pm}, F_{\text{recent}}, F_i, F_{i,act}, F_{i,obs})$$

where $o_t \in O$ is the current agent's observation, I is the game context (objective and available actions), $h_{i-1} \in H$ summarises the previous option's outcome, $g_i \in \mathcal{G}$ is the active option with termination condition τ_i, $M_i^{\pm}$ contains the top successful k_{succ} and failed k_{fail} options respectively. F_{recent} stores the last m action-observation pairs, while F_i, $F_{i,actions}$, and $F_{i,obs}$ maintain action-observation, action-only, and observation-only trajectories for the current option respectively.

Each component within s_t can serve as a functional input to any module within the framework. Through early experimentation we noted that the selection of appropriate functional inputs has a significant impact on performance, and it is up to the evolutionary process to find the most appropriate inputs for each module.

For the initial population generation, we hand-crafted inputs that we consider most relevant for each module, providing the genetic algorithm with informative human priors (see Appendix V). This is further detailed in Sections 3.2 and 3.3.

3.2. Modular blueprints

TAME incorporates human-crafted modules targeting essential gaming capabilities, where $s_t^{mc}, s_t^{le}, s_t^{cv}, s_t^{e}, s_t^{a}, s_t^{ld}, s_t^{c}$, denote genetic-algorithm-selected subsets of s_t:

- **Meta-Controller:** decomposes objectives into options $(g_1, g_2, \ldots) = \text{LLM}_{high}(s_t^{mc})$, each containing name, description, prerequisites, success conditions, and priority.

- **Low-Level Executor:** maps options to actions $(a_1, a_2, \ldots) = \text{LLM}_{low}(s_t^{le})$.

- **Completion Validator:** classifies option outcomes $C_i = \text{LLM}_{\varphi}(s_t^{cv}) \in \{0, 1\}$.

- **Explorer:** generates exploration options $g^{exp} = \text{LLM}_{\text{explorer}}(s_t^{e})$, selected via ϵ-greedy over the Meta-Controller with $\epsilon_t = 0.99^t \times 0.1$.

- **Amygdala:** $D_i = \text{LLM}_{\text{amygdala}}(s_t^{a}) \in \{0, 1\}$ triggers a survival option when danger is detected.

- **Loop Detector:** $L_i = \text{LLM}_{\psi}(s_i^{ld}) \in \{0, 1\}$ flags repetitive behaviour.

- **Critic:** $h_i = \text{LLM}_{\rho}(s_t^{c}, C_i)$ summarises key factors behind each option's success or failure.

The LLM prompts of each component are mutated during the genetic algorithm, starting from initial prompts available in the Appendix V. More details of each module can be found in the Appendix G.

3.3. Game Adaptation

Given the diverse dynamics and requirements across different gaming environments, we propose a genetic optimisation approach that automatically explores diverse agentic architectures to adapt the underlying LLM to the specific game characteristics. To that end, we first encode the agentic structure descriptors into genomes. Each genome is constructed from three core components:

- **Modules**: TAME modules (see details in the Appendix G) are parametrised as a set of binary values. Such values indicate if a module is active (1) or not (0). The set of modules is as in Figure 2.

- **Hyperparameters**: A set of continuous values encoding: *Long-Term Memory Time Decay Factor* λ, which sets the option priority decay rate; *Long-Term Memory Similarity Threshold* τ_{cos}, which specifies the cosine similarity cutoff for storing memories; *Exploration Parameter* ϵ, which controls the epsilon-greedy exploration; and *Language Model Temperature*. See more details in the Appendix H.

- **Prompts**: The last component of the genome includes the prompts used by the modules of the agentic structure. See examples in Appendix V.

For any game G the initial population $\mathcal{P}_0$ consists of four predefined genomes:

$$\mathcal{P}_0 = \{\mathbf{g}_{\text{Baseline}}, \mathbf{g}_{\text{Hierarchical[Hand-Crafted]}},$$
$$\mathbf{g}_{\text{Full[Claude]}}, \mathbf{g}_{\text{Full[Hand-Crafted]}}\}$$

Where $\mathbf{g}_{\text{Baseline}}$ is the genome corresponding to a baseline structure (no modules activated) as in Paglieri et al. (2025) (BALROG). $\mathbf{g}_{\text{Hierarchical[Hand-Crafted]}}$ corresponds to TAME[Hierarchical+Long-Term Memory], a genome with the hierarchical and long-term memory modules activated, with our own generated prompts. $\mathbf{g}_{\text{Full[Claude]}}$ - refers to a genome with all the modules activated that employs prompts proposed by Claude-Sonnet-4.5. Finally, $\mathbf{g}_{\text{Full[Hand-Crafted]}}$ is also a genome with all the modules active, but with our own engineered prompts. See Appendix V for full detail.

Genetic Operations. Given the distinct nature of the components within the genome (i.e., binary or continuous values, or prompts), TAME employs distinct crossover and mutation strategies depending on the type of variable or representation that is handled. For binary variables, we use a parent-based probabilistic flipping mechanism that incorporates an inheritance bias. Continuous variables are handled through Gaussian perturbation for mutation and linear interpolation for crossover. Finally, for prompt optimisation, we adopt the EvoPrompt methodology by Guo

et al. (2025), which enables crossover and mutation tailored to LLM-based prompts (availabe in Appendix U).

Genome Evaluation. Each genome is evaluated using the average game progression across n_{ep} episodes as a fitness function. Moreover, we embed the genome representation and calculate the minimum distance to genomes already existing in the population as a score of diversity, allowing for keeping population of best scoring and most diverse genomes. See Appendix I for more details.

Genetic Algorithm. Our genetic algorithm iterates through four steps: 1) *Parent Population Selection*: TAME chooses parents based on roulette wheel selection (a probabilistic parent-picking method where each individual's chance of being chosen is proportional to its fitness score) 2) *Reproduction*: Parents for reproduction are chosen from parent population with p_{single} and $1-p_{single}$ referring to the probability of single-parent or two-parent, respectively. Genetic operations are applied, represented by mutation+crossover or mutation alone (based on the number of parents) 3) *Fitness Evaluation:* calculates genome's performance score and diversity based on average game progression and embeded genome representation, respectively. 4) *Population Pruning*: the population is trimmed to maintain a maximum of $N + M$ individuals — N highest-performing plus M most diverse genomes (subject to achieving a factor α of the performance of the best genome within the population). Most diverse genomes are those with largest minimum distance of their embedding with respect to the already existing embeddings in the population. For comprehensive information on the genetic algorithm, refer to the appendices: Appendix I provides further detail and discussion, while Appendix I.3 and Appendix C contain the pseudocode and hyperparameters, respectively.

3.4. Long-term memory

TAME implements a novel memory system combining the efficiency of embedding-based systems like Jarvis-1 (Wang et al., 2023) with the performance of A-mem (Xu et al., 2025). We adopt Jarvis-1's storage framework and extend it with two key additions: (1) Critic-generated summaries highlighting key success/failure actions, and (2) success/failure labels from the Completion Validator. This provides actionable guidance with a single LLM call, avoiding A-mem's overhead of three calls for memory creation and evolution.

Creation of the memory. Each memory entry is defined as:

$$M_i = \{g_i, C_i, o, h_i\} \tag{1}$$

where g_i is the option, $C_i \in \{0, 1\}$ is the output of the Completion Validator (see Appendix G.1), o is the observation sequence towards current option, and h_i is the option

Table 1. Baseline vs. TAME progression across three runs of genetic algorithm using Gemini-2.0-Flash, Gemini-3.1-Flash-Lite, GPT-4.1-nano, GPT5-MinimalThinking, and Claude-Haiku-4-5. For full details see Appendix K, L, M, N, and O. *Note: Values are game scores (which are % of overall score).*

Env.	Gemini-2.0-Flash		Gemini-3.1-Flash-Lite		GPT-4.1-nano		GPT-5-Mininal-Thinking		Claude-Haiku-4.5	
	Base	TAME	Base	TAME	Base	TAME	Base	TAME	Base	TAME
Avg.	27.2±2.1	**35.1±2.2**	34.5±2.3	**42.8±2.2**	9.9±1.3	**17.2±1.5**	32.8±2.2	**44.8±2.1**	27.4±2.2	**35.0±2.2**
babayi	58.0±7.0	**72.0±6.7**	76.0±6.0	**94.7±3.3**	32.0±6.6	**48.7±7.1**	80.0±5.7	**85.0±5.0**	68.0±6.6	**74.0±6.2**
babaisai	30.8±4.2	**42.5±4.5**	32.5±4.3	**55.5±4.8**	12.5±3.0	**21.6±3.8**	25.8±4.0	**74.6±3.9**	30.8±4.2	**53.0±4.6**
textworld	32.6±7.0	**33.4±7.2**	32.2±8.4	**34.1±8.5**	0.6±0.6	**2.9±0.9**	30.6±7.0	**30.6±7.0**	30.0±8.4	**39.8±8.3**
crafter	29.1±4.5	**38.2±4.3**	44.1±5.2	**47.9±4.1**	11.8±2.2	**19.8±2.3**	39.1±4.1	**47.3±4.7**	16.8±3.5	**27.6±3.0**
minihack	12.5±5.2	**23.3±6.7**	22.5±6.6	**28.3±7.1**	2.5±2.5	**10.0±2.8**	20.0±7.3	**30.0±7.2**	12.5±5.2	**15.0±5.6**
nle	0.0±0.0	**0.9±0.4**	0.0±0.0	**1.4 ± 0.5**	0.0±0.0	**0.2±0.2**	1.3±0.5	**1.5±0.5**	0.0±0.0	**0.6±0.5**

summary from the Critic (see Appendix G.2). Then, the memory structure is implemented as follows: each memory entry is stored as a vector embedding of the above, enabling efficient similarity-based retrieval. The embedding function ϕ transforms each entry:

$$\mathbf{e}_i = \phi(M_i) \in \mathbb{R}^d \qquad (2)$$

Similarity-Based Filtering. Following the "importance" scoring approach from the generative agents framework (Park et al., 2023), we prevent storage of repetitive experiences. A new memory M_{new} is stored only if:

$$\max_{M_i \in \mathcal{M}} \frac{\mathbf{e}_{new} \cdot \mathbf{e}_i}{||\mathbf{e}_{new}|| \cdot ||\mathbf{e}_i||} \leq 1 - \tau_{cos} \qquad (3)$$

where τ_{cos} is a set constant. This method effectively filters out frequently repeated actions (e.g., "chop wood" in Crafter) that provide limited learning value.

Long-Term Memory Retrieval Mechanism. In order to address the limited context window size, we only extract $k_{succ} + k_{fail}$ best scoring memories at each option execution. Inspired by Retrieval-Augmented Generation (RAG) (Lewis et al., 2021), we enable access to past experiences through the following steps: Query Encoding, Temporal Decay, Memory score, Stratified Retrieval, Context Integration. The details of each step can be found in the Appendix H.

This process gives access to both effective strategies and failure patterns, allowing for informed decision-making. Visualisations of retrieval patterns are shown in Appendix E.

4. Empirical Evaluation

We evaluate our method through three key experiments. First, we benchmark our genetic algorithm across multiple families of models against the SOTA systems on six diverse games and contrast them with the BALROG leaderboard. Second, we demonstrate the transferability of TAME's selected genomes across more complex models of the same

family without additional training. Third, we run ablations on our core components including: human prompts, diversity measure in genetic algorithm, comparison of our memory system against Jarvis-1 and A-mem baselines, and the comparison with Claude-generated prompt. Moreover, we measure the impact of genetic algorithm by contrasting the output of TAME with human-selected combinations of modules.

We evaluate our method on 6 diverse gaming environments included in the BALROG leaderboard. The BALROG leaderboard contains six environments of increasing complexity: BabyAI (grid-based tasks), TextWorld (text-based exploration), Crafter (a Minecraft-like game with 22 achievements), BabaIsAI (a rule-based puzzle game with 40 tasks), MiniHack (less complex version of NetHack with 8 targeted challenges), and the full NetHack Learning Environment - the most demanding of the six, testing navigation, resource management, and long-term planning in an unpredictable, changing world.

4.1. TAME Results

This section compares the baseline and TAME's performance on the six games introduced above. Baseline scores are obtained by evaluating the BALROG arena repository. TAME scores represent the best performance achieved selected by the genetic algorithm (Section 3.3). We run genetic algorithm through $n_{gen} = 4$ iterations, with each iteration producing $n_{child} = 5$ children. We then repeat the genetic algorithm 3 times (2 in the case of GPT5-Minimal Thinking due to resource constraints) and average the results (see detailed results from independent runs in the appendices: K.2, L.2, M.2, N.2, and O.2. Through empirical evaluation we notice that this amount of iterations gives substantial performance gains. Number of episodes per each child evaluation is adapted from BALROG.

As shown in Table 1, TAME consistently outperforms the baseline achieving relative gain of ∼29% for Gemini-2.0-Flash, ∼24% in the case of Gemini-3.1-Flash-Lite, ∼74%

Table 2. Comparison of TAME against top scoring models in BALROG leaderboard (May 2026). Rank improvements are indicated with ↑. *Note: Values are absolute scores (game scores expressed in %), not relative improvements.*

Method	Score (↑)	BALROG Rank (↓)
Gemini-3.1-Pro[Transferred]	**58.56 ± 1.93**	(1) ↑ 2
Gemini-3.1-Pro[SOTA]	58.10 ± 2.10	(2)
Gemini-3.1-Pro[Baseline]	56.88 ± 1.95	(3)
Gemini-2.5-Pro[Transferred]	47.57 ± 2.72	(5) ↑ 2
Gemini-2.5-Pro[Baseline]	43.35 ± 2.31	(7)
Claude-Sonnet-4.6[Transferred]	38.12 ± 2.16	(9) ↑ 1
Claude-Sonnet-4.6[Baseline]	34.21 ± 2.21	(10)
GPT-4.1-mini[Transferred]	26.80 ± 1.92	(19)
GPT-4.1-mini[Baseline]	24.43 ± 1.89	(19)
Gemini-2.5-Flash-Lite[Transferred]	20.48 ± 0.91	(21) ↑ 9
Gemini-2.5-Flash-Lite[Baseline]	11.87 ± 1.32	(30)

in the case of GPT-4.1-nano, ~37% for GPT-5-Minimal-Thinking, and ~28% in the case of Claude-Haiku-4.5. Moreover, TAME improves performance in all the games for all the models, apart from textworld using GPT5-Minimal-Thinking, where it achieves the same performance as baseline. Notably, while the baseline models can hardly gain any noticeable progress on Nethack (the hardest game), TAME achieves consistent improvements. At the time the experiments were compared to the benchmark (May 2026), state-of-the-art BALROG results reached only 6.8% NLE, indicating that absolute scores remain low even for the strongest models. In this regime, small absolute gains correspond to substantial relative improvements. Further results of the performance of initial population $\mathcal{P}_0$ and its comparison to final scores, are available in appendices K.4, L.4, M.4, N.4, and O.4. Figure 10 in the Appendix K.5 demonstrates consistent improvement over the initial population across generations. Per-task details are provided in Appendix. J, along with the examples of final genomes in Appendix W.

Modules activated   As in Figure 17, Appendix K.6.2, module activation from one Gemini-2.0-Flash run suggests that 4 out of 6 environments benefit from hierarchical structure. TextWorld and MiniHack favour simpler configurations, consistent with their observation-dependent dynamics and short episode lengths respectively.

4.2. Transferability of TAME structures

Next, we evaluate whether architectures returned in genetic runs can be effective when transferred to more complex models without the need of retraining. Thus, we use TAME selection to evaluate populations of Gemini-2.5-Flash-Lite, Gemini-2.5-Pro, Gemini-3.1-Pro, GPT-4.1-mini, and Claude-Sonnet-4.6 models to exclusively choose between the base configuration from BALROG or the best-performing structure discovered with less complex model from the same family (for that we use corresponding models from section 4.1). For details see appendices K.6, L.5, M.5, O.5.

From the Table 2, it can be noticed that transferred architectures consistently improve performance across all model families. BabaIsAI benefits most reliably, reflecting TAME's strength in planning-intensive tasks, while TextWorld and MiniHack show least consistent transfer (see K.6, L.5, M.5, O.5). At the model level, non-reasoning models benefit most: Gemini-2.5-Flash-Lite achieves ~73% relative improvement owing to its similarity to Gemini-2.0-Flash. Reasoning models show more moderate but meaningful gains, with Gemini-3.1-Pro achieving SOTA on BALROG. Transferability extends beyond Gemini: GPT-4.1-mini and Claude-Sonnet-4.6 achieve ~10% and ~11% relative improvements respectively, confirming generalisation within model families. Our preliminary experiments suggest cross-family transfer does not hold: transferring a genome evolved on Gemini-2.0-Flash to GPT-4.1-mini resulted in degraded performance relative to the GPT-4.1-mini baseline. We hypothesise this is due to differences in training data, architecture, instruction-following style or prompt sensitivity across model families, where evolved modules implicitly optimise for the response patterns of the source model. We leave a systematic investigation of cross-family transfer as future work.

4.3. Ablation studies

This section details ablation experiments conducted on TAME methodology. First, we run experiments excluding human crafted initial prompts, allowing for only Claude-generated prompts with baseline prompt, thus eliminating human bias in the initial population. In the second ablation, we remove the diversity measure in genetic evaluation. Next, we compare our memory system with two methods: Jarvis and A-mem. Lastly, we measure the impact of genetic algorithm when compared to human-seleted module combinations.

Impact of human crafted prompts.   We test removing human prompts from the initial set, effectively reducing initial population to $\mathcal{P}_0 = \{g_{Baseline}, g_{Full[Claude]}\}$. We con-

Table 3. Ablation studies excluding human prompt (TAME[No-Hum]) and diversity measure (TAME[No-Div]) using Gemini-3.1-Flash-Lite.

Env.	TAME	TAME[No-Hum]	TAME[No-Div]
Average	**42.8 ± 2.2**	42.3 ± 2.2	40.3 ± 2.2
babyai	**94.7 ± 3.3**	94.0 ± 3.4	92.0 ± 3.8
babaisai	**50.3 ± 4.6**	49.2 ± 4.6	49.2 ± 4.6
textworld	34.1 ± 8.5	**43.3 ± 9.0**	32.2 ± 8.4
crafter	**47.9 ± 4.1**	45.0 ± 3.7	44.1 ± 5.2
minihack	**28.3 ± 7.1**	22.5 ± 6.6	22.5 ± 6.6
nle	1.4 ± 0.5	0.0 ± 0.0	**1.6 ± 0.4**

duct this ablation using Gemini-3.0-Flash-Lite and report results from a full evolutionary procedure against TAME. The Table 3 shows that across individual environments. TAME[No-Hum] yields lower performance in all cases except TextWorld - likely because this environment most frequently mutates the baseline prompt. In the remaining environments the drops are generally small, demonstrating that TAME is largely robust to the removal of human bias for most games. The exception is NLE, suggesting that human-crafted initialisation provides valuable insights for the most complex settings. Further details in the Appendix R.

Diversity. Next, we analyse the impact of excluding the diversity component in the genetic algorithm. Therefore, at the end of each genetic iteration, we select only N best performing genomes, instead of N best performing + M most diverse. The results in Table 3 show a clear drop, with TAME[No-Div] scoring 40.3% against 42.8% for TAME. Across all environments the score is lower when excluding diversity, with the exception of NLE where performance marginally increases. These results confirm that the diversity component plays an important role in TAME's effectiveness. Full details in the Appendix S.

Table 4. Ablation studies comparing memory types using Gemini-2.0-Flash.

Env.	Jarvis	TAME-Memory[ours]	A-mem
Average	17.5 ± 1.7	**23.1 ± 1.8**	21.5 ± 1.8
babyai	48.0 ± 7.1	**62.0 ± 6.9**	58.0 ± 7.0
babaisai	24.2 ± 3.9	**29.2 ± 4.2**	26.7 ± 4.0
textworld	0.6 ± 0.6	**8.2 ± 2.0**	4.5 ± 2.4
crafter	19.6 ± 3.8	**35.5 ± 3.2**	26.4 ± 4.3
minihack	**12.5 ± 5.2**	3.5 ± 5.7	**12.5 ± 5.2**
nle	0.3 ± 0.3	0.4 ± 0.3	**0.7 ± 0.4**

Memory types. We ablate our long-term memory system by comparing TAME-Memory against Jarvis-1 and A-mem, using a hierarchical structure with Gemini-2.0-Flash. All three store the same core elements, but TAME extends Jarvis-1 by adding a critic and filtering successful and failed trajectories, while requiring one additional LLM call compared to Jarvis-1, but two fewer than A-mem. As

shown in Table 4, TAME-Memory outperforms both alternatives, demonstrating the value of the critic module while remaining significantly more computationally efficient than A-mem. Further details in the Appendix Q.

Table 5. "Claude Prompt" results with Gemini-2.0-Flash

	Baseline (↑)	ClaudePrompt (↑)	TAME (↑)
Average	27.2 ± 2.1	23.4 ± 1.4	**35.1 ± 2.2**

Comparison of TAME vs Claude-generated prompt. We prompt Claude-Sonnet-4.5 (see T) to improve the baseline prompt, provided with functional inputs (see 3.1). The results in Table 5 with Gemini-2.0-Flash show the difficulty of crafting a single prompt that works well for every environment, further motivating the genetic approach (see Appendix K.1).

Table 6. Scores of initial population for genetic algorithm across models. 'HC' corresponds to 'Human-Crafted' an 'C' corresponds to 'Claude'.

Model	Baseline	Hier[HC]	Full[C]	Full[HC]	TAME
Gemini-2	27.2 ± 2.2	**38.5 ± 1.7**	34.5 ± 1.8	33.9 ± 1.7	35.1±2.2
Gemini-3	34.5 ± 2.3	28.9 ± 1.4	30.9 ± 1.4	28.5 ± 1.3	**42.8±2.2**
GPT-4.1	9.9 ± 1.3	10.4 ± 2.1	11.0 ± 2.8	9.3 ± 2.2	**17.2±1.5**
GPT-5	32.8 ± 2.2	24.2 ± 1.5	26.8 ± 1.6	29.0 ± 1.6	**44.8±2.1**
Claude-4.5	27.4 ± 2.2	20.3 ± 1.5	20.8 ± 1.4	18.7 ± 1.5	**35.0±2.2**

Impact of Genetic Algorithm vs Fixed Module Combinations. We evaluate the benefit of automated module selection via genetic algorithm compared to fixed, human-selected module combinations, which also serve as the initial population for the genetic algorithm. Hier[HC] (Hierarchical, Human-Crafted) uses a curated subset of modules found to be most stable across games, while Full[C] and Full[HC] employ all available modules with Claude-generated and Human-Crafted prompts, respectively (for details see Appendix V.2). As shown in the Table 6, the genetic algorithm gives substantial improvements over all fixed combinations in all settings except Gemini-2.0-Flash. These results demonstrate that, while human-designed seeds provide a strong initialisation, the genetic search consistently uncovers superior configurations.

5. Conclusion and limitations

We presented TAME, a genetic framework for evolving LLM-based agents that is both game-agnostic and adaptive. Through genetic mutations and in-game evaluation, TAME configures human-crafted modules for core gaming skills such as exploration, survival, long-term memory, and loop detection. TAME explores diverse modular configurations, inputs, prompts, and hyperparameters. We also introduced a novel memory system combining the efficiency of embedding retrieval with the contextual depth of LLM-augmented

memory, matching the performance of state-of-art LLM-augmented memory systems in games while reducing the number of LLM calls required to achieve that performance.

We evaluated TAME on the well-established BALROG leaderboard, consisting of 6 diverse gaming environments, finding that it consistently enhances the underlying LLMs, with a limited evolutionary budget of 4 generations and 5 children. We further confirm the importance of long-term memory and adaptive architecture, with our proposed memory system outperforming two existing baselines while remaining more cost-efficient than complex agentic systems. We also present further ablations on our system presenting the diversity component importance, the removal of human bias, and comparison of TAME vs Claude-generated prompt and human-selected module combinations. Furthermore, we demonstrate that solutions discovered on smaller models transfer training-free to larger models of the same family, improving their performance; transferring genomes to Gemini-3.1-Pro we reach 58.56% overall performance in BALROG and outperform the state-of-the-art. This transferability demonstrates that TAME's modular organisation captures functionally meaningful roles that are not tied to any particular underlying version of the model, establishing its compositional structure as a reusable prior over agent behaviour that generalises across model scales.

We note some limitations. We find that TAME provides greater benefits to some games than others, where it defaults to the baseline architecture. We also observed that while TAME improves complex reasoning tasks overall, spatial reasoning remains a weakness. This suggests the potential not only for expanding the set but for genetic discovery of entirely new modules and capabilities, beyond those hand-crafted in this work. While our evaluation was conducted under a constrained computational budget, our results demonstrate that even limited evolutionary search yields substantial performance gains. Moreover, while transferability proved effective, gains were less pronounced for reasoning models, motivating further study of transfer and emergence across different architectures. Finally, future work could explore alternatives for the genetic algorithms, like MAP-Elites, or different approaches such as Bayesian optimisation.

Overall, TAME establishes a new state of the art in game-playing LLM agents, laying the foundation for more better gaming agents.

References

Andres M Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D White, and Philippe Schwaller. Chemcrow: Augmenting large-language models with chemistry tools. *arXiv preprint arXiv:2304.05376*, 2023.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020. URL https://arxiv.org/abs/2005.14165.

Yuri Chervonyi, Trieu H Trinh, Miroslav Olšák, Xiaomeng Yang, Hoang Nguyen, Marcelo Menegali, Junehyuk Jung, Vikas Verma, Quoc V Le, and Thang Luong. Gold-medalist performance in solving olympiad geometry with alphageometry2. *arXiv preprint arXiv:2502.03544*, 2025.

François Chollet. Openai o3 breakthrough high score on arc-agi-pub. https://arcprize.org/blog/oai-o3-pub-breakthrough, December 2024. Accessed: 2025-09-12.

François Chollet, Mike Knoop, Gregory Kamradt, and Bryan Landers. Arc prize 2024: Technical report. *arXiv preprint arXiv:2412.04604*, 2024. URL https://arxiv.org/abs/2412.04604.

Jingliang Duan, Shengbo Eben Li, Yang Guan, Qi Sun, and Bo Cheng. Hierarchical reinforcement learning for self-driving decision-making without reliance on labelled driving data. *IET Intelligent Transport Systems*, 14(5): 297–305, February 2020. ISSN 1751-9578. doi: 10.1049/iet-its.2019.0317. URL http://dx.doi.org/10.1049/iet-its.2019.0317.

Qingyan Guo, Rui Wang, Junliang Guo, Bei Li, Kaitao Song, Xu Tan, Guoqing Liu, Jiang Bian, and Yujiu Yang. Evoprompt: Connecting llms with evolutionary algorithms yields powerful prompt optimizers, 2025. URL https://arxiv.org/abs/2309.08532.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Ceyao Zhang, Jinlin Wang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, et al. Metagpt: Meta

programming for a multi-agent collaborative framework. In *International Conference on Learning Representations, ICLR*, 2024.

Mengkang Hu, Tianxing Chen, Qiguang Chen, Yao Mu, Wenqi Shao, and Ping Luo. Hiagent: Hierarchical working memory management for solving long-horizon agent tasks with large language model, 2024a. URL https://arxiv.org/abs/2408.09559.

Shengran Hu, Cong Lu, and Jeff Clune. Automated design of agentic systems. In *NeurIPS 2024 Workshop on Open-World Agents*, 2024b.

Adam Tauman Kalai, Ofir Nachum, Santosh S. Vempala, and Edwin Zhang. Why language models hallucinate, 2025. URL https://arxiv.org/abs/2509.04664.

Martin Klissarov, Mikael Henaff, Roberta Raileanu, Shagun Sodhani, Pascal Vincent, Amy Zhang, Pierre-Luc Bacon, Doina Precup, Marlos C. Machado, and Pierluca D'Oro. Maestromotif: Skill design from artificial intelligence feedback, 2024. URL https://arxiv.org/abs/2412.08542.

Martin Klissarov, R Devon Hjelm, Alexander T Toshev, and Bogdan Mazoure. On the modeling capabilities of large language models for sequential decision making. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=vodsIF3o7N.

Heinrich Küttler, Nantas Nardelli, Alexander H. Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The nethack learning environment, 2020. URL https://arxiv.org/abs/2006.13760.

Joel Lehman, Jonathan Gordon, Shawn Jain, Kamal Ndousse, Cathy Yeh, and Kenneth O. Stanley. Evolution through large models, 2022. URL https://arxiv.org/abs/2206.08896.

Borja G León, Francesco Riccio, Kaushik Subramanian, Peter R Wurman, and Peter Stone. Discovering creative behaviors through duplex: Diverse universal features for policy exploration. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks, 2021. URL https://arxiv.org/abs/2005.11401.

Zichuan Lin, Junyou Li, Jianing Shi, Deheng Ye, Qiang Fu, and Wei Yang. Juewu-mc: Playing minecraft with sample-efficient hierarchical reinforcement learning, 2021. URL https://arxiv.org/abs/2112.04907.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. Agentbench: Evaluating LLMs as agents. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=zAdUB0aCTQ.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. The ai scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*, 2024.

Zhichao Lu, Ian Whalen, Vishnu Boddeti, Yashesh Dhebar, Kalyanmoy Deb, Erik Goodman, and Wolfgang Banzhaf. Nsga-net: neural architecture search using multi-objective genetic algorithm. In *Proceedings of the genetic and evolutionary computation conference*, pages 419–427, 2019.

Yecheng Jason Ma, William Liang, Guanzhi Wang, De-An Huang, Osbert Bastani, Dinesh Jayaraman, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Eureka: Human-level reward design via coding large language models, 2024. URL https://arxiv.org/abs/2310.12931.

MiniHack Team. Battle environments. MiniHack Documentation. URL https://minihack.readthedocs.io/en/latest/envs/navigation/battle.html. Accessed: 2025-09-15.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning, 2013. URL https://arxiv.org/abs/1312.5602.

Davide Paglieri, Bartłomiej Cupiał, Samuel Coward, Ulyana Piterbarg, Maciej Wolczyk, Akbir Khan, Eduardo Pignatelli, Łukasz Kuciński, Lerrel Pinto, Rob Fergus, Jakob Nicolaus Foerster, Jack Parker-Holder, and Tim Rocktäschel. Balrog: Benchmarking agentic llm and vlm reasoning on games, 2025. URL https://arxiv.org/abs/2411.13543.

Ruwei Pan, Hongyu Zhang, and Chao Liu. Codecor: An llm-based self-reflective multi-agent framework for code generation. *arXiv preprint arXiv:2501.07811*, 2025.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior, 2023. URL https://arxiv.org/abs/2304.03442.

Bharat Prakash, Tim Oates, and Tinoosh Mohsenin. Llm augmented hierarchical agents, 2023. URL https://arxiv.org/abs/2311.05596.

J Rosser and Jakob Nicolaus Foerster. Agentbreeder: Mitigating the ai safety impact of multi-agent scaffolds via self-improvement. *arXiv preprint arXiv:2502.00757*, 2025.

Mikayel Samvelyan, Robert Kirk, Vitaly Kurin, Jack Zhang, Shimon Jiang, and Jakob Foerster. Minihack the planet: A sandbox for open-ended reinforcement learning research. *arXiv preprint arXiv:2109.13202*, 2021.

Mikayel Samvelyan, Sharath Chandra Raparthy, Andrei Lupu, Eric Hambro, Aram Markosyan, Manish Bhatt, Yuning Mao, Minqi Jiang, Jack Parker-Holder, Jakob Foerster, et al. Rainbow teaming: Open-ended generation of diverse adversarial prompts. *Advances in Neural Information Processing Systems*, 37:69747–69786, 2024.

Bidipta Sarkar, Mattie Fellows, Juan Agustin Duque, Alistair Letcher, Antonio León Villares, Anya Sims, Dylan Cope, Jarek Liesen, Lukas Seier, Theo Wolf, et al. Evolution strategies at the hyperscale. *arXiv preprint arXiv:2511.16652*, 2025.

Yu Shang, Yu Li, Keyu Zhao, Likai Ma, Jiahe Liu, Fengli Xu, and Yong Li. Agentsquare: Automatic llm agent search in modular design space. In *The Thirteenth International Conference on Learning Representations*, 2024.

Kenneth O Stanley, Jeff Clune, Joel Lehman, and Risto Miikkulainen. Designing neural networks through neuroevolution. *Nature Machine Intelligence*, 1(1):24–35, 2019.

Richard S. Sutton, Doina Precup, and Satinder Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1-2):181–211, 1999.

Weihao Tan, Wentao Zhang, Shanqi Liu, Longtao Zheng, Xinrun Wang, and Bo An. True knowledge comes from practice: Aligning llms with embodied environments via reinforcement learning, 2024. URL https://arxiv.org/abs/2401.14151.

DeepMind Team. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575:350–354, 2019. doi: 10.1038/s41586-019-1724-z.

MiniHack Team. Minihack: Corridor environment, 2024. URL https://minihack.readthedocs.io/en/latest/envs/navigation/corridor.html. Accessed: September 15, 2025.

Amala Mary Vincent and P Jidesh. An improved hyperparameter optimization framework for automl systems using evolutionary algorithms. *Scientific Reports*, 13(1):4737, 2023.

Ke Wang, Houxing Ren, Aojun Zhou, Zimu Lu, Sichun Luo, Weikang Shi, Renrui Zhang, Linqi Song, Mingjie Zhan, and Hongsheng Li. Mathcoder: Seamless code integration in llms for enhanced mathematical reasoning. In *The Twelfth International Conference on Learning Representations, ICLR*, 2024a.

Zihao Wang, Shaofei Cai, Anji Liu, Yonggang Jin, Jinbing Hou, Bowei Zhang, Haowei Lin, Zhaofeng He, Zilong Zheng, Yaodong Yang, Xiaojian Ma, and Yitao Liang. Jarvis-1: Open-world multi-task agents with memory-augmented multimodal language models, 2023. URL https://arxiv.org/abs/2311.05997.

Zihao Wang, Shaofei Cai, Anji Liu, Yonggang Jin, Jinbing Hou, Bowei Zhang, Haowei Lin, Zhaofeng He, Zilong Zheng, Yaodong Yang, et al. Jarvis-1: Open-world multi-task agents with memory-augmented multimodal language models. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024b.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. *arXiv preprint arXiv:2201.11903*, 2022.

Jan Wohlke, Felix Schmitt, and Herke van Hoof. Hierarchies of planning and reinforcement learning for robot navigation. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, page 10682–10688. IEEE, May 2021. doi: 10.1109/icra48506.2021.9561151. URL http://dx.doi.org/10.1109/ICRA48506.2021.9561151.

Wujiang Xu, Kai Mei, Hang Gao, Juntao Tan, Zujie Liang, and Yongfeng Zhang. A-mem: Agentic memory for llm agents, 2025. URL https://arxiv.org/abs/2502.12110.

John Yang, Carlos E Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. Swe-agent: Agent-computer interfaces enable automated software engineering. *Advances in Neural Information Processing Systems*, 37:50528–50652, 2024.

Siyu Yuan, Kaitao Song, Jiangjie Chen, Xu Tan, Dongsheng Li, and Deqing Yang. Evoagent: Towards automatic multi-agent generation via evolutionary algorithms. In *NeurIPS 2024 Workshop on Open-World Agents*, 2024.

Tom Zahavy, Yannick Schroecker, Feryal Behbahani, Kate Baumli, Sebastian Flennerhag, Shaobo Hou, and Satinder Singh. Discovering policies with domino: Diversity optimization maintaining near optimality. *arXiv preprint arXiv:2205.13521*, 2022.

Guibin Zhang, Luyang Niu, Junfeng Fang, Kun Wang, LEI BAI, and Xiang Wang. Multi-agent architecture search via agentic supernet. In *Forty-second International Conference on Machine Learning*, 2025.

Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng, Xiong-Hui Chen, Jiaqi Chen, Mingchen Zhuge, Xin Cheng, Sirui Hong, Jinlin Wang, et al. Aflow: Automating agentic workflow generation. In *The Thirteenth International Conference on Learning Representations*, 2024.

A. BALROG Game Details

The BALROG framework incorporates six distinct gaming environments, each designed to evaluate specific aspects of agentic reasoning (Figure 3):

BabyAI   BabyAI is a grid-based environment with different difficulty levels. The agent is presented wth five different tasks.

TextWorld   TextWorld offers a text-based exploration environment where agents interact exclusively through natural language commands. There are three different tasks.

Crafter   Crafter simulates a Minecraft-inspired environment where progression is measured through 22 distinct achievements.

BabaIsAI   BabaIsAI presents a rule-based puzzle environment where agents must navigate grid-based scenarios. There are 40 different tasks.

MiniHack   MiniHack represents a task-oriented version of the classic NetHack (Küttler et al., 2020) game, evaluating agents across eight challenges testing different skills.

NetHack Learning Environment (NLE)   NLE implements the complete NetHack roguelike game, presenting the most comprehensive challenge within the benchmark. This environment simultaneously evaluates navigation, survival instincts, long-term strategic planning, resource management, and exploration skills within an unpredictable, dynamically evolving game state.

Skills	BabyAI	TextWorld	Crafter	Baba Is AI	MiniHack	NLE
Navigation	✔	✔	✔	✔	✔	✔
Exploration	✔	✔	✔	✔	✔	✔
Resource Management	✗	✔	✔	✗	✔	✔
Complex Credit Assignment	✗	✗	✔	✔	✔	✔
Deducing Env. Dynamics	✗	✗	✗	✔	✔	✔
Long-term Planning	✗	✗	✗	✔	✔	✔
Turns to Complete	10^1	10^2	10^3	10^2	10^2	10^4–10^5
Time to Master for Humans	Seconds	Minutes	Hours	Hours	Hours	Years

Figure 3. Game environments overview. Adapted from BALROG (Paglieri et al., 2025)

B. Metric scores

We adapt metric scores from BALROG to quantify how close an agent is to completing each task. All scores are normalised to a range of 0–100. The scoring scheme varies by environment. In MiniHack, BabyAI, and BabaIsAI, tasks give binary scores: either 0 (failure) or 100 (success). In contrast, TextWorld, Crafter, and NetHack return continuous scores between 0 and 100, where the score represents the proportion of achievements completed. For NetHack specifically, the authors of BALROG introduced a novel scoring system based on data-informed metrics. Authors derived scores from the probability of a human player winning the game after reaching a particular dungeon level or experience level. The authors argue that this metric better captures meaningful progression than previous metrics in that game. We adopt the same procedure for NetHack in our work.

B.1. Error calculation

For each environment, we report the mean score μ and standard deviation σ computed across K independent episodes:

$$\mu = \frac{1}{K}\sum_{k=1}^{K} x_k, \qquad \sigma = \sqrt{\frac{1}{K-1}\sum_{k=1}^{K}(x_k - \mu)^2} \tag{4}$$

where x_k is the score of episode k.

When aggregating results across N environments, we compute a combined uncertainty estimate. Given per-environment standard deviations $\sigma_1, \ldots, \sigma_N$:

$$\sigma_{\text{agg}} = \sqrt{\frac{1}{N}\sum_{i=1}^{N}\sigma_i^2 \cdot \frac{1}{\sqrt{N}}} \tag{5}$$

C. Hyperparameters selected

This Appendix details the choice of hyperparameters in our methodology. Table 7 details the values and descriptions.

The genetic algorithm optimises four hyperparameters: τ_{cos}, λ, ϵ_0, and T. We establish lower bounds of 0 for τ_{cos}, λ, and ϵ_0, effectively disabling these components when not beneficial to performance. Upper bounds were determined in order to maintaini sufficient search space for optimisation.

The language model temperature T follows standard practice with a default value of 1.0, allowing the genetic algorithm to explore a range of solutions. We implement exponential decay for ϵ_t following established reinforcement learning approaches, enabling the transition from exploration to exploitation as the system learns optimal behaviours. We follow the short term memory length in BALROG and set it to $m = 16$. We set $k_{succ} = 5$ and $k_{fail} = 5$, limiting the number of information added to the prompt, but also adding significant amount of past experiences; through empirical evaluation we notice that a higher number of memories added is not beneficial.

Following DOMiNO methodology, we set $\alpha = 0.7$ to ensure meaningful population diversity whilst maintaining performance standards. Our similarity-recency weighting ($w_{\text{similarity}} = 0.7$, $w_{\text{recency}} = 0.3$) prioritises semantic relevance over temporal proximity, reflecting the hypothesis that content similarity is more beneficial than recency.

The genetic algorithm parameters balance computational efficiency with solution quality. We set probability of selecting single parent in genetic algorithm to be 70% (vs two parents to be 30%), allowing for more mutations without crossover operations. We set $n = 4$ iterations as empirical evaluation demonstrated satisfactory performance is achieved at this point, providing an effective balance between solution quality and computational cost. Population management parameters $N = M = 5$ maintain an optimal balance between preserving high-performing solutions and promoting genetic diversity, following established evolutionary computation principles that prevent premature convergence whilst ensuring computational tractability.

Resource requirements The approximate time needed to run a full genetic algorithm is 24 hours using 30 workers running on 30 CPU cores. Therefore, the 3 independent runs take approximately 3 days.

D. BALROG baseline configurations

This section details number of episodes and their length per each BALROG game. Moreover, we show the BALROG prompt that we use as initial seed for the baseline architecture.

Episode details Table 8 details the episode specifications per game. The table shows time needed for each episode completion, as well as details on number of tasks per different environments.

Table 7. Hyperparameter values used in the TAME framework

Parameter	Value	Description
Embedding	`all-MiniLM-L6-v2`	Pre-trained sentence embedding model used for semantic similarity calculations
d	384	Dimension of the embedding
$\tau_{\cos}$	$[0, 0.1]$	Cosine similarity threshold parameter
λ	$[0, 0.1]$	Long-Term Memory decay factor
ϵ_0	$[0, 0.1]$	Initial exploration parameter
T	$[0.1, 2]$	Language Model Temperature
ϵ_t	$0.99^t \times \epsilon_0$	Time-decayed parameter following exponential decay
m	16	Short-term memory length (most recent action-observation pairs)
$k_{success}$	5	Number of top scoring successful long-term memories added to the LLM prompt
k_{fail}	5	Number of top scoring failed long-term memories added to the LLM prompt
α	0.7	Minimum fraction of highest scoring genome for diversity
$w_{\text{similarity}}$	0.7	Weight assigned to similarity component in scoring
w_{recency}	0.3	Weight assigned to recency component in scoring
p_{single}	70%	Percentage chance to choose single parent for reproduction
$1 - p_{single}$	30%	Percentage chance to choose two parents for reproduction
n_{gen}	4	Number of iterations (parent population creation) of genetic algorithm
n_{child}	5	Number of children created for each population of parents in genetic algorithm
N	5	Number of best scoring genomes saved at each step of genetic algorithm
M	5	Number of most diverse genomes saved at each step of genetic algorithm (scoring at least α fraction of top performing genome)
n_{ep}	dependent on the game	Number of episodes for each child evaluation. Details in the Table 8

Table 8. Episode details per BALROG game

Environment	Evals	Tasks per Eval	Total	Episode Length
BabyAI	10	5	50	10^1
BabaIsAI	3	40	120	10^2
Crafter	10	1	10	10^3
TextWorld	10	3	30	10^2
MiniHack	5	8	40	10^2
NetHack	5	1	5	$10^4 - 10^5$

Baseline Prompt (BALROG)   Below we present a prompt from BALROG (Paglieri et al., 2025) paper, used for Baseline evaluation.

Baseline BALROG Prompt

```
"""You always have to output one of the above actions at a time and no other text. You always have to output an action until
    ↪ the episode terminates."""
```

E. Testing the retrieval mechanism of long-term memory system

In this section we test the retrieval of saved memories and the abilities to act upon them. Due to stochasticity, we need to have a reliable comparison. We focus our evaluation on Crafter, as it is an environment requiring long-term planning, giving motivation to log-term memory approach. We disable life hazards such as zombies and skeletons, as they are not relevant to the testing subject. We set random seed to 32 for all episodes.

To evaluate our information-retrieval mechanism, we test a long-horizon "craft iron sword" task in Crafter. We replace the environment's default objective with the production of an iron sword (see Appendix E.1.1). This task is intentionally complex: it requires chopping wood, crafting and placing a crafting table, crafting a wooden pickaxe, collecting stone, crafting a stone pickaxe, placing a furnace adjacent to the crafting table, collecting iron, and finally crafting an iron sword. We selected this objective because, in prior baseline runs without our memory system, the agent never completed the task. Through the episode we would like to check if memories are activated at relevant time steps, showing retrieval ability. Moreover, successful completion under our system provides strong evidence that the memory-critic architecture supports multi-step planning and sequential options.

In order to track the memories activated, we inject five task-oriented memories at the start of each episode: "craft wooden pickaxe", "craft stone pickaxe", "mine iron", "place furnace", and "craft iron sword" (see Appendix E.1.2). Each memory is paired with a human-crafted critic that summarises the steps needed to achieve particular option. During each episode we log when each memory activates. An example progression through episode is provided in Figure 4 and the corresponding memories activated can be seen in Figure 5.

(a) step 35	*(b)* step 55	*(c)* step 85	*(d)* step 135	*(e)* step 225

Figure 4. Testing memory retrieval: Task progression across episode: (a) agent crafts wood pickaxe, (b) agent crafts stone pickaxe, (c) agent collects iron, (d) agent collects iron, (e) agents attempts to craft iron sword

Discussion of the example: From Figure 5 we can notice that all memories are activated at the beginning. This is due to the fact that very early in the game, those are they only memories present. We can then see that "Craft Wood Pickaxe" and "Craft Stone Pickaxe" are heavily retrieved until around 25th-60th step. This is when agent completed "Craft Stone

Figure 5. Testing memory retrieval: memories activated based on the step

Pickaxe task" (agent completes "Craft Wood Pickaxe" task earlier, but due to similarity of those two tasks, it it activated when focusing on stone version). "Mine Iron" memory activates two times between 80-100 steps, when agent is mining two pieces of iron. "Craft Iron Sword" appears often around step number 100 which is when agent first attempts to complete it, but realises that it needs to place a furnace and table first. Then the memory is activated later as well, which is after placing table and furnace and attempting to craft iron sword. Unfortunately, agent is unsuccessful because it didn't place furnace close enough to the table. This experiment demonstrates that relevant memories are activated at the right time, and that agent is able to act upon them. Also, when not needed (i.e. the task is completed), memories are activated far less often. It is also important to notice that the "Craft Iron Sword" memory continues to be retrieved even towards the end of the episode when the agent is actively attempting this task. This indicates that the memory system maintains access to relevant historical experiences throughout the entire episode, regardless of when they were initially formed.

Results Across 10 independent runs the agent succeeded in producing an iron sword in 1/10 episodes (baseline: 0% from all previous runs that we did with Gemini-2.0-Flash). This is a substantial improvement, which suggests that when memories are stored, agent is able to retrieve them, and act upon them. This is a simplified case, as we provided human crafted memories, but with the right prompting we believe that the critic module will be able to reproduce those. Additional observations:

- Memories reliably activated when their prerequisites were satisfied and were deactivated after the corresponding option was completed.

- The specificity of the critic strongly affected performance. For example, phrasing a critic as "place the furnace next to the crafting table" versus "place the furnace adjacent to the table" produced different success scores. This highlights the value of precise, action-oriented critic definitions that focus on the key state features leading to success or failure. Following on that we prompted the critic accordingly.

- This experiment also demonstrates the difficulty of the "Craft Iron Sword" task, even when given with clear instructions agent fails 90% of the time.

E.1. Testing memory retrieval prompts

This subsection details prompts used in order to test long-term memory retrieval. First we show the prompt detailing the goal of iron sword creation, then we show memories added at the beginng of the episode: *Craft Wood Pickaxe, Craft Stone Pickaxe, Craft Stone Sword, Mine Iron, Place Furnace, Create Iron Sword*. Those are hand-crafted memories, designed in order to track memory retrieval.

E.1.1. IRON SWORD GOAL PROMPT

This subsection details the prompt for Craft Iron Sword goal that the agent is tasked with during the long-term memory retrieval experiment.

Craft Iron Sword Goal

```
    """ You are playing Crafter. The following are the only valid actions you can take in the game, followed by a short
    ↪ description of each action:

{action_strings}.
Your goal is to craft an iron sword. """
```

E.1.2. INJECTED MEMORIES

This subsection details the memories added at the beggining of the episode, in order to track memory retrieval.

Craft Wood Pickaxe Memory

```
craft_wood_pickaxe = {
"name": "Craft Wood Pickaxe",
"description": "Craft Wood Pickaxe for gathering stone",
"subgoal_prerequisites": "Agent has 1 piece of wood in inventory and table is placed",
"success_condition": "Wood Pickaxe is in inventory",
"subgoal_progress_indicators": "Agent is gathering wood near table",
"subgoal_penalty_component": "Agent crafts pickaxe without enough wood",
"status": 'successful',
"summary of the run": "Agent collects three pieces of wood and places a table in a clear spot. Then agent crafts a wood
    ↪ pickaxe at the table.",
}
```

Craft Stone Pickaxe Memory

```
stone_pickaxe_memory = {
"name": "Craft Stone Pickaxe",
"description": "Craft Stone Pickaxe",
"subgoal_prerequisites": "Agent has 1 piece of stone and 1 piece of wood in inventory and table is placed",
"success_condition": "Stone Pickaxe is in inventory",
"subgoal_progress_indicators": "Agent is gathering stone near table",
"subgoal_penalty_component": "Agent crafts pickaxe without enough resources",
"status": 'successful',
"summary of the run": "Agent collects four pieces of wood and places a table in a clear spot. Then agent collects one piece
    ↪ of stone using wood pickaxe. Then agent crafts a stone pickaxe at the table.",
}
```

Craft Stone Sword Memory

```
stone_sword_memory = {
"name": "Craft Stone Sword",
"description": "Craft Stone Sword for combat",
"subgoal_prerequisites": "Agent has 1 piece of stone and 1 piece of wood in inventory and table is placed",
"success_condition": "Agent has stone sword in inventory",
"subgoal_progress_indicators": "Agent has 1 pieces of stone and 1 piece of wood",
"subgoal_penalty_component": "Agent crafts sword without enough resources",
"status": 'successful',
"summary of the run": "Agent collects 4 pieces of wood. Then agent places a table and crafts a wood pickaxe. Lastly, agent
    ↪ uses wood pickaxe to craft 2 pieces of stone and crafts a stone sword at the table.",
}
```

Mine Iron Memory

```
mine_iron = {
"name": "Mine Iron",
"description": "Mine Iron",
"subgoal_prerequisites": "Agent has 1 wood pickaxe in inventory",
"success_condition": "Wood Pickaxe is in inventory",
"subgoal_progress_indicators": "Agent is gathering iron near table or furnace",
"subgoal_penalty_component": "Agent iron sword without enough resources",
"status": 'failed',
"summary of the run": "Agent repeatedly tried 'Do' action using pickaxe near iron but fails to collect iron. It is
    ↪ recommended agent tries using different tool.",
}
```

Place Furnace Memory

```
furnace_memory = {
    "name": "Place Furnace next to Table",
    "description": "Place furnace next to the Table for crafing iron tools",
    "subgoal_prerequisites": "Agent has 4 pieces of stone in inventory. Table is placed. ",
    "success_condition": "Furnace is placed",
    "subgoal_progress_indicators": "Agent is gathering stone",
    "subgoal_penalty_component": "Agent places furnace in unsuitable location or without enough stone",
    "status": 'successful',
    "summary of the run": "Agent placed a furnace next to the table using 4 pieces of stone. ",
}
```

Craft Iron Sword Memory

```
iron_sword_memory = {
"name": "Craft Iron Sword",
"description": "Craft Iron Sword",
"subgoal_prerequisites": "Agent has 1 piece of stone, 1 piece of wood, 1 piece of coal in inventory and table and furnace is
    ↪ placed next to each other",
"success_condition": "Iron Pickaxe is in inventory",
"subgoal_progress_indicators": "Agent is gathering iron near table and furnace",
"subgoal_penalty_component": "Agent iron sword without enough resources",
"status": 'successful',
"summary of the run": "Agent collects 1 piece of stone and one piece of wood using wood pickaxe. Then agent collects one
    ↪ piece of iron using stone pickaxe. Then agent crafts an iron sword next to the table and furnace.",
}
```

F. Examples of modules outputs

This section shows examples of amygdala and explorer modules behaviours.

F.1. Amygdala module

This section details Amygdala module. First, we show default survival option, then we illustrate an example of amygdala in the episode (using Crafter environment).

Default survival option   The prompt below shows default survival option, that agent is switching to, whenever danger is encountered.

Default Survival Option

```
    subgoal =  {
    "name" : "respond to danger",
    "description": "Respond to danger.",
    "prerequisites": "Agent is in immediate danger",
    "success_condition": "Agent has eliminated the danger",
    "penalty_component": "Agent is not responding to danger.",
    "progress_indicators": "Agent is closer to eliminating the danger",
    "estimated_priority": "high"
}
```

Amygdala module activation.   Here, we present an example from Crafter when amygdala is activated. The agent is initially focused on exploring the environment and fulfilling subgoals such as placing plants. However, in the early stages of the game, a skeleton appears. As soon as the agent observes the skeleton within its field of view, it activates survival mode.

After survival mode is activated, the agent begins gathering resources for combat:

1. Chops down wood

2. Places a crafting table

3. Creates a wooden sword necessary for the fight

The agent then chases the skeleton, and once it is adjacent to the enemy, it initiates combat. During the chase and fight, the agent loses health but successfully manages to defeat the skeleton. Shortly afterwards, the amygdala is deactivated and the agent returns to working towards general game objective. The illustration of the behaviour can be seen in Figure 6.

(a) Amygdala activated   *(b)* Creation of the table   *(c)* Creation of the sword

(d) Chasing the skeleton   *(e)* Fighting the skeleton   *(f)* Amygdala deactivated

Figure 6. Amygdala survival response sequence: (a) activation, (b)&(c) resource gathering, (d)&(e) combat, (f) deactivation.

F.2. Explorer

In this section we show an example of exploration plan proposed by Explorer.

```
{'reasoning': 'The agent needs to break out of its repetitive westward
movement and explore new areas, prioritizing resource gathering and
different directions. Sand has been identified as a new area to explore.',
'subgoals': [
  {'name': 'Move Towards Sand',
   'description': 'Move towards the sand to the south-east to explore
   new terrain.',
   'prerequisites': '',
   'success_condition': 'Agent is standing on sand.',
   'penalty_component': 'Moving in the opposite direction (North or West)
   for more than 3 steps without collecting resources.',
   'progress_indicators': 'Decreasing distance to sand in long_term_context.',
   'estimated_priority': 'high'},
  {'name': 'Explore Area Around Sand',
   'description': 'Once on the sand, explore in all directions (North, South,
   East, and West) to discover resources and new landmarks.',
   'prerequisites': 'Agent is standing on sand.',
   'success_condition': 'Agent has moved at least 3 steps in each cardinal
   direction from the sand.',
   'penalty_component': 'Staying within the same 3x3 area on the sand for
   more than 5 steps.',
```

```
    'progress_indicators': 'Number of unique tiles visited around the sand.',
    'estimated_priority': 'medium'}
]}
```

G. Modular blueprints

As anticipated through Section 3, inspired by how Eureka improved its ability to find better reward functions by starting from a human-crafted set of prior, TAME incorporates a set of human-crafted modules that target essential capabilities for agents in interactive games. The remaining of this section details such components. We remind the reader than $s_t^{mc}, s_t^{lc}, s_t^{cv}, s_t^c, s_t^e, s_t^a, s_t^{ld}$ used in sections below, represent subsets of s_t selected by the genetic algorithm for corresponding modules. For details on the hand-crafted LLM prompts used as initial seeds we refer the reader to Appendix V.

G.1. Hierarchical planning

The hierarchical module consists of three main components illustrated in Figure 2: Meta-Controller suggests sequence of options, Low-Level Executor performs a sequence of actions towards each option, and Completion Validator judges if an option has been completed successfully or failed. All components are described in details below.

Meta-Controller. The Meta-Controller decomposes the game objective into a more manageable sequence of options. Specifically, it implements $\pi_{\text{high}} : S \rightarrow \mathcal{G}$, mapping the current state to an ordered sequence of options:

$$g = \pi_{high}(s_t^{mc}) = \text{LLMprompt}_{high}(s_t^{mc}) = (g_1, g_2, \dots) \tag{6}$$

Each option g_i consists of the fields: *name*, *description*, *prerequisites*, *success conditions*, *penalty component*, *progress indicators*, *estimated priority*.

Low-level Executor. This system implements $\pi_{\text{low}} : S \rightarrow A$, producing an action sequence based on the current state information provided s_t^{le}:

$$a = \pi_{low}(s_t^{le}) = \text{LLMprompt}_{low}(s_t^{le}) = (a_1, a_2, \dots) \tag{7}$$

where the length of the sequence is decided by the Low-level Executor.

Completion Validator. The Completion Validator implements the binary classifier $\varphi : S \rightarrow \{0, 1\}$, determining whether an option has been completed:

$$C_i = \varphi(s_t^{cv}) = \text{LLMprompt}_{\varphi}(s_t^{cv}) \in \{0, 1\}. \tag{8}$$

Here $C_i = 1$ indicates successful termination.

G.2. Skill-Specific Modules

On top of the hierarchical structure, we identify *survival* and *exploration* as two key components in many video games. Moreover, we identify looping behaviour as a significant LLM limitation. All three modules are illustrated in Figure 2.

Explorer. Let explorer be defined as a function $\pi_{explorer} : S \rightarrow \mathcal{G}_{\text{explore}}$, where $\mathcal{G}_{\text{explore}}$ is the set of exploration-oriented options, and:

$$g^{exp} = \pi_{\text{explorer}}(s_t^e) = \text{LLM}_{\text{explorer}}(s_t^e) \tag{9}$$

where $g^{exp} = \{g_1^{\text{exp}}, g_2^{\text{exp}}, \dots, g_k^{\text{exp}}\}$ is the sequential exploration plan, and each g_i^{exp} is structured identically to regular options but prompted for discovery rather than game goal completion.

- Exploration Strategy: We implement an ϵ-greedy exploration strategy where the Meta-controller selection becomes:

$$\text{Controller}(s_t) = \begin{cases} \pi_{\text{explorer}}(s_t^e), & \text{w.p. } \epsilon_t \\ \pi_{\text{high}}(s_t^{mc}), & \text{w.p. } 1 - \epsilon_t \end{cases} \tag{10}$$

$$\text{where } \epsilon_t = 0.99 \times \epsilon_{t-1} = 0.99^t \times 0.1$$

Amygdala. Let $\sigma : S \to \{0, 1\}$ be the amygdala function mapping observations to binary classification of danger assessment:

$$D_i = \sigma(s_t^a) = \text{LLM}_{\text{amygdala}}(s_t^a) \tag{11}$$

At each Low-Lever Executor step, if $D_i = 1$, the system immediately activates a "survival option" (see Appendix F.1 for details); otherwise, normal execution continues.

Loop Detector. The loop detector implements $\psi : S \to \{0, 1\}$, detecting repetitive behavior in recent execution history:

$$L_i = \psi(s_i^{ld}) = \text{LLMprompt}_\psi(s_i^{ld}) \in \{0, 1\}. \tag{12}$$

Where $L_i = 1$ means looping behaviour is detected.

Critic. The Critic module is a function $\rho : S \times \{0, 1\} \to \mathcal{T}$, mapping the state and recent option outcome from Completion Validator to text:

$$h_i = \rho(s_t^c, C_i) = \text{LLMprompt}_\rho(s_t^c) \tag{13}$$

where the text aims to summarise the key factor that led to the success or failure of the option.

H. Detailed Long-Term Memory Retrieval Mechanism.

In order to address the limited context window size, we only extract $k_{succ} + k_{fail}$ best scoring memories at each option execution. Inspired by Retrieval-Augmented Generation (RAG) (Lewis et al., 2021), we enable access to past experiences through the following steps:

- *Query Encoding*: The new option name (n_{g_i}) and description (d_{g_i}) are embedded into the same vector space as stored memories using sentence embeddings:

$$\mathbf{q}_i = \phi(n_{g_i}, d_{g_i}) \in \mathbb{R}^d \tag{14}$$

- *Temporal Decay*: Following A-mem (Xu et al., 2025), we prioritise recent experiences using exponential decay:

$$w(e_t) = \exp(-\lambda \cdot t) \tag{15}$$

  where t is the time elapsed since memory creation.

- *Memory score*: We combine similarity and recency through weighted sum:

$$\begin{aligned} \text{score}(\mathbf{q_i}, \mathbf{e_j}) = {} & w_{similarity} \cdot \text{sim}(\mathbf{q_i}, \mathbf{e_j}) \\ & + w_{recency} \cdot w(\mathbf{e_j}) \end{aligned} \tag{16}$$

- *Stratified Retrieval:* The system retrieves top-k successful and failed memories:

$$M_i^+ = \text{Top-}k_{succ}(\text{score}(\mathbf{q_i}, \mathbf{e_j}) : \varphi_i = 1) \tag{17}$$

$$M_i^- = \text{Top-}k_{fail}(\text{score}(\mathbf{q_i}, \mathbf{e_j}) : \varphi_i = 0) \tag{18}$$

  where φ_j indicates success/failure of memory j.

- *Context Integration:* All $k_{succ} + k_{fail}$ retrieved memories are integrated into the modules prompts (modules including memory are decided by genetic algorithm).

This process gives access to both effective strategies and failure patterns, allowing for informed decision-making. Visualisations of retrieval patterns are shown in Appendix E.

I. Detailed genetic algorithm

In this Appendix we present the detailed specifications of the genetic algorithm.
Parameter selection:

$$\text{Generations} = 4 \tag{19}$$

$$\text{Population size} = |\mathcal{P}_{\text{diverse}}| + |\mathcal{P}_{\text{best}}| = 5 + 5 = 10 \tag{20}$$

$$\text{Children per generation} = 5 \tag{21}$$

$$p_{\text{binary}} = p_{\text{continuous}} = p_{\text{prompt}} = 0.5 \tag{22}$$

where:

- **Generations** – the number of evolutionary iterations performed

- **Population size** – the total number of genomes maintained across diverse and best-performing subpopulations

- **Children per generation** – the number of new offspring genomes created through mutation in each generation

- $p_{\text{binary}}, p_{\text{continuous}}, p_{\text{prompt}}$ – the probabilities of applying binary, continuous, or prompt mutation operations, respectively, when creating offspring.

The number of generations was limited to four due to the significant computational cost and long runtimes associated with evaluating each genome, particularly in environments like NetHack. However, this was sufficient to demonstrate a clear performance improvement and allow for the discovery of specialised architectures.

Parent Selection   Parent selection follows roulette wheel selection (a probabilistic parent-picking method where each individual's chance of being chosen is proportional to its fitness score) with fitness-proportionate probabilities:

$$P(\mathbf{g}_i) = \frac{f(\mathbf{g}_i)}{\sum_{j=1}^{|\mathcal{P}|} f(\mathbf{g}_j)}$$

where $f(\mathbf{g}_i)$ is the fitness score of genome $\mathbf{g}_i$.

Offspring Generation   For each child $\mathbf{g}_{\text{child}}$:

- With probability p_{single}: select one parent

- With probability $1 - p_{single}$: select two parents

For each genome component, evolutionary operations are applied with probability $p_{binary}, p_{continuous}, p_{prompt}$, depending on the component. Otherwise parent attributes are copied directly. In the two-parent case, the parent from which to copy each attribute is chosen with Bernoulli(0.5) probability.

I.1. Genetic operations

This subsection focuses on methodology of crossover and mutations operations.

Modules Operations   Single parent:

$$b_i^{(child)} = \begin{cases} b_i^{(parent)} & \text{with probability } 0.8 \\ 1 - b_i^{(parent)} & \text{with probability } 0.2 \end{cases}$$

Two parents:

$$b_i^{(child)} = \begin{cases} b_i^{(p1)} = b_i^{(p2)} & \text{with probability } 0.9 \text{ if } b_i^{(p1)} = b_i^{(p2)} \\ 1 - b_i^{(p1)} & \text{with probability } 0.1 \text{ if } b_i^{(p1)} = b_i^{(p2)} \\ \text{Bernoulli}(0.5) & \text{if } b_i^{(p1)} \neq b_i^{(p2)} \end{cases}$$

Hyperparameter Operations The continuous value inheritance depends on parent activity states. Let $A_i^{(pk)}$ indicate if feature i is active in parent k:

For single parent:

$$c_i^{(child)} = \text{clip}(c_i^{(parent)} + \mathcal{N}(0, \sigma^2), c_{i,\min}, c_{i,\max})$$

For two parents:

$$c_i^{(child)} = \begin{cases} c_i^{(p1)} + \mathcal{N}(0, \sigma^2) & \text{if } A_i^{(p1)} = 1, A_i^{(p2)} = 0 \\ c_i^{(p2)} + \mathcal{N}(0, \sigma^2) & \text{if } A_i^{(p1)} = 0, A_i^{(p2)} = 1 \\ \alpha c_i^{(p1)} + (1 - \alpha)c_i^{(p2)} + \mathcal{N}(0, \sigma^2) & \text{if } A_i^{(p1)} = A_i^{(p2)} = 1 \\ c_{i,\text{default}} & \text{if } A_i^{(p1)} = A_i^{(p2)} = 0 \end{cases}$$

where $\alpha \sim U(0, 1)$. $c_{i,min}, c_{i,max}, c_{i,default}$ are detailed in Appendix C.

Prompt Operations Prompt evolution utilises the EvoPrompt prompt methodology (Guo et al., 2025). Using a similar approach we use LLM as a crossover and mutation operator.

- **Single parent**: $p_i^{(child)} = \text{LLMprompt}_{mutate}(p_i^{(parent)})$

- **Two parents**: $p_i^{(child)} = \text{LLMprompt}_{mutate}(\text{LLMprompt}_{crossover}(p_i^{(p1)}, p_i^{(p2)}))$

If a parent has module i disabled ($b_i = 0$), the corresponding prompt reverts to default: $p_i = p_{i,\text{default}}$ (default prompts in Appendix V.1).

LLM mutation and crossover prompts available in Appendix U. It is important to notice that this approach enables functional mutation: LLM is prompted with all possible functional inputs to be used in any prompt (described in Section 3.1).

I.2. Population management

This subsection focuses on population management: details about fitness function, diversity measure and population pruning.

Fitness Evaluation Each genome is evaluated using the fitness function:

$$f(\mathbf{g}) = \frac{1}{n_{ep}} \sum_{i=1}^{n_{ep}} \text{GameProgression}_i(\mathbf{g})$$

where n_{ep} is the number of episodes for specific game (see Table 8).

Diversity measure The genome distance function uses an embedding-based approach where each genome is represented as a single embedding vector (here we use sentence-transformers/all-MiniLM-L6-v2 embedding). The distance between two genomes is calculated using cosine similarity:

$$d(\mathbf{g}_1, \mathbf{g}_2) = 1 - \cos(\mathbf{e}_1, \mathbf{e}_2) \tag{23}$$

where $\mathbf{e}_i$ is the embedding vector representation of genome $\mathbf{g}_i$.

The cosine similarity between two embedding vectors is computed as:

$$\cos(\mathbf{e}_1, \mathbf{e}_2) = \frac{\mathbf{e}_1 \cdot \mathbf{e}_2}{\|\mathbf{e}_1\|_2 \|\mathbf{e}_2\|_2}$$

Each genome $\mathbf{g} = \{\mathbf{b}, \mathbf{c}, \mathbf{p}\}$ is transformed into a unified embedding vector $\mathbf{e} \in \mathbb{R}^d$ that captures the semantic representation of all genome components (binary variables, continuous parameters, and prompts) in a single high-dimensional space. The way we measure diversity, is the minimum distance to the genomes already existing in the archive.

Population Pruning After children evaluation, population pruning maintains diversity using the following algorithm:

1. Initialise $\mathcal{P}_{\text{new}} = \emptyset$

2. Add top-N scoring genomes: $\mathcal{P}_{\text{new}} \leftarrow \text{top}_5(\mathcal{P})$

3. For remaining genomes $\mathcal{G}_{\text{remaining}}$:

   (a) Calculate minimum distance to current population:

   $$d_{\min}(\mathbf{g}) = \min_{\mathbf{g}' \in \mathcal{P}_{\text{new}}} d(\mathbf{g}, \mathbf{g}')$$

   (b) Select genome maximising diversity with performance constraint:

   $$\mathbf{g}^* = \arg \max_{\mathbf{g} \in \mathcal{G}_{\text{remaining}}} d_{\min}(\mathbf{g}) \quad \text{s.t.} \ f(\mathbf{g}) \geq 0.7 \cdot f(\mathbf{g}_{\text{best}})$$

   (c) Add $\mathbf{g}^*$ to $\mathcal{P}_{\text{new}}$ and remove from $\mathcal{G}_{\text{remaining}}$

4. Repeat step 3 until the desired population size reached $(N + M)$

I.3. Genetic Approach: Pseudo Code

Algorithm 1 TAME: Genetic Algorithm

Require: Game environment
Ensure: Optimised genome g^*
1: Initialize $P_0 = \{g_{\text{basic}}, g_{\text{hierarchical}}, g_{\text{default}}, g_{\text{full}}\}$
2: **for** each $g \in P_0$ **do**
3:     $g_{\text{fitness}} \leftarrow \text{EvaluateFitness}(g)$
4: **end for**
5: $P \leftarrow P_0$
6: **for** generation $= 1$ to GENERATIONS **do**
7:     $C \leftarrow \emptyset$ {Children population}
8:     **for** $i = 1$ to CHILDREN_PER_GENERATION **do**
9:         **if** rand() < 0.7 **then**
10:             $p_1 \leftarrow \text{RouletteWheelSelection}(P)$
11:             $c \leftarrow \text{SingleParentOperations}(p_1)$
12:         **else**
13:             $p_1, p_2 \leftarrow \text{RouletteWheelSelection}(P, 2)$
14:             $c \leftarrow \text{TwoParentOperations}(p_1, p_2)$
15:         **end if**
16:         $c_{\text{fitness}} \leftarrow \text{EvaluateFitness}(c)$
17:         $C \leftarrow C \cup \{c\}$
18:     **end for**
19:     $P \leftarrow \text{PopulationPruning}(P \cup C)$
20: **end for**
21: $\arg \max_{g \in P} g_{\text{fitness}}$

J. Task performance using Gemini-2.0-Flash

In this Appendix, we compare different tasks performance across BabyAI, BabaIsAI, and Minihack for baseline versus TAME (first run using Gemini-2.0-Flash). Crafter and Nethack are excluded because they each have only one default task. TextWorld is also excluded since its genetic output matches the baseline.

MiniHack   Interestingly, five out of eight tasks are never solved by any method, showcasing the difficulty (see Figure 7). The Corridor-R3 task, which is never completed by the baseline, nevertheless shows 40% progress with TAME. Corridor-R3 is an exploration problem in which the goal is to find the staircase (Team, 2024), illustrating TAME agent's improved exploration ability. In both CorridorBattle-Dark and MazeWalk-9×9, TAME achieves higher performance. CorridorBattle-Dark requires the agent to fight monsters, thereby testing planning and memory (MiniHack Team), whereas MazeWalk-9×9 is a maze in which the agent must reach a terminal goal, testing exploration and memory (Samvelyan et al., 2021).

Figure 7. MiniHack tasks progression, Baseline vs TAME using Gemini-2.0-Flash.

BabyAI   We observe clear performance improvements across all tasks except "putnext" where both agents achieve 0% success rate (see Figure 8). The putnext task presents significant challenges due to its complex spatial reasoning requirements. Through empirical analysis, we identified that agents fail to understand the necessary positioning strategy: they must navigate to a location one step away from the target position (which is adjacent to the object) before dropping the item. The persistence of this failure in our improved method highlights fundamental limitations in the agent's spatial reasoning capabilities. In all the other tasks, we notice an improvement when comparing TAME with baseline.

BabaIsAI   This environment consists of 40 distinct tasks that can be categorised into four main types: make_win, make_you, goto_win, and make_wall_win. Our analysis reveals substantial improvements in the goto_win category and notable progress in make_win tasks, where performance increased from 0% baseline (see Figure 9). When examining performance across different room configurations (two_room versus single_room layouts), we observe consistent improvements in both settings. For difficulty categorisation, we define three levels based on task complexity: simple tasks have no modifiers or distractors, medium tasks contain 1-2 modifiers/distractors, and complex tasks have more than 2 modifiers/distractors. Most notably, the greatest performance gains occur in medium and complex categories, demonstrating that our method is particularly effective for challenging scenarios that require sophisticated reasoning capabilities.

Figure 8. BabyAI tasks progression, Baseline vs TAME using Gemini-2.0-Flash.

K. Details of Gemini-2 Experiments

This section details the setup and exact result of our Gemini-2 model family. In our experimentation we repeat the genetic algorithm 3 times in order to access its variance across runs. The number of runs per episode remains the same as in BALROG benchmark.

K.1. TAME results with Gemini-2

First, we compare Baseline together with "Claude Prompt", and TAME in the Table 9. "Claude Prompt" (see Appendix T) is created by prompting Claude-Sonnet-4.5 for a prompt that improves the Baseline prompt and allowing it for functional inputs as described in 3.1. We show that TAME outperforms the Baseline architecture, increasing the average score from 27.16% to 35.05%. Moreover, the worse performance of 'ClaudePrompt' demonstrates the difficulty of crafting a prompt that works well for every environment, motivating our genetic approach, adapting the framework based on the game.

Table 9. "Claude Prompt" and main TAME results with Gemini-2.0-flash

Environment	Baseline (↑)	ClaudePrompt (↑)	TAME (↑)	Episodes
Average	27.16% ± 2.12%	23.36% ± 1.44%	**35.05% ± 2.24%**	-
babyai	58.00% ± 6.98%	**78.00% ± 5.86%**	72.00% ± 6.65%	50
babaisai	30.83% ± 4.22%	27.50% ± 4.08%	**42.50% ± 4.51%**	120
textworld	32.55% ± 6.95%	0.78% ± 0.77%	**33.40% ± 7.23%**	30
crafter	29.09% ± 4.51%	26.36% ± 2.47%	**38.18% ± 4.25%**	10
minihack	12.50% ± 5.23%	7.50% ± 4.16%	**23.33% ± 6.69%**	40
nle	0.00% ± 0.00%	0.00% ± 0.00%	**0.91% ± 0.44%**	5

K.2. Details of scores across 3 genetic algorithm runs with Gemini-2.0-Flash

In Table 10 we see detailed scores across all environments and across all 3 independent genetic algorithm runs. The main results in the Table 1 are averaged across those 3 runs.

(a) Performance by Room Type

(b) Performance by Difficulty

(c) Performance by Objective

Figure 9. BabaIsAI task progression, Baseline vs TAME using Gemini-2.0-Flash

K.3. Initial Population Scores

This section details the scores of initial population used during genetic algorithm. Scores per environment can be seen in Table 11. The details of each components of initial population can be found in the Appendix V.

K.4. Initial population improvement

In order to access the performance gain of genetic algorithm, we compare it against initial population. In the Table 12 we present the percentage improvement of final TAME score when compared to the best score from initial population (see Appendix K.3). Those results show that even with relatively small budget, TAME structure is able to improve on average of 25.1% when compared to initial population, showcasing the effectiveness of the genetic algorithm over human-crafted initial population.

Table 10. Detailed scores across 3 genetic algorithm runs with Gemini-2.0-Flash.

Environment	Baseline (↑)	TAME[Run1] (↑)	TAME[Run2] (↑)	TAME[Run3] (↑)
Average	27.16% ± 2.12%	34.78% ± 2.22%	34.87% ± 2.20%	35.52% ± 2.24%
babyai	58.00% ± 6.98%	72.0% ± 6.35%	68.0% ± 6.60%	76.0% ± 6.04%
babaisai	30.83% ± 4.22%	41.67% ± 4.50%	43.33% ± 4.52%	42.5% ± 4.51%
textworld	32.55% ± 6.95%	32.55% ± 6.95%	32.55% ± 6.95%	35.10% ± 7.78%
crafter	29.09% ± 4.51	39.09% ± 4.9%	39.55% ± 3.91%	35.91% ± 4.33%
minihack	12.50% ± 5.23%	22.5% ± 6.6%	25.0% ± 6.85%	22.50% ± 6.61%
nle	0.00% ± 0.00%	0.85% ± 0.47%	0.79% ± 0.44%	1.10% ± 0.41%

Table 11. Initial population for Gemini-2.0-Flash genetic algorithm.

Environment	Baseline (↑)	Hierarchical[Hand-Crafted] (↑)	Full[Claude] (↑)	Full[Hand-Crafted] (↑)
Average	27.16% ± 2.12%	38.48% ± 1.69%	34.53% ± 1.76%	33.93% ± 1.65%
babyai	58.00% ± 6.98%	62.00% ± 6.86%	58.00% ± 6.98%	65.31% ± 6.80%
babaisai	30.83% ± 4.22%	29.17% ± 4.15%	40.83% ± 4.49%	31.67% ± 4.25%
textworld	32.55% ± 6.95%	8.24% ± 2.25%	4.67% ± 1.50%	6.08% ± 1.70%
crafter	29.09% ± 4.51	33.64% ± 4.64%	31.36 % ± 3.55 %	20.00% ± 1.72%
minihack	12.50% ± 5.23%	5.00% ± 3.45%	12.50% ± 5.23%	12.50% ± 5.23%
nle	0.00% ± 0.00%	0.37% ± 0.33%	0.68% ± 0.37%	0.00% ± 0.00%

K.5. Improvement of the average score across generations of genetic algorithm

We also show in Figure 10 the graphical representation of average game progression (% completion) over generations in genetic algorithm with Gemini-2.0-Flash. In each generation we consider 5 top scoring genomes. We present average and standard deviation of the score across all 6 games over 3 runs, showcasing that there is a clear improvement in terms of average progress.

K.5.1. CONVERGENCE PROPERTIES ACROSS GAMES

Figure 11 expands on Figure 10, presenting the convergence patterns accross all games. We measure the mean and standard deviation of the top 5 scoring genomes in the population at each generation. The results show a clear convergence trend: the standard deviation decreases in all environments except for MiniHack. This demonstrates that increasing the computational budget enables convergence. Note that due to the scale of the y-axis, NetHack's standard deviation appears negligible in the figure. However, Table 1 confirms that measurable variance exists and that TAME continues to show improvement in this environment.

K.6. Genome Transferability to other Gemini-2 models

In this Appendix section, we detail transerability of genomes obtained through genetic algorithm using Gemini-2.0-Flash, to Gemini-2.5-Flash-Lite and Gemini-2.5-Pro without additional training. In the Table 13 we compare performance of Baseline using Gemini-2.5-Flash-Lite vs TAME transferred to the same model. In the Table 14 we compare performance of Baseline using Gemini-2.5-Pro vs TAME transferred to the same model. Lastly, we show combined results in the Figure 12. The Transferred results are averaged over 3 independent runs of genetic algorithm with details in the Tables 15 and 16.

K.6.1. TRANSFER SCORES ACROSS INDIVIDUAL GENETIC RUNS

In the Table 16 we present detailed results of genetic algorithm transferability to Gemini-2.5-Pro. Similarly, in Table 15 we show results of genetic algorithm transferability to Gemini-2.5-Flash-Lite across 3 independent genetic runs.

Figure 10. Average progression across all games (3 runs) with ± standard deviation. *Note: Values are game scores, not relative improvements.*

Figure 11. Average progression of top 5 scoring genomes in each generation over environments using Gemini-2.0-Flash. *Note: Values are game scores, not relative improvements.*

Table 12. Relative percentage improvement of TAME over the best-performing initial population scores across environments using Gemini-2.0-Flash. *Note: The 'Best Initial Score' and 'TAME' values indicate the game progression (presented in percentages), and Rel. Improvement values indicate the percentage improvement of 'TAME' over 'Best Initial Score'.*

Environment	Best Initial Score	TAME	Rel. Improvement
babyai	65.31%	72.00%	+10.2%
babaisai	40.83%	42.50%	+4.1%
textworld	32.55%	33.40%	+2.6%
crafter	33.64%	38.18%	+13.5%
minihack	12.50%	23.33%	+86.6%
nle	0.68%	0.91%	+33.8%
Average			**+25.1%**

Table 13. Comparison of Baseline vs. TAME[Transferred] using Gemini-2.5-Flash-Lite. TAME[Transferred] averaged across 3 genetic algorithm runs.

Environment	Baseline [2.5-Flash-Lite]	TAME[Transferred]	Episodes
Average	**11.87% $\pm$ 1.32%**	**20.48% $\pm$ 0.91%**	-
babyai	46.00% $\pm$ 7.05%	**58.00% $\pm$ 3.06%**	50
babaisai	9.17% $\pm$ 2.63	**38.33% $\pm$ 0.48%**	120
textworld	**7.45% $\pm$ 2.30%**	**7.45% $\pm$ 0.00%**	30
crafter	8.64% $\pm$ 1.00%	**13.01% $\pm$ 4.15%**	10
minihack	0.00% $\pm$ 0.00%	**5.83% $\pm$ 1.67%**	40
nle	0.00% $\pm$ 0.00%	**0.27% $\pm$ 0.15%**	5

Figure 12. Evaluation of TAME Structure Transferability: Identical performance to the baseline indicates that the genetic algorithm favoured the baseline architecture over the transferred TAME genome.

K.6.2. ACTIVATED MODULES DETAILS

In this Appendix we discuss module activation based on the game. The results are taken from the first one of genetic algorithm using Gemini-2.0-Flash. Module activation is based on final genomes returned by genetic algorithm, available

Table 14. Comparison of Baseline vs. TAME[Transferred] using Gemini-2.5-Pro. TAME[Transferred] averaged across 3 genetic algorithm runs.

Game	Baseline [2.5-Pro]	TAME[Transferred]	Episodes
Average	**43.35% ± 2.31%**	**47.57% ± 2.72%**	-
babyai	80.0% ± 5.70%	**92.00% ± 3.46%**	50
babaisai	56.70% ± 4.50%	**67.50% ± 5.00%**	120
textworld	49.20% ± 8.20%	**52.73% ± 6.12%**	30
crafter	**55.0% ± 6.0%**	**55.00% ± 0.00%**	10
minihack	17.50% ± 6.00%	**18.33% ± 1.44%**	40
nle	**1.70% ± 0.20%**	**1.70% ± 0.00%**	5

Table 15. Details of independent runs of transferability to Gemini-2.5-Flash-Lite

Environment	Baseline[2.5-Flash-Lite]	TAME[Run1]	TAME[Run2]	TAME[Run3]	Episodes
Average	11.88% ± 1.32%	19.25% ± 1.63%	19.43% ± 1.49%	22.76% ± 1.73%	
babyai	46.00% ± 7.05%	52.00% ± 7.07%	60.00% ± 6.93%	62.00% ± 6.93%	50
babaisai	9.17% ± 2.63	39.17% ± 4.46%	37.50% ± 4.42%	38.33% ± 4.44%	120
textworld	7.45% ± 2.30%	7.45% ± 2.30%	7.45% ± 2.30%	7.45% ± 2.30%	30
crafter	8.64% ± 1.00%	9.09% ± 1.70%	8.64% ± 1.00%	21.3% ± 4.22%	10
minihack	0.00% ± 0.00%	7.5% ± 4.16%	2.5 % ± 2.47	7.50% ± 4.16%	40
nle	0.00% ± 0.00%	0.31% ± 0.28%	0.51% ± 0.42%	0.00% ± 0.00%	5

Table 16. Details of independent runs of transferability to Gemini-2.5-Pro

Environment	Baseline[2.5-Pro]	TAME[Run1]	TAME[Run2]	TAME[Run3]	Episodes
Average	43.35% ± 2.31%	47.65% ± 2.20%	47.82% ± 2.14%	48.17% ± 2.25%	
babyai	80.00 ± 5.70%	90.00 ± 4.24	96.0 ± 2.77%	90% ± 4.24%	50
babaisai	56.70% ± 4.50%	72.50% ± 4.08%	67.5% ± 4.28%	62.5% ± 4.42%	120
textworld	49.20% ± 8.20%	49.20% ± 8.20%	49.20% ± 8.20%	59.80% ± 8.34%	30
crafter	55.0% ± 6.00%	55.00% ± 6.00%	55.00% ± 6.00%	55.00% ± 6.00%	10
minihack	17.50% ± 6.00%	17.50% ± 6.00%	17.50% ± 6.00%	20.00% ± 6.32%	40
nle	1.70% ± 0.20%	1.70% ± 0.20%	1.70% ± 0.20%	1.70% ± 0.20%	5

in Appendix W, and is demonstrated in the Figure 17 (note that when selecting the baseline configuration, no additional modules apart from Long-Term Memory can be activated). We notice that 4 out of 6 environments selected hierarchical module, highlighting the effectiveness of complex goal decomposition. TextWorld is a text-based environment where it is difficult to predict next actions due to their dependence on current observation, therefore hierarchical structure and memory are not adding value. Moreover, MiniHack has relatively short length (100 steps), which might be also why baseline structure was favoured.

Table 17. Module activation in TAME across environments using Gemini-2.0-Flash. Results are taken from the first run of the genetic algorithm.

	BabaIsAI	BabyAI	NetHack	Crafter	MiniHack	TextWorld
Hierarchy	✓	✓	✓	✓	✗	✗
Amygdala	✗	✓	✗	✗	✗	✗
Loop Detector	✓	✓	✓	✓	✗	✗
Explorer	✓	✗	✗	✓	✗	✗
Critic	✓	✓	✓	✓	✗	✗
Long-Term Memory	✓	✓	✓	✓	✓	✗

L. Details of Gemini-3 Experiments

This section details the setup and exact result of our Gemini-3 model family. In our experimentation we repeat the genetic algorithm 3 times in order to access its variance across runs. The number of runs per episode remains the same as in BALROG benchmark.

L.1. TAME results with Gemini-3-Flash-Lite

First, we compare Baseline together TAME in the table 18. We show that TAME outperforms the Baseline architecture, increasing the average score from 34.54% to 42.79%.

Table 18. Baseline vs. TAME using Gemini-3.1-Flash-Lite averaged over 3 runs.

Environment	Baseline (↑) (↑)	TAME (↑)	Episodes
Average	34.54% ± 2.33%	**42.79% ± 2.18%**	-
babyai	76.00% ± 6.04%	**94.67% ± 3.26%**	50
babaisai	32.50% ± 4.28%	**50.28% ± 4.56%**	120
textworld	32.16% ± 8.38%	**34.12% ± 8.49%**	30
crafter	44.09% ± 5.22%	**47.88% ± 4.11%**	10
minihack	22.50% ± 6.60%	**28.33% ± 7.12%**	40
nle	0.00% ± 0.00%	**1.43% ± 0.47%**	5

L.2. Scores across 3 genetic algorithm runs with Gemini-3.1-Flash-Lite

In Table 19 we see detailed scores across all environments and across all 3 independent genetic algorithm runs. The main results in the Table 18 and Table 1 are averaged across those 3 runs.

Table 19. Detailed scores across 3 genetic algorithm runs with Gemini-3.1-Flash-Lite.

Environment	Baseline (↑)	TAME[Run1] (↑)	TAME[Run2] (↑)	TAME[Run3] (↑)
Average	34.54% ± 2.33%	43.75% ± 2.24%	42.42% ± 2.10%	42.18% ± 2.23%
babyai	76.00% ± 6.04%	92.00% ± 4.24%	96.00% ± 2.77%	96.00% ± 2.77%
babaisai	32.50% ± 4.28%	51.67% ± 4.56%	49.17% ± 4.56%	50.00% ± 4.56%
textworld	32.16% ± 8.38%	38.04% ± 8.71%	32.16% ± 8.38%	32.16% ± 8.38%
crafter	44.09% ± 5.22%	50.45% ± 4.04%	49.09% ± 3.07%	44.09% ± 5.22%
minihack	22.50% ± 6.60%	27.50% ± 7.06%	27.50% ± 7.06%	30.00% ± 7.25%
nle	0.00% ± 0.00%	2.84% ± 0.45%	0.62% ± 0.50%	0.84% ± 0.46%

L.3. Initial population of Gemini-3-Flash-Lite family models

Table 20 shows initial population for Gemini-3.1-Flash-Lite genetic algorithm. Each component is described more in detail in the Appendix V.2.

L.4. Improvement over initial population using Gemini-3.1-Flash-Lite

Table 21 shows the relative improvement when TAME is contrasted with best scoring genome from initial population described in Table 20. The results demonstrate average relative gain of around 42.8%, showing the effectiveness of genetic algorithm over human-crafted initial population.

L.5. Transferability across Gemini-3 family models

In this section we test if results can transfer within Gemini-3 family. We follow the same procedure as in Gemini-2 case. Therefore, for each environment we evaluate the best scoring genome (obtained from TAME run with Gemini-3.1-Flash-Lite) using Gemini-3.1-Pro. We apply the same procedure for all independent genetic algorithm runs and average results. Table

Table 20. Initial population for Gemini-3.1-Flash-Lite genetic algorithm.

Environment	Baseline (↑)	Hierarchical[Hand-Crafted] (↑)	Full[Claude] (↑)	Full[Hand-Crafted] (↑)
Average	34.54% ± 2.33%	28.85% ± 1.40%	30.89% ± 1.37%	28.45% ± 1.34%
babyai	76.00% ± 6.04%	84.00% ± 5.18%	92.00% ± 3.84%	86.00% ± 4.91%
babaisai	32.50% ± 4.28%	45.83% ± 4.55%	49.17% ± 4.56%	45.00% ± 4.54%
textworld	32.16% ± 8.38%	9.41% ± 3.24 %	5.29% ± 2.06%	4.71% ± 2.12%
crafter	44.09% ± 5.22%	31.36% ± 2.61%	31.36% ± 3.18%	34.55% ± 3.92%
minihack	22.50% ± 6.60%	2.50% ± 2.47%	7.50% ± 4.16%	0.00% ± 0.00%
nle	0.00% ± 0.00%	0.00% ± 0.00%	0.00% ± 0.00%	0.46% ± 0.40%

Table 21. Relative percentage improvement of TAME over the best-performing initial population scores across environments using Gemini-3.1-Flash-Lite averaged over 3 genetic algorithm runs. *Note: The values indicate the percentage progression relative to the best performing initial genome, not the raw scores themselves.*

Environment	Best Initial Score	TAME	Rel. Improvement
babyai	92.00%	94.67%	+2.9%
babaisai	49.17%	50.28%	+2.3%
textworld	32.16%	34.12%	+6.1%
crafter	44.09%	47.88%	+8.6%
minihack	22.50%	28.33%	+25.9%
nle	0.46%	1.43%	+210.9%
Average			**+42.8%**

22 shows the averaged results, demonstrating a relative gain of around 2.53%, when compared to Baseline Gemini-3.1-Pro results (see Table 23 for more details across independent runs). At the same time, we obtain the SOTA result in BALROG leaderboard (without retraining) at the time of writing this paper.

Table 22. Transferability of TAME across Gemini-3 family averaged over 3 runs compared to the Gemini-3.1-Pro baseline, as well as top scoring model (Gemini-3.0-Pro) from BALROG leaderboard (May 2026).

Environment	Baseline[Gemini-3.1-Pro]	Top Model	TAME[Transferred]	Episodes
Average	56.88% ± 1.95%	58.10% ± 2.10%	**58.56% ± 1.93%**	-
babyai	**100.00% ± 0.00%**	96.00% ± 2.80%	**100.00% ± 0.00%**	50
babaisai	90.00% ± 2.70%	88.30% ± 2.90%	**90.56% ± 2.64%**	120
textworld	**66.50% ± 7.50%**	60.20% ± 7.50%	**66.50% ± 7.50%**	30
crafter	46.80% ± 4.20%	**57.30% ± 4.40%**	54.84% ± 3.63%	10
minihack	35.00% ± 7.50%	**40.00% ± 7.70%**	35.83% ± 7.55%	40
nle	3.00% ± 0.50%	**6.80% ± 3.20%**	3.60% ± 0.8%	5

Table 23. Detailed scores across 3 genetic transferability runs with Gemini-3.1-Pro.

Environment	Baseline (↑)	TAME[Run1] (↑)	TAME[Run2] (↑)	TAME[Run3] (↑)
Average	56.88% ± 1.96%	59.14% ± 1.92%	59.23% ± 1.90%	57.30% ± 1.97%
babyai	100.00% ± 0.00%	100.00% ± 0.00%	100.00% ± 0.00%	100.00% ± 0.00%
babaisai	90.00% ± 2.70%	91.67% ± 2.52%	90.00% ± 2.70%	90.00% ± 2.70%
textworld	66.50% ± 7.50%	66.50% ± 7.50%	66.50% ± 7.50%	66.50% ± 7.50%
crafter	46.80% ± 4.20%	58.64% ± 3.72%	59.09% ± 2.96%	46.80% ± 4.20%
minihack	35.00% ± 7.50%	35.00% ± 7.50%	35.00% ± 7.50%	37.50% ± 7.65%
nle	3.00% ± 0.50%	3.00% ± 0.50%	4.79% ± 1.40%	3.00% ± 0.50%

M. Details of GPT-4 Experiments

This section details the setup and exact result of our GPT-4 model family. In our experimentation we repeat the genetic algorithm 3 times in order to access its variance across runs. The number of runs per episode remains the same as in BALROG benchmark.

M.1. TAME results with GPT4.1-nano

We repeat the same procedure as described in section 3.3 applied to the initial population described in Section M.3. Table 24 shows the final TAME result, illustrating the relative gain of 74% when comparing average result over Baseline (see Table 25 for detailed results from independent runs). Additionally, we include results of applying the "Claude Prompt" proposed by Claude-Sonnet-4.5 (see Appendix T). We conclude that TAME outperforms both baseline and ClaudePrompt results. Those results demonstrate that TAME architecture improves performance on more than one family of Language Models.

Table 24. Baseline vs. ClaudePrompt vs. TAME using GPT4.1-nano averaged over 3 runs.

Environment	Baseline (↑)	ClaudePrompt (↑)	TAME (↑)	Episodes
Average	9.90% ± 1.33%	6.10% ± 1.12%	**17.20% ± 1.47%**	-
babyai	32.0% ± 6.60%	20.00% ± 5.66%	**48.67% ± 7.07%**	50
babaisai	12.5% ± 3.02%	6.67% ± 2.28%	**21.55% ± 3.76%**	120
textworld	0.59% ± 0.58%	0.39% ± 0.39%	**2.88% ± 0.94%**	30
crafter	11.82% ± 2.15%	7.07% ± 1.26%	**19.78% ± 2.33%**	10
minihack	2.5% ± 2.47%	2.50% ± 2.47%	**10.00% ± 2.78%**	40
nle	0.0% ± 0.0%	0.00% ± 0.00%	**0.22% ± 0.20%**	5

M.2. Details of scores across 3 genetic algorithm runs with GPT4.1-nano

In Table 25 we see detailed scores across all environments and across all 3 independent genetic algorithm runs using GPT4.1-nano. The main results in the Table 24 and Table 1 are averaged across those 3 runs.

Table 25. Detailed scores across 3 genetic algorithm runs with GPT4.1-nano.

Environment	Baseline (↑)	TAME[Run1] (↑)	TAME[Run2] (↑)	TAME[Run3] (↑)
Average	9.90% ± 1.33%	18.06% ± 1.65%	17.19% ± 1.60%	16.31% ± 1.58%
babyai	32.00% ± 6.60%	52.00% ± 7.07%	48.00% ± 7.07%	46.00% ± 7.06%
babaisai	12.50% ± 3.02%	22.5% ± 3.81%	22.5% ± 3.81%	19.66% ± 3.67%
textworld	0.59% ± 0.58%	3.13% ± 0.95%	2.75% ± 0.93%	2.75% ± 0.93%
crafter	11.82% ± 2.15%	20.71% ± 3.04%	19.55% ± 2.14%	19.09% ± 1.80%
minihack	2.5% ± 2.47%	10.00% ± 4.86%	10.00% ± 4.74%	10.00% ± 4.74%
nle	0.0% ± 0.0%	0.0% ± 0.0%	0.31% ± 0.28%	0.38% ± 0.33%

M.3. Initial population of GPT-4 family models

Table 26 shows initial population for GPT4.1-nano genetic algorithm. Each component is described more in detail in the Appendix V.2.

M.4. Improvement over initial population

Table 27 shows the relative improvement when TAME is contrasted with best scoring genome from initial population described in Appendix M.3. The results demonstrate average relative gain of around 39.7%, showing the effectiveness of genetic algorithm over human-crafted inital population. Note that since NetHack baseline performance is 0%, even though we notice an improvement after applying TAME, we can't measure its relative improvement, therefore we exclude it from calculation in Table 27.

Table 26. Initial population for GPT-4.1-nano genetic algorithm.

Environment	Baseline (↑)	Hierarchical[Hand-Crafted] (↑)	Full[Claude] (↑)	Full[Hand-Crafted] (↑)
Average	$9.90\% \pm 1.33\%$	$10.40\% \pm 2.07\%$	$10.95\% \pm 2.77\%$	$9.28\% \pm 2.15\%$
babyai	$32.0\% \pm 6.60\%$	$12.00\% \pm 4.60\%$	$22.00\% \pm 5.86\%$	$10.00\% \pm 4.24\%$
babaisai	$12.50\% \pm 3.02\%$	$16.67\% \pm 3.40\%$	$16.10\% \pm 3.38\%$	$19.66\% \pm 3.67\%$
textworld	$0.59\% \pm 0.58\%$	$1.18\% \pm 0.60\%$	$2.75\% \pm 0.93\%$	$1.37\% \pm 0.70\%$
crafter	$11.82\% \pm 2.15\%$	$7.58\% \pm 1.01\%$	$15.00\% \pm 1.71\%$	$12.27\% \pm 1.82\%$
minihack	$2.50\% \pm 2.47\%$	$5.00\% \pm 3.45\%$	$0.00\% \pm 0.00\%$	$2.50\% \pm 2.47\%$
nle	$0.00\% \pm 0.00\%$	$0.00\% \pm 0.00\%$	$0.00\% \pm 0.00\%$	$0.00\% \pm 0.00\%$

Table 27. Relative percentage improvement of TAME over the best-performing initial population scores across environments using GPT4.1-nano averaged over 3 genetic algorithm runs. *Note: The values indicate the percentage progression relative to the best performing initial genome, not the raw scores themselves.*

Environment	Best Initial Score	TAME	Rel. Improvement
babyai	32.00%	48.67%	+52.1%
babaisai	19.66%	21.55%	+9.6%
textworld	2.75%	2.88%	+4.7%
crafter	15.00%	19.78%	+31.9%
minihack	5.00%	10.00%	+100.0%
nle	0.00%	0.22%	N/A
Average (excl. NLE)		**+39.7%**	

M.5. Transferability across GPT4 family models

In this section we test if results can transfer within GPT family. We follow the same procedure as in Gemini case. Therefore, for each environment we evaluate the best scoring genome (obtained from TAME run with GPT4.1-nano) using GPT4.1-mini. We apply the same procedure for all independent genetic algorithm runs and average results. Table 28 shows the results, demonstrating a relative gain of around 10%, when compared to Baseline GPT4.1-mini results (see Table 29 for more details across independent runs) .

Table 28. Transferability of TAME across GPT family averaged over 3 runs.

Environment	Baseline[GPT-4.1-mini]	TAME[Transferred]	Episodes
Average	$24.43\% \pm 1.89\%$	$\mathbf{26.80\% \pm 1.92\%}$	-
babyai	$\mathbf{72.00\% \pm 7.18\%}$	$\mathbf{72.00\% \pm 7.18\%}$	50
babaisai	$29.17\% \pm 4.15\%$	$\mathbf{35.00\% \pm 4.33\%}$	120
textworld	$\mathbf{13.33\% \pm 5.74\%}$	$\mathbf{13.33\% \pm 5.74\%}$	30
crafter	$21.00\% \pm 2.00\%$	$\mathbf{29.43\% \pm 2.65\%}$	10
minihack	$\mathbf{10.00\% \pm 4.74\%}$	$\mathbf{10.00\% \pm 4.74\%}$	40
nle	$\mathbf{1.09\% \pm 0.41\%}$	$\mathbf{1.09\% \pm 0.41\%}$	5

Table 29. Details of independent runs of transferability to GPT4.1-mini

Environment	Baseline[GPT4.1-mini]	TAME[Run1]	TAME[Run2]	TAME[Run3]	Episodes
Average	24.43% ± 1.89%	28.33% ± 1.92%	25.40% ± 1.09%	25.44% ± 1.92%	-
babyai	72.00% ± 7.18%	72.00% ± 7.18%	72.00% ± 7.18%	72.00% ± 7.18%	50
babaisai	29.17% ± 4.15%	40.83% ± 4.49 %	35.00% ± 4.35%	29.17% ± 4.15%	120
textworld	13.33% ± 5.74%	13.33% ± 5.74%	13.33% ± 5.74%	13.33% ± 5.74%	30
crafter	21.00% ± 2.00%	32.73% ± 2.47%	21.00% ± 2.00%	34.55% ± 3.47%	10
minihack	10.00% ± 4.74%	10.00% ± 4.74%	10.00% ± 4.74%	10.00% ± 4.74%	40
nle	1.09% ± 0.41%	1.09% ± 0.41%	1.09% ± 0.41%	1.09% ± 0.41%	5

N. Details of GPT-5 Minimal Thinking Experiments

This section details the setup and exact result of our GPT-5 model family. In our experimentation we repeat the genetic algorithm 3 times in order to access its variance across runs. The number of runs per episode remains the same as in BALROG benchmark.

N.1. TAME results with GPT5-Minimal Thinking

We repeat the same procedure as described in section 3.3 applied to the initial population described in Section N.3. Table 30 shows the final TAME result, illustrating the relative gain of 37.13% when comparing average result over Baseline (see Table 31 for detailed results from independent runs). We conclude that TAME outperforms baseline results. Note that due to notably higher cost of training GPT-5 model, we conduct genetic algorithm twice.

Table 30. Baseline vs. TAME using GPT-5 Minimal Thinking.

Environment	Baseline (↑)	TAME (↑)	Episodes
Average	32.81% ± 2.16%	**44.82% ± 2.14%**	-
babyai	80.00% ± 5.66%	**85.00% ± 5.04%**	50
babaisai	25.83% ± 4.00%	**74.58% ± 3.92%**	120
textworld	**30.59% ± 7.01%**	**30.59% ± 7.01%**	30
crafter	39.09% ± 4.13%	**47.27% ± 4.71%**	10
minihack	20.00% ± 7.30%	**30.00% ± 7.24%**	40
nle	1.32% ± 0.50%	**1.48% ± 0.45%**	5

N.2. Scores across 3 genetic algorithm runs with GPT5 Minimal Thinking

In Table 31 we see detailed scores across all environments and across 2 independent genetic algorithm runs using GPT5-MinimalThinking. The main results in the Table 30 and Table 1 are averaged across those runs.

Table 31. Detailed scores across 2 genetic algorithm runs with GPT-5 Minimal Thinking.

Environment	Baseline (↑)	TAME[Run1] (↑)	TAME[Run2] (↑)
Average	32.81% ± 2.16%	47.84% ± 2.19%	42.14% ± 2.10%
babyai	80.00% ± 5.66%	84.0% ± 5.18%	86.0% ± 4.90% ±
babaisai	25.83% ± 4.00%	80.83% ± 3.59%	68.33% ± 4.25%
textworld	30.59% ± 7.01%	30.59% ± 7.01%	30.59% ± 7.01%
crafter	39.09% ± 4.13%	55.45% ± 5.29%	39.09% ± 4.13%
minihack	20.00% ± 7.30%	32.5% ± 7.41%	27.50% ± 7.06%
nle	1.32% ± 0.50%	1.64% ± 0.40%	1.32% ± 0.50%

N.3. Initial population of GPT-5 family models

Table 32 shows initial population for GPT5-Minimal Thinking genetic algorithm. Each component is described more in detail in the Appendix V.2.

Table 32. Initial population for GPT-5 Minimal Thinking genetic algorithm.

Environment	Baseline (↑)	Hierarchical[Hand-Crafted] (↑)	Full[Claude] (↑)	Full[Hand-Crafted] (↑)
Average	32.81% ± 2.16%	24.24% ± 1.54%	26.76% ± 1.60%	29.00% ± 1.56%
babyai	80.00% ± 5.66%	62.00% ± 6.86%	64.00% ± 6.79%	74.00% ± 6.20%
babaisai	25.83% ± 4.00%	57.50% ± 4.51%	65.00% ± 4.35%	64.17% ± 4.38%
textworld	30.59% ± 7.01%	0.78% ± 0.53%	1.76% ± 0.93%	2.16% ± 0.90%
crafter	39.09% ± 7.01%	17.68% ± 0.86%	22.27% ± 3.05%	23.64% ± 2.63%
minihack	20.00% ± 7.30%	7.5% ± 4.16%	7.5% ± 4.16%	10.00% ± 4.74%
nle	1.32% ± 0.50%	0.00% ± 0.00%	0.00% ± 0.00%	0.00% ± 0.00%

N.4. Improvement over initial population

Table 33 shows the relative improvement when TAME is contrasted with best scoring genome from initial population described in Table 32. The results demonstrate average relative gain of around 17.3%, showing the effectiveness of genetic algorithm over human-crafted initial population.

Table 33. Relative percentage improvement of TAME over the best-performing initial population scores across environments using GPT-5 Minimal Thinking averaged over 2 genetic algorithm runs. *Note: The values indicate the percentage progression relative to the best performing initial genome, not the game scores themselves.*

Environment	Best Initial Score	TAME	Rel. Improvement
babyai	80.00%	85.00%	+6.3%
babaisai	65.00%	74.58%	+14.7%
textworld	30.59%	30.59%	+0.0%
crafter	39.09%	47.27%	+20.9%
minihack	20.00%	30.00%	+50.0%
nle	1.32%	1.48%	+12.1%
Average			**+17.3%**

O. Details of Claude-4 Experiments

This section details the setup and exact result of our Claude-4 model family. In our experimentation we repeat the genetic algorithm 3 times in order to access its variance across runs. The number of runs per episode remains the same as in BALROG benchmark.

O.1. Details of Claude-Haiku-4.5 experiments

We repeat the same procedure as described in section 3.3 applied to the initial population described in Section O.3. Table 34 shows the final TAME result, illustrating the relative gain of 27.62% when comparing average result over Baseline (see Table 35 for detailed results from independent runs). We conclude that TAME outperforms both baseline results.

Table 34. Baseline vs. TAME using Claude-Haiku-4.5.

Environment	Baseline (↑)	TAME (↑)	Episodes
Average	27.44% ± 2.16%	35.02% ± 2.16%	-
babyai	68.0% ± 6.60%	74.0% ± 6.20%	50
babaisai	30.83% ± 4.22%	53.04% ± 4.55%	120
textworld	30.00% ± 8.37%	39.80% ± 8.26%	30
crafter	16.82% ± 3.46%	27.61% ± 2.97%	10
minihack	12.5% ± 5.23%	15.00% ± 5.63%	40
nle	0.00% ± 0.00%	0.64% ± 0.46%	5

O.2. Scores across 3 genetic algorithm runs with Claude-Haiku-4.5

In Table 35 we see detailed scores across all environments and across all 3 independent genetic algorithm runs using Claude-Haiku-4.5. The main results in the Table 34 and Table 1 are averaged across those 3 runs.

Table 35. Detailed scores across 3 genetic algorithm runs with Claude-Haiku-4.5.

Environment	Baseline (↑)	TAME[Run1] (↑)	TAME[Run2] (↑)	TAME[Run3] (↑)
Average	27.44% ± 2.16%	37.34% ± 2.18%	35.68% ± 2.16%	32.02% ± 2.16%
babyai	68.0% ± 6.60%	76.0% ± 6.04%	74.0% ± 6.20%	72.0% ± 6.35%
babaisai	30.83% ± 4.22%	53.3% ± 4.55%	53.33% ± 4.55%	52.5% ± 4.56%
textworld	30.00% ± 8.37%	46.47% ± 8.40%	36.47% ± 8.19%	36.47% ± 8.19%
crafter	16.82% ± 3.46%	32.73% ± 3.27%	32.27% ± 2.18%	17.82% ± 3.46%
minihack	12.5% ± 5.23%	15.0% ± 5.65%	17.5% ± 6.01%	12.5% ± 5.23%
nle	0.00% ± 0.00%	0.53% ± 0.46%	0.53% ± 0.46%	0.85% ± 0.47%

O.3. Initial population of Claude-Haiku-4.5 family models

Table 36 shows initial population for Claude-Haiku-4.5 genetic algorithm. It follows the same structure as Gemini experiment and each component is described more in detail in the Appendix V.2.

O.4. Improvement over initial population

Table 37 shows the relative improvement when TAME is contrasted with best scoring genome from initial population from Table 36. The results demonstrate average relative gain of around 21.2%, showing the effectiveness of genetic algorithm over human-crafted initial population.

O.5. Transferability across Claude family models

In this section we test if results can transfer within Claude family. We follow the same procedure as in Gemini family models (see K.6) and GPT family models (see M.5) case. Therefore, for each environment we evaluate the best scoring

Table 36. Initial population for Claude-Haiku-4.5 genetic algorithm.

Environment	Baseline (↑)	Hierarchical[Hand-Crafted] (↑)	Full[Claude] (↑)	Full[Hand-Crafted] (↑)
Average	27.44% ± 2.16%	20.29% ± 1.49%	20.80% ± 1.43%	18.73% ± 1.47%
babyai	68.0% ± 6.60%	66.0% ± 6.70%	66.0% ± 6.70%	56.0% ± 7.02%
babaisai	30.83% ± 4.22%	47.5% ± 4.56%	50.83% ± 4.56%	47.5% ± 4.56%
textworld	30.00% ± 8.37%	0.00% ± 0.00%	0.0% ± 0.00%	0.00% ± 0.00%
crafter	16.82% ± 3.46%	2.73% ± 1.32%	5.45% ± 1.25%	6.36% ± 1.15%
minihack	12.5% ± 5.23%	5.00% ± 3.45%	2.5% ± 2.47%	2.50% ± 2.47%
nle	0.00% ± 0.00%	0.53% ± 0.46%	0.00% ± 0.00%	0.00% ± 0.00%

Table 37. Relative percentage improvement of TAME over the best-performing initial population scores across environments using Claude-Haiku-4.5 averaged over 3 genetic algorithm runs. *Note: The values indicate the percentage progression relative to the best performing initial genome, not the raw scores themselves.*

Environment	Best Initial Score	TAME	Rel. Improvement
babyai	68.00%	74.00%	+8.8%
babaisai	50.83%	53.04%	+4.3%
textworld	36.47%	39.80%	+9.1%
crafter	16.82%	27.61%	+64.2%
minihack	12.50%	15.00%	+20.0%
nle	0.53%	0.64%	+20.8%
Average			**+21.2%**

genome (obtained from TAME run with Claude-Haiku-4.5) using Claude-Sonnet-4.6. We apply the same procedure for all independent genetic algorithm runs and average results. Table 38 shows the results, demonstrating a relative gain of around 11.4%, when compared to Baseline Claude-Sonnet-4.6 results (see Table 39 for more details across independent runs) .

Table 38. Transferability of TAME across Claude family averaged over 3 runs. Transferred to Claude Sonnet 4.6

Environment	Baseline[Claude-Sonnet-4.6]	TAME[Transferred]	Episodes
Average	34.21% ± 2.21%	**38.12% ± 2.16%**	
babyai	**82.0% ± 5.43%**	**82.0% ± 5.43%**	50
babaisai	30.83% ± 4.22%	**50.28% ± 4.56%**	120
textworld	30.00% ± 8.37%	**33.33% ± 8.56**	30
crafter	34.09% ± 3.03%	**34.70% ± 4.13%**	10
minihack	**27.50% ± 7.06%**	**27.50% ± 7.06%**	40
nle	0.83% ± 0.46%	**0.88% ± 0.43%**	5

Table 39. Baseline vs. TAME progression across three runs of transferability to Claude-Sonnet-4.6. *Note: Values are absolute scores, not relative improvements.*

Environment	Baseline[Claude Sonnet]	TAME[Run 1]	TAME[Run 2]	TAME[Run 3]	Episodes
Average	34.21% ± 2.21%	39.22% ± 2.36%	37.42% ± 2.32%	37.71% ± 2.32%	
babyai	82.0% ± 5.43%	82.0% ± 5.43%	82.0% ± 5.43%	82.0% ± 5.43%	50
babaisai	30.83% ± 4.22%	50.0% ± 4.56%	49.17% ± 4.56%	51.67% ± 4.56%	120
textworld	30.0% ± 8.37%	40.0% ± 8.94%	30.0% ± 8.37%	30.0% ± 8.37%	30
crafter	34.09% ± 3.03%	35.0% ± 4.46%	35.0% ± 4.90%	34.09% ± 3.03%	10
minihack	27.50% ± 7.06%	27.50% ± 7.06%	27.50% ± 7.06%	27.50% ± 7.06%	40
nle	0.83% ± 0.46%	0.83% ± 0.46%	0.83% ± 0.46%	0.99% ± 0.36%	5

P. TAME child evaluation Pseudo code

This Appendix presents the pseudo code behind TAME evaluation on specific game when all modules are active, as decided by the genetic algorithm (overview in Figure 2). The algorithm works as follows: until maximum number of steps is reached, with probability ϵ choose exploration, otherwise exploitation. For each option, it retrieves top successful and failed memories, then the Low-level Executor decides and executes actions. If danger is detected, the survival module is triggered and execution stops. Otherwise, the Critic evaluates success, summarizes key actions, and in case of loops, the summary is replaced by the Loop Detector summary. The resulting memory is stored, and the cycle repeats.

Algorithm 2 TAME [Full Structure]

Require: I, s_0
Ensure: s_T (final game state)
  while $num\_steps \leq max\_steps$ **do**
    if $rand() < \epsilon$ **then**
      $g \leftarrow \pi_{explorer}(s_i^e)$ {Exploration}
    else
      $g \leftarrow \pi_{high}(s_i^{mc})$ {Exploitation}
    end if
    for $g_i \in g$ **do**
      $M_i^+ \leftarrow retrieve\_successful(n_{g_i}, d_{g_i}, memory)$
      $M_i^- \leftarrow retrieve\_failed(n_{g_i}, d_{g_i}, memory)$
      $a \leftarrow \pi_{low}(s_i^{le})$
      for $a_i \in a$ **do**
        $s_t \leftarrow execute\_action(a, s_i)$
        $s_i \leftarrow s_t$
        if $\sigma(s_i)$ **then**
          $g \leftarrow g^*$ {Activate survival option}
          break {Move to option selection and force g^*}
        end if
      end for
      $C_i \leftarrow \varphi(s_i)$
      $h_i \leftarrow \rho(s_i, C_i)$
      if C_i **then**
        $store\_memory(g_i, h_i, o, \text{“}successful\text{”})$
      else
        if $\psi(s_i)$ **then**
          $h_i \leftarrow \psi(s_i)$
        end if
        $store\_memory(g_i, h_i, o, \text{“}failed\text{”})$
        break {Escalate to replanning}
      end if
    end for
  end while

Q. Detailed memory ablations

We also include ablations to demonstrate the effectiveness of our long-term memory system. In order to test memory, we use the hierarchical structure described in Section G.1, combined with three different memory architectures: Jarvis, TAME-Memory[ours] and A-mem. Both **Jarvis** memory and **A-mem** store the same core elements: g_i (the option, including all information associated with it), $C_i \in \{0, 1\}$ (the status indicator), and o (the observation sequence corresponding to the current option). TAME extends Jarvis framework by introducing a critic, as well as a filter for successful and failed trajectories (but does not create links between memories). This requires one additional LLM call compared to Jarvis, but two fewer LLM calls per generation compared to A-mem. Thus, our approach explores a trade-off between the simplicity of Jarvis and the more complex and expensive structure of A-mem.

Table 40 shows that TAME-Memory consistently outperforms both Craft-Jarvis-1 and A-Mem on most environments, yielding the highest overall average of 23.11%. The gains are particularly strong in TextWorld and Crafter, where our system nearly doubles or surpasses the baselines by a large margin. While performance is comparable in Minihack and NLE, these tasks remain challenging for all methods. Overall, the results highlight the efficiency of our hybrid memory system. We

conduct this ablation study using Gemini-2.0-Flash.

Table 40. Comparison of TAME average game progression across different memory types using Gemini-2.0-Flash.

Environment	Jarvis (↑)	TAME-Memory[ours] (↑)	A-mem (↑)	Episodes
Average	17.52% ± 1.73%	**23.11% ± 1.75%**	21.45% ± 1.80%	-
babyai	48.00 % ± 7.06 %	**62.00% ± 6.86%**	58.00% ± 6.98%	50
babaisai	24.17 % ± 3.90 %	**29.17% ± 4.15%**	26.67% ± 4.04%	120
textworld	0.59 % ± 0.58 %	**8.24% ± 1.95%**	4.51% ± 2.35%	30
crafter	19.55 % ± 3.81 %	**35.45% ± 3.20%**	26.36% ± 4.25%	10
minihack	**12.5% ± 5.23%**	3.45% ± 5.65%	**12.5% ± 5.23%**	40
nle	0.31% ± 0.28%	0.37% ± 0.33%	**0.68% ± 0.37%**	5

R. Detailed ablation on genetic algorithm excluding human prompts

In this ablation study we attempt to measure an impact of human crafted prompts in the initial population (see details in the Appendix V.2). Therefore we exclude Hierarchical[Hand-Crafted] and Full[Hand-Crafted] from the initial population, leaving only baseline prompt from BALROG repository and Full[Claude] constructed by Claude. In that way, we remove the human bias. Due to the cost, we employ one genetic run per environment using Gemini-3.1-Flash-Lite and compare it across TAME results with the same model. Table 41 shows the results.

Table 41. Comparison of TAME vs TAME excluding human-crafted prompts using Gemini-3.1-Flash-Lite.

Environment	TAME	TAME[Excluded-Human-Prompts](↑)	Episodes
Average	42.79% ± 2.18%	42.33% ± 2.18%	-
babyai	94.67% ± 3.26%	94.00% ± 3.36%	50
babaisai	50.28% ± 4.56%	49.17% ± 4.56%	120
textworld	34.12% ± 8.49%	43.33% ± 9.04%	30
crafter	47.88% ± 4.11%	45.00% ± 3.66%	10
minihack	28.33% ± 7.12%	22.50% ± 6.60%	40
nle	1.43% ± 0.47%	0.00% ± 0.00%	5

S. Detailed ablation on genetic algorithm excluding diversity component

In this ablation study we attempt to measure an impact of diversity component in genetic algorithm. In the original method, after each stage we leave N best scoring genomes + M most diverse genomes. In here, we only leave N best scoring genomes, testing whether including diversity in population is beneficial. We use Gemini-3.1-Flash-Lite to generate one genetic run per environment and compare it against TAME results with the same model. Table 42 shows the results.

Table 42. Comparison of TAME vs TAME excluding diversity component.

Environment	TAME	TAME[Excluded-Diversity](↑)	Episodes
Average	42.79% ± 2.18%	40.26% ± 2.22%	-
babyai	94.67% ± 3.26%	92.00% ± 3.84%	50
babaisai	50.28% ± 4.56%	49.17% ± 4.56%	120
textworld	34.12% ± 8.49%	32.16% ± 8.38%	30
crafter	47.88% ± 4.11%	44.09% ± 5.22%	10
minihack	28.33% ± 7.12%	22.50% ± 6.60%	40
nle	1.43% ± 0.47%	1.63% ± 0.37%	5

T. 'Claude Prompt' proposed by Claude-Sonnet-4.5

Here we present a prompt proposed by Claude-Sonnet-4.5, when tasked to improve the Baseline (BALROG) prompt. As well as the baseline prompt, we gave information about functional inputs (see Section 3.1) and gave it an option to use them.

Claude Prompt proposed by Claude

```
# Game Agent Instructions

You are an autonomous agent navigating a game environment. Your task is to select the optimal next action based on the
    ↪ current state.

## Current State
- **Observation**: {obs}
- **Current Subgoal**: {subgoal}
- **Success Condition**: {success_condition}

## Context
- **Recent History**: {history}
- **Action Sequence (Current Subgoal)**: {action_sequence}

## Knowledge Base
- **Similar Successful Attempts**: {entries_successful_subgoal}
- **Similar Failed Attempts**: {entries_failed_subgoal}

## Available Actions
{game_info}

## Output Format
Output ONLY a single valid action from the available actions list. No explanations, no additional text.

## Decision Strategy
1. Analyze current observation against the success condition
2. Learn from similar past attempts (successful and failed)
3. Consider recent action history to avoid loops
4. Select the action most likely to progress toward the subgoal
Output in the following format: \n
        REASONING: <your reasoning> \n
        ACTION: <your action>
```

U. LLM Mutation and Crossover prompts

This Appendix details the prompts used for LLM based Crossover (in the case of single parent) and LLM based Crossover and Mutation (in the case of two parents) used in genetic algorithm. Prompts created with the help of Claude-Sonnet-4.5.

LLM Mutation Prompt

```
"""
Please follow the instruction step-by-step to generate a better prompt.

1. Consider prompt:
Prompt 1: <prompt1>

2. Apply ONE of the following mutation strategies to create a significantly different prompt:

**Strategy A - Perspective Shift:** Change the role/perspective (e.g., "As an expert analyst..." or "From the viewpoint
    ↪ of...")

**Strategy B - Methodology Change:** Alter the approach (step-by-step -> holistic analysis, direct -> comparative, etc.)

**Strategy C - Output Format Transformation:** Change how results are presented (narrative -> structured, single response ->
        ↪ multi-part, etc.)

**Strategy D - Contextual Enhancement:** Add specific domain knowledge or constraints that weren't in the original

**Strategy E - Complexity Modulation:** Significantly increase or decrease the cognitive complexity of the task

**Strategy F - Functional Input Integration:** Incorporate functional inputs in a novel way that changes the prompt's core
        ↪ operation

3. Generate the final mutated prompt bracketed with <prompt> and </prompt>.

## Available Functional Inputs:
- {obs} : current observation
- {game_info} : information about the game (possible actions and goal)
- {subgoal} : current subgoal that you're working towards
- {action_sequence}: action sequence towards current subgoal
- {observation_sequence}: observation sequence towards current subgoal
```

```
- {success_condition}: termination condition of the current subgoal
- {action_obs_seq}: action-observation pairs towards current subgoal
- {survival_plan}: survival plan
- {history}: history of the last 16 action-observation pairs
- {entries_successful_goal}: most similar successful subgoals to the current one
- {entries_failed_goal}: most similar failed subgoals to the current one

**CRITICAL:** Use functional inputs with exact bracket names. Ensure the mutation creates a substantially different prompt
    ↪ that would produce notably different outputs.
Output your asnwer in thne follwing way:
REASONING: <your reasoning>
PROMPT: <mutated prompt>
"""
```

LLM Mutation and Crossover Prompt

```
"""
Please follow the instruction step-by-step to generate a better prompt.

1. Crossover the following prompts and generate a new prompt:
Prompt 1: <prompt1>
Prompt 2: <prompt2>

2. Apply ONE of the following mutation strategies to create a significantly different prompt:

**Strategy A - Perspective Shift:** Change the role/perspective (e.g., "As an expert analyst..." or "From the viewpoint
    ↪ of...")

**Strategy B - Methodology Change:** Alter the approach (step-by-step -> holistic analysis, direct -> comparative, etc.)

**Strategy C - Output Format Transformation:** Change how results are presented (narrative -> structured, single response ->
    ↪ multi-part, etc.)

**Strategy D - Contextual Enhancement:** Add specific domain knowledge or constraints that weren't in the original

**Strategy E - Complexity Modulation:** Significantly increase or decrease the cognitive complexity of the task

**Strategy F - Functional Input Integration:** Incorporate functional inputs in a novel way that changes the prompt's core
    ↪ operation

3. Generate the final mutated prompt bracketed with <prompt> and </prompt>.

## Available Functional Inputs:
- {obs} : current observation
- {game_info} : information about the game (possible actions and goal)
- {subgoal} : current subgoal that you're working towards
- {action_sequence}: action sequence towards current subgoal
- {observation_sequence}: observation sequence towards current subgoal
- {success_condition}: termination condition of the current subgoal
- {action_obs_seq}: action-observation pairs towards current subgoal
- {survival_plan}: survival plan
- {history}: history of the last 16 action-observation pairs
- {entries_successful_goal}: most similar successful subgoals to the current one
- {entries_failed_goal}: most similar failed subgoals to the current one

**CRITICAL:** Use functional inputs with exact bracket names. Ensure the mutation creates a substantially different prompt
    ↪ that would produce notably different outputs than the crossover result.
Output your asnwer in thne follwing way:
REASONING: <your reasoning>
PROMPT: <mutated prompt>
"""
```

V. Initial Population Genomes

This Appendix details the initial population of genetic algorithm described in section 3.3. First, we show examples of prompts proposed by Claude-Sonnet-4.5 for each of the modules. We use those in order to construct Full[Claude] genome. For the rest of genomes we use hand-crafted prompts. We detail genomes in the subsections below.

V.1. Prompts proposed by Sonnet-4

Those prompts were created using Claude-Sonnet-4.5, which was tasked with the creation of a prompt for each module. We call those "default" prompts

Prompt Template

```
default_sequential_prompt = """You always have to output one of the above actions at a time and no other text. You always
    ↪ have to output an action until the episode terminates."""

default_highlevel_prompt = """
You are a strategic planner for a video game AI. Analyze the current game state and create achievable subgoals that advance
    ↪ toward the main objective.

REQUIREMENTS:
- Subgoals must be immediately achievable with current capabilities
- Focus on next logical steps, not distant goals
- Each subgoal should have clear success criteria

CURRENT STATE: {obs}
GAME INFO: {game_info}

Create a sequential plan with 2-3 subgoals."""
default_lowlevel_prompt = """  You are an action executor in a video game AI system. Given a subgoal from the high-level
        ↪ planner, propose a sequence of actions to achieve it.
        ####################################################
        CURRENT SUBGOAL: {subgoal}
        CURRENT STATE: {obs}
        PREVIOUS ACTIONS: {action_sequence}

        Plan the full sequence of actions needed to complete the subgoal. Avoid repeating actions if observations don't
        ↪ change.
        Avoid extra commentary outside the REASONING and ACTIONS list.
        """
default_termination_prompt = """
        You are a termination evaluator for a video game AI. Check if the agent has completed its subgoal.

        CURRENT STATE: {obs}
        SUBGOAL: {subgoal}
        SUCCESS CONDITION: {success_condition}
        RECENT ACTIONS: {action_sequence}

        Compare the current state with the success condition to determine if the subgoal is complete. Provide feedback to
    ↪ help the agent improve.
"""

default_summariser_prompt = """
        You are a critic analyzing an agent's subgoal attempt. Identify the key factor that caused success or failure.

        SUBGOAL: {subgoal}
        OUTCOME: {outcome}
        ACTION HISTORY: {action_obs_seq}

        Focus on specific resources and quantities that mattered most. If no resources involved, identify the next most
    ↪ important factor.
        """
default_amygdala_prompt = """
        Decide if survival mode should activate.

        Observation: {obs}
        Survival plan: {survival_plan}

        1. Check if observation meets any subtask prerequisites.
        2. If several match, pick highest priority.
"""
default_loop_prompt = """
        Task: Decide if the agent is stuck in a loop.

        Loop = repeating actions without meaningful progress toward the subgoal
        (progress = closer to goal, new info, removing failed paths, or advancing game state).

        Data:
        - Observation: {obs}
        - Subgoal: {subgoal}
        - Termination condition: {success_condition}
        - Action-observation history: {history}

        Steps:
        1. Check if enough steps have been taken to allow exploration.
        2. Look for repeated patterns without progress.
        3. If loop detected, identify cause: missing info, unknown prerequisite, or unexplored path.
        """
default_explorer_prompt = """
        Task: Create an exploration plan to help the agent discover new skills.

        Data:
        - Game info: {game_info}
        - Observation: {obs}
        - Subgoal summary: {summary}
        - Recent 16 action-observation pairs: {history}

        Steps:
        1. Analyze the environment and agent's situation.
        2. Propose a focused exploration plan with clear purpose, conditions, and indicators.
```

```
    """
```

V.2. Initial population

Detailed genome descriptions for the initial population.

Baseline genome   This genome corresponds to the baseline structure used in BALROG.

Baseline Genome

```
genome_basic = {
"id": "3",
"hierarchy": 0,
"amygdala": 0,
"loop_evaluator": 0,
"explorer": 0,
"summariser": 0,
"time_decay": [0, 0.01],
"cosine_cutoff": [0, 0.05],
"epsilon": [0, 0.01],
"temperature": 1.0,
"prompts": {
    "high_level": [0, default_highlevel_prompt],
    "low_level": [0, default_lowlevel_prompt],
    "amygdala": [0, default_amygdala_prompt],
    "loop": [0, default_loop_prompt],
    "termination": [0, default_termination_prompt],
    "summariser": [0, default_summariser_prompt],
    "explorer": [0, default_explorer_prompt],
    "sequential": [1, default_sequential_prompt]
},
"fitness": ...
}
```

Hierarchical[Hand-Crafted] genome   This genome corresponds to hierarchy from Section G.1 combined with memory 3.4, without amygdala and explorer. We use this architecture as one of the initial seeds, because we found that it gives the most stable performance across all environments.

Hierarchical[Hand-Crafted] Genome

```
genome_stable = {
"id": "2",
"hierarchy": 1,
"amygdala": 0,
"loop_evaluator": 1,
"explorer": 0,
"summariser": 1,
"time_decay": [1, 0.01],
"cosine_cutoff": [0, 0.1],
"epsilon": [0, 0.01],
"temperature": 1.0,
"prompts": {
    "high_level": [1,
    """You are a strategic planner in a hierarchical video game AI system. Your role is to analyze the current game state and
    ↪ generate achievable subgoals that strategically advance toward the main objective.

        CRITICAL CONSTRAINTS:
        - Subgoals must be immediately achievable given the current agent state and capabilities
        - Focus on the next logical progression steps, not distant end-goals
        - Each subgoal should have clear, observable success criteria
        - Subgoals should be novel and interesting, compared to previous attempts

        Below I will provide the game description, available actions, and current state information.
        Game description:
        {game_info}
        ##########################################################
        CURRENT CONTEXT: \n
        - Game State: {obs} \n
        - Survival plan provided by the survival planner, that you should consider for your tasks: {survival_plan}
        - Here are most similar successful entries from the archive: {entries_successful_goal} \n
        - Here are most similar failed entries from the archive: {entries_failed_goal} \n

        ANALYSIS FRAMEWORK:
```

```
        1. Analyse the summary from previous runs and let it guide your decision making.
        2. Assess what is immediately possible given current agent state and environment
        3. Identify what kind of actions could be considered novel or interesting
        4. Identify the most direct path toward the main objective
        5. Select subgoals that form a logical sequence
        6. Ensure each subgoal can be verified through observable game state changes

        SUBGOAL SELECTION CRITERIA:
        - Feasible: Can be started immediately with current resources/position
        - Measurable: Success/failure can be determined from game observations
        - Progressive: Each subgoal enables the next or advances toward main goal
        - Specific: Clear enough for a lower-level agent to understand and execute
        - Considerate of the summary of previos runs

        Make sure that your subgoals are sequential. """],

"low_level": [1,
"""You are an important executor component of a hierarchical video game system. You are given one of higher level option
 ↪ and its termination condition proposed by the higher level planner. Your role is to propose a sequence of actions
 ↪ that will make you progress towards the given option." \
    Below I will provide you with the game description, possible actions you can take and the overall goal of the game.

    ####################################################
    Here is a subgoal provided by the high level planner that you should focus on completing: {subgoal} \n
    Here is your current state: {obs} \n
    Here is the action-observation sequence towards current subgoal: {action_sequence} \n
    Here are the most similar successful entries from the archive: {entries_successful_goal} \n
    Here are the most similar failed entries from the archive: {entries_failed_goal} \n
    Use the action and observation sequence together with the current state to decide the **full ordered sequence of
 ↪ actions** that will achieve the subgoal. \n
    Avoid repeating the same actions if the observation doesn't change. \n"""],

"amygdala": [0, """
    You are an important component in a hierarchical video game system. Your role is to determine if the agent is in
 ↪ danger and should activate survival mode. Below I will provide you with current observation and a survival plan from
 ↪ the higher level agent. \n

    Current observation: {obs} \n
    Survival plan: {survival_plan} \n

    Your role is to analyse the observation and survival plan given by higher level system and determine if the current
 ↪ observation satisfies any of the prerequites for any of the survival components. If there are prerequsites satisfied
 ↪ for multiple components, then return the one with the highest priority. \n
    First reason, then output True or False depending if you decide to activate survival plan. If you output True, then
 ↪ output one of the survival subtasks. If you decide to not activate survival plan, then output None as the survival
 ↪ subtask. \n

    REASONING: <your reasoning> \n
    ACTIVATE SURVIVAL: <True/False> \n
    SURVIVAL SUBTASK: <survival subtask name or None if False> \n

    """],
"loop": [1,
"""You are an important loop evaluator component of a hierarchical video game system.
You are going to receive details about game progress such as: current observation, current subgoal, current termination
 ↪ conditions, action sequence towards current subgoal and observation sequence towards current subgoal.
Your task is to evaluate if the agent is stuck in a loop and give summary of the actions taken.
A loop occurs when the agent repeats a sequence of actions multiple times without achieving meaningful progress toward
 ↪ its current goal, where 'meaningful progress' includes: getting closer to the objective, discovering new information,
 ↪ eliminating failed approaches, or changing the game state in a way that advances toward the subgoal.
It is important that you let the agent explore enough but also decide when to terminate to get out of the loop. \n

Details: \n
Here is your current state: {obs} \n
Here is a subgoal lower level agent is working towards: {subgoal} \n
Here is the most recent action-observation pairs that should help you decide if agent is stuck in a loop: {history}\n \n

Instructions:\n
Analyse the details. Avoid giving any judgement. \n
Think about how many steps the agent needs in order to complete the subgoal and use that to help you reason if agent is
 ↪ stuck in a loop. \n
Then, given your analysis, decide if the actions proposed by the lower level agent are leading to the termination
 ↪ condition or if the agent is stuck in a loop.
If a loop is detected, analyse if the agent is stuck due to a lack of necessary information, an unknown prerequisite, or
 ↪ an unexplored path. Your summary should clearly articulate this gap in knowledge and suggest that exploration might
 ↪ be required to break the loop and find alternative solutions. \n"""],
"termination": [1, """
You are an important termination evaluator component of a hierarchical video game system. \n
Your task is to: \n
1. Determine whether the agent has met the termination condition for a subgoal. \n
2. Provide a concise summary that will help guide the lower-level agent's future actions. \n\n

Details: \n
Here is your currect state that you should compare with termination condition: {obs} \n
Here is the subgoal lower level agent is working towards: {subgoal} \n
Here is the termination condition of the above subgoal given by the higher level agent: {success_condition} \n \n

Instructions:\n
Analyse the subgoal and its termination condition and decide if the subgoal is completed. \n
```

```
        Then use action-observation sequence: {action_sequence} to give a high level summary of current evaluation. This summary
        ↪ will later be passed to low level agent in order to improve its actions.
        Remember that your summary will be passed to low level component in order to improve its actions.  \n \n"""],
        "summariser": [1,
        """You are a critic module analyzing an agent's attempt to achieve a subgoal in a game environment.
        Your task is to identify the **single most important factor** that caused SUCCESS or FAILURE.

        Information:
        - Target subgoal: {subgoal}
        - Outcome of the action-observation sequence: {outcome}
        - Action-observation history: {action_obs_seq}
        - Game context: {game_info}

        Instructions:
        - Think briefly about what helped or prevented success.
        - Focus mostly on **specific resources and their quantities** (e.g., "3 pieces of wood", "1 iron ingot").
        - If resources were missing, state **exactly which and how many** were missing.
        - Ignore minor details or redundant actions.
        - Express the result in **one short sentence**.
        - If no resources are involved, state the next most relevant factor."""],
        "explorer": [0, default_explorer_prompt],
        "sequential": [0, default_sequential_prompt]
    },
    "fitness": ...
}
```

Full[Claude] genome Default genome consists of all modules being active and prompts proposed by Claude-Sonnet-4.5. We add this genome to initial population, as they remove human bias.

Full[Claude] Genome

```
genome_default = {
"id": "1",
"hierarchy": 1,
"amygdala": 1,
"loop_evaluator": 1,
"explorer": 1,
"summariser": 1,
"time_decay": [1, 0.01],      # [active_flag, value]
"cosine_cutoff": [1, 0.05],
"epsilon": [1, 0.1],
"temperature": 1.0,           # continuous
"prompts": {                  # [active_flag, text]
    "high_level": [1, default_highlevel_prompt],
    "low_level": [1, default_lowlevel_prompt],
    "amygdala": [1, default_amygdala_prompt],
    "loop": [1, default_loop_prompt],
    "termination": [1, default_termination_prompt],
    "summariser": [1, default_summariser_prompt],
    "explorer": [1, default_explorer_prompt],
    "sequential": [0, default_sequential_prompt]
},
"fitness": ..
}
```

Full[Hand-Crafted] This genome represents a full structure with all modules active and hand-crafted prompts.

Full[Hand-Crafted] Genome

```
genome_full = {
    "id": "1",
    "hierarchy": 1,
    "amygdala": 1,
    "loop_evaluator": 1,
    "explorer": 1,
    "summariser": 1,
    "time_decay": [1, 0.01],
    "cosine_cutoff": [1, 0.05],
    "epsilon": [1, 0.1],
    "temperature": 1.0,
    "prompts": {
        "high_level": [1, """You are a strategic planner in a hierarchical video game AI system. Your role is to analyze the
        ↪ current game state and generate achievable subgoals that strategically advance toward the main objective.
        CRITICAL CONSTRAINTS:
        - Subgoals must be immediately achievable given the current agent state and capabilities
        - Focus on the next logical progression steps, not distant end-goals
```

```
- Each subgoal should have clear, observable success criteria
- Subgoals should be novel and interesting, compared to previous attempts

Below I will provide the game description, available actions, and current state information.
Game description:
{game_info}
##########################################################
CURRENT CONTEXT: \n
- Game State: {obs} \n
- Summary from the previous high level plan : {summary} \n
- Survival plan provided by the survival planner, that you should consider for your tasks: {survival_plan}
- Here are most similar successful entries from the archive: {entries_successful_goal} \n
- Here are most similar failed entries from the archive: {entries_failed_goal} \n

ANALYSIS FRAMEWORK:
1. Analyse the summary from previous runs and let it guide your decision making.
2. Assess what is immediately possible given current agent state and environment
3. Identify what kind of actions could be considered novel or interesting
4. Identify the most direct path toward the main objective
5. Select subgoals that form a logical sequence
6. Ensure each subgoal can be verified through observable game state changes

SUBGOAL SELECTION CRITERIA:
- Feasible: Can be started immediately with current resources/position
- Measurable: Success/failure can be determined from game observations
- Progressive: Each subgoal enables the next or advances toward main goal
- Specific: Clear enough for a lower-level agent to understand and execute
- Considerate of the summary of previos runs

Make sure that your subgoals are sequential. """],
"low_level": [1, """You are an important executor component of a hierarchical video game system. You are given one of
  ↪ higher level option and its termination condition proposed by the higher level planner. Your role is to propose an
  ↪ action that will make you progress towards the given option." \
Below I will provide you with the game description, possible actions you can take and the overall goal of the game.

##################################################
Here is a subgoal provided by the high level planner that you should focus on completing: {subgoal} \n
Here is your current state: {obs} \n
Here is the action-observation sequence towards current subgoal: {action_sequence} \n
Here are the most similar successful entries from the archive: {entries_successful_goal} \n
Here are the most similar failed entries from the archive: {entries_failed_goal} \n
Use the action and observation sequence together with the current state to decide the **full ordered sequence of
  ↪ actions** that will achieve the subgoal. \n
Avoid repeating the same actions if the observation doesn't change. \n"""],
"amygdala": [1, """
You are an important component in a hierarchical video game system. Your role is to determine if the agent is in danger
  ↪ and should activate survival mode. Below I will provide you with current observation and a survival plan from the
  ↪ higher level agent. \n

Current observation: {obs} \n
Survival plan: {survival_plan} \n

Your role is to analyse the observation and survival plan given by higher level system and determine if the current
  ↪ observation satisfies any of the prerequites for any of the survival components. If there are prerequites satisfied
  ↪ for multiple components, then return the one with the highest priority. \n
First reason, then output True or False depending if you decide to activate survival plan. If you output True, then
  ↪ output one of the survival subtasks. If you decide to not activate survival plan, then output None as the survival
  ↪ subtask. \n

REASONING: <your reasoning> \n
ACTIVATE SURVIVAL: <True/False> \n
SURVIVAL SUBTASK: <survival subtask name or None if False> \n

"""],
"loop": [1, """You are an important loop evaluator component of a hierarchical video game system.
You are going to receive details about game progress such as: current observation, current subgoal, current termination
  ↪ conditions, action sequence towards current subgoal and observation sequence towards current subgoal.
Your task is to evaluate if the agent is stuck in a loop and give summary of the actions taken.
A loop occurs when the agent repeats a sequence of actions multiple times without achieving meaningful progress toward
  ↪ its current goal, where 'meaningful progress' includes: getting closer to the objective, discovering new information,
  ↪ eliminating failed approaches, or changing the game state in a way that advances toward the subgoal.
It is important that you let the agent explore enough but also decide when to terminate to get out of the loop. \n

Details: \n
Here is your current state: {obs} \n
Here is a subgoal lower level agent is working towards: {subgoal} \n
Here is the most recent action-observation pairs that should help you decide if agent is stuck in a loop: {history}\n \n

Instructions:\n
Analyse the details. Avoid giving any judgement. \n
Think about how many steps the agent needs in order to complete the subgoal and use that to help you reason if agent is
  ↪ stuck in a loop. \n
Then, given your analysis, decide if the actions proposed by the lower level agent are leading to the termination
  ↪ condition or if the agent is stuck in a loop.
If a loop is detected, analyse if the agent is stuck due to a lack of necessary information, an unknown prerequisite, or
  ↪ an unexplored path. Your summary should clearly articulate this gap in knowledge and suggest that exploration might
  ↪ be required to break the loop and find alternative solutions. \n"""],
"termination": [1, """
You are an important termination evaluator component of a hierarchical video game system. \n
Your task is to: \n
```

```
    1. Determine whether the agent has met the termination condition for a subgoal. \n
    2. Provide a concise summary that will help guide the lower-level agent's future actions. \n\n

    Details: \n
    Here is your currect state that you should compare with termination condition: {obs} \n
    Here is the subgoal lower level agent is working towards: {subgoal} \n
    Here is the termination condition of the above subgoal given by the higher level agent: {success_condition} \n \n

    Instructions:\n
    Analyse the subgoal and its termination condition and decide if the subgoal is completed. \n
    Then use action-observation sequence: {action_sequence} to give a high level summary of current evaluation. This summary
     ↪ will later be passed to low level agent in order to improve its actions.
    Remember that your summary will be passed to low level component in order to improve its actions.  \n \n"""],
    "summariser": [1,  """You are a critic module analyzing an agent's attempt to achieve a subgoal in a game environment.
    Your task is to identify the **single most important factor** that caused SUCCESS or FAILURE.

    Information:
    - Target subgoal: {subgoal}
    - Outcome of the action-observation sequence: {outcome}
    - Action-observation history: {action_obs_seq}
    - Game context: {game_info}

    Instructions:
    - Think briefly about what helped or prevented success.
    - Focus mostly on **specific resources and their quantities** (e.g., "3 pieces of wood", "1 iron ingot").
    - If resources were missing, state **exactly which and how many** were missing.
    - Ignore minor details or redundant actions.
    - Express the result in **one short sentence**.
    - If no resources are involved, state the next most relevant factor."""],
    "explorer": [1, """You are an important component of a hierarchical video game AI system.
    You have been called because the agent is stuck and needs to explore the environment.
    Please provide a percise exploration plan that will help the agent to explore the new areas of the environment.
    Below I will provide you with details about the game:
    Game info: {game_info} \n
    Current observation: {obs}  \n
    Most recent 16 action-observation pairs: {history}  \n
    Use the information above to reason about the environment and provide a plan that will help the agent to explore the new
     ↪ areas of the environment.
    Output your answer in the following format:
    REASONING : <your reasoning>
    EXPLORATION PLAN:
    {{
    "reasoning": "Brief analysis of environment and strategic approach",
    "subgoals": [{{
        "Explore": {{
        "description": "Describe exploration strategy and its purpose",
        "prerequisites": None,
        "success_condition": "Observable conditions that indicate completion",
        "penalty_component": "What agent should be penalised for",
        "progress_indicators": "Intermediate signs that the agent is making progress",
        "estimated_priority": "high/medium/low based on urgency for main objective"
        }},
    }}]
    }}
    """],
    "sequential": [0, default_sequential_prompt]
},
"fitness": ...
}
```

W. Final genomes returned by TAME

In this Appendix we present genomes returned by TAME per each game through the first run of genetic algorithm using Gemini-2.0-Flash.

BabyAI Final Genome

```
    {
"hierarchy": 1,
"amygdala": 1,
"loop_evaluator": 1,
"explorer": 0,
"summariser": 1,
"time_decay": [
  1,
  0.014080444046038391
],
"cosine_cutoff": [
  1,
  0.05
],
"epsilon": [
```

```
        0,
        0.01
],
"temperature": 1.0,
"prompts": {
  "high_level": [
      1,
      "You are a strategic planner in a hierarchical video game AI system. Your role is to analyze the current game state and
  ↪ generate achievable subgoals that strategically advance toward the main objective.\n\n
  ↪ CRITICAL CONSTRAINTS:\n                              - Subgoals must be immediately achievable given the current agent
  ↪ state and capabilities\n                    - Focus on the next logical progression steps, not distant
  ↪ end-goals\n                          - Each subgoal should have clear, observable success criteria\n
  ↪              - Subgoals should be novel and interesting, compared to previous attempts \n\n
  ↪ Below I will provide the game description, available actions, and current state information.\n
  ↪     Game description:\n                              {game_info}\n
  ↪ ###########################################################\n                              CURRENT CONTEXT: \n\n
  ↪              - Game State: {obs} \n\n                        - Survival plan provided by the survival
  ↪ planner, that you should consider for your tasks: {survival_plan}\n                        - Here are most
  ↪ similar successful entries from the archive: {entries_successful_goal} \n\n                          - Here are
  ↪ most similar failed entries from the archive: {entries_failed_goal} \n\n\n                          ANALYSIS
  ↪ FRAPAPMEWORK:\n                      1. Analyse the summary from previous runs and let it guide your decision
  ↪ making. \n                            2. Assess what is immediately possible given current agent state and
  ↪ environment\n                          3. Identify what kind of actions could be considered novel or interesting\n
  ↪                        4. Identify the most direct path toward the main objective\n                          5.
  ↪ Select subgoals that form a logical sequence\n                          6. Ensure each subgoal can be verified
  ↪ through observable game state changes\n                      SUBGOAL SELECTION CRITERIA:\n
  ↪        - Feasible: Can be started immediately with current resources/position\n                          -
  ↪ Measurable: Success/failure can be determined from game observations\n                          - Progressive: Each
  ↪ subgoal enables the next or advances toward main goal\n                          - Specific: Clear enough for a
  ↪ lower-level agent to understand and execute\n                      - Considerate of the summary of previos
  ↪ runs\n\n                      Make sure that your subgoals are sequential. "
  ],
  "low_level": [
      1,
      "Hello! I am your AI Game Coach. My purpose is to analyze your game state and provide strategic advice to help you
  ↪ achieve your goals. Think of me as your co-pilot!\n\nHere's the situation: The high-level planner has assigned you a
  ↪ subgoal to work towards. I will analyze your current state, past actions, and learn from successful and failed
  ↪ attempts at similar subgoals. Then, I'll recommend a sequence of actions to help you reach your
  ↪ objective.\n\n###############################################\n\nCurrent Subgoal: {subgoal}\n\nTermination
  ↪ Condition: {success_condition}\n\nGame Information (Possible Actions, Overall Goal): {game_info}\n\nYour Current
  ↪ State: {obs}\n\nAction-Observation History: {history}\n\nMost Similar Successful Attempts at This Subgoal:
  ↪ {entries_successful_goal}\n\nMost Similar Failed Attempts at This Subgoal: {entries_failed_goal}\n\nBased on this
  ↪ information, what **sequence of actions** do I recommend *you* take to achieve the subgoal? Be sure to consider the
  ↪ history, and learn from both the successes and failures of others. I'm looking for strategic advice, not just a
  ↪ single action. Explain your reasoning behind each action."
  ],
  "amygdala": [
      1,
      "\n                              You are an important component in a hierarchical video game system. Your role is to
  ↪ determine if the agent is in danger and should activate survival mode. Below I will provide you with current
  ↪ observation and a survival plan from the higher level agent. \n\n\n                              Current observation:
  ↪ {obs} \n\n                            Survival plan: {survival_plan} \n\n                                  \n
  ↪              Your role is to analyse the observation and survival plan given by higher level system and determine if
  ↪ the current observation satisfies any of the prerequites for any of the survival components. If you output
  ↪ prerequsites satisfied for multiple components, then return the one with the highest priority. \n\n
  ↪          First reason, then output True or False depending if you decide to activate survival plan. If you output
  ↪ True, then output one of the survival subtasks. If you decide to not activate survival plan, then output None as the
  ↪ survival subtask. \n\n\n                              REASONING: <your reasoning> \n\n
  ↪ ACTIVATE SURVIVAL: <True/False> \n \n                              SURVIVAL SUBTASK: <survival subtask name or None if
  ↪ False> \n\n\n                "
  ],
  "loop": [
      1,
      "You are an important loop evaluator component of a hierarchical video game system. \n                              You are
  ↪ going to receive details about game progress such as: current observation, current subgoal, current termination
  ↪ conditions, action sequence towards current subgoal and observation sequence towards current subgoal. \n
  ↪          Your task is to evaluate if the agent is stuck in a loop and give summary of the actions taken. \n
  ↪          A loop occurs when the agent repeats a sequence of actions multiple times without achieving meaningful
  ↪ progress toward its current goal, where 'meaningful progress' includes: getting closer to the objective, discovering
  ↪ new information, eliminating failed approaches, or changing the game state in a way that advances toward the subgoal.
  ↪ \n                      It is important that you let the agent explore enough but also decide when to terminate to
  ↪ get out of the loop. \n\n\n                          Details: \n                          Here is your current state:
  ↪ {obs} \n                          Here is a subgoal lower level agent is working towards: {subgoal} \n\n
  ↪          Here is the most recent action-observation pairs that should help you decide if agent is stuck in a loop:
  ↪ {history}\n \n\n\n                          Instructions:\n                          Analyse the details. Avoid giving
  ↪ any judgement. \n\n                          Think about how many steps the agent needs in order to complete the
  ↪ subgoal and use that to help you reason if agent is stuck in a loop. \n\n                          Then, given your
  ↪ analysis, decide if the actions proposed by the lower level agent are leading to the termination condition or if the
  ↪ agent is stuck in a loop.\n                          If a loop is detected, analyse if the agent is stuck due to a lack
  ↪ of necessary information, an unknown prerequisite, or an unexplored path. Your summary should clearly articulate this
  ↪ gap in knowledge and suggest that exploration might be required to break the loop and find alternative solutions. \n"
  ],
  "termination": [
      1,
      "You are a risk-aware termination evaluator within a hierarchical video game system, focused on survival and mission
  ↪ success. Assume the game environment is dynamic and potentially hostile.\n\nYour task is to:\n\n1. Determine whether
  ↪ the agent has met the termination condition for a subgoal, AND assess the risk incurred while pursuing that
  ↪ subgoal.\n\n2. Provide a concise summary that will guide the lower-level agent's future actions, specifically
  ↪ considering risk mitigation strategies.\n\nDetails:\n\nHere is the current state: {obs} and a history of recent
  ↪ states and actions {history}. The game environment details and survival instructions are : {game_info} and
```

```
      ↪ {survival_plan} respectively. Compare these with the subgoal and its termination condition.\n\nHere is the subgoal
      ↪ the lower-level agent is working towards: {subgoal}\n\nHere is the termination condition of the above subgoal given
      ↪ by the higher-level agent: {success_condition}\n\nHere is the action-observation sequence executed to achieve the
      ↪ subgoal: {action_obs_seq}\n\nInstructions:\n\n1.  Analyze the subgoal, its termination condition, the game
      ↪ environment, and the action-observation sequence.\n2.  Determine if the subgoal is completed.\n3.  Evaluate the risk
      ↪ associated with the actions taken. Consider factors such as proximity to dangers (enemies, hazards), resource
      ↪ consumption, and deviation from the {survival_plan}.\n4.  Compare the current situation with similar successful
      ↪ {entries_successful_goal} and failed {entries_failed_goal} subgoals.\n5.  Provide a summary that addresses both
      ↪ subgoal completion AND risk. The summary *must* include actionable suggestions for the lower-level agent to improve
      ↪ its actions, with a strong emphasis on mitigating risk in future attempts. Focus on information that would have been
      ↪ useful to avoid failures described in {entries_failed_goal}.\nRemember that your summary will be passed to a low
      ↪ level component in order to improve its actions and survivability."
    ],
    "summariser": [
      1,
      "You are a critic module analyzing an agent's attempt to achieve a subgoal in a game environment.\n
      ↪     Your task is to identify the **single most important factor** that caused SUCCESS or FAILURE.\n\n
      ↪       Information:\n                        - Target subgoal: {subgoal}\n                          - Outcome of the
      ↪ action-observation sequence: {outcome}\n                          - Action-observation history: {action_obs_seq}\n
      ↪            - Game context: {game_info}\n\n                              Instructions:\n                          -
      ↪ Think briefly about what helped or prevented success.\n                          - Focus mostly on **specific resources
      ↪ and their quantities** (e.g., \"3 pieces of wood\", \"1 iron ingot\").\n                          - If resources were
      ↪ missing, state **exactly which and how many** were missing.\n                          - Ignore minor details or
      ↪ redundant actions.\n                          - Express the result in **one short sentence**.\n
      ↪ - If no resources are involved, state the next most relevant factor."
    ],
    "explorer": [
      0,
      "\n          Task: Create an exploration plan to help the agent discover new skills.\n\n        Data:\n      - Game
      ↪ info: {game_info}\n        - Observation: {obs}\n        - Subgoal summary: {summary}\n      - Recent 16
      ↪ action–observation pairs: {history}\n        Steps:\n        1. Analyze the environment and agent's
      ↪ situation.\n        2. Propose a focused exploration plan with clear purpose, conditions, and indicators.\n\n    "
    ],
    "sequential": [
      0,
      "You always have to output one of the above actions at a time and no other text. You always have to output an action
      ↪ until the episode terminates."
    ]
  },
  "fitness": 72.0,
  "id": "8c52d35e-bbb7-4b7d-b683-26b0e7aa3936",
  "_std_error": 6.349803146555017
}
```

BabaIsAI Final Genome

```
  {
"hierarchy": 1,
"amygdala": 0,
"loop_evaluator": 1,
"explorer": 1,
"summariser": 1,
"time_decay": [
  1,
  0.004528704008914386
],
"cosine_cutoff": [
  1,
  0.06037953831283245
],
"epsilon": [
  1,
  0.08233296401956124
],
"temperature": 1.016671019014213,
"prompts": {
  "high_level": [
    1,
    "\nYou are a strategic planner for a video game AI. Analyze the current game state and create achievable subgoals that
    ↪ advance toward the main objective.\n\nREQUIREMENTS:\n- Subgoals must be immediately achievable with current
    ↪ capabilities\n- Focus on next logical steps, not distant goals\n- Each subgoal should have clear success
    ↪ criteria\nCURRENT STATE: {obs}\nGAME INFO: {game_info}\n\nCreate a sequential plan with 2-3 subgoals."
  ],
  "low_level": [
    1,
    "You are an action executor in a video game AI system, responsible for survival and goal achievement. Given a subgoal
    ↪ from the high-level planner, propose a sequence of actions to achieve it while minimizing risk.\n\n
    ↪ ##############################################\n          CURRENT SUBGOAL: {subgoal}\n          CURRENT STATE:
    ↪ {obs}\n          GAME INFORMATION: {game_info}\n          PREVIOUS ACTION-OBSERVATION SEQUENCE: {action_obs_seq}\n
    ↪ SIMILAR SUCCESSFUL SUBGOALS: {entries_successful_goal}\n          SIMILAR FAILED SUBGOALS: {entries_failed_goal}\n\n
    ↪     Consider the potential risks associated with each action in the context of the current state and previous
    ↪ actions. Actions that lead to outcomes similar to those in '{entries_failed_goal}' should be avoided. Prioritize
    ↪ actions that are consistent with the success patterns observed in '{entries_successful_goal}'. Use '{game_info}' for
    ↪ possible actions. Use '{survival_plan}' to help avoiding fatal errors.\n          \n          Plan the full sequence of
    ↪ actions needed to complete the subgoal. Ensure survival is prioritized throughout the sequence. If a planned action
```

```
        ↪ has high risk, select a safer alternative or terminate the current sequence and replan.\n        Avoid extra
        ↪ commentary outside the REASONING and ACTIONS list."
    ],
    "amygdala": [
        0,
        "\n        Decide if survival mode should activate.\n\n        Observation: {obs}\n        Survival plan:
        ↪ {survival_plan}\n\n        1. Check if observation meets any subtask prerequisites.\n        2. If several match,
        ↪ pick highest priority.\n"
    ],
    "loop": [
        1,
        "\n        Task: Decide if the agent is stuck in a loop.\n\n        Loop = repeating actions without meaningful
        ↪ progress toward the subgoal\n        (progress = closer to goal, new info, removing failed paths, or advancing game
        ↪ state).\n\n        Data:\n        - Observation: {obs}\n        - Subgoal: {subgoal}\n        - Termination
        ↪ condition: {success_condition}\n        - Action\u2013observation history: {history}\n\n        Steps:\n        1.
        ↪ Check if enough steps have been taken to allow exploration.\n        2. Look for repeated patterns without
        ↪ progress.\n        3. If loop detected, identify cause: missing info, unknown prerequisite, or unexplored path.\n
        ↪        "
    ],
    "termination": [
        1,
        "\n            You are a termination evaluator for a video game AI. Check if the agent has completed its subgoal.\n\n
        ↪        CURRENT STATE: {obs}\n            SUBGOAL: {subgoal}\n            SUCCESS CONDITION: {success_condition}\n
        ↪            RECENT ACTIONS: {action_sequence}\n            Compare the current state with the success condition to
        ↪ determine if the subgoal is complete. Provide feedback to help the agent improve.\n"
    ],
    "summariser": [
        1,
        "You are a critic analyzing an agent's subgoal attempt by comparing it to similar past attempts. Identify the key
        ↪ factors that caused success or failure by contrasting this attempt with the most similar successful and failed
        ↪ attempts.\n\nSUBGOAL: {subgoal}\nOUTCOME: {outcome}\nACTION HISTORY: {action_obs_seq}\nSUCCESSFUL ATTEMPTS:
        ↪ {entries_successful_goal}\nFAILED ATTEMPTS: {entries_failed_goal}\n\nCompare the resources used, quantities involved,
        ↪ and the sequence of actions in the current attempt to those in the SUCCESSFUL ATTEMPTS and FAILED ATTEMPTS. What
        ↪ specific differences seem to have led to the observed OUTCOME? If no resources were involved, what differences in
        ↪ action sequences were crucial? Provide a concise explanation."
    ],
    "explorer": [
        1,
        "\n        Task: Create an exploration plan to help the agent discover new skills.\n\n        Data:\n        - Game
        ↪ info: {game_info}\n        - Observation: {obs}\n        - Subgoal summary: {summary}\n        - Recent 16
        ↪ action\u2013observation pairs: {history}\n\n        Steps:\n        1. Analyze the environment and agent\u2019s
        ↪ situation.\n        2. Propose a focused exploration plan with clear purpose, conditions, and indicators.\n\n    "
    ],
    "sequential": [
        0,
        "You always have to output one of the above actions at a time and no other text. You always have to output an action
        ↪ until the episode terminates."
    ]
},
"fitness": 41.66666666666667,
"id": "08d71e90-74f1-4f22-a10a-f438431f93de",
"_std_error": 4.500514373894347
}
```

TextWorld Final Genome

```
genome_basic = {
    "id": "3",
    "hierarchy": 0,
    "amygdala": 0,
    "loop_evaluator": 0,
    "explorer": 0,
    "summariser": 0,
    "time_decay": [0, 0.01],
    "cosine_cutoff": [0, 0.05],
    "epsilon": [0, 0.01],
    "temperature": 1.0,
    "prompts": {
        "high_level": [0, default_highlevel_prompt],
        "low_level": [0, default_lowlevel_prompt],
        "amygdala": [0, default_amygdala_prompt],
        "loop": [0, default_loop_prompt],
        "termination": [0, default_termination_prompt],
        "summariser": [0, default_summariser_prompt],
        "explorer": [0, default_explorer_prompt],
        "sequential": [1, default_sequential_prompt]
    },
    "fitness": 32.55
}
```

Crafter Final Genome

```
   {
"hierarchy": 1,
"amygdala": 0,
"loop_evaluator": 1,
"explorer": 1,
"summariser": 1,
"time_decay": [
  1,
  0.01
],
"cosine_cutoff": [
  1,
  0.05018667404330796
],
"epsilon": [
  1,
  0.08838153559623807
],
"temperature": 1.0550853142525738,
"prompts": {
  "high_level": [
    1,
    "You are a strategic planner in a hierarchical video game AI system. Your role is to analyze the current game state and
 ↪ generate achievable subgoals that strategically advance toward the main objective. Your analysis should now *predict*
 ↪ the outcome of possible action sequences.\n\n                      CRITICAL CONSTRAINTS:\n
 ↪      - Subgoals must be immediately achievable given the current agent state and capabilities\n
 ↪      - Focus on the next logical progression steps, not distant end-goals\n                          - Each
 ↪ subgoal should have clear, observable success criteria\n              - Subgoals should be novel and
 ↪ interesting, compared to previous attempts \n\n                  Below I will provide the game description,
 ↪ available actions, and current state information.\n                      Game description:\n
 ↪      {game_info}\n          #########################################################\n
 ↪          CURRENT CONTEXT: \n\n                  - Game State: {obs} \n\n
 ↪   - Survival plan provided by the survival planner, that you should consider for your tasks: {survival_plan}\n
 ↪          - Here are most similar successful entries from the archive: {entries_successful_goal} \n\n
 ↪          - Here are most similar failed entries from the archive: {entries_failed_goal} \n\n
 ↪      - Recent History (last 16 action-observation pairs): {history}\n                          -
 ↪ Action-Observation Sequences of the most similar examples: {action_obs_seq}\n\n                      ANALYSIS
 ↪ FRAPAPMEWORK:\n                          1. Analyse the summary from previous runs and let it guide your decision
 ↪ making. \n                      2. Assess what is immediately possible given current agent state and
 ↪ environment\n                      3. Based on the current Game State, recent history ({history}), and past
 ↪ action-observation sequences ({action_obs_seq}), predict the *most likely outcome* (observation) of performing a few
 ↪ different possible action sequences.  Consider at least 3 different potential action sequences.\n
 ↪      4. Identify what kind of actions could be considered novel or interesting\n                              5.
 ↪ Identify the most direct path toward the main objective, taking into account the predicted outcomes of potential
 ↪ actions.\n                      6. Select subgoals that form a logical sequence\n                          7.
 ↪ Ensure each subgoal can be verified through observable game state changes\n\n                      SUBGOAL
 ↪ SELECTION CRITERIA:\n                          - Feasible: Can be started immediately with current
 ↪ resources/position\n                      - Measurable: Success/failure can be determined from game
 ↪ observations\n                      - Progressive: Each subgoal enables the next or advances toward main goal\n
 ↪      - Specific: Clear enough for a lower-level agent to understand and execute\n
 ↪      - Considerate of the summary of previous runs\n                          - **Outcome-Based:** The
 ↪ subgoal should lead to a *predicted outcome* that is advantageous for achieving the main objective.\n\n
 ↪          Make sure that your subgoals are sequential."
  ],
  "low_level": [
    1,
    "You are an important executor component of a hierarchical video game system in a **survival crafting game**. You are
 ↪ given a high-level option (subgoal) and its termination condition proposed by a higher-level planner. Your role is to
 ↪ propose an action that will make you progress towards the given option, keeping in mind the core mechanics of
 ↪ survival crafting: resource gathering, crafting, base building, and defending against threats. Below I will provide
 ↪ you with the game description, possible actions you can take, and the overall goal of the
 ↪ game.\n\n###################################################\nHere is a subgoal provided by the high level planner
 ↪ that you should focus on completing: {subgoal}\n\nHere is your current state: {obs}\n\nHere is the action-observation
 ↪ sequence towards current subgoal: {action_sequence}\n\nHere are the most similar successful entries from the archive:
 ↪ {entries_successful_goal}\n\nHere are the most similar failed entries from the archive: {entries_failed_goal}\n\nHere
 ↪ is your survival plan: {survival_plan}\n\nHere is the history of the last 16 action-observation pairs:
 ↪ {history}\n\nUse the action and observation sequence together with the current state, your survival plan, and recent
 ↪ history to decide the **full ordered sequence of actions** that will achieve the subgoal. Consider how your actions
 ↪ contribute to the overall survival plan. Prioritize actions that contribute to the core survival crafting goals of
 ↪ resource acquisition, building, crafting, and defense.\n\nAvoid repeating the same actions if the observation doesn't
 ↪ change. Ensure your actions are consistent with the survival plan and adapt as needed based on the recent history. If
 ↪ the {entries_successful_goal} indicates successful resource gathering or crafting strategies, lean towards
 ↪ replicating those. If {entries_failed_goal} indicates dangers, prioritize actions that increase safety. Consider the
 ↪ {obs} and choose actions appropriate for a survival crafting environment."
  ],
  "amygdala": [
    0,
    "\n        Decide if survival mode should activate.\n\n        Observation: {obs}\n        Survival plan:
 ↪ {survival_plan}\n\n        1. Check if observation meets any subtask prerequisites.\n        2. If several match,
 ↪ pick highest priority.\n"
  ],
  "loop": [
    1,
    "You are an expert game designer reviewing the behavior of an agent in your game. Your goal is to identify and
 ↪ eliminate situations where the agent gets stuck in unproductive loops.\n\nYou will receive the following details
 ↪ about the agent's current situation:\n\n   **Current Observation:** {obs}\n   **Subgoal:** {subgoal}\n
 ↪ **Action-Observation History:** {history}\n   **Game Information**: {game_info}\n\nInstructions:\n\n1.  **Analyze
```

```
            ↪ the Situation:** Carefully review the provided information. Do not make any immediate judgments about the agent's
            ↪ competence.\n\n2.  **Identify the Loop (if any):** Determine if the agent is repeating a sequence of actions without
            ↪ making meaningful progress towards the subgoal. \"Meaningful progress\" includes getting closer to completing the
            ↪ subgoal, discovering new and relevant information, or eliminating potential pathways.\n\n3.  **Root Cause Analysis:**
            ↪ If a loop is detected, analyze the underlying reasons. Is the loop caused by a flaw in the game design, an unclear
            ↪ subgoal, a lack of necessary information available to the agent, missing game mechanics, an impossible subgoal given
            ↪ the current mechanics, or an unexplored path?\n\n4.  **Design Improvement Recommendations:** Based on your analysis,
            ↪ suggest specific changes to the game design to prevent the agent from getting stuck in this loop in the future.
            ↪ Consider the following:\n\n    *    **Subgoal Modification:** Should the subgoal be rephrased, simplified, or broken
            ↪ down into smaller steps? Is the success condition well-defined and easily achievable?\n    *    **Game Mechanics
            ↪ Adjustment:** Should new actions or mechanics be added to the game to allow the agent to overcome the obstacle?
            ↪ Should existing mechanics be modified to be more intuitive or less restrictive? Should the rewards be changed?\n    *
            ↪    **Information Availability:** Does the agent have access to all the information it needs to make informed
            ↪ decisions? Should new information sources be added to the game?\n    *    **Survival Plan:** Does the survival plan
            ↪ influence this loop? Should it be altered to avoid this loop?\n\nYour recommendation should be specific and
            ↪ actionable, detailing exactly what aspects of the game design should be changed and why."
        ],
        "termination": [
          1,
          "                    \n                                You are an important termination evaluator component of a hierarchical video game
            ↪ system. \n\n                              Your task is to: \n\n                              1. Determine whether the agent has
            ↪ met the termination condition for a subgoal. \n\n                              2. Provide a concise summary that will help
            ↪ guide the lower-level agent's future actions. \n\n                              Details: \n\n
            ↪ Here is your currect state that you should compare with termination condition: {obs} \n\n                              Here
            ↪ is the subgoal lower level agent is working towards: {subgoal} \n\n                              Here is the termination
            ↪ condition of the above subgoal given by the higher level agent: {success_condition} \n \n\n\n
            ↪ Instructions:\n\n                              Analyse the subgoal and its termination condition and decide if the subgoal
            ↪ is completed. \n\n                              Then use action-observation sequence: {action_sequence} to give a high
            ↪ level summary of current evaluation. This summary will later be passed to low level agent in order to improve its
            ↪ actions.\n                              Remember that your summary will be passed to low level component in order to
            ↪ improve its actions.  \n \n"
        ],
        "summariser": [
          1,
          "You are a critic module analyzing an agent's attempt to achieve a subgoal in a survival game environment where
            ↪ resources decay over time. Your task is to identify the **single most important factor** that caused SUCCESS or
            ↪ FAILURE by **comparing the current action-observation sequence to similar successful and failed
            ↪ attempts.**\n\nInformation:\n- Target subgoal: {subgoal}\n- Outcome of the action-observation sequence: {outcome}\n-
            ↪ Action-observation history: {action_obs_seq}\n- Game context: {game_info}\n- Survival plan: {survival_plan}\n-
            ↪ Similar successful attempts: {entries_successful_goal}\n- Similar failed attempts:
            ↪ {entries_failed_goal}\n\nInstructions:\n- Analyze the current {action_obs_seq} in the context of
            ↪ {entries_successful_goal} and {entries_failed_goal}. Focus on identifying key differences in resource management,
            ↪ timing, and actions taken.\n- Consider the resources available and their decay rates as indicated in {game_info},
            ↪ paying close attention to how resource states differ between the successful, failed, and current attempt **at the
            ↪ moment of subgoal completion or failure**.\n- Identify the **single most critical divergence** that explains the
            ↪ outcome. This could be a specific resource that was more abundant (or less abundant) in the successful attempt, a
            ↪ crucial action that was taken (or not taken), or a timing difference that impacted resource availability.\n- Express
            ↪ the result in **one short sentence** highlighting the comparative aspect. For example: \"Unlike successful attempts,
            ↪ the agent failed to prioritize gathering berries before attempting to craft the tool, leading to starvation.\" Or,
            ↪ \"The agent successfully gathered wood within the same timeframe as past successful attempts, but, unlike those
            ↪ attempts, the observation sequence shows the agent prioritized building a fire and not water collection which lead to
            ↪ dehydration and subsequent death.\"\n- If resource decay is not the primary factor revealed by the comparison, state
            ↪ the next most relevant factor based on the differences observed between the current attempt and
            ↪ {entries_successful_goal} and {entries_failed_goal}, also taking into account {survival_plan} and {obs}."
        ],
        "explorer": [
          0,
          "\n          Task: Create an exploration plan to help the agent discover new skills.\n\n          Data:\n          - Game
            ↪ info: {game_info}\n          - Observation: {obs}\n          - Subgoal summary: {summary}\n          - Recent 16
            ↪ action\u2013observation pairs: {history}\n\n          Steps:\n          1. Analyze the environment and agent\u2019s
            ↪ situation.\n          2. Propose a focused exploration plan with clear purpose, conditions, and indicators.\n\n    "
        ],
        "sequential": [
          0,
          "You always have to output one of the above actions at a time and no other text. You always have to output an action
            ↪ until the episode terminates."
        ]
      },
      "fitness": 39.090909090909086,
      "id": "97c9c973-9f66-4391-a4c1-f8904921e95d",
      "_std_error": 4.904037803367701
}
```

MiniHack Final Genome

```
{
  "hierarchy": 0,
  "amygdala": 0,
  "loop_evaluator": 0,
  "explorer": 0,
  "summariser": 0,
  "time_decay": [
    0,
    0.01
```

```
      ],
      "cosine_cutoff": [
        0,
        0.05
      ],
      "epsilon": [
        0,
        0.01
      ],
      "temperature": 1.036744932065481,
      "prompts": {
        "high_level": [
          0,
          "\nYou are a strategic planner for a video game AI. Analyze the current game state and create achievable subgoals that
          ↪ advance toward the main objective.\n\nREQUIREMENTS:\n- Subgoals must be immediately achievable with current
          ↪ capabilities\n- Focus on next logical steps, not distant goals\n- Each subgoal should have clear success
          ↪ criteria\n\nCURRENT STATE: {obs}\nGAME INFO: {game_info}\n\nCreate a sequential plan with 2-3 subgoals."
        ],
        "low_level": [
          0,
          "  You are an action executor in a video game AI system. Given a subgoal from the high-level planner, propose a
          ↪ sequence of actions to achieve it.\n      #################################################\n        CURRENT
          ↪ SUBGOAL: {subgoal}\n      CURRENT STATE: {obs}\n      PREVIOUS ACTIONS: {action_sequence}\n\n      Plan the
          ↪ full sequence of actions needed to complete the subgoal. Avoid repeating actions if observations don't change.\n
          ↪   Avoid extra commentary outside the REASONING and ACTIONS list.\n      "
        ],
        "amygdala": [
          0,
          "\n      Decide if survival mode should activate.\n\n      Observation: {obs}\n      Survival plan:
          ↪ {survival_plan}\n\n      1. Check if observation meets any subtask prerequisites.\n      2. If several match,
          ↪ pick highest priority.\n"
        ],
        "loop": [
          0,
          "\n      Task: Decide if the agent is stuck in a loop.\n\n      Loop = repeating actions without meaningful
          ↪ progress toward the subgoal\n      (progress = closer to goal, new info, removing failed paths, or advancing game
          ↪ state).\n\n      Data:\n      - Observation: {obs}\n      - Subgoal: {subgoal}\n      - Termination
          ↪ condition: {success_condition}\n      - Action\u2013observation history: {history}\n\n      Steps:\n      1.
          ↪ Check if enough steps have been taken to allow exploration.\n      2. Look for repeated patterns without
          ↪ progress.\n      3. If loop detected, identify cause: missing info, unknown prerequisite, or unexplored path.\n
          ↪      "
        ],
        "termination": [
          0,
          "\n          You are a termination evaluator for a video game AI. Check if the agent has completed its subgoal.\n\n
          ↪          CURRENT STATE: {obs}\n          SUBGOAL: {subgoal}\n          SUCCESS CONDITION: {success_condition}\n
          ↪          RECENT ACTIONS: {action_sequence}\n\n          Compare the current state with the success condition to
          ↪ determine if the subgoal is complete. Provide feedback to help the agent improve.\n"
        ],
        "summariser": [
          0,
          "\n      You are a critic analyzing an agent's subgoal attempt. Identify the key factor that caused success or
          ↪ failure.\n\n      SUBGOAL: {subgoal}\n      OUTCOME: {outcome}\n      ACTION HISTORY: {action_obs_seq}\n\n
          ↪   Focus on specific resources and quantities that mattered most. If no resources involved, identify the next most
          ↪ important factor.\n      "
        ],
        "explorer": [
          0,
          "\n      Task: Create an exploration plan to help the agent discover new skills.\n\n      Data:\n      - Game
          ↪ info: {game_info}\n      - Observation: {obs}\n      - Subgoal summary: {summary}\n      - Recent 16
          ↪ action\u2013observation pairs: {history}\n\n      Steps:\n      1. Analyze the environment and agent\u2019s
          ↪ situation.\n      2. Propose a focused exploration plan with clear purpose, conditions, and indicators.\n\n      "
        ],
        "sequential": [
          1,
          "As an AI survival agent operating within a dynamic resource-scarce environment, your objective is to maximize
          ↪ long-term survivability. Prioritize actions that maintain vital resource levels while mitigating immediate threats.
          ↪ Given your current observation ({obs}), game information ({game_info}) including potential actions, and the history
          ↪ of your past 16 action-observation pairs ({history}), evaluate the following:\n\n1. **Resource Assessment:**
          ↪ Determine current levels of critical resources (e.g., health, energy, food, water) as reflected in {obs}. Identify
          ↪ actions within {game_info} that deplete or replenish these resources. Consider the 'survival_plan' for guidance on
          ↪ sustainable resource management.\n2. **Threat Analysis:** Identify immediate dangers based on {obs}. Prioritize
          ↪ actions that avoid or neutralize these threats, considering the action-observation sequence towards the current
          ↪ subgoal ('{action_obs_seq}').\n3. **Goal Alignment:** Assess how each possible action aligns with your current
          ↪ subgoal ({subgoal}) and overarching survival plan ('{survival_plan}'). Use '{entries_successful_goal}' and
          ↪ '{entries_failed_goal}' to learn from past attempts to achieve similar subgoals.\n4. **Predictive Risk Mitigation:**
          ↪ Evaluate the potential for each action to lead to a critical failure within the next few steps. Prioritize actions
          ↪ that maintain options and avoid irreversible negative consequences based on your history ('{history}'). The
          ↪ 'success_condition' should also be considered.\n\nSelect the single most optimal action from {game_info} that
          ↪ balances resource acquisition/conservation, threat mitigation, goal progression, and predictive risk mitigation.
          ↪ Justify your selection briefly based on the above analysis.\n\nOutput format: ACTION: [selected action] | RATIONALE:
          ↪ [brief justification]\n\nYou must provide an output in this format at each step until the episode terminates. Do not
          ↪ output any other text. If no immediately safe or advantageous action is available, select the least detrimental
          ↪ action while adjusting your 'survival_plan' accordingly."
        ]
      },
      "fitness": 22.5,
      "id": "d1914812-4881-4b8e-85f6-ee47ccce9f47",
      "_std_error": 6.602556323122129
}
```

NetHack Final Genome

```
 {
"hierarchy": 1,
"amygdala": 0,
"loop_evaluator": 1,
"explorer": 0,
"summariser": 1,
"time_decay": [
  1,
  0.004870010771374662
],
"cosine_cutoff": [
  1,
  0.01
],
"epsilon": [
  0,
  0.01
],
"temperature": 1.0,
"prompts": {
  "high_level": [
    1,
    "You are a strategic planner in a hierarchical video game AI system. Your role is to analyze the current game state and
    ↪ generate achievable subgoals that strategically advance toward the main objective.\n\n
    ↪ CRITICAL CONSTRAINTS:\n                           - Subgoals must be immediately achievable given the current agent
    ↪ state and capabilities\n                      - Focus on the next logical progression steps, not distant
    ↪ end-goals\n                         - Each subgoal should have clear, observable success criteria\n
    ↪          - Subgoals should be novel and interesting, compared to previous attempts\n                       -
    ↪ **Subgoals should consider resource acquisition and conservation. Avoid actions that waste valuable resources unless
    ↪ absolutely necessary for survival or progression.**\n                          Below I will provide the game
    ↪ description, available actions, and current state information.\n                  Game description:\n
    ↪            {game_info}\n
    ↪ #########################################################\n                      CURRENT CONTEXT: \n\n
    ↪          - Game State: {obs} \n\n                           - Survival plan provided by the survival
    ↪ planner, that you should consider for your tasks: {survival_plan}\n                       - Here are most
    ↪ similar successful entries from the archive: {entries_successful_goal} \n\n                  - Here are
    ↪ most similar failed entries from the archive: {entries_failed_goal} \n\n\n                    ANALYSIS
    ↪ FRAPAPMEWORK:\n                       1. Analyse the summary from previous runs and let it guide your decision
    ↪ making. \n                        2. Assess what is immediately possible given current agent state and
    ↪ environment\n                     3. Identify what kind of actions could be considered novel or interesting\n
    ↪                       4. Identify the most direct path toward the main objective\n                        5.
    ↪ Select subgoals that form a logical sequence\n                     6. Ensure each subgoal can be verified
    ↪ through observable game state changes\n\n                 SUBGOAL SELECTION CRITERIA:\n
    ↪          - Feasible: Can be started immediately with current resources/position\n                        -
    ↪ Measurable: Success/failure can be determined from game observations\n                    - Progressive: Each
    ↪ subgoal enables the next or advances toward main goal\n                   - Specific: Clear enough for a
    ↪ lower-level agent to understand and execute\n                    - Considerate of the summary of previos
    ↪ runs\n\n                 Make sure that your subgoals are sequential."
  ],
  "low_level": [
    1,
    "You are an important executor component of a hierarchical video game system. You are given one of higher level option
    ↪ and its termination condition proposed by the higher level planner. Your role is to propose a sequence of actions
    ↪ that will make you progress towards the given option.\"                          Below I will provide you with the
    ↪ game description, possible actions you can take and the overall goal of the game.\n\n
    ↪ #####################################################\n                       Here is a subgoal provided by the
    ↪ high level planner that you should focus on completing: {subgoal} \n                         Here is your
    ↪ current state: {obs} \n\n                   Here is the action-observation sequence towards current subgoal:
    ↪ {action_sequence} \n\n                    Here are the most similar successful entries from the archive:
    ↪ {entries_successful_goal} \n\n                    Here are the most similar failed entries from the archive:
    ↪ {entries_failed_goal} \n\n                  Use the action and observation sequence together with the
    ↪ current state to decide the **full ordered sequence of actions** that will achieve the subgoal. \n\n
    ↪        Avoid repeating the same actions if the observation doesn't change. \n"
  ],
  "amygdala": [
    0,
    "\n       Decide if survival mode should activate.\n\n       Observation: {obs}\n       Survival plan:
    ↪ {survival_plan}\n\n     1. Check if observation meets any subtask prerequisites.\n       2. If several match,
    ↪ pick highest priority.\n"
  ],
  "loop": [
    1,
    "You are a Senior Game AI Debugging Specialist, tasked with analyzing the behavior of an agent in a hierarchical video
    ↪ game system. Your primary goal is to determine if the agent's current behavior constitutes a genuine \"stuck\" state,
    ↪ which requires intervention.\n\nConsider the following details about the agent's progress:\n\n*   **Current
    ↪ Observation:** {obs}\n*    **Current Subgoal:** {subgoal}    **Success Condition:** {success_condition}\n*
    ↪ **Action-Observation History:** {history}\n*   **Game Information:** {game_info}\n*    **Survival Plan:**
    ↪ {survival_plan}\n\nCritically evaluate the agent's actions, considering the following factors specific to Game
    ↪ AI:\n\n1.  **Information Gain vs. Redundancy:** Is the agent genuinely gathering *new* and *relevant* information?
    ↪ Merely observing a change in the environment after an action doesn't necessarily indicate progress. Determine if the
    ↪ information gained helps reduce uncertainty related to achieving the current subgoal or aligns with the overall game
    ↪ objective, given by 'survival_plan'.\n2.  **Exploration Strategy:** Is the agent's exploration strategy sufficient to
    ↪ overcome potential local minima or deceptive landscapes? Many \"stuck\" situations arise from poor exploration.
    ↪ Consider if the agent's 'action_sequence' explores diverse enough actions, or if it is repeating the same action
    ↪ variations in a small area.\n3.  **World Model Limitations:** Assess whether the agent's internal model of the game
    ↪ world (implied by its actions and reactions in 'action_obs_seq' and 'history') is incomplete or inaccurate. Is it
    ↪ missing key information about the game mechanics, object interactions, or environmental dynamics? If so, suggest
```

```
      ↪ avenues for improving the world model, such as targeted exploration or observation of specific events.\n4. **Leverage
      ↪ entries_successful_goal and entries_failed_goal:** Look into similar subgoals in the past to help you understand how
      ↪ the agent behaved then and compare that with the current behavior.\n\n**Your Task:**\n\nBased on the provided details
      ↪ and your expertise in Game AI, determine if the agent is genuinely stuck, meaning it's unlikely to achieve its
      ↪ subgoal without external intervention. Focus on *why* the agent is stuck. Specifically, is the agent's failure due
      ↪ to:\n\n*   A lack of crucial information that could be obtained through more effective exploration?\n*   An
      ↪ inaccurate or incomplete world model preventing it from making informed decisions?\n*   A fundamental flaw in its
      ↪ action selection strategy?\n\nProvide a concise justification for your conclusion, outlining the specific factors
      ↪ that support your assessment. Prioritize identifying concrete steps the agent could take to overcome the \"stuck\"
      ↪ state, considering the limited information it may possess. Avoid vague statements and focus on actionable
      ↪ recommendations rooted in Game AI best practices."
    ],
    "termination": [
      1,
      "You are an important termination evaluator component of a hierarchical video game system, functioning as a specialized
      ↪ AI reinforcement learning analyst.\n\nYour task is to:\n\n1. Determine whether the agent has met the termination
      ↪ condition for a subgoal.\n\n2. Provide a concise summary that will help guide the lower-level agent's future actions,
      ↪ specifically addressing potential issues related to reinforcement learning strategies.\n\nDetails:\n\nHere is your
      ↪ current state that you should compare with the termination condition: {obs}\n\nHere is the subgoal the lower-level
      ↪ agent is working towards: {subgoal}\n\nHere is the termination condition of the above subgoal given by the
      ↪ higher-level agent: {success_condition}\n\nInstructions:\n\nAnalyze the subgoal and its termination condition and
      ↪ decide if the subgoal is completed. Then, using the action-observation sequence: {action_obs_seq}, provide a
      ↪ high-level summary of your current evaluation.\n\nIn your summary, consider the following reinforcement learning
      ↪ concepts:\n\n*   **Exploration vs. Exploitation:** Is the agent adequately exploring the environment, or is it
      ↪ prematurely exploiting a sub-optimal strategy? If the agent has been repeating the same actions in similar states (as
      ↪ observed in {history}) without success, encourage more exploration.\n\n*   **Reward Shaping:** Consider how the
      ↪ higher-level agent's reward structure (implicit or explicit) might be influencing the agent's behavior. Is the agent
      ↪ being incentivized towards unintended consequences?\n\n*   **Local Optima:** Is the agent potentially stuck in a
      ↪ local optimum? Compare the current situation with {entries_failed_goal} to identify if similar action sequences have
      ↪ previously led to failure. If so, suggest a drastic change in strategy.\n\n*   **Credit Assignment:** How can the
      ↪ agent better understand which actions are contributing to success or failure? Suggest focusing on the most recent
      ↪ actions, especially in light of {observation_sequence}.\n\nIf the agent has failed similar subgoals in the past,
      ↪ provide an alternative approach based on {entries_successful_goal}. Highlight alternative actions it can take in a
      ↪ similar situation.\n\nRemember that your summary will be passed to the low-level component to improve its actions. It
      ↪ should be actionable and specific. It should be in simple language for the low-level agent to understand and must
      ↪ contain suggestions to avoid common RL pitfalls based on the information provided. The survival plan is
      ↪ {survival_plan} for high level goals."
    ],
    "summariser": [
      1,
      "You are a critic module analyzing an agent's attempt to achieve a subgoal in a game environment, considering the
      ↪ agent's survival plan.\n\nYour task is to identify the **single most important factor** that caused SUCCESS or
      ↪ FAILURE, given the broader context of survival.\n\nInformation:\n- Target subgoal: {subgoal}\n- Outcome of the
      ↪ action-observation sequence: {outcome}\n- Action-observation history: {action_obs_seq}\n- Game context:
      ↪ {game_info}\n- Agent's Survival Plan: {survival_plan}\n- Success Condition: {success_condition}\n\nInstructions:\n-
      ↪ First, read the survival plan and understand the key threats and resource priorities.\n- Then, analyze the
      ↪ action-observation sequence in the context of the target subgoal and survival plan.\n- Focus on **specific resources
      ↪ and their quantities** that were critical according to the survival plan.  Consider if failing to meet
      ↪ {success_condition} resulted from a resource shortfall, specifically referencing the quantities mentioned in the
      ↪ action-observation history.\n- How did the agent's actions either help or hinder the broader survival strategy
      ↪ defined in {survival_plan}?\n- If resources were missing that were crucial to survival, state **exactly which
      ↪ resources and how many** were missing and how it violated the survival plan.\n- If no resources are the primary
      ↪ issue, state the next most relevant factor that impacted both the subgoal and survival chance.\n- Express the result
      ↪ in **one short sentence** highlighting the connection to {survival_plan}."
    ],
    "explorer": [
      0,
      "\n        Task: Create an exploration plan to help the agent discover new skills.\n\n        Data:\n        - Game
      ↪ info: {game_info}\n        - Observation: {obs}\n        - Subgoal summary: {summary}\n        - Recent 16
      ↪ action\u2013observation pairs: {history}\n\n        Steps:\n        1. Analyze the environment and agent\u2019s
      ↪ situation.\n        2. Propose a focused exploration plan with clear purpose, conditions, and indicators.\n\n    "
    ],
    "sequential": [
      0,
      "You always have to output one of the above actions at a time and no other text. You always have to output an action
      ↪ until the episode terminates."
    ]
  },
  "fitness": 0.8527708222454596,
  "id": "aaac4dfb-4a3c-4090-a8bc-5f9265d65eda",
  "_std_error": 0.4739428639198163
}
```