Explicable Policy Search

Abstract

Human teammates often form conscious and subconscious expectations of each
other to better interact. Teaming success is contingent on whether such expectations
can be met. For an intelligent agent to operate with humans beside them, similarly,
it must consider the human's expectation of its behavior. Otherwise, it may result
in loss of trust and degraded team performance. A key challenge here is that
the human's expectation may not align with the agent's optimal behavior, due to,
for example, the human's partial or inaccurate understanding of the task domain.
Prior work on *explicable planning* describes the ability of agents to respect their
human teammate's expectations by trading off task performance for more expected
or "*explicable*" behaviors. In this paper, we introduce *Explicable Policy Search*
(EPS) to significantly extend such an ability to a reinforcement learning (RL)
setting and to handle stochastic domains with continuous state and action spaces.
However, in contrast to the traditional RL method, EPS must at the same time infer
the human's hidden expectations. Such inferences require information about the
human's belief about domain dynamics and her reward model but directly querying
them is impractical. We demonstrate that they can be sufficiently encoded by a
surrogate reward function, which can be learned based on the human's feedback
on the agent's behavior. The surrogate reward function is then used to reshape
the agent's reward function, which is shown to be equivalent to searching for an
explicable policy. We evaluate our method for EPS in a set of continuous navigation
domains with synthetic human models and in an autonomous driving domain with
a user study. The results suggest that our method can generate explicable behaviors
that reconcile task performance with human expectation intelligently and has
real-world relevance in human-agent teaming domains.

1 Introduction

Intelligent agents are quickly becoming a part of our daily lives in a variety of domains, including
smart home, autonomous driving, education, and so on. In such domains, the agents are expected
to perform in human inhabited environments and even collaborate closely with them. Members in
such a collaborative setting often form conscious and subconscious expectations of each other and
the success of collaboration depends on whether such expectations can be met. A key challenge
here is that the human's expectation may not align with the agent's optimal behavior. Hence, agents
choosing their optimal behaviors without considering the human observers or collaborators could be
seen as unexpected, leading to degraded team performance and loss of trust [19, 6].

Consider a drone navigation scenario in Fig. 1a where a drone is tasked to navigate from the starting
position (as shown) to a destination. On a good day, the drone would be expected to mostly navigate
straight to the goal with some air perturbation (thus possibly introducing a slightly curved trajectory
as shown in red in Fig. 1a). However, there is a heavy wind today that changes the domain dynamics
(which a human observer is unaware of) and it becomes impossible for the drone to navigate as usual.

(a) Motivating scenario. (b) Problem setting of EPS.

Figure 1: The learning agent learns its behavior with a given engineered reward model, r_A, in the task environment under the true domain dynamics $\mathcal{T}_A$. The human generates her expectation of the agent's behavior π_A^H based on $\mathcal{T}_A^H$ that captures her belief or understanding of the true domain dynamics, and her reward model r_H, which may be different from $\mathcal{T}_A$ and r_A, respectively. The differences may be due to personal preferences in the reward model, biases and misunderstandings about the domain dynamics, etc. In the traditional learning setting, the agent computes the optimal policy π under its models for behavior generation, which could be different from its expectation formed by the human based on her models. Shaded nodes are known to the agent and unshaded nodes are unknown.

Two alternatives are illustrated where the drone navigates in a zigzag and a curved pathway. The curved pathway is more optimal since it makes fewer sharp turns (due to the windy condition) but the former is likely to be perceived as more expected to the human observer, given its *closeness* to the expected behavior. We note here that the explicable behavior goes beyond simply choosing from or combining the agent's optimal behavior with the human's expected behavior. Hence, achieving such a capability requires a more fundamental treatment. In the experiments, we will show that our learning agent can generate novel behaviors that are rarely seen in training scenarios.

The problem setting of *explicable policy search (EPS)* is illustrated in Fig. 1b, which is fundamentally a model reconciliation business [7]. In such a setting, considering the learning problem only from the perspective of the agent would sabotage the teaming when the agent's behavior differs from human's expectation. Our method considers any feedback the human may provide to the agent based on her expectation of its behavior (generated under her models) to help the agent improve. Hence, our method has a variety of applications where machines must be tuned to individual users, such as an autonomous vehicle that learns to improve its driving behavior based on its owner's feedback but at the same time must abide by standardized operating requirements to ensure safety, comfort, etc. In our problem, we assume that the human is nosily rational at generating her expectation of the agent to accommodate her computational limitations. In general, noisy rationality is one type of bounded rationality [45] due to a limited computational capability, resulting in sub-optimal behaviors. While noisy rationality may not perfectly describe our computational model [43] due to various cognitive biases, modeling humans as such has been a common practice and demonstrated as a reasonable assumption in prior methods [34, 2]. Furthermore, similar to prior work on explicable planning [48, 25], we assume that the human is a sole observer of the agent. Extending it to an collaborative setting requires additional machinery and will be discussed in future work, with steps already taken in a classical planning setting [47].

In this paper, we formulate *explicable policy search (EPS)* in Markov Decision Processes (MDPs). The goal is to learn a policy that reconciles between maximizing the long-term return (based on the engineered reward model r_A) and minimizing the deviation of the agent's behavior from the human's expectation of it, which is quantified by an *explicability* score. We formulate the problem as a linear combination of two objectives and show that such a simple treatment already yields substantial benefits in our evaluation. The challenge in this problem formulation mainly lies in the fact that the human's expectation is hidden (but partially observable via human feedback) and must be learned. A straightforward solution involves learning both the human's belief about the domain dynamics ($\mathcal{T}_A^H$) and her reward model (r_H) from human feedback, which is possible but impractical. Instead, we show that the information needed from them for EPS can be sufficiently encoded by a surrogate reward function, which is much easier to learn. Such a reward function can then be incorporated into a policy search process to recover an explicable policy. The final modified reward function for EPS bears some similarity to maximum entropy reinforcement learning [20, 21] but is derived under a completely different motivation.

For evaluation, we design a set of navigation domains where the human's feedback on her expectation of the agent's behavior is synthetically generated based on the true domain dynamics modified with various "misunderstandings". We compare our method with three baselines that are selected to represent the traditional RL methods to demonstrate the key advantages of EPS under model differences. Furthermore, to show its real-world relevance, we conduct a human study in an autonomous driving domain [29] where we design driving scenarios to elicit existing human biases about the vehicle's domain dynamics that could be dangerous to ignore during learning. The results show that our method can intelligently generate explicable behaviors that are safe and preferred over those of the baselines.

The contribution of this paper is three-fold. First, we introduce and formulate explicable policy search, which extends explicable planning to a reinforcement learning setting and to stochastic domains with continuous state and action spaces. Second, we propose a practical solution for this challenging problem by introducing a surrogate reward function learned from human feedback data, which sufficiently encodes the necessary information for explicable policy search. Third, we evaluate our learning method extensively with simulations and human subjects.

2 Related Work

The problem of generating communicative actions or behaviors (a.k.a. explainable planning) has been well studied as a subarea in explainable AI. Various terms have been introduced for explainable planning that are different but share similarities, such as legibility, explicability, transparency, etc. For a review of their differences, refer to here [7]. For example, legible motion planning [12] is about generating motion trajectories to better reveal the underlying goal of the agent. Explicable planning that we study in this work [48, 25, 16, 47] differs from legible planning in that it focuses on plans that better align with the human's expectation *given the goal*. The key characterization of explicable planning methods revolves around the idea of model reconciliation where an agent makes decisions based on two different models instead of one (with a focus on domain dynamics) [8, 6, 7]. While there exists prior work [33, 5] on training value-aligned learning agents that must learn to respect two different reward models, they do not consider the differences in the domain dynamics. Prior methods on explicable planning addressed the problem in a classical planning setting (e.g., PDDL [15]) under deterministic domains. We argue that explicable planning should also be considered in a learning setting where human users can provide feedback on the agent's behavior for the agent to improve over time (i.e., for personalization). Furthermore, extending explicable planning to a learning setting makes the approach applicable in stochastic environments with continuous state and action spaces. Differing from the prior work, we consider that the user's reward model may also differ from the agent's, but assume the differences do not introduce a discrepancy in the perception of the agent's "goal". Considering multiple candidate goals is the setting of legible planning [12]. Note that generating explainable behavior has a subtle but important difference from generating interpretable behavior [44, 35, 38, 39], where the focus is to make the human understand the agent's behavior, not necessarily to "expect" its behavior. In particular, an interpretable behavior may not be an expected behavior. However, an expected behavior must be interpretable. In high-stake domains where "surprises" should be minimized if at all possible, explicable behaviors would be more desirable.

As seen from Fig. 1b, estimating the human's expectation requires learning both the human's belief about domain dynamics and her reward model based on human feedback. Existing work on inverse reinforcement learning (IRL) [1, 36, 49] and reward learning [11, 41, 13] learns the reward model from human data with the assumption that the human has access to an accurate model of domain dynamics. It was shown that the human's inaccurate belief of domain dynamics may skew the human feedback and lead to learning the opposite preferences with respect to the human's true reward model [17]. A similar situation exists in policy learning for which various methods have been devised that use human feedback, which include reward shaping, policy shaping [18], and interactive RL [24, 32, 10, 27]. When the human has an inaccurate belief of domain dynamics, as we will show, it can lead to non-convergence during learning or high variances in the learned behaviors for these methods. While it may be possible to learn the human's belief of the domain dynamics separately [37], the belief and human's reward model are generally tightly coupled in the human feedback and should be jointly learned. Joint learning is possible [23, 17] but very challenging due to its high dimensionality, which makes it impractical for real-world domains. Another possible approach [30] (InfoGAIL) that may be leveraged uses latent code to discover salient semantic features

132 to accommodate demonstrations from different experts. Even though the aim is quite different from
133 ours, one may consider the biases in the domain dynamics as captured by the latent code. However,
134 their work is focused on "discovering" the differences while we focus on "reconciling" the differences
135 (without explicit modeling of the differences). For example, it likely would fail in situations where
136 all experts are biased. When considering only differences in domain dynamics, our problem may be
137 viewed as a form of off-dynamics learning [14] that addresses transfer learning from a source to a
138 target domain. However, we do not have direct access to the target domain in EPS, which is hidden in
139 the human's mind.

3 Problem Formulation

141 In this paper, we formulate any task domain as a Markov Decision Process (MDP). An MDP is
142 represented by a tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{T}, r, \rho, \gamma)$, where $\mathcal{S}$ is the set of states, $\mathcal{A}$ the set of actions,
143 $\mathcal{T}(s|s, a)$ the transition function, r the reward function, $\rho(\cdot)$ the initial state distribution, and γ
144 the discount factor. For the problem setting as shown in Fig. 1b, we need to consider two MDPs.
145 Assuming the two MDPs share the same $\mathcal{S}$, $\mathcal{A}$, ρ, and γ, one is the agent's model $\mathcal{M}_A$ with the true
146 domain dynamics $\mathcal{T}_A$ and the engineered reward function r_A, and the other is the human's model of
147 expectation $\mathcal{M}_A^H$ with her belief about the domain dynamics $\mathcal{T}_A^H$ and the human's reward function
148 r_H. For explicable policy search, $\mathcal{T}_A$, $\mathcal{T}_A^H$, and r_H are *unknown*. Note that our approach can also be
149 easily applied to situations where $\mathcal{T}_A$ is known in model-based learning methods.

150 **Definition 1. Explicable Policy Search (EPS)**   *is the problem of searching for a policy via learning*
151 *to maximize two objectives: the expected cumulative reward, and a **policy explicability score** between*
152 *the agent's policy under $\mathcal{M}_A$ and the expected policy under the human's model $\mathcal{M}_A^H$.*

153 In this paper, we consider a linearly weighted sum of the two objectives:

$$\pi^* = \arg\max_{\pi} \mathbb{E}_{\pi, \mathcal{T}_A} \Big[\underbrace{\sum_t \gamma^t r_A(s_t, a_t)}_{cumulative\ reward} \Big] + \lambda \underbrace{\mathcal{E}(\pi, \mathcal{M}_A, \pi^H, \mathcal{M}_A^H)}_{policy\ explicability\ score}, \tag{1}$$

154 where π and π^H denote the agent's policy and human's expected policy, respectively. We combine
155 the two objectives linearly via a *reconciliation factor* λ to be consistent with the literature [48, 25]
156 and simplify the technical development.

157 Next, we motivate the design of our explicability metric. Intuitively, a model can better explain the
158 data when it assigns the data a high probability. Similarly, under the assumption that the human
159 generates her expectations based on $\mathcal{T}_A^H$, and r_H, a behavior (i.e., trajectory) τ would be more likely
160 to be generated by the human's model (i.e., expected by the human) when it is associated with a high
161 probability in the model. In contrast, when the trajectory has a low probability, we would say that it is
162 "inexplicable" with respect to the model. As a result, the probability of the trajectory in the human's
163 model ($\mathcal{T}_A^H$ and r_H), denoted by $p_A^H(\tau)$, may be considered as an explicability metric as the first
164 thought. However, using $p_A^H(\tau)$ only ignores an important aspect of explicability under stochastic
165 setting since it is *relative* at the same time: a trajectory that is more expected should also appear more
166 frequently in the real-world. Likewise, a trajectory that is less expected should appear less. This
167 means that the explicability metric should be specified with respect to the relative frequency of the
168 trajectory in the human's model and the agent's model, e.g., $\frac{p_A(\tau)}{p_A^H(\tau)}$! Hence, evaluating the explicability
169 metric under stochastic domains becomes computing the expectation of such an explicability metric
170 under a distribution of the trajectories. This essential equates the choice for our explicability score
171 to the negative KL-divergence of the two distributions of trajectories under the agent and human's
172 models, respectively.

173 Hence, we introduce the *policy explicability score* for stochastic environments, which differs funda-
174 mentally from the explicability scores defined in the prior work.[1] In [48, 25], explicability scores have
175 been considered as a similarity metric between the agent's plan and the expected plan in the human's
176 mind. Policy explicability extends such a metric to consider distributions of plans. With the newly

---

[1] The policy explicability score does not consider the similarity between any two trajectories as considered in
the explicability scores in the prior work: they are *orthogonal* aspects of explicability that are equally important.

established policy explicability metric, the second objective in Eq. (1) becomes a measurement of consistency between the generated agent's trajectories and the human's expectation. Intuitively, this means that an agent that only learns to maximize it would learn to *replicate* (as closely as possible) what the human expects the agent to behave–exactly what we set out to pursue! Also note that when the two distributions match exactly, the policy explicability score would be 0, exerting no influence on the final policy as desired! In such a case, Eq. (1) can be rewritten as:

$$\pi^* = \arg\max_{\pi} \mathbb{E}_{\pi,\mathcal{T}_A}\left[\sum_t \gamma^t r_A(s_t, a_t)\right] + \lambda \cdot -\mathcal{D}_{\mathrm{KL}}(p_A(\tau)\|p_A^H(\tau)), \tag{2}$$

where $p_A(\tau)$ and $p_A^H(\tau)$ denote the distributions of trajectories for the agent and human, respectively.

Remark: Depending on whether the agent's state and action are observable, the distribution of trajectories must be computed differently. When both the state and action are observable, the human would be able to contrast both the agent's action and resulting state with her expectation; otherwise, only the observable part needs to be considered. In the following discussion, we assume that both the state and action are observable. For explicable policy search, the implication here is that the agent optimizing Eq. (2) would actively avoid parts of the state space where either its policy differs from the human's expectation or the dynamics differs, which is reflected in the final solution derived.

4 Explicable Policy Search (EPS)

To present our learning method, we start by expressing the probability distribution of the agent's trajectories and human's expectation. We parameterize the agent's policy using θ. The probability of realizing the agent's trajectory τ with π_θ (and similarly for the human's expectation) is:

$$p_A(\tau) = \rho(s_0)\prod_t \mathcal{T}_A(s_{t+1}|s_t, a_t)\pi_\theta(a_t|s_t), \quad p_A^H(\tau) = \rho(s_0)\prod_t \mathcal{T}_A^H(s_{t+1}|s_t, a_t)\pi_A^H(a_t|s_t). \tag{3}$$

Given these two distributions, we can now derive our solution for EPS. Since both objectives in Eq. (2) are expressed as expectations over the same distribution of trajectories (i.e., $p_A(\tau)$), we can combine them after rewriting the policy explicability score in Eq. (2) as follows:

$$\begin{aligned} &-\mathcal{D}_{\mathrm{KL}}(p_A(\tau)\|p_A^H(\tau)) \\ &= -\mathbb{E}_{p_A}\left[\sum_t \log \mathcal{T}_A(s_{t+1}|s_t, a_t) + \log \pi_\theta(a_t|s_t) - \log \mathcal{T}_A^H(s_{t+1}|s_t, a_t) - \log \pi_A^H(a_t|s_t)\right] + C, \end{aligned} \tag{4}$$

where C is a constant. The main challenge in solving the optimization problem in Eq. (2) now lies in the fact that neither the human's policy π_H nor her belief of the domain dynamics $\mathcal{T}_A^H$ are known.

4.1 Surrogate Reward Function

Eq. (4) can be merged into Eq. (2) such that the log terms essentially reshape the engineered reward function. In such a case, a straightforward approach is to learn the human's belief about the domain dynamics and her expected policy separately based on human feedback, while maintaining estimates of the true domain dynamics and current agent's policy. While possible, it is inefficient and unnecessary. Instead, we propose to use a surrogate reward function. The goal is to learn such a function u_H that retains the sufficient and necessary information about the human's belief of domain dynamics and expected policy for policy search, i.e., $u_H \doteq \log \mathcal{T}_A^H(s_{t+1}|s_t, a_t) + \log \pi_A^H(a_t|s_t)$. Next, we reveal how such a goal can be achieved by manipulating a preference-based formulation.

Intuitively, we learn a reward function that alone can explain the human's expectation of the trajectories–a reward function that introduces the same distribution of the expected trajectories. At the same time, we must take care to minimize the human feedback to make it practical. A popular approach that imposes feasible input requirement on human is preference-based RL [46, 10]. For EPS, instead of soliciting human preferred trajectories, we can present pairs of trajectories and ask humans to comment on which one is *more expected*. Then, we can fit a reward function that would "prefer" more expected trajectories. More specifically, we can try to correlate the distribution of expected trajectories with the surrogate reward function to be learned as follows:

$$p_A^H(\tau) \propto \exp\left(\sum_t u_H(s_t, a_t)\right). \tag{5}$$

Proposition 1. *There exists a **unique** reward function u_H such that trajectory distribution under the softmax human preference model with u_H described above matches with the human's expected trajectory distribution given in Eq. (3).*

When we compare mathematically the two equations of $p_A^H(\tau)$ (i.e., Eqs. (3) and (5)), we see that the only way to match the distributions is by satisfying:

$$\sum_t u_H(s_t, a_t) = \sum_t \log \mathcal{T}_A^H(s_{t+1}|s_t, a_t) + \sum_t \log \pi_A^H(a_t|s_t) + C_1.$$

One straightforward way for this is to set $u_H(s_t, a_t) = \log \mathcal{T}_A^H(s_{t+1}|s_t, a_t) + \log \pi_A^H(a_t|s_t)$. In the other direction, since the trajectories may be of various lengths in general (including the length of 1 as special cases), we can conclude further that:

$$u_H(s_t, a_t) = \log \mathcal{T}_A^H(s_{t+1}|s_t, a_t) + \log \pi_A^H(a_t|s_t) + C_1.$$

Plugging this result into any trajectory of length greater than 1, we can conclude that $C_1 = 0$. This result is similar to that in MaxEnt IRL [49]. Hence, our learning approach based on such a model is also one that does not exhibit any additional preferences beyond matching the human feedback.

This means that u_H in such a case becomes equivalent to $\log \mathcal{T}_A^H$ and $\log \pi_H$ for representing the distribution of expected trajectories, which implies that the information needed from $\mathcal{T}_A^H$ and π_H for optimizing Eq. (2) can be substituted with u_H. u_H can be learned by applying preference-based learning with a softmax preference model based on human feedback as described earlier (more details to follow). To learn the unique surrogate reward function and avoid the non-identifiabillity issue [40], however, requires the learning to be globally optimized. In our implementation, we simply normalize the learned rewards. Now, we rewrite Eq. (2) based on the above result:

$$\theta^* \doteq \arg\max_{\pi_\theta} \mathbb{E}_{p_A}\left[\sum_t \gamma^t \Big(r_A(s_t, a_t) + \lambda\big(u_H(s_t, a_t) + \mathcal{H}_{\mathcal{T}_A}[s_{t+1}|s_t, a_t] + \mathcal{H}_{\pi_\theta}[a_t|s_t]\big)\Big)\right]. \quad (6)$$

Note that Eq. (6) is an approximation of the original objective in Eq. (2) by applying discounting to the surrogate reward function and entropy terms. This allows us to use them to reshape the reward function. We can view this objective function as two parts. The first two terms, $r_A(s_t, a_t) + \lambda u_H(s_t, a_t)$, requires the agent to maximize rewards from two sources: the engineered reward and the surrogate reward learned from human feedback. These two reward functions are weighted according to the reconciliation parameter as expected. The second part of this objective function is $\mathcal{H}_{\mathcal{T}_A}[s_{t+1}|s_t, a_t] + \mathcal{H}_{\pi_\theta}[a_t|s_t]$, which are two entropy terms. The first term is for the agent's domain dynamics while the second term is for the target policy.

The second entropy term for the target policy (referred to as "*policy entropy*") is well studied in the maximum entropy (MaxEnt) RL framework. [20, 21], However, we note that this term in our work is derived for a completely different reason. In MaxEnt RL, maximizing $\mathcal{H}_{\pi_\theta}$ encourages the agent to explore during learning and increase robustness. Given a fixed surrogate reward function, this term in EPS likewise encourages stochasticity in the agent's policy to increase robustness. A more distinguishing feature of explicable policy search lies in the first term. Maximizing $\mathcal{H}_{\mathcal{T}_A}$ encourages the agent to prefer parts of the environment where there is more stochasticity, which we refer to as "*environment entropy*". The incentive here is to reduce the influence to the policy explicability score due to differences in the agent's policy and expected policy. Intuitively, at more stochastic parts of the environment where action choices for the agent matter less, the agent's trajectory is more likely to match with the human's expectation even when the agent's policy and the expected policy differ.

Expectation-based Preferences: For learning u_H, we apply a preference-based learning framework. We request humans to provide their feedback on which segment in a pair of segments $\{(\sigma^1, \sigma^2)\}$ extracted from the agent's trajectories *is more expected*. To consider noise in human feedback, the human's expectation preference is formulated as follows, similar to that in [10, 31, 3, 4]:

$$\hat{P}[\sigma^1 \succ \sigma^2] = \frac{\exp \sum u_H(s_t^1, a_t^1)}{\exp \sum u_H(s_t^1, a_t^1) + \exp \sum u_H(s_t^2, a_t^2)}$$

We learn u_H to minimize the cross entropy between our prediction of the expectation preferences and feedback data. In order to efficiently solicit the human's expectation preference for the agent's behavior, we leverage uncertainty-based sampling [10, 28] to select traces for the human in an active

learning fashion. To estimate $\mathcal{T}_A$, we assume it follows a Gaussian distributions and model it using a two-headed neural network that outputs its mean and logarithm of standard deviation given the state and action. The agent interacts with the environment and collects transition data for learning. $\mathcal{T}_A$ is estimated using a data-driven method by minimizing the L_2 one-step prediction loss [26]. We use Soft Actor Critic (SAC) [21] for policy learning but other policy search methods are also applicable. To alleviate the issue of non-stationary prediction of expectation preferences during learning, we relabel the data samples every time u_H is updated [27]. The algorithm for EPS is in the appendix.

5 Evaluation

We evaluate our method on a set of continuous navigation domains with synthetic human models and a simulated autonomous driving domain with a human subject study. The study is IRB approved and all protocols have been followed. The synthetic experiments are used to validate the effectiveness of our method for searching for explicable policies. The user study is to 1) confirm that our beliefs about domain dynamics can be inaccurate or biased, which can affect our judgements and lead to severe consequences if ignored, and 2) show that our method can effectively address such hidden issues by achieving an intelligent reconciliation between the task performance and human's expectation.

5.1 Synthetic Navigation Domains

We conduct experiments on four navigation domains with continuous state and action spaces, as illustrated in Fig. 2. More detailed descriptions of our domains are in the appendix. For all the domains, the agent starts from the upper left corner and aims to navigate to the goal area (depicted in green). We introduce various human inaccurate beliefs about domain dynamics for these four domains[2]. For Domain 1 (D1) and Domain 2 (D2) (i.e., the first two rows in Fig. 2), the human believes that the agent is more likely to fall into the pit when it is close by; the truth is everywhere is the same. For Domain 3 (D3) and Domain 4 (D4) (i.e., the third and fourth row in Fig. 2), the human's belief is that the agent could easily slip on ice. Moreover, the human believes that the agent can readily handle sandy roads. The truth is that the agent is proficient on ice but can easily get stuck on sand in D3. For D4, the agent is in addition capable of handling sand albeit being more costly. The human's expectation preferences for the agent's behaviors is generated synthetically with respect to ground truth human model.

5.1.1 Baselines

We compared our method to three baselines to illustrate its advantages compared to the traditional RL methods that do not consider model differences: Soft Actor Critic (SAC) [21], Deep RL from Human Preferences (DRLHP) [10], and Policy Shaping (PS) [18]. SAC optimizes policy with respect to the engineered reward function and true domain dynamics without considering the human's expectation. DRLHP uses human expectation-based preferences for the agent's behavior to estimate a reward function and applies it to guide policy search. It ignores the engineered reward function. For SAC and DRLHP, we could not use reward signals from both sources due to their different formats. The closest competitor to EPS is policy shaping. Policy shaping learns two policies using reward signals from the environment and human expectation preferences, respectively. A combination policy is then obtained by multiplying them together. It also seeks to combine different information sources that are however assumed to be consistent. That is why it has difficulty handling situations where the human's expectation and agent's optimal behavior conflict (see D3 in Fig. 2).

5.1.2 Results and Discussion

Table 1 shows the average return and policy explicability score of EPS compared to the baselines over 100 rollouts, with the sample standard deviations. The policy explicability score is computed using Eq. (4) based on the synthetic human models. For EPS, the reconciliation parameter λ is tuned manually to show the different behaviors compared to the baselines in Fig. 2, with $\lambda \in$

---

[2]For simplicity, we modified the human's belief about the domain dynamics only while keeping the reward functions the same for the two models. This should not impact the evaluation since the surrogate reward function can encode information for both for policy search.

D1:

D2:

D3:

D4:

(a) Human   (b) EPS   (c) SAC   (d) DRLHP   (e) PS

Figure 2: Comparison of different learning methods with human's expectation (left). The dark grey area represents the walls. The brown area is the pit (with -100 penalty) and the green area is the goal (with +100 reward). The blue area represents icy roads and the yellow area represents sandy roads.

Domain	Avg. Return (Std)				Avg. Explicability (Std)			
	EPS	SAC	DRLHP	PS	EPS	SAC	DRLHP	PS
D1	95.53 (1.88)	**97.46 (1.53)**	74.51 (29.92)	93.91 (3.55)	**94.87 (1.95)**	92.57 (1.48)	73.01 (28.75)	89.17 (4.82)
D2	94.07 (2.43)	**95.65 (1.98)**	23.28 (43.71)	95.55 (3.17)	**92.10 (2.44)**	91.00 (3.15)	20.94 (43.97)	90.66 (3.94)
D3	**96.80 (1.16)**	94.47 (2.77)	-50.76 (56.49)	-178.76 (63.88)	**94.72 (1.43)**	91.88 (3.32)	-50.79 (56.44)	-181.46 (63.87)
D4	92.37 (1.80)	**93.27 (2.03)**	26.52 (49.02)	90.11 (14.79)	**92.17 (1.86)**	90.77 (2.44)	26.49 (49.03)	90.11 (16.63)

Table 1: Comparison of EPS to baselines using averaged return and explicability score.

$[2.0, 2.8]^3$. For all domains, EPS achieved the highest policy explicability score and followed the best performer for average return. Note that SAC also achieved good explicability scores in the domains since the synthetic human models did not penalize the optimal behavior as much as they could (i.e., the human beliefs were not modeled to be much more stochastic than the ground truth). PS performed well on most tasks while being considerably worse than others in D3. Due to the conflict between the human's expectation and task priorities in D3, the method failed to achieve a meaningful combination. DRLHP performed poorly on all the domains because preference-based learning methods have difficulty dealing with domains with sparse or delayed rewards, which makes credit assignment challenging and results in large variations. Since EPS also applies a preference-based learning method to learn the surrogate reward function, we demonstrate this using the learned function. As shown in Fig. 3, this function has a significant amount of uncertainty so is not ideal for guiding policy search. Although it adds variability into policy learning, it serves very well as an *auxiliary* objective by informing the agent where the human expects it to perform.

We show sampled trajectories for EPS, the baselines, and the human's expectation computed using the synthetic human models in Fig. 2. In D1 and D2, SAC agent always chooses the shortest path while EPS agent takes a detour that bypasses the pit and hence is more explicable. In D3 and D4, SAC agent chooses the path passing through the top since the agent can get stuck on sandy roads in D3 and the top path is more

(a) D1   (b) D2   (c) D3 & D4

Figure 3: Visualization of the learned surrogate reward functions for D1-D4. The darker the lower reward value and the brighter the higher.

---

[3]The spectrum of policies generated by difference values of λ is included in the appendix.

efficient in D4. It is worth noting that EPS agent
makes different decisions on these two domains.
It selects the top path in D3 when the sandy road is difficult to navigate even though it is against the
human's expectation. This is because if the agent conforms to the human's expectation, it would
result in a huge loss to the engineered reward. However, when it can better navigate on sand in D4,
it chooses to respect the human's expectation to be more explicable, at the cost of lowering task
performance. Policy shaping agent is also successful in D4, but gets stuck in D3, because simply
multiplying two different policies could result in a new policy that is uninformative, irrespective of
the λ used (e.g., when we have $p_1 = (0.1, 0.9), p_2 = (0.9, 0.1)$, the resulting policy from multiplying
them would always be $p = (0.5, 0.5)$), which can lead to poor behaviors. In summary, we show that
EPS can successfully generate effective behaviors that achieve an *intelligent* reconciliation between
the human's expectation and task priorities. It can generate novel reconciled behaviors (D1 and D2),
stick to the task priorities (D3), or follow the human's expectation (D4), as appropriately.

5.2   Autonomous Driving Domain

We used a simulated autonomous driving domain [29] to evaluate our method with human subjects
and demonstrate its real-world relevance, as illustrated in Fig. 4. The state space is featured by the
position and velocity of the ego-vehicle and nearby vehicles. The action space consists of five discrete
actions. Initially, the autonomous driving vehicle (green) is running on the highway with a car in front
of it (blue) on the same lane and with the same speed. The task of the autonomous driving agent is to
handle situations when the front car slows down quickly and abruptly. One common type of cognitive
bias is the *availability bias*, which reflects humans' tendency to overestimate the likelihood of events
with greater availability in memory. Such biases can occur in driving since we regularly drive under
familiar conditions. To design an experiment where such biases are present, we considered scenarios
with a regular driving condition and a sleety condition where the vehicle's domain dynamics became
more stochastic due to slippery roads. With the availability bias, however, humans are likely to make
the same decisions under these similar but in actuality different conditions, leading to safety risks.

The user study consists of two phases: training and testing. At the beginning of the training phase,
we requested the participates to provide the importance ratings for several factors governing the
autonomous driving behavior [9] in a 5-point Likert scale, such as average speed (3.42), distance
to the front car (4.57), relative speed to neighboring cars (3.28), and lane following (3.78). The
average participants' responses are shown in the parentheses above. Their responses served as the
engineered reward model (r_A) and are linearly combined. For example, the distance to the front car is
directly associated with collision and hence given a larger weight. Before human data collection, we
also presented the participants with the vehicle's behavior after braking under the regular condition
when the front car slows down suddenly. Then, given the information that it is driving on a sleety
day, we selected segments that showcased different vehicle behaviors after braking (i.e., braking
behaviors under different effectiveness). The participants were asked to select which one matched
their expectations the most. Their responses were used to validate the availability biases in this
experiment. Then, we collected human data by actively selecting pairs of trajectory segments for
the participants to compare with. The collected data was used to train our method and the baselines.
Then, we showed rollouts of the learned policy for each method to new participants and asked them
to rate those rollouts in the testing phase.

5.2.1   Results and Discussion

We published the experiments on Amazon Mechanical Turk (MTurk). To sift out invalid responses,
a sanity check demonstration was added that showed a collision, which should not be preferred
under any situation. We recruited 15 participants for training, and one failed the sanity check. For
the bias validation question, 12 out of 14 valid participants chose that the ego-vehicle would slow
down effectively on a sleety day when braking. This reflects the availability bias that the participants
had, which can lead to collisions on a slippery road if ignored. We also noticed that the participants
preferred to brake than steer in general during training, which accords with the participants' responses
that attached a high importance rating to distance to the front car and lane following.

The testing phase occurs on a sleety day. The behavior of EPS, SAC, and DRLHP agents are
illustrated in Fig. 4. SAC agent steers immediately when the front car slows down. It is the most
efficient behavior with the most return on a slippery road since braking would not be effective.

(a) EPS ($\mu = 7.6, \sigma = 2.4$)   (b) SAC ($\mu = 5.0, \sigma = 2.3$)   (c) DRLHP ($\mu = 5.9, \sigma = 2.2$)

Figure 4: Agents' behaviors in the autonomous driving domain illustrated in three characteristic steps from the top to bottom for each agent. The agent's name is followed by its average rating and standard deviation. The p-value from one-way ANOVA is 0.037. We conducted the Shapiro-Wilk test for normality assumption, where the p-value is 0.1192 (> 0.05). The Levene's test is applied to check the homoscedasticity assumption, where the p-value is 0.8465 (> 0.05). The results show that our tests satisfy the normality and homoscedasticity assumptions of one-way ANOVA [42].

385 DRLHP agent, on the other hand, chooses to brake while staying in the same lane. Such a behavior,
386 however, is more likely to lead to a collision (risk to human passengers). As we can see from Fig. 4,
387 the agent is getting dangerously close to the vehicle in the front. EPS agent first chooses to brake
388 (to be explicable), and then steers to the other lane (to stay safe and continue moving forward),
389 which maintains both explicability and task efficiency. We demonstrated these rollouts in the testing
390 phase to new participants. We informed the participants that the vehicle was running on a sleety
391 day. Each participant was required to provide ratings to all the demonstrations ranging from 1 to 10.
392 We obtained 15 valid responses. Interestingly, the participants rated EPS agent the most preferable,
393 followed by DRLHP and SAC agents. The average rating for each agent and its standard deviation
394 are shown in Fig. 4. We note that the results contradict with the importance ratings solicited for the
395 engineered reward model, which should have led to preferring the steering behavior as chosen by the
396 SAC agent on slippery roads. This further suggests that the participants had a biased belief about
397 the vehicle's dynamics (i.e., braking is as efficient under the regular condition as under the sleety
398 condition). Regardless, our agent chose the behavior that was both explicable and safe.

6   Discussions and Conclusions

400 In this paper, we introduced and formulated the problem of explicable policy search that considers
401 model differences between the learning agent and its human observer. We developed an efficient
402 solution by learning a surrogate reward function that was then used to recover an explicable policy.
403 Our method significantly extends explicable planning to an RL setting and to stochastic environments
404 with continuous state and action spaces. We evaluated in simulations and with human subjects.
405 Results showed that our approach could better handle situations under model differences than several
406 baselines and thus contributed a critical tool to achieving explainable human-agent interaction.

407 **Limitations and Future Work.** The assumptions underlying our work are that the human generates
408 her expectation based on her objective and belief about the domain dynamics in a noisily rational
409 way, and the human has a softmax preference model. While such assumptions were commonly
410 made in prior work, it is worthwhile to consider situations where the human is cognitively bounded.
411 Furthermore, we assume that the human's (inaccurate) belief about the domain dynamics does not
412 easily update as observations of the agent are made. For scenarios where inaccuracies stem from
413 intrinsic cognitive biases that are difficult to change, this is a reasonable assumption. In other cases
414 where discrepancies were due to, e.g., information asymmetries, the belief can change dynamically
415 and needs to be actively monitored [22]. Other possible directions include more complex (such
416 as state dependent) reconciliation of the expected return and policy explicability score, as well
417 as weighted policy explicability scores to incorporate trajectory similarity as considered in prior
418 work [48, 25].

419 Our approach covers many real-world applications since the human understanding of the agent's
420 model is inevitably different from the ground truth in real-world scenarios. As a result, EPS may
421 sometimes cause the user preferences to be ignored, which may be "unexplainable" but is a necessary
422 cost to pay in many scenarios. In particular, EPS combines the surrogate reward with an engineered
423 reward from the agent designer to ensure critical features (e.g., safety) while respecting user preference
424 whenever feasible. Note that the combination of such two reward functions should not be replaced

by the user's reward even if it can be perfectly estimated due to complexities such as human biases and misunderstandings of the domain. However, real-world deployment of EPS would require more work, such as an interactive design that explains to the user why her preferences are ignored.

Societal Impacts. Our research is generally fundamental in nature without notable negative societal impacts. However, it is conceivable that our approach may be used to misguide RL agents to ignore human preferences in adversarial settings. Further investigation must be conducted to understand such a possibility in more detail.

References

[1] P. Abbeel and A. Y. Ng. Apprenticeship learning via inverse reinforcement learning. In *ICML*, 2004.

[2] C. Baker, R. Saxe, and J. Tenenbaum. Bayesian theory of mind: Modeling joint belief-desire attribution. In *Proceedings of the annual meeting of the cognitive science society*, volume 33, 2011.

[3] D. Brown, W. Goo, P. Nagarajan, and S. Niekum. Extrapolating beyond suboptimal demonstrations via inverse reinforcement learning from observations. In *International conference on machine learning*, pages 783–792. PMLR, 2019.

[4] D. S. Brown, W. Goo, and S. Niekum. Better-than-demonstrator imitation learning via automatically-ranked demonstrations. In *Conference on robot learning*, pages 330–359. PMLR, 2020.

[5] D. S. Brown, J. Schneider, A. Dragan, and S. Niekum. Value alignment verification. In *International Conference on Machine Learning*, pages 1105–1115. PMLR, 2021.

[6] T. Chakraborti, S. Kambhampati, M. Scheutz, and Y. Zhang. Ai challenges in human-robot cognitive teaming. *arXiv preprint arXiv:1707.04775*, 2017.

[7] T. Chakraborti, A. Kulkarni, S. Sreedharan, D. E. Smith, and S. Kambhampati. Explicability? legibility? predictability? transparency? privacy? security? the emerging landscape of interpretable agent behavior. In *ICAPS*, 2019.

[8] T. Chakraborti, S. Sreedharan, Y. Zhang, and S. Kambhampati. Plan explanations as model reconciliation: moving beyond explanation as soliloquy. In *IJCAI*, 2017.

[9] E. Cheung, A. Bera, E. Kubin, K. Gray, and D. Manocha. Identifying driver behaviors using trajectory features for vehicle navigation. In *IROS*, 2018.

[10] P. F. Christiano, J. Leike, T. Brown, M. Martic, S. Legg, and D. Amodei. Deep reinforcement learning from human preferences. In *NeurIPS*, 2017.

[11] C. Daniel, M. Viering, J. Metz, O. Kroemer, and J. Peters. Active reward learning. In *RSS*, 2014.

[12] A. D. Dragan, K. C. Lee, and S. S. Srinivasa. Legibility and predictability of robot motion. In *2013 8th ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pages 301–308. IEEE, 2013.

[13] B. Erdem, M. Palan, N. C. Landolfi, D. P. Losey, D. Sadigh, et al. Asking easy questions: A user-friendly approach to active reward learning. In *CoRL*, 2020.

[14] B. Eysenbach, S. Asawa, S. Chaudhari, S. Levine, and R. Salakhutdinov. Off-dynamics reinforcement learning: Training for transfer with domain classifiers. *arXiv preprint arXiv:2006.13916*, 2020.

[15] M. Fox and D. Long. Pddl2. 1: An extension to pddl for expressing temporal planning domains. *Journal of artificial intelligence research*, 20:61–124, 2003.

[16] Z. Gong and Y. Zhang. Behavior explanation as intention signaling in human-robot teaming. In *RO-MAN*, 2018.

[17] Z. Gong and Y. Zhang. What is it you really want of me? generalized reward learning with biased beliefs about domain dynamics. In *AAAI*, 2020.

[18] S. Griffith, K. Subramanian, J. Scholz, C. L. Isbell, and A. Thomaz. Policy shaping: integrating human feedback with reinforcement learning. In *NeurIPS*, 2013.

[19] D. Gunning. Explainable artificial intelligence (xai). *DARPA*, 2017.

[20] T. Haarnoja, H. Tang, P. Abbeel, and S. Levine. Reinforcement learning with deep energy-based policies. In *ICML*, 2017.

[21] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

[22] A. Hanni and Y. Zhang. Generating active explicable plans in human-robot teaming. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 2993–2998. IEEE, 2021.

[23] M. Herman, T. Gindele, J. Wagner, F. Schmitt, and W. Burgard. Inverse reinforcement learning with simultaneous estimation of rewards and dynamics. In *AISTATS*, 2016.

[24] W. B. Knox and P. Stone. Interactively shaping agents via human reinforcement: The tamer framework. In *K-CAP*, 2009.

[25] A. Kulkarni, Y. Zha, T. Chakraborti, S. G. Vadlamudi, Y. Zhang, and S. Kambhampati. Explicable planning as minimizing distance from expected behavior. In *AAMAS*, 2019.

[26] T. Kurutach, I. Clavera, Y. Duan, A. Tamar, and P. Abbeel. Model-ensemble trust-region policy optimization. In *ICLR*, 2018.

[27] K. Lee, L. Smith, and P. Abbeel. Pebble: Feedback-efficient interactive reinforcement learning via relabeling experience and unsupervised pre-training. *ICML*, 2021.

[28] K. Lee, L. Smith, A. Dragan, and P. Abbeel. B-pref: Benchmarking preference-based reinforcement learning. *arXiv preprint arXiv:2111.03026*, 2021.

[29] E. Leurent. An environment for autonomous driving decision-making. `https://github.com/eleurent/highway-env`, 2018.

[30] Y. Li, J. Song, and S. Ermon. Infogail: Interpretable imitation learning from visual demonstrations. *Advances in Neural Information Processing Systems*, 30, 2017.

[31] C. Lucas, T. Griffiths, F. Xu, and C. Fawcett. A rational model of preference learning and choice prediction by children. *Advances in neural information processing systems*, 21, 2008.

[32] J. MacGlashan, M. K. Ho, R. Loftin, B. Peng, G. Wang, D. L. Roberts, M. E. Taylor, and M. L. Littman. Interactive learning from policy-dependent human feedback. In *ICML*, 2017.

[33] M. S. A. Nahian, S. Frazier, B. Harrison, and M. Riedl. Training value-aligned reinforcement learning agents using a normative prior. *arXiv preprint arXiv:2104.09469*, 2021.

[34] M. Oaksford and N. Chater. *Bayesian rationality: The probabilistic approach to human reasoning*. Oxford University Press, 2007.

[35] R. Paleja, Y. Niu, A. Silva, C. Ritchie, S. Choi, and M. Gombolay. Learning interpretable, high-performing policies for continuous control problems. *arXiv preprint arXiv:2202.02352*, 2022.

[36] D. Ramachandran and E. Amir. Bayesian inverse reinforcement learning. In *IJCAI*, 2007.

[37] S. Reddy, A. D. Dragan, and S. Levine. Where do you think you're going? inferring beliefs about dynamics from behavior. In *NeurIPS*, 2018.

[38] C. Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019.

[39] C. Rudin, C. Chen, Z. Chen, H. Huang, L. Semenova, and C. Zhong. Interpretable machine learning: Fundamental principles and 10 grand challenges. *Statistics Surveys*, 16:1–85, 2022.

[40] S. Russell. Learning agents for uncertain environments. In *Proceedings of the eleventh annual conference on Computational learning theory*, pages 101–103, 1998.

[41] D. Sadigh, A. D. Dragan, S. Sastry, and S. A. Seshia. Active preference-based learning of reward functions. In *RSS*, 2017.

[42] M. L. Schrum, M. Johnson, M. Ghuy, and M. C. Gombolay. Four years in review: Statistical practices of likert scales in human-robot interaction studies. In *Companion of the 2020 ACM/IEEE International Conference on Human-Robot Interaction*, pages 43–52, 2020.

[43] R. Shah, N. Gundotra, P. Abbeel, and A. Dragan. On the feasibility of learning, rather than assuming, human biases for reward inference. In *ICML*, 2019.

[44] A. Silva, M. Gombolay, T. Killian, I. Jimenez, and S.-H. Son. Optimization methods for interpretable differentiable decision trees applied to reinforcement learning. In *International conference on artificial intelligence and statistics*, pages 1855–1865. PMLR, 2020.

[45] H. A. Simon. Bounded rationality. In *Utility and probability*, pages 15–18. Springer, 1990.

[46] C. Wirth, R. Akrour, G. Neumann, J. Fürnkranz, et al. A survey of preference-based reinforcement learning methods. *JMLR*, 2017.

[47] M. Zakershahrak, A. Sonawane, Z. Gong, and Y. Zhang. Interactive plan explicability in human-robot teaming. In *RO-MAN*, 2018.

[48] Y. Zhang, S. Sreedharan, A. Kulkarni, T. Chakraborti, H. H. Zhuo, and S. Kambhampati. Plan explicability and predictability for robot task planning. In *ICRA*, 2017.

[49] B. D. Ziebart, A. L. Maas, J. A. Bagnell, and A. K. Dey. Maximum entropy inverse reinforcement learning. In *AAAI*, 2008.