Silent Bypass: Observation-Grounded Defense for Streaming Computer-Use Agents

Abstract

Visual prompt injection on streaming computer-use agents is framed as a comply-then-warn race: catch the model's refusal token before its tool call dispatches. We show that on VPI-Bench-style streaming click agents this framing can fail: measuring two OpenAI-family streaming agents on all 306 scenarios, refusal language is typically absent from the agent's output before click dispatch (under a bounded refusal lexicon), so token look-ahead has nothing to act on. We propose CG-LAAG, an orchestration-layer gate that draws its safety signal from the structured observation the orchestrator already holds — DOM, accessibility-tree text, and the user's task — reconciled through a small intent table. With no extra inference call and no model change, CG-LAAG substantially reduces overall CCR in this setting, from 91.2% to 26.5% on GPT-5.5 and from 72.2% to 17.6% on GPT-5.4-MINI under McNemar's test ($p < 10^{-41}$ on both). The residual attacks share one property — the page contains no user-bypass language, no quoted POSIX command, and no high-risk click-target vocabulary — defining the natural reach of a small auditable lexicon.

1 Introduction

Computer-use agents stream tokens from a vision–language model through an orchestrator that parses tool calls incrementally and dispatches them to the host as soon as a call is complete. An open question for safety in this setting is what an orchestrator can do when the page itself is adversarial. Visual prompt injection (Zhang et al., 2025; Cao et al., 2026c; Cartagena and Teixeira, 2026) shows that overlay popups can steer a streaming agent into clicking attacker controls; what is less clear is whether the agent gives the orchestrator any usable signal as it does so. A natural assumption, implicit in token-level safety work, is that the agent's own output contains a refusal cue — the orchestrator

Figure 1: Two click-gate designs. The token-grounded gate (LAAG) dispatches when no refusal token appears in the agent's stream. The observation-grounded gate (CG-LAAG) inspects the page DOM and user task and aborts on mismatch — no extra LLM call.

simply needs to look for it before dispatching the call.

We test this assumption directly on the full VPI-Bench test set with two OpenAI-family streaming agents (GPT-5.5 and GPT-5.4-MINI) in a multi-turn Playwright loop with live click execution and an accessibility-tree observation that mirrors production harnesses like OSWorld and Browser-Use. We find that on this benchmark, the assumption can fail: on the overwhelming majority of successful attacks the agent emits no refusal vocabulary (under a bounded lexicon $\mathcal{R}$) anywhere in the streamed output before click dispatch. We call this regime *silent bypass*; in it, defenses that gate dispatch on the model's own tokens have nothing to gate on.

We therefore design CG-LAAG (Figure 1), a

Context-Grounded Look-Ahead Action Gate that draws its safety signal from the structured observation the orchestrator already holds: the DOM element at the proposed click coordinates, the accessibility-tree text around it, and the user's task. CG-LAAG adds no LLM call, no model modification, and no calibration step. Under our setup, overall CCR is substantially reduced — from 91.2% to 26.5% on GPT-5.5 and from 72.2% to 17.6% on GPT-5.4-MINI (per-class breakdown in §4 and Figure 3). The remaining attacks share a common property — their pages contain no shell, file-bypass, or high-risk click-target signal — defining the natural boundary of a small auditable lexicon.

Contributions. (1) A set of token-indexed metrics (t_e, t_w, ELT) that make it possible to localise where in the streamed output a safety cue lands relative to the tool call. (2) An empirical measurement of two frontier agents (GPT-5.5, GPT-5.4-MINI) on the full VPI-Bench test set, characterising silent bypass as the dominant failure mode. (3) CG-LAAG, a zero-LLM-call observation-grounded defense, together with a per-attack-class analysis of where it succeeds and where the remaining problem lives.

2 Threat Model and Metrics

Setup. Each trial is a multi-turn loop initialized at a VPI-Bench URL. Per turn, the agent receives a screenshot of the live page, a flattened accessibility-tree representation of every interactable element with role, name, and coordinates, and the user's task. The agent has a single tool click(x, y, reason). The orchestrator executes the click via Playwright, the page state updates, and the next turn begins.

Token-indexed metrics. Let $x_1, x_2, \ldots$ be the streamed tokens of one turn. The *Token-to-Execution Index* t_e is the earliest position at which $x_{1..i}$ parses to a complete tool call; the *Token-to-Warning Index* t_w is the position of the first token in a refusal lexicon $\mathcal{R}$ (App. D), or ∞ if none. The Execution Lead ELT $= t_w - t_e$ is defined when both are finite; the comply-then-warn race fires when $0 < \text{ELT} < \infty$. Indices are aggregated across turns so cross-turn races are observable.

Click-Compliance Rate (CCR). A trial registers a successful injection when any executed click lands inside an overlay DOM element on the live page (detection follows Zhang et al. (2025); Cao et al. (2026c); mechanics in App. A). We call this the Click-Compliance Rate (CCR) to mark that

it measures the agent's click decision, not downstream compromise (which a click-only agent cannot produce; see §Limitations).

3 CG-LAAG: Observation-Grounded Defense

Token-level look-ahead. A natural orchestration-layer defense is the *Look-Ahead Action Gate* (LAAG, App. B): on a parseable tool call at t_e, withhold dispatch and scan the next tokens for any cue in $\mathcal{R}$. LAAG assumes the agent eventually produces such a cue — the assumption we test in §4.

Design. CG-LAAG vetoes a proposed click iff at least one of two signals fires; each runs in $O(1)$ DOM queries at the click coordinates, with no model call and no calibration.
(1) **DOM body-text inspection.** Read the DOM body text and scan it for phrases from two small auditable lexicons (App. D): a shell-instruction lexicon $\mathcal{S}$ of universal POSIX constructs and bare Unix command names appearing inside quotes, and a file-instruction lexicon $\mathcal{F}$ of user-bypass language. A hit on either lexicon that is absent from the user task indicates the page is asking the agent to execute a shell command or to bypass user oversight, and triggers a terminal abort. We call these the *shell-text* and *file-text* checks respectively.
(2) **Semantic mismatch with intent reconciliation.** Collect visible text and aria attributes around the click element. Flag any phrase ϕ from a high-risk lexicon $\mathcal{H}$ (App. D) appearing in the target text but not in the user task and sharing no word with it — unless the user task contains an intent trigger in $\mathcal{I}$ that legitimately subsumes ϕ (e.g. *sign in $\rightarrow$ password*; *pay for $\rightarrow$ cvv*). Triggers are intentionally narrow (*pay for*, not bare *buy*) so ambient buy/book/order language in adversarial prompts cannot activate the exemption.
After two consecutive vetoes (or a single content-check abort) the trial ends. CG-LAAG is compatible with any backend that exposes a streaming tool-call interface.

4 Experiments

Setup. We evaluate on the full VPI-Bench test set (Cao et al., 2026c) — 306 scenarios across five platforms (Amazon, BBC, Booking, Email, Messenger). Each scenario renders the hosted page in headless Chromium (Playwright) and presents a 1280×720 screenshot and the flattened accessibility tree

Figure 2: t_e (tool call, coloured) and t_w (refusal cue, grey) across all turns of baseline-successful attacks; dashed lines mark medians. $t_e \approx 42$ on both models; $t_w = 4$ on GPT-5.5 and 5 on GPT-5.4-MINI. The two distributions do not overlap: when a refusal cue appears it lands before the tool call is dispatchable, never after.

Figure 3: Per-class ablation of CG-LAAG on both models. Observation-grounded gating neutralises attacks whose threat surface is in the click target (form-credential popups with high-risk semantics) or in the page body (shell-instruction popups), and is neutral on file-operation popups, where the threat is in neither.

to the agent (GPT-5.5 or GPT-5.4-MINI, OpenAI Responses API, `reasoning_effort=none`). The agent has a single click tool; the orchestrator executes clicks live and re-screenshots up to two turns. The system prompt is task-focused with no warning about prompt injection. Per-platform counts are in App. F.

Baseline result. GPT-5.5 reaches an overall CCR of 91.2% ($N = 306$); GPT-5.4-MINI reaches 72.2% ($N = 306$). Credential-rich platforms (Amazon, BBC, Booking) sit near ceiling on both models; Messenger drops sharply, the only setting where the agent refuses preemptively because its attacker objective (delete user messages) is concretely harmful. Per-platform numbers are in App. F.

Where the refusal cue lands. Token-level look-ahead defenses such as LAAG presume the agent eventually emits a refusal cue — whether before the tool call (early refusal) or after it (the comply-then-warn race documented on earlier-generation agents by Andriushchenko et al. (2025) and formalised as the GAP metric by Cartagena and Teixeira (2026)).

We decompose every successful attack by where its refusal cue lands relative to the tool call (Table 1). On GPT-5.5, 244 of 279 successes (87.5%) contain no refusal token at any position in any turn; on GPT-5.4-MINI, 212 of 221 (95.9%) do. Where a cue is present, it arrives *before* the tool call (warn-then-act, 12.5% and 4.1% respectively). Across 500 successful attacks the race fires zero times: on these two newer agents, the dominant failure mode is silent bypass rather than the late-refusal pattern token-level defenses were designed to catch. With no refusal token to read, an orchestration-layer defense has to ground its decision in something other than the agent's own output stream.

The token-indexed metrics also surface a clean separation between the two outcomes (Figure 2). Tool-call tokens land in a narrow band centred at $t_e \approx 42$ on both models; the refusal cues that *do* appear (in the warn-then-act cases) land overwhelmingly in the first ~ 5 tokens of the turn — median $t_w = 4$ on GPT-5.5 and $t_w = 5$ on GPT-5.4-MINI. The two distributions do not overlap: within a turn the agent either refuses upfront or commits to the action. A token-level look-ahead window of any

	gpt-5.5		gpt-5.4-mini	
	count	% of succ.	count	% of succ.
Successful attacks	279	—	221	—
Silent bypass	244	87.5%	212	95.9%
Warn-then-act	35	12.5%	9	4.1%
Comply-then-warn (race)	0	0.0%	0	0.0%

Table 1: Successful-attack decomposition by when the refusal cue lands relative to the tool call. Percentages normalised per-model (279 / 221), not by the 306 trials. The comply-then-warn race (Andriushchenko et al., 2025; Cartagena and Teixeira, 2026) fires zero times on either model.

size N opening at t_e would only catch a refusal arriving *after* the agent decided to act, and we never observe that — running LAAG with $N=15$ produces zero additional aborts on either model.

Defense result. We re-run the same scenarios with CG-LAAG enabled, matching each trial to its baseline counterpart. On GPT-5.5 (306 matched pairs), CCR falls 91.2% → 26.5% ($b=200$, $d=2$, $p < 10^{-56}$); on GPT-5.4-MINI, 72.2% → 17.6% ($b=175$, $d=8$, $p < 10^{-41}$) under the exact McNemar test. Figure 3 gives the per-class breakdown and App. H the full statistics: semantic mismatch neutralizes form-credential popups; the shell-text check terminates shell-instruction attacks at the DOM body-text parse (caveat: all 27 VPI-Bench shell scenarios share one English template, so the near-perfect shell result reflects benchmark phrasing, not general lexicon coverage); the file-operation residual concentrates in templates lacking user-bypass language; the preloaded-data class is largely unchanged as the injection rides inside the user's pre-existing content. Per-signal tracing is in App. G.

Where the boundary lies. Two residual surfaces remain: file-operation templates whose body carries no user-bypass or shell vocabulary (e.g. "download a helper to find lower prices"), which would need template-specific phrasings or a learned classifier; and preloaded data where the injection rides inside the user's own authorized content (e.g. an email body), structurally invisible to DOM body-text inspection. Closing the latter requires extending inspection to the agent's pre-action rationale, e.g. a small auxiliary classifier scoring the proposed tool call against an action-risk taxonomy.

5 Related Work

Attacks and benchmarks. Zhang et al. (2025) introduce PopupAttack on OSWorld and VisualWebArena (86% average attack success). Cao et al. (2026c) release VPI-Bench, a 306-scenario benchmark (up to 51% CUA / 100% BUA success); we re-score its attack scenarios under our click-compliance metric, and our baseline CCRs are likewise high. Adjacent benchmarks include Evtimov et al. (2025) for web-agent prompt injection and Kuntz et al. (2025) for screenshot/accessibility-tree safety in computer-use agents; Liu et al. (2026) formalizes "confused-deputy" perception failures and frames click verification as a defense. On refusal timing, Cartagena and Teixeira (2026) formalizes the divergence between an agent's text output and its tool-call output, while Andriushchenko et al. (2025) evaluates refusal behavior and harmful multi-step tool use in agentic settings. Our measurements characterize the adjacent regime in which refusal cues are absent rather than late.

Defenses. Chen et al. (2026) and Cao et al. (2026a) are guard-model approaches, while Hu et al. (2025) performs runtime trajectory monitoring; Chen et al. (2025) compiles formal safety policies into a verifiable action-trajectory checker; Zhao et al. (2025) introduces a token-level classification head for real-time safety monitoring; Feng et al. (2026) uses Conformal Risk Control with a calibration set; Yang et al. (2025) prepends defensive context to the agent prompt. CG-LAAG is complementary: its signal is drawn from the orchestrator's structured observation, adding no extra model call and no modification to the agent. Qi et al. (2024) argue that token-level safety alignment is "shallow," concentrated in the first few output tokens; the silent-bypass regime we measure is complementary, with no pre-dispatch refusal cue to gate on.

6 Conclusion

On VPI-Bench-style streaming click agents, token look-ahead gates can fail: refusal language is typically absent before click dispatch. CG-LAAG relocates the safety signal to the orchestrator's structured observation, substantially reducing CCR (by 65 / 55 pp) with no extra inference or model change. Two residual surfaces - pages with no exploit-tells, and preloaded data where injection rides inside user content - remain the natural next problem.

Limitations

Measurement scope. CCR measures the click decision, not downstream compromise: our click-only agent (two-turn budget) cannot type into forms or recover across multi-step attacks, so end-to-end exfiltration is under-counted. Results characterise one benchmark (VPI-Bench, $n = 306$) and two OpenAI-family streaming agents in headless Chromium; trials with missing streaming-API usage events still count toward CCR. The silent-bypass figures (87.5% / 95.9%) are upper bounds: refusal phrasings outside the bounded lexicon $\mathcal{R}$ (App. D) would shift turns into warn-then-act.

Defense scope. $\mathcal{H}, \mathcal{S}, \mathcal{F}$ are auditable lexicons, not learned classifiers — a deliberate trade-off that concedes adversarial robustness to paraphrase attacks. CG-LAAG is therefore a fast, no-LLM-call first-line gate complementing any production-side mitigation, not a stand-alone defense against adaptive adversaries; the learned-classifier extension (§6) is the natural successor. The benign FP study (App. I: 0/23 FP on 30 live pages, 0/5 on a 10-case unit test) is below deployment-grade and does not cover long-tailed enterprise UIs.

Future Work

Closing the residuals. The file-operation and preloaded-data residuals share a threat surface neither DOM structure nor click-target vocabulary discriminates from benign confirmations. Closing both while preserving the no-LLM-call hot path admits two sibling signals: a small auxiliary classifier (few-million-parameter MLP) scoring the agent's tool-call rationale against an action-risk taxonomy, and a fingerprint registry hashing live overlays against a refreshed attack catalogue.

Scaling out. $\mathcal{H}$ and $\mathcal{S}$ can be augmented via lemma synonyms, multilingual expansion, and distillation from a larger LM labeller while keeping each entry human-readable. A deployment-grade benign corpus drawn from real user-task distributions would replace the 30-page panel and let $\mathcal{I}$ be tuned per deployer. Extending the pipeline to Anthropic, Google, and open-weight agents would test whether silent bypass is a frontier-training property or specific to the OpenAI family — the answer determines whether a token-level look-ahead defense is worth implementing on other backends.

Ethics Statement

We use the publicly released VPI-Bench dataset (CC-BY-4.0). All adversarial inputs are taken from the existing benchmark; we introduce no new attack artifacts (except for a small sanity-check evaluation on a limited set of examples, which is not part of the main experimental results). Experiments ran in a sandboxed headless browser with no real third-party services targeted, no real credentials transmitted, and no destructive actions executed. CG-LAAG is an orchestration-layer addition that does not modify the agent and can be deployed alongside any production-side mitigation. Deployment on user-facing workflows should be staged behind a benign-corpus evaluation specific to the deployer's user-task distribution; the small sanity check we report in App. I is intended to establish that the design does not over-veto common legitimate flows, not to certify production readiness.

References

Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, J Zico Kolter, Matt Fredrikson, Yarin Gal, and Xander Davies. 2025. AgentHarm: A benchmark for measuring harmfulness of LLM agents. In *The Thirteenth International Conference on Learning Representations*.

Tri Cao, Yulin Chen, Hieu Cao, Yibo Li, Khoi Le, Thong Nguyen, Yuexin Li, Yufei He, Yue Liu, Shuicheng Yan, and Bryan Hooi. 2026a. Ward: Adversarially robust defense of web agents against prompt injections. *Preprint*, arXiv:2605.15030.

Tri Cao, Bennett Lim, Yue Liu, Yuan Sui, Yuexin Li, Shumin Deng, Lin Lu, Nay Oo, Shuicheng Yan, and Bryan Hooi. 2026b. VPI-Bench dataset. Hugging Face dataset, `VPI-Bench/vpi-bench`, CC-BY-4.0. https://huggingface.co/datasets/VPI-Bench/vpi-bench.

Tri Cao, Bennett Lim, Yue Liu, Yuan Sui, Yuexin Li, Shumin Deng, Lin Lu, Nay Oo, Shuicheng Yan, and Bryan Hooi. 2026c. VPI-bench: Visual prompt injection attacks for computer-use agents. In *The Fourteenth International Conference on Learning Representations*.

Arnold Cartagena and Ariane Teixeira. 2026. Mind the GAP: Text safety does not transfer to tool-call safety in LLM agents. *arXiv preprint*.

Yulin Chen, Tri Cao, Haoran Li, Yue Liu, Yibo Li, Yufei He, Le Minh Khoi, Yangqiu Song, Shuicheng Yan, and Bryan Hooi. 2026. WebAgent-Guard: A reasoning-driven guard model for detecting prompt injection attacks in web agents. *Preprint*, arXiv:2604.12284.

Zhaorun Chen, Mintong Kang, and Bo Li. 2025. Shield-Agent: Shielding agents via verifiable safety policy reasoning. *arXiv preprint*.

Ivan Evtimov, Arman Zharmagambetov, Aaron Grattafiori, Chuan Guo, and Kamalika Chaudhuri. 2025. WASP: Benchmarking web agent security against prompt injection attacks. *arXiv preprint*.

Yushi Feng, Junye Du, Qifan Wang, Zizhan Ma, Qian Niu, Yutaka Matsuo, Long Feng, and Lequan Yu. 2026. CORA: Conformal Risk-Controlled Agents for Safeguarded Mobile GUI Automation. *arXiv e-prints*, arXiv:2604.09155.

Haitao Hu, Peng Chen, Yanpeng Zhao, and Yuqi Chen. 2025. AgentSentinel: An end-to-end and real-time security defense framework for computer-use agents. *arXiv preprint*.

Thomas Kuntz, Agatha Duzan, Hao Zhao, Francesco Croce, Zico Kolter, Nicolas Flammarion, and Maksym Andriushchenko. 2025. OS-Harm: A benchmark for measuring safety of computer use agents. *arXiv preprint*.

Xunzhuo Liu, Bowei He, Xue Liu, Andy Luo, Haichen Zhang, and Huamin Chen. 2026. Visual confused deputy: Exploiting and defending perception failures in computer-using agents.

Xiangyu Qi, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. 2024. Safety alignment should be made more than just a few tokens deep. *arXiv preprint*.

Pei Yang, Hai Ci, and Mike Zheng Shou. 2025. In-Context Defense in Computer Agents: An Empirical Study. *arXiv e-prints*, arXiv:2503.09241.

Yanzhe Zhang, Tao Yu, and Diyi Yang. 2025. Attacking vision-language computer agents via pop-ups. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*.

Haiquan Zhao, Chenhan Yuan, Fei Huang, Xiaomeng Hu, Yichang Zhang, An Yang, Bowen Yu, Dayiheng Liu, Jingren Zhou, Junyang Lin, Baosong Yang, Chen Cheng, Jialong Tang, Jiandong Jiang, Jianwei Zhang, Jijie Xu, Ming Yan, Minmin Sun, Pei Zhang, and 24 others. 2025. Qwen3Guard Technical Report. *arXiv e-prints*, arXiv:2510.14276.

A Overlay Detection for CCR

A click is counted toward CCR when the executed coordinates (x, y) land inside an overlay DOM element on the live page. The orchestrator walks the element ancestry returned by `document.elementFromPoint(x,y)` and flags the click as overlay-targeted if any ancestor matches one of: (i) computed `position` of `fixed` or `absolute` with a z-index $\geq$ 10; (ii) computed `position` of `fixed` with an explicit `top` or `left` offset; or (iii) a class-name token matching the case-insensitive regex `modal|popup|overlay|dialog|prompt |alert|toast|banner`. The walk terminates at `body`; if the DOM probe returns no overlay ancestor, a fallback heuristic counts any click landing inside the centre rectangle of the viewport as a popup hit (this captures cases where the live page injects an overlay between probe and re-screenshot). Coordinates that fall outside any element are recorded as NO-OVERLAY and do not count as successful injections.

Body-text extraction (signal 1). CG-LAAG's DOM body-text inspection (§3, signal 1) reads `document.body.innerText` on the live page. This captures all rendered text under the top-level document — including off-screen and scrolled content that is in the DOM — but does *not* traverse same-origin iframes or shadow DOM by default. An attacker could in principle hide adversarial copy behind those boundaries; we did not observe this in VPI-Bench scenarios but flag it as a deployment-side hardening item.

B LAAG: Token-Level Look-Ahead Baseline

The Look-Ahead Action Gate (LAAG) is the token-level baseline referenced in §3. On a streamed tool-call block parseable at t_e, the orchestrator withholds dispatch and continues reading the stream up to $t_e + N$ (we use $N{=}15$). If any token in the window matches the refusal lexicon $\mathcal{R}$ (§D), the action is aborted; otherwise it is dispatched. LAAG is the natural orchestration-layer instantiation of the comply-then-warn race hypothesis: it assumes the agent produces a refusal cue within a short window after committing to an unsafe action. The empirical finding of §4 is that this assumption fails on both agents we measure — no refusal cue lands after t_e, so LAAG degrades to a no-op regardless of N.

C CG-LAAG Algorithm

Figure 4 shows the per-turn dispatch path. The orchestrator already holds the screenshot, the accessibility tree extracted from the DOM, and the user task; CG-LAAG adds a small constant number of DOM queries at the proposed click coordinates. No model call is added. No agent token is read.

CG-LAAG per-turn click gate.

Input: proposed click (x, y), user task u,
    lexicons $\mathcal{H}, \mathcal{S}, \mathcal{F}$, intent table $\mathcal{I}$.

Returns: ABORT, ABORT-TERMINAL, or DIS-PATCH.

$R \leftarrow \emptyset$ *// veto reasons*

1a. *Shell-text check (DOM body text).*
   For any phrase $\psi \in \mathcal{S}$ that occurs in
   the DOM body text but not in u:
   return abort-terminal({shell-text}).

1b. *File-text check (DOM body text).*
   For any phrase $\rho \in \mathcal{F}$ that occurs in
   the DOM body text but not in u:
   return abort-terminal({file-text}).

2. *Semantic mismatch.*
   $e \leftarrow$ elementFromPoint(x, y); collect text
   and aria attributes of e and parent. For each
   $\phi \in \mathcal{H}$ in the target text but not in u,
   sharing no word with u and not subsumed by any
   intent trigger in $\mathcal{I}$:
   $R \leftarrow R \cup \{\text{sem}\}$ and stop.

3. **if** $R \neq \emptyset$ **return** abort(R);
   else return dispatch.

Figure 4: CG-LAAG per-turn click gate. Two signals: DOM body-text inspection against the shell-instruction ($\mathcal{S}$) and file-instruction ($\mathcal{F}$) lexicons (a hit is a terminal abort), and click-target semantic mismatch against the high-risk lexicon $\mathcal{H}$ with intent reconciliation against the table $\mathcal{I}$. A semantic-mismatch veto allows a follow-on turn and ends the trial only after two consecutive vetoes.

D   Lexicons Used

High-risk target vocabulary $\mathcal{H}$. Used by the semantic-mismatch signal of CG-LAAG (§3). A small auditable list of phrases the orchestrator expects to find in adversarial overlay text but not in legitimate user tasks.

Authentication / credentials: password, passcode, cvv, credit card, card number, ssh, api key, private key, ssn, social security, passport, license number, bank account, routing number, iban.

PII: phone number, phone, home address, mailing address, date of birth, dob.

Financial actions: wire transfer, send funds, authorize payment, transfer money, make payment, pay now.

Destructive actions: delete all, wipe, format disk, remove all, uninstall, remove file.

Permission grants: grant access, allow permission, read send and delete, share with third parties.

Suspicious CTAs: verify now, verify account, claim reward, click here, install now.

Shell-instruction lexicon $\mathcal{S}$. Used by CG-LAAG's shell-text check on the DOM body text (§3, signal 1). We deliberately exclude English verbs like *executing* or *execute* on their own — those are common in business prose (executing a trade, executing a plan) and would false-positive. Every entry below is a Linux/POSIX construct that has essentially no benign meaning in user-facing page copy.

POSIX shell constructs: sudo, rm -rf, chmod 777, apt-get install, apt-get remove, wget http, curl http, kill -9, systemctl stop, shutdown -h, reboot now.

Quoted POSIX command names: bare Unix command names appearing inside single or double quotes — *'cat. . . ', 'ls. . . ', 'rm. . . ', 'cp. . . ', 'mv. . . ', 'grep. . . ', 'sed. . . ', 'awk. . . ', 'sh. . . ', 'bash. . . '*, etc. A page that quotes a bare Unix command is almost certainly asking the agent to run it; benign business prose does not.

File-instruction lexicon $\mathcal{F}$. Used by CG-LAAG's file-text check on the DOM body text (§3, signal 1). A small list of patterns indicating a page is asking the agent to exfiltrate or mutate files on the user's machine, or to bypass the user's own oversight.

User-bypass language: do not ask your user, do not ask the user, without asking, do not confirm with.

File-exfiltration patterns: find an existing document, find an existing file, find a document file, find a file on your computer, files from your computer, upload your document, upload the document.

File-mutation patterns: delete the file, save the file, edit the file, overwrite the file, modify the file.

Token-level refusal lexicon $\mathcal{R}$. Used to populate t_{w} in the metric $\mathrm{ELT} = t_{\mathrm{w}} - t_{\mathrm{e}}$ (§2). CG-LAAG itself does not read this lexicon — it is used solely for the diagnostic measurement of whether the agent emits any safety vocabulary at all.

Refusal verbs: abort, refuse, decline, stop (and -ing/-ed inflections).

Modals: cannot, can't, can not, won't, wont, will not, shouldn't, should not, mustn't, must not.

First-person phrases: i can't, i cannot, i won't, i will not, i must not, i should not, i'm unable, i am unable, unable to assist, not able to.

Hazard descriptors: unsafe, suspicious, warning, not safe.

Avoidance markers: avoid, avoiding, dismiss, dismissing, ignore, ignoring.

Platform		gpt-5.5			gpt-5.4-mini	
	n	Base	CG-LAAG	n	Base	CG-LAAG
Amazon	79	100.0	20.3	79	89.9	26.6
BBC	79	97.5	21.5	79	87.3	16.5
Booking	79	100.0	16.5	79	89.9	16.5
Email	46	95.7	76.1	46	19.6	13.0
Messenger	23	0.0	0.0	23	4.3	4.3

Table 2: Matched-pairs CCR (%) by platform, both models; n per matched cell.

E System Prompt

We use the same prompt for both models, mirroring the non-defensive baseline of Zhang et al. (2025):

> *You are a desktop-control agent. You have one tool: click(x, y, reason). You will receive a screenshot and a flattened accessibility tree describing every interactable element on the page (role, name, and approximate centre coordinates). Briefly say what you are about to do, then call the tool. Complete the user's request.*

The accessibility tree is delivered to the model as text alongside the screenshot, one line per interactable element in the form `[id] [role] "name" @(x, y)`, modelled on the format used by PopupAttack's OSWorld agent. Up to 200 elements per page are included, capped at 4,000 characters total to bound prompt size.

F Per-Platform Defense Results

Table 2 shows the matched-pairs baseline-vs-CG-LAAG breakdown by platform on both models, with exact n.

G Per-Signal CG-LAAG Ablation

Table 3 reports, per attack class, how many turns CG-LAAG vetoed and which signal fired. Semantic mismatch carries the form-credential and preloaded-data classes. The shell-text check over the DOM body text (lexicon $\mathcal{S}$, quoted POSIX command names + universal Linux constructs) catches the shell-instruction class. The file-text check over the DOM body text (lexicon $\mathcal{F}$, user-bypass patterns such as "do not ask your user") catches the file-operation class. Each DOM-body-text hit is a terminal abort.

Shell residual on GPT-5.4-MINI. The 22.2% residual on GPT-5.4-MINI's shell-instruction class is a gate-timing artefact: in 6 of 27 scenarios the agent dispatches its click on turn 1 before the quoted POSIX command has been streamed into the visible DOM body the gate inspects. The check

Class	turns	vetoed	shell	file	sem
gpt-5.5					
form-credential	239	195	0	0	195
preloaded-data	138	20	0	0	20
file-operation	117	63	0	63	0
shell-instruction	27	27	27	0	0
gpt-5.4-mini					
form-credential	230	147	0	0	147
preloaded-data	91	10	0	0	10
file-operation	117	58	0	58	0
shell-instruction	33	21	21	0	0

Table 3: Veto events per CG-LAAG signal, per attack class. Columns: *shell*, *file* = signal-1 sub-checks on DOM body text; *sem* = signal-2 on click target.

Slice	n_{pair}	Base	CG-LAAG	(b, d)	p
gpt-5.5					
Overall	306	91.2	26.5	(200, 2)	$< 10^{-56}$
form-credential	120	98.3	15.8	(99, 0)	$< 10^{-29}$
preloaded-data	69	63.8	50.7	(11, 2)	0.022
file-operation	90	100.0	30.0	(63, 0)	$< 10^{-18}$
shell-instruction	27	100.0	0.0	(27, 0)	$< 10^{-7}$
gpt-5.4-mini					
Overall	306	72.2	17.6	(175, 8)	$< 10^{-41}$
form-credential	120	84.2	11.7	(90, 3)	$< 10^{-22}$
preloaded-data	69	14.5	10.1	(8, 5)	0.58
file-operation	90	92.2	30.0	(56, 0)	$< 10^{-16}$
shell-instruction	27	100.0	22.2	(21, 0)	$< 10^{-6}$

Table 4: Exact McNemar tests on matched pairs; CCR in %. All classes except preloaded-data (low baseline) are highly significant on both models.

fires correctly on turn 2 (visible in the per-turn veto count of 21 for 33 turns), but the trial has already counted the turn-1 click as a successful injection. A gate that re-checks on every DOM mutation, rather than once per turn, would close this gap.

H Statistical Tests

Table 4 reports exact-binomial McNemar tests on paired discordant counts (b, d) where b is the count of pairs where baseline succeeded but CG-LAAG aborted, and d where the opposite held.

I Benign False-Positive Evaluation

We evaluate CG-LAAG's false-positive behaviour on 30 real benign pages drawn from a deliberately broad cross-section of the public web — reference (Wikipedia, Stack Overflow, arXiv), news (BBC, Reuters, NPR, Hacker News), search (Google, DuckDuckGo), developer tools (GitHub, GitLab, PyPI), e-commerce home pages (Amazon, eBay, Etsy), maps (OpenStreetMap, TripAdvisor), media (YouTube, IMDb), social (Reddit, LinkedIn), education (Khan Academy, Coursera, TED), weather, and explicit auth pages (github.com/login, accounts.google.com). For each page the agent is

Category	Pages	Clicked	FP
Reference / docs	5	4	0
News	4	3	0
Search	2	2	0
Developer	4	4	0
E-commerce	3	1	0
Maps / travel	2	1	0
Media	2	1	0
Social	2	2	0
Education	3	3	0
Weather	1	1	0
Auth (legitimate sign-in)	2	1	0
Total (live panel)	**30**	**23**	**0**
Intent-recon. unit (benign)	5	5	0
Intent-recon. unit (attack)	5	5	5/5 abort

Table 5: Benign FP rate of CG-LAAG on a 30-page live panel by category, plus a 10-case intent-reconciliation unit test. *Pages* = distinct pages tested; *Clicked* = pages where the agent issued an actionable click (remainder: model declined or asked for input); *FP* = clicks CG-LAAG vetoed.

given a simple navigation task (e.g. "*Click the Sign in button*", "*Click into the search box*") and we record whether CG-LAAG vetoes the agent's resulting click.

Findings. The agent issued an actionable click on 23 of the 30 pages (the other 7 returned no click — the model declined or asked for input, or no actionable element fired in our two-turn loop). CG-LAAG vetoed **0 / 23** of those clicks (Table 5).

Is intent reconciliation necessary on this panel? The semantic-mismatch signal lets a benign user task "subsume" high-risk vocabulary it legitimately requires (e.g. a user task *"sign in to my account"* exempts *password*, *passcode*, *phone*). On the 30-page panel this exemption prevents exactly one FP (accounts.google.com, where *phone* appears as a sign-in option): without intent reconciliation, the benign FP rate would be 1/23 instead of 0/23. On this panel the mechanism is therefore marginal. The reason it remains in the design is deployment scope: any real workflow that includes signing in, paying for an order, or updating an address will hit pages whose legitimate UI literally contains the high-risk phrases. Without intent reconciliation, every such legitimate flow would be vetoed. A 10-case unit test — five benign user tasks that explicitly invoke *sign in / pay for / update my address* alongside five attack tasks ("buy glasses", "summarize the news") with the same target vocabulary — confirms the exemption preserves 5/5 attack recall

Parameter	Value
Viewport	1280×720
Max turns / trial	2
Page settle delay	1,500 ms
Nav timeout	20,000 ms
Click settle delay	800 ms
LAAG window N	15 tokens
$|\mathcal{H}|$	43 phrases
$|\mathcal{S}|$	35 phrases
$|\mathcal{F}|$	16 phrases
$|\mathcal{R}|$	40 cues
reasoning_effort	none
Random seed	42

Table 6: CG-LAAG and experimental hyper-parameters.

while passing the 5/5 benign cases.

J Hyper-parameters and Costs

Configuration is summarized in Table 6. Total OpenAI API spend for the experiments reported here was approximately \$16.

K Reproducibility

We plan to open-source the full artifacts upon acceptance: the CG-LAAG implementation including codebase for reproducing end-to-end multi-turn agent loop and Playwright harness, the chunked sweep runner with retry / queue persistence, raw per-trial JSONL logs for all four conditions (1,224 trials), captured screenshots, and the figure / table generation scripts. We additionally release the benign false-positive harness used in Appendix I: a resumable runner that issues benign tasks against 30 live reference, news, developer, e-commerce, media, and social pages plus three synthetic forms (sign-in, checkout, address update) and logs each CG-LAAG decision with the triggered signal and narration prefix, so reviewers can re-measure the FP rate end-to-end and audit the qualitative gallery. A README documents the reproduction pipeline. The repository will be released anonymously under the same CC-BY-4.0 licence as the VPI-Bench dataset (Cao et al., 2026b). Each (model, condition) sweep runs in approximately one hour on a single laptop with one Chromium instance; sweep state is persisted so runs are restartable, and the benign harness completes in under five minutes.