CPT: Efficient Deep Neural Network Training via Cyclic Precision

Abstract

Low-precision deep neural network (DNN) training has gained tremendous attention as reducing precision is one of the most effective knobs for boosting DNNs' training time/energy efficiency. In this paper, we attempt to explore low-precision training from a new perspective as inspired by recent findings in understanding DNN training: we conjecture that DNNs' precision might have a similar effect as the learning rate during DNN training, and advocate dynamic precision along the training trajectory for further boosting the time/energy efficiency of DNN training. Specifically, we propose Cyclic Precision Training (CPT) to cyclically vary the precision between two boundary values which can be identified using a simple precision range test within the first few training epochs. Extensive simulations and ablation studies on five datasets and ten models demonstrate that CPT's effectiveness is consistent across various models/tasks (including classification and language modeling). Furthermore, through experiments and visualization we show that CPT helps to (1) converge to a wider minima with a lower generalization error and (2) reduce training variance which we believe opens up a new design knob for simultaneously improving the optimization and efficiency of DNN training. All codes will be released upon acceptance.

1 Introduction

The record-breaking performance of modern deep neural networks (DNNs) often comes at a prohibitive training cost due to the required massive training data and model parameters, limiting the development of the highly demanded DNN-powered intelligent functions for use in numerous applications. As an illustration, training ResNet50 (He et al., 2016) involves 10^{18} FLOPs (FLOPs: floating-point operations) of computations and can take 14 days on one state-of-the-art NVIDIA M40 GPU (You et al., 2018). Meanwhile, the large DNN training costs have raised increasing financial and environmental concerns. For example, it is estimated that training one DNN can cost more than \$10K US dollars and emit carbon as high as a car's lifetime emissions. In parallel, recent DNN advances have fueled a tremendous need for intelligent edge devices, many of which require on-device in-situ learning to ensure the accuracy under dynamic real-world environments, where there is a mismatch between the devices' limited resources and the required prohibitive DNN training costs.

To address the aforementioned challenges, extensive research efforts have been devoted to developing efficient DNN training techniques. Among them, low-precision training has gained significant attention as it can largely boost the training time/energy efficiency (Jacob et al., 2018; Wang et al., 2018a; Sun et al., 2019). For instance, GPUs can now perform mixed-precision DNN training with 16-bit IEEE Half-Precision floating-point formats (Micikevicius et al., 2017b). Despite their promise, existing low-precision works have not yet fully explored the opportunity of leveraging recent findings in understanding DNN training. In particular, existing works mostly fix the model precision during the whole training process, i.e., adopt a **static** quantization strategy, while recent works in DNN training optimization suggest dynamic hyperparameters along DNNs' training trajectory. For example, (Li et al., 2019) shows that a large initial learning rate helps the model to memorize easier-to-fit and more generalizable patterns, which aligns with the common practice to start from a large learning rate for exploration and anneal to a small one for final convergence; and (Smith, 2017; Loshchilov & Hutter, 2016) improve DNNs' classification accuracy by adopting cyclical learning rates.

Inspired by prior works, we advocate dynamic precision for DNN training, and make the following contributions in this paper:

- We show that DNNs' precision seems to have a similar effect as the learning rate during DNN training, i.e., low precision with large quantization noise helps DNN training exploration while high precision with more accurate updates aids model convergence, and dynamic precision schedules help DNNs converge to a better minima. This finding opens up a design knob for simultaneously improving the optimization and efficiency of DNN training.

- We propose Cyclic Precision Training (CPT) which adopts a cyclic precision schedule along DNNs' training trajectory for pushing forward the achievable trade-offs between DNNs' achieved accuracy and training efficiency. Furthermore, we show that the cyclic precision bounds can be automatically identified at the very early stage of training using a simple precision range test, which has a negligible computational overhead.

- Extensive experiments on **five datasets** and **ten models** across a wide spectrum of applications (including classification and language modeling) validate the consistent effectiveness of the proposed CPT technique in boosting the training efficiency while leading to a comparable or even better accuracy. Furthermore, we provide loss surface visualization for better understanding CPT's effectiveness and discuss its connection with recent findings in understanding DNNs' training optimization.

2 RELATED WORKS

Quantized DNNs. DNN quantization (Courbariaux et al., 2015; 2016; Rastegari et al., 2016; Zhu et al., 2016; Li et al., 2016; Jacob et al., 2018; Mishra & Marr, 2017; Mishra et al., 2017; Park et al., 2017; Zhou et al., 2016) has been well explored based on the target accuracy-efficiency trade-offs. For example, (Jacob et al., 2018) proposes quantization-aware training to preserve the post quantization accuracy; (Jung et al., 2019; Bhalgat et al., 2020; Esser et al., 2019; Park & Yoo, 2020) strive to improve low-precision DNNs' accuracy using learnable quantizers. Mixed-precision DNN quantization (Wang et al., 2019a; Xu et al., 2018; Elthakeb et al., 2020; Zhou et al., 2017) assigns different bitwidths for different layers/filters. While these works all adopt a **static** quantization strategy, i.e., the assigned precision is fixed post quantization, CPT adopts a **dynamic** precision schedule during the training process.

Low-precision DNN training. Pioneering works (Wang et al., 2018a; Banner et al., 2018; Micikevicius et al., 2017a; Gupta et al., 2015; Sun et al., 2019) have shown that DNNs can be trained with reduced precision. For distributed learning, (Seide et al., 2014; De Sa et al., 2017; Wen et al., 2017; Bernstein et al., 2018) quantize the gradients to reduce the communication costs, where the training computations still adopt full precision; For centralized/on-device learning, the weights, activations, gradients, and errors involved in both the forward and backward computations all adopt reduced precision. Our CPT can be applied on top of these low-precision training techniques, all of which adopt a **static** precision during the **whole** training trajectory, to further boost the training efficiency.

Dynamic-precision DNNs. There exist some dynamic precision works which aim to derive a quantized DNN for inference after the full-precision training. Specifically, (Zhuang et al., 2018) first trains a full-precision model to reach convergence and then gradually decreases the model precision to the target one for achieving better inference accuracy; (Khoram & Li, 2018) also starts from a full-precision model and then gradually learns the precision of each layer to derive a mixed-precision counterpart; and (Yang & Jin, 2020) learns a fractional precision of each layer/filter based on the linear interpolation of two consecutive bitwidths which doubles the computation and requires an extra fine-tuning step. To the best of our knowledge, CPT is the first to study a **dynamic** precision schedule **along the training process** for boosting DNNs' training efficiency.

3 THE PROPOSED CPT TECHNIQUE

In this section, we first introduce the hypothesis that motivates us to develop CPT using visualization examples in Sec. 3.1, and then present the CPT concept in Sec. 3.2 followed by the Precision Range Test (PRT) method in Sec. 3.3, where PRT aims to automate the precision schedule for CPT.

3.1 CPT: MOTIVATION

Motivation hypothesis. Recent findings in DNN training have motivated us to rethink the role of DNN precision. Specifically, it has been discussed that (1) DNNs **learn to fit different patterns at**

different training stages, e.g., (Rahaman et al., 2019; Xu et al., 2019) reveals that DNN training first learns lower-frequency components and then high-frequency features, with the former being more robust to perturbations and noises; and (2) **dynamic learning rate schedules help** to improve the optimization in DNN training, e.g., (Li et al., 2019) points out that a large initial learning rate helps the model to memorize easier-to-fit and more generalizable patterns while (Smith, 2017; Loshchilov & Hutter, 2016) shows that cyclical learning rate schedules improve DNNs' classification accuracy. These works inspire us to **hypothesize** that precision has a similar effect as the learning rate and dynamic precision might help DNNs to reach a better optimum in the optimization landscape.

Visualization examples. Our hypothesis above has been consistently confirmed by various empirical observations. For example, Fig. 1 shows that progressively increasing the precision during training achieves a slightly higher accuracy (+0.3%) than its static counterpart, while the former reduces the training cost. Specifically, we train a ResNet-74 on CIFAR-100 using the same training setting as (Wang et al., 2018b) except that we quantize the weights, activations, and gradients during training; for the **progressive** precision case we uniformly increase the precision of weights and activations from 3-bit to

Figure 1: Test accuracy vs. epoch of ResNet-74 on CIFAR-100 under different precision schedules.

8-bit in the first 80 epochs and adopt static 8-bit gradients, while the static precision baseline uses 8-bit for all the weights/activations/gradients. Furthermore, we visualize the loss landscape (following the method in (Li et al., 2018)) in Fig. 3(b): interestingly the progressive precision schedule helps to converge to a better local minima with wider contours, indicating a lower generalization error (Li et al., 2018), compared with the static 8-bit baseline in Fig. 3(a).

The natural following question would be: what kind of dynamic schedules would be effective while being simple to implement for different tasks/models? In this work, we show that a simple cyclic schedule consistently benefits the training convergence while boosting the training efficiency.

3.2 CPT: THE KEY CONCEPT

The key concept of CPT draws inspiration from (Li et al., 2019) which demonstrates that a large initial learning rate helps the model to learn more generalizable patterns. We thus hypothesize that a lower precision that leads to a short-term poor accuracy might actually help the DNN exploration during training thanks to its associated larger quantization noise, while it is well known that a higher precision enables the learning of higher-complexity, fine-grained patterns that is critical to better convergence. Together, this combination could improve the achieved ac-

Figure 2: Static vs. Cyclic Precision Training (CPT), where CPT cyclically schedules the precision of weights and activations during training.

curacy as it might better balance coarse-grained exploration and fine-grained optimization during DNN training, which leads to the idea of CPT. Specifically, as shown in Fig. 2, CPT varies the precision cyclically between two bounds instead of fixing the precision during training, letting the models explore the optimization landscape with different granularities.

While CPT can be implemented using different cyclic scheduling methods, here we present as an example an implementation of CPT in a cosine manner:

$$B_t^n = \lceil B_{min}^n + \frac{1}{2}(B_{max}^n - B_{min}^n)(1 - cos(\frac{t \% T_n}{T_n}\pi)) \rceil \tag{1}$$

where B_{min}^n and B_{max}^n are the lower and upper precision bound, respectively, in the n-th cycle of precision schedule, $\lceil \cdot \rceil$ and $\%$ denote the rounding operation and the remainder operation, and B_t^n is the precision at the t-th global epoch which falls into the n-th cycle with a cycle length of T_n. Note that the cycle length T_n is equal to the total number of training epochs divided by the total number

Figure 3: Loss landscape visualization after convergence of ResNet-74 on CIFAR-100 trained with different precision schedules, where wider contours with larger intervals indicate a better local minima and a lower generalization error as analyzed in (Li et al., 2018).

of cycles denoted as N, where N is a hyperparameter of CPT. For example, if $N = 2$, then a DNN training with CPT will experience two cycles of cyclic precision schedule during training. As shown in Sec. 4.3, we find that the benefits of CPT are maintained when adopting different total number of cyclic precision schedule cycles during training, i.e., CPT is not sensitive to N. A visualization example for the precision schedule can be found in Appendix A. Note that we find that CPT is generally effective when using different dynamic precision schedule patterns (i.e., not necessarily the cosine schedule in Eq. (1)). We implement CPT following Eq. (1) in this work and discuss the potential variants in Sec. 4.3.

We visualize the training curve of CPT on ResNet-74 with CIFAR-100 in Fig. 1 and find that it achieves a 0.91% higher accuracy paired with a 36.7% reduction in the required training BitOPs (bit operations), as compared to its **static** fixed precision counterpart. In addition, Fig. 3 (c) visualizes the corresponding loss landscape, showing the effectiveness of CPT, i.e., such a simple and automated precision schedule leads to a better convergence with lower sharpness.

3.3 CPT: PRECISION RANGE TEST

The concept of CPT is simple enough to be plugged into any models and tasks to boost the training efficiency. One remaining question is how to determine the precision bounds, i.e., B_{min}^i and B_{max}^i in Eq. (1), which we find can be automatically decided in the first cycle (i.e., $T_i = T_0$) of the precision schedule using a simple PRT at a negligible computational cost. Specifically, PRT starts from the lowest possible precision, e.g., 2-bit, and gradually increases the precision while monitoring the difference in the training accuracy magnitude averaged over several consecutive iterations; once this training accuracy difference is larger than a preset threshold, indicating that the training can at least partially converge, PRT would claim that the lower bound is identified. While the upper bound can

Figure 4: Illustrating the precision range test for ResNet-152 and MobileNetV2 on CIFAR-100, where the switching point which exceeds the preset threshold is denoted by red circles.

be similarly determined, there exists an alternative which suggests simply adopting the precision of CPT's static precision counterpart. The remaining cycles use the same precision bounds.

Fig. 4 visualizes the PRT for ResNet-152/MobileNetV2 trained on CIFAR-100. We can see that the lower precision bound identified when the model experiences a notable training accuracy improvement for ResNet-152 is 3-bit while that for MobileNetV2 is 4-bit, aligning with the common observation that ResNet-152 is more robust to quantization than the more compact model MobileNetV2.

4 EXPERIMENT RESULTS

In this section, we will first describe the experiment setup in Sec. 4.1, benchmarking results over SOTA training methods across various tasks in Sec. 4.2, and then comprehensive ablation studies of CPT in Sec. 4.3. Finally, we will discuss CPT's connection with recent findings about DNN training.

4.1 EXPERIMENT SETUP

Models, datasets and baselines. We consider ten models (including ResNet-18/34/38/74/110/152/164 (He et al., 2016), MobileNetV2 (Sandler et al., 2018), Transformer (Vaswani et al., 2017), and LSTM (Hochreiter & Schmidhuber, 1997)) and five tasks (including CIFAR-10/100 (Krizhevsky et al., 2009), ImageNet (Deng et al., 2009), WikiText-103 (Merity et al., 2016), and Penn Treebank (PTB) (Mikolov et al., 2010)). In particular, we follow (Wang et al., 2019b) for implementing MobileNetV2 on CIFAR-10/100. Baselines: We first benchmark CPT over three SOTA static low-precision DNN training techniques: SBM (Banner et al., 2018), DoReFa (Zhou et al., 2016), and WAGEUBN (Yang et al., 2020), each of which adopts a different quantizer. Since SBM is the most competitive baseline among the three based on both their reported and our experiment results, we apply CPT on top of SBM, and all the static precision baselines adopt the SBM quantizer unless specifically stated. Another baseline is cyclic learning rate (CLR) (Loshchilov & Hutter, 2016) on top of static precision training, and we follow the best setting in (Loshchilov & Hutter, 2016).

Training settings. We follow the standard training setting in all the experiments. In particular, for classification tasks, we follow SOTA settings in (Wang et al., 2018b) for CIFAR-10/100 and (He et al., 2016) for ImageNet experiments, respectively; and for language modeling tasks, we follow (Baevski & Auli, 2018) for Transformer on WikiText-103 and (Merity et al., 2017) for LSTM on PTB.

Precision settings. The lower precision bound in all the experiments are set using the PRT in Sec.3.3 and the upper bound is the same as the precision of the corresponding static precision baselines. We only apply CPT to the weights and activations (together annotated as FW) and use static precision for the errors and gradients (together annotated as BW), the latter of which is to ensure stability of gradients (Wang et al., 2018a) (more discussion in Appendix B). In particular, CPT from 3-bit to 8-bit with 8-bit gradient is annotated as FW(3,8)/BW8. The total number of periodic precision cycles, i.e., N in Sec.3.3, for all the experiments is fixed to be 32 (see the ablation studies in Sec. 4.3).

Hardware settings and metrics. To validate the real hardware efficiency of the proposed CPT, we adopt standard FPGA implementation flows. Specifically, we employ the Vivado HLx design flow to implement FPGA-based accelerators on a Xilinx development board called ZC706 (Xilinx). To

Table 1: The test accuracy, computational cost, and latency of CPT, DoReFa (Zhou et al., 2016), WAGEUBN (Yang et al., 2020) and SBM (Banner et al., 2018) for training the ResNet-74/164 and MobileNetV2 models on CIFAR-10/100.

Model	Method	Precision (FW/BW)	CIFAR-10 Acc (%)	CIFAR-100 Acc (%)	GBitOPs	Latency (hour)
ResNet-74	DoReFa	8 / 8	91.16	69.31	2.67e8	44.6
	WAGEUBN	8 / 8	91.35	69.61	2.67e8	44.6
	SBM	8 / 8	92.57	71.44	2.67e8	44.6
	Proposed CPT	**3 - 8 / 8**	**93.23**	**72.35**	**1.68e8**	**35.04**
	Improv.		**+0.66**	**+0.91**	**-37.1%**	**-21.4%**
ResNet-74	DoReFa	6 / 6	90.94	69.01	1.50e8	33.2
	WAGEUBN	6 / 6	91.01	69.37	1.50e8	33.2
	SBM	6 / 6	91.15	70.31	1.50e8	33.2
	Proposed CPT	**3 - 6 / 6**	**92.4**	**70.83**	**1.05e8**	**27.5**
	Improv.		**+1.25**	**+0.52**	**-30.0%**	**-17.2%**
ResNet-164	DoReFa	8 / 8	91.40	70.90	6.04e8	101.9
	WAGEUBN	8 / 8	92.5	71.86	6.04e8	101.9
	SBM	8 / 8	93.63	72.53	6.04e8	101.9
	Proposed CPT	**3 - 8 / 8**	**93.83**	**72.9**	**3.8e8**	**80.5**
	Improv.		**+0.20**	**+0.37**	**-37.1%**	**-21.0%**
ResNet-164	DoReFa	6 / 6	91.13	70.53	3.40e8	76.7
	WAGEUBN	6 / 6	92.44	71.50	3.40e8	76.7
	SBM	6 / 6	91.95	70.34	3.40e8	76.7
	Proposed CPT	**3 - 6 / 6**	**93.02**	**71.79**	**2.37e8**	**63.5**
	Improv.		**+1.07**	**+0.29**	**-30.3%**	**-17.2%**
MobileNetV2	DoReFa	8 / 8	91.03	70.17	1.49e8	26.2
	WAGEUBN	8 / 8	92.32	71.45	1.49e8	26.2
	SBM	8 / 8	93.57	75.28	1.49e8	26.2
	Proposed CPT	**4 - 8 / 8**	**93.76**	**75.65**	**1.04e8**	**21.6**
	Improv.		**+0.19**	**+0.37**	**-30.2%**	**-17.6%**
MobileNetV2	DoReFa	6 / 6	90.25	68.4	8.39e7	18.4
	WAGEUBN	6 / 6	91.00	71.05	8.39e7	18.4
	SBM	6 / 6	91.56	72.31	8.39e7	18.4
	Proposed CPT	**4 - 6 / 6**	**91.81**	**73.18**	**6.63e7**	**15.7**
	Improv.		**+0.25**	**+0.87**	**-21.0%**	**-14.7%**

better evaluate the training cost, we consider both calculated GBitOPs (Giga bit operations) and real-measured latency on the ZC706 FPGA board.

4.2 BENCHMARK WITH SOTA STATIC PRECISION TRAINING METHODS

Benchmark on CIFAR-10/100. Benchmark over SOTA quantizers: We benchmark CPT with three SOTA static low-precision training methods, as summarized in Tab. 1, when training ResNet-74/164 and MobileNetV2 on CIFAR-10/100, covering both deep and compact models which are representative difficult cases of low-precision DNN training. Note that **the accuracy improvement is the difference between CPT and the strongest baseline under the same setting**. From Tab. 1, we can observe that (1) our CPT consistently achieves a win-win with both a higher accuracy (+0.19% ~ +1.25%) and a lower (-21.0% ~ -37.1% computational cost and -14.7% ~ -21.4% latency) under all the cases on CIFAR-10/100, even for the compact model MobileNetV2, and (2) CPT notably outperforms the baselines in terms of accuracy **under extremely low precision**, which is one of the most useful scenarios for low-precision DNN training. In particular, CPT with periodic precision between 4-bit and 6-bit boosts the accuracy by +1.25% and +1.07% on ResNet-74/164 respectively as compared with the static 6-bit training on CIFAR-10, verifying that CPT leads to a better convergence.

Benchmark over CLR on top of SBM: We further benchmark CPT with CLR (Loshchilov & Hutter, 2016) (inherit its besting setting on CIFAR-100), with both being applied on top of SBM as it achieves the best performance among SOTA quantizers as shown in Tab. 1, based on more DNN models and precision as shown in Fig. 5. We can see that (1) CPT still consistently outperforms all the baselines with a better accuracy and efficiency trade-off, and (2) CLR on top of SBM leads to a negative effect on the training accuracy, which we conjecture is caused by both the instability of gradients and the sensitivity of gradients to learning rate under low-precision training, as discussed in (Wang et al., 2018a), showing that CPT are more applicable to low-precision training than CLR.

Loss landscape visualization: To better understand the superior performance achieved by CPT, we visualize the loss landscape following the method in (Li et al., 2018), as shown in Fig. 6 covering both compact models and two low-precision settings (i.e., 6-bit and 8-bit) which are bottlenecks for low-precision DNN training. We can observe that again both standard and compact DNNs trained with CPT experience wider contours with less sharpness, indicating that CPT helps DNN training optimization to converge to a better local optima.

Benchmark on ImageNet. To verify the scalability of CPT on more complex tasks and larger models, we benchmark CPT with the SOTA staic precision training method SBM (Banner et al., 2018) on

Figure 5: Achieved accuracy vs. the required GBitOPs when training ResNet-38/74/110/152/164 and MobileNetV2 on CIFAR-100 using static precision, static precision plus CLR and CPT methods.

ResNet-110 Static FW8 / BW8	**ResNet-110 Cyclic FW(4,8) / BW 8**	**MobileNet-V2 Static FW6 / BW6**	**MobileNetV2 Cyclic FW(4,6) / BW6**
(a)	(b)	(c)	(d)

Figure 6: Loss landscape visualization of ResNet-110 and MobileNetV2 trained on CIFAR-100.

ResNet-18/34/50 with ImageNet, under which it is challenging for low-precision training such as 4-bit to work. As shown in Tab. 2, we can observe that CPT still achieves a reduced computational cost (up to -30.4%) with a comparable accuracy (-0.20% ~ +0.06%). In particular, CPT works well on ResNet-50, leading to both a slightly higher accuracy and a better training efficiency, indicating the scalability of CPT with the model complexity and thus its potential application in large scale training in addition to on-device training scenarios.

Table 2: The test accuracy and computational cost of ResNet-18/34/50 on ImageNet, trained with the proposed CPT and SBM (Banner et al., 2018).

Model	Method	Precision (FW/BW)	Acc (%)	GBitOPs	Precision	Acc (%)	GBitOPs
ResNet-18	SBM	8 / 8	69.60	2.86e9	6 / 6	69.30	1.61e9
	Proposed CPT	4 - 8 / 8	**69.64**	**1.99e9**	4 - 6 / 6	**69.33**	**1.27e9**
	Improv.		**+0.04**	**-30.4%**		**+0.03**	**-21.1%**
ResNet-34	SBM	8 / 8	**73.32**	5.77e9	6 / 6	**72.82**	3.24e9
	Proposed CPT	4 - 8 / 8	73.12	**4.03e7**	4 - 6 / 6	72.74	**2.57e9**
	Improv.		-0.20	**-30.2%**		-0.08	**-20.7%**
ResNet-50	SBM	8 / 8	76.29	6.47e9	6 / 6	75.72	3.63e9
	Proposed CPT	4 - 8 / 8	**76.35**	**4.51e9**	4 - 6 / 6	**75.74**	**2.87e9**
	Improv.		**+0.06**	**-30.3%**		**+0.02**	**-20.9%**

Table 3: The test accuracy and computational cost of (1) Transformer on WikiText-103 and (2) 2-LSTM (two-layer LSTM) on PTB for language modeling tasks, trained with the proposed CPT and SBM (Banner et al., 2018).

Model / Dataset	Method	Precision (FW/BW)	Perplexity	GBitOPs	Precision	Perplexity	GBitOPs
Transformer WikiText-103	SBM	8 / 8	31.77	1.44e6	6 / 8	32.41	9.87e5
	Proposed CPT	**4 - 8 / 8**	**30.22**	**1.0e6**	**4 - 6 / 8**	**31.0**	**7.66e5**
	Improv.		**-1.55**	**-30.2%**		**-1.41**	**-22.4%**
2-LSTM PTB	SBM	8 / 8	96.95	4.03e3	6 / 8	97.47	2.77e3
	Proposed CPT	**5 - 8 / 8**	**96.39**	**3.09e3**	**5 - 6 / 8**	**97.0**	**2.48e3**
	Improv.		**-0.56**	**-23.2%**		**-0.47**	**-10.5%**

Benchmark on WikiText-103 and PTB. We also apply CPT on language modeling tasks (including WikiText-103 and PTB) as shown in Tab. 3 to show that CPT is also applicable to natural language processing models. Tab. 3 shows that (1) CPT again consistently achieves a win-win in terms of accuracy (i.e., perplexity - the lower the better) and training efficiency, and (2) language modeling models/tasks are more sensitive to quantization, especially in LSTM models, as it always adapts to a larger lower precision bound, aligning with SOTA observations (Hou et al., 2019).

4.3 ABLATION STUDIES OF CPT

CPT with different precision ranges. We also evaluate CPT under a wide range of upper precision bounds, which correspond to different target efficiency to see if CPT still works well. As shown in Fig. 7, which plots a boxplot with each experiment being repeated ten times, we can see that (1) regardless of the adopted precision ranges CPT consistently achieves a win-win (a +0.74% ~ +2.03% higher accuracy and a -18.3% ~ -48.0% reduction in computational cost), especially under lower precision scenarios, and (2) **CPT even shrinks the accuracy variance**, which better aligns with the practical goal of efficient training.

Figure 7: Boxplots of CPT and its static counterpart on ResNet-74 with CIFAR-100 under various precision ranges.

Figure 8: The achieved test accuracy of CPT under different adopted number of precision schedule cycles, as compared to the static precision baseline SBM, when training ResNet-38/74 on CIFAR-100.

CPT with different adopted numbers of precision schedule cycles. To evaluate the sensitivity of CPT to the total number of adopted cyclic precision schedule cycles, we apply CPT on ResNet-38/74 and CIFAR-100 when using different numbers of schedule cycles. As shown in Fig. 8, which plots the mean of the achieved accuracy based on ten repeated experiments, we can see that (1) different choices for the total number of cycles lead to a comparable accuracy (within 0.5% accuracy) on CIFAR-10/100; and (2) CPT under different number of precision schedule cycles consistently outperforms the static baseline SBM in the achieved accuracy. Based on this experiment, we set $N = 32$ for simplicity.

CPT with different precision schedules. We also evaluate CPT using other cyclic precision schedule methods in addition to the cosine one, including a triangular schedule motivated by (Smith, 2017) and a cosine annealing schedule as the learning rate schedule in (Loshchilov & Hutter, 2016). Both methods adopt 32 cyclic cycles for fairness. As shown in Tab. 4, we can see that (1) CPT integrated with other precision schedules shows general effectiveness, and (2) the other two schedules even surpass our current adopted schedule in some cases but both of them do not perform well on compact models. We leave how to determine a global optimal cyclic schedule for a given model and task as a future work.

Table 4: Integrating different precision schedules into cyclic precision training for ResNet-74/164 and MobileNetV2 on CIFAR-100. Cosine (CPT) is the current schedule adopted by CPT.

	ResNet-74		ResNet-164		MobileNetV2	
Schedule	FW(3,8) / BW8	FW(3,6) / BW6	FW(3,8) / BW8	FW(3,6) / BW6	FW(4,8) / BW8	FW(4,6) / BW6
Cosine (our CPT)	**72.35**	70.83	72.7	71.77	**75.65**	**73.18**
Triangular	71.61	**71.22**	**72.94**	**72.37**	74.92	71.37
Cosine anneal	71.37	70.80	72.4	72.03	74.59	73.12

4.4 CONNECTIONS WITH RECENT THEORETICAL FINDINGS

There has been a growing interest in understanding and optimizing DNN training. For example, (Li et al., 2019) shows that training DNNs with a large initial learning rate helps the model to memorize easier-to-fit and more generalizable patterns faster and better. Recently, (Zhu et al., 2020) showed that under a convexity assumption the convergence bound of reduced-precision DNN training is determined by a linear combination of the quantization noise and learning rate. These findings regarding DNN training seem to be consistent with the effectiveness of our proposed CPT. In fact, (Zhu et al., 2020) motivates us to rethink the role of the adopted precision in DNN training.

5 CONCLUSION

We hypothesize that DNNs' precision might have a similar effect as the learning rate when it comes to DNN training, i.e., low precision with large quantization noise helps DNN training exploration while high precision with more accurate updates aids model convergence, and thus advocate that dynamic precision schedules help to DNN training optimization. We then propose a CPT framework which adopts a periodic precision schedule for low-precision DNN training in order to boost the achievable Pareto of task accuracy and training efficiency. Furthermore, we show that the periodic precision bounds can be automatically identified at the very early training stage using a simple precision range test, which has negligible computational overhead. Extensive experiments and ablation studies verify that CPT can notably reduce computational cost during training while achieving a comparable or even better accuracy. Our future work will strive to identify more theoretical grounds for such dynamic low-precision training.

REFERENCES

Alexei Baevski and Michael Auli. Adaptive input representations for neural language modeling. *CoRR*, abs/1809.10853, 2018. URL `http://arxiv.org/abs/1809.10853`.

Ron Banner, Itay Hubara, Elad Hoffer, and Daniel Soudry. Scalable methods for 8-bit training of neural networks. In *Advances in neural information processing systems*, pp. 5145–5153, 2018.

Jeremy Bernstein, Yu-Xiang Wang, Kamyar Azizzadenesheli, and Anima Anandkumar. signsgd: Compressed optimisation for non-convex problems. *arXiv preprint arXiv:1802.04434*, 2018.

Yash Bhalgat, Jinwon Lee, Markus Nagel, Tijmen Blankevoort, and Nojun Kwak. Lsq+: Improving low-bit quantization through learnable offsets and better initialization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 696–697, 2020.

Matthieu Courbariaux, Yoshua Bengio, and Jean-Pierre David. Binaryconnect: Training deep neural networks with binary weights during propagations. In *Advances in neural information processing systems*, pp. 3123–3131, 2015.

Matthieu Courbariaux, Itay Hubara, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks: Training deep neural networks with weights and activations constrained to+ 1 or-1. *arXiv preprint arXiv:1602.02830*, 2016.

Christopher De Sa, Matthew Feldman, Christopher Ré, and Kunle Olukotun. Understanding and optimizing asynchronous low-precision stochastic gradient descent. In *Proceedings of the 44th Annual International Symposium on Computer Architecture*, pp. 561–574, 2017.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Ahmed Taha Elthakeb, Prannoy Pilligundla, Fatemeh Mireshghallah, Amir Yazdanbakhsh, and Hadi Esmaeilzadeh. Releq: A reinforcement learning approach for automatic deep quantization of neural networks. *IEEE Micro*, 2020.

Steven K Esser, Jeffrey L McKinstry, Deepika Bablani, Rathinakumar Appuswamy, and Dharmendra S Modha. Learned step size quantization. *arXiv preprint arXiv:1902.08153*, 2019.

Suyog Gupta, Ankur Agrawal, Kailash Gopalakrishnan, and Pritish Narayanan. Deep learning with limited numerical precision. In *International Conference on Machine Learning*, pp. 1737–1746, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016. URL `https://github.com/facebookarchive/fb.resnet.torch`.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Lu Hou, Jinhua Zhu, James Kwok, Fei Gao, Tao Qin, and Tie-yan Liu. Normalization helps training of quantized lstm. In *Advances in Neural Information Processing Systems*, pp. 7346–7356, 2019.

Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew Howard, Hartwig Adam, and Dmitry Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2704–2713, 2018.

Sangil Jung, Changyong Son, Seohyung Lee, Jinwoo Son, Jae-Joon Han, Youngjun Kwak, Sung Ju Hwang, and Changkyu Choi. Learning to quantize deep networks by optimizing quantization intervals with task loss. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4350–4359, 2019.

Soroosh Khoram and Jing Li. Adaptive quantization of neural networks. In *International Conference on Learning Representations*, 2018.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Fengfu Li, Bo Zhang, and Bin Liu. Ternary weight networks. *arXiv preprint arXiv:1605.04711*, 2016.

Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. In *Advances in Neural Information Processing Systems*, pp. 6389–6399, 2018.

Yuanzhi Li, Colin Wei, and Tengyu Ma. Towards explaining the regularization effect of initial large learning rate in training neural networks. In *Advances in Neural Information Processing Systems*, pp. 11674–11685, 2019.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Stephen Merity, Nitish Shirish Keskar, and Richard Socher. Regularizing and optimizing lstm language models. *arXiv preprint arXiv:1708.02182*, 2017.

Paulius Micikevicius, Sharan Narang, Jonah Alben, Gregory Diamos, Erich Elsen, David Garcia, Boris Ginsburg, Michael Houston, Oleksii Kuchaiev, Ganesh Venkatesh, et al. Mixed precision training. *arXiv preprint arXiv:1710.03740*, 2017a.

Paulius Micikevicius, Sharan Narang, Jonah Alben, Gregory F. Diamos, Erich Elsen, David García, Boris Ginsburg, Michael Houston, Oleksii Kuchaiev, Ganesh Venkatesh, and Hao Wu. Mixed precision training. *CoRR*, abs/1710.03740, 2017b. URL http://arxiv.org/abs/1710.03740.

Tomas Mikolov, Martin Karafiát, Lukás Burget, Jan Cernocký, and Sanjeev Khudanpur. Recurrent neural network based language model. In Takao Kobayashi, Keikichi Hirose, and Satoshi Nakamura (eds.), *INTERSPEECH*, pp. 1045–1048. ISCA, 2010. URL http://dblp.uni-trier.de/db/conf/interspeech/interspeech2010.html#MikolovKBCK10.

Asit Mishra and Debbie Marr. Apprentice: Using knowledge distillation techniques to improve low-precision network accuracy. *arXiv preprint arXiv:1711.05852*, 2017.

Asit Mishra, Eriko Nurvitadhi, Jeffrey J Cook, and Debbie Marr. Wrpn: wide reduced-precision networks. *arXiv preprint arXiv:1709.01134*, 2017.

Eunhyeok Park and Sungjoo Yoo. Profit: A novel training method for sub-4-bit mobilenet models. *arXiv preprint arXiv:2008.04693*, 2020.

Eunhyeok Park, Junwhan Ahn, and Sungjoo Yoo. Weighted-entropy-based quantization for deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5456–5464, 2017.

Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of neural networks. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 5301–5310. PMLR, 09–15 Jun 2019.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *European conference on computer vision*, pp. 525–542. Springer, 2016.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

Frank Seide, Hao Fu, Jasha Droppo, Gang Li, and Dong Yu. 1-bit stochastic gradient descent and its application to data-parallel distributed training of speech dnns. In *Fifteenth Annual Conference of the International Speech Communication Association*, 2014.

Leslie N Smith. Cyclical learning rates for training neural networks. In *2017 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 464–472. IEEE, 2017.

Xiao Sun, Jungwook Choi, Chia-Yu Chen, Naigang Wang, Swagath Venkataramani, Vijayalak-shmi Viji Srinivasan, Xiaodong Cui, Wei Zhang, and Kailash Gopalakrishnan. Hybrid 8-bit floating point (hfp8) training and inference for deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 4900–4909, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Kuan Wang, Zhijian Liu, Yujun Lin, Ji Lin, and Song Han. Haq: Hardware-aware automated quantization with mixed precision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8612–8620, 2019a.

Naigang Wang, Jungwook Choi, Daniel Brand, Chia-Yu Chen, and Kailash Gopalakrishnan. Training deep neural networks with 8-bit floating point numbers. In *Advances in neural information processing systems*, pp. 7675–7684, 2018a.

Xin Wang, Fisher Yu, Zi-Yi Dou, Trevor Darrell, and Joseph E Gonzalez. Skipnet: Learning dynamic routing in convolutional networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 409–424, 2018b.

Yue Wang, Ziyu Jiang, Xiaohan Chen, Pengfei Xu, Yang Zhao, Yingyan Lin, and Zhangyang Wang. E2-train: Training state-of-the-art cnns with over 80% energy savings. In *Advances in Neural Information Processing Systems*, pp. 5138–5150, 2019b.

Wei Wen, Cong Xu, Feng Yan, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. Terngrad: Ternary gradients to reduce communication in distributed deep learning. In *Advances in neural information processing systems*, pp. 1509–1519, 2017.

Xilinx. Xilinx zynq-7000 soc zc706 evaluation kit. `https://www.xilinx.com/products/boards-and-kits/ek-z7-zc706-g.html`. (Accessed on 09/30/2020).

Yuhui Xu, Shuai Zhang, Yingyong Qi, Jiaxian Guo, Weiyao Lin, and Hongkai Xiong. Dnq: Dynamic network quantization. *arXiv preprint arXiv:1812.02375*, 2018.

Zhi-Qin John Xu, Yaoyu Zhang, Tao Luo, Yanyang Xiao, and Zheng Ma. Frequency principle: Fourier analysis sheds light on deep neural networks. *arXiv preprint arXiv:1901.06523*, 2019.

Linjie Yang and Qing Jin. Fracbits: Mixed precision quantization via fractional bit-widths. *arXiv preprint arXiv:2007.02017*, 2020.

Yukuan Yang, Lei Deng, Shuang Wu, Tianyi Yan, Yuan Xie, and Guoqi Li. Training high-performance and large-scale deep neural networks with full 8-bit integers. *Neural Networks*, 125:70–82, 2020.

Yang You, Zhao Zhang, Cho-Jui Hsieh, James Demmel, and Kurt Keutzer. Imagenet training in minutes. In *Proceedings of the 47th International Conference on Parallel Processing*, pp. 1. ACM, 2018.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Train-ing low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv preprint arXiv:1606.06160*, 2016.

Yiren Zhou, Seyed-Mohsen Moosavi-Dezfooli, Ngai-Man Cheung, and Pascal Frossard. Adaptive quantization for deep neural network. *arXiv preprint arXiv:1712.01048*, 2017.

Chenzhuo Zhu, Song Han, Huizi Mao, and William J Dally. Trained ternary quantization. *arXiv preprint arXiv:1612.01064*, 2016.

Feng Zhu, Ruihao Gong, Fengwei Yu, Xianglong Liu, Yanfei Wang, Zhelong Li, Xiuqi Yang, and Junjie Yan. Towards unified int8 training for convolutional neural network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1969–1979, 2020.

Bohan Zhuang, Chunhua Shen, Mingkui Tan, Lingqiao Liu, and Ian Reid. Towards effective low-bitwidth convolutional neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7920–7928, 2018.

A VISUALIZATION OF THE PRECISION SCHEDULE IN CPT

Fig. 9 visualizes the precision schedule FW(3,8) with eight cycles for training on CIFAR-10/100.

Figure 9: Visualization of precision schedule FW(3,8) with eight cycles. The red line is the cosine-manner schedule and the blue line is the adopted precision after rounding.

B CPT ON TOP OF GRADIENT

We decide not to apply CPT on top of gradient since (1) the instability of gradients during low precision training (Wang et al., 2018a) harms the final convergence, and (2) generally the required precision of gradient is higher than that of weight and activation, so that it's hard to benefit from the CPT on gradient in terms of efficiency.

To validate this, we show the result of applying CPT on top of gradient only with fixed precision for weight and activation in Tab. 5. Compared with the static precision baseline, CPT on top of gradient can hardly benefit either accuracy or efficiency. Therefore, we adopt use fixed gradient precision in all the main experiments.

Table 5: Training ResNet-74 on CIFAR-100 with static precision and CPT on top of gradient only.

FW	BW	Accuracy (%)
6	6	70.31
6	8	70.51
6	6-8	69.45
6	6-10	70.32
6	6-12	69.59
6	6-16	70.24