Thinking in Different Spaces: Domain-Specific Latent Geometry Survives Cross-Architecture Translation

Abstract

We investigate whether independently trained language models converge to geometrically compatible latent representations, and whether this compatibility can be exploited to correct model behavior at inference time without weight updates. We learn a linear projection matrix mapping activation vectors from a teacher model into a student model's coordinate system, then intervene on the student's residual stream during generation by substituting its internal state with the translated teacher representation. Across 20 heterogeneous teacher-student pairings, the projection achieves $R^2 \approx 0.50$ on verbal reasoning and $R^2 \approx 0.40$ on mathematical reasoning, with behavioral correction rates of 14.0%–50.0% on TruthfulQA and 8.5%–43.3% on GSM8K, demonstrating generalization across reasoning domains. Geometric alignment quality does not predict correction rate ($r \approx -0.07$), suggesting directional accuracy matters more than variance explained. Student sensitivity profiles are architecture-specific and invert across domains: the most steerable verbal student becomes the least steerable mathematical student. Finally, a double dissociation across all 20 pairings confirms that projection matrices collapse catastrophically when transferred across domains (mean $R^2 = -3.83$), establishing domain-specific subspace geometry as a universal property of cross-architecture latent alignment.

1 Introduction

The remarkable convergence of large language models (LLMs) on similar outputs suggests they might be learning the exact same underlying structure of language. However, it remains an open question whether their internal representations reflect a shared reality. Current interpretability research overwhelmingly focuses on intra-model dynamics—extracting, analyzing, and manipulating features within a single, isolated network. We extend this paradigm to inter-model steering. By mapping activations from one architecture directly to another, we probe whether independently trained models actually share a fundamental topological structure in their latent spaces.

We hypothesize that models trained on overlapping linguistic distributions naturally converge to topologically similar manifolds for core semantic concepts. If this holds true, their internal representations should not be entirely alien to one another. Instead, a straightforward linear transformation—essentially a combination of rotation and scaling—should be sufficient to align these manifolds. To test this, we learn a projection matrix that maps the intermediate activation space of a "teacher" model into the coordinate system of a "student" model. We then intervene on the student during inference, substituting its internal state with the translated teacher state to correct reasoning trajectories in real time.

Our findings demonstrate that this cross-architecture alignment is not only possible but highly effective, though it is bounded by strict geometric constraints. Specifically, our primary contributions are as follows:

- **Empirical Existence Proof:** We show that a linear projection consistently aligns latent representations across highly heterogeneous architectures for both verbal and mathematical reasoning, achieving $R^2 \approx 0.50$ on TruthfulQA and $R^2 \approx 0.40$ on GSM8K across 20 independent model pairings.

- **Distributed Encoding:** Through ablation studies comparing L_2 and L_1 regularization, we confirm that shared representations are

distributed rather than sparse. The collapse of L_1 mappers to $R^2 \approx 0.01$ indicates semantic alignment relies holistically on the full activation vector.

- **Architecture-Specific Intervention Dynamics:** We demonstrate that optimal intervention strength is a property of the student architecture rather than a universal hyperparameter, with student models exhibiting characteristic sensitivity profiles that invert across reasoning domains—Phi-3-Mini is the most steerable student on verbal tasks and the least steerable on mathematical tasks.

- **Manifold Orthogonality:** We provide definitive evidence of domain modularity via double dissociation confirmed across all 20 model pairings without exception. Projection matrices trained on verbal truthfulness collapse to a mean $R^2 = -3.83$ on arithmetic reasoning and vice versa ($R^2 = -1.73$), proving that distinct reasoning domains occupy geometrically orthogonal latent subspaces.

2 Related Work

2.1 Linear Representations in Neural Networks

The foundational observation motivating our work is that neural networks encode semantic knowledge geometrically. Mikolov et al. (2013) first demonstrated this at scale in word embeddings, showing that semantic relationships manifest as stable linear directions in vector space. The Linear Representation Hypothesis, formalized by Elhage et al. (2022) and validated by Nanda et al. (2023), extends this to transformer residual streams: semantic concepts are encoded as specific directions in activation space, making the model's internal state a structured geometric object whose distances and angles carry interpretable semantic content. If concepts are encoded as directions, a rotation and uniform scaling—operations captured exactly by a linear transformation—are in principle sufficient to align two coordinate systems encoding the same concepts in different orientations.

2.2 Cross-Architecture Alignment and Model Stitching

Bansal et al. (2021) demonstrated that independently trained models can form functional composites via model stitching: inserting a learned linear layer between the first k layers of one network and the final $n - k$ layers of another produces surprisingly modest performance degradation, suggesting that a shared training objective is sufficient to produce compatible representations regardless of shared weights or structure. Csiszárik et al. (2021) extended this by developing rigorous metrics for representational similarity, showing that models converge to geometrically matchable representations even under different random initializations. Together, these results establish the *affine compatibility assumption* as an empirically grounded prior. Our work departs from this foundation in a critical way: prior stitching routes activations through a fixed adapter at training time, whereas our method performs *active inference-time intervention*, dynamically overwriting the student's residual stream during generation.

2.3 Representation Engineering and Activation Steering

A parallel body of work has demonstrated that model behavior can be steered by directly manipulating internal activations without weight updates. Subramani et al. (2022) showed that continuous steering vectors extracted from a model's residual stream can guide generation toward target behaviors. Turner et al. (2024) demonstrated that fixed bias vectors added at specific layers reliably shift behavior across dimensions including honesty, sentiment, and persona. Panickssery et al. (2024) extended this via contrastive activation addition, showing that difference-of-means vectors constructed from contrastive prompt pairs produce reliable behavioral shifts across tasks. Stolfo et al. (2025) further demonstrated that activation steering improves instruction-following without any weight update. Zou et al. (2023) revealed that such vectors exhibit universal properties, generalizing across model families and tasks. This literature establishes the residual stream as a writable medium, but all prior work operates within a single model. Our work extends this to cross-architecture steering, requiring explicit

geometric translation before application.

Concurrently, Wang et al. (2025) propose ExpertSteer, which derives steering signals from an external expert model via autoencoder alignment and Recursive Feature Machines. Our method differs in two fundamental respects: we learn a single affine projection directly on paired hidden states rather than a nonlinear autoencoder pipeline, and we perform direct residual stream substitution rather than additive steering—a distinction that enables the geometric interpretability analysis central to our theoretical framework.

2.4 Probing and Hierarchical Layer Processing

Interpretability research consistently demonstrates that transformer layers process information hierarchically: lower layers resolve syntax, middle layers construct semantic representations, and final layers produce task-specific outputs (Tenney et al., 2019; Belinkov, 2022). Because our teacher and student models differ substantially in depth, this hierarchy motivates parameterizing layer selection by *relative processing depth* rather than absolute index—a layer at 75% depth in a 32-layer model occupies an analogous functional role to one at 75% depth in an 80-layer model. Din et al. (2024) further establish injection timing as a consequential variable, directly motivating the temporal alignment strategy in Section 3.3.

3 Theoretical Framework

This section formalizes the three core components of our method: the affine compatibility assumption that justifies the projection, the intervention mechanics governing injection strength, and the temporal alignment strategy determining where in the student's pipeline injection must occur.

3.1 Affine Manifold Compatibility

Contemporary language models are trained to minimize next-token prediction loss over largely overlapping linguistic corpora. Because the statistical regularities of language are properties of the data rather than properties a model invents, two models compressing the same regularities will build geometrically compatible internal representations: their conceptual manifolds will align in topology even if coordinate orientations differ.

We formalize this as *affine compatibility*. Rather than assuming strict isomorphism, we assume the relationship between the student's hidden state h_S and the teacher's hidden state h_T is well-approximated by:

$$h_S \approx W h_T + b \qquad (1)$$

where $W \in \mathbb{R}^{d_S \times d_T}$ captures the rotation and scaling required to align the teacher's conceptual manifold with the student's coordinate system, and b absorbs mean shifts between spaces. We deliberately restrict this transformation to be linear: W encodes a global rotation of the representational manifold, making every concept subject to the same geometric operation. A nonlinear projection would allow the adapter to warp different manifold regions independently, obscuring whether representations are genuinely compatible or merely forced into alignment by an expressive enough function.

3.2 Intervention Strength and the α Spectrum

We model the intervention as a combination of the student's original residual state and the projected teacher representation:

$$h_{\text{final}} = (1 - \alpha) h_{\text{student}} + \alpha (W h_T) \qquad (2)$$

For $\alpha \in (0, 1)$, this interpolates between the two states. At $\alpha = 1$, the student's state is replaced entirely by the projected teacher vector. For $\alpha > 1$, the formula enters an extrapolative regime whose geometric meaning is revealed by rearranging at $\alpha = 2$:

$$h_{\text{final}} = W h_T + (W h_T - h_{\text{student}}) \qquad (3)$$

Here the intervention simultaneously amplifies the projected teacher vector and subtracts the student's original activation—active error negation rather than blending. This is physically meaningful when the student's residual stream has accumulated sufficient inertia that simple substitution is insufficient to redirect computation (nostalgebraist, 2020; Elhage et al., 2021). We treat α as an empirical quantity: different student architectures exhibit characteristic sensitivities to injected representations, and optimal α is a property of the student model rather than a universal hyperparameter. We note that Equation 2 assumes the projected vector $W h_T$

operates in a compatible magnitude regime; the practical realization of this constraint is detailed in Section 4.

3.3 Temporal Alignment and Layer Selection

Effective intervention requires temporal alignment: the projected representation must arrive where it can propagate meaningfully to the output distribution, neither so early that subsequent layers overwrite it nor so late that decoding computation is bypassed. We parameterize layer selection by *relative processing depth* $l \in [0, 1]$, mapping the hierarchical stages identified in the probing literature onto a common scale that transfers across architectures (Tenney et al., 2019; Belinkov, 2022).

We hypothesize a *semantic handoff*: extracting from deep teacher layers ($l_T \approx 0.90$), where abstract reasoning is fully resolved, and injecting into mid-to-late student layers ($l_S \approx 0.75$), where the student transitions from semantic representation to vocabulary decoding (Din et al., 2024). We treat relative depth as a principled *search space* rather than a fixed prescription, as the optimal injection point is sensitive to each student architecture's functional organization. We therefore evaluate injection across a grid of relative depth combinations and characterize the empirical behavior in Section 5.5.

4 Methodology

4.1 Datasets

We evaluate on two benchmarks targeting distinct reasoning domains. **TruthfulQA** (Lin et al., 2022) is a dataset of 817 questions probing factual recall and verbal truthfulness across domains including health, law, history, and common misconceptions. Each question is paired with a `best_answer` field and a `correct_answers` field. We use the full validation split. **GSM8K** (Cobbe et al., 2021) is a dataset of grade school arithmetic word problems requiring multi-step numerical reasoning. We use the test split (1,319 questions) for intervention evaluation. Each problem is paired with a full chain-of-thought solution ending with a final numeric answer delimited by `####`. We extract this final answer for evaluation. Both benchmarks use the prompt template `Question: {question} Answer:`, with `max_new_tokens=50` for TruthfulQA and `max_new_tokens=100` for GSM8K to accommodate numeric answer generation.

4.2 Optimization Objective

For each model pair, we perform a full forward pass over all 817 questions and extract the final-token hidden state at each candidate layer.

$$\tilde{h} = \frac{h}{\|h\|_2} \qquad (4)$$

ensuring directional alignment is learned rather than magnitude differences, which are architectural artifacts. We optimize:

$$\min_W \|H_S - H_T W\|_F^2 + \lambda \|W\|_F^2 \qquad (5)$$

with fixed $\lambda = 0.1$, learned with a bias term corresponding to the full affine formulation in Equation 1. All R^2 scores are reported on a held-out test set using a 70/30 train/test split (seed 42).

4.3 Representation Structure Controls

We employ two controls to validate that the learned W captures genuine semantic geometry rather than spurious correlations.

Permutation Control. A second Ridge regression is fit with rows of H_S randomly shuffled, destroying semantic correspondence while preserving the marginal distribution. Any R^2 achieved by this sham mapper reflects distributional properties of the vectors rather than semantic alignment.

Sparsity Control (L_1). We replace the L_2 penalty with an L_1 (Lasso) penalty ($\lambda = 0.0001$, max 5000 iterations):

$$\min_W \|H_S - H_T W\|_F^2 + \lambda \|W\|_1 \qquad (6)$$

If shared semantic information is localized to sparse features, the L_1 mapper should identify them and maintain competitive R^2. Collapse under sparsity would confirm that alignment relies on distributed correlations across the full activation vector.

4.4 Intervention Mechanics

For each model pair and layer combination, we identify an *opportunity set*: questions where the teacher answered correctly and the student did not. We pre-compute projected activations for all opportunity items:

$$\hat{h}_S^{(i)} = W \tilde{h}_T^{(i)} + b \qquad (7)$$

These are injected via a forward hook on the target layer, rescaled to match the L_2 norm of the student's current residual stream before application:

$$h_{\text{final}} = (1 - \alpha)\, h_{\text{student}} + \alpha \left(\hat{h}_S \cdot \|h_{\text{student}}\|_2 \right) \quad (8)$$

ensuring the intervention operates as a directional correction regardless of dimensional gap between architectures. We sweep layer depths at four relative positions $l \in \{0.25, 0.50, 0.75, 0.90\}$ for both teacher and student (16 combinations per pairing) and the intervention coefficient across eight values:

$$\alpha \in \{0.25, 0.5, 0.8, 1.0, 2.0, 3.0, 5.0, 10.0\} \quad (9)$$

All generation uses greedy decoding (`do_sample=False`, max 50 new tokens) ensuring fully deterministic outputs.

4.5 Evaluation Metric

We use deterministic matching rather than LLM-as-judge evaluation to avoid variance from probabilistic evaluators.

For **TruthfulQA**, success is binary inclusion against reference fields:

$$\text{Score}(x) = \mathbb{I}(y_{\text{best}} \in x) \vee \bigvee_{y \in \mathcal{Y}_{\text{correct}}} \mathbb{I}(y \in x) \quad (10)$$

where x is the generated text lowercased and stripped.

For **GSM8K**, we extract the gold numeric answer from the #### delimiter and check for numeric equivalence in the generated text, handling formatting variants including comma separators and currency prefixes. The correction rate Δ reports the percentage of opportunity set items where the intervention converted an incorrect output to a correct one. This strict standard acts as a conservative lower bound: any observed $\Delta > 0$ is a direct consequence of the intervention forcing retrieval of the precise target concept.

5 Experiments and Results

5.1 Experimental Setup

Table 1 lists all models evaluated, spanning intra-family pairings, a domain-specialized teacher, and a synthetically trained student. The full sweep produces 2,560 conditions: 20 pairings × 16 layer combinations × 8 α values.

5.2 Linear Alignment Efficacy

When estimated via Ridge regression, the projection matrix consistently recovers substantial variance in the student's activation space. Across all 20 pairings and layer combinations, the Ridge mapper achieves mean $R^2 \approx 0.50$, with a peak of $R^2 = 0.684$ for the Llama-8B $\rightarrow$ Llama-1B intra-family pairing. Explaining approximately half the target variance via a single affine transformation across completely independent architectures with no shared weights, training procedure, or initialization constitutes a substantial structural signal.

The permutation control confirms that this signal reflects genuine semantic geometry. Destroying semantic correspondence by shuffling target vectors collapses regression to $R^2 \approx -0.22$ consistently across all 20 pairings, ruling out exploitation of vector norms, distributional properties, or high-dimensional noise. The domain-specificity of this alignment is examined in Section 5.7.

5.3 Representation Structure: Distributed Encoding

Table 2 reports mean R^2 under Ridge (L_2, $\lambda = 0.1$), Lasso (L_1, $\lambda = 0.0001$), and permutation control, averaged across all 20 pairings.

The L_1 mapper flatlines at $R^2 \approx 0.014$—barely above the permutation baseline and a near-total collapse from the Ridge mapper. Forcing sparsity destroys the mapping entirely, confirming that cross-architecture alignment relies on the full distributed structure of the activation vector and cannot be recovered from any sparse subset of dimensions. This directly validates the use of dense Ridge regression as the appropriate projection estimator.

5.4 Downstream Intervention Efficacy

Figure 1 presents peak correction rate Δ across all 20 model pairings. The intervention is effective without exception, demonstrating that cross-architecture latent steering generalizes across heterogeneous model families, parameter scales, and training methodologies. Correction rates range from 14.0% (Gemma-9B $\rightarrow$ Llama-1B) to 50.0% (Granite-8B $\rightarrow$ Phi-3-Mini), with a mean of 25.2%.

Phi-3-Mini is consistently the most steerable student, receiving the highest correction rate from

Role	Model	Parameters	Type
Teacher	`meta-llama/Meta-Llama-3-70B-Instruct`	70B	Dense
Teacher	`meta-llama/Meta-Llama-3-8B-Instruct`	8B	Dense
Teacher	`mistralai/Mistral-7B-Instruct-v0.3`	7B	MoE
Teacher	`google/gemma-2-9b-it`	9B	Dense
Teacher	`ibm-granite/granite-8b-code-instruct`	8B	Code-specialized
Student	`meta-llama/Llama-3.2-1B-Instruct`	1B	Dense
Student	`Qwen/Qwen2.5-1.5B-Instruct`	1.5B	Dense
Student	`google/gemma-2-2b-it`	2B	Dense
Student	`microsoft/Phi-3-mini-4k-instruct`	3.8B	Synthetic

Table 1: Teacher and student models comprising the experimental matrix. The Llama-70B teacher was loaded in 4-bit NF4 quantization due to hardware constraints.

Mapping Condition	Regularization	Mean R^2
Ridge Regression	L_2 (distributed)	0.499
Lasso Regression	L_1 (sparse)	0.014
Permutation Control	L_2 (shuffled)	-0.220

Table 2: Projection performance under different regularization constraints, averaged across all 20 model pairings.

Figure 1: Peak intervention correction rate (Δ) across the full 5×4 teacher-student matrix. Each cell reports the maximum Δ over all layer combinations and α values.

four of five teachers. We attribute this to its synthetic training corpus: curated, structured training data may produce more geometrically regular internal representations amenable to external redirection. The Llama-70B teacher consistently underperforms Llama-8B despite its larger parameter count, a result of two compounding factors: the dimensional reduction from $d_T = 8192$ to $d_S \leq 2048$ introduces lossy compression, and 4-bit quantization injects rounding noise into extracted activation vectors, degrading projection precision.

Geometric Alignment Does Not Predict Behavioral Correction. The near-zero correlation ($r = -0.071$) between R^2 and

Δ reveals a fundamental dissociation: directional accuracy matters more than variance explained. A projection pointing in the right direction outperforms a high-R^2 projection that fits the full distributional structure of the target space.

5.5 Architectural Sensitivity: Alpha and Layer Analysis

Intervention Coefficient. Figure 2 plots mean correction rate vs. α per student architecture. Rather than a universal optimum, the four architectures exhibit markedly distinct sensitivity profiles.

Figure 2: Mean Δ as a function of α per student architecture, averaged across all teachers and layer combinations. The dashed line marks $\alpha = 1$. Phi-3-Mini exhibits a sharp peak at $\alpha = 0.25$ with immediate collapse; Llama-1B maintains a flat response across the sweep.

Phi-3-Mini peaks sharply at $\alpha = 0.25$ (mean $\Delta = 26.5\%$) before collapsing below 10% for all $\alpha \geq 0.8$, indicating high sensitivity to representational displacement—a gentle directional nudge suffices while stronger interventions destabilize generation. Llama-1B exhibits the flattest profile, tolerating a broad injection range, suggesting greater representational inertia. Across all architectures,

optimal performance occurs within the interpolation regime ($\alpha \leq 1$) in 80.6% of configurations (median optimal $\alpha = 0.5$). Extrapolative coefficients account for the remaining 19.4%, concentrated in Llama-1B. A consistent dip at $\alpha \in \{0.8, 1.0\}$ across multiple architectures suggests full replacement of the student's residual state is frequently counterproductive; partial blending outperforms complete substitution for most models.

Layer Selection. Figure 3 presents the layer interaction heatmap for Granite-8B → Phi-3-Mini.

Figure 4: Peak intervention correction rate (Δ) on GSM8K across the full 5×4 teacher-student matrix. Correction rates range from 8.5% to 43.3% with a mean of 25.5%, virtually identical to the TruthfulQA mean of 25.2%.

Figure 3: Peak Δ across 16 $l_T \times l_S$ combinations for Granite-8B → Phi-3-Mini. Performance increases monotonically with teacher extraction depth; student injection depth shows a weaker, less consistent effect.

Correction rates increase monotonically as l_T increases from 0.25 to 0.90, consistent with the semantic handoff hypothesis: deeper teacher layers yield more fully resolved conceptual representations. Student injection depth shows a weaker pattern; peak cells at $l_T = 0.90$ are achieved at both $l_S = 0.75$ and $l_S = 0.90$. This asymmetry establishes deep teacher extraction as a more reliable design principle than any specific student injection target.

5.6 Generalization to Mathematical Reasoning

To assess whether cross-architecture steering generalizes beyond verbal reasoning, we replicate the full intervention sweep on GSM8K, evaluating all 20 model pairings across the identical grid of layer combinations and α values. Figure 4 presents peak correction rates across the model matrix.

The method generalizes completely: correction rates range from 8.5% to 43.3% with a mean of 25.5%, statistically indistinguishable from the TruthfulQA mean of 25.2%. This replication across a fundamentally different cognitive domain — multi-step arithmetic versus short-form factual recall — establishes cross-architecture latent steering as a general-purpose correction mechanism rather than a benchmark-specific artifact.

Two structural patterns distinguish the GSM8K results from TruthfulQA. First, student steerability rankings invert completely across domains. Phi-3-Mini, the most steerable student on TruthfulQA (peak $\Delta = 50.0\%$), becomes the least steerable on GSM8K (peak $\Delta = 23.7\%$). Conversely, Llama-1B, the hardest student to steer verbally (peak $\Delta = 16.7\%$), becomes one of the most steerable mathematically (peak $\Delta = 40.5\%$). This complete rank reversal demonstrates that steerability is not an intrinsic architectural property but a domain-specific one, reflecting the geometric organization of each model's reasoning subspaces rather than its overall representational plasticity.

Second, the optimal α collapses entirely to the sub-interpolation regime on GSM8K: $\alpha = 0.25$ is optimal in 99.4% of configurations, and mean correction rate hits 0.0% for all $\alpha \geq 0.8$. Mathematical representations are substantially more fragile than verbal ones — a gentle directional nudge suffices, while any stronger intervention destroys generation entirely. This asymmetry suggests that mathematical reasoning subspaces are more narrowly organized, with less tolerance for representational displacement before coherent output collapses.

	TQA	TQA→GSM	GSM	GSM→TQA
Mean R^2	0.343	−3.831	0.256	−1.729
Min R^2	0.278	−8.170	0.176	−3.227
Max R^2	0.446	−1.807	0.351	−1.081

Table 3: Double dissociation across all 20 pairings. In-domain columns show held-out R^2; transfer columns show cross-domain R^2. Both directions collapse catastrophically. Confirmed 20/20.

5.7 Domain Modularity: A Universal Double Dissociation

We now ask whether learned geometry transfers across domains. For each of the 20 model pairings at $l_T = l_S = 0.75$, we train a projection on 200 in-domain questions and evaluate it on 100 held-out questions from the opposite domain, in both directions.

The results constitute a universal double dissociation confirmed without exception across all 20 pairings. The TruthfulQA-trained mapper collapses to a mean $R^2 = −3.831$ on GSM8K; the GSM8K-trained mapper collapses to mean $R^2 = −1.729$ on TruthfulQA. Both transferred projections perform catastrophically worse than predicting the target mean ($R^2 = 0$), indicating active geometric interference rather than mere uninformativeness. The worst single cell reaches $R^2 = −8.170$ (Granite-8B → Qwen-1.5B, TQA-trained mapper applied to GSM8K), meaning the projection orients student activations in a direction nearly maximally opposed to correct mathematical representations.

Notably, Qwen-1.5B consistently shows the most extreme dissociation in both directions (TQA→GSM range: −7.867 to −8.170; GSM→TQA range: −2.908 to −3.227), approximately twice the interference magnitude of other students, suggesting its reasoning subspaces are more modularly organized with sharper geometric boundaries between domains.

To verify that this universal finding is not specific to the fixed layer combination used in the 20-pair sweep, we conduct a complementary experiment sweeping all 16 layer depth combinations for the Mistral-7B → Qwen-1.5B pair, evaluating dissociation at every $l_T \times l_S$ intersection. The dissociation is confirmed in all 16/16 combinations (Appendix H), ruling out the possibility that orthogonality is a depth-specific artifact. The magnitude of interference varies systematically with injection depth: mid-network injection ($l_S \approx 0.50$) produces the most catastrophic transfer collapse (TQA→GSM mean $R^2 = −11.5$), while late injection ($l_S \approx 0.90$) produces the weakest interference (TQA→GSM mean $R^2 = −3.1$). This gradient confirms that mid-network layers are the primary site of domain-specific semantic construction — mismatched representations injected there corrupt the entire downstream computation, while late injection gives the network less time to propagate the interference before output.

These results establish domain orthogonality as a universal geometric law: a projection matrix must be trained on data representative of the target reasoning domain.

6 Conclusion

We have presented a framework for cross-architecture inference-time steering via learned linear projection of latent representations. A single affine transformation suffices to translate activation vectors between heterogeneous architectures, and injecting translated representations into a student model's residual stream produces reliable behavioral corrections without weight updates, shared architecture, or access to training data.

The method generalizes across reasoning domains, achieving mean correction rates of 25.2% on TruthfulQA and 25.5% on GSM8K across 20 heterogeneous pairings. Four findings sharpen the picture: geometric fidelity does not predict behavioral correction ($r \approx −0.07$); optimal intervention strength inverts across domains; deep teacher extraction ($l_T \approx 0.90$) is a more reliable design principle than any specific student injection target; and mathematical representations tolerate substantially less representational displacement than verbal ones.

Finally, the double dissociation between verbal and mathematical domains, confirmed across all 20 model pairings without exception and across all 16 layer combinations for the pilot pair, establishes domain-specific subspace geometry as a universal geometric law rather than an artifact of any particular architecture. A projection matrix must be trained on data representative of the target reasoning domain, and the geometric structure of one reasoning type cannot be repurposed for another.

Limitations

Benchmark Scope. Behavioral intervention results are reported on TruthfulQA and GSM8K, covering short-form verbal factual recall and arithmetic word problems respectively. How correction rates generalize to multi-step inference, longer generation contexts, or other reasoning types such as commonsense or causal reasoning has not been established.

Sparse Layer Grid. Layer selection is evaluated at only four relative depth positions, leaving behavior between grid points uncharacterized. Finer-grained sweeps may reveal non-monotonic dynamics or narrow optimal windows the current resolution cannot detect.

Quantization Noise. The Llama-70B teacher was loaded in 4-bit NF4 quantization due to hardware constraints, introducing rounding noise into extracted activations. The 70B results represent a lower bound on full-precision performance rather than a representative evaluation of large-scale teacher utility.

Dissociation Layer Generalization. The full layer sweep confirming dissociation across all 16 depth combinations is conducted on a single model pair (Mistral-7B $\rightarrow$ Qwen-1.5B). Whether the systematic variation in interference magnitude with injection depth generalizes across other architecture combinations remains unverified, though the binary dissociation result itself is confirmed across all 20 pairs at a representative layer combination.

Open-Weight Models Only. Whether affine compatibility holds for proprietary closed-weight architectures or models trained on substantially different data distributions remains untested.

Evaluation Metric Ceiling. Deterministic substring matching counts interventions that redirect reasoning but produce lexically distinct correct answers as failures. Reported Δ values are conservative lower bounds on true behavioral impact.

Ethical Considerations

This work investigates the geometric structure of latent representations in large language models and demonstrates a method for correcting model outputs at inference time via cross-architecture activation steering.

We identify two areas warranting ethical consideration. First, the intervention mechanism demonstrated here—which modifies a model's internal reasoning trajectory without any weight update or user-visible indication—could in principle be applied to steer model outputs in undesirable directions as readily as beneficial ones. We emphasize that all experiments in this work are directed at *correcting* factually incorrect outputs toward ground-truth answers, and that the method requires explicit access to the target model's internal activations, limiting its applicability outside controlled research settings. Second, all models used in this work are publicly available open-weight models. No proprietary systems, private data, or human subjects were involved in any experiment. TruthfulQA and GSM8K are publicly available benchmarks with no sensitive personal information.

We believe the primary contribution of this work—characterizing the geometric structure of shared latent representations and their domain specificity—is a positive contribution to the interpretability and transparency of large language models.

Reproducibility Statement

We have made substantial efforts to ensure the reproducibility of all results reported in this paper. All experiments use publicly available open-weight models accessible via HuggingFace, and all benchmarks (TruthfulQA, GSM8K) are publicly available datasets. Exact model identifiers, quantization configurations, random seeds, train/test split ratios, regularization hyperparameters, and generation settings are specified in Section 4 and Appendix I. The intervention hook implementation, projection matrix estimation procedure, and evaluation logic are described in full in Appendix I. The layer dissociation experiment parameters—sample sizes, layer combinations, and Ridge regression configuration—are specified in Section 5.7 and Appendix H. All results are deterministic: generation uses greedy decoding (`do_sample=False`) throughout, and all random operations use `random_state=42`. Complete experimental code will be released as anonymous supplementary material with the

submission.

References

Yamini Bansal, Preetum Nakkiran, and Boaz Barak. 2021. Revisiting model stitching to compare neural representations. In *Proceedings of the 35th International Conference on Neural Information Processing Systems*, NIPS '21, Red Hook, NY, USA. Curran Associates Inc.

Yonatan Belinkov. 2022. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Adrián Csiszárik, Péter Kőrösi-Szabó, Ákos K. Matszangosz, Gergely Papp, and Dániel Varga. 2021. Similarity and matching of neural network representations. In *Proceedings of the 35th International Conference on Neural Information Processing Systems*, NIPS '21, Red Hook, NY, USA. Curran Associates Inc.

Alexander Yom Din, Taelin Karidi, Leshem Choshen, and Mor Geva. 2024. Jump to conclusions: Short-cutting transformers with linear transformations. *Preprint*, arXiv:2303.09435.

Nelson Elhage, Tristan Hume, Catherine Olsson, Neel Nanda, Tom Henighan, Scott Johnston, Sheer ElShowk, Nicholas Joseph, Nova DasSarma, Ben Mann, Danny Hernandez, Amanda Askell, Kamal Ndousse, Andy Jones, Dawn Drain, Anna Chen, Yuntao Bai, Deep Ganguli, Liane Lovitt, and 14 others. 2022. Softmax linear units. *Transformer Circuits Thread*. Https://transformer-circuits.pub/2022/solu/index.html.

Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, and 6 others. 2021. A mathematical framework for transformer circuits. *Transformer Circuits Thread*. Https://transformer-circuits.pub/2021/framework/index.html.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. Truthfulqa: Measuring how models mimic human falsehoods. pages 3214–3252.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Distributed representations of words and phrases and their compositionality. In *Proceedings of the 27th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'13, page 3111–3119, Red Hook, NY, USA. Curran Associates Inc.

Neel Nanda, Andrew Lee, and Martin Wattenberg. 2023. Emergent linear representations in world models of self-supervised sequence models. *Preprint*, arXiv:2309.00941.

nostalgebraist. 2020. Interpreting GPT: the logit lens. LessWrong. Accessed: 2026-03-11.

Nina Panickssery, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner. 2024. Steering llama 2 via contrastive activation addition. *Preprint*, arXiv:2312.06681.

Alessandro Stolfo, Vidhisha Balachandran, Safoora Yousefi, Eric Horvitz, and Besmira Nushi. 2025. Improving instruction-following in language models through activation steering. *Preprint*, arXiv:2410.12877.

Nishant Subramani, Nivedita Suresh, and Matthew E. Peters. 2022. Extracting latent steering vectors from pretrained language models. *Preprint*, arXiv:2205.05124.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. 2019. Bert rediscovers the classical nlp pipeline. In *Association for Computational Linguistics*.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. 2024. Steering language models with activation engineering. *Preprint*, arXiv:2308.10248.

Weixuan Wang, Minghao Wu, Barry Haddow, and Alexandra Birch. 2025. Expertsteer: Intervening in llms through expert knowledge. *Preprint*, arXiv:2505.12313.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *Preprint*, arXiv:2307.15043.

A Full Geometric Alignment Results

Table 5 reports the peak R^2 achieved by the Ridge projection for each of the 20 teacher-student pairings, maximized over all 16 layer depth combinations. Values are consistently in the range $[0.62, 0.68]$ across the five teachers, with the notable exception of Gemma-9B pairings which cluster slightly lower at $[0.62, 0.64]$. The absence of any pairing with $R^2 < 0.60$ confirms that affine compatibility holds broadly across the experimental matrix and is not dependent on architectural similarity between teacher and student.

Figure 5: Peak R^2 (Ridge regression) for each of the 20 teacher-student pairings, maximized over all 16 layer combinations. The Llama-8B $\rightarrow$ Llama-1B intra-family pairing achieves the highest alignment ($R^2 = 0.684$). All pairings exceed $R^2 = 0.62$, confirming broad affine compatibility across the experimental matrix.

B Extended Layer Interaction Heatmaps

Figure 6 presents layer interaction heatmaps for the six model pairings with the highest within-pair variance in correction rate across layer combinations (standard deviation $> 5\%$). These pairings were selected because their heatmaps are most informative: the layer choice meaningfully affects outcome, and the gradient patterns visible in each provide evidence about the generalizability of the semantic handoff hypothesis discussed in Section 3.3.

Figure 6: Peak correction rate Δ across all 16 $l_T \times l_S$ combinations for the six highest-variance model pairings. Rows are ordered with deepest teacher extraction at the top. The monotonic improvement with teacher extraction depth observed in the main paper (Figure 3) generalizes across these pairings, while student injection depth consistently shows a weaker and less structured effect. The Granite-8B $\rightarrow$ Gemma-2B pairing shows the highest within-pair variance ($\sigma = 6.7\%$), with a pronounced performance gradient that makes layer selection particularly consequential for this pairing.

C Per-Teacher Alpha Sensitivity Profiles

Figure 7 decomposes the alpha sensitivity curves from Figure 2 by teacher architecture, plotting mean correction rate vs. α for each student separately within each teacher panel. This view addresses a question the main paper leaves open: whether the characteristic sensitivity profiles of each student are consistent across teachers, or whether the teacher architecture modulates them.

Figure 7: Mean correction rate Δ vs. α broken down by teacher architecture, with one line per student. The dashed vertical line marks $\alpha = 1$. Student sensitivity profiles are highly consistent across teachers: Phi-3-Mini peaks at $\alpha = 0.25$ and collapses immediately regardless of teacher, while Qwen-1.5B consistently prefers $\alpha = 0.5$. The Mistral-7B panel is the notable exception, where Gemma-2B achieves its best performance at $\alpha = 2.0$ rather than the sub-interpolation values preferred across other teachers, suggesting a specific compatibility between Mistral's MoE representations and Gemma-2B's residual stream that benefits from stronger intervention.

D Full Double Dissociation Results

Table 4 reports all four R^2 values for each of the 20 teacher-student pairings in the domain dissociation experiment. In-domain values reflect proper held-out evaluation on 100 test questions. Transfer values confirm catastrophic collapse in both directions for every pairing without exception.

E GSM8K Alpha Sensitivity Profiles

Figure 8 plots mean correction rate vs. α for each student architecture on GSM8K. The contrast with the TruthfulQA profiles (Figure 2) is stark: all four architectures collapse to near-zero correction rate for $\alpha \geq 0.8$, with no recovery at higher extrapolation values. This uniform collapse across architectures indicates that mathematical representations are substantially more fragile than verbal ones, tolerating only the most conservative interventions before coherent generation fails entirely.

Teacher	Student	TQA	TQA→GSM	GSM	GSM→TQA
Llama-70B	Llama-1B	0.354	−2.748	0.198	−1.108
Llama-70B	Qwen-1.5B	0.368	−8.133	0.222	−3.005
Llama-70B	Gemma-2B	0.290	−2.838	0.296	−1.261
Llama-70B	Phi-3-Mini	0.285	−1.807	0.300	−1.567
Llama-8B	Llama-1B	0.389	−2.389	0.230	−1.101
Llama-8B	Qwen-1.5B	0.372	−7.867	0.226	−3.037
Llama-8B	Gemma-2B	0.290	−2.798	0.303	−1.182
Llama-8B	Phi-3-Mini	0.296	−1.834	0.254	−1.529
Mistral-7B	Llama-1B	0.377	−2.439	0.244	−1.081
Mistral-7B	Qwen-1.5B	0.405	−8.078	0.176	−3.227
Mistral-7B	Gemma-2B	0.312	−2.714	0.297	−1.178
Mistral-7B	Phi-3-Mini	0.291	−1.827	0.220	−1.670
Gemma-9B	Llama-1B	0.353	−2.748	0.190	−1.176
Gemma-9B	Qwen-1.5B	0.398	−8.019	0.226	−2.908
Gemma-9B	Gemma-2B	0.361	−2.513	0.326	−1.115
Gemma-9B	Phi-3-Mini	0.303	−1.870	0.301	−1.527
Granite-8B	Llama-1B	0.417	−2.845	0.195	−1.191
Granite-8B	Qwen-1.5B	0.446	−8.170	0.275	−2.922
Granite-8B	Gemma-2B	0.281	−3.060	0.289	−1.313
Granite-8B	Phi-3-Mini	0.278	−1.930	0.351	−1.489
Mean		0.343	−3.831	0.256	−1.729

Table 4: Full double dissociation results for all 20 pairings. TQA and GSM columns show held-out in-domain R^2. TQA→GSM and GSM→TQA show transfer R^2. Dissociation confirmed in all 20 pairs.

Figure 8: Mean correction rate Δ vs. α on GSM8K per student architecture, averaged across all teachers and layer combinations. All architectures collapse to near-zero for $\alpha \geq 0.8$, in sharp contrast to TruthfulQA profiles where partial recovery occurs at higher α values. The dashed line marks $\alpha = 1$.

the fragility of mathematical representations under representational displacement is a domain-level property rather than an architecture-level one.

Figure 9: Alpha sensitivity profiles for TruthfulQA (left) and GSM8K (right), one line per student architecture averaged across all teachers and layer combinations. The dashed vertical line marks $\alpha = 1$. TruthfulQA profiles are architecturally heterogeneous with partial recovery at higher α; GSM8K profiles converge uniformly on $\alpha = 0.25$ with complete collapse beyond $\alpha = 0.5$ across all architectures.

F Alpha Sensitivity: TruthfulQA vs. GSM8K

Figure 9 presents TruthfulQA and GSM8K alpha sensitivity profiles side by side, making the domain contrast directly legible. On TruthfulQA, student architectures exhibit distinct and heterogeneous profiles with partial recovery at moderate extrapolation values. On GSM8K, all four architectures converge on a single behavioral pattern: peak performance at $\alpha = 0.25$ followed by uniform collapse. The architectural heterogeneity visible on the left panel disappears entirely on the right, suggesting that

G GSM8K Layer Interaction Heatmap

Figure 10 presents the layer interaction heatmap for Gemma-9B → Qwen-1.5B, the highest-performing pairing on GSM8K (peak $\Delta = 43.3\%$). Compared to the TruthfulQA counterpart (Figure 3), the monotonic improvement with teacher depth is less pronounced, and lower teacher extraction depths perform more competitively. This suggests that mathematical reasoning representations reach a usable state of resolution at shallower teacher layers than verbal reasoning representations,

consistent with the simpler syntactic structure of arithmetic problems relative to open-domain factual questions.

Layer Interaction: Gemma-9B → Qwen-1.5B (GSM8K)

Figure 10: Peak correction rate Δ across all 16 $l_T \times l_S$ combinations for Gemma-9B → Qwen-1.5B on GSM8K. Rows are ordered with deepest teacher extraction at the top. The gradient with teacher depth is less monotonic than the TruthfulQA counterpart, with lower-depth teacher extraction performing more competitively.

H Layer Dissociation: Full Depth Sweep

Figure 11 presents transfer R^2 values across all 16 teacher extraction depth × student injection depth combinations for the Mistral-7B → Qwen-1.5B pair. Color intensity reflects the absolute magnitude of transfer interference — darker cells indicate more catastrophic geometric mismatch. Dissociation is confirmed in all 16/16 combinations in both transfer directions, establishing that domain orthogonality is not a depth-specific artifact.

A systematic pattern is visible across both panels: student injection depth (l_S) modulates interference magnitude more strongly than teacher extraction depth (l_T). Mid-network injection ($l_S = 0.50$) consistently produces the strongest interference (TQA→GSM range: -11.0 to -11.9), while late injection ($l_S = 0.90$) produces the weakest (range: -2.9 to -3.3). Teacher extraction depth has a comparatively weaker and less consistent effect. This asymmetry implicates the mid-network student layers as the primary site of domain-specific semantic construction, consistent with the hierarchical processing account in Section 3.3.

Figure 11: Transfer R^2 across all 16 $l_T \times l_S$ combinations for Mistral-7B → Qwen-1.5B. Left panel: TruthfulQA-trained mapper evaluated on GSM8K. Right panel: GSM8K-trained mapper evaluated on TruthfulQA. Color intensity reflects absolute interference magnitude; all values are negative. Mid-network injection ($l_S = 0.50$) produces the strongest interference in both directions; late injection ($l_S = 0.90$) produces the weakest. Dissociation confirmed 16/16.

I Implementation and Reproducibility Details

Hardware. All experiments were conducted on a single NVIDIA A100 80GB GPU. Teacher and student models were loaded sequentially to manage GPU memory: the teacher was loaded, all activation vectors were extracted and cached to CPU, and the teacher was then unloaded before the student was loaded. The Llama-70B teacher was the only model requiring quantization, loaded in 4-bit NF4 format using `BitsAndBytesConfig` with `bnb_4bit_compute_dtype= torch.float16` and `bnb_4bit_use_double_quant=True`. All other models were loaded in `bfloat16` precision.

Inference Configuration. All forward passes used left-padded tokenization (`padding_side='left'`) with `pad_token` set to `eos_token` where no dedicated pad token existed. Activation vectors were extracted as the final-token hidden state at each candidate layer using `output_hidden_states=True`. Batch size was 32 for all extraction and intervention passes. Generation used greedy decoding (`do_sample=False`, `max_new_tokens=50` for TruthfulQA, `max_new_tokens=100` for GSM8K).

Intervention Hook. The residual stream intervention was implemented as a PyTorch forward hook registered on `model.model.layers[layer_idx]`. The hook intercepts the layer output, extracts

the final token position, rescales the pre-computed projected vector to match the current residual stream norm, applies the weighted combination from Equation 8, and returns the modified hidden state. The hook is registered immediately before each batched generation call and removed immediately after, ensuring no cross-contamination between intervention and baseline passes.

Projection Matrix Estimation. Ridge and Lasso regressors were implemented using scikit-learn's `Ridge(alpha=0.1)` and `Lasso(alpha=0.0001, max_iter=5000)` with default `fit_intercept=True`. The 70/30 train/test split used `sklearn.model_selection.train_test_split` with `random_state=42`. Permutation controls used `numpy.random.permutation` on the training split target matrix prior to fitting, with the same fixed seed.

Evaluation. Generated text was decoded with `skip_special_tokens=True`, split on the `"Answer:"` delimiter to isolate the model's response, and lowercased and stripped before substring matching. Both the `best_answer` and all entries in `correct_answers` were lowercased prior to matching. A response was counted as correct if any reference string appeared as a substring of the generated text.