MGSM-Pro: A Simple Strategy for Robust Multilingual Mathematical Reasoning Evaluation

Abstract

Large language models have made substantial progress in mathematical reasoning. However, benchmark development for multilingual evaluation has lagged behind English in both difficulty and recency. Recently, GSM-Symbolic (Mirzadeh et al., 2025) showed a strong evidence of high variance when models are evaluated on different instantiations of the same question; however, the evaluation was conducted only in English. In this paper, we introduce MGSM-Pro, an extension of MGSM dataset with GSM-Symbolic approach. Our dataset provides five instantiations per MGSM question by varying names, digits and irrelevant context. Evaluations across nine languages reveal that many low-resource languages suffer large performance drops when tested on digit instantiations different from those in the original test set. We further find that models robustness in HRL setting do not necessarily translate to LRL. Moreover, proprietary models, such as Gemini 2.5 Flash and GPT-4.1 are less robust to digit, whereas Gemini 3.0 Pro is more robust. Among open models, GPT-OSS 120B and DeepSeek v3 show stronger robustness. Based on these findings, we recommend evaluating each problem using at least five digit-varying instantiations to obtain a more robust and realistic assessment of math reasoning.

1 Introduction

Large language models (LLMs) have drastically improved in capability in recent years, particularly on challenging knowledge-intensive and reasoning tasks, with open models closing the gap as evidenced by public benchmarks (Liu et al., 2024; Yang et al., 2025; Gemma-Team et al., 2025). However, progress in developing benchmarks for multilingual settings, particularly for mathematical reasoning, has lagged behind English in both difficulty and recency, [1] making existing multilingual

---

[1]E.g. AIME https://artofproblemsolving.com/wiki/index.php/AIME_Problems_and_Solutions

benchmarks easily saturated and potentially prone to memorization or being over-optimized (Shi et al., 2022b; Chen et al., 2024).

One way to address this issue is to create new benchmarks that are more recent such as MMath (Luo et al., 2025) and PolyMath (Wang et al., 2025) often translated from existing English benchmarks, but without modification of the numbers and context. However, it remains unclear whether LLMs evaluated on these benchmarks generalize to other similar problems. Prior evidence in English shows that LLMs exhibit high variance when presented with different instantiations of the same question (known as GSM-Symbolic) (Mirzadeh et al., 2025). We carefully extend this finding to the multilingual setting.

In this paper, we introduce `MGSM-Pro`, a multilingual extension of `GSM-Symbolic` based on the MGSM dataset (Shi et al., 2022a) in two steps: (1) *template construction* in English that allows easy replacement of names and digits (2) *dataset construction* that translates the template to multiple languages (with an LLM), followed by human verification—this helps to generate different instantiations of same question (e.g. 5 instances).

Our results reveal a more precarious setting than GSM-Symbolic: low-resource languages (LRLs) experience a sharp performance drop when accuracy is averaged over five instances instead of a single example, unlike high-resource languages (HRLs). As shown in Figure 1, Gemini 3.0 Pro and Gemini 3.5 Flash are more robust to this degradation, whereas smaller-sized open models like Gemma 3 4B and older LLMs (regardless of size) such as Llama 3 70B struggle to maintain accuracy relative to the original dataset. When languages are grouped by resource-level (i.e. HRL vs. LRLs), LRLs suffer the most in terms of huge drop in performance and in some cases losing more than -20.0 drop in performance. Finally, we show that leaderboard rankings can undergo substantial

Figure 1: Relative decrease in accuracy from the original dataset to five instances of changing both names and numbers and adding irrelevant context, averaged over all nine languages.

changes when results are averaged over at least five instances, with Gemini 2.5 Flash, for example, falling from 3rd to 7th place.

Based on our findings on nine typologically diverse languages, **we recommend that math reasoning evaluation should be performed on a minimum of five instances** of the same problem by modifying digits.[2] We are *releasing the new dataset* (`MGSM-Pro`) with more instances to encourage a more robust evaluation. Similar to how we expect a good student that understands a sample problem to be able to solve various instances with modified digits. We expect both open LLMs and proprietary LLMs to be robust to these small changes. The dataset will be released on HuggingFace on paper acceptance.

2 Related Work

Math Reasoning Benchmarks With the increase of interest in evaluating a model's logical reasoning capabilities, multiple English math benchmarks have been introduced (Cobbe et al., 2021; Hendrycks et al., 2021b; Mishra et al., 2022; Patel et al., 2021; Miao et al., 2020). Extending the investigation into the multilingual setting, (Shi et al., 2022a; Adelani et al., 2025) notices weaker model performances under low-resource language setting. However, it is unclear if success on these benchmarks translates to effectiveness on related prob-

lems or memorization of test set.

Robustness in Reasoning True logical reasoning requires robustness to minor variations and noise. Several English datasets highlight significant accuracy drops in such scenarios (Shi et al., 2023; Abedin et al., 2025; Mirzadeh et al., 2025). However, their investigations remain limited to English. Our work introduces `MGSM-Pro`, a new dataset that expands these investigations to multilingual setting.

Re-purposing existing benchmarks Scaling labeled datasets across many languages remains challenging due to annotation costs and the difficulty of constructing sufficiently challenging benchmarks. Recent work has explored re-purposing existing datasets to increase both their complexity and coverage. For instance, SIB-200 (Adelani et al., 2024) and Belebele (Bandarkar et al., 2024) extend the FLORES-200 benchmark by introducing additional labels or multiple-choice formulations, enabling evaluation across a broader set of languages. Similarly, MMLU-Pro (Wang et al., 2024) increases task difficulty of MMLU (Hendrycks et al., 2021a) by expanding the number of answer choices from four to eight, while MMLU-ProX (Xuan et al., 2025) further extends this framework to additional languages. GlobalMMLU augments MMLU with annotations that distinguish between questions requiring Western cultural knowledge and those that do not. Collectively, these efforts enable more rigorous and scalable evaluation of large language models across diverse languages and tasks. Building on this line of work, we introduce `MGSM-Pro`,

---

[2]i.e. evaluating on 1250 instances of MGSM rather than the original 250 for a more robust evaluation

Figure 2: MGSM-Pro creation diagram, illustrating both template creation and multilingual data construction steps on a sample language.

which expands the original MGSM dataset fivefold (248 to 1,240 questions) by systematically generating new instances through controlled digit substitutions. This approach enables a more robust and fine-grained evaluation of multilingual mathematical reasoning.

3 MGSM-Pro: Creation Process

We introduce, `MGSM-Pro`—a multilingual extension of `GSM-Symbolic` based on the MGSM dataset (Shi et al., 2022a) to nine languages with various resource levels as defined by Joshi et al. (2020). This includes high-resource languages or HRLs (**English**, **Chinese**, **French**, and **Japanese**; Class 5) and low-resource languages or LRLs (**Swahili**, **Amharic**, **Igbo**, **Yoruba**, and **Twi**; Classes 1–2). We also cover six dataset variants per language. These variations are organized into two series: Symbolic (SYM) and Irrelevant Context (IC). Each series consists of three distinct variations.

The Symbolic Series (`SYM`) involves systematic modifications to a problem's surface features without altering its logical structure. This series includes three variants:

- **`SYM_N`**, which replaces *names* with culturally relevant ones;

- **`SYM_#`**, which changes *numerical* data; and

- **`SYM_N#`**, which varies *both names and numbers* simultaneously.

The Irrelevant Context Series (`IC`) mirrors the modifications in the `SYM` series but introduces a distinct layer of difficulty as it inserts an *irrelevant sentence* to the problem. The resulting variants are denoted as `IC_N`, `IC_#`, and `IC_N#`.

In this section, we introduce the methodology for constructing MGSM-Pro with two steps: template construction (§3.1) and dataset construction (§3.2). Figure 2 shows an example of the data generation workflow in which names and digits are first identified and replaced with multiple instances.

3.1 Template Construction

The foundation of our dataset lies in the creation of adaptable templates. We adopt the GSM-Symbolic framework to generate symbolic templates for 248 out of 250 English MGSM questions.[3] To simplify cross-lingual transfer, we restrict parametrization strictly to names and numbers (i.e. SYM). Each template includes a symbolic equation alongside variable constraints to ensure that generated combinations yield correct, logical answers. Once the English template is crafted, we employ Gemini 2.0 Flash to generate multilingual templates. These translations then undergo a rigorous verification process: they are first reviewed by native speakers, followed by automated alignment checks against the English source. Any template failing these checks is subjected to a second round of human

---

[3]The remaining two were excluded because the questions do not have digits, so, difficult to use of template approach that focuses on digit replacement.

Language	Gemini 2.5 Flash				Gemini 3.0 Pro				Claude 4 Sonnet				GPT-4.1				GPT-5				Δ Ave.	Δ Med.
	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	–	–
English	96.8	94.6	83.1	81.0	98.0	96.2	94.4	93.2	98.0	96.0	91.5	90.4	96.4	91.7	81.5	79.6	96.8	93.3	92.8	88.0	−10.7	−8.8
Chinese	89.9	89.0	78.0	79.0	93.5	93.1	93.2	93.5	93.1	91.9	88.7	88.5	89.9	90.6	78.6	76.8	92.3	91.9	89.3	88.4	−6.5	−4.7
French	91.5	87.1	77.5	73.8	90.7	89.7	88.6	87.2	91.5	90.4	86.4	85.3	88.7	85.5	75.9	74.5	89.9	88.4	85.4	84.2	−9.5	−6.2
Japanese	86.7	83.9	74.9	73.1	90.7	89.4	87.6	88.0	89.9	84.8	83.1	81.5	87.1	83.6	74.8	74.1	90.7	84.1	83.6	82.6	−9.2	−8.5
Swahili	91.5	89.9	80.3	78.7	97.6	93.9	93.0	92.4	91.9	90.9	85.1	84.4	91.5	89.0	79.8	77.5	90.7	92.4	87.7	89.3	−8.2	−7.5
Amharic	81.9	81.9	71.0	70.2	87.5	85.4	83.2	83.0	82.3	81.5	74.5	73.1	68.1	68.2	53.0	51.2	71.8	74.0	67.6	70.1	−8.8	−9.2
Igbo	81.5	79.7	68.6	66.6	89.9	87.5	82.1	81.2	78.2	76.7	68.1	66.0	79.0	71.3	58.5	54.0	79.8	74.5	70.2	66.7	−14.8	−13.1
Yoruba	83.9	79.4	69.7	68.1	86.3	85.7	83.1	80.9	77.4	73.7	67.9	66.0	72.6	69.6	59.8	55.6	74.6	73.5	67.7	68.9	−11.2	−11.4
Twi	65.3	61.9	51.5	49.6	77.8	74.9	70.6	69.1	52.8	46.0	43.2	36.2	41.9	36.9	31.5	28.4	46.8	43.1	38.5	37.9	−12.7	−13.5
Average	85.4	83.0	72.7	71.1	90.2	88.4	86.2	85.4	83.9	81.3	76.5	74.6	79.5	76.3	65.9	63.5	81.5	79.5	75.9	75.0		

Table 1: Different closed models' accuracy across dataset variations (SYM_#, IC_N, IC_#) and original (D_O). Cells are shaded by how far each variant falls below its row's D_O within the same model group; values at or above D_O are left white. We report the Average (Ave.) and Median (Med.) of $\Delta(\texttt{IC\_\#} - D_O)$ taken across the five models.

Language	Gemma 3 27B				Qwen 3 32B				Qwen 3.5 27B				DeepSeek V3				GPT-OSS 120B				Δ Ave.	Δ Med.
	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	D_O	IC_N	SYM_#	IC_#	–	–
English	95.6	93.3	81.6	77.6	89.1	87.3	87.7	86.5	98.4	94.2	93.8	90.7	98.4	94.3	92.7	89.7	96.4	93.9	93.5	92.1	−8.3	−7.7
Chinese	87.9	85.5	75.2	72.3	89.9	88.8	87.8	88.1	89.9	90.1	87.3	83.9	92.3	91.4	89.9	88.1	91.5	90.6	90.2	89.7	−5.9	−4.2
French	89.1	84.5	73.4	69.9	89.5	87.6	86.3	84.0	91.1	87.2	87.2	84.1	90.7	88.7	87.8	85.7	90.7	88.7	86.5	86.5	−8.2	−5.5
Japanese	85.1	79.4	71.1	64.6	88.7	85.2	84.8	83.3	87.5	80.1	76.0	72.1	88.7	83.0	79.8	79.8	89.1	85.2	85.2	83.9	−11.1	−8.9
Swahili	89.1	85.4	72.2	71.2	78.2	71.0	73.6	67.3	91.9	86.5	88.1	84.9	90.7	86.9	86.3	84.0	84.7	82.2	81.5	79.6	−9.5	−7.0
Amharic	71.4	70.2	57.4	55.1	42.7	39.4	37.7	33.6	77.0	76.0	68.1	67.4	76.2	73.5	71.9	66.0	60.9	57.7	58.5	53.7	−10.5	−9.6
Igbo	64.1	54.0	50.0	41.3	19.8	14.9	14.7	10.0	73.8	70.8	69.5	62.9	73.8	67.8	64.6	58.0	77.4	73.3	67.7	64.7	−14.4	−12.7
Yoruba	44.4	40.5	38.2	31.4	26.6	17.3	23.1	14.0	74.6	70.0	69.3	63.2	66.1	58.0	57.1	52.7	76.2	66.9	66.1	61.3	−13.0	−13.0
Twi	18.1	10.4	13.4	9.3	5.6	3.5	4.6	2.2	37.5	27.4	31.3	25.4	48.0	36.9	38.0	28.1	44.8	37.7	39.0	31.5	−11.5	−12.1
Average	71.6	67.0	59.2	54.7	58.9	55.0	55.6	52.1	80.2	76.0	74.5	70.5	80.6	75.9	74.2	70.3	79.1	75.1	74.2	71.4		

Table 2: Different open models' accuracy across dataset variations (SYM_#, IC_N, IC_#) and original (D_O). Cells are shaded by how far each variant falls below its row's D_O within the same model group; values at or above D_O are left white. We report the Average (Ave.) and Median (Med.) of $\Delta(\texttt{IC\_\#} - D_O)$ taken across the five models.

correction. Finally, to enable a controlled increase in difficulty, we build upon GSM-IC's (Mirzadeh et al., 2025) methodology to create irrelevant context templates for every English question. We applied similar rigorous checks as with the SYM questions.

3.2 Dataset Construction

To efficiently generate a large quantity of problem instances that share the same underlying logical structure, we leverage the symbolic equations and restrictions defined during the template phase. This methodology enables the systematic sampling of new numerical values that are guaranteed to be mathematically valid and distinct from those present in the original training data.

A limitation in previous datasets, such as MGSM and AfriMGSM, was the reliance on direct translations, where names were frequently phonetic transliterations of English origin. This approach compromised the problems' local fit and cultural meaning. To ensure deep cultural relevance across all languages in MGSM-Pro, we tasked native annotators with curating a comprehensive repository of entities specific to their locale. This includes categories such as cities, personal names, and common pet names, guaranteeing that the generated problems resonate well with native speakers and accurately represent the target language's culture, for example an annotator suggested using 'Zainabu' as a female name in the Swahili as opposed to 'Carla' which was found in the original Swahili MGSM dataset.

Ranking of model average accuracy across All Languages on original dataset (D_O) alongside High-Resource and Low-Resource performance metrics. Arrows indicate rank changes relative to the previous column.

4 Experimental Setup and Results

4.1 Experiment Setup

Models evaluated We benchmark 18 models in a zero-shot setting across six variations within the SYM and IC series for each language. To ensure robustness, every variation is evaluated five times using different values and we report the mean performance across these iterations. We report the results of **original data** (D_O), IC_N, IC_# and SYM_# in the main paper, and others in Appendix D.1.

Figure 3: Comparison of relative accuracy decrease from HRL and LRL D_o, averaged across six variants of MGSM-Pro.

(a) Gemma 3 Family

(b) GPT-OSS Family

Figure 4: **Relative Accuracy Drop Across Model Families.** The figures illustrate the relative decline in accuracy for (a) the Gemma-3 family and (b) the GPT-OSS family. The drop is measured from the original dataset to two configurations: IC_N# and SYM_N#, averaged over nine languages.

Prompts The prompt is structured to ensure the model adheres to the CoT format while including clear instructions to help numerical result capture. Our prompt suggests reasoning in English since previous works show LLM reason better in English (Tam et al., 2025; Qi et al., 2025). However, we discuss the impact of using native language in the result, with consistent conclusions (§5.1).

> **Evaluation Prompt**
>
> *Explain your reasoning step by step in clear **English** to solve the problem.*
> *Your response should end with the final numerical answer, without including units.*
> *Question: {question}*

4.2 Results

4.2.1 Main results

Table 1 and Table 2 show the results of five closed and five open LLMs respectively. The models include Gemini 2.5 Flash, Gemini 3.0 Pro, Claude 4

Sonnet, GPT-4.1, GPT-5, Gemma 3 27B, Qwen 3 32B, Qwen 3.5 27B, DeepSeek V3, and GPT-OSS 120B. We highlight the main findings below:

LLM performance is less sensitive to name variation Simply changing the names of person or items (i.e. SYM_N setting) does not necessarily hurt performance. [4] However, when irrelevant contexts are added (i.e. IC_N), there is little drop. In general IC_N is more critical for LRLs such as Twi, Igbo or Yoruba than HRLs. Also, we find proprietary models to be more robust to this drop, for example on average Gemini 3.0 Pro accuracy on all languages dropped by -1.8 while open models such as DeepSeek V3 and GPT-OSS 120B dropeed by -4.7 and -4.0 respectively.

Numerical variation leads to huge drop in performance While names variation leads to small drop, changing numbers used in the questions leads to huge drop in performance especially when com-

---

[4] Full result for SYM_N is in Appendix D.1, omitted in main table due to space constraint.

Model	All Language									High-Resource			Low-Resource		
	D_O		Avg-5				Avg-10				Avg-5			Avg-5		
	🏅	%	🏅	↕	%	±	🏅	↕	%	±	🏅	%	±	🏅	%	±
Gemini 3.0 Pro	1	90.2	1	–	84.1	1.5	1	–	84.2	0.9	1	89.6	1.3	1	79.7	1.6
Gemini 3.0 Flash	2	89.2	2	–	82.3	1.5	2	–	82.4	0.8	2	89.5	1.5	2	76.5	1.5
Gemini 2.5 Flash	3	85.4	7	▼	70.1	1.8	7	–	69.6	1.1	12	75.4	1.6	3	65.8	2.0
Claude 4	4	83.9	3	▲	74.2	1.5	3	–	73.9	1.0	4	85.9	1.4	4	64.8	1.6
Gemini 2.0 Flash	5	83.4	9	▼	68.3	2.3	9	–	67.8	1.5	10	76.2	1.8	6	62.0	2.7
GPT-5	6	81.5	4	▲	73.3	2.0	4	–	73.5	1.1	7	84.4	1.8	5	64.5	2.2
DeepSeek V3	7	80.6	5	▲	70.5	1.6	6	▼	70.7	1.1	5	85.6	1.6	8	58.4	1.6
Qwen 3.5 27B	8	80.2	8	–	69.4	1.9	8	–	69.4	1.1	8	81.5	2.0	7	59.8	1.9
GPT 4.1	9	79.5	10	▼	63.2	1.8	10	–	63.1	1.1	11	75.9	1.6	10	53.1	1.9
GPT-OSS 120B	10	79.1	6	▲	70.4	1.7	5	▲	70.8	1.1	3	86.4	1.5	9	57.6	1.9
Gemma 3 27B	11	71.6	11	–	54.6	2.0	11	–	53.9	1.5	13	70.8	2.0	11	41.6	2.0
GPT-OSS 20B	12	67.0	12	–	52.3	1.8	12	–	52.5	1.1	9	78.9	1.5	13	31.1	2.1
Gemma 3 12B	13	66.3	14	▼	49.4	1.9	14	–	49.3	1.1	14	66.9	2.2	12	35.4	1.6
Gemma 2 27B	14	62.0	15	▼	34.4	2.0	15	–	34.2	1.2	16	47.4	2.4	15	24.0	1.6
Qwen 3 32B	15	58.9	13	▲	51.2	1.4	13	–	51.2	1.0	6	84.6	1.6	14	24.4	1.2
Gemma 2 9B	16	52.9	17	▼	30.0	2.4	17	–	30.2	1.3	18	44.6	2.5	16	18.4	2.3
Llama 3 70B	17	51.8	18	▼	27.7	1.9	18	–	27.7	1.2	17	46.2	2.4	18	12.9	1.6
Gemma 3 4B	18	48.9	16	▲	32.1	2.0	16	–	32.0	1.3	15	52.6	2.4	17	15.6	1.7

Table 3: Model ranking and average accuracy on IC_N# under various resource levels and both Avg-5 and Avg-10 instances per problem. Sub-columns include: 🏅 rank, ↕rank change vs. the previous metric (▲ rise, ▼ fall, – unchanged), % accuracy, ± standard deviation.

bined with irrelevant contexts. All models dropped by at least -6.5 points under the IC_# setting, except for the top performing Gemini 3.0 Pro.

High-resource languages are more robust to variations From Table 1 and Table 2, we observe that overall models are less robust in LRL setting than HRL setting. For instance, the median accuracy drop on Twi is -12.1 and -13.5 for open and closed models respective. On the other hand, Chinese only exhibits -4.2 and -4.7 for open and closed models respective.

More capable recent models are more robust Figure 3 corroborate the finding the LRL are less robust. Here, we show the comparison of the relative accuracy drop across models on HRLs and LRLs. Across all models, LRL setting has larger drop than the HRL setting, indicating that model robustness differ per language, and LRL suffer more. We find the more recent Gemini 3.0 Flash to be more robust than Gemini 2.5 Flash, this shows newer LLMs are improving in robustness. We also find similar result comparing Qwen 3 32B and Qwen 3.5 27B. Model size is often not a good indicator of the robustness of the model.

Model size do not correlate to robustness Figure 4 shows the effect of scaling of model sizes

and robustness to change in names and numbers (IC_N#). There is no clear pattern across different model architectures. For Gemma family of models, the drop in performance gets worse as the model parameters increases from 4B, 12B and 27B (Figure 4a). However, for GPT-OSS, we have the opposite trend where bigger model size is more robust to the performance drop (Figure 4b). Surprisingly, we find GPT-OSS 120B to be more robust to degradation than GPT-4.1 which may be of bigger parameter size since it is a closed model. These findings suggest that model robustness is not a direct result of model size but rather other things, maybe such as training recipe.

4.2.2 Reliability of Leaderboard ranking

Five evaluations provide stability Most leaderboard ranking for math reasoning are based on one instance. Our results in Table 3 show that these rankings are unstable. The leaderboard positions shift significantly when evaluated across five distinct instances of IC_N# datasets. Repeating the experiments 10 times (Avg-10), gave similar results as the Avg-5, with little perturbation in rankings. This findings is interesting, since varying the questions with five instances already gives a more robust, and realistic estimation of math reasoning

| Languages | DeepSeek V3 | | | | | | Gemini 2.5 Flash | | | | | |
| | English Solve | | | Native Solve | | | English Solve | | | Native Solve | | |
	D_O	Sym_#	Δ	D_O	Sym_#	Δ	D_O	Sym_#	Δ	D_O	Sym_#	Δ
English	98.4	92.7	-5.7	97.6	91.8	-5.8	96.8	83.1	-13.7	95.2	83.8	-11.4
Chinese	92.3	89.9	-2.4	93.2	90.3	-2.9	89.9	78.0	-11.9	90.0	79.3	-10.7
French	90.7	87.8	-2.9	90.8	86.0	-4.8	91.5	77.5	-14.0	90.8	79.0	-11.8
Japanese	88.7	79.8	-9.0	89.6	82.8	-6.8	86.7	74.9	-11.8	88.0	74.4	-13.6
Swahili	90.7	86.3	-4.4	88.4	82.7	-5.7	91.5	80.3	-11.2	90.4	78.4	-12.0
Amharic	76.2	71.9	-4.4	72.0	69.9	-2.1	81.9	71.0	-10.9	82.8	68.1	-14.7
Igbo	73.8	64.6	-9.2	71.2	61.3	-9.9	81.5	68.6	-12.8	80.4	65.9	-14.5
Yoruba	66.1	57.1	-9.0	62.4	53.7	-8.7	83.9	69.7	-14.2	81.2	65.9	-15.3
Twi	48.0	38.0	-10.0	46.4	37.7	-9.4	65.3	51.5	-13.9	67.2	51.0	-16.2
Ave.	80.5	74.2	-6.3	79.1	72.8	-6.3	85.4	72.7	-12.7	85.1	71.8	-13.4

Table 4: **Comparison of native and english solve on 5-instances of SYM_# with Deepseek V3 and Gemini 2.5**. We report $\Delta(\texttt{SYM\_\#} - D_o)$

for the language and LLM. We therefore recommend, math reasoning evaluation should use Avg-5 setting as the default.

High and low resource leaderboard rankings
Table 3 shows the model rankings on five instances of both IC_N# for HRLs and LRLs. Interestingly, the rankings across the two settings differ greatly. On LRLs, Gemini 3.0 Pro, 3.0 Flash, and 2.5 Flash take the top three spots. Meanwhile, DeepSeek V3 and GPT-OSS 120B trail in eighth and ninth place, respectively. Under the HRL setting, however, Gemini 2.5's ranking drops significantly to twelfth place. At the same time, DeepSeek V3 and GPT-OSS 120B rises to rank four and three respectively. This indicates that mathematical robustness under HRL do not translate to LRL.

5 Discussion

In the Result section (§4.2), we focused on other issues that may lead to drop in performance or limit robustness such as effect of language choice on reasoning and investigating the cause of lack of robustness—are they related to language understanding or arithmetic competence?

5.1 Effect of Language Choice on Reasoning

One natural question is the effect of language choice on the performance of LLM when they are asked to reason in "native" language rather than in "English". While there are several evidence showing that *prompting the LLM in English* tend to give worse performance especially for low-resource languages (Tam et al., 2025; Qi et al., 2025), we need to verify if asking the model to reason in *native* language reduces robustness. While all results

reported are from english-solve setting, we also evaluated models under native-solve setting via the prompt below. Due to computational restraints, we limit our evaluation on DeepSeek V3 and Gemini 2.5.

> **Native Evaluation Prompt**
>
> *Explain your reasoning step by step in the problem's **native language** to solve the problem.*
> *Your response should end with the final numerical answer, without including units.*
> *Question: {question}*

Does Native reasoning yield similar conclusion as english reasoning? Table 4 compares both models under native reasoning and english reasoning on SYM_# setting. As previous work pointed out, average performance of "Native solve" is lower than "English solve". More importantly, we observe similar patterns in native-reasoning in comparison to english-reasoning, where LRLs observe sharper drop in performance than HRLs. Interestingly, the drop in accuracy (i.e. $\Delta(\texttt{SYM\_\#} - D_o)$) is very similar with only a few exceptions: For DeepSeek, the drop in performance is smaller for Japanese and Amharic, languages with non-Latin scripts while for Gemini 2.5 Flash, the difference of Δ, is often less than ± 2.

5.2 Which is more important? Arithmetic competence or language understanding

Table 5 compares the errors made by DeepSeek V3 and Gemini 2.5 on SYM_#, classifying them into three types: linguistic misunderstandings, logical reasoning errors, and arithmetic mistakes. A

Language	DeepSeek V3			Gemini 2.5 Flash		
	🔤	🧠	🖩	🔤	🧠	🖩
English	1.2	5.2	4.0	0.8	4.8	14.8
Chinese	4.0	8.4	2.4	5.2	8.4	15.2
French	3.5	4.8	3.6	3.2	8.8	16.0
Japanese	9.2	13.6	4.8	6.8	7.2	13.2
Swahili	7.2	12.8	3.6	4.8	7.6	10.0
Amharic	19.2	20.8	5.6	10.4	13.2	12.4
Igbo	26.0	23.6	3.6	22.0	18.0	10.0
Yoruba	39.6	31.2	6.0	18.4	15.6	11.2
Twi	62.0	52.4	3.2	39.2	30.0	10.8

Table 5: **Error analysis of LLM models:** DeepSeek V3 and Gemini 2.5 Flash across high- and low-resource languages via GPT-5.4 as a judge. Errors rates (%) are categorized into LINGUISTIC (🔤), LOGIC (🧠), and ARITHMETIC (🖩).

Figure 5: GPT-OSS 20B average accuracy over all languages on D_O, IC_N, SYM_#, and IC_# under 0-shot and 8-shot prompting.

clear pattern emerges: linguistic errors increase substantially as we move from high-resource to low-resource languages. This trend is especially pronounced for DeepSeek V3, whose linguistic error rate rises from below 10% on all high-resource languages to 62.0% on Twi. Gemini 2.5 Flash shows the same trend but with consistently lower linguistic error rates, suggesting stronger multilingual comprehension under distribution shift. We also observe that these initial linguistic errors frequently propagate into logical reasoning failures, ultimately leading to incorrect answers.

In contrast, the arithmetic error rates for both models remain relatively stable across languages, indicating that calculation abilities are largely unaffected by language shift. Overall, this suggests that the multilingual nature of MGSM-Pro adds a new layer of difficulty that directly impacts model robustness as ultimately, a model's performance relies on both its arithmetic capability and its familiarity with the target language.

5.3 Does few-shot prompting improve robustness?

Figure 5 compares GPT-OSS 20B under 0-shot and 8-shot prompting on D_O, IC_N, SYM_#, and IC_#, averaged across all languages. We only conducted few-shot experiments on GPT-OSS 20B because the other models often performed worse under few-shot prompting than in the zero-shot setting. On D_O, 8-shot prompting yielded only a modest accuracy improvement of +0.8. However, the impact of few-shot prompting was substantially larger for IC_N, SYM_#, and IC_#. The largest gains were

observed in the irrelevant-context setting, where performance improved by more than +5.0 on average across languages. The improvement for the SYM_# setting was smaller, but still appears significant. These findings suggest that few-shot prompting can partially recover math reasoning performance degraded by irrelevant contexts and digit substitutions. Nevertheless, performance in both the zero-shot and few-shot settings remains below that of the original D_O benchmark. This calls for a better strategy in improving mathematics robustness in multilingual settings. The full result is in C.3.

6 Conclusion

In this paper, we investigated the robustness of LLM evaluation for math reasoning when presented with multiple instantiation of the same question by varying names, digits and adding irrelevant contexts. We developed MGSM-Pro, an extension of MGSM with five new instances per question to encourage more robust and realistic evaluation across nine typologically diverse languages. All LLMs experienced a significant drop in performance, especially for low-resource languages. Moreover, we observe model robustness varies from languages and strong linguistic understanding is just as important as arithmetic capabilities.

7 Limitations

Our study has a few limitations. First, our dataset covers a relatively small set of nine languages due to resource constraints. The construction process requires significant human labour to verify each of the 248 questions when converted to template, taking almost 12 hours per language for verification. However, our approach can be easily extended to

other languages, provided the resource. Expanding MGSM-Pro to other languages such as Tamil would provide a more complete picture of multilingual mathematical robustness. Moreover, our evaluation covers only 18 models because of limited compute budget. It remains to be seen how other model families, such as Kimi would perform.

References

Zain Ul Abedin, Shahzeb Qamar, Lucie Flek, and Akbar Karimi. 2025. Arithmattack: Evaluating robustness of llms to noisy context in math problem solving. In *Proceedings of the LLMSEC Workshop at the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*.

David Ifeoluwa Adelani, Hannah Liu, Xiaoyu Shen, Nikita Vassilyev, Jesujoba O. Alabi, Yanke Mao, Haonan Gao, and En-Shiun Annie Lee. 2024. SIB-200: A simple, inclusive, and big evaluation dataset for topic classification in 200+ languages and dialects. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 226–245, St. Julian's, Malta. Association for Computational Linguistics.

David Ifeoluwa Adelani, Jessica Ojo, Israel Abebe Azime, Jian Yun Zhuang, Jesujoba O. Alabi, Xuanli He, Millicent Ochieng, Sara Hooker, Andiswa Bukula, En-Shiun Annie Lee, Chiamaka Chukwuneke, Happy Buzaaba, Blessing Sibanda, Godson Kalipe, Jonathan Mukiibi, Salomon Kabongo, Foutse Yuehgoh, Mmasibidi Setaka, Lolwethu Ndolela, and 8 others. 2025. Irokobench: A new benchmark for african languages in the age of large language models. In *Proceedings of the 2025 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*.

Lucas Bandarkar, Davis Liang, Benjamin Muller, Mikel Artetxe, Satya Narayan Shukla, Donald Husa, Naman Goyal, Abhinandan Krishnan, Luke Zettlemoyer, and Madian Khabsa. 2024. The belebele benchmark: a parallel reading comprehension dataset in 122 language variants. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 749–775, Bangkok, Thailand. Association for Computational Linguistics.

Nuo Chen, Zinan Zheng, Ning Wu, Ming Gong, Dongmei Zhang, and Jia Li. 2024. Breaking language barriers in multilingual mathematical reasoning: Insights and observations. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 7001–7016, Miami, Florida, USA. Association for Computational Linguistics.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Computing Research Repository*, arXiv:2110.14168. Introduces the GSM8K dataset.

Gemma-Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, and 1 others. 2025. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021a. Measuring massive multitask language understanding. In *International Conference on Learning Representations*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021b. Measuring mathematical problem solving with the math dataset. *Advances in Neural Information Processing Systems (NeurIPS)*, 34:24933–24949.

Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. 2020. The state and fate of linguistic diversity and inclusion in the NLP world. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6282–6293, Online. Association for Computational Linguistics.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, and 1 others. 2024. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*.

Wenyang Luo, Wayne Xin Zhao, Jing Sha, Shijin Wang, and Ji-Rong Wen. 2025. MMATH: A multilingual benchmark for mathematical reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 11187–11202, Suzhou, China. Association for Computational Linguistics.

Shen-Yun Miao, Chao-Chun Liang, and Keh-Yih Su. 2020. A diverse corpus for evaluating and developing english math word problem solvers. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 8344–8355.

Seyed Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. 2025. GSM-symbolic: Understanding the limitations of mathematical reasoning in large language models. In *The Thirteenth International Conference on Learning Representations*.

Swaroop Mishra, Arindam Mitra, Neeraj Varshney, Bhavdeep Sachdeva, Peter Clark, Chitta Baral, and Ashwin Kalyan. 2022. Numglue: A suite of fundamental yet challenging mathematical reasoning tasks. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, page to appear.

Arkil Patel, Satwik Bhattamishra, and Navin Goyal. 2021. Are nlp models really able to solve simple math word problems? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, pages 4074–4085.

Jirui Qi, Shan Chen, Zidi Xiong, Raquel Fernández, Danielle Bitterman, and Arianna Bisazza. 2025. When models reason in your language: Controlling thinking language comes at the cost of accuracy. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 20279–20296.

Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed Chi, Nathanael Schärli, and Denny Zhou. 2023. Large language models can be easily distracted by irrelevant context. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, pages 30833–30848.

Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. 2022a. Language models are multilingual chain-of-thought reasoners. *Computing Research Repository*, arXiv:2210.03057. Introduces the MGSM benchmark.

Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, and 1 others. 2022b. Language models are multilingual chain-of-thought reasoners. In *The Eleventh International Conference on Learning Representations*.

Zhi Rui Tam, Cheng-Kuang Wu, Yu Ying Chiu, Chieh-Yen Lin, Yun-Nung Chen, and Hung-yi Lee. 2025. Language matters: How do multilingual input and reasoning paths affect large reasoning models? *arXiv preprint arXiv:2505.17407*.

Yiming Wang, Pei Zhang, Jialong Tang, Haoran Wei, Baosong Yang, Rui Wang, Chenshu Sun, Feitong Sun, Jiran Zhang, Junxuan Wu, and 1 others. 2025. Polymath: Evaluating mathematical reasoning in multilingual contexts. *arXiv preprint arXiv:2504.18428*.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, Tianle Li, Max Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue, and Wenhu Chen. 2024. MMLU-pro: A more robust and challenging multi-task language understanding benchmark. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Weihao Xuan, Rui Yang, Heli Qi, Qingcheng Zeng, Yunze Xiao, Aosong Feng, Dairui Liu, Yun Xing, Junjue Wang, Fan Gao, Jinghui Lu, Yuang Jiang, Huitao Li, Xin Li, Kunyu Yu, Ruihai Dong, Shangding Gu, Yuekang Li, Xiaofei Xie, and 13 others. 2025. MMLU-ProX: A multilingual benchmark for advanced large language model evaluation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 1513–1532, Suzhou, China. Association for Computational Linguistics.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

A Appendix

A.1 Language Details

The resource levels and language families of the nine languages in MGSM-Pro are shown in Table 6. Each language has 234 question templates out of the 250 MGSM questions.

Language	Code	Language Family	Joshi Class
English	eng_Latn	Indo-European	Class 5
Chinese	zho_Hans	Sino-Tibetan	Class 5
French	fra_Latn	Indo-European	Class 5
Japanese	jpn_Jpan	Japonic	Class 5
Swahili	swh_Latn	Niger-Congo	Class 2
Amharic	amh_Ethi	Afro-Asiatic	Class 2
Igbo	ibo_Latn	Niger-Congo	Class 1
Yoruba	yor_Latn	Niger-Congo	Class 2
Twi	twi_Latn	Niger-Congo	Class 1

Table 6: Selected languages categorized by ISO code, linguistic family, and resource availability (Joshi Class).

A.2 Name Categories

Table 7 illustrates the domains and specific name types extracted from the original problems.

Domain	Name Types
People	Male name, Female name, Family name
Places	City name, Mountain name
Pet	Dragon name, Dinosaur name, Cat name

Table 7: Grouped name variables categorized by domain

A.3 IC Template Construction

Figure 6: Example of a MGSM-Pro question template alongside its IC sentence template

Each question in the MGSM-Pro dataset is paired with a corresponding IC sentence template. The curation of IC sentence template follows the methodology of (Shi et al., 2023), where we ensure that the irrelevant sentences have: 1) some related connection with the problem and 2) uses names found in the question. An examplar is shown in Figure 6.

B Prompts for Large Language Models

B.1 Evaluation Prompts

B.2 Template Construction Prompts

All multilingual templates are first translated from the English template via Gemini 2.0 Flash. Afterwards, they each will be reviewed by a native speaker. The prompt used to translate multilingual template is as follow:

> **Annotator Instructions**
>
> *Your task is to convert an English template into a native-language template, preserving all placeholder formats. Do not change the ordering of words of the output sentence, just label them with brackets as shown below:*
> *Input:*
> *- English template (with placeholders)*
> *- Native sentence (no placeholders)*
> *Output:*
> *- Native sentence with the same placeholders, matching values and positions.*
> *Placeholder formats:*
> *- Names: {name_male, xxx}, {name_female, xxx}*
> *- Digits: {num_digit, xxx}*
> *Guidelines:*
> *1. Tag all placeholders from English in the native sentence.*
> *2. Names may differ across languages (e.g. James → Jacques) — match by position.*
> *3. Always tag the first word if it's a person name.*
> *4. Do not reword the native sentence in anyway, you should just be inserting the variable names and brackets*
>
> *Input: {english template}*
> *Native: {native question}*
> *Output:*

C Instructions for Annotators

This section provides a brief introduction to the annotation guide for the MGSM-Pro dataset. We categorize the MGSM-Pro annotation process into two main tasks: 1) correcting native templates, and 2) providing native names

C.1 Template Correction Annotation

For each problem template correction, 3 items will be provided for you to use.

1. English Template
This is the gold template. You should make sure the native language template is as similar to the english template as possible.

2. Original Native Question
This is the original native question in the dataset. You should use this as a reference alongside the English template to judge if the Native language template is correct.

3. Native Language Template
This is a machine-created native language template. It could very likely contain errors. This is the template that you will judge if it is correct or not.

Below are the five critierias the native language template must achieve in order to be considered as correct.

1. Native Language Templates will need to contain the original question. I.E. the wording of the native template should not change from the native question, the template should only be adding in the variable names. If this is not the case, you should ignore the Native Language Template and please provide the new annotated template inside the correction column

2. No missing variable annotation. I.E. all names or digits tagged in English template is tagged in the native language template. You should add the corresponding {type, value} annotation around the target language word or number.

3. No extra annotation. I.E. there is no extra variables annotated in the translation but was not in the English template. You should remove any { } markers around words or numbers that were not annotated in English.

4. No incorrect bracket {} span. I.E. the annotated span is not too long or too short. You should adjust the braces so they exactly enclose the intended word or number, matching the English span.

C.2   Native Name Annotation

You will be given eight types of name.

You will need to provide 10 names to these name types that fit into your native language. The name should be relevant to your specific language and not English names. However, if there are more than one and less than 10 unique names for a specific name cateogry, it is fine to provide less. Moreover, if there are no native names for a specific name category, you can provide english substitute.

The list of name types are as follows:

Male name, Female name, Family

Lang.	Do		Sym#		ICN		IC#	
	0-S	8-S	0-S	8-S	0-S	8-S	0-S	8-S
English	95.6	97.6	88.9	91.1	87.7	93.0	80.6	86.8
Chinese	89.1	88.7	84.4	86.6	86.6	88.1	81.9	84.0
French	87.9	87.5	84.1	84.6	85.6	87.3	81.9	82.7
Japanese	85.1	85.5	81.3	80.8	79.0	82.0	77.2	79.8
Swahili	74.6	73.0	66.2	68.7	61.5	68.5	53.9	61.5
Amharic	39.5	44.0	32.4	36.8	28.1	36.9	22.4	32.2
Igbo	56.0	60.1	47.2	49.9	47.1	55.4	37.3	44.8
Yoruba	52.0	49.6	39.8	41.5	38.6	44.4	30.3	35.8
Twi	23.0	24.2	16.6	21.2	13.4	19.8	11.6	16.4
Ave.	67.0	67.8	60.1	62.4	58.6	63.9	53.0	58.2

Table 8: 0-Shot(0-S) and 8-Shot(8-S) performance across Do, SYM_#, IC_N, and IC_# for various languages for GPT-OSS-20B

```
775    ↪ name, City name, Mountain
776    ↪ name, Dragon name, Dinosaur
777    ↪  name, Cat name
```

C.3   0-Shot VS 8-Shot Results

Table Table 8 illustrates the 0-Shot vs 8-Shot performance of GPT-OSS-20B on 4 different dataset settings.

D   Experiment Result Details

D.1   Full Experiment Results

	Gemini 2.0 Flash							**Gemini 2.5 Flash**							**Gemini 3 Flash**						
Language	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#
English	96.0	94.1	94.0	85.2	84.3	84.5	81.4	96.8	95.0	94.6	83.1	81.0	80.6	80.1	98.8	97.3	95.9	95.3	94.0	94.9	93.3
Chinese	86.7	89.4	86.5	80.0	77.9	80.7	76.5	89.9	90.7	89.0	78.0	79.0	78.3	76.2	93.1	92.3	91.5	91.7	91.4	91.3	90.2
French	90.7	86.7	87.2	77.2	76.5	78.5	76.7	91.5	87.3	87.1	77.5	73.8	75.8	73.5	92.3	89.7	89.2	88.1	87.6	87.1	86.5
Japanese	84.3	84.4	82.1	75.9	72.4	74.4	70.4	86.7	85.0	83.9	74.9	73.1	73.2	71.7	90.7	89.5	88.5	88.9	88.4	88.6	88.0
Swahili	91.9	90.8	87.6	79.0	77.9	78.1	77.3	91.5	90.7	89.9	80.3	78.7	78.1	77.7	96.8	94.0	93.0	91.6	90.8	90.5	89.4
Amharic	80.2	80.2	80.6	67.3	68.0	66.9	66.5	81.9	83.9	81.9	71.0	70.2	71.0	69.3	86.3	85.7	84.4	81.9	81.5	82.4	80.2
Igbo	78.6	80.0	74.2	63.4	59.8	65.6	61.0	81.5	80.3	79.7	68.6	66.6	70.2	68.0	86.7	87.4	84.2	79.9	78.0	80.1	78.0
Yoruba	79.4	77.9	71.6	64.4	60.2	63.5	59.8	83.9	83.5	79.4	69.7	68.1	69.4	65.8	83.9	84.0	82.2	79.9	76.4	78.7	74.8
Twi	62.5	63.5	58.1	50.4	47.3	51.0	45.3	65.3	66.3	61.9	51.5	49.6	52.7	48.3	73.8	72.5	71.1	66.1	61.0	65.1	60.1
Average	83.4	83.0	80.2	71.4	69.4	71.5	68.3	85.4	84.7	83.0	72.7	71.1	72.1	70.1	89.2	88.0	86.7	84.8	83.2	84.3	82.3

Table 9: Different models' accuracy across different dataset variations (D_O, SYM_N, IC_N, SYM_#, IC_#, SYM_N#, IC_N#) for each language

	Gemini 3.0 Pro							**GPT 4.1**							**GPT 5**						
Language	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#
English	98.0	96.3	96.2	94.4	93.2	93.5	92.8	96.4	94.7	91.7	81.5	79.6	81.1	79.9	96.8	-	93.3	92.8	-	-	87.6
Chinese	93.5	93.5	93.1	93.2	93.5	92.5	92.3	89.9	91.4	90.6	78.6	76.8	78.3	76.4	92.3	-	91.9	89.3	-	-	87.1
French	90.7	89.3	89.7	88.6	87.2	88.5	86.0	88.7	86.7	85.5	75.9	74.5	76.0	74.0	89.9	-	88.4	85.4	-	-	83.0
Japanese	90.7	89.0	89.4	87.6	88.0	88.0	87.2	87.1	85.8	83.6	74.8	74.1	73.5	73.2	90.7	-	83.6	83.6	-	-	81.1
Swahili	97.6	94.5	93.9	93.0	92.4	91.3	91.2	91.5	90.0	89.0	79.8	77.5	77.5	77.3	90.7	-	87.7	87.7	-	-	87.9
Amharic	87.5	86.8	85.4	83.2	83.0	82.8	82.2	68.1	69.4	68.2	53.0	51.2	52.7	51.2	71.8	-	67.6	67.6	-	-	65.9
Igbo	89.9	88.8	87.5	82.1	81.2	82.2	81.1	79.0	77.2	71.3	58.5	54.0	59.4	55.5	79.8	-	70.2	70.2	-	-	65.8
Yoruba	86.3	86.5	85.7	83.1	80.9	81.0	77.8	72.6	73.2	69.6	59.8	55.6	59.0	55.2	74.6	-	67.7	67.7	-	-	65.4
Twi	77.8	77.1	74.9	70.6	69.1	69.8	66.0	41.9	43.5	36.9	31.5	28.4	31.7	26.2	46.8	-	38.5	38.5	-	-	37.5
Average	90.2	89.1	88.4	86.2	85.4	85.5	84.1	79.5	79.1	76.3	65.9	63.5	65.5	63.2	81.5	-	79.5	75.9	-	-	73.5

Table 10: Different models' accuracy across different dataset variations (D_O, SYM_N, IC_N, SYM_#, IC_#, SYM_N#, IC_N#) for each language

	GPT 20 B							**GPT 120B**							**DeepSeek V3**						
Language	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#
English	95.6	94.9	87.7	88.9	80.6	88.1	78.8	96.4	96.2	93.9	93.5	92.1	92.0	90.6	98.4	96.6	94.3	92.7	89.7	91.9	89.5
Chinese	89.1	89.0	86.6	84.4	81.9	84.0	81.3	91.5	92.3	90.6	90.2	89.7	90.4	88.1	92.3	93.2	91.4	89.9	88.1	89.1	87.2
French	87.9	87.3	85.6	84.1	81.9	83.3	79.9	90.7	88.6	88.7	86.5	86.5	86.5	83.9	90.7	89.9	88.7	87.8	85.7	86.6	85.7
Japanese	85.1	83.2	79.0	81.3	77.2	81.0	75.7	89.1	86.6	85.2	85.2	83.9	84.5	82.9	88.7	83.9	83.0	79.8	79.8	80.8	79.8
Swahili	74.6	74.9	61.5	66.2	53.9	64.1	54.7	84.7	84.7	82.2	81.5	79.6	81.4	79.5	90.7	90.5	89.6	86.3	84.0	85.9	85.2
Amharic	39.5	40.4	28.1	32.4	22.4	32.1	21.4	60.9	64.5	57.7	58.5	53.7	58.9	52.3	76.2	77.2	73.5	71.9	66.0	71.9	66.9
Igbo	56.0	60.1	47.1	47.2	37.3	46.9	37.9	77.4	78.1	73.3	67.7	64.7	68.1	63.4	73.8	74.7	67.8	64.6	58.0	64.2	58.7
Yoruba	52.0	50.6	38.6	39.8	30.3	39.1	30.2	76.2	71.7	66.9	66.1	61.3	65.1	59.6	66.1	65.9	58.0	57.1	52.7	58.1	51.9
Twi	23.0	21.3	13.4	16.6	11.6	16.1	11.2	44.8	46.9	37.7	39.0	31.5	37.9	33.1	48.0	43.7	36.9	38.0	28.1	39.4	29.4
Average	67.0	66.8	58.6	60.1	53.0	59.4	52.3	79.1	78.9	75.1	74.2	71.4	73.9	70.4	80.6	79.5	75.9	74.2	70.3	74.2	70.5

Table 11: Different models' accuracy across different dataset variations (D_O, SYM_N, IC_N, SYM_#, IC_#, SYM_N#, IC_N#) for each language

	Gemma 3 4B							**Gemma 3 12B**							**Gemma 3 27B**						
Language	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#
English	85.5	85.6	80.0	68.1	64.0	66.5	61.3	92.7	92.8	92.7	76.9	77.3	75.8	76.5	95.6	94.4	93.3	81.6	77.6	80.2	77.6
Chinese	76.2	78.6	67.8	63.5	54.0	60.2	53.1	86.7	88.0	84.9	70.9	65.6	70.6	66.0	87.9	89.7	85.5	75.2	72.3	76.4	72.1
French	79.0	78.2	69.3	59.0	53.8	60.3	52.7	87.9	85.9	81.8	71.7	66.2	70.2	65.4	89.1	87.4	84.5	73.4	69.9	74.4	69.0
Japanese	70.2	67.3	58.1	51.9	45.2	52.1	43.4	83.5	81.2	79.4	66.1	60.2	65.3	59.8	85.1	83.1	79.4	71.1	64.6	70.5	64.8
Swahili	59.7	64.4	55.6	48.7	40.6	46.6	39.0	81.5	86.5	81.4	65.6	61.1	65.6	61.7	89.1	87.7	85.4	72.2	71.2	72.3	70.1
Amharic	40.7	42.9	37.7	32.7	26.0	32.3	27.2	68.1	69.2	67.9	56.6	52.3	55.6	54.5	71.4	71.9	70.2	57.4	55.1	56.8	53.8
Igbo	16.5	15.0	13.5	10.6	7.5	10.2	7.6	55.6	53.2	44.4	38.1	33.0	38.9	34.8	64.1	65.0	54.0	50.0	41.3	51.9	42.8
Yoruba	7.7	9.0	4.9	4.8	3.5	5.2	3.3	32.7	34.4	26.8	24.9	20.2	26.0	21.7	44.4	49.1	40.5	38.2	31.4	38.1	31.9
Twi	4.4	3.5	1.9	1.8	0.9	2.1	1.0	7.7	8.2	6.2	7.0	4.3	5.6	4.4	18.1	17.1	10.4	13.4	9.3	14.0	9.4
Average	48.9	49.4	43.2	37.9	32.8	37.3	32.1	66.3	66.6	62.8	53.1	48.9	52.6	49.4	71.6	71.7	67.0	59.2	54.7	59.4	54.6

Table 12: Different models' accuracy across different dataset variations (D_O, SYM_N, IC_N, SYM_#, IC_#, SYM_N#, IC_N#) for each language

Language	Claude 4							Llama 3 70B							Gemma 2 27B						
	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#
English	98.0	96.4	96.0	91.5	90.4	90.8	90.5	95.2	93.4	88.4	68.9	65.0	68.7	64.4	90.3	80.5	78.5	56.0	53.0	54.2	51.8
Chinese	93.1	93.5	91.9	88.7	88.5	88.7	87.6	69.8	73.9	66.9	51.5	41.5	51.6	43.5	81.0	86.8	80.5	55.7	52.3	58.1	53.3
French	91.5	90.4	90.4	86.4	85.3	84.9	83.2	75.0	73.9	64.8	47.6	41.2	49.5	41.7	84.7	68.1	58.7	51.5	39.8	49.7	39.9
Japanese	89.9	86.3	84.8	83.1	81.5	81.2	82.1	69.8	65.9	54.5	43.0	34.8	42.3	35.2	79.0	76.9	68.1	52.2	44.0	52.1	44.5
Swahili	91.9	92.6	90.9	85.1	84.4	85.1	83.9	63.7	64.4	50.8	41.6	32.4	39.8	31.2	86.7	82.4	74.0	54.7	47.6	53.5	48.1
Amharic	82.3	82.3	81.5	74.5	73.1	75.4	73.6	15.3	18.7	6.0	11.9	3.9	11.8	3.5	39.9	45.5	40.5	25.9	23.4	26.6	24.1
Igbo	78.2	79.1	76.7	68.1	66.0	70.0	65.9	43.5	44.6	33.8	26.4	18.3	27.0	18.5	44.4	45.3	40.2	26.7	21.4	27.7	22.7
Yoruba	77.4	78.6	73.7	67.9	66.0	67.5	63.2	19.0	22.3	12.4	14.0	8.6	12.3	7.7	33.1	32.8	26.2	18.6	15.7	20.2	15.6
Twi	52.8	52.9	46.0	43.2	36.2	44.8	37.5	14.9	14.1	8.3	8.5	5.0	9.5	3.4	18.5	19.1	16.5	10.4	9.2	12.3	9.8
Average	83.9	83.6	81.3	76.5	74.6	76.5	74.2	51.8	52.3	42.9	34.8	27.9	34.7	27.7	62.0	59.7	53.7	39.1	34.0	39.4	34.4

Table 13: Different models' accuracy across different dataset variations (D_O, SYM_N, IC_N, SYM_#, IC_#, SYM_N#, IC_N#) for each language

Language	Qwen 3 32B							Qwen 3.5 27B							Gemma 2 9B						
	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#	D_O	SYM_N	IC_N	SYM_#	IC_#	SYM_N#	IC_N#
English	89.1	84.7	87.3	87.7	86.5	86.0	86.0	98.4	97.2	94.2	93.8	90.7	92.0	88.9	75.9	77.9	76.7	45.3	47.3	44.7	48.5
Chinese	89.9	90.9	88.8	87.8	88.1	88.2	86.1	89.9	91.5	90.1	87.3	83.9	86.4	85.1	78.4	83.3	76.8	49.0	46.1	49.2	44.2
French	89.5	86.9	87.6	86.3	84.0	85.1	83.5	91.1	89.8	87.2	87.2	84.1	86.9	83.6	79.6	80.1	75.2	48.6	46.1	48.5	45.6
Japanese	88.7	86.2	85.2	84.8	83.3	84.3	82.9	87.5	83.7	80.1	76.0	72.1	76.1	68.5	75.1	70.0	64.4	45.1	39.3	43.2	39.9
Swahili	78.2	79.2	71.0	73.6	67.3	71.3	64.6	91.9	90.9	88.5	88.1	84.9	88.2	84.0	69.8	71.3	68.6	44.4	42.4	43.2	43.8
Amharic	42.7	45.8	39.4	37.7	33.6	38.6	30.6	77.0	79.4	76.0	68.1	67.4	67.3	64.0	41.6	43.5	36.8	24.2	20.7	24.2	18.9
Igbo	19.8	20.2	14.9	14.7	10.0	15.0	10.8	73.8	74.7	70.8	69.5	62.9	70.8	63.2	31.6	34.0	29.5	17.1	17.1	18.1	16.6
Yoruba	26.6	26.5	17.3	23.1	14.0	21.2	13.9	74.6	75.6	70.0	69.3	63.2	68.2	62.1	16.0	20.4	16.3	10.3	9.2	11.4	9.5
Twi	5.6	5.7	3.5	4.6	2.2	5.6	2.2	37.5	35.9	27.4	31.3	25.4	32.4	25.5	8.0	10.5	7.8	6.7	3.3	7.0	3.1
Average	58.9	58.4	55.0	55.6	52.1	55.0	51.2	80.2	79.9	76.0	74.5	70.5	74.3	69.4	52.9	54.5	50.2	32.3	30.2	32.2	30.0

Table 14: Different models' accuracy across different dataset variations (D_O, SYM_N, IC_N, SYM_#, IC_#, SYM_N#, IC_N#) for each language