LIFTING IMBALANCED REGRESSION WITH SELF-SUPERVISED LEARNING

ABSTRACT

A new influential task called imbalanced regression, most recently inspired by imbalanced classification, originating straightforwardly from both the imbalance and regression worlds, has received a great deal of attention. Yet we are still at a fairly preliminary stage in the exploration of this task, so more attempts are needed. In this paper, we work on a seamless marriage of imbalanced regression and self-supervised learning. But with this comes the first question of how to measure the similarity and dissimilarity under the regression sense, for which the definition is clear in the classification. To overcome the limitation, the formal definition of similarity in the regression task is given. On top of this, through experimenting on a simple neural network, we found that self-supervised learning could help alleviate the problem. However, the second problem is, it is not guaranteed that the noisy samples are similar to original samples when scaling to a deep network by adding random noise to the input, we specifically propose to limit the volume of noise on the output, and in doing so to find meaningful noise on the input by back propagation. Experimental results show that our approach achieves the state-of-the-art performance.

1 INTRODUCTION

Regression is a fundamental task in machine learning and statistical analysis, which involves modeling the relationship, between one or more independent and dependent variables. As distinct from the discrete output values in classification, regression makes predictions for continuous values. The issue of imbalanced recognition, arising from the conjunction of imbalance and classification, is drawing the attention of researchers recently (Shu et al., 2019; Cao et al., 2019; Ren et al., 2020; Jamal et al., 2020; Kang et al., 2020; 2021). By analogy, it is natural to question whether there exists long-tailed regression (Or one can also call it imbalanced regression, the equivalence of these two names in the paper). Exactly what we expected, a fresh task, namely long-tailed regression, has recently been proposed by Yang et al. (2021). Regardless of the newness of the task, there is no way to neglect its immense significance in terms of application and research. For example, age estimation from facial images, health indicators for various populations in healthcare (Soualhi et al., 2014), these quantities usually exhibit a long-tailed distribution. Going further, in terms of performance, progress in the long-tailed regression research is also far from satisfactory.

More recently, self-supervised contrastive learning has emerged as a new rage in the research community, owing to its straightforward learning paradigm yet excellent performance (Noroozi & Favaro, 2016; Gidaris et al., 2018; Wu et al., 2018; He et al., 2020). The excellence of the approach has been admired not only on classification with well-balanced datasets, but also surprisingly on long-tailed classification by Kang et al. (2021) who found its benefits. It prompts some thoughts on the potential and practical applications, in particular, applications to self-supervised learning for long-tailed regression (Yang et al., 2021). Mindful that the majority of available techniques on self-supervised learning are in the context of classification (Oord et al., 2018; Hjelm et al., 2018; Chen et al., 2020a; Henaff, 2020), with the differences between classification and regression (Razi & Athappilly, 2005; Breiman et al., 2017; Liaw et al., 2002; Yang et al., 2021) (As next described the comparison in Figure 1a). Upon deeper pondering, however, there are obstacles and problems that we face: *Can self-supervised learning really relieve the long-tailed regression problem*? *If so, how might we seamlessly combine the two*? The seamless combination of the two is emphasized because the application of self-supervised learning to the categorization task posits data augmentation of the

Figure 1: (a) A more visual illustration of the difference between regression and classification with regard to their sensitivity to noise, the left image suggest a greater change with augmented data. The right image remains cat predicted under the same slight perturbation (b) concepts of similarity and dissimilarity in regression. The right images indicate that after adding noise to the input image, the difference between the age predicted by the noisy image and the original one is less than the threshold δ, so they are considered as similar samples, on the contrary, the difference between the two images on the left is greater than δ, they are therefore recognized as dissimilar samples.

input data, and this shallow perturbation will not ambiguate the categories (Chen et al., 2020a;b;c; Grill et al., 2020; He et al., 2020; Tian et al., 2021).

Figure 1a illustrates the motivation, by adding noise to the image of the cat, it is very unlikely to be misclassified into a class that differs greatly from it, such as a bird. They are discrete and the categories diverge greatly from each other. In the case of regression, however, it's not at all feasible when a similar migration was made. We imagine that if noise is added to a face image, then the network's estimation of the person's age may be significantly biased. In this regard, it becomes essential to work out and comprehend the degree of noise that induces "similarity and dissimilarity" amongst regression values from a regression standpoint. On the foundation of this definition, questions are raised about how to exploit noise in a sensible and effective way.

With this paper, we try for the first time to propose answers to these questions. We have broadened the concept of similarity and dissimilarity between noise samples and original samples from classification to regression. Repurposing this definition, our simple experiments enlightened us that self-supervised learning is indeed a facilitator of long-tailed regression. Having been convinced of the beneficial effect of the union of the two, we extend it to the neural network-based long-tailed regression task. For the purpose of ensuring that the noise is manageable *w.r.t.* the similarity of the regression, in an innovative way, noise is generated within a predefined threshold and added to the regression value, subsequently back-propagating to obtain the noise-added input samples. Through this, we obtain an optimization problem on noise with an efficient approximate solution algorithm based on a first-order Taylor expansion. As a practical trial for the proposed method, the results reveal that we attained not only the best results, but also the possibility to mix it freely with other training techniques.

2 PRELIMINARY

In this section, we cover the description of imbalanced regression, and then, with reference to the concept of similarity and dissimilarity in classification, we broaden this concept to regression, and provide a new definition of similarity and dissimilarity in regression.

Notations. In this paper, lowercase typeface letters (*e.g.*, x) represent scalar, lowercase bold typeface letters (*e.g.*, $\boldsymbol{x}$) represent vectors, uppercase typeface letters (*e.g.*, X) stand for random variable, uppercase bold typeface letters (*e.g.*, $\boldsymbol{X}$) represent matrix. diag($\cdot$) means diagonalising a vector into a matrix.

2.1 PROBLEM STATEMENT

A collection of paired training data $\{(\boldsymbol{x}_i^s, y_i^s)\}_{i=1}^{N_s}$, validation samples $\{(\boldsymbol{x}_i^v, y_i^v)\}_{i=1}^{N_v}$ and test samples $\{(\boldsymbol{x}_i^t, y_i^t)\}_{i=1}^{N_t}$ are presumed to be available, where $\boldsymbol{x}_i^o \in \mathbb{R}^d, o \in \{s, v, t\}$, and y_i^o are a continuous variables. We suppose that y_i^o is well-bounded and notate the maximum and minimum values of y_i^o as y_{max}^o and y_{min}^o accordingly. Further, we are able to partition y_i^o into B bins $[y_0^o, y_1^o), [y_1^o, y_2^o), \ldots, [y_{B-1}^o, y_B^o)$ with equal interval $\Delta y = \frac{y_{max}^o - y_{min}^o}{B}$. In so doing we could put every y_i^o in the dataset into the corresponding bin fulfilling the condition $y_b^o < y_i^o \leq y_{b+1}^o$, where $b \in \{0, 1, \ldots, B-1\}$. With three splits (train, validation, test), if we count the number of data points that fall into each bin and form these into a vector $\boldsymbol{m}^o = (m_1^o, \ldots, m_B^o)$. The *imbalanced character* of the normal regressions lies in the existence of $m_{b_i}^s, m_{b_j}^s \in \boldsymbol{m}^s$, allowing $m_{b_i}^s \gg m_{b_j}^s$ to hold. It is the opposite of this that the values of the elements of the two vectors $\boldsymbol{m}^v$ and $\boldsymbol{m}^t$, are approximately equal. A desire for imbalanced regression enables model $z_i^o = f(\boldsymbol{x}_i^o; \boldsymbol{\theta})$ produced on an imbalanced training set to be potentially generalized to a balanced validation and test set to the maximum extent possible. Typically, $f(\boldsymbol{x}_i^o; \boldsymbol{\theta})$ may be a neural network with parameter $\boldsymbol{\theta}$ because of its impressive fitting ability. In what follows, for the sake of convenience, we will *drop the superscript o*.

In the introduction section, we elaborate on the predicament that the lack of a clear definition of the concepts of similarity and dissimilarity in the regression, as regression involves continuous targets, where hard boundaries between classes do not exist. As a solution to this problem, we formally propose the following definition:

Definition 1 *There exists some threshold δ, regarding two data samples $(\boldsymbol{x}_i, \hat{y}_i), (\tilde{\boldsymbol{x}}_i, \tilde{y}_i)$, $\tilde{\boldsymbol{x}}_i$ is obtained by adding some noise $\boldsymbol{r}$ to $\boldsymbol{x}_i$, and $\tilde{y}_i$ and $\hat{y}_i$ is inferred by the model $f(\boldsymbol{x}_i; \boldsymbol{\theta})$ from $\tilde{\boldsymbol{x}}_i$ and $\boldsymbol{x}_i$ respectively. We remark that $(\boldsymbol{x}_i, \hat{y}_i), (\tilde{\boldsymbol{x}}_i, \tilde{y}_i)$ are similar samples of the model $f(\boldsymbol{x}_i; \boldsymbol{\theta})$ if the distance between the two samples under some distance function $\mathcal{D}(\cdot, \cdot)$ is less than δ. Mathematically, it can be phrased in this following:*

$$\mathcal{I}(\boldsymbol{x}_i, \tilde{\boldsymbol{x}}_i) = \begin{cases} 1, & if \quad \mathcal{D}(\hat{y}_i, \tilde{y}_i) < \delta \\ 0, & if \quad \mathcal{D}(\hat{y}_i, \tilde{y}_i) \geq \delta, \end{cases} \tag{1}$$

where $\mathcal{I}(\boldsymbol{x}_i, \tilde{\boldsymbol{x}}_i)$ indicates the trueness of the condition whether two samples $\boldsymbol{x}_i$ and $\tilde{\boldsymbol{x}}_i$ are similar samples. The parameter δ here is manually specified and task-dependent. We display a virtual example of this definition as illustrated in Figure 1b. We select images from AgeDB-DIR and attach noises to them, afterward we estimate the ages of the original images and their corresponding noisy images with the network. Finally, we identify a pair of original image and noisy image as not similar if their difference exceeds the threshold δ, and vice versa.

3 MOTIVATION

Herewith we illustrate, for simple shallow neural networks, that self-supervised learning facilitates long-tailed regression in a positive way. Aside from this, we would characterize the difficulties involved in extending our approach to deep neural networks, *i.e.* for controlling the level of noise to guarantee the creation of similar samples under the sense of regression. We first describe the data generation, together with a description of the specific experimental settings followed by an analysis. The network structure and implementation details are available in the appendix.

Data generation. Consider two components of data following two different Gaussian distribution, in particular, $\boldsymbol{x}_1 \sim \mathcal{N}(\mu_1 \cdot \boldsymbol{1}_d, \text{diag}(\sigma_1 \cdot \boldsymbol{1}_d)), \boldsymbol{x}_2 \sim \mathcal{N}(\mu_2 \cdot \boldsymbol{1}_d, \text{diag}(\sigma_2 \cdot \boldsymbol{1}_d))$. $\boldsymbol{1}_d$ denotes a vector with all 1's. The values of $\mu_1(\sigma_1)$ and $\mu_2(\sigma_2)$ are quite different. With linear mapping to $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ with parameter $\boldsymbol{w} \in \mathbb{R}^d$, it yields the output value $y = \boldsymbol{w}^\mathsf{T} \boldsymbol{x}$. As a result, we get two collections of training data $\{\boldsymbol{x}_{1,i}^s, y_{1,i}^s\}_{i=1}^{N_1^s}, \{\boldsymbol{x}_{2,i}^s, y_{2,i}^s\}_{i=1}^{N_2^s}$. Suppose $N_1^s > N_2^s$, and we measure imbalance here in terms of $R = \frac{N_1^s}{N_2^s}$. We pick up the value of R in $\{1, 2, 4, 6, 8, 10, 100\}$. Despite the training samples are imbalanced, the test set $\{\boldsymbol{x}_{1,j}^t, y_{1,j}^t\}_{j=1}^{N_1^t}, \{\boldsymbol{x}_{2,j}^t, y_{2,j}^t\}_{j=1}^{N_2^t}$ we generate is balanced. Additionally, we produce similar samples by controlling the noise so that the condition $\min(y_{1,i}, y_{2,j}) \gg \delta, \forall i \in \{1, \ldots, N^s\}, j \in \{1, \ldots, N^t\}$ is satisfied.

(a)   (b)

Figure 2: (a) Mean Square Error with different imbalanced coefficients. Very clearly it is observed that under supervised learning, MSE grows as the imbalanced coefficient increases, contrary to the self-supervised learning case where MSE is considerably smaller with the same imbalanced coefficient. (b) A demonstration of the impact of noise generation on the regression values, when adding random noise to the original image, the difference between the output value of noisy image versus such a component of the original image will most likely exceed the threshold.

Experimental settings. We compare two training methods here: (i) *Representation Learning*: It is trained in the first T_1 epochs using a self-supervised approach, and the resulting network is treated as an initialized network, and in the second T_2 epochs it is trained in a standard supervised learning manner.(ii) *Supervised Learning*: it is entirely trained using supervised learning in the $T_1 + T_2$ epochs. As per the normal process, the model is trained on the training set and tested on the test set. To evaluate we use Mean Square Error (MSE) as a criterion. Here we use the vanilla mean squared loss function.

Experimental findings. We plot the variation curve of MSE with the imbalance coefficient on the test set for the two training methods. As illustrated in Figure 2a, what has been clearly observed is that the MSE for both methods grows with an increase in the imbalance coefficient. More importantly, it is found that self-supervised learning could alleviate this problem to some degree. The experimental findings, thus, lead us to mitigate the imbalance regression problem with self-supervised learning.

Remark It is true that the above experiments concede that self-supervised learning can be beneficial to long-tailed regression, albeit with some restrictions that remain when we adapt it to neural networks. Well, yes, we have imposed settings for noise, namely, the noise added is controllable in terms of its impact on the regression values. Unfortunately, scaling the technique beyond shallow to deep networks, there is a difficulty in keeping the difference between the output values of similar samples under regression within a threshold, a concern that arises in the case of a sample augmented with random noise, where the difference between the output values of the noisy sample and the original sample is more than the threshold, as shown in Figure 2b, *hence the challenge stems from finding valid noise to ensure the generation of similar samples*.

4 METHOD

Just as we showed before, it is not feasible to merely port the above method to regression tasks. Instead, it will backfire if at all we do so. Hence, it is essential to control the noise $\boldsymbol{r}$ to limit the gap between $\hat{y}_i$ and $\tilde{y}_i$ in the length of a bin Δy. We search for the most anisotropic noise causing the generated samples to be similar or dissimilar to the original samples, which means that we have to impose constraints on the output values. Rather than adding noise to the input, we blaze new a trail, that is, we apply noise to the output value. Mathematically, it can be expressed by the following formula:

$$\arg\min_{\boldsymbol{\theta}} \arg\max_{\boldsymbol{r}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta}), \tag{2}$$

$$s.t. \quad ||\boldsymbol{r}_i|| < \epsilon, \tag{3}$$

$$\text{where} \quad \hat{y}_i = f(\boldsymbol{x}_i; \boldsymbol{\theta}) \ \text{and} \ \tilde{y}_i = \hat{y}_i + z_i \ \text{and} \ \tilde{y}_i = f(\boldsymbol{x}_i + \boldsymbol{r}_i; \boldsymbol{\theta}) \tag{4}$$

where $\mathcal{D}$ denotes the distance loss function, and $\tilde{y}_i$ is the noisy output *w.r.t.* noises z_i and $\boldsymbol{r}_i$.

Here $|z_i|$ is randomly sampled from $[0, \Delta y]$. This allows us to assure that $\tilde{y}_i$ and $\hat{y}_i$ are similar, while simultaneously enhancing the local smoothness of the output. Normally it is not possible to obtain $\boldsymbol{r}$ to find a closed-form solution. Since neural networks are highly dimensional and nonlinear, the analytical solutions can not be derived for $\boldsymbol{r}$. For the purpose of facilitating analysis and simultaneously providing efficient training of the network, we approximate $\mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})$ by the first-order Taylor expansion:

$$\mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta}) \approx \nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta}) \left(\tilde{\boldsymbol{x}}_i - \boldsymbol{x}_i\right) + a = \nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})^{\mathsf{T}} \boldsymbol{r}_i + a \tag{5}$$

$$s.t. \quad ||\boldsymbol{r}_i|| < \epsilon \tag{6}$$

Where $a = \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})|_{\boldsymbol{x} = \boldsymbol{x}_i}$ is a constant term around $\boldsymbol{x}_i$. Based on this, the close-form solution of $\boldsymbol{r}_i$ can be calculated as

$$\boldsymbol{r}_i := \operatorname*{arg\,max}_{\boldsymbol{r}_i : ||\boldsymbol{r}_i|| \leq \epsilon} \nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta}) \boldsymbol{r}_i + a \tag{7}$$

$$= \frac{\nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})}{||\nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})||} ||\boldsymbol{r}_i||_{\max} \tag{8}$$

$$s.t. \quad ||\boldsymbol{r}_i|| \leq \epsilon \tag{9}$$

Therefore, it is obviously that $\boldsymbol{r}_i = \epsilon \frac{\nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})}{||\nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})||}$. Furthermore, as Eq. 4 presented, $\tilde{y}_i = \hat{y}_i + z_i$, so $\boldsymbol{r}_i$ can be further denoted as

$$\boldsymbol{r}_i = \epsilon \frac{\nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \hat{y}_i + z_i; \boldsymbol{\theta})}{||\nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \hat{y}_i + z_i; \boldsymbol{\theta})||} \tag{10}$$

Algorithm 1: Self-Supervised Imbalanced Regression (SSIR)

Input: Mini-batch $\boldsymbol{B}$ with M samples, model $f(\cdot; \boldsymbol{\theta})$ with its parameters $\boldsymbol{\theta}$, bin length Δy, limitation coefficient of noise ϵ, divergence distance function $\mathcal{D}$, values range of input samples (v_{min}, v_{max}), function $clip(\cdot, v_{max}, v_{min})$ to clip values that out of range of (v_{min}, v_{max})

Result: Updated parameters of the model $\hat{\boldsymbol{\theta}}$.

1 **for** $\boldsymbol{x}_i$ *in* $\boldsymbol{B}$ **do**
2   Initial random noise z_i, *s.t.* $|z_i| < \Delta y$;
3       $\hat{y}_i = f(\boldsymbol{x}_i; \boldsymbol{\theta})$, $\tilde{y}_i = \hat{y}_i + z_i$;
4   Calculate $\boldsymbol{r}_i$ by taking the gradient of $\mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})$ *w.r.t.* $\boldsymbol{x}_i$:
5           $\boldsymbol{g}_i = \nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta}) = \nabla_{\boldsymbol{x}_i} \mathcal{D}(f(\boldsymbol{x}_i; \boldsymbol{\theta}), f(\boldsymbol{x}_i; \boldsymbol{\theta}) + z_i)$
6           $\boldsymbol{r}_i \leftarrow \epsilon \times \boldsymbol{g}_i / ||\boldsymbol{g}_i||_2$;
7   Update $\tilde{y}_i$ by taking $\boldsymbol{x}_i + \boldsymbol{r}_i$ as the input of f:
8           $\tilde{\boldsymbol{x}}_i = clip(\boldsymbol{x}_i + \boldsymbol{r}_i, v_{max}, v_{min})$;
9           $\tilde{y}_i = f(\tilde{\boldsymbol{x}}_i; \boldsymbol{\theta})$;
10   Update $\boldsymbol{r}_i$ by by taking the gradient of $\mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})$*w.r.t.* $\boldsymbol{x}_i$:
11          $\boldsymbol{g}_i = \nabla_{\boldsymbol{x}_i} \mathcal{D}(\hat{y}_i, \tilde{y}_i; \boldsymbol{\theta})$
12          $\boldsymbol{r}_i \leftarrow \epsilon \times \boldsymbol{g}_i / ||\boldsymbol{g}_i||_2$;
13      $\tilde{\boldsymbol{x}}_i = clip(\boldsymbol{x}_i + \boldsymbol{r}_i, v_{max}, v_{min})$
14      $\tilde{y}_i = f(\tilde{\boldsymbol{x}}_i; \boldsymbol{\theta})$
15 **end**

16 **return** $\hat{\boldsymbol{\theta}} \leftarrow \boldsymbol{\theta} - \nabla_{\boldsymbol{\theta}} \left(\frac{1}{M} \sum_{i=1}^{M} \mathcal{D}(\hat{y}_i, \tilde{y}_i, \boldsymbol{\theta})\right)$

$\tilde{\boldsymbol{x}} = \boldsymbol{x} + \boldsymbol{r}$ obtained in this way, however, may exceed the boundary value of the feature (For example, the range of image pixels is $[0, 255]$). To cope with such an accident, we constrain the feature values to this range by clipping their values. On the other hand, considering that a single back-propagation optimization may not be an accurate approximation, we therefore performed a two-step optimization of $\boldsymbol{r}$. Up to now, our proposed *Self-Supervised Imbalanced Regression* (SSIR) algorithm is completely introduced. In order to show the SSIR more clearly. We give the algorithm workflow in Algorithm 1.

Our training strategy includes normal regression training and self-supervised regression. For the regression training, we directly apply supervised training to minimize the loss function between the outputs of the model $\hat{y}$ and the corresponding ground truth y. Besides, an additional coefficient λ is introduced to the final loss. Our overall training function is shown below:

$$\mathcal{L}_{joint} = \mathcal{L}_R + \lambda\mathcal{L}_{SSIR} \tag{11}$$

$$= \frac{1}{N}\sum_{i=1}^{N}\left[\mathcal{D}(\hat{y}_i, y_i; \theta) + \lambda\mathcal{D}(\hat{y}_i, \tilde{y}_i; \theta)\right] \tag{12}$$

$$= \frac{1}{N}\sum_{i=1}^{N}\left[\mathcal{D}(f(\boldsymbol{x}_i; \boldsymbol{\theta}), y_i) + \lambda\mathcal{D}(f(\boldsymbol{x}_i; \boldsymbol{\theta}), f(\boldsymbol{x}_i + \boldsymbol{r}_i; \boldsymbol{\theta}))\right] \tag{13}$$

5 EXPERIMENTS

In this section, we report the results on three datasets to demonstrate the superiority of our proposed methods, when compared with state-of-the-art baselines. Specifically, we compare our method with **VANILLA**, **SMOTER** (Torgo et al., 2013), **SMOGN** (Branco et al., 2017), **RRT**, **INV**, **SQINV**, **FOCAL-R**, **LDS**, **FDS** (Yang et al., 2021) and some of their combinations on three imbalanced regression datasets including **IMDN-WIKI-DIR**, **AgeDB-DIR** and **NYUD2-DIR**. Note that, in all the experiments, the **LDS** is combined with re-weighting methods *i.e.* **SQINV** or **INV**. In otherwise, our proposed SSIR can be combined with various methods in training process that demonstrates the flexibility of SSIR. The evaluation metrics used on **IMDB-WIKI-DIR** and **AgeDB-DIR** datasets are **MAE** and **GM** (Yang et al., 2021), besides, **RMSE** and δ_1 are also employed on **NYUD2-DIR** dataset. For the details of datasets, baselines, evaluation metrics and implementation details, we put them in the appendix.

Table 1: Comparison on the MAE and GM with several competed baselines on IMDB-WIKI-DIR dataset. The underlined part denotes the second-best result, and the bold part denotes the best result.

Method	MAE				GM			
	All	Many	Med.	Few	All	Many	Med.	Few
VANILLA	8.06	7.23	15.12	26.33	4.57	4.17	10.59	20.46
SMOTER	8.14	7.42	14.15	25.28	4.64	4.30	9.05	19.46
SMOGN	8.03	7.30	14.02	25.93	4.63	4.30	8.74	20.12
SMOGN + LDS + FDS	7.97	7.38	13.22	22.95	4.59	4.39	7.84	14.94
RRT	7.81	7.07	14.06	25.13	4.35	4.03	8.19	16.96
RRT + LDS + FDS	7.65	7.06	12.41	23.51	4.31	4.07	7.17	15.44
INV	8.17	7.64	12.46	22.83	4.70	4.51	6.94	13.78
SQINV	7.87	7.24	12.44	22.76	4.47	4.22	7.25	15.10
SQINV + LDS + FDS	7.78	7.20	12.61	**22.19**	4.37	4.12	7.39	**12.61**
SQINV + SSIR	**7.63**	**7.06**	**12.17**	23.10	**4.26**	4.02	**6.82**	14.93
FOCAL-R	7.97	7.12	15.14	26.96	4.49	4.10	10.37	21.20
FOCAL-R + LDS + FDS	7.88	7.10	14.08	25.75	4.47	4.11	9.32	18.67
FOCAL-R + SSIR	7.88	7.08	14.75	25.16	4.39	**4.01**	10.20	18.04

5.1 MAIN RESULTS

In the experiments on IMDB-WIKI-DIR dataset, we combine our proposed SSIR with SQINV and FOCAL-R respectively. As shown in Table 1, our method achieves the best performance with 7.63 and 4.26 on MAE and GM accordingly. Compared with the second-best method RRT + LDS + FDS, there has improvements of 0.02 and 0.05 in MAE and GM with our approach. Besides, in comparison with other FOCAL-R-based methods, greater performance can be achieved with the combination of FOCAL-R and SSIR with a better GM score of 4.39 and the MAE score of 7.88.

For re-weighting-based methods, the combination of SQINV and SSIR outperforms the second-best re-weighting-based method SQINV + LDS + FDS and improves 0.15 and 0.11 on MAE and GM respectively.

Table 2: Comparison on the MAE and GM with several competed baselines on AgeDB-DIR dataset. The underlined part denotes the second-best result, and the bold part denotes the best result.

Method	MAE				GM			
	All	Many	Med.	Few	All	Many	Med.	Few
VANILLA	7.77	6.62	9.55	13.67	5.05	4.23	7.01	10.75
SMOTER	8.16	7.39	8.65	12.28	5.21	4.65	5.69	8.49
SMOGN	8.26	7.64	9.01	12.09	5.36	4.90	6.19	8.44
SMOGN + LDS + FDS	7.90	7.32	8.51	11.19	4.98	4.64	5.41	7.35
RRT	7.74	6.98	8.79	11.99	5.00	4.50	5.88	8.63
RRT + LDS + FDS	7.66	6.99	8.60	11.32	4.80	4.42	5.53	6.99
INV	7.97	7.31	8.81	11.62	5.05	4.64	5.75	8.20
SQINV	7.81	7.16	8.80	11.20	4.99	4.57	5.73	7.77
SQINV + LDS + FDS	7.55	7.01	**8.24**	**10.79**	4.72	4.36	5.45	**6.79**
SQINV + SSIR	7.49	6.81	8.54	11.04	**4.61**	4.28	**5.12**	6.92
FOCAL-R	7.64	6.68	9.22	13.00	4.90	4.26	6.39	9.52
FOCAL-R + LDS + FDS	7.47	6.69	8.30	12.55	4.71	4.25	5.36	8.59
FOCAL-R + SSIR	**7.35**	**6.53**	8.51	11.81	4.62	**4.09**	5.64	8.46

In the experiments on AgeDB-DIR, with the same experimental settings on IMDB-WIKI-DIR, we combine our proposed SSIR with SQINV and FOCAL-R respectively. Table 2 illustrates the main results of our method and baselines on AgeDB-DIR dataset. Clearly our method achieves the best performance on both MAE and GM with 7.35 and 4.61 respectively. As the combination of the re-weighting method and SSIR, SQINV + SSIR performs better than the other four re-weighting-based methods with 0.06 and 0.11 improvements on MAE and GM separately, compared to the second-best re-weighting-based method SQINV + LDS + FDS. For FOCAL-R-based methods, the association with SSIR can further decrease the testing error than FOCAL-R and FOCAL-R + LDS + FDS.

For NYUD2-DIR dataset, we combine SSIR with VANILLA and re-weighting method INV respectively. As presented in Table 3, our method INV + SSIR achieves the best performance among other methods. Specifically, INV + SSIR outperforms the second-best method INV + LDS + FDS on RMSE with 0.047, and our method achieves the best performance on δ_1 with 0.075. Compared with VANILLA, the combination with SSIR can improve the performance significantly with 0.07 on RMSE and 0.007 on δ_1.

Table 3: Comparison on the RMSE and δ_1 with several competed baselines on NYUD2-DIR dataset. The underlined part denotes the second-best result, and the bold part denotes the best result.

Method	RMSE				δ_1			
	All	Many	Med.	Few	All	Many	Med.	Few
VANILLA	1.477	0.591	0.952	2.123	0.677	**0.777**	0.693	0.570
VANILLA + SSIR	1.407	**0.580**	0.883	2.022	0.684	0.772	0.704	0.590
INV + LDS + FDS	1.338	0.670	**0.851**	1.880	0.705	0.730	**0.764**	0.655
INV + SSIR	**1.291**	0.766	0.894	**1.756**	**0.705**	0.669	0.763	**0.718**

Figure 3: (a) Parameter study of our method on AgeDB-DIR dataset, for a fixed value of λ, we vary the value of ϵ. (b) Original outputs and noisy outputs of samples from AgeDB-DIR dataset.

5.2 PARAMETER AND CASE STUDY

Parameter study. Figure 3a illustrates the results of parameter study. As it shows, each line denotes the results of different λ when fixing ϵ, and we conduct such experiments with the ϵ of 5e-3, 1e-3, 5e-4 and 1e-4. The overall results show that our method achieves the best performance with $\epsilon = 1e - 3$ and $\lambda = 1.0$.

Case Study. We also conduct case studies to visualize some results of selected examples. As Figure 3b shows, the gaps between the outputs and their associated noisy outputs of all the chosen 6 examples do not exceed a bin length, which means our proposed method can successfully control the noise to limit the noisy outputs within a reasonable range.

Visualization on Noisy Samples. Moreover, we also show three examples and their corresponding noisy examples with ϵ of 0.05, 0.1, 0.3, 0.5 and 1.0 respectively in Figure 4. Obviously, with the ϵ increasing, the noisy examples become unclearer that means the noise level is positively correlated with ϵ.

Figure 4: Three groups of noisy samples generated from three samples chosen from AgeDB-DIR dataset with different ϵ.

6   RELATED WORK

Presented here are the literature on imbalance problems and self-supervised learning. Concerning imbalance problems, the introduction focuses on classification and regression. For self-supervised learning, we review some of the advances and applications.

6.1   IMBALANCED PROBLEM

From the object of imbalanced problems, it can be divided into two categories: imbalanced classification and imbalanced regression.

Imbalanced classification. In the imbalanced classification task, existing methods mainly adopt data-based or model-based solutions (Yang et al., 2021). The core idea of data-based methods is reducing the gap of sampling numbers between many-shot classes and few-shot classes (Chawla et al., 2002; He et al., 2008). For the model-based methods, several works have been proposed to tackle such challenges based on lots of aspects. Jamal et al. (2020) proposed to solve long-tailed classification through domain adaptation perspective. Kang et al. (2020) used a two-stage learning strategy to learn representations for the classification layer using a long-tailed training set. Kang et al. (2021) explored the impact of balanced feature spaces when dealing with imbalanced data, and proposed a self-supervised learning-based method to better learn the representation for imbalanced classification. Furthermore, there also has some methods addressing the problem by well-designed loss functions (Zhang et al., 2017; Cao et al., 2019; Cui et al., 2019; Ren et al., 2020) and other learning paradigms, *i.e.* meta learning (Shu et al., 2019; Wang et al., 2020; Kang et al., 2021).

Imbalanced regression. Imbalanced problem has also been explored in regression problems. Conventional works mainly applied data-based methods to solve the imbalanced problem in regression tasks. One of the first works to address this problem, is published by Torgo et al. (2013) using SMOTE (Chawla et al., 2002). Branco et al. (2017) proposed a Gaussian noise-based synthetic case generation method for imbalanced regression. After that, they further proposed a bagging-based method to aggregate various data pre-processing strategies (Branco et al., 2018) for the same task. Recently, Yang et al. (2021) further delved into such problem by analyzing the error distribution and the statistic distribution of features, both *w.r.t.* labels, and proposed two distribution smoothing methods for labels and features. And they also proposed the Focal-R, a new loss function for imbalanced regression, motivated by Focal loss (Lin et al., 2017).

6.2   SELF-SUPERVISED LEARNING

Recently, self-supervised learning has received extensive attention in the field of deep learning. Different from conventional unsupervised learning and supervised learning, self-supervised learning can use the semantic or contexture supervision information to learn robust and well-generalization representations without manual annotations, include contrastive learning-based methods (Chen et al., 2020a;b;c; He et al., 2020) and some other pretext tasks-based methods, such as image inpainting (Pathak et al., 2016; Jenni & Favaro, 2018), context prediction (Doersch et al., 2015), rotation prediction (Gidaris et al., 2018) and so on. Whereas we tackle the optimization problem in a very similar way, the difference concerns the fact that we apply noise to the output directly rather than to the input, as well as the fact that the problem we analyze varies from semi-supervised classification problems to imbalanced regression problems.

7   CONCLUSION

In this paper, we explore the Self-Supervised Learning (SSL) in imbalanced regression scenario. Specifically, we propose *Self-Supervised Imbalanced Regression* (SSIR) to better address the imbalanced problem in regression tasks. In SSIR, instead of adding noise to the inputs directly to generate the noisy samples, we add noise, which is limited by the bin size, to the output of the model to avoid the excessive dissimilarity between samples and noisy samples, followed by back propagation steps to obtain the meaningful noisy samples. This work provides a new paradigm to tackle this challenge. Further, extensive experiments have shown the superiority of our proposed SSIR over existing state-of-the-art baselines.

REFERENCES

Paula Branco, Luís Torgo, and Rita P Ribeiro. Smogn: a pre-processing approach for imbalanced regression. In *First international workshop on learning with imbalanced domains: Theory and applications*, pp. 36–50. PMLR, 2017.

Paula Branco, Luis Torgo, and Rita P Ribeiro. Rebagg: Resampled bagging for imbalanced regression. In *Second International Workshop on Learning with Imbalanced Domains: Theory and Applications*, pp. 67–81. PMLR, 2018.

Leo Breiman, Jerome H Friedman, Richard A Olshen, and Charles J Stone. *Classification and regression trees*. Routledge, 2017.

Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Arechiga, and Tengyu Ma. Learning imbalanced datasets with label-distribution-aware margin loss. *Advances in Neural Information Processing Systems*, 32:1567–1578, 2019.

Nitesh V Chawla, Kevin W Bowyer, Lawrence O Hall, and W Philip Kegelmeyer. Smote: synthetic minority over-sampling technique. *Journal of artificial intelligence research*, 16:321–357, 2002.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020a.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey E Hinton. Big self-supervised models are strong semi-supervised learners. *Advances in Neural Information Processing Systems*, 33:22243–22255, 2020b.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020c.

Yin Cui, Menglin Jia, Tsung-Yi Lin, Yang Song, and Serge Belongie. Class-balanced loss based on effective number of samples. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9268–9277, 2019.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE international conference on computer vision*, pp. 1422–1430, 2015.

Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. *arXiv preprint arXiv:1803.07728*, 2018.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, koray kavukcuoglu, Remi Munos, and Michal Valko. Bootstrap your own latent - a new approach to self-supervised learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 21271–21284, 2020.

Haibo He, Yang Bai, Edwardo A Garcia, and Shutao Li. Adasyn: Adaptive synthetic sampling approach for imbalanced learning. In *2008 IEEE international joint conference on neural networks*, pp. 1322–1328. IEEE, 2008.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Olivier Henaff. Data-efficient image recognition with contrastive predictive coding. In *International Conference on Machine Learning*, pp. 4182–4192. PMLR, 2020.

R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. *arXiv preprint arXiv:1808.06670*, 2018.

Junjie Hu, Mete Ozay, Yan Zhang, and Takayuki Okatani. Revisiting single image depth estimation: Toward higher resolution maps with accurate object boundaries. In *2019 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 1043–1051. IEEE, 2019.

Muhammad Abdullah Jamal, Matthew Brown, Ming-Hsuan Yang, Liqiang Wang, and Boqing Gong. Rethinking class-balanced methods for long-tailed visual recognition from a domain adaptation perspective. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7610–7619, 2020.

Simon Jenni and Paolo Favaro. Self-supervised feature learning by learning to spot artifacts. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2733–2742, 2018.

Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2020.

Bingyi Kang, Yu Li, Sa Xie, Zehuan Yuan, and Jiashi Feng. Exploring balanced feature spaces for representation learning. In *International Conference on Learning Representations*, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Andy Liaw, Matthew Wiener, et al. Classification and regression by randomforest. *R news*, 2(3): 18–22, 2002.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988, 2017.

Stylianos Moschoglou, Athanasios Papaioannou, Christos Sagonas, Jiankang Deng, Irene Kotsia, and Stefanos Zafeiriou. Agedb: the first manually collected, in-the-wild age database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 51–59, 2017.

Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European conference on computer vision*, pp. 69–84. Springer, 2016.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Deepak Pathak, Philipp Krahenbuhl, Jeff Donahue, Trevor Darrell, and Alexei A Efros. Context encoders: Feature learning by inpainting. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2536–2544, 2016.

Muhammad A Razi and Kuriakose Athappilly. A comparative predictive analysis of neural networks (nns), nonlinear regression and classification and regression tree (cart) models. *Expert systems with applications*, 29(1):65–74, 2005.

Jiawei Ren, Cunjun Yu, Shunan Sheng, Xiao Ma, Haiyu Zhao, Shuai Yi, and Hongsheng Li. Balanced meta-softmax for long-tailed visual recognition. In *Proceedings of Neural Information Processing Systems(NeurIPS)*, 2020.

Rasmus Rothe, Radu Timofte, and Luc Van Gool. Deep expectation of real and apparent age from a single image without facial landmarks. *International Journal of Computer Vision*, 126(2):144–157, 2018.

Jun Shu, Qi Xie, Lixuan Yi, Qian Zhao, Sanping Zhou, Zongben Xu, and Deyu Meng. Meta-weight-net: Learning an explicit mapping for sample weighting. *Advances in Neural Information Processing Systems*, 32:1919–1930, 2019.

Nathan Silberman, Derek Hoiem, Pushmeet Kohli, and Rob Fergus. Indoor segmentation and support inference from rgbd images. In *European conference on computer vision*, pp. 746–760. Springer, 2012.

Abdenour Soualhi, Kamal Medjaher, and Noureddine Zerhouni. Bearing health monitoring based on hilbert–huang transform, support vector machine, and regression. *IEEE Transactions on instrumentation and measurement*, 64(1):52–62, 2014.

Yuandong Tian, Xinlei Chen, and Surya Ganguli. Understanding self-supervised learning dynamics without contrastive pairs. In *International Conference on Machine Learning (ICML)*, 2021.

Luís Torgo, Rita P Ribeiro, Bernhard Pfahringer, and Paula Branco. Smote for regression. In *Portuguese conference on artificial intelligence*, pp. 378–389. Springer, 2013.

Renzhen Wang, Kaiqin Hu, Yanwen Zhu, Jun Shu, Qian Zhao, and Deyu Meng. Meta feature modulator for long-tailed recognition. *arXiv preprint arXiv:2008.03428*, 2020.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3733–3742, 2018.

Yuzhe Yang, Kaiwen Zha, Ying-Cong Chen, Hao Wang, and Dina Katabi. Delving into deep imbalanced regression. In *International Conference on Machine Learning (ICML)*, 2021.

Xiao Zhang, Zhiyuan Fang, Yandong Wen, Zhifeng Li, and Yu Qiao. Range loss for deep face recognition with long-tailed training data. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 5409–5418, 2017.

8 APPENDIX

In the appendix, we give the implementation details in the motivation, as well as the details of the datasets and baseline methods included in the experiments. Besides, we also present more detailed experimental results of parameter studies, and loss curves within different settings.

8.1 EXPERIMENTS SETTINGS

Datasets We evaluate our proposed method on three large-scale deep imbalanced regression datasets, the tasks of which are age estimation and depth estimation. For all the datasets used in our experiments, we follow the settings in (Yang et al., 2021) and segment the target bins into three subsets: many-shot which contains more than 100 training images, medium-shot in which the number of training samples in each bin is in the range of 20 to 100, and few-shot that contains less than 20 training samples in each bin. The details of the datasets are as following:

- **IMDB-WIKI-DIR:** IMDB-WIKI-DIR is an imbalanced age estimation dataset. This dataset is created by Yang et al. (2021) based on the IMDB-WIKI dataset (Rothe et al., 2018). The original IMDB-WIKI contains 523.0K face images with associated ages. In IMDB-WIKI-DIR, the training set contains 191.5K images, and both validation and testing sets include 11.0K bin-balanced images separately. The length of a bin is set to 1 year with the range from 0 to 186, and the density of each bin is from 1 to 7,149.

- **AgeDB-DIR:** AgeDB-DIR is also a imbalanced age estimation dataset proposed by Yang et al. (2021) using AgeDB dataset (Moschoglou et al., 2017). In the dataset, the age range is from 0 to 101 and the bin length is 1 year. The maximal and minimal numbers of images in a bin are 353 and 1 respectively. The training set contains 12,208 images with imbalanced densities among bins, while the validation and testing sets contain 2,140 bin-balanced images respectively.

- **NYUD2-DIR:** The NYUD2-DIR is a dataset constructed by Yang et al. (2021) for imbalanced indoor scenes depth estimation, which is an imbalanced version of NYU Depth Dataset V2 (Silberman et al., 2012). The dataset contains images of different indoor scenes and their corresponding depth maps. The bin length is set to 0.1 meters. The maximal and minimal depth is 10 meters and 0.7 meters separately in the dataset. Following Yang et al. (2021), there are 50K images in the training set and 654 images in the testing set. In each bin, the number of pixels is in the range from 1.13×10^6 to 1.46×10^8. Besides, the number of testing pixels selected for each bin from test images is set to 9,357 (the minimal number of pixels in each bin in the testing set), which aims to make the testing set balanced. The total number of pixels in the training set and testing set are 3.51×10^9 and 8.70×10^5 respectively.

Baselines We conduct experiments to compare our proposed method with the following baselines:

- **Vanilla model:** The pure backbone model that does not apply any techniques to improve the performance is presented as **VANILLA**. Following (Yang et al., 2021), we use ResNet-50 (He et al., 2016) as **VANILLA** for both IMDB-WIKI-DIR and AgeDB-DIR datasets, and ResNet-50-based encoder-decoder method (Hu et al., 2019) for NYUD2-DIR dataset.

- **Synthetic samples:** We choose existing synthetic samples methods, which are used for imbalanced regression, as baselines, including **SMOTER** (Torgo et al., 2013) and **SMOGN** (Branco et al., 2017).

- **Focal-R: FOCAL-R** (Yang et al., 2021) is the regression version of Focal loss (Lin et al., 2017), which uses a continuous function, *e.g. Sigmoid* function, to map the absolute error into the range of 0 to 1 instead of the scaling factor in Focal loss.

- **Regressor Re-Training (RRT): RRT** (Yang et al., 2021) is a two-stage training strategy inspired by Kang et al. (2020), in which the feature and classifier are decoupled.

- **Re-weighting:** We also select Re-weighting methods as baselines, including inverse-frequency weighting (**INV**) and its square-root weighting variant (**SQINV**) (Yang et al., 2021).

- **Distribution Smoothing:** Distribution Smoothing (Yang et al., 2021) includes Label Distribution Smoothing (LDS) and Feature Distribution Smoothing (FDS). Such methods are designed to utilize the information from nearby bins by smoothing the distribution of labels or features. Note that, **LDS** should be used with re-weighting methods, and we follow Yang et al. (2021) to combine **LDS** with **INV** and **SQINV**.

Evaluation metrics Here, we will introduce the details of all the evaluation metrics used in our experiments.

- **Mean Absolute Error (MAE):** MAE is a common evaluation metric in regression problems, which is used to measure the averaged absolute difference between ground truth and prediction results. MAE can be denoted as $\frac{1}{N}\sum_{i=1}^{N}|\hat{y}_i - y_i|$, where N denotes the number of total samples, $\hat{y}_i$ and y_i are the prediction result and ground truth of the i-th sample respectively.

- **Root Mean Squared Error (RMSE):** Similar to MAE, RMSE is also a widely used evaluation metric in regression tasks. Different from MAE, RMSE is used to measure the rooted averaged squared difference between ground truth and prediction results, which can be presented as $\frac{1}{N}\sum_{i=1}^{N}(\hat{y}_i - y_i)^2$, where N denotes the number of total samples, $\hat{y}_i$ and y_i are the prediction result and ground truth of the i-th sample respectively.

- **error Geometric Mean (GM):** GM is a new evaluation metric proposed by Yang et al. (2021). Instead of applying arithmetic mean, GM uses geometric mean over the prediction errors, which is defined as $(\prod_{i=1}^{N} e_i)^{\frac{1}{N}}$, where $e_i \triangleq |\hat{y}_i - y_i|$ denotes the L_1 error of the i-th sample.

- **Threshold Accuracy (δ_i):** For NYUD2-DIR dataset, we follow Yang et al. (2021) and use standard depth estimation evaluation metric δ_i which is defined as $\max(\frac{d_i}{g_i}, \frac{g_i}{d_i}) = \delta_i < 1.25^i$, where g_i and d_i denote the ground truth value and the the prediction value of a pixel respectively. Here, in our experiments on NYUD2-DIR, we set i to 1 as the settings in (Yang et al., 2021).

8.2 IMPLEMENTATION DETAILS IN MAIN EXPERIMENTS

IMDB-WIKI-DIR: For IMDB-WIKI-DIR dataset, we use ResNet-50 (He et al., 2016) as backbone and train it with our proposed SSIR method for 90 epochs using Adam optimizer (Kingma & Ba, 2014) with L_1 loss. The initial learning rate is set to 1e-3 and decayed to 1e-4 and 1e-5 at the 60-th and 80-th epoch respectively. Besides, we set the batch size, λ and ϵ to 256, 0.1 and 1e-3 separately.

AgeDB-DIR: For AgeDB-DIR dataset, the settings of backbone, optimizer, learning rate, loss function and batch size are the same with that of IMDB-WIKI-DIR. For the training of Focal-R+SSIR, we set the λ and ϵ to 1.0 and 1e-3 respectively. Besides, they are set to 0.1 and 1e-3 for SQINV+SSIR.

NYUD2-DIR: For the experiments on NYUD2-DIR, we apply a ResNet-50-based encoder-decoder architecture (Hu et al., 2019). We train our method by Adam optimizer with 20 epochs. The initial learning rate is set to 1e-4 and decayed by 0.1 every 5 epochs. We set the batch size and weight decay to 32 and 1e-4 respectively. For λ and ϵ, we set them to 1.0 and 5e-4 for VANILLA+SSIR, and 2.5, 5e-4 for INVERSE+SSIR.

8.3 IMPLEMENTATION DETAILS IN MOTIVATION EXPERIMENTS

For the settings in the data generation of our motivation, we set the mean and variance of the two Gaussian distribution μ_1, σ_1 and μ_2, σ_2 to 10, 25 and -10, 25 respectively, and the dimension of the generated data d is set to 100. We apply a two-layer Multi-Layer Perception (MLP) with 128 hidden neurons as the prediction model in the experiments. For the settings of the training process in the experiments, we set epochs T_1 and T_2 to 1000 and 500 respectively. The learning rates of the two training methods: *Representation Learning* and *Supervised Learning*, are set to 1e-3 and 1e-2 respectively. Besides, we set the weight decay of the training process in the experiments to 5e-5.

8.4 PARAMETER STUDIES

Here, we study the different parameter settings of ϵ and λ on all three datasets and report all the results of the experiments that we conducted.

Table 4: Parameter study of our methods on IMDB-WIKI-DIR dataset.

ϵ	λ	re-weighting	Loss	MAE				GM			
				All	Many	Med.	Few	All	Many	Med.	Few
1e-3	0.01	SQINV	L_1	7.74	7.15	12.61	22.94	4.38	4.13	7.35	15.04
1e-3	0.05	SQINV	L_1	7.74	7.13	12.67	23.34	4.33	4.08	7.35	14.72
1e-3	0.10	SQINV	L_1	7.63	7.06	12.17	23.10	4.26	4.02	6.82	14.93
1e-3	0.50	SQINV	L_1	7.83	7.20	12.91	23.86	4.50	4.24	7.63	16.27
1e-3	0.10	-	FOCAL-R	7.88	7.08	14.75	25.16	4.39	4.01	10.20	18.04
1e-3	0.30	-	FOCAL-R	7.95	7.16	14.79	24.78	4.46	4.08	10.36	18.26
1e-3	0.50	-	FOCAL-R	8.11	7.25	15.44	26.76	4.61	4.20	11.04	19.46
1e-3	1.00	-	FOCAL-R	8.17	7.35	15.26	25.11	4.65	4.25	10.98	17.27

Table 4 illustrates the experiments results of different settings of ϵ and λ. The top part of the table is the results of different parameters settings of SQINV + SSIR, and the bottom part shows the results of FOCAL-R + SSIR on different settings of ϵ and λ.

Table 5: Parameter study of our method on AgeDB-DIR dataset.

ϵ	λ	re-weighting	Loss	MAE				GM			
				All	Many	Med.	Few	All	Many	Med.	Few
5e-4	0.1	SQINV	L_1	7.56	7.06	8.32	10.26	4.90	4.52	5.67	7.00
5e-4	0.3	SQINV	L_1	7.67	6.98	8.86	10.95	4.88	4.44	5.84	7.27
5e-4	0.5	SQINV	L_1	7.63	7.02	8.59	10.69	4.84	4.41	5.81	7.12
5e-4	1.0	SQINV	L_1	7.65	7.01	8.47	11.49	4.96	4.58	5.67	7.22
1e-3	0.1	SQINV	L_1	7.49	6.81	8.54	11.04	4.61	4.28	5.12	6.92
1e-3	0.3	SQINV	L_1	7.73	7.05	8.74	11.34	4.86	4.38	5.97	7.33
1e-3	0.5	SQINV	L_1	7.61	6.94	8.74	10.80	4.93	4.53	5.81	7.00
1e-3	1.0	SQINV	L_1	7.70	7.02	8.69	11.37	4.83	4.37	5.90	7.34
5e-3	0.1	SQINV	L_1	7.62	6.84	8.75	11.87	4.86	4.41	5.84	7.36
5e-3	0.3	SQINV	L_1	7.65	6.86	8.83	11.80	4.88	4.34	6.05	8.12
5e-3	0.5	SQINV	L_1	7.61	6.97	8.35	11.57	4.81	4.36	5.56	8.27
5e-3	1.0	SQINV	L_1	8.04	7.15	9.56	12.20	5.13	4.50	6.68	8.37
1e-4	0.1	-	FOCAL-R	7.62	6.75	8.85	12.43	4.94	4.41	5.97	8.67
1e-4	0.3	-	FOCAL-R	7.38	6.59	8.26	12.39	4.79	4.32	5.46	8.90
1e-4	0.5	-	FOCAL-R	7.62	6.81	8.54	12.73	4.91	4.37	5.89	8.92
1e-4	1.0	-	FOCAL-R	7.53	6.66	8.59	12.73	4.76	4.14	5.98	9.46
5e-4	0.1	-	FOCAL-R	7.69	6.66	9.30	13.04	4.90	4.23	6.26	9.96
5e-4	0.3	-	FOCAL-R	7.51	6.49	9.05	12.95	4.65	3.97	6.11	9.74
5e-4	0.5	-	FOCAL-R	7.46	6.59	8.51	12.83	4.69	4.13	5.73	9.13
5e-4	1.0	-	FOCAL-R	7.61	6.64	9.14	12.64	4.91	4.24	6.36	9.53
1e-3	0.1	-	FOCAL-R	7.44	6.50	8.83	12.44	4.73	4.11	6.13	8.62
1e-3	0.3	-	FOCAL-R	7.39	6.45	8.81	12.37	4.69	4.11	5.74	9.26
1e-3	0.5	-	FOCAL-R	7.39	6.47	8.81	12.09	4.68	4.09	6.06	8.22
1e-3	1.0	-	FOCAL-R	7.35	6.53	8.51	11.81	4.62	4.09	5.64	8.46
5e-3	0.1	-	FOCAL-R	7.48	6.54	8.99	12.10	4.81	4.21	5.98	9.06
5e-3	0.3	-	FOCAL-R	7.42	6.50	8.56	12.97	4.76	4.11	5.98	10.28
5e-3	0.5	-	FOCAL-R	7.60	6.53	8.98	13.84	4.89	4.14	6.40	11.28
5e-3	1.0	-	FOCAL-R	8.13	6.87	9.75	15.51	5.23	4.37	7.05	12.72

The results of the parameter study of our method on AgeDB-DIR dataset are presented in Table 5. As the table shows, we present the results of different ϵ and λ settings of our approach. The top part of the table is regarding with SQINV + SSIR, and the bottom part denotes the results of different parameter settings of FOCAL-R + SSIR.

Table 6: Parameter study of our method on NYUD2-DIR dataset.

ϵ	λ	re-weighting	Loss	RMSE				δ_1			
				All	Many	Med.	Few	All	Many	Med.	Few
5e-4	0.1	_	MSE	1.542	0.580	0.871	2.246	0.669	0.787	0.739	0.523
5e-4	0.3	_	MSE	1.531	0.536	0.878	2.238	0.663	0.796	0.690	0.519
5e-4	0.5	_	MSE	1.540	0.566	0.917	2.239	0.643	0.778	0.713	0.481
5e-4	1.0	_	MSE	1.407	0.580	0.883	2.022	0.684	0.772	0.704	0.590
5e-4	1.5	_	MSE	1.475	0.564	0.872	2.140	0.692	0.793	0.723	0.579
5e-4	2.0	_	MSE	1.402	0.601	0.893	2.005	0.692	0.755	0.704	0.625
5e-4	2.5	_	MSE	1.623	0.535	0.932	2.380	0.640	0.801	0.704	0.455
5e-4	3.0	_	MSE	1.476	0.560	0.899	2.137	0.686	0.789	0.723	0.570
1e-3	0.1	_	MSE	1.476	0.564	0.919	2.134	0.693	0.791	0.723	0.585
1e-3	0.3	_	MSE	1.540	0.560	0.932	2.238	0.680	0.792	0.724	0.550
1e-3	0.5	_	MSE	1.520	0.568	0.876	2.212	0.667	0.787	0.733	0.521
1e-3	1.0	_	MSE	1.537	0.557	0.898	2.239	0.658	0.787	0.716	0.507
5e-4	1.0	INVERSE	MSE	1.365	0.667	0.930	1.915	0.685	0.711	0.717	0.647
5e-4	1.5	INVERSE	MSE	1.391	0.679	0.849	1.968	0.670	0.713	0.734	0.602
5e-4	2.0	INVERSE	MSE	1.313	0.749	0.919	1.795	0.700	0.702	0.742	0.682
5e-4	2.5	INVERSE	MSE	1.291	0.766	0.894	1.756	0.705	0.669	0.763	0.718

Figure 5: (a) Training and validation loss *w.r.t* training epochs of SQINV + SSIR on IMDB-WIKI-DIR dataset. (b) Training and validation loss *w.r.t* training epochs of FOCAL-R + SSIR on IMDB-WIKI-DIR dataset. (c) Training and validation loss *w.r.t* training epochs of SQINV + SSIR on AgeDB-DIR dataset. (d) Training and validation loss *w.r.t* training epochs of FOCAL-R + SSIR on AgeDB-DIR dataset.

Table 6 is the parameter study regards to ϵ and λ on NYUD2-DIR dataset. The top part of the table illustrates the results of different parameters settings of VANILLA + SSIR while the bottom part shows that of INVERSE + SSIR.

8.5 TRAINING AND VALIDATION LOSSES

We present the training and validation loss of our proposed approach on IMDB-WIKI-DIR and AgeDB-DIR datasets. Figure 5a and 5b present the training and validation losses *w.r.t.* training epochs of SQINV + SSIR and FOCAL-R + SSIR respectively on IMDB-WIKI-DIR dataset. Figure 5c and 5d illustrate the training and validation losses of SQINV + SSIR and FOCAL-R + SSIR on AgeDB-DIR dataset.