PROVABLE MEMORIZATION CAPACITY OF TRANSFORMERS

ABSTRACT

Quantifying memorization capacity is essential for understanding the expressiveness and generalizability of deep learning model architectures. However, the memorization capacity of the Transformer architecture has yet to be explored. In this work, we present the first study of the memorization capacity of the Transformer architecture. We prove that Transformers are capable of memorizing N sequence-to-sequence mappings of length n with d-dimensional input tokens using $\tilde{O}(d + n + \sqrt{nN})$ parameters. Our theory supports memorization both with and without permutation equivariance, utilizing positional encodings in the latter case. Building on our theory, we also analyze the memorization capacity of Transformers in the sequence classification task. To verify these theoretical findings, we conduct experiments analyzing the memorization capacity of Transformers in the natural language domain.

1 INTRODUCTION

Transformer networks (Vaswani et al., 2017) have shown tremendous success in natural language processing tasks (Devlin et al., 2019; Yang et al., 2019; Brown et al., 2020; Fedus et al., 2022), rapidly becoming the standard architecture for natural language modeling. The success of Transformers has also transferred to various other sequence and set modeling tasks, including image recognition (Parmar et al., 2018; Dosovitskiy et al., 2021), semantic segmentation (Zheng et al., 2021), video understanding (Akbari et al., 2021; Bertasius et al., 2021), reinforcement learning (Parisotto et al., 2020; Chen et al., 2021; Janner et al., 2021), 3D point cloud processing (Zhao et al., 2021), protein structure prediction (Jumper et al., 2021), and automatic theorem proving (Polu & Sutskever, 2020). Despite this success across various areas, the theoretical understanding of Transformers lags behind that of standard fully-connected networks.

The major strength of Transformers is in their efficient scaling, which is enabled through parallel token processing with parameter sharing and simple dot-product-based token interaction. Surprisingly, even though the parameter sharing and simple token interaction impose constraints on the function space of Transformers, Yun et al. (2020a) show that Transformers can approximate any continuous function from input to output sequences. However, their result focuses on the function approximation capacity with infinite precision, leaving the finite sample memorization capacity with finite precision unexplored. We note that universal function approximation does not automatically imply efficient memorization in terms of the number of parameters. Generalizing infinite precision results to the finite precision case is not straightforward and may not be possible in some cases. For example, Transformers are Turing complete only with infinite precision (Pérez et al., 2019), but not with finite precision (Dehghani et al., 2019).

Understanding the memorization capacity of a model is critical for choosing an appropriate model size. Practitioners often choose a model size with enough representation capacity to achieve zero training loss (i.e., a size larger than memorization capacity). Moreover, the memorization capacity has generalization implications, as observed in the double descent phenomena (Belkin et al., 2019; Nakkiran et al., 2021). As the network size increases, generalization performance exhibits a bias-variance tradeoff until the memorization is possible and then improves monotonically afterward. Understanding the memorization capacity of Transformers requires answers to the following questions: How large should the size and precision of the Transformer architecture be to enable

memorization of any given number of input-output sequence pairs? How does the memorization capacity of Transformers differ for various problem settings in practical application scenarios?

In this paper, we answer these questions by proving that Transformers can memorize N sequences of d-dimensional tokens with length n using $\tilde{O}(d + n + \sqrt{nN})$ parameters. Our proof constructs permutation equivariant Transformers that can memorize all permutations of N input sequences. We extend this construction to the memorization without permutation equivariance by adding positional encodings. In addition, we derive the memorization capacity for sequence classification task from our proposed theory.

The key technical component of our construction is efficient contextual mapping, which requires only n self-attention layers. Our contextual mapping also applies to sparse-attention Transformers making fewer assumptions on sparsity patterns than Yun et al. (2020b) and Zaheer et al. (2020). Furthermore, we present the generalization of contextual mapping to function approximation settings, vastly improving the parameter efficiency of attention layers compared to the selective-shifting-based contextual mapping in Yun et al. (2020a).

Our main contributions are summarized as follows:

- We prove the memorization capacity of Transformers for sequence-to-sequence mappings with and without permutation equivariance. We analyze the memorization capacity in other standard task settings, such as sequence classification.

- We show that the efficient contextual mapping presented in our theoretical analysis extends to sparse attention settings and improves the function approximation results.

- We provide experiments validating the memorization capacity of Transformers for token classification and sequence classification tasks.

1.1 RELATED WORKS

Memorization capacity. Characterizing the memorization capacity of neural networks has been an active research area with a long history (Baum, 1988; Sontag, 1997; Huang & Babri, 1998; Huang, 2003; Zhang et al., 2017; Yun et al., 2019; Bubeck et al., 2020; Vershynin, 2020; Rajput et al., 2021; Park et al., 2021; Vardi et al., 2022). Recently, Park et al. (2021) constructed neural networks with $O(N^{2/3})$ parameters to memorize N data points. They bypass the $\Omega(N)$ lower bound in Sontag (1997) by assuming a simple separation (i.e., $\|\mathbf{x}_i - \mathbf{x}_j\| \geq \delta, \forall i \neq j$). Vardi et al. (2022) improve further, showing that $\tilde{O}(N^{1/2})$ parameters are sufficient. They also prove the matching lower bound of $\tilde{\Omega}(N^{1/2})$ through the VC-dimension analysis.

Inspired by Park et al. (2021) and Vardi et al. (2022), our construction assumes a similar separation, but it is between pairs of distinct tokens, not the whole sequence pairs. (See Definition 3.1 and the discussion that follows the definition.) In addition, our construction uses the same pipeline of projection, string matching, and bit extraction as in Vardi et al. (2022). However, we introduce an additional critical step: efficient contextual mapping to complement projection by summarizing all token information via self-attention layers.

In contrast to the extensive results on fully-connected networks, there are few studies on the memorization capacity of specific modern architectures. Hardt & Ma (2017) show that the residual network with ReLU activation and $O(N)$ hidden neurons can memorize N data points under the separation assumption. Nguyen & Hein (2018) show that the convolutional network with $O(N)$ hidden neurons can memorize N data points. To the best of our knowledge, there is no existing literature on the memorization capacity of the Transformer architecture.

Transformer expressivity. Given the recent empirical success of Transformers observed across multiple areas, several papers have studied the expressivity of Transformers. Yun et al. (2020a) establish the first universal approximation theorem for Transformers, and the result is later extended to sparse-attention Transformers (Yun et al., 2020b; Zaheer et al., 2020) and Transformers with hard constraints (Kratsios et al., 2022). All these results study the function approximation but not the finite sample memorization as in our paper. We also note that our construction can reduce the number of self-attention layers in the function approximation setting.

There are other lines of studies focusing on different aspects of the representation capacity of Transformers. Some papers aim to characterize the representation capacity of a single self-attention layer. Bhojanapalli et al. (2020) suggest that the small size of attention heads limits the rank of a self-attention matrix. Dong et al. (2021) show that the rank of self-attention decays exponentially when self-attention layers are composed without skip-connections or feedforward layers. Likhosherstov et al. (2021) show that a fixed self-attention module can approximate any sparsity pattern.

Other papers investigate a tradeoff between width and depth since it is a crucial issue when scaling Transformers. Levine et al. (2020) demonstrate the depth efficiency in modeling feature interaction through the separation rank analysis of Transformers. Wies et al. (2021) identify the rank of the input embedding matrix as a bottleneck for the network width's contribution to expressivity.

Finally, Vuckovic et al. (2020) and Kim et al. (2021) study the Lipschitz smoothness of attention operations. Edelman et al. (2022) derive the norm-based generalization bounds from the Lipschitz smoothness of norm-bounded attention layers to analyze the inductive bias of attention layers. Wei et al. (2021) study the expressivity of Transformers under the constraint of statistical learnability. Our memorization study provides a complementary understanding of the capacity of Transformers.

2 PRELIMINARIES

This section establishes the notation and defines the Transformer architecture.

2.1 NOTATION

Denote the number of input-output pairs as N, the number of output classes as C, the token embedding dimension as d, and the sequence length as n. We use $\tilde{O}(\cdot)$ to hide logarithmic factors and $O(\cdot)$ to hide constant factors. We use σ_R to represent the ReLU activation function. We let σ_S and σ_H be the softmax and hardmax operators, respectively. These operators take a matrix as an input, apply softmax/hardmax columnwise, and output a column stochastic matrix of the same size.

For $m \in \mathbb{N}$, we define $[m] = \{1, 2, \cdots, m\}$. We use $|\mathcal{S}|$ to denote the number of elements in a set $\mathcal{S}$. We denote a set or a function as an upper case caligraphic letter, a matrix by an upper case bold letter and a vector by a lower case bold letter. We denote the standard unit vector with all but i-th coordinates 0 as $\boldsymbol{e}_i$, the m dimensional vector with all coordinates 1 as $\mathbf{1}_m$ and the m dimensional vector with all coordinates 0 as $\mathbf{0}_m$. For a vector $\boldsymbol{x}$, we represent its i-th entry as $\boldsymbol{x}[i]$ and its Euclidean norm as $\|\boldsymbol{x}\|$. For a matrix $\boldsymbol{X}$, we use $\boldsymbol{X}[i,j]$, $\boldsymbol{X}[i,:]$, and $\boldsymbol{X}[:,j]$ to represent (i,j)-th entry, i-th row, and j-th column, respectively. We use $\|\boldsymbol{X}\|_F$ to represent the Frobenius norm of the matrix $\boldsymbol{X}$.

2.2 TRANSFORMER ARCHITECTURE

We define a Transformer $\mathcal{N} : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ of depth L as a composition of L Transformer blocks with input and output embedding mappings:

$$\mathcal{N} = \mathcal{E}_{out} \circ \mathcal{F}_L \circ \cdots \circ \mathcal{F}_2 \circ \mathcal{F}_1 \circ \mathcal{E}_{in}$$

where each Transformer block $\mathcal{F}_l : \mathbb{R}^{m \times n} \to \mathbb{R}^{m \times n}$ is a sequence-to-sequence function consisting of two subblocks: a self-attention subblock and a tokenwise feedforward subblock. The input embedding block $\mathcal{E}_{in} : \mathbb{R}^{d \times n} \to \mathbb{R}^{m \times n}$ and the output embedding block $\mathcal{E}_{out} : \mathbb{R}^{m \times n} \to \mathbb{R}^{1 \times n}$ are 1-layer tokenwise linear mappings.

The self-attention subblock represents the interaction among tokens. Formally, given an input $\boldsymbol{Z} \in \mathbb{R}^{m \times n}$, the self-attention subblock $\mathcal{F}_l^{(SA)}$ with h heads and head size k computes

$$\mathcal{F}_l^{(SA)}(\boldsymbol{Z}) = \boldsymbol{Z} + \sum_{i=1}^{h} \boldsymbol{W}_{l,i}^{(O)} \left(\boldsymbol{W}_{l,i}^{(V)} \boldsymbol{Z} \right) \sigma_S \left[\left(\boldsymbol{W}_{l,i}^{(K)} \boldsymbol{Z} \right)^T \left(\boldsymbol{W}_{l,i}^{(Q)} \boldsymbol{Z} \right) \right],$$

where $\boldsymbol{W}_{l,i}^{(O)} \in \mathbb{R}^{m \times k}$ and $\boldsymbol{W}_{l,i}^{(V)}, \boldsymbol{W}_{l,i}^{(K)}, \boldsymbol{W}_{l,i}^{(Q)} \in \mathbb{R}^{k \times m}$ are the weight matrices parametrizing the self-attention subblock. We include a skip-connection in the self-attention subblock.

The feedforward subblock processes each token independently in parallel by applying two feedforward layers. Given an input $\boldsymbol{H} \in \mathbb{R}^{m \times n}$, the feedforward subblock $\mathcal{F}_l^{(FF)}$ with dimension q computes

$$\mathcal{F}_l^{(FF)}(\boldsymbol{H}) = \boldsymbol{H} + \boldsymbol{W}_l^{(2)} \sigma_R \left(\boldsymbol{W}_l^{(1)} \boldsymbol{H} + \boldsymbol{b}_l^{(1)} \mathbb{1}_n^T \right) + \boldsymbol{b}_l^{(2)} \mathbb{1}_n^T,$$

where $\boldsymbol{W}_l^{(2)} \in \mathbb{R}^{m \times q}$, $\boldsymbol{b}_l^{(2)} \in \mathbb{R}^m$, $\boldsymbol{W}_l^{(1)} \in \mathbb{R}^{q \times m}$ and $\boldsymbol{b}_l^{(1)} \in \mathbb{R}^q$ parametrize the feedforward subblock. The feedforward subblock also includes a skip-connection.

Finally, the Transformer block composes two subblocks as

$$\mathcal{F}_l(\boldsymbol{Z}) = \mathcal{F}_l^{(FF)}(\mathcal{F}_l^{(SA)}(\boldsymbol{Z}))$$

Unlike the original formulation in Vaswani et al. (2017), our definition excludes layer normalization as Yun et al. (2020a) to simplify our analysis. Since layer normalizations mainly contribute to optimization without much effect on expressivity, our definition still captures the representation aspect of the Transformer architecture.

Since each Transformer block consists of a fixed number of layers even in the most fine-grained sense, we use the number of blocks L as the *depth* of the network. We define the *width* of the network as $\max\{m, kh, q\}$[1]. The *number of parameters* is the number of non-zero weights in our network. We note that the single parameter is reused n times for a sequence length n, but still is counted as one parameter. The *bit complexity of the network* is the maximum bit complexity of its weights, where the *bit complexity of a weight* is the number of bits required to represent it. We adopt these definitions of the number of parameters and the bit complexity from the convention in the VC dimension literature (Bartlett et al., 2019) and the recent paper on the optimal memorization capacity of fully-connected networks (Vardi et al., 2022).

3 MEMORIZATION CAPACITY OF TRANSFORMERS

In this section, we describe the problem setting and present our main theorem on the memorization capacity of the Transformer architecture. Then, we sketch the proof for our main theorem and discuss the memorization capacity of Transformers in other standard task settings.

3.1 PROBLEM SETTING

We consider the memorization of N input-output sequence pairs $(\boldsymbol{X}^{(1)}, \boldsymbol{Y}^{(1)}), \cdots, (\boldsymbol{X}^{(N)}, \boldsymbol{Y}^{(N)})$ where each input $\boldsymbol{X}^{(i)} \in \mathbb{R}^{d \times n}$ is a sequence of n token vectors in dimension d. Each output $\boldsymbol{Y}^{(i)} \in [C]^{1 \times n}$ is a sequence of n labels where each label $\boldsymbol{Y}^{(i)}[1, k]$ is assigned to a token $\boldsymbol{X}^{(i)}[:, k]$. We define the *context* of each input sequence $\boldsymbol{X}^{(i)}$ as $\mathcal{V}^{(i)} = \{\boldsymbol{v} \in \mathbb{R}^d : \boldsymbol{v} = \boldsymbol{X}^{(i)}[:, k] \text{ for some } k \in [n]\}$. We define the *vocabulary* $\mathcal{V} = \bigcup_{i \in [N]} \mathcal{V}^{(i)}$ as the set of all tokens appearing in the input sequences. Note that $|\mathcal{V}| \leq nN$.

As pointed out in Park et al. (2021) and Vardi et al. (2022), we must assume some conditions on the dataset to bypass the lower bound in Sontag (1997) and memorize N data points with $o(N)$ parameters. We present a natural generalization of the separation condition defined in Vardi et al. (2022) to sequence modeling settings.

Definition 3.1. Let $r \geq 1, 0 < \delta \leq 1$. Let $\boldsymbol{X}^{(1)}, \cdots, \boldsymbol{X}^{(N)} \in \mathbb{R}^{d \times n}$ be N input sequences with vocabulary $\mathcal{V}$. We say that $\boldsymbol{X}^{(1)}, \cdots, \boldsymbol{X}^{(N)}$ are tokenwise (r, δ)-separated if

1. $\|\boldsymbol{v}\| \leq r$ for all $\boldsymbol{v} \in \mathcal{V}$ and
2. $\|\boldsymbol{v} - \boldsymbol{v}'\| \geq \delta$ for all $\boldsymbol{v}, \boldsymbol{v}' \in \mathcal{V}$ with $\boldsymbol{v} \neq \boldsymbol{v}'$.

This condition requires (1) each token to have a bounded norm and (2) each pair of distinct tokens to be separated. We note that the tokenwise separation is a stronger condition than the separation of input sequences[2]. However, the condition better captures many practical settings where the number of tokens in the vocabulary is much smaller than the number of input sequences.

---

[1]We recall that m is the embedding dimension, h is the number of attention heads, k is the attention head size, and q is the feedforward dimension.

[2]When $\boldsymbol{X}^{(1)}, \cdots, \boldsymbol{X}^{(N)} \in \mathbb{R}^{d \times n}$ are distinct and (r, δ)-separated, then (1) $\|\boldsymbol{X}^{(i)}\|_F \leq r\sqrt{n}$ for $i \in [N]$ and (2) $\|\boldsymbol{X}^{(i)} - \boldsymbol{X}^{(j)}\|_F \geq \delta$ for $i, j \in [N]$ with $i \neq j$.

For the permutation equivariant mappings, we need the following label consistency condition.

Definition 3.2. Let $(\boldsymbol{X}^{(1)}, \boldsymbol{Y}^{(1)}), \cdots, (\boldsymbol{X}^{(N)}, \boldsymbol{Y}^{(N)}) \in \mathbb{R}^{d \times n} \times [C]^{1 \times n}$ be N input-output pairs of sequences. We say that $(\boldsymbol{X}^{(1)}, \boldsymbol{Y}^{(1)}), \cdots, (\boldsymbol{X}^{(N)}, \boldsymbol{Y}^{(N)})$ are consistently labeled if

$$\boldsymbol{X}^{(i)}[:, k] = \boldsymbol{X}^{(i)}[:, l] \text{ implies } \boldsymbol{Y}^{(i)}[:, k] = \boldsymbol{Y}^{(i)}[:, l]$$

for every $i \in [N]$ and $k, l \in [n]$.

We emphasize that we impose this condition only on the memorization with permutation equivariance but not on the memorization without permutation equivariance[3]. The condition implies that two identical tokens appearing in the same context should have the same label. Consider a permutation equivariant mapping $\mathcal{F}$ and an input sequence $\boldsymbol{X}$. Define $\boldsymbol{X}'$ by swapping two tokens $\boldsymbol{X}[:, k]$ and $\boldsymbol{X}[:, l]$ in $\boldsymbol{X}$. Then, we have $\mathcal{F}(\boldsymbol{X})[:, k] = \mathcal{F}(\boldsymbol{X}')[:, l]$ due to the permutation equivariance. However, if two tokens $\boldsymbol{X}[:, k]$ and $\boldsymbol{X}[:, l]$ were identical, then $\boldsymbol{X} = \boldsymbol{X}'$ and consequently $\mathcal{F}(\boldsymbol{X})[:, k] = \mathcal{F}(\boldsymbol{X})[:, l]$.

3.2 MAIN RESULTS

We now present our main theorem on the memorization capacity of Transformers.

Theorem 3.1. *Let $N, d, n, C \in \mathbb{N}$ and $r \geq 1, 0 < \delta \leq 1$. Let $(\boldsymbol{X}^{(1)}, \boldsymbol{Y}^{(1)}), \cdots, (\boldsymbol{X}^{(N)}, \boldsymbol{Y}^{(N)}) \in \mathbb{R}^{d \times n} \times [C]^{1 \times n}$ be N input-output sequence pairs of sequences where input sequences are distinct and tokenwise (r, δ)-separated.*

1. *(With permutation equivariance) Suppose that contexts $\mathcal{V}^{(i)}$ are distinct and sequences are consistently labeled. Then, there exists a Transformer network $\mathcal{N} : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ such that*

$$\mathcal{N}(\boldsymbol{X}^{(i)} \boldsymbol{P}) = \boldsymbol{Y}^{(i)} \boldsymbol{P}$$

   for every $i \in [N]$ and for every permutation matrix $\boldsymbol{P} \in \mathbb{R}^{n \times n}$.

2. *(Without permutation equivariance) There exists a Transformer network $\mathcal{N} : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ and positional encoding $\boldsymbol{E} \in \mathbb{R}^{d \times n}$ such that*

$$\mathcal{N}(\boldsymbol{X}^{(i)} + \boldsymbol{E}) = \boldsymbol{Y}^{(i)}$$

   for every $i \in [N]$.

In both cases, the Transformer $\mathcal{N}$ has width 16 ($m = 6$, $h = k = 1$ and $q = 16$), depth

$$O\left(n + \sqrt{nN \log(nN)} + \sqrt{\frac{nN}{\log(nN)} \cdot \max\{\log C, \log R\}}\right)$$

and bit complexity bounded by

$$O\left(\log d + \sqrt{\frac{nN}{\log(nN)} \cdot \max\{\log C, \log R\}}\right)$$

where we denote $R := 3000 r^2 \delta^{-2} dn^5 N^6$.

Theorem 3.1 shows that $\tilde{O}(d + n + \sqrt{nN})$ parameters are enough to memorize N sequence-to-sequence mapping of length n with token dimension d since the initial embedding layer has d parameters and the rest layers have a constant number of parameters. We provide the proof sketch in Section 3.3 and the full proof in Appendix A.

Remark 3.2. *Extensions to real vector outputs.* Some application scenarios of Transformers require real vector outputs. As proposed in Park et al. (2021) and Vardi et al. (2022), extension to real scalar values is easily achievable by using $O(\frac{1}{\epsilon})$ classes when the output has a bounded range. More concretely, we partition the output range into ϵ-length intervals and match each class to one partition to perform regression with error ϵ per token. This replaces $\log C$ in Theorem 3.1 with $\log(\frac{1}{\epsilon})$.

---

[3]The general sequence-to-sequence mappings do not satisfy the condition. For example, the same word appearing multiple times in a sentence may have different meanings.

Similarly, extension to vector outputs is possible when the output has a bounded domain. Suppose that we aim to minimize the tokenwise L2 distances in dimension p. We partition the output range into $\frac{\epsilon}{\sqrt{p}}$-length cubes and match each class to one cube. Then, we use $O\left(\left(\frac{\sqrt{p}}{\epsilon}\right)^p\right)$ classes to perform regression with error ϵ per token. This construction replaces $\log C$ in Theorem 3.1 with $p\log(\frac{p}{\epsilon})$.

Remark 3.3. *Large width and fixed bit complexity.* Theorem 3.1 uses fixed width and large bit complexity to minimize the number of parameters. However, a common approach to scaling Transformers is to increase width (Levine et al., 2020) while using the same number of bits per parameter. Using a similar argument as Vardi et al. (2022), we extend Theorem 3.1 to the cases with a larger width and with bounded bit complexity. When the larger width is allowed, Transformers of width $O(nN/L^2)$, depth $\tilde{O}(n+L)$ and bit complexity $\tilde{O}(L)$ memorize the same dataset for some $L \leq \sqrt{nN}$. When the bit complexity is bounded, Transformers of width $O(1)$, depth $\tilde{O}(n+nN/B)$ and bit complexity $\tilde{O}(B)$ memorize the same dataset for some $B \leq \sqrt{nN}$. We provide the formal theorem and the proof in Appendix B.

Remark 3.4. *Tightness in the order of bit counts.* Suppose the token dimension d and the sequence length n are both $O(N)$. Theorem 3.1 shows that a Transformer memorizes N input-output sequence pairs using $\tilde{O}(\sqrt{nN})$ parameters of bit complexity $\tilde{O}(\sqrt{nN})$, which sum up to $\tilde{O}(nN)$ bits. Without any additional assumption on a dataset, representing models that memorize all C^{nN} possible labels[4] for N input sequences requires $\Omega(nN)$ bits. Thus, Theorem 3.1 is tight upto logarithmic factors in the order of bit counts.

Remark 3.5. *Comparison against fully-connected ReLU networks.* With a slight modification of results in Vardi et al. (2022)[5], fully-connected ReLU networks require $\tilde{O}(dn + \sqrt{nN})$ parameters.

- The dependence on the number of data points N is the same as $\tilde{O}(\sqrt{nN})$. However, for the permutation equivariant case, Transformers memorize all permutations of each input sequence. That is, Transformers are capable of memorizing at most $n!$ times more data points at the cost of reusing each parameter n times[6].

- Our construction has a better dependence on d and n: $O(d+n)$ for Transformers and $O(dn)$ for fully-connected ReLU networks. Transformers exploit the structure of sequence data through parameter sharing. As a result, Transformers do not need $O(dn)$ parameters to read all dn values in the input sequence.

We note that this comparison is not completely fair because (1) our result makes a slightly stronger assumption of the separation between tokens than the separation between whole input; and (2) fully-connected networks are not designed for permutation equivariant datasets. However, the difference in assumption affects the final bound only to the logarithmic terms. Furthermore, there is no known result on the memorization capacity of other permutation equivariant architectures.

3.3 PROOF SKETCH

We outline the proof of Theorem 3.1. A more formal statement of each stage with detailed proof is in Appendix A. Our proof adopts the approach from Vardi et al. (2022) and shares similar steps. We discuss our technical novelty after sketching the main ideas of our proof.

Our proof constructs a Transformer in 4 stages. The first two stages assemble contextual token ids that encode the identity of corresponding tokens and sequences. We ensure that contextual token ids are well separated and permutation equivariant. The last two stages map each contextual token id to the corresponding token label. We describe key ideas of each stage.

- **Stage 1. Tokenwise Projection.** We project each token vector to a scalar token id while keeping distinct tokens well separated.

---

[4]There are C possible labels for n tokens in N sequences.

[5]We consider inputs as dn-dimensional flattened vectors and outputs as values from $[C^n]$. We choose a different balancing point between stages 2 and 3 in their construction to balance the extra factors.

[6]A similar benefit of Transformers has been previously observed in the function approximation (Yun et al., 2020a): the number of parameters is reduced by $(n-1)!$ times to successfully approximate permutation equivariant functions.

- **Stage 2. Contextual Mapping.** We collect token ids in decreasing order of magnitude and linearly combine them into a sequence id. The sequence ids are permutation invariant, but an appropriate choice of positional encoding bypasses permutation invariance by collecting token ids in the position order. We compose the token id and the sequence id to obtain a contextual token id.

- **Stage 3. String Lookup.** We partition all nN contextual token ids into intervals, each containing the same number of ids. We construct two encoding numbers for each interval by concatenating all corresponding contextual token ids and token labels. Then, we find which group the contextual token id falls into and retrieve the corresponding encoding numbers.

- **Stage 4. Bit Extraction.** We extract each contextual token id and token label from the encoding numbers. If the extracted contextual token id agrees with the one composed in stage 2, then we output the corresponding token label.

Our technical novelty in this proof is in (1) the implementation of the contextual mapping in stage 2 using self-attention subblocks and (2) generalizing stages 3 and 4 to incorporate skip connections.

Remark 3.6. *Contextual mapping.* The number of self-attention subblocks that our proof uses is proportional to the length of the sequence n but independent of the number of data points N. This requirement is in striking contrast to the selective-shifting-based contextual mapping from Yun et al. (2020a), which requires the number of self-attention subblocks equal to the number of distinct token values. In our setting, the selective-shifting-based contextual mapping would need nN self-attention subblocks, which alone is already larger than the number of required layers in our result. We showcase the benefit of our contextual mapping in Appendix C. Specifically, we show that our contextual mapping are capable of incorporating sparse self-attention settings with minimal parameter overhead. Moreover, we show that the same idea of our contextual mapping can be applied in the function approximation setting.

Remark 3.7. *Parameter contribution.* In our construction, self-attention subblocks contribute only $O(n)$ parameters while feedforward subblocks contribute $O(\sqrt{nN})$. When $n < N$, most of the parameter count comes from feedforward subblocks. Although the self-attention layers play a critical role in contextual mapping, we do not need many of them. This explains the model design in practice, where more than half of the parameters are in the tokenwise feedforward subblocks (Vaswani et al., 2017; Devlin et al., 2019; Brown et al., 2020; Geva et al., 2021). Moreover, Mandava et al. (2020) observes that the self-attention layers can be further reduced without much performance loss.

4 MEMORIZATION CAPACITY IN OTHER TASKS

In this section, we generalize Theorem 3.1 to analyze the memorization capacity for other standard task settings. We consider sequence classification task.

4.1 SEQUENCE CLASSIFICATION

In sequence classification, we assign a single label $y^{(i)} \in [C]$ for each input sequence $\boldsymbol{X}^{(i)}$. We present our theorem for sequence classification task.

Theorem 4.1. *Let $N, d, n, C \in \mathbb{N}$ and $r \geq 1, 0 < \delta \leq 1$. Let $(\boldsymbol{X}^{(1)}, y^{(1)}), \cdots, (\boldsymbol{X}^{(N)}, y^{(N)}) \in \mathbb{R}^{d \times n} \times [C]$ be N input-output pairs of sequences where input sequences are distinct and tokenwise (r, δ)-separated.*

1. *(With permutation invariance) Suppose that contexts $\mathcal{V}^{(i)}$ are distinct. Then, there exists a Transformer network $\mathcal{N} : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ such that*

$$\mathcal{N}(\boldsymbol{X}^{(i)}\boldsymbol{P})[1, k] = y^{(i)}$$

for every $i \in [N], k \in [n]$ and for every permutation matrix $\boldsymbol{P} \in \mathbb{R}^{n \times n}$.

2. *(Without permutation invariance) There exists a Transformer network $\mathcal{N} : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ and positional encoding $\boldsymbol{E} \in \mathbb{R}^{d \times n}$ such that*

$$\mathcal{N}(\boldsymbol{X}^{(i)} + \boldsymbol{E})[1, k] = y^{(i)}$$

for every $i \in [N], k \in [n]$.

(a) Token Classification (b) Sequence Classification

Figure 1: Heatmaps of Train Errors. The values of the x-axis are the hidden sizes of BERT. Y-axis indicates the number of training samples. Subfigure 1a shows the results of token classification. The model size is incremented by the size of 12. Subfigure 1b is the heatmap of sequence classification, where the size increases by 96.

In both cases, the Transformer $\mathcal{N}$ has width 16 ($m = 6$, $h = k = 1$ and $q = 16$), depth

$$O\left(n + \sqrt{N \log N} + \sqrt{\frac{N}{\log N} \cdot \max\{\log C, \log R\}}\right)$$

and bit complexity bounded by

$$O\left(\log d + \sqrt{\frac{N}{\log N} \cdot \max\{\log C, \log R\}}\right)$$

where we denote $R := 3000 r^2 \delta^{-2} d n^5 N^6$.

Theorem 4.1 shows that $\tilde{O}(d + n + \sqrt{N})$ parameters are enough to memorize N sequence classification examples of length n with token dimension d. Compared to the sequence-to-sequence mapping, there is $\sqrt{n}$ factor of saving in the last term. We provide the full proof of Theroem 4.1 in Appendix D.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETUP

We perform the experiments on Transformers with BERT Devlin et al. (2019) to validate our theory. We consider token classification where each token is assigned a label as in Theorem 3.1 and sequence classification where entire sequence is assigned a label as in Theorem 4.1 We scale the size of the network with the hidden size and set the number of layers as 6, the self-attention heads as 12. The model is trained for 1,500 gradient steps for the token classification and 7,500 steps for the sequence classification, with 10% drop-out rate. For optimization, we use Adam optimizer with a learning rate of 0.00002. See Appendix F for the details.

5.2 RESULTS

We study the training errors of the model of increasing size and of increasing number of training data when trained to completion. As expected, Figures 1 show that the smaller training data size requires a smaller model size for memorization and display the boundary of convergence that supports our theory. To get a clearer perspective on the convergence boundary, we plot the number of model parameters at convergence for each training data size in Figures 2. We observe the square root relation between the training data size and the model size in the beginning. However, as the data size

(a) Token Classification   (b) Sequence Classification

Figure 2: Scatter Plots of Convergence. The x-axis indicates the number of training samples, and the y-axis is the number of parameters, i.e., the model size. Given a set number of training samples, we measure the number of parameters of the model that reaches convergence.

Figure 3: Entropy of Parameters at Convergence. For the token classification, we compute the entropy of the model parameters at the point of convergence.

increases, we notice a plateau and then a linear relationship. We conjecture that this phenomenon occurs due the fixed depth and bit complexity during the experiments (See Remark 3.3). To support our claim, we measure the parameters' size of the model at convergence by computing their entropy. As shown in Figure 3, the decrease in the parameters' entropy is observed, which implies that the bit complexity is not increasing as required by our theory.

6   CONCLUSIONS

In this paper, we prove that Transformers are capable of memorizing N length-n sequence-to-sequence mappings with $\tilde{O}(d + n + \sqrt{nN})$ parameters. We extend our theory to analyze the memorization capacity of Transformers in other standard task settings. Our proof constructs a contextual mapping with $O(n)$ self-attention layers, which significantly improves the previously proposed selective-shifting-based in parameter efficiency. Finally, we provide experimental results that verify our theory.

REFERENCES

Hassan Akbari, Liangzhe Yuan, Rui Qian, Wei-Hong Chuang, Shih-Fu Chang, Yin Cui, and Boqing Gong. Vatt: Transformers for multimodal self-supervised learning from raw video, audio and text. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 24206–24221. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/file/cb3213ada48302953cb0f166464ab356-Paper.pdf.

Peter L. Bartlett, Nick Harvey, Christopher Liaw, and Abbas Mehrabian. Nearly-tight vc-dimension and pseudodimension bounds for piecewise linear neural networks. *Journal of Machine Learning*

Research, 20(63):1–17, 2019. URL `http://jmlr.org/papers/v20/17-612.html`.

Eric B Baum. On the capabilities of multilayer perceptrons. *Journal of Complexity*, 4(3):193–215, 1988. ISSN 0885-064X. doi: https://doi.org/10.1016/0885-064X(88)90020-9. URL `https://www.sciencedirect.com/science/article/pii/0885064X88900209`.

Mikhail Belkin, Daniel Hsu, Siyuan Ma, and Soumik Mandal. Reconciling modern machine-learning practice and the classical bias-variance trade-off. *Proceedings of the National Academy of Sciences*, 116(32):15849–15854, 2019. doi: 10.1073/pnas.1903070116. URL `https://www.pnas.org/doi/abs/10.1073/pnas.1903070116`.

Gedas Bertasius, Heng Wang, and Lorenzo Torresani. Is space-time attention all you need for video understanding? In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 813–824. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/bertasius21a.html`.

Srinadh Bhojanapalli, Chulhee Yun, Ankit Singh Rawat, Sashank Reddi, and Sanjiv Kumar. Low-rank bottleneck in multi-head attention models. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 864–873. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/bhojanapalli20a.html`.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf`.

Sebastien Bubeck, Ronen Eldan, Yin Tat Lee, and Dan Mikulincer. Network size and size of the weights in memorization with two-layers neural networks. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 4977–4986. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/34609bdc08a07ace4e1526bbb1777673-Paper.pdf`.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 15084–15097. Curran Associates, Inc., 2021. URL `https://proceedings.neurips.cc/paper/2021/file/7f489f642a0ddb10272b5c31057f0663-Paper.pdf`.

Mostafa Dehghani, Stephan Gouws, Oriol Vinyals, Jakob Uszkoreit, and Lukasz Kaiser. Universal transformers. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=HyzdRiR9Y7`.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://aclanthology.org/N19-1423`.

Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: pure attention loses rank doubly exponentially with depth. In Marina Meila and Tong Zhang (eds.),

Proceedings of the 38th International Conference on Machine Learning, volume 139 of *Proceedings of Machine Learning Research*, pp. 2793–2803. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/dong21a.html`.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=YicbFdNTTy`.

Benjamin L Edelman, Surbhi Goel, Sham Kakade, and Cyril Zhang. Inductive biases and variable creation in self-attention mechanisms. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 5793–5831. PMLR, 17–23 Jul 2022. URL `https://proceedings.mlr.press/v162/edelman22a.html`.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022. URL `http://jmlr.org/papers/v23/21-0998.html`.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 5484–5495, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.446. URL `https://aclanthology.org/2021.emnlp-main.446`.

Moritz Hardt and Tengyu Ma. Identity matters in deep learning. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=ryxB0Rtxx`.

Guang-Bin Huang. Learning capability and storage capacity of two-hidden-layer feedforward networks. *IEEE Transactions on Neural Networks*, 14(2):274–281, 2003. doi: 10.1109/TNN.2003.809401.

Guang-Bin Huang and H.A. Babri. Upper bounds on the number of hidden neurons in feedforward networks with arbitrary bounded nonlinear activation functions. *IEEE Transactions on Neural Networks*, 9(1):224–229, 1998. doi: 10.1109/72.655045.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 1273–1286. Curran Associates, Inc., 2021. URL `https://proceedings.neurips.cc/paper/2021/file/099fe6b0b444c23836c4a5d07346082b-Paper.pdf`.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

Hyunjik Kim, George Papamakarios, and Andriy Mnih. The lipschitz constant of self-attention. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5562–5571. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/kim21i.html`.

Anastasis Kratsios, Behnoosh Zamanlooy, Tianlin Liu, and Ivan Dokmanić. Universal approximation under constraints is possible with transformers. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=JGO8CvG5S9`.

Yoav Levine, Noam Wies, Or Sharir, Hofit Bata, and Amnon Shashua. Limits to depth efficiencies of self-attention. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 22640–22651. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/ff4dfdf5904e920ce52b48c1cef97829-Paper.pdf`.

Valerii Likhosherstov, Krzysztof Choromanski, and Adrian Weller. On the expressive power of self-attention matrices. *CoRR*, abs/2106.03764, 2021. URL `https://arxiv.org/abs/2106.03764`.

Ilya Loshchilov and Frank Hutter. Fixing weight decay regularization in adam. *CoRR*, abs/1711.05101, 2017. URL `http://arxiv.org/abs/1711.05101`.

Swetha Mandava, Szymon Migacz, and Alex Fit-Florea. Pay attention when required. *CoRR*, abs/2009.04534, 2020. URL `https://arxiv.org/abs/2009.04534`.

Preetum Nakkiran, Gal Kaplun, Yamini Bansal, Tristan Yang, Boaz Barak, and Ilya Sutskever. Deep double descent: where bigger models and more data hurt. *Journal of Statistical Mechanics: Theory and Experiment*, 2021(12):124003, dec 2021. doi: 10.1088/1742-5468/ac3a74. URL `https://doi.org/10.1088/1742-5468/ac3a74`.

Quynh Nguyen and Matthias Hein. Optimization landscape and expressivity of deep CNNs. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 3730–3739. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/nguyen18a.html`.

Emilio Parisotto, Francis Song, Jack Rae, Razvan Pascanu, Caglar Gulcehre, Siddhant Jayakumar, Max Jaderberg, Raphaël Lopez Kaufman, Aidan Clark, Seb Noury, Matthew Botvinick, Nicolas Heess, and Raia Hadsell. Stabilizing transformers for reinforcement learning. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 7487–7498. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/parisotto20a.html`.

Sejun Park, Jaeho Lee, Chulhee Yun, and Jinwoo Shin. Provable memorization via deep neural networks using sub-linear parameters. In Mikhail Belkin and Samory Kpotufe (eds.), *Proceedings of Thirty Fourth Conference on Learning Theory*, volume 134 of *Proceedings of Machine Learning Research*, pp. 3627–3661. PMLR, 15–19 Aug 2021. URL `https://proceedings.mlr.press/v134/park21a.html`.

Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Lukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. Image transformer. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 4055–4064. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/parmar18a.html`.

Stanislas Polu and Ilya Sutskever. Generative language modeling for automated theorem proving. *CoRR*, abs/2009.03393, 2020. URL `https://arxiv.org/abs/2009.03393`.

Jorge Pérez, Javier Marinković, and Pablo Barceló. On the turing completeness of modern neural network architectures. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=HyGBdo0qFm`.

Shashank Rajput, Kartik Sreenivasan, Dimitris Papailiopoulos, and Amin Karbasi. An exponential improvement on the memorization capacity of deep threshold networks. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 12674–12685. Curran Associates, Inc., 2021. URL `https://proceedings.neurips.cc/paper/2021/file/69dd2eff9b6a421d5ce262b093bdab23-Paper.pdf`.

Eduardo D. Sontag. Shattering All Sets of 'k' Points in "General Position" Requires (k — 1)/2 Parameters. *Neural Computation*, 9(2):337–348, 02 1997. ISSN 0899-7667. doi: 10.1162/neco.1997.9.2.337. URL `https://doi.org/10.1162/neco.1997.9.2.337`.

Erik F. Tjong Kim Sang and Fien De Meulder. Introduction to the CoNLL-2003 shared task: Language-independent named entity recognition. In *Proceedings of the Seventh Conference on Natural Language Learning at HLT-NAACL 2003*, pp. 142–147, 2003. URL `https://aclanthology.org/W03-0419`.

Gal Vardi, Gilad Yehudai, and Ohad Shamir. On the optimal memorization power of reLU neural networks. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=MkTPtnjeYTV.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

Roman Vershynin. Memory capacity of neural networks with threshold and rectified linear unit activations. *SIAM Journal on Mathematics of Data Science*, 2(4):1004–1033, 2020. doi: 10.1137/20M1314884. URL https://doi.org/10.1137/20M1314884.

James Vuckovic, Aristide Baratin, and Remi Tachet des Combes. A mathematical theory of attention. *CoRR*, abs/2007.02876, 2020. URL https://arxiv.org/abs/2007.02876.

Colin Wei, Yining Chen, and Tengyu Ma. Statistically meaningful approximation: a case study on approximating turing machines with transformers. *CoRR*, abs/2107.13163, 2021. URL https://arxiv.org/abs/2107.13163.

Noam Wies, Yoav Levine, Daniel Jannai, and Amnon Shashua. Which transformer architecture fits my data? a vocabulary bottleneck in self-attention. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 11170–11181. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/wies21a.html.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/dc6a7e655d7e5840e66733e9ee67cc69-Paper.pdf.

Chulhee Yun, Suvrit Sra, and Ali Jadbabaie. Small relu networks are powerful memorizers: a tight analysis of memorization capacity. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/dbea3d0e2a17c170c412c74273778159-Paper.pdf.

Chulhee Yun, Srinadh Bhojanapalli, Ankit Singh Rawat, Sashank Reddi, and Sanjiv Kumar. Are transformers universal approximators of sequence-to-sequence functions? In *International Conference on Learning Representations*, 2020a. URL https://openreview.net/forum?id=ByxRM0Ntvr.

Chulhee Yun, Yin-Wen Chang, Srinadh Bhojanapalli, Ankit Singh Rawat, Sashank Reddi, and Sanjiv Kumar. O(n) connections are expressive enough: Universal approximability of sparse transformers. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 13783–13794. Curran Associates, Inc., 2020b. URL https://proceedings.neurips.cc/paper/2020/file/9ed27554c893b5bad850a422c3538c15-Paper.pdf.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, and Amr Ahmed. Big bird: Transformers for longer sequences. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 17283–17297. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/c8512d142a2d849725f31a9a7a361ab9-Paper.pdf.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Sy8gdB9xx&.

Hengshuang Zhao, Li Jiang, Jiaya Jia, Philip H.S. Torr, and Vladlen Koltun. Point transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 16259–16268, October 2021.

Sixiao Zheng, Jiachen Lu, Hengshuang Zhao, Xiatian Zhu, Zekun Luo, Yabiao Wang, Yanwei Fu, Jianfeng Feng, Tao Xiang, Philip H.S. Torr, and Li Zhang. Rethinking semantic segmentation from a sequence-to-sequence perspective with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6881–6890, June 2021.

A   PROOF OF THEOREM 3.1

Our proof of Theorem 3.1 consists of four stages as described in Section 3.3. We state and prove the main lemma for each stage in the following subsections. Then, we combine all stages in the end. The lemmas in each stage assumes permutation equivariance. We analyze how to circumvent permutation equivariance through the positional encoding in a separate subsection.

A.1   STAGE 1: TOKENWISE PROJECTION

The main lemma for stage 1 is stated below.

Lemma A.1. *Let $N, d, n \in \mathbb{N}$ and $r \geq 1, 0 < \delta \leq 1$. Let $\boldsymbol{X}^{(1)}, \cdots, \boldsymbol{X}^{(N)} \in \mathbb{R}^{d \times n}$ be a set of N input sequences that are distinct and tokenwise (r, δ)-separated. Denote $r' = \lceil 6rn^2 N^2 \sqrt{\pi d} \delta^{-1} \rceil$.*

Then, there exists a network $\mathcal{N}_1 : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ consisting of the input embedding block and one tokenwise feedforward subblock with feedforward dimension $q = 1$ and bit complexity $\lceil \log(4rn^2 N^2 d\sqrt{\pi} \delta^{-1}) \rceil$ such that $\mathcal{N}_1(\boldsymbol{X}^{(i)}), i \in [N]$ are tokenwise $(r', 2)$-separated. Moreover, for $i, j \in [N]$ and $k, l \in [n]$,

$$\mathcal{N}_1(\boldsymbol{X}^{(i)})[1, k] = \mathcal{N}_1(\boldsymbol{X}^{(j)})[1, l] \text{ if and only if } \boldsymbol{X}^{(i)}[:, k] = \boldsymbol{X}^{(j)}[:, l].$$

Proof. Our proof defines a vector $\boldsymbol{u} \in \mathbb{R}^d$ such that sequences $\boldsymbol{x}^{(i)} = \boldsymbol{u}^T \boldsymbol{X}^{(i)} \in \mathbb{R}^{1 \times n}, i \in [N]$ are tokenwise $(r', 2)$-separated and satisfy that, for $i, j \in [N]$ and $k, l \in [n]$,

$$\boldsymbol{x}^{(i)}[1, k] = \boldsymbol{x}^{(j)}[1, l] \text{ if and only if } \boldsymbol{X}^{(i)}[:, k] = \boldsymbol{X}^{(j)}[:, l]$$

Then, we construct the network $\mathcal{N}_1$ with the required size and bit complexity that computes $\mathcal{N}_1(\boldsymbol{X}) = \boldsymbol{u}^T \boldsymbol{X}$.

Construction of $\boldsymbol{u}$.   Recall the definition of the vocabulary $\mathcal{V} = \bigcup_{i \in [N]} \mathcal{V}^{(i)} = \{\boldsymbol{v} \in \mathbb{R}^d : \boldsymbol{v} = \boldsymbol{X}^{(i)}[:, k] \text{ for some } i \in [N], k \in [n]\}$. Note that $|\mathcal{V}| \leq nN$. We use Lemma E.1 on $\mathcal{V}$ to find $\tilde{\boldsymbol{u}}$ such that

$$\frac{1}{n^2 N^2} \sqrt{\frac{8}{\pi d}} \|\boldsymbol{v} - \boldsymbol{v}'\| \leq \frac{1}{|\mathcal{V}|^2} \sqrt{\frac{8}{\pi d}} \|\boldsymbol{v} - \boldsymbol{v}'\| \leq \left| \tilde{\boldsymbol{u}}^T (\boldsymbol{v} - \boldsymbol{v}') \right| \leq \|\boldsymbol{v} - \boldsymbol{v}'\|$$

for every $\boldsymbol{v}, \boldsymbol{v}' \in \mathcal{V}$.

Let $\hat{\boldsymbol{u}} \in \mathbb{R}^d$ be a vector with each coordinate being the first $\lceil \log(n^2 N^2 d\sqrt{\pi}) \rceil$ bits of the corresponding coordinate of $\tilde{\boldsymbol{u}}$. We note that $\|\hat{\boldsymbol{u}} - \tilde{\boldsymbol{u}}\| \leq \frac{\sqrt{d}}{2^{\log(n^2 N^2 d\sqrt{\pi})}} = \frac{1}{n^2 N^2} \sqrt{\frac{1}{\pi d}}$.

Define $\boldsymbol{u} = S\hat{\boldsymbol{u}}$ with $S = \lceil 2n^2 N^2 \sqrt{\pi d} \delta^{-1} \rceil \geq 2$. We now check that $\boldsymbol{x}^{(i)} = \boldsymbol{u}^T \boldsymbol{X}^{(i)}, i \in [N]$ are tokenwise $(r', 2)$-separated with $r' = \lceil 6rn^2 N^2 \sqrt{\pi d} \delta^{-1} \rceil$. Let $i, j \in [N], k, l \in [n]$ with $\boldsymbol{X}^{(i)}[:, k] \neq \boldsymbol{X}^{(j)}[:, l]$ and $\boldsymbol{v}, \boldsymbol{v}' \in \mathcal{V}$ with $\boldsymbol{v} = \boldsymbol{X}^{(i)}[:, k], \boldsymbol{v}' = \boldsymbol{X}^{(j)}[:, l]$. Then, we have

$$
\begin{aligned}
\left| \boldsymbol{x}^{(i)}[1, k] \right| &= \left| \boldsymbol{u}^T \boldsymbol{X}^{(i)}[:, k] \right| \\
&= S \left| \hat{\boldsymbol{u}}^T \boldsymbol{v} \right| \\
&\leq S \left(\left| \tilde{\boldsymbol{u}}^T \boldsymbol{v} \right| + \left| (\hat{\boldsymbol{u}} - \tilde{\boldsymbol{u}})^T \boldsymbol{v} \right| \right) \\
&\leq S \left(\|\boldsymbol{v}\| + \frac{1}{n^2 N^2} \sqrt{\frac{1}{\pi d}} \|\boldsymbol{v}\| \right) \\
&\leq 2S \|\boldsymbol{v}\| \\
&\leq 2Sr \\
&= 4rn^2 N^2 \sqrt{\pi d} \delta^{-1} + 2r \leq 6rn^2 N^2 \sqrt{\pi d} \delta^{-1} \leq r'.
\end{aligned}
$$

We also have

$$
\begin{aligned}
\left| \boldsymbol{x}^{(i)}[1,k] - \boldsymbol{x}^{(j)}[1,l] \right| &= \left| \boldsymbol{u}^T(\boldsymbol{X}^{(i)}[:,k] - \boldsymbol{X}^{(j)}[:,l]) \right| \\
&= S \left| \hat{\boldsymbol{u}}^T(\boldsymbol{v} - \boldsymbol{v}') \right| \\
&\geq S \left(\left| \tilde{\boldsymbol{u}}^T(\boldsymbol{v} - \boldsymbol{v}') \right| - \left| (\hat{\boldsymbol{u}} - \tilde{\boldsymbol{u}})^T(\boldsymbol{v} - \boldsymbol{v}') \right| \right) \\
&\geq S \left(\frac{1}{n^2 N^2} \sqrt{\frac{8}{\pi d}} \| \boldsymbol{v} - \boldsymbol{v}' \| - \frac{1}{n^2 N^2} \sqrt{\frac{1}{\pi d}} \| \boldsymbol{v} - \boldsymbol{v}' \| \right) \\
&\geq S \frac{1}{n^2 N^2} \sqrt{\frac{1}{\pi d}} \| \boldsymbol{v} - \boldsymbol{v}' \| \\
&\geq S \frac{1}{n^2 N^2} \sqrt{\frac{1}{\pi d}} \delta \geq 2,
\end{aligned}
$$

which also implies

$$
\boldsymbol{x}^{(i)}[1,k] = \boldsymbol{x}^{(j)}[1,l] \text{ if and only if } \boldsymbol{X}^{(i)}[:,k] = \boldsymbol{X}^{(j)}[:,l].
$$

Construction of $\mathcal{N}_1$. We construct $\mathcal{N}_1$ as a composition of the input embedding block $\mathcal{E}_{in}$: $\mathbb{R}^{n \times d} \to \mathbb{R}^{1 \times n}$ and a tokenwise feedforward block $\mathcal{F}^{(FF)} : \mathbb{R}^{1 \times n} \to \mathbb{R}^{1 \times n}$ with a skip-connection. We define $\mathcal{E}_{in}(\boldsymbol{X}) = \hat{\boldsymbol{u}}^T \boldsymbol{X}$ and

$$
\mathcal{F}^{(FF)}(\boldsymbol{z}) = \boldsymbol{z} + (S-1)\sigma_R(\boldsymbol{z} + 2\lceil r \rceil \mathbf{1}_n^T) - 2\lceil r \rceil (S-1)\mathbf{1}_n^T.
$$

Then, we have

$$
\begin{aligned}
\mathcal{N}_1(\boldsymbol{X}) &= \mathcal{F}^{(FF)}(\mathcal{E}_{in}(\boldsymbol{X})) \\
&= \hat{\boldsymbol{u}}^T \boldsymbol{X} + (S-1)\sigma_R(\hat{\boldsymbol{u}}^T \boldsymbol{X} + 2\lceil r \rceil \mathbf{1}_n^T) - 2\lceil r \rceil (S-1)\mathbf{1}_n^T \\
&= \hat{\boldsymbol{u}}^T \boldsymbol{X} + (S-1)(\hat{\boldsymbol{u}}^T \boldsymbol{X} + 2\lceil r \rceil \mathbf{1}_n^T) - 2\lceil r \rceil (S-1)\mathbf{1}_n^T \\
&= S\hat{\boldsymbol{u}}^T \boldsymbol{X} = \boldsymbol{u}^T \boldsymbol{X},
\end{aligned}
$$

where we removed the ReLU activation because $\hat{\boldsymbol{u}}^T \boldsymbol{X} + 2\lceil r \rceil \mathbf{1}_n^T$ have all positive values. Therefore, we conclude $\mathcal{N}_1(\boldsymbol{X}^{(i)}) = \boldsymbol{u}^T \boldsymbol{X}^{(i)} = \boldsymbol{x}^{(i)}$.

It is straightforward from the definition of $\mathcal{F}^{(FF)}$ that the feedforward dimension of the network is 1. Moreover, we can represent each coordinate of $\hat{\boldsymbol{u}}$ with $\lceil \log(n^2 N^2 d\sqrt{\pi}) \rceil$ bits, the weights in $\mathcal{F}^{(FF)}$ with $\lceil \log S \rceil = \lceil \log(2n^2 N^2 \sqrt{\pi d} \delta^{-1}) \rceil$ bits, and the biases in $\mathcal{F}^{(FF)}$ with $\lceil \log(2\lceil r \rceil (S-1)) \rceil$ bits. Thus, the bit complexity of the network $\mathcal{N}_1$ is $\lceil \log(4rn^2 N^2 d\sqrt{\pi} \delta^{-1}) \rceil$. □

A.2 STAGE 2: CONTEXTUAL MAPPING

Before proceeding on to the stage 2, we reindex the tokens of each output from Lemma A.1. Due to the permutation equivariance of the Transformer architecture, we may reorder tokens in any order as we want without loss of generality.

For each $i \in [N]$, we consider $\boldsymbol{x}^{(i)} \in \mathbb{R}^n$ as a vector and reindex as follows. Suppose that there are n_i unique tokens in $\boldsymbol{X}^{(i)}$. Then, there are also n_i unique values in $\boldsymbol{x}^{(i)}$. We assign indices for tokens so that the first n_i tokens have n_i unique values of $\boldsymbol{x}^{(i)}$ in descending order:

$$
\boldsymbol{x}^{(i)}[1,1] > \boldsymbol{x}^{(i)}[1,2] > \cdots > \boldsymbol{x}^{(i)}[1,n_i].
$$

Then, we index the remaining redundant tokens in descending order:

$$
\boldsymbol{x}^{(i)}[1,n_i+1] \geq \boldsymbol{x}^{(i)}[1,n_i+2] \geq \cdots \geq \boldsymbol{x}^{(i)}[1,n].
$$

We note that the resulting vector $\boldsymbol{x}^{(i)}$ is uniquely defined. That is, $\boldsymbol{X}^{(i)}$ corresponds to one and only one valid resulting vector $\boldsymbol{x}^{(i)}$.

We need the following definition in this section.

Definition A.1. Let $N, n \in \mathbb{N}$ and $r \geq 1, 0 < \delta \leq 1$. Let $\boldsymbol{x}^{(1)}, \cdots, \boldsymbol{x}^{(N)} \in \mathbb{R}^n$ be N data instances. We say that $\boldsymbol{x}^{(1)}, \cdots, \boldsymbol{x}^{(N)}$ are (r, δ)-separated if

- $\|\boldsymbol{x}^{(i)}\| \leq r$ for all $i \in [N]$ and
- $\|\boldsymbol{x}^{(i)} - \boldsymbol{x}^{(j)}\| \geq \delta$ for all $i, j \in [N]$ with $i \neq j$.

We now state the main lemma for stage 2.

Lemma A.2. *Let $N, n, r' \in \mathbb{N}$. Let $\boldsymbol{x}^{(1)}, \cdots, \boldsymbol{x}^{(N)} \in \mathbb{R}^n$ be a set of N input sequences that are tokenwise $(r', 2)$-separated. Denote $R' = \lceil 6r'nN^2\sqrt{\pi} \rceil$.*

Then, there exists a network $\mathcal{N}_2 : \mathbb{R}^{3 \times n} \to \mathbb{R}^{3 \times n}$ consisting of $2n$ Transformer blocks with the number of head $h = 1$, head size $k = 1$, feedforward dimension $q = 4$ and bit complexity $\lceil \log(2r'nN^2\sqrt{\pi}) \rceil$ such that

$$\mathcal{N}_2 \left(\begin{bmatrix} \boldsymbol{x}^{(i)T} \\ \mathbf{0}_n^T \\ \mathbf{0}_n^T \end{bmatrix} \right) = \begin{bmatrix} \mathbf{0}_n^T \\ \mathbf{0}_n^T \\ z^{(i)}\mathbf{1}_n^T \end{bmatrix}$$

where $z^{(i)} \in \mathbb{R}, i \in [N]$ are $(R' + 1, 2)$-separated.

Proof. Our proof defines a vector $\boldsymbol{w} \in \mathbb{R}^n$ such that values $\tilde{z}^{(i)} = \boldsymbol{w}[1 : n_i]^T \boldsymbol{x}^{(i)}[1 : n_i] \in \mathbb{R}, i \in [N]$ are $(R', 4)$-separated where we denote the number of unique values in $\boldsymbol{x}^{(i)}$ as n_i. Then, we construct the network $\mathcal{N}_2$ with the required size and bit complexity that computes

$$\mathcal{N}_2 \left(\begin{bmatrix} \boldsymbol{x}^{(i)T} \\ \mathbf{0}_n^T \\ \mathbf{0}_n^T \end{bmatrix} \right) = \begin{bmatrix} \mathbf{0}_n^T \\ \mathbf{0}_n^T \\ z^{(i)}\mathbf{1}_n^T \end{bmatrix}$$

where $z^{(i)}$ approximates $\tilde{z}^{(i)}$ within 1 as

$$\left| z^{(i)} - \tilde{z}^{(i)} \right| \leq 1.$$

Since we have

$$\left| z^{(i)} \right| \leq \left| \tilde{z}^{(i)} \right| + \left| z^{(i)} - \tilde{z}^{(i)} \right| \leq R' + 1$$

for $i \in [N]$ and

$$\left| z^{(i)} - z^{(j)} \right| \geq \left| \tilde{z}^{(i)} - \tilde{z}^{(j)} \right| - \left| z^{(i)} - \tilde{z}^{(i)} \right| - \left| z^{(j)} - \tilde{z}^{(j)} \right| \geq 4 - 1 - 1 = 2$$

for $i, j \in [N]$ with $i \neq j$, we conclude that $z^{(i)} \in \mathbb{R}, i \in [N]$ are $(R' + 1, 2)$-separated.

Construction of $\boldsymbol{w}$. For $i \in [N]$, we define $\tilde{\boldsymbol{x}}^{(i)} \in \mathbb{R}^n$ as a vector having the same values as $\boldsymbol{x}^{(i)}$ in the first n_i coordinates and 0 in the rest. We use Lemma E.1 on $\tilde{\boldsymbol{x}}^{(1)}, \tilde{\boldsymbol{x}}^{(2)}, \cdots, \tilde{\boldsymbol{x}}^{(N)}$ to find $\tilde{\boldsymbol{w}}$ such that

$$\frac{1}{N^2} \sqrt{\frac{8}{\pi n}} \|\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)}\| \leq \left| \tilde{\boldsymbol{w}}^T \left(\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)} \right) \right| \leq \|\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)}\|$$

for every $i, j \in [N]$.

Let $\hat{\boldsymbol{w}} \in \mathbb{R}^d$ be a vector with each coordinate being the first $\lceil \log(nN^2\sqrt{\pi}) \rceil$ bits of the corresponding coordinate of $\tilde{\boldsymbol{w}}$. We note that $\|\hat{\boldsymbol{w}} - \tilde{\boldsymbol{w}}\| \leq \frac{\sqrt{n}}{2^{\log(nN^2\sqrt{\pi})}} = \frac{1}{N^2}\sqrt{\frac{1}{\pi n}}$.

Define $\boldsymbol{w} = P\hat{\boldsymbol{w}}$ with $P = \lceil 2N^2\sqrt{\pi n}\rceil$. We now check that $\tilde{z}^{(i)} = \boldsymbol{w}[1:n_i]^T\boldsymbol{x}^{(i)}[1:n_i] = \boldsymbol{w}^T\tilde{\boldsymbol{x}}^{(i)}, i \in [N]$ are $(R', 4)$-separated. Let $i, j \in [N]$ with $i \neq j$. Then, we have

$$
\begin{aligned}
\left|\tilde{z}^{(i)}\right| &= \left|\boldsymbol{w}^T\tilde{\boldsymbol{x}}^{(i)}\right| \\
&= P\left|\hat{\boldsymbol{w}}^T\tilde{\boldsymbol{x}}^{(i)}\right| \\
&\leq P\left(\left|\tilde{\boldsymbol{w}}^T\tilde{\boldsymbol{x}}^{(i)}\right| + \left|(\hat{\boldsymbol{w}} - \tilde{\boldsymbol{w}})^T\tilde{\boldsymbol{x}}^{(i)}\right|\right) \\
&\leq P\left(\|\tilde{\boldsymbol{x}}^{(i)}\| + \frac{1}{N^2}\sqrt{\frac{1}{\pi n}}\|\tilde{\boldsymbol{x}}^{(i)}\|\right) \\
&\leq 2P\|\tilde{\boldsymbol{x}}^{(i)}\| \\
&= 2P\sqrt{\sum_{k=1}^n \left|\tilde{x}_k^{(i)}\right|^2} \\
&\leq 2Pr'\sqrt{n} \\
&= 4r'nN^2\sqrt{\pi} + 2r'\sqrt{n} \leq 6r'nN^2\sqrt{\pi} \leq R'.
\end{aligned}
$$

and

$$
\begin{aligned}
\left|\tilde{z}^{(i)} - \tilde{z}^{(j)}\right| &= \left|\boldsymbol{w}^T(\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)})\right| \\
&= P\left|\hat{\boldsymbol{w}}^T(\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)})\right| \\
&\geq P\left(\left|\tilde{\boldsymbol{w}}^T(\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)})\right| - \left|(\hat{\boldsymbol{w}} - \tilde{\boldsymbol{w}})^T(\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)})\right|\right) \\
&\geq P\left(\frac{1}{N^2}\sqrt{\frac{8}{\pi n}}\|\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)}\| - \frac{1}{N^2}\sqrt{\frac{1}{\pi n}}\|\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)}\|\right) \\
&\geq P\frac{1}{N^2}\sqrt{\frac{1}{\pi n}}\|\tilde{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(j)}\| \\
&\geq P\frac{1}{N^2}\sqrt{\frac{1}{\pi n}} \cdot 2 \geq 4.
\end{aligned}
$$

Construction of $\mathcal{N}_2$. We construct $\mathcal{N}_2 = \mathcal{F}_{2n} \circ \mathcal{F}_{2n-1} \circ \cdots \circ \mathcal{F}_1$ in n steps. Each step $l \in [n]$ consists of 2 Transformer blocks $\mathcal{F}_{2l-1}, \mathcal{F}_{2l} : \mathbb{R}^{3\times n} \to \mathbb{R}^{3\times n}$.

First, we use Lemma E.2 to obtain a self-attention module $\tilde{\mathcal{F}}_{2l-1}^{(SA)} : \mathbb{R}^{1\times n} \to \mathbb{R}^{1\times n}$ that computes a vector with all coordinates holding $\frac{1}{2P\sqrt{n}}$-approximation $\hat{x}_{\max}$ of $x_{\max} = \max_{i\in[n]}\boldsymbol{x}[i]$ given $\boldsymbol{x} \in \mathbb{R}^n$. We extend $\tilde{\mathcal{F}}_{2l-1}^{(SA)}$ to define a valid self-attention subblock $\mathcal{F}_{2l-1}^{(SA)} : \mathbb{R}^{3\times n} \to \mathbb{R}^{3\times n}$ as

$$
\mathcal{F}_{2l-1}^{(SA)}\left(\begin{bmatrix}\boldsymbol{x}^T \\ \boldsymbol{0}_n^T \\ \boldsymbol{z}^T\end{bmatrix}\right) = \begin{bmatrix}\boldsymbol{x}^T \\ \boldsymbol{0}_n^T \\ \boldsymbol{z}^T\end{bmatrix} + \begin{bmatrix}\boldsymbol{0}_n^T \\ \tilde{\mathcal{F}}_{2l-1}^{(SA)}(\boldsymbol{x}^T) \\ \boldsymbol{0}_n^T\end{bmatrix} = \begin{bmatrix}\boldsymbol{x}^T \\ \hat{x}_{\max}\boldsymbol{1}_n^T \\ \boldsymbol{z}^T\end{bmatrix}
$$

for $\boldsymbol{x}, \boldsymbol{z} \in \mathbb{R}^n$. The subblock $\mathcal{F}_{2l-1}^{(SA)}$ finds the $\frac{1}{2P\sqrt{n}}$-approximate maximum token id among the first coordinate values and outputs in the second coordinate.

Next, we use Lemma E.3 to obtain a tokenwise feedforward module $\tilde{\mathcal{F}}_{2l-1}^{(FF)} : \mathbb{R}^{2\times n} \to \mathbb{R}^{1\times n}$ that outputs r' for tokens with the same value in two coordinates. We define a tokenwise feedforward subblock $\mathcal{F}_{2l-1}^{(FF)} : \mathbb{R}^{3\times n} \to \mathbb{R}^{3\times n}$ by extending $\tilde{\mathcal{F}}_{2l-1}^{(FF)}$ so that, for $\boldsymbol{x}, \mathbf{y}, \boldsymbol{z} \in \mathbb{R}^n$,

$$
\mathcal{F}_{2l-1}^{(FF)}\left(\begin{bmatrix}\boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T\end{bmatrix}\right) = \begin{bmatrix}\boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T\end{bmatrix} + \begin{bmatrix}-\tilde{\mathcal{F}}_{2l-1}^{(FF)}([\boldsymbol{x},\mathbf{y}]^T) \\ \boldsymbol{0}_n^T \\ \boldsymbol{0}_n^T\end{bmatrix} = \begin{bmatrix}\tilde{\boldsymbol{x}}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T\end{bmatrix},
$$

where

$$\tilde{\boldsymbol{x}}[i] = \begin{cases} \boldsymbol{x}[i] - r' & \text{if } |\boldsymbol{x}[i] - \boldsymbol{y}[i]| < \frac{1}{2} \\ \boldsymbol{x}[i] & \text{if } |\boldsymbol{x}[i] - \boldsymbol{y}[i]| > 1 \end{cases}.$$

The subblock $\mathcal{F}_{2l-1}^{(FF)}$ compares the first two coordinates and subtracts r' from the first coordinate if they are closer than $\frac{1}{2}$. If they are separated by 1, then the first coordinate keeps the same value as the first coordinate of the input.

Since we do not need the self-attention subblock from $\mathcal{F}_{2l}$, we set all weights of $\mathcal{F}_{2l}^{(SA)}$ to zero. We define $\mathcal{F}_{2l}^{(FF)} : \mathbb{R}^{3\times n} \to \mathbb{R}^{3\times n}$ as

$$\begin{aligned}
\mathcal{F}_{2l}^{(FF)}\left(\begin{bmatrix} \boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T \end{bmatrix}\right) &= \begin{bmatrix} \boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T \end{bmatrix} + \begin{bmatrix} 1 & 0 \\ 0 & -1/P \\ 0 & \hat{w}_k \end{bmatrix} \sigma_R\left(\begin{bmatrix} -\mathbf{e}_1^T \\ P\mathbf{e}_2^T \end{bmatrix} \begin{bmatrix} \boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T \end{bmatrix}\right) \\
&= \begin{bmatrix} \boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T \end{bmatrix} + \begin{bmatrix} 1 & 0 \\ 0 & -1/P \\ 0 & \hat{w}_k \end{bmatrix} \sigma_R\left(\begin{bmatrix} -\boldsymbol{x}^T \\ P\mathbf{y}^T \end{bmatrix}\right) \\
&= \begin{bmatrix} \boldsymbol{x}^T + \sigma_R(-\boldsymbol{x}^T) \\ \mathbf{y}^T - \sigma_R(\mathbf{y}^T) \\ \boldsymbol{z}^T + \hat{w}_k P \sigma_R(\mathbf{y}^T) \end{bmatrix} \\
&= \begin{bmatrix} \sigma_R(\boldsymbol{x}^T) \\ \mathbf{y}^T - \sigma_R(\mathbf{y}^T) \\ \boldsymbol{z}^T + w_k \sigma_R(\mathbf{y}^T) \end{bmatrix},
\end{aligned}$$

where $P > 0$ and $w_k = \hat{w}_k P$ are defined earlier. When $\mathbf{y} \geq 0$, then we can further simplify as

$$\mathcal{F}_{2l}^{(FF)}\left(\begin{bmatrix} \boldsymbol{x}^T \\ \mathbf{y}^T \\ \boldsymbol{z}^T \end{bmatrix}\right) = \begin{bmatrix} \sigma_R(\boldsymbol{x}^T) \\ \mathbf{0}_n^T \\ \boldsymbol{z}^T + w_k\mathbf{y}^T \end{bmatrix}.$$

Let $\boldsymbol{Z}^{(i,l)} = \mathcal{F}_{2l} \circ \mathcal{F}_{2l-1} \circ \cdots \circ \mathcal{F}_1\left(\begin{bmatrix} \boldsymbol{x}^{(i)T} \\ \mathbf{0}_n^T \\ \mathbf{0}_n^T \end{bmatrix}\right) \in \mathbb{R}^{3\times n}$ be the output of the l-th step when the input is $\boldsymbol{x}^{(i)}$ for $l = 0, \cdots, n$. We show inductively that

$$\boldsymbol{Z}^{(i,l)}[1,k] = \begin{cases} \boldsymbol{x}^{(i)}[k] & \text{if } l < n_i \text{ and } \boldsymbol{x}^{(i)}[k] < \boldsymbol{x}^{(i)}[l] \\ 0 & \text{otherwise} \end{cases},$$

$$\boldsymbol{Z}^{(i,l)}[2,k] = 0,$$

$$\boldsymbol{Z}^{(i,l)}[3,k] = \boldsymbol{w}[1:\min\{l,n_i\}]^T \hat{\boldsymbol{x}}^{(i)}[1:\min\{l,n_i\}] = \sum_{j=1}^{\min\{l,n_i\}} \boldsymbol{w}[j]\hat{\boldsymbol{x}}^{(i)}[j]$$

for $i \in [N], l, k \in [n]$, where $\hat{\boldsymbol{x}}^{(i)}[j]$ is $\frac{1}{2P\sqrt{n}}$-approximation of $\boldsymbol{x}^{(i)}[j]$.

For $l = 0$, the above conditions hold for the input $\begin{bmatrix} \boldsymbol{x}^{(i)T} \\ \boldsymbol{0}_n^T \\ \boldsymbol{0}_n^T \end{bmatrix}$. Suppose that the above conditions hold

for $l = \tilde{l} - 1$. Then, we obtain

$$
\begin{aligned}
\mathcal{F}_{2\tilde{l}}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(SA)} \left(\boldsymbol{Z}^{(i,\tilde{l}-1)} \right) &= \mathcal{F}_{2\tilde{l}}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(SA)} \left(\begin{bmatrix} \boldsymbol{Z}^{(i,\tilde{l}-1)}[1,:] \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[2,:] \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[3,:] \end{bmatrix} \right) \\
&= \mathcal{F}_{2\tilde{l}}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(SA)} \left(\begin{bmatrix} \boldsymbol{Z}^{(i,\tilde{l}-1)}[1,:] \\ \boldsymbol{0}_n^T \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[3,:] \end{bmatrix} \right) \\
&= \mathcal{F}_{2\tilde{l}}^{(FF)} \circ \mathcal{F}_{2\tilde{l}-1}^{(FF)} \left(\begin{bmatrix} \boldsymbol{Z}^{(i,\tilde{l}-1)}[1,:] \\ \hat{\boldsymbol{x}}^{(i)}[\tilde{l}]\boldsymbol{1}_n^T \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[3,:] \end{bmatrix} \right) \\
&= \mathcal{F}_{2\tilde{l}}^{(FF)} \left(\begin{bmatrix} \tilde{\boldsymbol{x}}^{(i,\tilde{l}-1)T} \\ \hat{\boldsymbol{x}}^{(i)}[\tilde{l}]\boldsymbol{1}_n^T \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[3,:] \end{bmatrix} \right) \\
&= \begin{bmatrix} \sigma_R \left(\tilde{\boldsymbol{x}}^{(i,\tilde{l}-1)T} \right) \\ \boldsymbol{0}_n^T \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[3,:] + \boldsymbol{w}[\tilde{l}]\hat{\boldsymbol{x}}^{(i)}[\tilde{l}]\boldsymbol{1}_n^T \end{bmatrix}.
\end{aligned}
$$

Here, $\hat{x}_{\tilde{l}}^{(i)}$ is $\frac{1}{2P\sqrt{n}}$-approximate maximum element from $\boldsymbol{Z}^{(i,\tilde{l}-1)}[1,:]$. By the induction hypothesis, $\hat{\boldsymbol{x}}^{(i)}[\tilde{l}]$ is $\frac{1}{2P\sqrt{n}}$-approximation of $\boldsymbol{x}^{(i)}[\tilde{l}]$ when $\tilde{l} \le n_i$ and 0 when $\tilde{l} > n_i$. We note that the last two coordinates match with those of $\boldsymbol{Z}^{(i,\tilde{l})}$. Also, we use $\tilde{\boldsymbol{x}}^{(i,\tilde{l}-1)}$ to denote

$$
\tilde{\boldsymbol{x}}^{(i,\tilde{l}-1)}[k] = \begin{cases} \boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] - r' & \text{if } |\boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] - \hat{\boldsymbol{x}}^{(i)}[\tilde{l}]| < \frac{1}{2} \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] & \text{if } |\boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] - \hat{\boldsymbol{x}}^{(i)}[\tilde{l}]| > 1 \end{cases}
$$

so

$$
\sigma_R(\tilde{\boldsymbol{x}}^{(i,\tilde{l}-1)}[k]) = \begin{cases} 0 & \text{if } |\boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] - \hat{\boldsymbol{x}}^{(i)}[\tilde{l}]| < \frac{1}{2} \\ \boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] & \text{if } |\boldsymbol{Z}^{(i,\tilde{l}-1)}[1,k] - \hat{\boldsymbol{x}}^{(i)}[\tilde{l}]| > 1 \end{cases}.
$$

Since distinct tokens are separated by 2, $\frac{1}{2P\sqrt{n}}$-approximations of them are separated by 1. On the other hand, since $\frac{1}{2P\sqrt{n}} < \frac{1}{2}$, the $\frac{1}{2P\sqrt{n}}$-approximation of the maximum element stays closer than $\frac{1}{2}$. Consequently, $\sigma_R(\tilde{\boldsymbol{x}}^{(i,\tilde{l}-1)T})$ is the same as $\boldsymbol{Z}^{(i,\tilde{l})}[1,:]$. Thus, we conclude our induction proof.

In the end of n steps, the output is $\boldsymbol{Z}^{(i,n)} = \begin{bmatrix} \boldsymbol{0}_n^T \\ \boldsymbol{0}_n^T \\ z^{(i)}\boldsymbol{1}_n^T \end{bmatrix}$ with $z^{(i)} = \boldsymbol{w}^T \hat{\boldsymbol{x}}^{(i)}$. We check that $z^{(i)}$

approximates $\tilde{z}^{(i)}$ within 1 as

$$
\begin{aligned}
\left| z^{(i)} - \tilde{z}^{(i)} \right| &\le \left| \boldsymbol{w}^T \hat{\boldsymbol{x}}^{(i)} - \boldsymbol{w}^T \tilde{\boldsymbol{x}}^{(i)} \right| \\
&\le \|\boldsymbol{w}\| \|\hat{\boldsymbol{x}}^{(i)} - \tilde{\boldsymbol{x}}^{(i)}\| \\
&\le P\|\hat{\boldsymbol{w}}\| \frac{\sqrt{n}}{2P\sqrt{n}} \\
&\le \frac{1}{2} \left(\|\tilde{\boldsymbol{w}}\| + \|\hat{\boldsymbol{w}} - \tilde{\boldsymbol{w}}\| \right) \\
&\le \frac{1}{2} \left(1 + \frac{1}{N^2} \sqrt{\frac{1}{\pi n}} \right) \le 1.
\end{aligned}
$$

Our construction of $\mathcal{N}_2$ involves $2n$ Transformer blocks. From Lemma E.2, the subblock $\mathcal{F}_{2l-1}^{(SA)}$ uses 1 head ($h = 1$) with head size 1 ($k = 1$) and bit complexity $\lceil \log \left(\log(4n^{3/2}r'P) \right) \rceil = \lceil \log \left(\log(8n^2N^2r'\sqrt{\pi}) \right) \rceil$. From Lemma E.3, the subblock $\mathcal{F}_{2l-1}^{(FF)}$ uses feedforward dimension 4 with bit complexity $\lceil \log r' \rceil$. The subblock $\mathcal{F}_{2l}^{(FF)}$ uses feedforward dimension 2. All weights in $\mathcal{F}_{2l}^{(FF)}$ are either $0, \pm 1, P, -1/P$ or $\hat{w}_k$. Since we represent each coordinate of $\hat{w}_k$ using $\lceil \log(nN^2\sqrt{\pi}) \rceil$ bits, the bit complexity of $\mathcal{F}_{2l}^{(FF)}$ is $\max\{\lceil \log P \rceil, \lceil \log(nN^2\sqrt{\pi}) \rceil\} = \lceil \log(2nN^2\sqrt{\pi}) \rceil$. Thus, the network $\tilde{\mathcal{N}}_2$ has 1 head ($h = 1$) with the head size 1 ($k = 1$), the feedforward dimension 4 and the bit complexity $\lceil \log(2r'nN^2\sqrt{\pi}) \rceil$. $\qquad \square$

A.3 STAGE 3: STRING LOOKUP

We can extend stage 2 by using extra dimension to pass $\boldsymbol{x}^{(i)}$ from stage 1 without any additional parameter. Then, after stage 2, the k-th token in the i-th sequence contains $z^{(i)}$ and $\boldsymbol{x}^{(i)}[k]$, which are enough to identify the corresponding label $\boldsymbol{y}^{(i)}[k]$. We note that $\left| \boldsymbol{x}^{(i)}[k] \right| \le r'$ and $\left| z^{(i)} \right| \le R' + 1$ with $r', R' > 6$. We define $\boldsymbol{a}^{(i)}[k] = (\lfloor \hat{z}^{(i)} \rfloor + R' + 1)(2r' + 1) + \lfloor \boldsymbol{x}^{(i)}[k] \rfloor + r' + 1$ to be the unique integer id for each token in each sequence. Then, we have

- $1 \le \boldsymbol{a}^{(i)}[k] < (2R' + 3)(2r' + 1) < 9r'R'$ for $i \in [N]$ and
- $\left| \boldsymbol{a}^{(i)}[k] - \boldsymbol{a}^{(j)}[l] \right| \ge 2$ for $i, j \in [N], k, l \in [n]$ with $\mathcal{V}^{(i)} \ne \mathcal{V}^{(j)}$ or $\boldsymbol{X}^{(i)}[:, k] \ne \boldsymbol{X}^{(j)}[:, l]$.

We denote $R = 9r'R'$. Now, our goal is to map $\boldsymbol{a}^{(i)}[k] \in [R]$ to $\boldsymbol{y}^{(i)}[k] \in [C]$ using tokenwise feedforward subblocks. We denote the number of distinct $\boldsymbol{a}^{(i)}[k]$'s as $N' \le nN$. We reindex each of unique tokens and the corresponding label as $\tilde{a}^{(i)}$ and $\tilde{y}^{(i)}$ for $i \in [N']$, respectively. Without loss of generality, we suppose that $1 \le \tilde{a}^{(1)} < \cdots < \tilde{a}^{(N')} < R$. The subsequent construction in stages 3 and 4 adopts stages 2 and 3 in Vardi et al. (2022) to our architecture that involves skip-connections.

We now state the main lemma for stage 3.

Lemma A.3. *Let $N', R \in \mathbb{N}$ and $1 \le \tilde{a}^{(1)} < \cdots < \tilde{a}^{(N')} < R$ to be distinct integer ids that identify each token in each sequence. We suppose that $\left| \tilde{a}^{(i)} - \tilde{a}^{(j)} \right| \ge 2$ for $i, j \in [N']$ with $i \ne j$. Let $A, B, b \in \mathbb{N}$ with $A < N'$ and $B = \lceil \frac{N'}{A} \rceil$. Let $w_1, \cdots, w_A \in \mathbb{N}$ with the number of bits in their binary representation at most b.*

Then, there exists a network $\mathcal{N}_3 : \mathbb{R}^2 \to \mathbb{R}^2$ consisting of A feedforward blocks with skip-connections every 2 layers, feedforward dimension $r = 4$ and bit complexity $b + \lceil \log(2R + 1) \rceil$ such that

$$\mathcal{N}_3 \left(\tilde{a}^{(i)}, 0 \right) = \left(\tilde{a}^{(i)}, w_{\lceil \frac{i}{B} \rceil} \right).$$

Proof. We construct $\mathcal{N}_3 = \mathcal{F}_A \circ \mathcal{F}_{A-1} \circ \cdots \circ \mathcal{F}_1$ as a composition of A feedforward blocks $\mathcal{F}_l : \mathbb{R}^2 \to \mathbb{R}^2, l \in [A]$ where each feedforward block contains a single hidden layer and a skip-connection.

Let $l \in [A]$. We use Lemma E.4 to define $\tilde{\mathcal{F}}_l : \mathbb{R}^2 \to \mathbb{R}^1$ such that $\tilde{\mathcal{F}}_l(x) = w_l$ if $x \in \left[\tilde{a}^{((l-1) \cdot B + 1)}, \tilde{a}^{(l \cdot B)} \right]$ and $\tilde{\mathcal{F}}_i(x) = 0$ if $x \notin \left[\tilde{a}^{((l-1) \cdot B + 1)} - \frac{1}{2}, \tilde{a}^{(l \cdot B)} + \frac{1}{2} \right]$ where we regard $l \cdot B > N'$ to be N'. We extend $\tilde{\mathcal{F}}_l$ to define a valid feedforward block $\mathcal{F}_l$ as

$$\mathcal{F}_l(x, y) = (x, y) + \left(0, \tilde{\mathcal{F}}_i(x) \right) = \left(x, y + \tilde{\mathcal{F}}_i(x) \right).$$

Throughout the computation of $\mathcal{N}_3$, the first coordinate is the same across all blocks. For $i \in [N']$, $\tilde{a}^{(i)}$ only activates one of $\tilde{\mathcal{F}}_l, l \in [A]$. In particular, $\tilde{\mathcal{F}}_l(\tilde{a}^{(i)}) = w_l$ if $l = \lceil \frac{i}{B} \rceil$ and $\tilde{\mathcal{F}}_l(\tilde{a}^{(i)}) = 0$ otherwise. Thus, we get

$$\mathcal{N}_3 \left(\tilde{a}^{(i)}, 0 \right) = \left(\tilde{a}^{(i)}, w_{\lceil \frac{i}{B} \rceil} \right).$$

Our construction involves A feedforward blocks with skip-connections every 2 layers. From Lemma E.4, feedforward dimension $r = 4$ and the bit complexity is $b + \lceil \log(2R + 1) \rceil$. $\qquad \square$

Remark A.4. *We can extend the construction from Lemma A.3 to output multiple strings corresponding to the same range without additional feedforward dimension. In particular, the first layer*

in the construction of Lemma E.4 does not depend on w. Thus, we can reuse this four units with different output weights to output additional strings corresponding to the same range. In stage 4, we need 2 strings for each range.

A.4 STAGE 4: BIT EXTRACTION

We first define $\text{BIN}_{i:j}(n)$ to be the substring of n with bits in places from i to j inclusive for $n, i, j \in \mathbb{N}$ with $i \leq j$. We now state the main lemma for stage 4.

Lemma A.5. *Let $B, \rho, \gamma \in \mathbb{N}$ and $u, w \in \mathbb{N}$. Suppose that the number of bits in binary representation of u and w are ρB and γB, respectively. We assume that $\left| \text{BIN}_{\rho \cdot (i-1)+1:\rho \cdot i}(u) - \text{BIN}_{\rho \cdot (j-1)+1:\rho \cdot j}(u) \right| \geq 2$ for $i, j \in [B]$ with $i \neq j$.*

Then, there exists a network $\mathcal{N}_4 : \mathbb{R}^6 \rightarrow \mathbb{R}$ consisting of an output embedding block and $B \max\{\rho, \gamma\}$ feedforward blocks with skip-connections every 2 layers, feedforward dimension $r = 16$ and bit complexity $B \max\{\rho, c\} + 2$ such that

$$\mathcal{N}_4 (x, u, 0, w, 0, 0) = \text{BIN}_{\rho \cdot (i-1)+1:\rho \cdot i}(w),$$

if there exist $i \in [B]$ such that $x = \text{BIN}_{\rho \cdot (i-1)+1:\rho \cdot i}(u)$.

Proof. This is the direct consequence of Lemma A.5 in Vardi et al. (2022). $\qquad\square$

A.5 POSITIONAL ENCODING

Consider the token id $\boldsymbol{u}^T \boldsymbol{X}^{(n)}$ in stage 1. If we define the positional encoding as

$$\boldsymbol{E} = r' \boldsymbol{u}[n-1, n-2, \cdots, 1, 0],$$

then we have

$$\boldsymbol{u}^T(\boldsymbol{X}^{(n)} + \boldsymbol{E}) = \boldsymbol{u}^T \boldsymbol{X}^{(n)} + r'[n-1, n-2, \cdots, 1, 0],$$

Since every element of $\boldsymbol{u}^T \boldsymbol{X}^{(n)}$ are bounded above by r', positional encoding enforces the decreasing order used in stage 2 as the usual sequential order. Thus, the sequence id is no longer permutation invariant.

A.6 PROOF OF THEOREM 3.1

Combining $\mathcal{N}_i$ for $i = 1, 2, 3, 4$ as $\mathcal{N} = \mathcal{N}_4 \circ \mathcal{N}_3 \circ \mathcal{N}_2 \circ \mathcal{N}_1$, we get the desired Transformer that satisfies conditions in Theorem 3.1.

B LARGE WIDTH AND FIXED BIT COMPLEXITY

In this section, we formally study the generalization of Theorem 3.1 in the case of large width and fixed bit complexity from Remark 3.3. To simplify the argument, we state and prove the result only for the case without permutation equivariance. The theorem for the permutation equivariance case is straightforwardly obtained from our stated theorem.

B.1 LARGE WIDTH

We state and prove the theorem for large width.

Theorem B.1. *Assume the same setting as in Theorem 3.1. Let $L \leq \sqrt{nN}$. There exists a Transformer network $\mathcal{N} : \mathbb{R}^{d \times n} \rightarrow \mathbb{R}^{1 \times n}$ and positional encoding $\boldsymbol{E} \in \mathbb{R}^{d \times n}$ such that*

$$\mathcal{N}(\boldsymbol{X}^{(i)} + \boldsymbol{E}) = \boldsymbol{Y}^{(i)}$$

for every $i \in [N]$. In both cases, the Transformer $\mathcal{N}$ has width $16nN/L^2$ ($m = 6$, $h = k = 1$ and $q = 16$), depth

$$O \left(n + L\sqrt{\log(L)} + L\sqrt{\frac{1}{\log(L)}} \cdot \max\{\log C, \log R\} \right)$$

and bit complexity bounded by

$$O\left(\log d + L\sqrt{\frac{1}{\log(L)}} \cdot \max\{\log C, \log R\}\right)$$

where we denote $R \coloneqq 3000r^2\delta^{-2}dn^5N^6$.

Proof. Stage 1 and 2 are the same as the proof of Theorem 3.1. For stage 3 and 4, instead of directly memorizing nN contextual token ids directly, we construct nN/L^2 subnetworks where each memorize L^2 contextual token ids. By stacking subnetworks horizontally across width, we obtain the result. □

B.2 Fixed bit complexity

We state and prove the theorem for fixed bit complexity.

Theorem B.2. *Assume the same setting as in Theorem 3.1. Let $B \leq \sqrt{nN}$. There exists a Transformer network $\mathcal{N} : \mathbb{R}^{d\times n} \to \mathbb{R}^{1\times n}$ and positional encoding $\boldsymbol{E} \in \mathbb{R}^{d\times n}$ such that*

$$\mathcal{N}(\boldsymbol{X}^{(i)} + \boldsymbol{E}) = \boldsymbol{Y}^{(i)}$$

for every $i \in [N]$. In both cases, the Transformer $\mathcal{N}$ has width 16 ($m = 6$, $h = k = 1$ and $q = 16$), depth

$$O\left(n + \frac{nN}{B}\sqrt{\log(B)} + \frac{nN}{B}\sqrt{\frac{1}{\log(B)}} \cdot \max\{\log C, \log R\}\right)$$

and bit complexity bounded by

$$O\left(\log d + B\sqrt{\frac{1}{\log(B)}} \cdot \max\{\log C, \log R\}\right)$$

where we denote $R \coloneqq 3000r^2\delta^{-2}dn^5N^6$.

Proof. Stage 1 and 2 are the same as the proof of Theorem 3.1. For stage 3 and 4, instead of directly memorizing nN contextual token ids directly, we construct nN/B^2 subnetworks where each memorize B^2 contextual token ids. By stacking subnetworks vertically across depth, we obtain the result. □

C Contextual Mapping Implications

C.1 Sparse Attention Transformers

This section shows how our result generalizes to sparse-attention Transformers. Sparse-attention Transformers replaces self-attention subblocks with sparse counterparts. Let $\mathcal{A}_k^l \subset [n]$ be the l-th sparsity pattern of k-th token where $k \in [n], l \in [p]$. Given an input $\mathbf{Z} \in \mathbb{R}^{m\times n}$, the sparse self-attention subblock $F_l^{(SSA)}$ with h heads and head size k computes

$$F_l^{(SSA)}(\mathbf{Z}) = \mathbf{Z} + \sum_{i=1}^{h} \mathbf{W}_{l,i}^{(O)}\left(\mathbf{W}_{l,i}^{(V)}\mathbf{Z}_{\mathcal{A}_k^l}\right)\sigma_S\left[\left(\mathbf{W}_{l,i}^{(K)}\mathbf{Z}_{\mathcal{A}_k^l}\right)^T\left(\mathbf{W}_{l,i}^{(Q)}\mathbf{Z}_{\mathcal{A}_k^l}\right)\right],$$

where $\mathbf{Z}_{\mathcal{A}_k^l} \in \mathbb{R}^{m\times|\mathcal{A}_k^l|}$ denote the submatrix consisting of columns of Z in the index set $\mathcal{A}_k^l$. Again, $\mathbf{W}_{l,i}^{(O)} \in \mathbb{R}^{m\times k}$ and $\mathbf{W}_{l,i}^{(V)}, \mathbf{W}_{l,i}^{(K)}, \mathbf{W}_{l,i}^{(Q)} \in \mathbb{R}^{k\times m}$ are the weight matrices parametrizing the sparse self-attention subblock.

We make the following assumption on the sparsity pattern, which relaxes the assumptions made in Yun et al. (2020b).

Assumption C.1. (Relaxed version of Assumption 1 in Yun et al. (2020b)) Define a sequence of set $\{\mathcal{S}_k^t\}_{t \geq 1}$ as

$$\mathcal{S}_k^1 := \mathcal{A}_k^1, \mathcal{S}_k^t := \bigcup_{j \in \mathcal{A}_k^{(t-1) \mod p+1}} \mathcal{S}_j^{t-1}$$

We assume that the sparsity patterns $\{\mathcal{A}_k^l\}$ satisfy that there exists a finite $s \in \mathbb{N}$ such that

$$s = \min\{u | \mathcal{S}_k^u = [n] \text{ for all } k \in [n]\}.$$

We provide the sparse-attention version of our main result.

Theorem C.1. *Let $N, d, n, C, s \in \mathbb{N}$ and $r \geq 1, 0 < \delta \leq 1$. Let $(\mathbf{X}^{(1)}, \mathbf{Y}^{(1)}), \cdots, (\mathbf{X}^{(N)}, \mathbf{Y}^{(N)}) \in \mathbb{R}^{d \times n} \times [C]^{1 \times n}$ be N input-output pairs of sequences that satisfies. Denote $R := 3000r^2\delta^{-2}dn^5N^6$. Then, there exists a Transformer network $F : \mathbb{R}^{d \times n} \to \mathbb{R}^{1 \times n}$ with width 16 ($m = 6$, $h = k = 1$ and $r = 16$), depth*

$$O\left(ns + \sqrt{nN \log N} + \sqrt{\frac{nN}{\log N} \cdot \max\{\log C, \log R\}}\right)$$

and bit complexity bounded by

$$O\left(\log d + \sqrt{\frac{nN}{\log N} \cdot \max\{\log C, \log R\}}\right)$$

such that $F(\mathbf{X}^{(i)}\mathbf{P}) = \mathbf{Y}^{(i)}\mathbf{P}$ for every $i \in [N]$ and for every permutation matrix $\mathbf{P} \in \mathbb{R}^{n \times n}$.

Proof. The stage 1, 3 and 4 are the same as the proof of Theorem 3.1. For stage 2, instead of using single self-attention layer to collect each token, we can use s self-attention layers to collect each token. Since stage 2 computes maximum over sparsity pattern and s consecutive sparsity pattern cover the whole sequence, we can find maximum using s self-attention layers. $\square$

The simplicity of our contextual mapping enables easy generalization to the sparse attention. Since the sparse attention Transformer only constrains the sparsity pattern in the self-attention subblock, stages 1, 3 and 4 in our construction works without any modification. For the contextual mapping in stage 2, we achieve the same memorization capacity with only s times more self-attention layers. The number of parameters is $\tilde{O}(d + sn + \sqrt{N})$.

C.2 IMPROVED CONTEXTUAL MAPPING FOR FUNCTION APPROXIMATION

Our idea can be used to reduce the number of self-attention layers for the contextual mapping in function approximation settings, too. Formally, we define the contextual mapping as follows.

Definition C.2. (Definition 3.1 in Yun et al. (2020a), Contextual Mapping) Consider a finite set $\mathcal{L} \subset \mathbb{R}^{d \times n}$. A map $q : \mathcal{L} \to \mathbb{R}^{1 \times n}$ is a contextual mapping if the map satisfies the following:

1. For any $L \in \mathcal{L}$, the n entries in $q(L)$ are distinct.

2. For any $L, L' \in \mathcal{L}$ with $L \neq L'$, all entries of $q(L)$ and $q(L')$ are distinct.

We state our improvement of the contextual mapping as follows.

Theorem C.2. *(Improved version of Lemma 6 in Yun et al. (2020a)) Consider the following subset of $\mathcal{G}_\delta = \{0, \delta, \cdots, 1 - \delta\}^{d \times n}$:*

$$\tilde{\mathcal{G}}_\delta := \{L \in \mathcal{G}_\delta | L_{:,i} \neq L_{:,j} \text{ for all } i \neq j\}.$$

Assume that $n \geq 2$ and $\delta^{-1} \geq 2$. For $L \in \mathcal{G}_\delta$, we write $\tilde{L} \in \mathbb{R}^{(d+2) \times n}$ as L with two 0 rows concatenated. Then, there exist a function $g_c : \mathbb{R}^{(d+2) \times n} \to \mathbb{R}^{(d+2) \times n}$ composed of n Transformer blocks with $h = 1$, $k = 1$ that employ the hardmax operator, a vector $\mathbf{u} \in \mathbb{R}^{d+2}$, constants $t_l, t_r \in \mathbb{R}$ ($0 < t_l < t_r$), such that $q(L) := \mathbf{u}^T g_c(\tilde{L})$ satisfies the following propeties:

1. *For any $L \in \tilde{\mathcal{G}}_\delta$, the entries of $q(L)$ are all distinct.*

2. *For any $L, L' \in \tilde{\mathcal{G}}_\delta$ such that L is not a permutation of L', all entries of $q(L), q(L')$ are distinct.*

3. *For any $L \in \tilde{\mathcal{G}}_\delta$, all the entries of $q(L)$ are in $[t_l, t_r]$.*

4. *For any $L \in \mathcal{G}_\delta^+ \setminus \tilde{\mathcal{G}}_\delta$, all the entries of $q(L)$ are outside $[t_l, t_r]$.*

The key idea is to use extra working memory units to find and accumulate the maximum.

D   OTHER TASKS

We provide the proof for Theorem 4.1. The stage 1 and 2 are the same. Instead of classifying the contextual token id, we can directly classify sequence ids. Since there are N possible sequence id, the parameter complexity form Theorem 3.1 replaces nN with N.

E   TECHNICAL LEMMAS

Here, we state technical lemmas that are used in our proofs.

Lemma E.1. *(Lemma 13 from Park et al. (2021)) Let $N, d \in \mathbb{N}$ and $\boldsymbol{x}^{(1)}, \cdots \boldsymbol{x}^{(N)} \in \mathbb{R}^d$. Then, there exists a unit vector $\boldsymbol{u} \in \mathbb{R}^d$ such that $\frac{1}{N^2}\sqrt{\frac{8}{\pi d}}\|\boldsymbol{x}^{(i)} - \boldsymbol{x}^{(j)}\| \le |\boldsymbol{u}^T(\boldsymbol{x}^{(i)} - \boldsymbol{x}^{(j)})| \le \|\boldsymbol{x}^{(i)} - \boldsymbol{x}^{(j)}\|$ for every $i, j \in [N]$.*

Lemma E.2. *Let $n \in \mathbb{N}$ and $r', P > 1$. Then, there exists a neural network $\mathcal{F} : \mathbb{R}^{1 \times n} \to \mathbb{R}^{1 \times n}$ consisting of a single softmax self-attention with 1 head, head size 1 and bit complexity $\lceil \log(\log(4n^{3/2}r'P)) \rceil$ such that $\mathcal{F}(\boldsymbol{x}^T) = c\mathbf{1}_n^T$ with $x_{\max} - \frac{1}{2P\sqrt{n}} \le c \le x_{\max}$ whenever $\boldsymbol{x} \in \mathbb{R}^n$ satisfies*

- *$|\boldsymbol{x}[i]| \le r'$ for $i \in [n]$ and*
- *$\boldsymbol{x}[i] \le x_{\max} - 2$ for $i \in [n]$ with $\boldsymbol{x}[i] \ne x_{\max}$,*

where we denote $x_{\max} = \left(\max_{i \in [n]} \boldsymbol{x}[i]\right)$.

Proof. When we have hardmax activation on the attention matrix, it is easy to construct the network that satisfies the condition. Consider the following self-attention:

$$\mathcal{F}(\boldsymbol{x}) = 1 \cdot (1 \cdot \boldsymbol{x})\sigma_H\left[(1 \cdot \boldsymbol{x})^T(0 \cdot \boldsymbol{x} + \mathbf{1}_n^T)\right] = \boldsymbol{x}\sigma_H\left[\boldsymbol{x}^T\mathbf{1}_n^T\right] = \left(\max_{i \in [n]} x_i\right)\mathbf{1}_n^T.$$

Indeed, the output is exactly $x_{\max}$ and the bit complexity is 1 since all weights are either 0 or 1.

To approximate hardmax with softmax, we introduce some large factor $t > 0$ in the attention matrix. Consider the following self-attention:

$$\mathcal{F}(\boldsymbol{x}) = 1 \cdot (1 \cdot \boldsymbol{x})\sigma_S\left[(t \cdot \boldsymbol{x})^T(0 \cdot \boldsymbol{x} + \mathbf{1}_n^T)\right] = \boldsymbol{x}\sigma_S\left[t\boldsymbol{x}^T\mathbf{1}_n^T\right] = c\mathbf{1}_n^T$$

where

$$c = \sum_{i=1}^n \boldsymbol{x}[i] \frac{\exp(t\boldsymbol{x}[i])}{\sum_{j=1}^n \exp(t\boldsymbol{x}[j])}.$$

Since c is a convex combination of $\boldsymbol{x}[i]$'s, it is easy to see that $x_{\max}$ upper bounds c. It suffices to find t that satisfies the lower bound condition.

Choose $t = \lceil \frac{1}{2} \log(4n^{3/2} r' P) \rceil$. We lower bound the softmax weights on $x_{\max}$ as

$$
\begin{aligned}
p_{\max} &:= \frac{\sum_{i:\boldsymbol{x}[i]=x_{\max}} \exp(t\boldsymbol{x}[i])}{\sum_{i=1}^{n} \exp(t\boldsymbol{x}[i])} \\
&= \frac{\sum_{i:\boldsymbol{x}[i]=x_{\max}} \exp(t\boldsymbol{x}[i])}{\sum_{i:\boldsymbol{x}[i]=x_{\max}} \exp(t\boldsymbol{x}[i]) + \sum_{i:\boldsymbol{x}[i]\neq x_{\max}} \exp(t\boldsymbol{x}[i])} \\
&\geq \frac{\sum_{i:\boldsymbol{x}[i]=x_{\max}} \exp(tx_{\max})}{\sum_{i:\boldsymbol{x}[i]=x_{\max}} \exp(tx_{\max}) + \sum_{i:\boldsymbol{x}[i]\neq x_{\max}} \exp(t(x_{\max}-2))} \\
&= \frac{n_{\max}}{n_{\max} + (n - n_{\max})\exp(-2t)} \\
&= \frac{1}{1 + (\frac{n}{n_{\max}} - 1)\exp(-2t)} \\
&\geq \frac{1}{1 + (\frac{n}{n_{\max}} - 1)\frac{1}{4n^{3/2}r'P}} \\
&\geq \frac{1}{1 + \frac{1}{4r'P\sqrt{n}}},
\end{aligned}
$$

where $n_{\max} := |\{i : \boldsymbol{x}[i] = x_{\max}\}|$. Now, we can lower bound c as

$$
\begin{aligned}
c &\geq x_{\max} p_{\max} - r'(1 - p_{\max}) \\
&= x_{\max} - (x_{\max} + r')(1 - p_{\max}) \\
&\geq x_{\max} - 2r'(1 - p_{\max}) \\
&\geq x_{\max} - 2r'\left(1 - \frac{1}{1 + \frac{1}{4r'P\sqrt{n}}}\right) \\
&= x_{\max} - \frac{\frac{1}{2P\sqrt{n}}}{1 + \frac{1}{4r'P\sqrt{n}}} \\
&\geq x_{\max} - \frac{1}{2P\sqrt{n}}.
\end{aligned}
$$

This self-attention module only has 1 head with head size 1. All weights are either 0, 1 or t so the bit complexity is $\lceil \log t \rceil \leq \lceil \log\left(\log(4n^{3/2}r'P)\right) \rceil$. $\qquad\square$

Lemma E.3. *Let $r' \in \mathbb{N}$. Then, there exists a neural network $\mathcal{F} : \mathbb{R}^2 \to \mathbb{R}$ with 1 hidden layer, width 4 and bit complexity $\lceil \log r' \rceil$ such that*

$$
\mathcal{F}(x,y) = \begin{cases} r' & \text{if } |x-y| < \frac{1}{2} \\ 0 & \text{if } |x-y| > 1 \end{cases}.
$$

Proof. Consider the following neural network:

$$
\begin{aligned}
\mathcal{F}(x,y) &= [r' \quad -r' \quad -r' \quad r']\,\sigma_R\left(\begin{bmatrix} 2 & -2 \\ 2 & -2 \\ 2 & -2 \\ 2 & -2 \end{bmatrix}\begin{bmatrix} x \\ y \end{bmatrix} + \begin{bmatrix} 2 \\ 1 \\ -1 \\ -2 \end{bmatrix}\right) \\
&= r'\left(\sigma_R(2x - 2y + 2) - \sigma_R(2x - 2y + 1) - \sigma_R(2x - 2y - 1) + \sigma_R(2x - 2y - 2)\right).
\end{aligned}
$$

It is straightforward to see that the above network computes the desired function. This network has 1 hidden layer and width 4. All parameters are either $\pm 1, \pm 2$ or $\pm r'$ so the bit complexity is $\lceil \log r' \rceil$. $\qquad\square$

Lemma E.4. *Let $a, b, w \in \mathbb{N}$ with $a < b$. Then, there exists a neural network $\mathcal{F} : \mathbb{R} \to \mathbb{R}$ with 1 hidden layer, width 4 and bit complexity $\lceil \log w \rceil + \lceil \log(2b + 1) \rceil$ such that*

$$
\mathcal{F}(x) = \begin{cases} w & \text{if } x \in [a, b] \\ 0 & \text{if } x \notin [a - \frac{1}{2}, b + \frac{1}{2}] \end{cases}.
$$

Proof. Consider the following neural network:

$$\mathcal{F}(x, y) = \begin{bmatrix} w & -w & -w & w \end{bmatrix} \sigma_R \left(\begin{bmatrix} 2 \\ 2 \\ 2 \\ 2 \end{bmatrix} x - \begin{bmatrix} 2a - 1 \\ 2a \\ 2b \\ 2b + 1 \end{bmatrix} \right)$$

$$= w \left(\sigma_R(2x - 2a + 1) - \sigma_R(2x - 2a) - \sigma_R(2x - 2b) + \sigma_R(2x - 2b - 1) \right).$$

It is straightforward to see that the above network computes the desired function. This network has 1 hidden layer and width 4. All parameters are either $\pm w, 2$ or $2a - 1, 2a, 2b, 2b + 1$ so the bit complexity is $\lceil \log w \rceil + \lceil \log(2b + 1) \rceil$. $\qquad \square$

Lemma E.5. *Let $i, j, n, x, y \in \mathbb{N}$ with $i < j \leq n$. Denote $\phi(z) = \sigma_R(\sigma_R(2z) - \sigma_R(4z - 2))$. Then, there exists a neural network $\mathcal{F} : \mathbb{R}^2 \to \mathbb{R}^3$ consisting of $j - i + 1$ feedforward blocks with skip-connections every 2 layers, feedforward dimension 8 and bit complexity $n + 2$ such that*

$$\mathcal{F} \left(\begin{bmatrix} \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right) \\ \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right) \\ y \end{bmatrix} \right) = \begin{bmatrix} \phi^{(j)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right) \\ \phi^{(j)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right) \\ y + \text{BIN}_{i:j}(x) \end{bmatrix}.$$

Proof. We first note that the triangle function can be implemented with one hidden layer as

$$\phi(z) = \sigma_R(2z) - \sigma_R(4z - 2) + \sigma_R(2z - 2).$$

Also, we can implement identity function as

$$z = \frac{1}{2} \sigma_R(2z) - \frac{1}{2} \sigma_R(-2z).$$

Finally, the i-th bit from x can be extracted from $\phi^{(i)}$ as

$$\text{BIN}_i(x) = 2^{n+1-i} \phi^{(i)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right) - 2^{n+1-i} \phi^{(i)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right) + \frac{1}{2}.$$

We can represent

$$\phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right), \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right)$$

$$\phi^{(i)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right), \phi^{(i)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right)$$

$$\text{BIN}_i(x)$$

as linear combinations of

$$\sigma_R(2z_1), \sigma_R(4z_1 - 2), \sigma_R(2z_1 - 2), \sigma_R(-2z_1)$$
$$\sigma_R(2z_2), \sigma_R(4z_2 - 2), \sigma_R(2z_2 - 2), \sigma_R(-2z_2)$$

where $z_1 = \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right)$ and $z_2 = \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right)$. Therefore, one feedforward block with feedforward dimension of 8 is enough in each layer to compute

$$\begin{bmatrix} \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right) \\ \phi^{(i-1)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right) \\ y \end{bmatrix} \mapsto \begin{bmatrix} \phi^{(i)} \left(\frac{x}{2^n} + \frac{1}{2^{n+1}} \right) \\ \phi^{(i)} \left(\frac{x}{2^n} + \frac{1}{2^{n+2}} \right) \\ y + \text{BIN}_i(x) \end{bmatrix}.$$

$\qquad \square$

F EXPERIMENTAL SETUP

Model: We consider BERT Devlin et al. (2019), a multi-layer bidirectional Transformer encoder. We utilize the BERT model implemented by HuggingFace[7] in PyTorch. We set the number of layers as 6, the self-attention heads as 12. We train with 10% droupt-out and no label smoothing. All experiments are conducted on an Nvidia Quatro RTX 5000, 16 GB memory GPU in a machine with Intel(R) Xeon(R) Silver 4214 CPU @ 2.20GHz.

---

[7] https://huggingface.co/

MODEL SIZE: We scale the size of the network by modifying the hidden size. The maximum number of hidden size is 768.

- Token classification: Scale by 12, e.g., $\{12, 24, \cdots, 768\}$.
- Sequence classification: Scale by 96, e.g., $\{96, 192, \cdots, 768\}$.

GRADIENT STEPS: We train the model for a fixed number of optimization steps. The number of steps is determined based on the convergence of the model given the entire training dataset.

- Token classification: 1,500 steps.
- Sequence classification: 7,500 steps.

Optimization: We use Adam optimizer (Loshchilov & Hutter, 2017) with a learning rate of 0.00002.

Loss function: The cross-entropy loss is used for all the experiments.

Batch size: We choose a batch size of 32.

Datasets: We use the following dataset for each experiment.

- Token classification: The CoNLL-2003 shared task data (Tjong Kim Sang & De Meulder, 2003) contains language-independent named entity recognition for each token. We use 14,000 training data and 3,453 test data from the dataset. For the experiment, we split the dataset in 1/10.
- Sequence classification: GLUE, the General Language Understanding Evaluation benchmark [8] is a collection of resources for natural language understanding systems. From GLUE, we use the Multi-Genre Natural Language Inference Corpus (MNLI), a crowd-sourced collection of sentence pairs with textual entailment annotations. There are 3 labels: *entailment, contradiction*, and *neutral*. Of 550k examples, we use 50,000 samples. Similarly, we split the dataset in 1/10.

---

[8] https://gluebenchmark.com/