Minimax Optimal Quantile and Semi-Adversarial Regret via Root-Logarithmic Regularizers

Abstract

Quantile (and, more generally, KL) regret bounds, such as those achieved by NormalHedge (Chaudhuri, Freund, and Hsu 2009) and its variants, relax the goal of competing against the best individual expert to only competing against a majority of experts on adversarial data. More recently, the semi-adversarial paradigm (Bilodeau, Negrea, and Roy 2020) provides an alternative relaxation of adversarial online learning by considering data that may be neither fully adversarial nor stochastic (I.I.D.). We achieve the minimax optimal regret in both paradigms using FTRL with separate, novel, root-logarithmic regularizers, both of which can be interpreted as yielding variants of NormalHedge. We extend existing KL regret upper bounds, which hold uniformly over target distributions, to possibly uncountable expert classes with arbitrary priors; provide the first full-information lower bounds for quantile regret on finite expert classes (which are tight); and provide an adaptively minimax optimal algorithm for the semi-adversarial paradigm that adapts to the true, unknown constraint faster, leading to uniformly improved regret bounds over existing methods.

1 Introduction

We focus on the setting of learning with expert advice [V90; LW94], where in each round the learner selects a probability distribution over experts, observes the loss of each expert, and incurs the average loss of the experts under the learner's selected distribution. The learner's objective is to minimize regret against some mixture of the experts, which is the difference between their cumulative loss and the cumulative loss of the expert mixture over T rounds.

The classical "worst-case" online learning paradigm assumes that the losses are adversarial—that is, they are chosen to make the learner perform as poorly as possible—and demands that the learner competes against the best-performing expert. However, there are many real-world settings where this assumption is too pessimistic, and consequently we focus on designing algorithms with provable guarantees that adapt to easier notions of both data and performance measures. A non-exhaustive list of work on "easy data" includes Freund and Schapire [FS97], Cesa-Bianchi, Mansour, and Stoltz [CMS07], van Erven, Grünwald, Koolen, and de Rooij [v+11], and Gaillard, Stoltz, and van Erven [GSv14], all of which use variants of the Hedge algorithm [FS97] to obtain regret bounds in terms of data-dependent quantities. Ideally, such quantities are small when the data are "easy" to predict.

In this work, we focus on two paradigms beyond the classical worst-case: first, we consider regret within the *semi-adversarial paradigm*, which defines a spectrum of constraints on the permissible data distributions between stochastic and adversarial, and second, we consider relaxing the performance measure to *quantile (KL) regret*, which only measures the ability of an algorithm to compete against an unknown mixture of the experts. The semi-adversarial paradigm considers constraining the adversary's choice of data distributions, which was first motivated by Rakhlin, Sridharan, and Tewari

[RST11]. Bilodeau, Negrea, and Roy [BNR20] extended this idea, defining *adaptive* minimax regret with respect to such constraints and providing an efficient algorithm with corresponding regret bounds. The concept of ϵ-quantile regret was introduced by Chaudhuri, Freund, and Hsu [CFH09], in which the player competes against the $\lfloor \epsilon N \rfloor$ best experts (out of N total) rather than the single best. The authors demonstrated empirically that Hedge does poorly in this paradigm, and introduced a new algorithm NormalHedge with an upper bound on quantile regret of $\sqrt{(T + (\log N)^2)(1 + \ln 1/\epsilon)}$. Later algorithms improved it to $\sqrt{T(1 + \ln 1/\epsilon)}$ [CV10; OP16], removing the dependency on N.

Contributions While the best known algorithms for the above two paradigms are intrinsically different, we show that the follow-the-regularized leader (FTRL) algorithm with new root-logarithmic regularizers achieves minimax optimal performance for both quantile and semi-adversarial regret. First, in the semi-adversarial paradigm, we improve the dependence on the number of experts and require no meta-learning step, obtaining uniformly improved upper bounds over previous work. Second, we provide the first FTRL algorithm with minimax optimal quantile regret guarantees, and do so without using the additive normalization step of previous algorithms [CL06, Section 2.1]. Moreover, we achieve root-KL bounds that hold uniformly over target distributions on (possibly uncountable) expert classes with arbitrary priors, and reduce to the optimal quantile regret for discrete uniform priors. Finally, we prove matching lower bounds for quantile regret with finite expert classes, demonstrating the optimality of known upper bounds (including our own) for the first time.

We achieve the above results through a novel local-norm analysis of FTRL with *linearly decomposable* regularizers on general (possibly uncountable) expert spaces. We use this analysis in conjunction with basic conditions on the first and second derivatives to design and analyze the root-logarithmic regularizers. We believe that this approach is fundamentally different from existing ones and could lead to further advances in obtaining optimal algorithms. In fact, there exist results stating if a regret bound is achievable by some algorithm, then that same bound is nearly achievable by mirror descent with some potential function (see, e.g., Srebro, Sridharan, and Tewari [SST11, Thm 9]). However, it is not clear how to design such a function in practice. In contrast, our general FTRL bound reduces the choice of regularizer to a single univariate function, and clarifies how fundamental properties of this function lead to trade-offs in the regret bound.

Related Work Chernov and Vovk [CV10] first discussed the fact that the ϵ-quantile regret corresponds to the KL divergence between a uniform prior and the uniform mixture of the top $\lfloor \epsilon N \rfloor$ competitors, and such KL bounds have consequently quickly followed quantile regret bounds. Luo and Schapire [LS14; LS15] provided a variant of NormalHedge along with a data-dependent KL regret bound at the cost of an additional $\log T$ factor; a similar but even tighter result was obtained by Koolen and van Erven [Kv15]. Orabona and Pál [OP16] showed that these algorithms can be obtained with a reduction to optimal coin-betting online algorithms, yet none of them can be reduced to an FTRL algorithm. Independently, Harvey, Liaw, Perkins, and Randhawa [H+20] proved that a similar strategy allows one to achieve the optimal anytime regret for the setting with $N = 2$ experts.

The first alternative to additively normalized algorithms in the (bandit) learning with experts setting was the INF algorithm [AB09], which was later recast as online mirror descent [ABL11]. Alquier [A21] also did not use additive normalization, and first introduced FTRL with f-divergences (focusing on the χ^2-divergence) along with regret bounds for continuous distributions with certain unbounded loss functions. For the specific case of Hedge (and its online mirror descent analogue), an analysis on continuous spaces was given by van der Hoeven, van Erven, and Kotłowski [vvK18], while a coarser analysis for f-divergences was given by Alquier [A21]. Finally, choosing regularizers that are tuned to minimize regret for specific tasks has recently led to advances in the online learning literature, both with bandit feedback [A+17; WL18; F+16] and in the full-information setting [LWZ18].

The best known asymptotic lower bound for learning with expert advice is by Cesa-Bianchi, Freund, Haussler, Helmbold, Schapire, and Warmuth [C+97], while a finite-time lower bound that asymptotically matches the leading constant was proved by Orabona and Pál [OP15a]. We are not aware of lower bounds for the quantile regret, with the notable exception of Koolen [K13], who proved a lower bound on the regret of learning with two experts based on the KL divergence against some prior.

2 Notation

To analyze FTRL beyond the finite setting requires some more care, and we rely on the language of measure theory to handle finite and uncountable expert classes simultaneously. Let (Θ, Σ) be a

measurable space endowed with a finite measure ν. A measure q on (Θ, Σ) is *absolutely continuous* with respect to ν (denoted $q \ll \nu$) if $q(A) = 0$ for all $A \in \Sigma$ such that $\nu(A) = 0$. For any integer N, let $[N] = \{1, \ldots, N\}$, and $\mathtt{simp}([N]) = \{p \in [0,1]^N : \sum_{i=1}^N p_i = 1\}$. Let $\mathbb{R}_+ = [0, \infty)$ and $\mathbb{R}_{++} = (0, \infty)$, and define $\mathbb{M} \equiv \mathbb{M}((\Theta, \Sigma), (\mathbb{R}, \mathcal{R}))$ to be the space of measurable functions from (Θ, Σ) to $(\mathbb{R}, \mathcal{R})$, where $\mathcal{R}$ is the Borel σ-field on $\mathbb{R}$. Define sets of bounded measurable functions

$$\mathcal{L}^\infty = \{\ell \in \mathbb{M} : \sup_{\theta \in \Theta} |\ell(\theta)| < \infty\} \text{ and } \mathcal{L}^\infty_{[0,1]} = \{\ell \in \mathbb{M} : 0 \le \ell \le 1\},$$

sets of integrable functions

$$\mathcal{L}^1(\nu) = \{x \in \mathbb{M} : \int |x(\theta)| \, \nu(\mathrm{d}\theta) < \infty\} \text{ and } \mathcal{L}^1_+(\nu) = \{x \in \mathcal{L}^1(\nu) : x \ge 0\},$$

and the set of Radon–Nikodym derivatives of probability measures

$$\mathcal{X}(\nu) = \{x \in \mathcal{L}^1_+(\nu) : \int x(\theta)\nu(\mathrm{d}\theta) = 1\}.$$

For any $x, z \in \mathcal{L}^1(\nu)$, denote their convex hull by $\mathrm{Conv}(x, z) = \{\alpha x + (1 - \alpha)z : \alpha \in [0, 1]\}$. For $x \in \mathcal{L}^1(\nu)$ let $\nu^{(x)}$ denote the unique probability measure satisfying $\mathrm{d}\nu^{(x)}/\mathrm{d}\nu = x$. For every $\ell \in \mathcal{L}^\infty$ and $x \in \mathcal{L}^1(\nu)$, define

$$\langle \ell, \, x \rangle_\nu = \int \ell(\theta) x(\theta) \nu(\mathrm{d}\theta).$$

Prediction with expert advice We consider the following setting of online linear optimization. For each round $t \in [T]$, the player selects $x_t \in \mathcal{X}(\nu)$ based only upon information available prior to round t, and then observes $\ell_t \in \mathcal{L}^\infty$. Performance is measured using the *regret* against some probability measure q on (Θ, Σ), which is defined by

$$R_T(q) = \sum_{t=1}^T \mathbb{E}_{\theta \sim \nu^{(x_t)}} [\ell_t(\theta)] - \sum_{t=1}^T \mathbb{E}_{\theta \sim q} [\ell_t(\theta)].$$

The player's goal is to select x_t so that the cumulative loss is not much larger than that of the average loss of an expert under q, and consequently to have small regret.

The elements of Θ can be regarded as experts for some prediction problem, and the learner aggregates the predictions of the experts by selecting an expert at random according to $\nu^{(x_t)}$ at round t. For concreteness, note that the usual prediction with expert advice setting for N experts is recovered by taking ν to be counting measure (making $\langle \cdot, \, \cdot \rangle_\nu$ the inner product on $\mathbb{R}^N$), in which case $\mathcal{X}(\nu) = \mathtt{simp}([N])$. Note that, for any convex loss, applying online linear optimization to the gradients of the losses provides an upper bound on the performance of online convex optimization.

Follow-the-regularized-leader Let $\overline{\mathbb{R}} = \mathbb{R} \cup \{+\infty\}$. Follow-the-regularized-leader (FTRL) [S07; AHR08; HK10] forms a broad class of algorithms for online convex optimization. For a sequence of regularizers $(\psi_t : \mathcal{X}(\nu) \to \overline{\mathbb{R}})_{t \in [T]}$, $(\psi_t)_{t \in [T]}$-regularized FTRL is defined by selecting

$$x_{t+1} \in \underset{x \in \mathcal{X}(\nu)}{\arg\min}\{\langle L_t, \, x \rangle_\nu + \psi_{t+1}(x)\},$$

where $L_0 = 0$ and $L_t = \sum_{s=1}^t \ell_s$.

As mentioned above, a classical algorithm for prediction with expert advice on a finite class of N experts is Hedge. While originally analyzed using potential functions, Hedge also corresponds to FTRL where ν is the counting measure and $\psi_t(\cdot) = -\eta_t^{-1}H(\cdot)$ for the Shannon entropy $H(x) = \sum_{i \in [N]} x(i) \log(1/x(i))$ and any sequence of learning rates $(\eta_t)_{t \in \mathbb{N}} \subseteq \mathbb{R}_{++}$.

Depending on whether the space is continuous or discrete, the range of elements of $\mathcal{X}(\nu)$ will change, and consequently also the minimal domain on which regularizers must be defined. Let $\underline{\nu} = \inf\{\nu(A) : A \in \Sigma, \nu(A) > 0\}$, and let $\mathcal{S}(\nu) = [0, 1/\underline{\nu}]$ if $\underline{\nu} > 0$ and $\mathbb{R}_+$ otherwise. By definition, $x(\theta) \in \mathcal{S}(\nu)$ for all $x \in \mathcal{X}(\nu)$ with probability one over ν.

Specifically, when ν is counting measure (corresponding to finite prediction with expert advice) then $\mathcal{S}(\nu) = [0, 1]$, and when ν is a continuous distribution then $\mathcal{S}(\nu) = \mathbb{R}_+$. In this work, we consider *linearly decomposable* regularizers of the form $\psi_t = \eta_t^{-1} \Psi^\nu_f(x)$, where

$$\Psi^\nu_f(x) = \int f(x(\theta))\nu(\mathrm{d}\theta) \tag{1}$$

for some $f : \mathcal{S}(\nu) \to \mathbb{R}$.

3   FTRL bounds for general expert spaces

In this section, we analyze the general case of FTRL with a regularizer of the form in Eq. (1). First, Lemma 1 provides a closed-form expression for the FTRL solution on general spaces. Specifically, it reduces solving the FTRL optimization problem of Eq. (1) to finding a root of a 1-dimensional equation (Eq. (2)), rather than solving a complex, possibly infinite dimensional, optimization problem. Second, Theorem 1 provides our fundamental regret bound for FTRL with such regularizers. It generalizes the well-known results involving local norms from the finite dimensional case [AR09; ZS19], and retains an additional summation term (usually uniformly bounded in FTRL analyses) that is crucial both for tight bounds in the semi-adversarial paradigm and for tight KL regret bounds. Lastly, we conclude this section with Corollary 1, which highlights the necessary conditions on f for Theorem 1 to imply variance bounds either with respect to the prior (normalized base measure) or predictive distributions. All results in this section are proved in Appendix A.

For continuously differentiable $f : \mathcal{S}(\nu) \to \mathbb{R}$, let $m_{f'} = \inf_{x \in \mathcal{S}(\nu)} f'(x)$, $M_{f'} = \sup_{x \in \mathcal{S}(\nu)} f'(x)$, and $\tau_{f'}(y) = \max(\min(y, M_{f'}), m_{f'})$. We focus on the setting where f' is strictly increasing, and thus $\tau_{f'}(y)$ truncates its argument to the domain of $[f']^{-1}$.

Lemma 1. *Suppose $f : \mathcal{S}(\nu) \to \mathbb{R}$ is twice continuously differentiable with $f'' > 0$ on interior$(\mathcal{S}(\nu))$ and $f''(0+) > 0$. For any $L \in \mathcal{L}^\infty$ and $\eta > 0$,*
$$x^*(\theta) = [f']^{-1}(\tau_{f'}(-\eta L(\theta) + k^*))$$
satisfies $x^* \in \arg\min_{x \in \mathcal{X}(\nu)}\{\langle L, \ x\rangle_\nu + \eta^{-1}\Psi_f^\nu(x)\}$, where $k^* \in \mathbb{R}$ solves
$$\int [f']^{-1}\left(\tau_{f'}(-\eta L(\theta) + k^*)\right) \nu(\mathrm{d}\theta) = 1. \tag{2}$$
Further, this solution is unique up to modification on a set of ν-measure 0.

In order to state our generic decomposition for the regret of FTRL algorithms on abstract spaces, we rely on the definition of the one-dimensional *Bregman divergence*, which is defined for any continuously differentiable, strictly convex $f : \mathbb{R} \to \mathbb{R}$ by
$$B_f(x; y) = f(x) - f(y) - f'(y)(x - y).$$

Theorem 1. *Suppose $f : \mathcal{S}(\nu) \to \mathbb{R}$ is twice continuously differentiable with $f'' > 0$ on interior$(\mathcal{S}(\nu))$ and $f''(0+) > 0$, and that x_t is chosen using $\Psi_f^\nu(\cdot)$-regularized FTRL with learning rate η_t. For all sequences $(\ell_t)_{t \in \mathbb{N}} \subseteq \mathcal{L}^\infty$ and $(m_t)_{t \in \mathbb{N}} \subseteq \mathbb{R}$, there exist $\hat{z}_{t+1} \in \mathrm{Conv}(x_t, x_{t+1})$ and $\tilde{z}_{t+1} \in \mathrm{Conv}(x_t, \tilde{x}_{t+1})$ such that for all $q \ll \nu$ and $\overline{z}_{t+1} \in \{\hat{z}_{t+1}, \tilde{z}_{t+1}\}$,*

$$
\begin{aligned}
R_T(q) \leq{} & \frac{1}{\eta_{T+1}} \Psi_f^\nu\left(\frac{\mathrm{d}q}{\mathrm{d}\nu}\right) - \frac{1}{\eta_1} \min_{x \in \mathcal{X}(\nu)} \Psi_f^\nu(x) \\
& + \sum_{t=1}^{T} \left[\int \frac{\eta_t}{2} \frac{(\ell_t(\theta) - m_t)^2}{f''(\overline{z}_{t+1}(\theta))} \nu(\mathrm{d}\theta) - \left(\frac{1}{\eta_{t+1}} - \frac{1}{\eta_t}\right) \Psi_f^\nu(x_{t+1}) \right],
\end{aligned} \tag{3}
$$

where
$$\tilde{x}_{t+1} \in \arg\min_{x \in \mathcal{L}_+^1(\nu)}\left\{ \langle \ell_t - m_t\mathbb{1}, \ x\rangle_\nu + \frac{1}{\eta_t} \int B_f(x(\theta); x_t(\theta))\nu(\mathrm{d}\theta) \right\}.$$

Further, if $\inf_{\theta \in \Theta} \ell_t(\theta) \geq m_t$, then $\tilde{z}_{t+1} \leq x_t$.

Under further conditions on f, these bounds can be used to derive variance bounds with respect to the (intermediate) predictive distributions, similar to AdaHedge [v+11] and AdaFTRL [OP15b], or with respect to the normalized base measure, as in [A21]. We state the conditions on the regularizer and the corresponding regret bounds in the following corollary.

Corollary 1. *In the setting of Theorem 1, suppose further that $f(1/\nu(\Theta)) \geq 0$ and $(\ell_t)_{t \in \mathbb{N}} \subseteq \mathcal{L}_{[0,1]}^\infty$.*

  1. If $1/f''(x) \leq Cx$, $\eta_{t+1} = (C[3/4 + \sum_{s=1}^{t-1} \mathrm{Var}_{\theta \sim \nu^{(\hat{z}_s)}} \ell_s(\theta)])^{-1/2}$ gives
$$R_T(q) \leq [\Psi_f^\nu(\mathrm{d}q/\mathrm{d}\nu) + 1]\sqrt{C[3/4 + \textstyle\sum_{t=1}^{T-1} \mathrm{Var}_{\theta \sim \nu^{(\hat{z}_t)}} \ell_t(\theta)]}.$$

  2. If $1/f'' \leq C$, $\eta_{t+1} = (C\,\nu(\Theta)[1/4 + \sum_{s=1}^{t} \mathrm{Var}_{\theta \sim \overline{\nu}} \ell_s(\theta)])^{-1/2}$ for $\overline{\nu} = \nu/\nu(\Theta)$ gives
$$R_T(q) \leq [\Psi_f^\nu(\mathrm{d}q/\mathrm{d}\nu) + 1]\sqrt{C\,\nu(\Theta)[1/4 + \textstyle\sum_{t=1}^{T} \mathrm{Var}_{\theta \sim \overline{\nu}} \ell_t(\theta)]}.$$

4 FTRL bounds for the semi-adversarial and quantile regret paradigms

In this section we introduce our new algorithms, FTRL-CARL (FTRL with constrained-adaptive root-logarithmic regularization) for the semi-adversarial paradigm and abNormal for KL regret, and present our regret upper bounds for these algorithms in Subsections 4.1 and 4.2 respectively. An important commonality of the regularizers used by FTRL-CARL and abNormal is that they are both defined using the form of Eq. (1) with functions f that approximately satisfy the differential equations

$$f \cdot f'' = \pm 1. \tag{4}$$

Since the generic bound we obtain in Theorem 1 yields components based upon integrals of both f and $1/f''$, balancing these terms without free tuning parameters requires Eq. (4) to approximately hold. Heuristically, trying to balance these terms with tuning parameters rather than by the choice of f seems to lead to non-adaptive or non-uniform bounds. Hedge provides an example of this for both the semi-adversarial and KL regret cases. In the semi-adversarial paradigm, Bilodeau, Negrea, and Roy [BNR20] showed that Hedge cannot be tuned in a way that is minimax optimal and agnostic to the semi-adversarial constraint that prevails. Similarly, without tuning the learning rate to be dependent on the comparator distribution (equivalently, the quantile of interest), KL (and quantile) regret bounds for Hedge are suboptimal.

In Subsection 4.2.2, we present our lower bound for quantile regret. Bounds for quantile regret and KL regret can be related by observing a) that for $\delta_{(i_\epsilon)}$ denoting a point-mass on the i_ϵth best expert with respect to L_T,

$$R_T(\delta_{(i_\epsilon)}) \leq R_T(u_\epsilon),$$

where $\epsilon = i_\epsilon/N$ and $u_\epsilon = \frac{1}{i_\epsilon} \sum_{j=1}^{i_\epsilon} \delta_{(j)}$ is the uniform distribution over the top i_ϵ experts, and b) that $\mathrm{KL}\left(u_\epsilon \| \mathrm{Unif}([N])\right) = \log(1/\epsilon)$. Thus, KL upper bounds are also upper bounds on quantile regret and quantile regret lower bounds are also lower bounds on certain KL regrets. The leading term of our lower bound for quantile regret has order matching the leading term in our upper bound for quantile regret implied by our KL bound, establishing the minimax rate of regret as $\sqrt{T \log(1/\epsilon)}$.

4.1 Semi-adversarial regret bounds

The semi-adversarial paradigm is characterized by an unknown a *time-homogeneous convex constraint* on the adversary's choice of loss distribution. This constraint is formally represented by a convex set of probability distributions on $\mathcal{L}_{[0,1]}^\infty$, denoted by $\mathcal{D}$. At each round t, the adversary is free to select any distribution from $\mathcal{D}$ to sample ℓ_t from. Note that when $\mathcal{D}$ is the set of all probability distributions, the worst-case adversarial setting is recovered, and when $\mathcal{D}$ is a singleton, the stochastic setting is recovered. For a more detailed description of this setting, see Section 2.2 of [BNR20].

Minimax regret in the semi-adversarial paradigm is quantified using a few key objects that summarize $\mathcal{D}$. The first is the collection of *effective stochastic gaps*, defined for each expert $i \in [N]$ by

$$\Delta_i = \inf_{p \in \mathcal{D}} \max_{i' \in [N]} \mathbb{E}_{\ell \sim p} \left[\ell(i) - \ell(i') \right].$$

Note that this extends the single stochastic gap of Bilodeau, Negrea, and Roy [BNR20], defined as

$$\Delta_0 = \min \left\{ \Delta_i : i \in [N], \Delta_i > 0 \right\}.$$

The second object is the set of *effective experts*, which is a subset of $[N]$ defined by

$$\mathcal{I}_0 = \left\{ i \in [N] : \Delta_i = 0 \right\}.$$

This is the set of all experts who are optimal in expectation for some element of $\mathcal{D}$ (or possibly in the limit along some sequence in $\mathcal{D}$). The number of effective experts is then $N_0 = |\mathcal{I}_0|$.

In this paradigm, the goal is to compete against the best expert. Letting δ_i denote a point-mass on expert i, for notational simplicity we set $R_T \equiv \max_{i \in [N]} R_T(\delta_i)$. A simplified version of the main result of this section (Theorem 2) demonstrates that the algorithm we introduce, FTRL-CARL, incurs an expected regret for any $T \in \mathbb{N}$ of at most

$$\mathbb{E}R_T \leq \sqrt{2T \log N_0} + 25 \frac{\log N}{\Delta_0}.$$

To describe FTRL-CARL, we introduce a new regularizer for FTRL designed for semi-adversarial regret, which improves on the performance of Meta-CARE from Bilodeau, Negrea, and Roy [BNR20] and does not require their extra meta-learning step. Let $h_C : [0,1] \to \mathbb{R}$ be given by

$$h_C(x) = \begin{cases} x\sqrt{2\log(1/x)} - \sqrt{\frac{\pi}{2}}\,\mathrm{erf}\left(\sqrt{\log(1/x)}\right) + x(N-1)\sqrt{\frac{\pi}{2}} & x \in (0,1] \\ -\sqrt{\pi/2} & x = 0, \end{cases}$$

set $H_C(w) = \sum_{i \in [N]} h_C(w(i))$, and define FTRL-CARL as FTRL with regularizer $\Psi^\nu_{-h_C}(w) = -H_C(w)$ and learning rate $\eta_t = 2/\sqrt{t}$. An intuitive explanation for this choice of regularizer can be found in Subsection 4.1.1.

To analyze FTRL-CARL, we define two more notions to characterize which stage of learning the algorithm is in. Note that each of these stages occur *implicitly* while running FTRL-CARL, and consequently the user does not need to know any of the quantities associated with $\mathcal{D}$.

For each $i \in [N] \setminus \mathcal{I}_0$, let $T_i = \lceil 8(\log N)/\Delta_i^2 \rceil$ and $T_0 = \max_{i \in [N] \setminus \mathcal{I}_0} T_i$. For each $t \in \mathbb{N}$ let $\mathcal{I}_0^{(t)} = \mathcal{I}_0 \cup \{i \in [N] \setminus \mathcal{I}_0 \text{ s.t. } T_i \geq t\}$ and $N_0^{(t)} = |\mathcal{I}_0^{(t)}|$. For each $j \in \{0, 1, ..., N - N_0 - 1\}$, let $T_{(j)}$ be the decreasing ordered values of T_i, so that $T_0 = T_{(0)} \geq T_{(1)} \geq ... \geq T_{(N-N_0-1)}$. Let $T_{(N-N_0)} = 0$. Let $\Delta_{(j)}$ be the corresponding increasing ordered values of Δ_i, so that $\Delta_0 = \Delta_{(0)} \leq \Delta_{(1)} \leq ... \leq \Delta_{(N-N_0-1)}$.

Theorem 2. *For any time-homogeneous convex constraint $\mathcal{D}$, FTRL-CARL achieves:*
If $T \leq T_0$,
$$\mathbb{E}R_T \leq \sqrt{2T \log N},$$
and if $T > T_0$,

$$\mathbb{E}R_T \leq \sqrt{2T \log N_0} + 4(\log N) \sum_{j=0}^{N-N_0-1} W_{j,N,N_0} \frac{1}{\Delta_{(j)}}$$
$$+ \frac{5\sqrt{2}}{N\sqrt{\log N}}(e^{-1/2} + \mathbb{I}[N_0 = 1]) \sum_{i \in [N] \setminus \mathcal{I}_0} \frac{\mathbb{I}[T > T_i]}{\Delta_i} + \sqrt{\log N},$$

where $W_{j,N,N_0} = \frac{1}{\sqrt{\log N}}\left(\sqrt{\log(N_0 + j + 1)} - \sqrt{\log(N_0 + j)}\right)$.

Remark 1. *A more refined version of the bound for $T < T_0$ can be found in Appendix B. Note that, by telescoping, $\sum_{j=0}^{N-N_0-1} W_{j,N,N_0} = 1 - \sqrt{(\log N_0)/(\log N)} \leq 1$. Further, using $1/\Delta_i \leq 1/\Delta_0$, we obtain an upper bound of order $\mathcal{O}(\sqrt{T \log N_0} + (\log N)/\Delta_0)$, which improves on the* Meta-CARE *upper bound for $N_0 > 1$ of order $\mathcal{O}(\sqrt{T \log N_0} + (\log N)^{3/2}/\Delta_0)$.* ◁

4.1.1 Intuition for FTRL-CARL in the semi-adversarial paradigm

The CARL regularizer can be motivated by the following intuition from the Hedge algorithm. For I.I.D. losses, the upper bounds for Hedge [Theorem 2, MG19] are only optimal with a learning rate $\eta_t \gtrsim \sqrt{(\log N)/t}$, and matching lower bounds for the adversarial setting suggest this learning rate constraint is actually necessary for optimal performance. Such a learning rate ensures that the weights of each suboptimal (in expectation) expert decay fast enough, where "fast enough" means the total expected regret incurred from rounds where Hedge selects that expert is bounded by $(\log N)/(N\Delta_i)$. In the semi-adversarial paradigm with more than one effective expert, FTRL-CARE (of [BNR20]) can be interpreted as Hedge with an adaptive learning rate that asymptotically satisfies $\eta_t \gtrsim \sqrt{(\log N_0)/t}$. This smaller learning rate applied to the effective experts is necessary to incur asymptotically $\sqrt{T \log N_0}$ regret. However, since this learning rate is smaller, when there are two or more effective experts the weights assigned to the ineffective experts are slightly too large. Specifically, the total expected regret incurred from rounds where FTRL-CARE selects the ith ineffective expert is $(\log N)^{3/2}/(N\Delta_i)$ rather than $(\log N)/(N\Delta_i)$.

To rectify this, heuristically, it would be ideal to have expert-specific learning rates of size $\sqrt{(\log N_0)/t}$ for the effective experts and $\sqrt{(\log N)/t}$ for the ineffective experts. Since the effective experts will have weights proportional to $1/N_0$ and the ineffective experts will have weights smaller than $1/N$, the heuristic learning rate can be implicitly defined by $\eta_t(i) = c\sqrt{\log(1/w_t(i))/t}$.

The weights of Hedge are defined by the equation $\log(1/w_t(i)) = \eta_t(L_{t-1}(i) + \lambda_t)$, where λ_t is chosen to ensure the weights are normalized. Replacing η_t with our heuristic yields $\log(1/w_t(i)) = c\sqrt{\log(1/w_t(i))/t}\,(L_{t-1}(i) + \lambda_t)$, which can be rearranged to obtain

$$\sqrt{\log(1/w_t(i))} = \tfrac{c}{\sqrt{t}}(L_{t-1}(i) + \lambda_t).$$

By Lemma 1, this is exactly the formula for the weights produced with FTRL for the regularizer $-H_C$ and learning rate $\eta_t = c/\sqrt{t}$.

As Theorem 2 shows, our modification to the Hedge algorithm is sufficient to yield semi-adversarial regret bounds with expected regret contribution of size $(\log N)/\Delta_0$ from the ineffective experts, improving on the order of the regret of FTRL-CARE in all cases and Meta-CARE when there is more than one effective expert.

4.2 Regret bounds for f-divergence FTRL

In the KL regret paradigm, the losses are once again chosen adversarially, but only compete against a mixture of the experts instead of the best. For any probability distribution π on (Θ, Σ) and convex $f : \mathbb{R}_+ \to \mathbb{R}$ with $f(1) = 0$, the f-divergence FTRL algorithm is defined for some $c > 0$ by selecting

$$x_{t+1} \in \operatorname*{arg\,min}_{x \in \mathcal{X}(\pi)} \left\{ \langle L_t,\, x \rangle_\pi + \tfrac{\sqrt{t}}{c}\, D_f^\pi(x) \right\}$$

at each round, where $D_f^\pi(x) = \int f(x(\theta))\pi(\mathrm{d}\theta) = D_f\left(\pi^{(x)} \,\middle\|\, \pi\right)$. We have the following theorem for the performance of this algorithm under certain conditions on f.

Theorem 3. *Suppose $f : \mathbb{R}_+ \to \mathbb{R}$ satisfies:*

  1. $f(1) = 0$;
  2. f is twice continuously differentiable, $f'' > 0$ on $\mathbb{R}_{++}$, and $f''(0+) > 0$;
  3. either f or $1/f''$ is increasing on $\mathbb{R}_{++}$;
  4. there exist $c_1, c_2 > 0$ such that $f'' \cdot (f + c_1) \geq c_2$.

For any sequence $(\ell_t)_{t \in \mathbb{N}} \subseteq \mathcal{L}_{[0,1]}^\infty$, probability measure q on (Θ, Σ), and T, f-divergence FTRL with $\eta_t = \sqrt{c_2/t}$ achieves

$$R_T(q) \leq \sqrt{\tfrac{T+1}{c_2}}\, D_f\left(q \,\middle\|\, \pi\right) + \tfrac{c_1}{\sqrt{c_2}}\sqrt{T}.$$

4.2.1 Root-KL regret bounds via f-divergence FTRL

Th f-divergence regret bound above can be easily turned into a uniform root-KL bound under the following additional assumption (the result follows from Lemma 8).

Corollary 2. *If, in addition to the assumptions of Theorem 3, there exist $k_1 \in \mathbb{R}$ and $k_2 \in \mathbb{R}_+$ with $f(x) \leq k_1 + k_2 x \sqrt{\log(1+x)}$, then*

$$R_T(q) \leq \sqrt{\tfrac{T+1}{c_2}}\left(k_1 + k_2\sqrt{1 + \mathrm{KL}\left(q \,\|\, \pi\right)}\right) + \tfrac{c_1}{\sqrt{c_2}}\sqrt{T}.$$

We refer to f-Divergence FTRL with an f satisfying the conditions of Theorem 3 and Corollary 2 as abNormal.

4.2.2 Lower bound for quantile regret

Our final theoretical result is the first general lower bound for quantile regret on N experts, which is tight (up to lower order terms) with Corollary 2 when π is uniform on $[N]$ and q is uniform on only the top quantile of experts.

Theorem 4. *For all $N \in \mathbb{N}$ there exists a probability distribution p on $[0,1]^N$ such that for any sequence of player predictions $(w_t)_{t \in \mathbb{N}} \subseteq \mathtt{simp}([N])$, $i_\epsilon \in \{1, \ldots, \lfloor N/4 \rfloor\}$, and $T \in \mathbb{N}$,*

$$\mathbb{E}_{\ell_{1:T} \sim p^{\otimes T}} R_T(\delta_{(i_\epsilon)}) \geq \sqrt{(T/2)\left(\log(1/\epsilon) - 2\log 2 + 1/\pi\right)} - \sqrt{2/\pi} - 2\log N - \log 2,$$

where $\delta_{(i_\epsilon)}$ is the point-mass on the i_ϵth best expert with respect to L_T and $\epsilon = i_\epsilon/N$.

4.2.3 Examples of f for f-divergence FTRL

To demonstrate the utility of Theorem 3, we now show how our result recovers the classical analysis for Hedge and applies to our new root-logarithmic regularizer.

Example 1 (Hedge). *The regularizer corresponding to* Hedge *(and the Gibbs posterior from Bayesian inference) is given by $f(x) = x \log x$, which satisfies $D_f(\cdot \| \pi) = \mathrm{KL}(\cdot \| \pi)$ for any probability measure π on (Θ, Σ). This choice satisfies the assumptions of Theorem 3 with $c_1 = 1 + 1/e$ and $c_2 = 1$, since $1/f''$ is increasing, but does* not *satisfy the conditions of Corollary 2. Thus, we do not obtain uniform root-KL bounds for* Hedge; *we conjecture this is in fact a limitation of* Hedge *and not merely an artifact of our analysis. We can, however, apply Corollary 1 with $C = 1$ to obtain*

$$R_T(q) \leq \left[\mathrm{KL}(q \| \pi) + 1 \right] \sqrt{3/4 + \sum_{t=1}^{T-1} \mathrm{Var}_{\theta \sim \pi(\hat{z}_t)} \ell_t(\theta)}.$$

The f-divergence FTRL solution with learning rate η_{t+1} recovers the familiar formula

$$x_{t+1}(\theta) = \frac{\exp(-\eta_{t+1} L_t(\theta))}{\int \exp(-\eta_{t+1} L_t(\vartheta)) \pi(\mathrm{d}\vartheta)}. \qquad \triangleleft$$

Example 2 (χ^2-divergence). *Alquier [A21] analyzed f-divergence FTRL with constant learning rates, obtaining variance bounds (Theorem 2.1) that require knowledge of the variance to tune the learning rate. He specifically focused on the KL-divergence, covered by the previous example, and the χ^2-divergence, corresponding to $f(x) = x^2 - 1$. This f clearly satisfies the conditions of Theorem 3 with $c_1 = c_2 = 2$, so we match the optimized bound of Alquier [A21, Corollary 2.4] with*

$$R_T(q) \leq \sqrt{T} \chi^2(q \| \pi) + \sqrt{2T}.$$

Further, the conditions of Corollary 1 are satisfied with $C = 1/2$, so we obtain the novel, potentially much smaller variance bound (without requiring advance knowledge of the variances)

$$R_T(q) \leq \frac{1}{\sqrt{2}} \left[\chi^2(q \| \pi) + 1 \right] \sqrt{1/4 + \sum_{t=1}^{T} \mathrm{Var}_{\theta \sim \pi} \ell_t(\theta)}.$$

Alquier [A21] does not comment on the computability of the FTRL solution except in the Gaussian case with KL-divergence. By Lemma 1, we obtain that the χ^2-divergence FTRL solution with learning rate η_{t+1} is given by

$$x_{t+1}(\theta) = \tfrac{1}{2} \left(k_{t+1}^* - \eta_{t+1} L_t(\theta) \right)_+$$

where $k_{t+1}^* \in \mathbb{R}$ solves $\int [\frac{1}{2}(k_{t+1}^* - \eta_{t+1} L_t(\theta))_+] \pi(\mathrm{d}\theta) = 1$. $\qquad \triangleleft$

Example 3 (abNormal). *One f that obtains root-KL bounds is $f(x) = \int_1^x \sqrt{2 \log(1+s)} \, \mathrm{d}s$. This satisfies the assumptions of Theorem 3 with $c_1 = 2$ and $c_2 = 1/\sqrt{2}$ since f is increasing, and satisfies the conditions of Corollary 2 with $k_1 = 0$ and $k_2 = \sqrt{2}$, so we obtain*

$$R_T(q) \leq 2\sqrt{(T+1)(1 + \mathrm{KL}(q \| \pi))} + \sqrt{8T}.$$

The f-divergence FTRL solution with learning rate η_{t+1} is given by

$$x_{t+1}(\theta) = \exp \left\{ \left(k_{t+1}^* - \eta_{t+1} L_t(\theta) \right)_+^2 / 2 \right\} - 1,$$

where $k_{t+1}^* \in \mathbb{R}$ solves $\int [\exp\{ (k_{t+1}^* - \eta_{t+1} L_t(\theta))_+^2 / 2\} - 1] \pi(\mathrm{d}\theta) = 1$. Note that this formula is remarkably similar to NormalHedge, *which assigns weights to experts according to*

$$w_t(i) \propto \left[\sum_{s=1}^{t-1} \langle \ell_s, w_s \rangle - L_{t-1}(i) \right]_+ \exp \left(\left[\sum_{s=1}^{t-1} \langle \ell_s, w_s \rangle - L_{t-1}(i) \right]_+^2 / 2c_{t-1} \right),$$

where c_{t-1} solves $\sum_{i \in [N]} \exp([\sum_{s=1}^{t-1} \langle \ell_s, w_s \rangle - L_{t-1}(i)]_+^2 / 2c_{t-1}) = eN$. $\qquad \triangleleft$

4.2.4 Intuition for f-divergence FTRL in the KL regret paradigm

The conditions on f in Theorem 3 are essentially the minimal conditions needed for the summation terms in Theorem 1 to cancel with each other regardless of the actual losses. Intuitively, to achieve f-divergence regret bounds with $D_f^\pi(\cdot)$-regularized FTRL using the bound of Theorem 1, these terms

must cancel so that there is no dependence in the final bound on the regularity of the distributions actually selected by the algorithm. The condition on f in Corollary 2 is essentially the minimal condition needed for Jensen's inequality to imply $D_f\left(\cdot \| \cdot\right) \lesssim \sqrt{\mathrm{KL}\left(\cdot \| \cdot\right)}$. That it is possible to satisfy both of these conditions simultaneously is the crucial observation that enables our result.

All regularizers to which both Theorem 3 and Corollary 2 apply are essentially equivalent to $f(x) = \int_1^x \sqrt{2\log(1+s)}\mathrm{d}s$, meaning they have the same asymptotic growth rate. To see this, first observe that this f has the minimum amount of curvature needed to satisfy $f'' \cdot (f + c_1) \geq c_2$ since $(x\sqrt{\log x}) \cdot (x\sqrt{\log x})''$ is asymptotically constant. Second, this f has the largest asymptotic growth rate that still satisfies $f(x) \leq k_1 + k_2 x\sqrt{\log(1+x)}$. These two facts together constrain the shape of f to the root-logarithmic choice.

4.2.5 Applications of root-KL regret bounds

Predicting as well as the terminal posterior using f-divergence FTRL   A reasonable choice of distribution to measure regret against is the posterior distribution $\hat{\pi}_T$ after having seen T rounds of data. A consequence of Theorem 3 and Corollary 2 is that, for bounded log-likelihoods, the total loss incurred by making predictions according to f-divergence FTRL for suitable f is bounded by the loss incurred by the terminal posterior $\hat{\pi}_T$ plus an excess regret of the order $\sqrt{T\,\mathrm{KL}\left(\hat{\pi}_T \| \pi\right)}$. This excess loss is smaller than $T + \mathrm{KL}\left(\hat{\pi}_T \| \pi\right)$, which is the best available bound for excess loss when predicting according to the posterior $\hat{\pi}_t$ at each round $t \in [T]$, and smaller than $\sqrt{T}\,\mathrm{KL}\left(\hat{\pi}_T \| \pi\right)$, which is the best available bound for the excess loss when predicting with Hedge if it is not tuned with *a priori* knowledge of $\mathrm{KL}\left(\hat{\pi}_T \| \pi\right)$. These worse excess loss bounds follow from the analysis contained in Zhang [Z06], although he only applies them to comparing against the "true" data-generating parameter.

Model selection using f-divergence FTRL   Extending the interpretation of Orabona and Pál [OP16] by Foster, Krishnamurthy, and Luo [FKL20] to countable union model classes, we can consider an infinite sequence of disjoint finite expert classes (note any nested sequence can be made disjoint), $\Theta_1, \Theta_2, \ldots$, and let $\Theta = \bigcup_{m\geq 1} \Theta_m$. Assigning to Θ the prior $\pi(\theta) \propto \frac{1}{m^2 |\Theta_m|}$ for each $\theta \in \Theta_m$, we recover the following regret bound for f-divergence FTRL with learning rate $\eta_t \propto 1/\sqrt{t}$ from Corollary 2:

$$R_T(\delta_\theta) \leq \mathcal{O}\left(\sqrt{T(\log|\Theta_m| + \log m)}\right) \text{ for all } \theta \in \Theta_m \text{ and all } m \in \mathbb{N}.$$

5   Limitations

One limitation of our results, which is common in the online learning literature, is that they only apply to bounded losses. The extension of learning theory to unbounded losses has seen increased interest in recent years [GM20; A21; MVZ21], although it remains a major open problem to achieve guarantees for arbitrary losses. In particular, log loss for many nonparametric learners is not covered by the current unbounded loss literature, and will have important implications in statistical learning and density estimation when resolved.

A second limitation of our work is that finding the implicit normalizing constant—k^* in Lemma 1—is computationally difficult. It is at least as costly as finding the normalizing constant for a Bayesian posterior (or running Hedge), which corresponds to one evaluation of the left-hand side of Eq. (2). For Hedge, where $f(x) = x\log(x)$, one evaluation of that equation is sufficient, but in general finding the root of Eq. (2) to a fixed precision will take a fixed number of evaluations depending on the desired precision, and so FTRL with a general f will be that many times more computationally expensive than Hedge. It is possible that variational approaches for Bayesian inference, which avoid direct normalization of the posterior, may also be applicable for FTRL with a general f, and that line of inquiry may lead to novel, efficient, and high-performance learning algorithms.

A final limitation is that we do not obtain variance bounds together with uniform root-KL bounds, although our approach leads to both separately (Corollary 1 and Corollary 2), so we are optimistic our techniques can lead to such bounds, which would resolve multiple open problems.

References

[A+17]   A. Agarwal, H. Luo, B. Neyshabur, and R. E. Schapire. "Corralling a Band of Bandit Algorithms". In: *Proceedings of the 30th Conference on Learning Theory*. 2017.

[A21]   P. Alquier. "Non-Exponentially Weighted Aggregation: Regret Bounds for Unbounded Loss Functions". In: *Proceedings of the 38th International Conference on Machine Learning*. 2021.

[AB09]   J.-Y. Audibert and S. Bubeck. "Minimax Policies for Adversarial and Stochastic Bandits". In: *Proceedings of the 22nd Conference on Learning Theory*. 2009.

[ABL11] J.-Y. Audibert, S. Bubeck, and G. Lugosi. "Minimax Policies for Combinatorial Prediction Games". In: *Proceedings of the 24th Conference on Learning Theory*. 2011.

[AC65]   M. M. Ali and L. K. Chan. "Some Bounds for Expected Values of Order Statistics". *Annals of Mathematical Statistics* 36.3 (1965), pp. 1055–1057.

[AHR08] J. D. Abernethy, E. Hazan, and A. Rakhlin. "Competing in the Dark: An Efficient Algorithm for Bandit Linear Optimization". In: *Proceedings of the 21st Conference on Learning Theory*. 2008.

[AR09]   J. D. Abernethy and A. Rakhlin. "Beating the Adaptive Bandit with High Probability". In: *Proceedings of the 22nd Conference on Learning Theory*. 2009.

[B42]   Z. W. Birnbaum. "An Inequality for Mill's Ratio". *Annals of Mathematical Statistics* 13.2 (1942), pp. 245–246.

[B60]   H. Bauer. "Minimalstellen von Funktionen und Extremalpunkte. II". *Archiv der Mathematik* 11.1 (1960), pp. 200–205.

[BM89]   J. Bretagnolle and P. Massart. "Hungarian Constructions from the Nonasymptotic Viewpoint". *Annals of Probability* 17.1 (1989), pp. 239–256.

[BNR20] B. Bilodeau, J. Negrea, and D. M. Roy. *Relaxing the I.I.D. Assumption: Adaptively Minimax Optimal Regret via Root-Entropic Regularization*. arXiv:2007.06552. 2020.

[C+97]   N. Cesa-Bianchi, Y. Freund, D. Haussler, D. P. Helmbold, R. E. Schapire, and M. K. Warmuth. "How to Use Expert Advice". *Journal of the ACM* 44.3 (1997), pp. 427–485.

[CFH09] K. Chaudhuri, Y. Freund, and D. J. Hsu. "A Parameter-Free Hedging Algorithm". In: *Advances in Neural Information Processing Systems 22*. 2009.

[CL06]   N. Cesa-Bianchi and G. Lugosi. *Prediction, Learning, and Games*. Cambridge: Cambridge University Press, 2006.

[CMS07] N. Cesa-Bianchi, Y. Mansour, and G. Stoltz. "Improved Second-Order Bounds for Prediction with Expert Advice". *Machine Learning* 66.2 (2007), pp. 321–352.

[CV10]   A. Chernov and V. G. Vovk. "Prediction with Advice of Unknown Number of Experts". In: *Proceedings of the 26th Conference on Uncertainty in Artificial Intelligence*. 2010.

[F+16]   D. J. Foster, Z. Li, T. Lykouris, K. Sridharan, and É. Tardos. "Learning in Games: Robustness of Fast Convergence". In: *Advances in Neural Information Processing Systems 30*. 2016.

[FKL20] D. J. Foster, A. Krishnamurthy, and H. Luo. "Open Problem: Model Selection for Contextual Bandits". In: *Proceedings of the 33rd Conference on Learning Theory*. 2020.

[FS97]   Y. Freund and R. Schapire. "A Decision-Theoretic Generalization of On-Line Learning and an Application to Boosting". *Journal of Computer and System Sciences* 55.1 (1997), pp. 119–139.

[GM20]   P. D. Grünwald and N. A. Mehta. "Fast Rates for General Unbounded Loss Functions: From ERM to Generalized Bayes". *Journal of Machine Learning Research* 21.56 (2020), pp. 1–80.

[GSv14] P. Gaillard, G. Stoltz, and T. van Erven. "A Second-Order Bound with Excess Losses". In: *Proceedings of the 27th Conference on Learning Theory*. 2014.

[H+20]   N. J. A. Harvey, C. Liaw, E. Perkins, and S. Randhawa. "Optimal Anytime Regret with Two Experts". In: *Proceedings of the 61st Annual IEEE Symposium on Foundations of Computer Science*. 2020.

[HK10]   E. Hazan and S. Kale. "Extracting Certainty from Uncertainty: Regret Bounded by Variation in Costs". *Machine Learning* 80.2 (2010), pp. 165–188.

[K13]   W. M. Koolen. "The Pareto Regret Frontier". In: *Advances in Neural Information Processing Systems 26*. 2013.

[Kv15]   W. M. Koolen and T. van Erven. "Second-Order Quantile Methods for Experts and Combinatorial Games". In: *Proceedings of the 28th Conference on Learning Theory*. 2015.

[LS14]   H. Luo and R. E. Schapire. "A Drifting-Games Analysis for Online Learning and Applications to Boosting". In: *Advances in Neural Information Processing Systems 27*. 2014.

[LS15]   H. Luo and R. E. Schapire. "Achieving All with no Parameters: Adanormalhedge". In: *Proceedings of the 28th Conference on Learning Theory*. 2015.

[LW94]   N. Littlestone and M. K. Warmuth. "The Weighted Majority Algorithm". *Information and Computation* 108.2 (1994), pp. 212–261.

[LWZ18]   H. Luo, C.-Y. Wei, and K. Zheng. "Efficient Online Portfolio with Logarithmic Regret". In: *Advances in Neural Information Processing Systems 32*. 2018.

[MG19]   J. Mourtada and S. Gaïffas. "On the Optimality of the Hedge Algorithm in the Stochastic Regime." *Journal of Machine Learning Research* 20.83 (2019), pp. 1–28.

[MVZ21]   J. Mourtada, T. Vaškevičius, and N. Zhivotovskiy. *Distribution-Free Robust Linear Regression*. arXiv:2102.12919. 2021.

[O19]   F. Orabona. *A Modern Introduction to Online Learning*. arXiv:1912.13213. 2019.

[OP15a]   F. Orabona and D. Pál. *Optimal Non-Asymptotic Lower Bound on the Minimax Regret of Learning with Expert Advice*. arXiv:1511.02176. 2015.

[OP15b]   F. Orabona and D. Pál. "Scale-Free Algorithms for Online Linear Optimization". In: *Proceedings of the 26th International Conference on Algorithmic Learning Theory*. 2015.

[OP16]   F. Orabona and D. Pál. "Coin Betting and Parameter-Free Online Learning". In: *Advances in Neural Information Processing Systems 29*. 2016.

[RST11]   A. Rakhlin, K. Sridharan, and A. Tewari. "Online Learning: Stochastic, Constrained, and Smoothed adversaries". In: *Advances in Neural Information Processing Systems 25*. 2011.

[S07]   S. Shalev-Shwartz. "Online Learning: Theory, Algorithms, and Applications". PhD thesis. The Hebrew University, 2007.

[SST11]   N. Srebro, K. Sridharan, and A. Tewari. "On the Universality of Online Mirror Descent". In: *Advances in Neural Information Processing Systems 24*. 2011.

[v+11]   T. van Erven, P. D. Grünwald, W. M. Koolen, and S. de Rooij. "Adaptive Hedge". In: *Advances in Neural Information Processing Systems 24*. 2011.

[V90]   V. G. Vovk. "Aggregating Strategies". In: *Proceedings of 3rd Workshop on Computational Learning Theory*. 1990.

[vvK18]   D. van der Hoeven, T. van Erven, and W. Kotłowski. "The Many Faces of Exponential Weights in Online Learning". In: *Proceedings of the 31st Conference On Learning Theory*. 2018.

[WL18]   C.-Y. Wei and H. Luo. "More Adaptive Algorithms for Adversarial Bandits". In: *Proceedings of the 31st Conference On Learning Theory*. 2018.

[Z06]   T. Zhang. "Information-Theoretic Upper and Lower Bounds for Statistical Estimation". *IEEE Transactions on Information Theory* 52.4 (2006), pp. 1307–1321.

[ZS19]   J. Zimmert and Y. Seldin. "An Optimal Algorithm for Stochastic and Adversarial Bandits". In: *The 22nd International Conference on Artificial Intelligence and Statistics*. 2019.