ReCo: Retrieve and Co-segment
for Zero-shot Transfer

Abstract

Semantic segmentation has a broad range of applications, but its real-world impact has been significantly limited by the prohibitive annotation costs necessary to enable deployment. Segmentation methods that forgo supervision can side-step these costs, but exhibit the inconvenient requirement to provide labelled examples from the target distribution to assign concept names to predictions. An alternative line of work in language-image pre-training has recently demonstrated the potential to produce models that can both assign names across large vocabularies of concepts and enable zero-shot transfer for classification, but do not demonstrate commensurate segmentation abilities.

In this work, we strive to achieve a synthesis of these two approaches that combines their strengths. We leverage the retrieval abilities of one such language-image pre-trained model, CLIP, to dynamically curate training sets from unlabelled images for arbitrary collections of concept names, and leverage the robust correspondences offered by modern image representations to co-segment entities among the resulting collections. The synthetic segment collections are then employed to construct a segmentation model (without requiring pixel labels) whose knowledge of concepts is inherited from the scalable pre-training process of CLIP. We demonstrate that our approach, termed **Re**trieve and **Co**-segment (ReCo) performs favourably to un-supervised segmentation approaches while inheriting the convenience of nameable predictions and zero-shot transfer. We also demonstrate ReCo's ability to generate specialist segmenters for extremely rare objects.

1 Introduction

The objective of *semantic segmentation* is to partition an image into coherent regions and to assign to each region a semantic label. This task has myriad applications across domains such as medical image analysis, autonomous driving, industrial process monitoring and wildlife tracking. However, there are several key challenges that have hindered the deployment of existing semantic segmentation approaches to date: (1) **Cost**: collecting manual pixel-level annotations is extraordinarily expensive (e.g. 90 minutes per image for high quality labels [14]), limiting the use of fully-supervised approaches; (2) **Flexibility**: supervised approaches have typically been trained with limited lists of pre-defined categories and lack the ability to recognise rare or novel categories (such as those described by free-form text); (3) **Complexity of deployment**: unsupervised segmentation methods have dramatically reduced annotation costs, but still exhibit the inconvenience of requiring labelled examples to assign names to predictions; (4) **Data access**: many existing approaches (both supervised and unsupervised) are trained on the *target data distribution*, requiring both that this distribution is

| image | ground-truth | ReCo (Ours) | ReCo+ (Ours) | image | ground-truth | ReCo (Ours) | ReCo+ (Ours) |

Figure 1: We propose ReCo, a new framework for semantic segmentation zero-shot transfer without pixel supervision. The figure depicts ReCo segmentations for COCO-Stuff [6], indicating promising results in the challenging zero-shot transfer setting. We also illustrate results with unsupervised adaptation to the target distribution (ReCo+), trading flexibility for improved segmentation quality.

known at training time (limiting flexibility) and that this data is accessible, which may not be the case for legal/ethical reasons (e.g. medical image data).

There is a rich body of semantic segmentation literature that proposes solutions to subsets of these challenges, but to our knowledge no existing work addresses their full combination. To tackle all four challenges, we draw inspiration from two lines of recent research. The first line of research has shown that modern deep architectures (most notably vision transformers [17]) develop the ability to infer the spatial extent of objects without pixel supervision [7, 57, 76, 83, 74] and moreover can establish semantically consistent correspondences across images [13, 23]. The second line of research has demonstrated that large-scale visual-language pre-training [68, 34] produces models that possess both a large vocabulary and remarkable *zero-shot transfer* potential—the ability to recognise concepts on target datasets without access to the target data distribution during training.

In this work, we target a synthesis of these two approaches that draws on their respective strengths for the semantic segmentation task. We first employ CLIP [68] to curate training sets from unlabelled images for any desired list of concepts. We then exploit the robust semantic correspondences offered by modern vision backbones to co-segment concepts among the resulting curated collections. Finally, we use these co-segmented concepts to construct a segmentation model for the given concepts, *without* requiring training. This framework, which we term **Re**trieve and **Co**-segment (ReCo), performs favourably to existing unsupervised segmentation approaches while preserving the benefits of a wide vocabulary, named predictions and zero-shot transfer exemplified by CLIP.

Our contributions are three-fold: (1) We propose the ReCo framework, enabling open vocabulary semantic segmentation, without pixel annotations or the need to provide labelled examples from the target domain, thus supporting the zero-shot transfer; (2) We compare our approach to prior work on standard semantic segmentation benchmarks (COCO-Stuff [6], Cityscapes [14], and KITTI-STEP [84]), and further illustrate the ability of ReCo to segment rare concepts beyond these benchmarks; (3) For cases when the target distribution *is* available, we demonstrate that a simple extension of our approach, ReCo+, can exploit this data access via unsupervised adaptation to bring further gains.

2   Related work

Our work is connected to several themes in the literature, which we describe next.

Unsupervised semantic segmentation. There has been considerable recent progress towards unsupervised semantic segmentation with deep neural networks by leveraging ideas from self-supervised learning. Learning objectives based on maximising mutual information between views [33, 58], metric learning across proposals [89, 79], equivariance and invariance constraints [12], distillation of self-supervised feature correspondences [23] and cross modal cues (vision and LiDAR) [82] have all shown their potential for this task. One drawback of these approaches is a reliance on either nearest neighbour search on a held-out set with pixel level annotations or the Hungarian algorithm [44] (optimally matching predictions against ground-truth semantic masks) to produce segments with

names. By contrast, ReCo is independent of labelled examples during both training and inference, simplifying deployment.

Weakly-supervised semantic segmentation. To reduce annotation costs, a number of works have explored weaker cues such eye tracking [60], pointing [4, 67, 11], sparse pixel labels [75], scribbles [48], web-queried samples [35], boxes [15, 41, 77], extreme clicks [61, 52], image-level labels [91, 85, 18, 1, 8, 64, 66] and free-form text [87]. However, such approaches still require the weak annotation to be attached to the data used to train the segmentation model—by contrast, ReCo can in principle train a segmenter from any unlabelled collection of images. ReCo also bears a conceptual similarity with *webly-supervised* approaches [19] for semantic segmentation [35, 73]. These methods employ an image search engine such as Google to provide training samples for concepts. However, their flexibility is limited (this approach cannot be applied to private or commercially sensitive data, for example) and lack the ability to leverage the knowledge of the search engine itself during inference (we demonstrate that integrating the vision-language model into the inference procedure brings significant gains in performance).

Zero-shot semantic segmentation with pretrained language/vision-language embeddings. A rich body of work has explored zero-shot semantic segmentation, broadly defined as the task of segmenting categories for which no labels were provided during training (often termed *zero-label* semantic segmentation [86]). The key idea underlying many of these works is to leverage relationships encoded in pretrained word embeddings (such as word2vec [53] or GloVe [65]) to enable generalisation to unseen categories [90, 5, 22, 86, 39, 28, 46, 62]. More recent work has sought to leverage the vision-language embedding space learned by CLIP [68] to improve dense prediction in various settings [92, 69, 45]. We adopt a variation of DenseCLIP [92] as a component of our framework. Additionally, differently from the above, we pursue the formulation of *zero-shot transfer* popularised by CLIP [68] which evaluates performance on *unseen datasets* rather than *unseen categories*. Consequently, unlike these works our model has no access to either labelled or unlabelled examples from the target data distribution. We note one exception: in addition to their primary zero-shot evaluations, DenseCLIP [92] also report an "annotation-free" evaluation without access to the target dataset—we compare our approach with theirs under an equivalent setting.

Large-vocabulary/rare concept segmenters. To scale up the number of concepts that can be segmented by a model several strategies based on captions [20], grounded text descriptions [38] and annotation transfer [29, 31] have been explored. In a differing direction, various losses and incremental learning techniques have been employed [30, 26] to better segment rare concepts. Unlike ReCo, however, each of the above approaches still requires costly pixel-level annotations.

Co-segmentation which aims to segment common regions among a collection of images, has been widely studied with classical computer vision approaches [70, 56, 80, 3, 37, 81]. The topic has been revisited with deep learning using shared encoder networks [9, 47, 2, 50], iterative refinement [88] and weak (class-label) supervision [27]. While ReCo can in principle make use of any unsupervised co-segmentation algorithm, we find that a simple correlation strategy works well, and thus we adopt it for our approach.

3   Method

In this section, we introduce the ReCo framework (Sec. 3.1) which enables zero-shot transfer for semantic segmentation with arbitrary categories. We describe a language-based gating mechanism to enhance the segmentation quality (Sec. 3.2), and a pseudo-labelling scheme, ReCo+, that adapts to a target distribution using predictions from ReCo (Sec. 3.3).

3.1   Retrieve and Co-segment (ReCo)

The inputs to ReCo are a collection of unlabelled images, and a list of text descriptions of concepts to be segmented. Through a combination of *image retrieval* and *co-segmentation* across the image collection, ReCo constructs a segmenter for the given concepts on the fly. During *inference*, this seg-menter is applied *without* fine-tuning to images from a target distribution of interest, thus supporting

Figure 2: In this work, we propose ReCo, a framework for open vocabulary semantic segmentation zero-shot transfer. **Top:** (1) Given a large-scale unlabelled dataset for indexing images, and a category to segment, we first curate an archive of k images from the unlabelled collection using CLIP [68]. (2) Using a pre-trained visual encoder (*e.g.,* MoCov2 [24], DeiT-S/16-SIN [57]), we extract dense features from the archive images, which are used to a generate reference image embedding for the given category via a a co-segmentation process. **Bottom:** (3) During inference, the reference image is employed to produce an initial segmentation of the target concept which is refined with DenseCLIP. $\otimes$ and $\odot$ denote inner product and Hadamard product, respectively. See Sec. 3 for details.

the zero-shot transfer. The interaction of these three stages is illustrated in Fig. 2 and discussed in more detail below.

Curating exemplars through image retrieval. The first hypothesis underpinning our approach is that it is possible to construct a sufficiently large and diverse unlabelled image collection that contains examples (or closely related examples) of any concept we wish to segment. We consider this hypothesis to be reasonable in light of the fact that recent research has produced a number of diverse datasets spanning billions of images [51, 21, 34, 72].

To make use of this hypothesis for segmentation, we employ a vision-language model to curate an archive of images for each concept of interest. In this work, we use CLIP [68], a model comprising an image encoder and a text encoder that enables efficient image retrieval for free-form text queries. In more detail, for a given text query describing a concept c the CLIP text encoder $\psi_{\mathcal{T}}$ produces an embedding $\psi_{\mathcal{T}}(c) \in \mathbb{R}^e$ which can be compared against the embeddings produced by the image encoder $\psi_{\mathcal{I}}$ for each image x in the unlabelled collection $\mathcal{U}$: $\{\psi_{\mathcal{I}}(x) \in \mathbb{R}^e : x \in \mathcal{U}\}$. We then build an archive from the k images that form nearest neighbours for each concept c. While a more sophisticated strategy (for instance, adjusting the archive size according to concept difficulty or prevalence) is possible with ReCo, we found that this simple approach worked well, and so we adopt it here. Note that, thanks to mature approximate nearest neighbour search techniques [36], this archive construction process can be readily applied to a collection $\mathcal{U}$ containing billions of images.

Co-segmentation with seed pixels. The second hypothesis underpinning our approach is that modern vision-language models such as CLIP are capable of constructing archives of *high purity* (i.e. a high ratio of the archive images contains the concept of interest) provided that such exemplars exist in the underlying image collection $\mathcal{U}$ (our first hypothesis). Our second hypothesis, which we validate through experiments in Sec. 4, enables the use of *co-segmentation* to obtain concept segments.

Concretely, given the k images comprising the archive for category c constructed by CLIP, we aim to segment regions corresponding to concepts that re-occur across the images. Since we expect the archive to be of high purity, and since modern visual backbones provide consistent semantic correspondences across images [23], we adopt a strategy of first identifying a *seed pixel* in each

image that we are confident belongs to the target category, c. Intuitively, good seed pixels are ones that have close neighbours (i.e. strong support) across each of the archive images, since we assume that: (i) the target concept is common to all images in the archive, (ii) our visual backbone will produce consistent features for pixels belonging to the same concept. We then use these seed pixels to construct a reference embedding that can be used to classify pixels belonging to c.

In detail, we first extract dense features for each image in the archive using a pre-trained image encoder $\phi_{\mathcal{I}}$:

$$\{F_1, \ldots, F_k\} = \{\phi_{\mathcal{I}}(x_1), \ldots, \phi_{\mathcal{I}}(x_k)\} \tag{1}$$

where $F_i \in \mathbb{R}^{d \times h \times w}$ denotes the dense features for the i^{th} image with height h, width w and d channels. Each such feature is L2-normalised along its channel dimension. [1] Note that any image encoder $\phi_{\mathcal{I}}$ can be employed here (it need not be CLIP).

We identify seed pixels in four steps: First, we construct an adjacency matrix $A^{khw \times khw}$ among all features in the archive. Here, each of the $k \times k$ submatrices, $A_{ij} \in \mathbb{R}^{hw \times hw}$, encodes pairwise similarities between features from image i and image j for $i, j \in \{1, ..., k\}$. Second, we aim to identify, for each pixel in the archive, the similarity of its nearest neighbour among each of the k images. To do so, we apply a `max` operator along the columns of each submatrix (reducing the hw colums of each submatrix to 1 and reducing the overall adjacency matrix dimensions to $khw \times k$). Third, we aim to identify the average *support* that each pixel has among the k archive images. For this, we apply a `mean` operator over the columns of each submatrix such that each row of the resulting $khw \times 1$ matrix encodes the mean maximum similarity across k images. Finally, we identify the seed pixel locations by applying an `argmax` operator to each of the k submatrices of size $hw \times 1$, yielding the spatial indices of the features in each image with highest average maximum similarity across the archive.

To construct a classifier for concept c, we simply average the embeddings of the k seed pixels from its archive and L2-normalise the resultant vector to produce the reference embedding $f_c \in \mathbb{R}^d$.

Inference. To localise an instance of the category in a new image x_{new}, we first compute the dot-product between f_c and the L2-normalised dense features F_{new} from the new image, and pass the result through a sigmoid:

$$P_{\text{new}}^c = \sigma(f_c \cdot F_{\text{new}}) \in [0, 1]^{h \times w} \tag{2}$$

where P_c denotes an initial estimate of the probability map corresponding to category c.

To refine this probability map, we draw inspiration from recent work [92, 69] showing that dense visual CLIP features can be usefully correlated against a given CLIP text embedding. Concretely, we employ the DenseCLIP mechanism of Zhou et al. [92] to highlight regions of the input that are salient for the target category c as follows. For image x_{new}, we extract features $V_{\text{new}} \in \mathbb{R}^{e_v \times h \times w}$ (here e_v denotes the value feature dimension) from the last self-attention layer values of the CLIP image encoder, project the features into the joint space $\mathbb{R}^e$ with the CLIP image encoder's final linear projection and L2-normalise the result. We then compute the CLIP text embedding $\psi_{\mathcal{T}}(c) \in \mathbb{R}^e$ for the target concept c (and L2-normalising) before producing a saliency map $\mathcal{S}_{\text{new}}^c \in [0, 1]^{h \times w}$ by applying the text embedding as a 1×1 convolution to the visual features and applying a sigmoid activation function to the result. Note that our use of a sigmoid activation function differs from the softmax used by [92], since we process each concept independently.

Our final probability map for category c is produced by the Hadamard product of these estimates:

$$\bar{P}_{\text{new}}^c = P_{\text{new}}^c \odot \mathcal{S}_{\text{new}}^c \tag{3}$$

In case of multiple categories predictions, we concatenate all the category prediction maps and apply `argmax` to the category dimension. As a post-processing step, we also experiment with the effect of applying a CRF [43] as a simple post-processing step (similarly to [23]). Pseudocode for ReCo can be found in the supplementary material.

---

[1]For clarity purposes, we assume that all images share the same spatial extent and thus their dense features. However, the proposed co-segmentation approach can be applied to images with different resolutions.

3.2 Language-guided co-segmentation and context elimination

Even when an archive has high purity, co-segmenting the target concept c from the collection of images can be challenging due to the potential presence of distractor category, $\tilde{c}$ that often co-occurs with c. For example, *cars* often co-occur with *roads* and likewise *aeroplanes* with *sky*. To minimise the risk of the co-segmentation algorithm anchoring on unintended categories, we introduce two mechanisms into the co-segmentation procedure, namely, *language-guided co-segmentation* and *context elimination*.

Language-guided co-segmentation. Specifically, for each x_i in the archive, we first compute the corresponding saliency map $\mathcal{S}_i^c \in [0,1]^{h \times w}$ using DenseCLIP. We then vectorise this map and use it to filter the co-segmentation similarities by replacing each row of $A_{j,i}$ with the Hadamard product of itself with $\text{vec}(\mathcal{S}_i^c) \in [0,1]^{1 \times hw}$ (where $\text{vec}(\cdot)$ denotes vectorisation) for each submatrix $j = \{1, ..., k\}$. Intuitively, this serves to act as a *gate* that preserves similarities only for pixels identified by CLIP as salient for the target concept.

Context elimination. To reduce the influence of widely co-occurring distractors, we select a few common background categories $\tilde{c}$ that frequently appear in images (*e.g., tree, sky, road*) and compute their reference embeddings $f_{\tilde{c}}$ as described in the seeding procedure of Sec. 3.1. We then use the resulting attention maps $P_i^{\tilde{c}}$ produced by these reference embeddings to suppress regions of common background context in the subsequent co-segmentation processes for different categories. This is done similarly as above, by vectorising and replacing each row of $A_{j,i}$ with the Hadamard product of itself with $\text{vec}(1 - P_i^{\tilde{c}}) \in [0,1]^{1 \times hw}$ for each submatrix $j = \{1, ..., k\}$. Note that if a target concept c is identical to one of the common background categories $\tilde{c}$, we simply assign f_c with $f_{\tilde{c}}$.

3.3 ReCo+: Fine-tuning ReCo with pseudo-labels

The ReCo framework outlined above requires no training and no access to the target distribution. However, it is possible to consider a simple extension to this idea when access to the target distribution is available. Our proposed extension, ReCo+, simply trains a segmentation architecture (*e.g.,* DeepLabv3+ [10]) with the segmentation masks from ReCo as pseudo-masks.

4 Experiments

In this section, we start by describing the datasets used for our experiments (Sec. 4.1) and implementation details (Sec. 4.2). Then, we conduct an ablation study (Sec. 4.3) and compare our model to state-of-the-art methods for unsupervised semantic segmentation (Sec. 4.4). Finally, we showcase our model's ability to segment rare-category objects (Sec. 4.5) and discuss limitations (Sec. 4.6).

4.1 Datasets

For our ablation study, we use the ImageNet1K [16] validation set to curate archive for concepts of interest. The dataset covers 1K classes with 50 images for each class. To measure segmentation performance in the zero-shot transfer setting, we use the PASCAL-Context [55] validation set for evaluation, which has 5,104 images of 59 categories excluding background class.

To compare with previous unsupervised segmentation methods, we further exploit the ImageNet1K training set to construct the reference embedding for the concept we wish to segment. The dataset has 1K classes with 1.2M images. We evaluate on standard benchmarks including the Cityscapes [14] validation split, which has 500 urban scene images of 27 categories, KITTI-STEP [84] validation set, which is composed of 2,981 urban scene images of 19 categories, and COCO-Stuff [6] validation split, which has 4,172 images of 171 low-level thing and stuff categories excluding background class. Following [12, 23], we only use the 27 mid-level categories for evaluation. For unsupervised adaptation with ReCo+ (Sec. 3.1), we train on ReCo pseudo-labels on the Cityscapes training set with 2,975 images, KITTI-STEP training set which contains 5,027 images, and the COCO-Stuff10K subset which has 9,000 images for each respective benchmark. We emphasize that **no ground-truth labels are used for training.**

Finally, to demonstrate our model's ability to segment rare concepts, we use the LAION-5B dataset [72] with 5 billion images as a large collection of images that we expect to satisfy our

Figure 3: **Ablation studies. Left:** Image retrieval performance of different CLIP models on the ImageNet1K validation set with k ranging from 5 to 50. ViT-L/14@336px performs particularly strongly, suggesting the ability to curate archives of high purity. **Right:** Co-segmentation performance on PASCAL-Context validation set, as we vary the archive size and choice of visual encoders. We observe a general trend towards improved performance with increasing archive size for all encoders.

first hypothesis, namely that it will have coverage of rare concepts. To assess performance, we use the FireNet dataset [59] which has 1,452 images spanning rare fire safety-related classes. For our experiment, we select the *fire extinguisher* class as an example of a concept that is important but rare in vision datasets (it is not contained in ImageNet1K [71], for example) and evaluate ReCo on 263 images containing at least one instance of the category. As a further proof of concept, we also demonstrate co-segmentations of the *Antikythera mechanism* (a historical item that does not appear in WordNet [54], or any labelled vision datasets that we are aware of).

4.2 Implementation details

Here, we describe the hyperparameters used to train ReCo+, inference details and evaluation metrics. Our implementation is based on the PyTorch library [63] and will be made publicly available.

ReCo+ Training. While ReCo does not require training, we train ReCo+ based on the DeepLabv3+ [10] segmentation architecture with a ResNet101 [25] backbone on the predictions from ReCo as described in 3.1. All training images are resized and center-cropped to 320×320 pixels and data augmentations such as random scaling, cropping, and horizontal flipping are applied with random color jittering, color dropping, and Gaussian blurring. We use the Adam optimiser [42] with an initial learning rate of 5×10^{-4} and a weight decay of 2×10^{-4} with the Poly learning rate schedule as in [49, 10]. Training consists of 20K gradient iterations with a batch size of 8 and takes about 5 hours on a single 24GB NVIDIA P40 GPU.

Inference. Whenever DenseCLIP is employed, we use the ResNet50x16 model (following [92]) to construct a saliency map for each image. For the COCO-Stuff and Cityscapes benchmarks, we resize and center crop the input images to 320×320 pixels as in [23]. For the KITTI-STEP validation set, we use the original resolution of each image as in [40]. For the FireNet benchmark, we resize the shorter side of images to 512 pixels and predict a single class of *fire extinguisher* by thresholding the predicted heatmap with probability of 0.5.

Evaluation metrics. Following the common practice [33, 12, 23], we report pixel accuracy (Acc.) and mean intersection-over-union (mIoU).

4.3 Ablation studies

Ability of CLIP to curate archives. We begin by assessing the validity of our second hypothesis—namely that CLIP is capable of achieving *high purity* archives from unlabelled images. To this end, we evaluate the retrieval performance of different CLIP models on ImageNet1K validation set when constructing different archive sizes. In detail, for each archive size, k, we compute the precision of the top-k retrieved images based on whether the the ground-truth image-labels match the query text. As can be seen in Fig. 3 (left), all CLIP models achieve solid retrieval performance, suggesting their potential for curating high purity archives as part of ReCo. Since ViT-L/14@336px performs best, we employ this as our retrieval model in the remaining experiments.

LGC	CE	CRF	Acc.	mIoU
✗	✗	✗	16.8	5.7
✓	✗	✗	24.2	9.5
✗	✓	✗	33.7	12.3
✓	✓	✗	36.9	13.7
✓	✓	✓	**37.3**	**13.9**

	DenseCLIP	Acc.	mIoU
ReCo (Ours)	✗	37.3	13.9
ReCo (Ours)	✓	**51.6**	**27.2**

Table 1: **Influence of ReCo components for zero-shot transfer on PASCAL-Context [55]. Left:** We observe that *Language-guided co-segmentation* (LGC), *Context elimination* (CE) and CRF [43] post-processing each contribute to improved performance. **Right:** We report the effect of integrating DenseCLIP during inference, which we observe brings a significant boost. All comparisons use a DeiT-SIN visual backbone for co-segmentation and ViT-L/14@336px for archive curation.

Influence of archive size and visual encoder used for co-segmentation. In Fig. 3 (right) we illustrate the effect of using different pre-trained architectures, *e.g.* MoCov2 [24], DINO [7], CLIP [68], DeiT-SIN [57], as the archive size (and thus the number of images used for co-segmentation) changes. The y-axis depicts segmentation performance for ReCo with these configurations on the PASCAL-Context benchmark. We observe that using larger archives tends to improve performance (likely due to their high purity) and that features from DeiT-SIN perform best. We therefore use DeiT-SIN with an archive size of k=50 for the remaining experiments otherwise stated.

Influence of ReCo framework components. We next assess the effect of the *language-guided co-segmentation* and *context elimination* components of ReCo which seek to improve the quality of co-segmentation achieved across each archive to boost downstream segmentation performance. When applying context elimination, we select *tree, sky, building, road*, and *person* as common background concepts appearing in natural images to be suppressed. In Tab. 1 (left), we show the effect of both of these strategies, together with the effect of applying a CRF [43] as post-processing. We observe that both language-guided co-segmentation and context elimination bring major gains in co-segmentation performance, while the CRF brings a further small gain. In Tab. 1 (right), we study the influence of integrating DenseCLIP into the inference procedure. We observe a significant gain which we believe is driven by the notable robustness of CLIP features under zero-shot transfer [68]. We therefore use each of these strategies (including CRF post-processing) in the remaining experiments.

4.4 Comparison to state-of-the-art unsupervised methods

We compare ReCo and ReCo+ to state-of-the-art unsupervised semantic segmentation models on standard benchmarks, including COCO-Stuff [6], Cityscapes [14] and KITTI-STEP [84] under both zero-shot transfer and unsupervised adaptation (training without labels on the target distribution). For COCO-Stuff, we observe that the mid-level categories used for evaluation are somewhat abstract for retrieval (for instance, one mid-level category is "outdoor objects", which may include many low-level categories beyond the target hierarchy). To avoid introducing ambiguity to the co-segmentation procedure, we instead directly use the low-level categories and then merge the predictions into the mid-level categories. Additionally, we rephrase two category names to be reduce ambiguity (*parking* to *parking lot* and *vegetation* to *tree*) in Cityscapes and KITTI-STEP based on the descriptions found in [14]. A detailed discussion can be found in the supplementary material.

As shown in Tab. 2, ReCo strongly outperforms prior models on all benchmarks for zero-shot transfer. Under an unsupervised adaptation protocol, ReCo+ outperforms the state-of-the-art by a large margin on the Cityscapes and KITTI-STEP. On COCO-Stuff, ReCo+ achieves slightly lower pixel accuracy compared to [23] but a considerably higher mIoU. In Fig. 1, we visualise the sample predictions of our models on the COCO-Stuff.

4.5 Segmenting rare concepts

By virtue of inheriting CLIP's diverse knowledge of nameable visual concepts, ReCo exhibits the ability to segment rare categories. We first demonstrate this ability for *fire extinguisher* objects, which have important fire-safety implications but seldom appear in popular semantic segmentation benchmarks. To assess performance, we evaluate segmentation quality on the FireNet dataset (as described in Sec. 4.1) and achieve reasonable performance on pixel accuracy (93.3) and IoU (44.9)

Model	Acc.	mIoU
Zero-shot transfer		
DenseCLIP [92]	32.2	19.6
ReCo (Ours)	**46.1**	**26.3**
Unsupervised adaptation		
IIC [33]	21.8	6.7
MDC [12]	32.2	9.8
PiCIE [12]	48.1	13.8
PiCIE + H [12]	50.0	14.4
STEGO [23]	**56.9**	28.2
ReCo+ (Ours)	54.1	**32.1**

Model	Acc.	mIoU
Zero-shot transfer		
DenseCLIP [92]	35.9	10.0
MDC† [12]	-	7.0
PiCIE† [12]	-	9.7
D&S† [82]	-	16.2
ReCo (Ours)	**74.5**	**19.3**
Unsupervised adaptation		
IIC [33]	47.9	6.4
MDC [12]	40.7	7.1
PiCIE [12]	65.5	12.3
STEGO [23]	73.2	21.0
ReCo+ (Ours)	**82.6**	**24.5**

Model	Acc.	mIoU
Zero-shot transfer		
DenseCLIP [92]	34.1	15.3
ReCo (Ours)	**70.6**	**29.8**
Unsupervised adaptation		
SegSort [32]	69.8	19.2
HSG [40]	73.8	21.7
ReCo+ (Ours)	**74.8**	**30.0**

Table 2: **Comparison to state-of-the art approaches on COCO-Stuff (left), Cityscapes (middle), and KITTI-STEP (right) validation sets.** †Models trained on Waymo Open [78] and evaluated at the original resolution (reported from [82]). The best score for each metric under each protocol is highlighted in **bold**. We observe that ReCo and ReCo+ perform strongly relative to prior work under zero-shot transfer and unsupervised adaptation protocols, respectively.

Figure 4: **Co-segmentations of rare concepts. Left:** *fire extinguisher*. **Right:** *Antikythera mechanism*. We show selected samples from ReCo archives for each concept, together with their co-segmentations. In each cases, ReCo successfully identifies the regions associated with the concept.

metrics. In Fig. 4 (left) we visualise the co-segmentation produced by ReCo across sample images container fire extinguishers. As an additional demonstration (Fig. 4, right), we also show co-segmentations for images containing the views of the (unique) *Antikythera mechanism*. In both cases, we observe that ReCo is capable of co-segmenting the concept of interest without labelled examples.

4.6 Limitations

Our work has several limitations: (1) There may be cases for which our first hypothesis does not hold—concepts so rare that they do not appear in billion-image scale datasets. In such cases, *e.g.* "a purple elephant with square orange feet wearing an inverted cowboy hat in front of the Doge's Palace", ReCo will struggle. (2) We make use of CLIP (a computationally heavy model) during inference. Future work could address this with pruning and hardware optimisation strategies. (3) We employ ImageNet as the unlabelled image collection for our primary investigations, which is known to exhibit an object-centric bias. While qualitative results suggest that ReCo can learn from extremely diverse data [72], a more comprehensive empirical evaluation would strengthen this result. (4) Models like CLIP are expensive to train and are consequently updated infrequently. If a new concept emerges (e.g. a new product) after CLIP was trained, ReCo will be unable to build an archive to enable co-segmentation for this concept. (5) Although our work is zero-shot in the sense that it is not trained on the target distribution, we still use of a subset of the target data distribution (primarily through ablations on PASCAL-Context) to guide the development of our method. As a result, our design likely contains choices that subtly favour performance on the evaluation tasks.

5 Conclusion

In this work, we introduced the ReCo framework for semantic segmentation zero-shot transfer. By drawing on the strengths of large-scale language-image pre-training and modern visual backbones, ReCo attains the ability to segment rare concepts and to directly assign names to concepts without labelled examples from the target distribution. In addition, experimental comparisons demonstrate that ReCo strongly outperforms existing zero-shot transfer approaches that forgo pixel supervision.

References

[1] Jiwoon Ahn and Suha Kwak. Learning pixel-level semantic affinity with image-level supervision for weakly supervised semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4981–4990, 2018.

[2] Sayan Banerjee, Avik Hati, Subhasis Chaudhuri, and Rajbabu Velmurugan. Cosegnet: Image co-segmentation using a conditional siamese convolutional network. In *IJCAI*, pages 673–679, 2019.

[3] Dhruv Batra, Adarsh Kowdle, Devi Parikh, Jiebo Luo, and Tsuhan Chen. icoseg: Interactive co-segmentation with intelligent scribble guidance. In *2010 IEEE computer society conference on computer vision and pattern recognition*, pages 3169–3176. IEEE, 2010.

[4] Amy Bearman, Olga Russakovsky, Vittorio Ferrari, and Li Fei-Fei. What's the point: Semantic segmentation with point supervision. In *ECCV*, 2016.

[5] Maxime Bucher, Tuan-Hung Vu, Mathieu Cord, and Patrick Pérez. Zero-shot semantic segmentation. In *NeurIPS*, 2019.

[6] Holger Caesar, Jasper Uijlings, and Vittorio Ferrari. Coco-stuff: Thing and stuff classes in context. In *CVPR*, 2018.

[7] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *ICCV*, 2021.

[8] Yu-Ting Chang, Qiaosong Wang, Wei-Chih Hung, Robinson Piramuthu, Yi-Hsuan Tsai, and Ming-Hsuan Yang. Weakly-supervised semantic segmentation via sub-category exploration. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8991–9000, 2020.

[9] Hong Chen, Yifei Huang, and Hideki Nakayama. Semantic aware attention based deep object co-segmentation. In *Asian Conference on Computer Vision*, pages 435–450. Springer, 2018.

[10] Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. In Vittorio Ferrari, Martial Hebert, Cristian Sminchisescu, and Yair Weiss, editors, *ECCV*, 2018.

[11] Bowen Cheng, Omkar Parkhi, and Alexander Kirillov. Pointly-supervised instance segmentation. *arXiv*, 2021.

[12] Jang Hyun Cho, Utkarsh Mall, Kavita Bala, and Bharath Hariharan. Picie: Unsupervised semantic segmentation using invariance and equivariance in clustering. In *CVPR*, 2021.

[13] Edo Collins, Radhakrishna Achanta, and Sabine Susstrunk. Deep feature factorization for concept discovery. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 336–352, 2018.

[14] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. In *CVPR*, 2016.

[15] Jifeng Dai, Kaiming He, and Jian Sun. Boxsup: Exploiting bounding boxes to supervise convolutional networks for semantic segmentation. In *Proc. ICCV*, 2015.

[16] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

[17] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[18] Ruochen Fan, Qibin Hou, Ming-Ming Cheng, Gang Yu, Ralph R. Martin, and Shi-Min Hu. Associating inter-image salient instances for weakly supervised semantic segmentation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

[19] Robert Fergus, Li Fei-Fei, Pietro Perona, and Andrew Zisserman. Learning object categories from google's image search. In *Tenth IEEE International Conference on Computer Vision (ICCV'05) Volume 1*, volume 2, pages 1816–1823. IEEE, 2005.

[20] Golnaz Ghiasi, Xiuye Gu, Yin Cui, and Tsung-Yi Lin. Open-vocabulary image segmentation. *arXiv preprint arXiv:2112.12143*, 2021.

[21] Priya Goyal, Quentin Duval, Isaac Seessel, Mathilde Caron, Mannat Singh, Ishan Misra, Levent Sagun, Armand Joulin, and Piotr Bojanowski. Vision models are more robust and fair when pretrained on uncurated images without supervision. *arXiv preprint arXiv:2202.08360*, 2022.

[22] Zhangxuan Gu, Siyuan Zhou, Li Niu, Zihan Zhao, and Liqing Zhang. Context-aware feature generation for zero-shot semantic segmentation. In *ACM MM*, 2020.

[23] Mark Hamilton, Zhoutong Zhang, Bharath Hariharan, Noah Snavely, and William T. Freeman. Unsupervised semantic segmentation by distilling feature correspondences. In *ICLR*, 2022.

[24] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020.

[25] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[26] Yin-Yin He, Peizhen Zhang, Xiu-Shen Wei, Xiangyu Zhang, and Jian Sun. Relieving long-tailed instance segmentation via pairwise class balance. *arXiv preprint arXiv:2201.02784*, 2022.

[27] Kuang-Jui Hsu, Yen-Yu Lin, Yung-Yu Chuang, et al. Co-attention cnns for unsupervised object co-segmentation. In *IJCAI*, volume 1, page 2, 2018.

[28] Ping Hu, Stan Sclaroff, and Kate Saenko. Uncertainty-aware learning for zero-shot semantic segmentation. *Advances in Neural Information Processing Systems*, 33:21713–21724, 2020.

[29] Ronghang Hu, Piotr Dollár, Kaiming He, Trevor Darrell, and Ross Girshick. Learning to segment every thing. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4233–4241, 2018.

[30] Xinting Hu, Yi Jiang, Kaihua Tang, Jingyuan Chen, Chunyan Miao, and Hanwang Zhang. Learning to segment the tail. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14045–14054, 2020.

[31] Dat Huynh, Jason Kuen, Zhe Lin, Jiuxiang Gu, and Ehsan Elhamifar. Open-vocabulary instance segmentation via robust cross-modal pseudo-labeling. *arXiv preprint arXiv:2111.12698*, 2021.

[32] Jyh-Jing Hwang, Stella X Yu, Jianbo Shi, Maxwell D Collins, Tien-Ju Yang, Xiao Zhang, and Liang-Chieh Chen. Segsort: Segmentation by discriminative sorting of segments. In *ICCV*, 2019.

[33] Xu Ji, João F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In *ICCV*, 2019.

[34] Chao Jia, Yinfei Yang, Ye Xia, Yi-Ting Chen, Zarana Parekh, Hieu Pham, Quoc Le, Yun-Hsuan Sung, Zhen Li, and Tom Duerig. Scaling up visual and vision-language representation learning with noisy text supervision. In *International Conference on Machine Learning*, pages 4904–4916. PMLR, 2021.

[35] Bin Jin, Maria V Ortiz Segovia, and Sabine Susstrunk. Webly supervised semantic segmentation. In *Proc. CVPR*, 2017.

[36] Jeff Johnson, Matthijs Douze, and Hervé Jégou. Billion-scale similarity search with gpus. *IEEE Transactions on Big Data*, 7(3):535–547, 2019.

[37] Armand Joulin, Francis Bach, and Jean Ponce. Discriminative clustering for image co-segmentation. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pages 1943–1950. IEEE, 2010.

[38] Aishwarya Kamath, Mannat Singh, Yann LeCun, Gabriel Synnaeve, Ishan Misra, and Nicolas Carion. Mdetr-modulated detection for end-to-end multi-modal understanding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1780–1790, 2021.

[39] Naoki Kato, Toshihiko Yamasaki, and Kiyoharu Aizawa. Zero-shot semantic segmentation via variational mapping. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops*, pages 0–0, 2019.

[40] Tsung-Wei Ke, Jyh-Jing Hwang, Yunhui Guo, Xudong Wang, and Stella X. Yu. Unsupervised hierarchical semantic segmentation with multiview cosegmentation and clustering transformers. In *CVPR*, 2022.

[41] Anna Khoreva, Rodrigo Benenson, Jan Hosang, Matthias Hein, and Bernt Schiele. Simple does it: Weakly supervised instance and semantic segmentation. In *Proc. CVPR*, 2017.

[42] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

[43] Philipp Krähenbühl and Vladlen Koltun. Efficient inference in fully connected crfs with gaussian edge potentials. In *NeurIPS*, 2011.

[44] Harold W. Kuhn. The Hungarian Method for the Assignment Problem. *Naval Research Logistics Quarterly*, 1955.

[45] Boyi Li, Kilian Q Weinberger, Serge Belongie, Vladlen Koltun, and Rene Ranftl. Language-driven semantic segmentation. In *ICLR*, 2022.

[46] Peike Li, Yunchao Wei, and Yi Yang. Consistent structural relation learning for zero-shot segmentation. *Advances in Neural Information Processing Systems*, 33:10317–10327, 2020.

[47] Weihao Li, Omid Hosseini Jafari, and Carsten Rother. Deep object co-segmentation. In C. V. Jawahar, Hongdong Li, Greg Mori, and Konrad Schindler, editors, *ACCV*, 2019.

[48] Di Lin, Jifeng Dai, Jiaya Jia, Kaiming He, and Jian Sun. Scribblesup: Scribble-supervised convolutional networks for semantic segmentation. In *Proc. CVPR*, 2016.

[49] Wei Liu, Andrew Rabinovich, and Alexander C. Berg. ParseNet: Looking Wider to See Better. *arXiv:1506.04579*, 2015.

[50] Weide Liu, Chi Zhang, Guosheng Lin, and Fayao Liu. Crnet: Cross-reference networks for few-shot segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4165–4173, 2020.

[51] Dhruv Mahajan, Ross Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens Van Der Maaten. Exploring the limits of weakly supervised pretraining. In *Proceedings of the European conference on computer vision (ECCV)*, pages 181–196, 2018.

[52] Kevis-Kokitsi Maninis, Sergi Caelles, Jordi Pont-Tuset, and Luc Van Gool. Deep extreme cut: From extreme points to object segmentation. In *Proc. CVPR*, 2018.

[53] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.

[54] George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11):39–41, 1995.

[55] Roozbeh Mottaghi, Xianjie Chen, Xiaobai Liu, Nam-Gyu Cho, Seong-Whan Lee, Sanja Fidler, Raquel Urtasun, and Alan Yuille. The role of context for object detection and semantic segmentation in the wild. In *CVPR*, 2014.

[56] Lopamudra Mukherjee, Vikas Singh, and Charles R Dyer. Half-integrality based algorithms for cosegmentation of images. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 2028–2035. IEEE, 2009.

[57] Muzammal Naseer, Kanchana Ranasinghe, Salman Khan, Munawar Hayat, Fahad Khan, and Ming-Hsuan Yang. Intriguing properties of vision transformers. In *NeurIPS*, 2021.

[58] Yassine Ouali, Céline Hudelot, and Myriam Tami. Autoregressive unsupervised image segmentation. In *ECCV*, 2020.

[59] Fabio Panella, Victor Melatti, and Jan Boehm. Firenet dataset. `http://www.firenet.xyz`. Accessed: 2022-05-17.

[60] Dim P Papadopoulos, Alasdair DF Clarke, Frank Keller, and Vittorio Ferrari. Training object class detectors from eye tracking data. In *ECCV*, 2014.

[61] Dim P Papadopoulos, Jasper RR Uijlings, Frank Keller, and Vittorio Ferrari. Extreme clicking for efficient object annotation. In *Proc. ICCV*, 2017.

[62] Giuseppe Pastore, Fabio Cermelli, Yongqin Xian, Massimiliano Mancini, Zeynep Akata, and Barbara Caputo. A closer look at self-training for zero-label semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2693–2702, 2021.

[63] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, 2019.

[64] Deepak Pathak, Philipp Krahenbuhl, and Trevor Darrell. Constrained convolutional neural networks for weakly supervised segmentation. In *Proceedings of the IEEE international conference on computer vision*, pages 1796–1804, 2015.

[65] Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

[66] Pedro O Pinheiro and Ronan Collobert. From image-level to pixel-level labeling with convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1713–1721, 2015.

[67] Rui Qian, Yunchao Wei, Honghui Shi, Jiachen Li, Jiaying Liu, and Thomas Huang. Weakly supervised scene parsing with point-based distance metric learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2019.

[68] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

[69] Yongming Rao, Wenliang Zhao, Guangyi Chen, Yansong Tang, Zheng Zhu, Guan Huang, Jie Zhou, and Jiwen Lu. Denseclip: Language-guided dense prediction with context-aware prompting. *arXiv preprint arXiv:2112.01518*, 2021.

[70] Carsten Rother, Tom Minka, Andrew Blake, and Vladimir Kolmogorov. Cosegmentation of image pairs by histogram matching-incorporating a global constraint into mrfs. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, volume 1, pages 993–1000. IEEE, 2006.

[71] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

[72] Christoph Schuhmann, Richard Vencu, Romain Beaumont, Theo Coombes, Cade Gordon, Aarush Katta, Robert Kaczmarczyk, and Jenia Jitsev. LAION-5B: laion-5b: A new era of open large-scale multi-modal datasets. `https://laion.ai/laion-5b-a-new-era-of-open-large-scale-multi-modal-datasets/`, 2022.

[73] Tong Shen, Guosheng Lin, Chunhua Shen, and Ian Reid. Bootstrapping the performance of webly supervised semantic segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1363–1371, 2018.

[74] Gyungin Shin, Samuel Albanie, and Weidi Xie. Unsupervised salient object detection with spectral cluster voting. *arXiv preprint arXiv:2203.12614*, 2022.

[75] Gyungin Shin, Weidi Xie, and Samuel Albanie. All you need are a few pixels: semantic segmentation with pixelpick. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1687–1697, 2021.

[76] Oriane Siméoni, Gilles Puy, Huy V Vo, Simon Roburin, Spyros Gidaris, Andrei Bursuc, Patrick Pérez, Renaud Marlet, and Jean Ponce. Localizing objects with self-supervised transformers and no labels. *arXiv preprint arXiv:2109.14279*, 2021.

[77] Chunfeng Song, Yan Huang, Wanli Ouyang, and Liang Wang. Box-driven class-wise region masking and filling rate guided loss for weakly supervised semantic segmentation. In *Proc. CVPR*, 2019.

[78] Pei Sun, Henrik Kretzschmar, Xerxes Dotiwalla, Aurelien Chouard, Vijaysai Patnaik, Paul Tsui, James Guo, Yin Zhou, Yuning Chai, Benjamin Caine, Vijay Vasudevan, Wei Han, Jiquan Ngiam, Hang Zhao, Aleksei Timofeev, Scott Ettinger, Maxim Krivokon, Amy Gao, Aditya Joshi, Yu Zhang, Jonathon Shlens, Zhifeng Chen, and Dragomir Anguelov. Scalability in perception for autonomous driving: Waymo open dataset. In *CVPR*, 2020.

[79] Wouter Van Gansbeke, Simon Vandenhende, Stamatios Georgoulis, and Luc Van Gool. Unsupervised semantic segmentation by contrasting object mask proposals. In *ICCV*, 2021.

[80] Sara Vicente, Vladimir Kolmogorov, and Carsten Rother. Cosegmentation revisited: Models and optimization. In *European Conference on Computer Vision*, pages 465–479. Springer, 2010.

[81] Sara Vicente, Carsten Rother, and Vladimir Kolmogorov. Object cosegmentation. In *CVPR*, 2011.

[82] Antonin Vobecky, David Hurych, Oriane Siméoni, Spyros Gidaris, Andrei Bursuc, Patrick Pérez, and Josef Sivic. Drive&segment: Unsupervised semantic segmentation of urban scenes via cross-modal distillation. *arXiv:2203.11160*, 2022.

[83] Yangtao Wang, Xi Shen, Shell Hu, Yuan Yuan, James Crowley, and Dominique Vaufreydaz. Self-supervised transformers for unsupervised object discovery using normalized cut. *arXiv preprint arXiv:2202.11539*, 2022.

[84] Mark Weber, Jun Xie, Maxwell Collins, Yukun Zhu, Paul Voigtlaender, Hartwig Adam, Bradley Green, Andreas Geiger, Bastian Leibe, Daniel Cremers, Aljosa Osep, Laura Leal-Taixe, and Liang-Chieh Chen. Step: Segmenting and tracking every pixel. In *NeurIPS Track on Datasets and Benchmarks*, 2021.

[85] Yunchao Wei, Huaxin Xiao, Honghui Shi, Zequn Jie, Jiashi Feng, and Thomas S. Huang. Revisiting dilated convolution: A simple approach for weakly- and semi-supervised semantic segmentation. In *Proc. CVPR*, 2018.

[86] Yongqin Xian, Subhabrata Choudhury, Yang He, Bernt Schiele, and Zeynep Akata. Semantic projection network for zero-and few-label semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8256–8265, 2019.

[87] Jiarui Xu, Shalini De Mello, Sifei Liu, Wonmin Byeon, Thomas Breuel, Jan Kautz, and Xiaolong Wang. Groupvit: Semantic segmentation emerges from text supervision. *arXiv preprint arXiv:2202.11094*, 2022.

[88] Chi Zhang, Guankai Li, Guosheng Lin, Qingyao Wu, and Rui Yao. Cyclesegnet: Object co-segmentation with cycle refinement and region correspondence. *IEEE TIP*, 2021.

[89] Xiao Zhang and Michael Maire. Self-supervised visual representation learning from hierarchical grouping. *Advances in Neural Information Processing Systems*, 33:16579–16590, 2020.

[90] Hang Zhao, Xavier Puig, Bolei Zhou, Sanja Fidler, and Antonio Torralba. Open vocabulary scene parsing. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2002–2010, 2017.

[91] Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proc. CVPR*, 2016.

[92] Chong Zhou, Chen Change Loy, and Bo Dai. Denseclip: Extract free dense labels from clip. *arXiv:2112.01071*, 2021.