VARIATIONAL DETERMINISTIC UNCERTAINTY QUANTIFICATION

ABSTRACT

Building on recent advances in uncertainty quantification using a single deep deterministic model (DUQ), we introduce variational Deterministic Uncertainty Quantification (vDUQ). We overcome several shortcomings of DUQ by recasting it as a Gaussian process (GP) approximation. Our principled approximation is based on an inducing point GP in combination with Deep Kernel Learning. This enables vDUQ to use rigorous probabilistic foundations, and work not only on classification but also on regression problems. We avoid uncertainty collapse away from the training data by regularizing the spectral norm of the deep feature extractor. Our method matches SotA accuracy, 96.2% on CIFAR-10, while maintaining the speed of softmax models, and provides uncertainty estimates competitive with Deep Ensembles. We demonstrate our method in regression problems and by estimating uncertainty in causal inference for personalized medicine.

1 INTRODUCTION

Deploying machine learning algorithms as part of automated decision making systems, such as self driving cars and medical diagnostics, requires implementing fail-safes. Whenever the model is presented with a novel or ambiguous situation, it would not be wise to simply trust its prediction. Instead, the system should try to get more information or simply withhold or defer judgment. While significant progress has been made towards estimating predictive uncertainty reliably in deep learning (Gal & Ghahramani, 2016; Lakshminarayanan et al., 2017), there is no single method that works on large datasets in classification and regression without significant computation overheads, such as multiple forward passes. We propose Variational Deterministic Uncertainty Quantification (vDUQ), a method for obtaining predictive uncertainty in deep learning for both classification and regression problems in only a single forward pass.

In previous work, van Amersfoort et al. (2020) show that combining a distance aware decision function with a regularized feature extractor, leads to a model (DUQ) that matches a softmax model in accuracy, but is competitive with Deep Ensembles for uncertainty on large datasets. The feature extractor is regularized using a two-sided gradient penalty, which encourages the model to be sensitive to changes in the input, avoiding feature collapse, and encouraging generalization by controlling the Lipschitz constant. This model, however, has several limitations; for example the uncertainty (a distance in feature space) cannot be interpreted probabilistically and it is difficult to disentangle aleatoric and epistemic uncertainty. Additionally, the loss function and centroid update scheme are not principled and do not extend to regression tasks.

A probabilistic and principled alternative to Deep RBF networks are Gaussian Processes (GPs) in combination with Deep Kernel Learning (DKL) (Wilson et al., 2016b;a; Hinton & Salakhutdinov, 2008). DKL was introduced as a "best of both worlds" solution: apply a deep model on the training data and learn the GP in feature space, ideally getting the advantages of both models. In practice, however, DKL suffers from the same failure as Deep RBF networks: the deep model is free to map out of distribution data close to the feature representation of the training data, removing the attractive properties of GPs with distance sensitive kernels.

Using insights from DUQ, we are able to mitigate the problems of uncertainty collapse in DKL. In particular, we use direct spectral normalization (Gouk et al., 2018; Miyato et al., 2018) in combination with a ResNet (He et al., 2016), a variation that was suggested in Liu et al. (2020). This

(a) Deep Ensembles (b) vDUQ

Figure 1: We show results on a 1D regression dataset of a sinusoid curve. In green are data points of the dataset and in blue the prediction including uncertainty (two standard deviations). As expected, vDUQ reverts to the prior away from the training data, while Deep Ensembles extrapolates arbitrarily and confidently. The uncertainty is the posterior variance in the case of vDUQ, and the variance across the ensemble element predictions in Deep Ensembles.

enforces an upper bound on the Lipschitz constant, while the residual connections enforce a lower bound, obtaining a similar result as the gradient penalty of DUQ by construction. We use an inducing point variational approximation of the GP predictive distribution (Hensman et al., 2015) to speed up inference in the GP model and decouple it from the dataset size. We release our code[1] and hope that it will become a drop in alternative for softmax models with improved uncertainty.

In Figure 1, we show how vDUQ and Deep Ensembles (Lakshminarayanan et al., 2017) perform on simple 1D regression. vDUQ shows the desired behavior of reverting back to the prior away from the data, while the Deep Ensemble extrapolates arbitrarily and confidently. In between the two sinusoids, the Deep Ensemble is certain while vDUQ increases its uncertainty. This task is particularly hard for deep networks as shown in Foong et al. (2019).

In summary, our contributions are as follows:

- We stabilize training deep networks using DKL and for the first time match the accuracy of training a deep network using regular softmax output.
- We discuss the theoretical motivations of spectral normalization for uncertainty, and its relationship to prior work.
- We demonstrate uncertainty estimation which obtains excellent results on toy data, matches or exceeds the state of the art on CIFAR-10, including ensembling approaches, and state of the art performance on a causal inference benchmark requiring uncertainty.

2 BACKGROUND

Gaussian Processes (GPs) provide an interpretable, explainable and principled way to make predictions, and can work well even with little training data due to their use of Bayesian inference. In contrast with neural networks, GPs have high uncertainty away from the training data and on noisy inputs. There are two main issues with the standard GP setup: performance on high dimensional inputs and computational scaling with larger datasets. The poor performance on high dimensional inputs is due to the fact that most standard shift-invariant kernels are based on the Euclidean distance, which is a poor metric for highly structured data like images (Theis et al., 2016). While kernels exist that better address this (Van der Wilk et al., 2017; Jacot et al., 2018), these are more computationally expensive and typically still under perform standard convolutional neural networks.

Deep Kernel Learning (Calandra et al., 2016; Hinton & Salakhutdinov, 2008; Wilson et al., 2016b) is a way to combine the expressiveness of deep neural networks with the attractive properties of Gaussian Processes. The core idea is to use a deep neural network inside the kernel of a GP,

---

[1]Available at: `anonymized-for-review`

(a) Input   (b) Features - no constraint   (c) Features - with constraint

Figure 2: A visualization of feature geometry, showing the importance of constraining the feature mapping. The feature representations learned on a 2D classification task where the classes are two Gaussian blobs (drawn in green), and a large set of random input points (colored according to their log-probability under the data generating distribution). In the center we see the features as computed by an unconstrained model, and on the right by a model with residual connections and spectral normalization. As we can see, the objective for the unconstrained model introduces a large amount of distortion of the space, largely collapsing the input to a single line, making it almost impossible to use distance-sensitive measures on these features. In contrast, a constrained mapping still makes the classes more separable, while maintaining the relative distances of the other points.

$k(\boldsymbol{x}_i, \boldsymbol{x}_j) \rightarrow k(f_\theta(\boldsymbol{x}_i), f_\theta(\boldsymbol{x}_j))$, where $f_\theta(\cdot)$ is a deep neural network, such as a Wide ResNet (Zagoruyko & Komodakis, 2016) up to the last linear layer, parametrized by θ. The kernel $k(\cdot, \cdot)$ can be any of the standard kernels, such as the RBF kernel. With the deep network it becomes possible to train the GP on datasets that contain high dimensional points, such as images. The main shortcoming of DKL is that much of the work is done by the parametric kernel, rather than the component of the model which is Bayesian. As this parametric model is unconstrained, uncertainty away from the data collapses (Bradshaw et al., 2017), and the model can be arbitrarily confident while no data has been observed in the region during training. See Section 3 for a detailed discussion of this effect and ways to mitigate it.

While DKL is a potentially powerful solution to overcome the problem of inexpressive kernels, it does not address the other scaling problem of Gaussian Processes: large datasets. The poor computational scaling comes from the fact that making predictions with an exact GP requires solving a linear system the size of the training data, namely computing $K(X, X)^{-1}K(X, x*)$ where $K(X, X)$ is the kernel matrix evaluated on the training dataset and $K(X, x*)$ the kernel between the training dataset and a test point. This is a significant computational problem in its own right (Wang et al., 2019; Wilson et al., 2016a). A powerful and principled alternative to exact GP inference is inducing point GP approximate inference, where only a small set of inducing points in the input space U are used to represent the entire training set, reducing the linear system to be solved to $K(u, u)^{-1}K(u, x*)$. The new linear system is m by m, where m is the number of inducing points, rather than N by N. Finding the optimal set of points, which are not necessarily part of our training set, can be done by treating them as variational parameters and maximizing a lower bound on the marginal log-likelihood (Titsias, 2009). We follow the variational inducing point formulation of SVGPC (Hensman et al., 2015) as implemented in GPyTorch (Gardner et al., 2018).

3 METHOD

vDUQ combines Deep Kernel Learning with an inducing point GP, learned using variational inference. In this section we will analyse why the uncertainty of DKL can collapse and how to avoid this. We will further explain the steps necessary such that we can train a deep model from end-to-end and avoid the pre-training of previous work (Bradshaw et al., 2017).

The crucial step we make to obtain reliable uncertainty with deep kernels is the introduction of spectral regularization on the deep model. Without it, the deep network, $f_\theta(\cdot)$, is free to map data points that are far away from the training distribution to a feature representation that's similar to in distribution data. This behavior is also exhibited in standard neural networks (Smith & Gal, 2018)

and sometimes referred to as *feature collapse*. We visualize this in Figure 2, where we map a 2D input space into feature space. With the feature space of the unconstrained model it is impossible to recover uncertainty: many points are collapsed on top of each other.

A GP with a stationary kernel reverts back to the prior away from the data (or in our case, the inducing points); in DKL we do not have this guarantee, since the "neural" component of the kernel is free to collapse the distance between any two inputs to an arbitrarily small value. Recent work has shown that it is possible to reduce *feature collapse* by regularizing the deep model using a bi-Lipschitz constraint (van Amersfoort et al., 2020), i.e to try to make the model satisfy

$$\frac{1}{K} d_X(x_1, x_2) \leq d_Y \left(f_\theta(x_1), f_\theta(x_2) \right) \leq K d_X(x_1, x_2) \tag{1}$$

The lower Lipschitz constraint is responsible for making the model sensitive to changes in the input: this means the model cannot simply collapse feature representations arbitrarily, but is constrained by the mechanisms in the model, such as strided convolutions. The upper Lipschitz constraint ensures the model is smooth and small changes in the input cannot cause massive shifts in the output. This appears to help optimization, and ensures the feature space accords with the implicit assumptions that for example RBF kernels make about the data. We discuss this theory behind this constraint in more depth in Section 3.1.

There is a number of methods proposed in the literature that attempt to satisfy the bi-Lipschitz constraint and each comes with different trade-offs:

- **Two-sided Gradient Penalty:** van Amersfoort et al. (2020) achieve the regularization using a two-sided gradient penalty, using a soft regularizer that penalizes the squared distance of the gradient from a fixed value at every input point. This approach is easy to implement, but is not guaranteed to work, and in practice both the stability of training and its effectiveness as a regularizer can be fairly sensitive to the weighting of this penalty.

- **Direct Spectral Normalization in combination with ResNets:** Spectral Normalization (Miyato et al., 2018; Gouk et al., 2018) directly regularizes the upper Lipschitz constraint and it is possible to combine this with an architecture that contains residual connections for the lower constraint, as suggested in Liu et al. (2020), as long as batch normalization (Ioffe & Szegedy, 2015) is also appropriately constrained. This method is faster than the gradient penalty, and in practice a more effective way of mitigating feature collapse.

- **Reversible Model:** A reversible model is constructed by using reversible layers and avoiding any down scaling operations (Jacobsen et al., 2018; Behrmann et al., 2019). This approach can guarantee that the overall function is bi-Lipschitz, but the resulting model consumes considerably more memory and can be difficult to train.

In this work, we use direct spectral normalization, as we find it to be more stable than a direct gradient penalty, and we find it difficult to get good performance using fully reversible models, as these preclude the use of layers that reduce dimensionality, like strided convolutions, which we find crucial for good performance.

The regularized feature extractor allows us to offload computational complexity from the GP onto the deep model without sacrificing uncertainty. An expressive deep model is able to find a feature representation which generalizes across all intra class variation, and thus cluster inputs of the same class in feature space. We choose to define the inducing points in feature space (Lázaro-Gredilla & Figueiras-Vidal, 2009; Hensman et al., 2017), which takes advantage of this clustering to reduce the number of inducing points required. In practice, we find that only very few inducing points, the number of classes in the case of classification, are necessary to obtain a well performing GP and we found similarly low numbers (in the 10 to 100 range) necessary for regression, which means that solving the linear system is fast and the GP has minimal overhead compared to a Softmax output. The fact that we can use few inducing points is not true in general for DKL, but requires the extra restrictions we have placed on our feature extractor to avoid the pathological feature collapse. It is important to note that in DKL and also in this paper we are not being Bayesian about our neural network parameters θ, so we only need a single pass through the feature extractor both when training and during inference.

In addition, we note that batch normalization, a very important component of training deep ResNets, has a non-trivial Lipschitz constant. This is not an issue with gradient penalties, but for methods

which use spectral normalization, this is important to take into account. In particular, since batch normalization, with scale and shift parameters γ and β, transforms the input according to:

$$x_{out} = \mathrm{diag}\left(\frac{\gamma}{\sqrt{\mathrm{Var}(x)}}\right)(x - \mathbb{E}(x)) + \beta. \tag{2}$$

It has a Lipschitz constant of $\max_i |\frac{\gamma_i}{\sqrt{\mathrm{Var}(x)}_i}|$ (Gouk et al., 2018). Using the above equation, it is straightforward to define a version of batch normalization which has a maximum Lipschitz of one by dividing the weight γ of the batch normalization by the (scaled) Lipschitz constant. In practice, we find empirically that typical batch normalization layers in trained ResNets have a relatively high Lipschitz constant, up to around 12, with 95% having a Lipschitz greater than one, see also Figure 5 in the Appendix. This is counter to the claim of Liu et al. (2020) that batch normalization *reduces* the Lipschitz value of the network. Unless otherwise noted, in this paper we use the spectral normalized version of batch normalization.

3.1 SPECTRAL NORMALIZATION AND BI-LIPSCHITZ

It is worth thinking about what the condition in Equation 1 means. As pointed out in Liu et al. (2020), there is an established connection between bi-Lipschitz mappings and metric spaces - if we have two metric spaces X and Y, with a continuous function $f : X \mapsto Y$ between them which is bijective, and f is bi-Lipschitz, then metric properties of X like boundedness and completeness have to be preserved by Y, and distances in X can be changed only by a bounded factor in Y. In this sense, a bi-Lipschitz map between X and Y can be considered to be "approximately" distance preserving, which is useful for measuring uncertainty in feature space. A function f which is parameterized as a residual network and regularized appropriately can be constructed to be bi-Lipschitz if it is a residual block between two spaces of the same dimensionality (Liu et al., 2020; Behrmann et al., 2019). However, it is straightforward to demonstrate the following observation (which we do not claim to be novel)

Proposition 1. *Let f be a function from $\mathbb{R}^n$ to $\mathbb{R}^m$, with $m < n$. Then f is not bi-Lipschitz.*

We provide a proof in Appendix B; it suffices to show that a bi-Lipschitz function is necessarily a homeomorphism, and so cannot exist between spaces of different dimensionality. Since layers which reduce the dimensionality, like pooling layers and strided convolutions, are common and often necessary for good performance on image data, this calls into question how informative the metric space perspective is on explaining the usefulness of bi-Lipschitz regularization for the model as a whole. Explanations of the effectiveness of these regularizers based on the assumption that the bi-Lipschitz condition *holds* are insufficient if the network uses dimensionality reduction, which the feature extraction architectures used in both Liu et al. (2020) and van Amersfoort et al. (2020) do.

These arguments would hold for invertible models. Some progress towards a well performing bijective deep model was made in Behrmann et al. (2019), however the iResNet is significantly slower and computationally expensive than the WRN, and we were unable to achieve the performance we report here without using dimension-reducing layers.

It is also important to note that the *proof* of bi-Lipschitz-ness in Liu et al. (2020) (and corresponding proof of invertibility in Behrmann et al. (2019) only holds if the spectral norm of the residual connection is constrained to be less than one. In practice, both in our work and that of Liu et al. (2020), we find that Lipschitz constraints looser than this work better in practice, raising further questions of how much this theory is explaining the observed usefulness of this regularization scheme.

A complete, rigorous theory of why the spectral normalization as used in this and previous work is a useful regularization scheme is not remains an open question. However, in practice we find that controlling the feature space distortion "enough" has a significant effect in enabling the GP to maintain its prior reversion effect.

4 RELATED WORK

Currently, the simplest and most effective way to obtain uncertainty in deep learning classification is using ensembling (Lakshminarayanan et al., 2017). Despite its simplicity it has shown to be

| (a) ResNet + Softmax | (b) FFN + DKL | (c) vDUQ |

Figure 3: We show uncertainty results on the two moons classification dataset. Yellow indicates high confidence, while blue indicates uncertainty. In Figure 3a, a simple feed forward resnet with a softmax output is certain everywhere except on the decision boundary. In Figure 3b, we see that a simple feed forward model in combination with DKL has large areas of certainty, even away from the training data. In Figure 3c, we show vDUQ with a residual network as feature extractor in combination with spectral normalization, showing close to ideal uncertainty on this dataset.

remarkably effective (Ovadia et al., 2019), outperforming alternatives such as MC Dropout (Gal & Ghahramani, 2016) and mean-field variational inference Bayesian Neural Networks(Farquhar et al., 2019) at the expense of having to train and evaluate multiple models. An important issue with Deep Ensembles is enforcing diversity; while on large and complicated datasets it is sufficient to use a different initialization and data order, this is not sufficient on easier or smaller datasets, as we highlight in Figure 1.

DUQ (van Amersfoort et al., 2020) demonstrated empirically that it is possible to quantify uncertainty in deep learning using only a single deterministic model. SNGP (Liu et al., 2020) takes the concept of DUQ, a distance aware prediction function and a bi-Lipschitz constraint, and achieves them by using a deep neural network with a random fourier features (RFF) approximate GP and spectral normalization on the convolutional weights. They do not account for batch normalization in their normalization scheme. While they obtain impressive results, it is important to note that the RFF approximation makes the GP parametric, meaning there are now a fixed number of basis functions used in the prediction which can lead to unreliable uncertainty. Using variational Bayes in the form of SVGPC conserves the non-parametric property and uses infinitely many basis functions; it is an approximation to the true GP posterior, whereas a random Fourier expansion is a *different* model which converges in expectation to the true model as the number of random fourier features tends to infinity. vDUQ only needs a handful of inducing points and increasing this number is guaranteed to improve the model monotonically as the pseudo inputs are part of the approximation and not parameters of the model. Finally, although in principle the method of Liu et al. (2020) could be adapted to regression in a straightforward way, they do not investigate this, while our experiments demonstrate the applicability of this kind of model both on standard classification benchmarks and uncertainty sensitive regression tasks, such as Causal Inference.

5 EXPERIMENTS

5.1 REGRESSION AND IN-BETWEEN UNCERTAINTY

In Figure 1, we show results on a 1D dataset created from sinusoids. For vDUQ, we use spectral normalization, a Matérn kernel with $\nu = \frac{1}{2}$ and 20 inducing points. This kernel is known to lead to less smooth learned functions, which leads to quickly increasing the uncertainty when there is no data. Full experimental details are provided in Appendix A

Deep Ensemble extrapolates incorrectly as x becomes more negative, at $x = -15$ the prediction is far away from what is seen in the training data, however the model still has low uncertainty. Meanwhile vDUQ reverts to the prior directly at the edge of the training data domain, which is the ideal behavior in this regression setting. In Deep Ensembles (Lakshminarayanan et al., 2017), it was suggested to let the model predict both the mean and the standard deviation. This standard deviation only measures the *aleatoric* uncertainty (see also Chua et al. (2018) for a discussion), which is the uncertainty arising from noise inherent in the data. In this dataset there is only minimal noise, and therefore the only way to assess the uncertainty is to compute the variance of the mean predictions.

Table 1: Results on CIFAR-10 and distinguishing the test set of CIFAR-10 and SVHN by uncertainty (AUROC). All results are the average and standard deviation of 5 runs.

Method	Accuracy (%)	AUROC
WRN	96.2±0.03	0.932±0.018
Ensemble of 5 WRN	96.6±0.06	0.967±0.011
SNGP [2]	96.0±0.09	0.940±0.013
DUQ	94.6±0.16	0.940±0.007
vDUQ	95.6±0.09	0.958±0.012
vDUQ (no Spectral Normalization)	96.2±0.11	0.937±0.014
vDUQ (only Spectral Normalization on convolutions)	96.1±0.13	0.930±0.003

In contrast, vDUQ's posterior variance is directly interpretable as the predictive uncertainty (also known as the total uncertainty). In the Appendix, Figure 4, we visualize sampling from the posterior, which highlights the non-smoothness of the kernel choice.

5.2 CLASSIFICATION ON TWO MOONS

We show results on Two Moons dataset (Pedregosa et al., 2011) for three different models: a standard softmax model, vDUQ and a variation where the spectral normalized ResNet is replaced by a fully connected model, similar to Bradshaw et al. (2017). For experimental details see Appendix A.

On this simple dataset, a multi layer neural network easily achieves 100% accuracy with a single, non-linear, decision boundary going between the two moons. However these models exhibit complete certainty everywhere in the input domain as shown in Figure 3a, with yellow the certain regions, and blue uncertain. The uncertainty is computed using the entropy of the class prediction: we model the problem as a two class classification problem. vDUQ (in Figure 3c) on the other hand quantifies uncertainty exactly as one would expect for the two moons dataset: certain on the training data, uncertain away from it and in between the two half moons. Figure 3b highlights the importance of our contribution. When using DKL with a deep network without the right constraints, the model generalizes beyond the training distribution and is certain even away from the training data.

5.3 CIFAR-10 AND SVHN

In this section we look at training a large model, the Wide Residual Network, on CIFAR-10 (Krizhevsky et al., 2009). In vDUQ, we train the large ResNet end-to-end with the GP, this is in contrast with prior work that used a pre-trained model (Bradshaw et al., 2017), which is a significant limitation. We follow the experimental setup of Zagoruyko & Komodakis (2016), and use a 28 layer model with BasicBlocks and dropout. Interestingly, we can follow hyper parameter suggestions (such as dropout rate, learning rate, and optimizer) directly when training vDUQ, and no special care is necessary for the variational parameters. We remove the final linear layer of the model and the resulting 640 dimensional feature vector is directly used in the GP. We train using only *10 inducing points*, which are shared among the independent output GPs (although $q(u)$ is different) and use Lipschitz factor 3. This means the model is fast, and going through one epoch is just 3% slower than using a softmax output. Further experimental details are discussed in Appendix A.

Results are shown in Table 1. Interestingly, using a softmax model it is possible to get good results on this benchmark. vDUQ without any spectral normalization matches the accuracy of the WRN, but the uncertainty is only slightly better than a softmax model. With spectral normalization the accuracy drops slightly, as expected, but the uncertainty improves significantly. Using spectral normalization only on the convolutions does not reduce the accuracy, but also does not improve the uncertainty.

5.4 CAUSAL INFERENCE

In this section, we consider the safety critical task of inferring the individual-level causal effects of a binary treatment t for an individual described by covariates x via the conditional average treatment

---

[2]Obtained using the author's open source implementation, which is available at `https://github.com/google/uncertainty-baselines`

Table 2: Comparing the performance of several causal effect inference methods. Best results in bold and note that DKLITE* results are obtained using their open source implementation (see A.3).

$\sqrt{\epsilon_{PEHE}}$ Method / *Policy*	CEMNIST (50% rejected)		IHDP Cov. (50% rejected)		IHDP (10% rejected)	
	random	*uncertainty*	*random*	*uncertainty*	*random*	*uncertainty*
BART	2.1±.02	2.0±.03	2.6±.2	1.8±.2	1.90±.20	1.60±.10
BT-Learner	.27±.00	.04±.01	2.3±.2	1.3±.1	0.95±.03	0.69±.01
BTARNet	.18±.01	**.00±.00**	2.2±.3	**1.2±.1**	1.10±.03	0.76±.03
BCFR-MMD	.32±.01	.13±.02	2.5±.2	1.7±.2	1.30±.06	0.91±.03
BDragonnet	.22±.01	.02±.01	2.4±.3	1.3±.2	1.50±.05	1.05±.02
BCEVAE	.30±.01	.04±.01	2.5±.2	1.7±.1	1.80±.06	1.47±.08
DKLITE*			2.6±.7	1.8±.5	1.74±.53	1.34±.41
vDUQ	**.16±.02**	.01±.00	**1.82±.35**	**1.23±.16**	**0.90±.18**	**0.53±.09**

effect: CATE $:= \mathbb{E}[Y_{t=1}(\boldsymbol{x}) - Y_{t=0}(\boldsymbol{x})]$ (Abrevaya et al., 2015). As it is only possible to observe one of the two potential outcomes, $Y_{t=0}(\boldsymbol{x})$ or $Y_{t=1}(\boldsymbol{x})$, identification of CATE hinges upon the assumption that we have conditioned on all features x of each patient which might have a confounding effect on treatment outcome. This assumption posits that the observed data is unconfounded ($\{Y_{t=0}, Y_{t=1}\} \perp\!\!\!\perp t|\boldsymbol{x}$) and that there is sufficient overlap ($0 < p(t = 1|\boldsymbol{x}) < 1$).

To get some intuition, consider a case where a helpful treatment t is more likely to be given to the severely ill. As a result, the survival rate of treated patients will be lower, creating an erroneous conclusion that the treatment has a negative effect if we don't condition on the current symptoms x of each patient. Conditioning on x removes this confounding effect. The unconfoundedness assumption says that we observe all possible factors that may affect the distribution of treatment. The overlap assumption means we need to have sufficient samples from each subgroup - e.g our data needs to contain at least some people who were assigned treatment for every set of attributes x for us to determine the conditional effect.

Jesson et al. (2020) show that violation of the overlap assumption can be framed as an out-of-distribution problem and that uncertainty aware models yield appropriately low confidence predictions for such out of distribution test examples. Further, they show that uncertainty estimates can be used to define treatment recommendation policies that defer to experts when it is suspected that either overlap is violated, or a new example represents a covariate shift. Therefore, causal inference can be seen as an interesting application of regression uncertainty because uncertainty can identify when a model has insufficient understanding to make a recommendation for a novel individual, as well as express confidence in the causal estimand itself, which would be invalid if overlap is violated.

We use the semi-synthetic IHDP (Hill, 2011), IHDP Cov. and CEMNIST (Jesson et al., 2020) datasets to assess the uncertainty estimates of vDUQ on this causal inference task following the experimental setup in (Jesson et al., 2020). IHDP and IHDP Cov. are regression datasets with only ~750 data points, while CEMNIST is a binary classification dataset with 10k points. For each dataset, predictions are withheld for a specified proportion (**50%** or **10%**) of the test set based on either a random sample (***random***), or on the highest uncertainty in CATE estimate (***uncertainty***). We report the root expected Precision in Estimation of Heterogeneous Effect (Hill, 2011) ($\sqrt{\epsilon_{PEHE}}$) to assess the error on the remaining examples (lower is better). Table 2 summarizes our results and shows that vDUQ has improved performance and uncertainty estimates better suited to rejection policies than other uncertainty aware methods. In particular, we improve on DKLITE (Zhang et al., 2020) a method specifically designed for CATE inference.

6 CONCLUSION

We have presented vDUQ, a practical probabilistic method which allows for using deep architectures and we established its efficacy in 2D, on a large image dataset and in causal inference for personalized medicine, obtaining or matching state of the art results in each. There are interesting future research opportunities exploring the theoretical justification for the regularization scheme, going beyond what is discussed in Section 3.1 and Liu et al. (2020) and incorporating research from the existing kernel literature. Good uncertainty and fast inference in both classification and regression make vDUQ a compelling plug in option for many applications, such as exploration in reinforcement learning, active learning and many real world tasks.

REFERENCES

Jason Abrevaya, Yu-Chin Hsu, and Robert P Lieli. Estimating conditional average treatment effects. *Journal of Business & Economic Statistics*, 33(4):485–505, 2015.

Jens Behrmann, Will Grathwohl, Ricky TQ Chen, David Duvenaud, and Jörn-Henrik Jacobsen. Invertible residual networks. In *International Conference on Machine Learning*, pp. 573–582, 2019.

John Bradshaw, Alexander G de G Matthews, and Zoubin Ghahramani. Adversarial examples, uncertainty, and transfer testing robustness in gaussian process hybrid deep networks. *arXiv preprint arXiv:1707.02476*, 2017.

Luitzen EJ Brouwer. Beweis der invarianz des n-dimensionalen gebiets. *Mathematische Annalen*, 71(3):305–313, 1911.

Roberto Calandra, Jan Peters, Carl Edward Rasmussen, and Marc Peter Deisenroth. Manifold gaussian processes for regression. In *2016 International Joint Conference on Neural Networks (IJCNN)*, pp. 3338–3345. IEEE, 2016.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Advances in Neural Information Processing Systems*, pp. 4754–4765, 2018.

Sebastian Farquhar, Michael Osborne, and Yarin Gal. Radial bayesian neural networks: Robust variational inference in big models. *arXiv preprint arXiv:1907.00865*, 2019.

Andrew YK Foong, Yingzhen Li, José Miguel Hernández-Lobato, and Richard E Turner. 'in-between'uncertainty in bayesian neural networks. *Workshop on Uncertainty and Robustness in Deep Learning*, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059, 2016.

Jacob R Gardner, Geoff Pleiss, David Bindel, Kilian Q Weinberger, and Andrew Gordon Wilson. Gpytorch: Blackbox matrix-matrix gaussian process inference with gpu acceleration. 2018.

Henry Gouk, Eibe Frank, Bernhard Pfahringer, and Michael Cree. Regularisation of neural networks by enforcing lipschitz continuity. *arXiv preprint arXiv:1804.04368*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

James Hensman, Alexander Matthews, and Zoubin Ghahramani. Scalable variational gaussian process classification. *JMLR*, 2015.

James Hensman, Nicolas Durrande, and Arno Solin. Variational fourier features for gaussian processes. *The Journal of Machine Learning Research*, 18(1):5537–5588, 2017.

Jennifer L. Hill. Bayesian nonparametric modeling for causal inference. *Journal of Computational and Graphical Statistics*, 20(1):217–240, 2011. doi: 10.1198/jcgs.2010.08162. URL `https://doi.org/10.1198/jcgs.2010.08162`.

Geoffrey E Hinton and Russ R Salakhutdinov. Using deep belief nets to learn covariance kernels for gaussian processes. In *Advances in neural information processing systems*, pp. 1249–1256, 2008.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pp. 448–456, 2015.

Jörn-Henrik Jacobsen, Arnold Smeulders, and Edouard Oyallon. i-revnet: Deep invertible networks. *arXiv preprint arXiv:1802.07088*, 2018.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in neural information processing systems*, pp. 8571–8580, 2018.

Andrew Jesson, Sören Mindermann, Uri Shalit, and Yarin Gal. Identifying causal effect inference failure with uncertainty-aware models. *arXiv preprint arXiv:2007.00163*, 2020.

Andreas Kirsch, Joost van Amersfoort, and Yarin Gal. Batchbald: Efficient and diverse batch acquisition for deep bayesian active learning. In *Advances in Neural Information Processing Systems*, pp. 7026–7037, 2019.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in neural information processing systems*, pp. 6402–6413, 2017.

Miguel Lázaro-Gredilla and Anibal Figueiras-Vidal. Inter-domain gaussian processes for sparse inference using inducing features. In *Advances in Neural Information Processing Systems*, pp. 1087–1095, 2009.

Jeremiah Zhe Liu, Zi Lin, Shreyas Padhy, Dustin Tran, Tania Bedrax-Weiss, and Balaji Lakshminarayanan. Simple and principled uncertainty estimation with deterministic deep learning via distance awareness. *arXiv preprint arXiv:2006.10108*, 2020.

Alexander Graeme de Garis Matthews. *Scalable Gaussian process inference using variational methods*. PhD thesis, University of Cambridge, 2017.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018.

Ian Osband, Charles Blundell, Alexander Pritzel, and Benjamin Van Roy. Deep exploration via bootstrapped dqn. In *Advances in neural information processing systems*, pp. 4026–4034, 2016.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, pp. 13991–14002, 2019.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *the Journal of machine Learning research*, 12:2825–2830, 2011.

Uri Shalit, Fredrik D Johansson, and David Sontag. Estimating individual treatment effect: generalization bounds and algorithms. In *International Conference on Machine Learning*, pp. 3076–3085. PMLR, 2017.

Lewis Smith and Yarin Gal. Understanding measures of uncertainty for adversarial example detection. *Conference on Uncertainty in Artificial Intelligence*, 2018.

L Theis, A van den Oord, and M Bethge. A note on the evaluation of generative models. In *International Conference on Learning Representations (ICLR 2016)*, pp. 1–10, 2016.

Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In *Artificial Intelligence and Statistics*, pp. 567–574, 2009.

Joost van Amersfoort, Lewis Smith, Yee Whye Teh, and Yarin Gal. Uncertainty estimation using a single deep deterministic neural network. *International Conference on Machine Learning*, 2020.

Mark Van der Wilk, Carl Edward Rasmussen, and James Hensman. Convolutional gaussian processes. In *Advances in Neural Information Processing Systems*, pp. 2849–2858, 2017.

Ke Wang, Geoff Pleiss, Jacob Gardner, Stephen Tyree, Kilian Q Weinberger, and Andrew Gordon Wilson. Exact gaussian processes on a million data points. In *Advances in Neural Information Processing Systems*, pp. 14648–14659, 2019.

Andrew G Wilson, Zhiting Hu, Russ R Salakhutdinov, and Eric P Xing. Stochastic variational deep kernel learning. In *Advances in Neural Information Processing Systems*, pp. 2586–2594, 2016a.

Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P Xing. Deep kernel learning. In *Artificial intelligence and statistics*, pp. 370–378, 2016b.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *BMVC*, 2016.

Yao Zhang, Alexis Bellot, and Mihaela van der Schaar. Learning overlapping representations for the estimation of individualized treatment effects. *arXiv preprint arXiv:2001.04754*, 2020.

A EXPERIMENTAL DETAILS

A.1 2D EXPERIMENTS

We perform our 2D experiments using a simple feed forward ResNet. The first linear layer maps from the input to the feature representation and does not have an activation function. From there on, the model is a ResNet, $x' = x + f(x)$, with $f(\cdot)$ a combination of a linear mapping and a relu activation function. The linear mapping has optional Spectral Normalization for which we use the implementation of Behrmann et al. (2019). We use the SGD optimizer for regression and Adam for the two moons with learning rate 0.01, and we use 4 layers with 128 features. For the toy regression, we use a max Lipschitz constant 0.95, one power iteration and 20 inducing points. For the two moons, we set the noise level to 0.1 and use five power iterations, a Lipschitz constant of 0.65 and four inducing points. For the Deep Ensemble in Figure 1 we train 10 separate models, using a different initialization and data order for each and train to minimize the squared error.

A.2 WIDE RESNET EXPERIMENTS

For the WRN, we follow the experimental setup and implementation of Zagoruyko & Komodakis (2016). This means that for CIFAR-10, we use depth 28 with widen factor 10 and BasicBlocks with dropout.

We train for the prescribed 200 epochs with batch size 128, starting with learning rate 0.1 and dropping with a factor of 0.2 at epoch 60, 120 and 160. We use the full training set and take the model at epoch 200 (no early stopping).

For Spectral Normalization, we again use the implementation of Behrmann et al. (2019), in particular the convolutional version and also constrain batch normalization as described in (Gouk et al., 2018). We use 1 power iteration and use the lowest Lipschitz constant that still allows for good accuracy, which we found to be around 3 in practice. We increase the momentum of batch normalization to 0.99 (from 0.9 default) to reduce the variance of the running average estimator of the empirical feature variance, which can be a source of instability (Gouk et al., 2018).

A.3 CAUSAL EXPERIMENTS

Following Shalit et al. (2017), we use 63/27/10 train/validation/test splits and report the PEHE evaluated on the test set over 1000, and 20 trials for the IHDP and CEMNIST datasets, respectively. For each trial, we train for a maximum of 750 epochs and evaluate the model with the lowest ELBO evaluated over the validation set. We employ Adam optimization with a learning rate of 0.001 and batch size of 100.

The feature extractor uses a feed forward ResNet architecture with 3, 200 unit hidden layers, and ELU activations. Dropout is applied after each activation at a rate of 0.1. The feature extractor takes the covariates x and treatment t as input. For the CEMNIST experiment, a depth 3 CNN Resnet is used to extract features from the image, which is then passed as an input to the above architecture. Spectral normalization is used on all layers of the feature extractor. We use a Matérn kernel with $\nu = \frac{1}{2}$, 200 inducing points, and a smoothed box prior on the lengthscales with range $(\exp(-1), \exp(1))$.

For the DKLITE experiments we use the open source code from the authors available at `https://bitbucket.org/mvdschaar/mlforhealthlabpub/src/master/alg/dklite/`. We write a custom loop over the IHDP dataset to follow the above protocol. For DKLITE on CEMNIST, in initial experimentation we found that the method did not adapt well to images, so we omit the comparison from the table. We make this adaptation available at `anonymized-for-review`.

A.4 INDUCING POINT GP

We initialize the inducing points by doing k-means on the feature representation of 1,000 points. We compute the initial length scale by taking the pairwise euclidean distance between feature representation of the 1,000 points. We whiten the inducing points before training, as suggested in Matthews

(2017). The kernel parameters, such as the length scale and output scale, are different per GP. We implement it using GPyTorch (Gardner et al., 2018) and use their default values if not otherwise specified.

B   PROOF OF PROPOSITION 1

This proof makes no claim to novelty, but is provided for completeness.

Proof of proposition 1. We can show that this follows from the fact that the metric spaces $\mathbb{R}^m$ and $\mathbb{R}^n$ are not homeomorphic (topologically equivalent) to one another (Brouwer, 1911). While this statement is extremely intuitive, proving it is surprisingly technical, so we will take it as given.

First, we prove the following lemma.

Lemma 1. *Let $f : X \mapsto Y$ be a bi-Lipschitz and onto function, so $\frac{1}{L}||x_1 - x_2||_X \leq ||f(x_1) - f(x_2)||_Y \leq L||x_1 - x_2||_X$, and Y is the image of X under f. Then f is a homeomorphism between X and Y, and so X and Y are homeomorphic.*

Proof. Recall that a function f is a homeomorphism if f is bijective, f is continuous, and f^{-1} is also continuous. We will address these in turn. To see that f is bijective, note that f is injective iff $\forall x_1, x_2 \in X$, we have $x_1 \neq x_2 \implies f(x_1) \neq f(x_2)$. But this follows directly from the lower Lipschitz property of f, since if $x_1 \neq x_2$, then $||x_1 - x_2||_X > 0$, so $||f(x_1) - f(x_2)||_Y > 0$, from which it follows that $f(x_1) \neq f(x_2)$. Since f is injective (one-to-one) and onto, it is a bijection. Since any function which is Lipschitz continuous is also continuous, the fact that f is continuous is given. Since f is bijective, the inverse function f^{-1} exists, and we need to show that it is continuous. We have, from the bi-Lipschitzness of f, that $\frac{1}{L}||f^{-1}(f(x_1)) - f^{-1}(f(x_1))||_X \leq ||f(x_1) - f(x_2)||_Y$, which implies that the inverse function is also Lipschitz, and hence also continuous. So f is a homeomorphism, and we are done. □

We have therefore established that if a bi-Lipschitz (and onto) function exists between two spaces X and Y, then X and Y are homeomorphic. This provides a proof of our claim by contradiction; if a function $f : \mathbb{R}^n \mapsto \mathbb{R}^m$ existed and was bi-Lipschitz, then we would have shown that $\mathbb{R}^n$ and $\mathbb{R}^m$ were homeomorphic, since any bi-Lipschitz function is a homeomorphism. But $\mathbb{R}^n$ and $\mathbb{R}^m$ are not homeomorphic unless $m = n$, so no such function can exist. □

C   SAMPLING FROM THE JOINT POSTERIOR

In Figure 4, we show samples from the joint predictive posterior. This type of sampling is not possible using standard deep learning models, because there is no covariance modelled between the batch elements. Possible applications of this include batch active learning, where we want to estimate a joint posterior (Kirsch et al., 2019), but also for deep exploration in RL where we can effectively sample a full policy (Osband et al., 2016).

Figure 4: The same setup as in 1b, but instead of visualizing the uncertainty directly, we visualize samples from the joint posterior. As expected, the functions become significantly less smooth away from the data as expected using the Matérn $\nu = \frac{1}{2}$ kernel.

Figure 5: A density of the Lipschitz values in batch normalization layers, averaged across 15 WRN models that were trained with Softmax output and without Spectral Normalization (exactly following Zagoruyko & Komodakis (2016)). We see that many of the constants are significantly above 1, invalidating the claim that Batch Normalization reduces the Lipschitz constant of the network.