Hidden Progress in Deep Learning: SGD Learns Parities Near the Computational Limit

Abstract

There is mounting empirical evidence of *emergent phenomena* in the capabilities of deep learning methods as we scale up datasets, model sizes, and training times. While there are some accounts of how these resources modulate statistical capacity, far less is known about their effect on the *computational* problem of model training. This work conducts such an exploration through the lens of learning k-sparse parities of n bits, a canonical family of problems which pose theoretical computational barriers. In this setting, we find that neural networks exhibit surprising phase transitions when scaling up dataset size and running time. In particular, we demonstrate empirically that with standard training, a variety of architectures learn sparse parities with $n^{O(k)}$ examples, with loss (and error) curves abruptly dropping after $n^{O(k)}$ iterations. These positive results nearly match known SQ lower bounds, even without an explicit sparsity-promoting prior. We elucidate the mechanisms of these phenomena with a theoretical analysis: we find that the phase transition in performance is *not* due to SGD "stumbling in the dark" until it finds the hidden set of features (a natural algorithm which also runs in $n^{O(k)}$ time); instead, we show that SGD gradually amplifies a *Fourier gap* in the population gradient.

1 Introduction

Neural networks perform better with more resources (data, model size, training time), but different tasks exhibit qualitatively different dependencies of performance on resources. In particular, while many learning tasks exhibit continuous improvement in performance with increasing resources, other cases show *discontinuous* improvement, where a capability emerges at a certain threshold. Through a statistical lens, it is well-understood that larger models, trained with more data, can fit more complex and expressive functions. However, far less is known about the analogous *computational* question: how does the scaling of these resources influence the success of gradient-based optimization for training these models?

These emergent *phase transitions* cannot be explained via statistical capacity alone. In many cases we see a phase transition even when the amount of data remains fixed, with only model size or training time increasing. A timely example is the emergence of reasoning and few-shot learning capabilities when scaling up language models (Radford et al., 2019; Brown et al., 2020; Chowdhery et al., 2022; Hoffmann et al., 2022). Power et al. (2022) give examples exhibiting discontinuous improvements in population accuracy ("grokking") when running time increases, while data and model size remain fixed.

In this work, we analyze the computational aspect of scaling in deep learning in a simple synthetic setting which already exhibits discontinuous improvements. Specifically, we consider the *sparse parity problem*— where the label is the parity (XOR) of $k \ll n$ bits in a random length-n binary string. This is a canonical problem which is computationally difficult for a range of algorithms, including

Figure 1: Main empirical findings at a glance. A variety of neural networks, with standard training and initialization, can solve the (n, k)-parity learning problem, with a number of iterations scaling as $n^{O(k)}$. *Left:* Training curves under various algorithmic choices (architecture, batch size, learning rate) on the $(n = 50, k = 3)$-parity problem. *Right:* Median convergence times for small (n, k).

gradient-based (Kearns, 1998) and streaming (Kol et al., 2017) algorithms. We focus on analyzing the resource measure of *training time*, and demonstrate that the loss curves for sparse parities display a phase transition across a variety of architectures and hyperparameters (see Figure 1, left). A striking observation is that SGD robustly finds the sparse subset (and hence, effectively, reaches 0 error) with a variety of activation functions and initialization schemes, even with *no* over-parameterization. This robust convergence is the starting point for our investigation.

Perhaps the most natural hypothesis to explain SGD's success in learning parities would be that it simply "stumbles in the dark", essentially performing random search for the unknown target (e.g. via stochastic gradient Langevin dynamics). If that were the case, we might expect to observe a convergence time of $2^{\Omega(n)}$, like a naive search over parameters or subsets of indices. However, Figure 1 *(right)*, already provides some evidence against this "random search" hypothesis: the convergence time is closer to an $n^{O(k)}$ scaling. Notably, such a convergence rate implies that SGD is closer to achieving the *optimal computation time* among a natural class of algorithms, namely SQ (statistical query) algorithms.

In this work, through an extensive empirical analysis of the scaling behavior of a variety of models, as well as theoretical analysis, we give strong evidence against the "stumbling in the dark" viewpoint. Instead, there is a *hidden progress measure* under which SGD is steadily improving. Furthermore, and perhaps surprisingly, we show that SGD achieves a computational runtime much closer to the optimal SQ lower bound than simply doing (non-sparse) parameter search. More generally, our theoretical and empirical investigations reveal a number of notable phenomena regarding the dependence of SGD's performance on resources, and we provide further theoretical and empirical evidence of phase transitions with data, model size, and training time.

1.1 Our contributions

SGD efficiently learns sparse parities, in theory and practice. It is known from SQ lower bounds that (noisy) gradient descent on *any* architecture requires at least $n^{\Omega(k)}$ computational steps to learn k-sparse n-dimensional parities (for background, see Appendix A). However, with standard architectures and initialization, which do not explicitly encode a sparsity prior, one may expect SGD's performance to be much worse, on the order of $2^{\Omega(n)}$. We give extensive empirical evidence that this is not the case.

Empirical Finding 1. *For all small instances ($n \leq 30, k \leq 4$) of the sparse parity problem, architectures $\mathcal{A} \in \{$2-layer MLPs, Transformers[1], sinusoidal (and other non-standard) neurons, PolyNets[2]$\}$, initializations in $\{$uniform, Gaussian, Bernoulli$\}$, and batch sizes $1 \leq B \leq 1024$, SGD*

---

[1]With a smaller range of hyperparameters.

[2]A non-standard architecture introduced in this work; see Section 3 for the definition.

on $\mathcal{A}$ solves the (n, k)-sparse parity problem (w.p. ≥ 0.2) within at most $c \cdot n^{\alpha k}$ steps, for small architecture-dependent constants c, α.

For a subset of these architectures, we performed more extensive training, to show scaling behaviors of the computation time;[3] see Figure 1 *(right)* and Figure 10 in the appendix.

The above results indicate that SGD succeeds at solving parities much faster than the $2^{\Omega(n)}$ steps that would be required by random search without a sparse prior. This suggests that despite flat loss and accuracy curves before the phase transition, SGD makes progress "under the hood". We show that this is indeed the case by coming up with a *progress measure* that continuously improves throughout training. We can explain the loss and accuracy curves using this progress measure, by showing that they typically rise sharply once the measure passes a certain threshold.

Theoretical Analysis. Our empirical results suggest that, in a number of computational steps matching the SQ limit, SGD is able to solve the parity problem and identify the influential coordinates, without an explicit sparse prior. We give a theoretical analysis which validates this claim.

Informal Theorem 2. *On 2-layer MLPs of width $2^{\Theta(k)}$, and with batch size $n^{O(k)}$, SGD converges with high probability to a solution with at most ϵ error on the (n, k)-parity problem in at most $2^{O(k)} \cdot \mathrm{poly}(1/\epsilon)$ iterations.*

We also present a stronger analysis for an idealized architecture (which we call the *disjoint-PolyNet*), which allows for any batch size, and captures the phase transitions observed in the error curves.

Informal Theorem 3. *On disjoint-PolyNets, SGD (with any batch size $B \geq 1$) converges with high probability to a solution with at most ϵ error on the (n, k)-parity problem in at most $n^{O(k)} \cdot \log(1/\epsilon)$ iterations. Continuous-time gradient flow exhibits a phase transition: it spends a $1 - o(1)$ fraction of its time before convergence with error $\geq 49\%$.*

In addition to refuting the alternative "random search" hypothesis, our work also poses a counterexample to other models for the computational mechanisms of deep learning; for instance, it provides a setting where deep neural nets successfully learn a concept to 100% accuracy while the corresponding Neural Tangent Kernel (NTK) only achieves trivial performance, hence showing the importance of *feature learning*. We also construct a counterexample to the *"deep only works if shallow is good"* principle of Malach and Shalev-Shwartz (2019), demonstrating a case where a deep network can get near-perfect accuracy even when greedy layerwise training (e.g. Belilovsky et al. (2019)) cannot beat trivial performance. By providing positive theory and empirics which elude these simplified explanations of SGD, we hope to point the way to a more complete understanding of learning dynamics in the challenging cases where no apparent progress is made for extended periods of time.

1.2 Related work

We present the most directly related work below, on feature learning, learning parities with neural nets, and the statistical mechanics of machine learning. A broader discussion of related work can be found in Appendix A.3.

SGD and feature learning. Theoretical analysis of gradient descent over neural networks is notoriously hard, due to the non-convex nature of the optimization problem. That said, it has been established that in some settings, the dynamics of GD keep the weights close to their initialization, thus behaving like convex optimization over the Neural Tangent Kernel (see, for example, Jacot et al. (2018); Allen-Zhu et al. (2019); Du et al. (2018)). In contrast, it has been shown that in various tasks, moving away from the fixed features of the NTK is essential for the success of neural networks trained with GD (for example Yehudai and Shamir (2019); Allen-Zhu and Li (2019); Wei et al. (2019) and the review in Malach et al. (2021)). These results demonstrate that feature learning is an important part of the GD optimization process. Our work also focuses on a setting where feature learning is essential for the target task. In our theoretical analysis, we show that the initial population gradient encodes the relevant features for the problem. The importance of the first gradient step for feature learning has been recently studied in (Ba et al., 2022).

---

[3] While our focus is on the performance as a function of *training time*, we also performed some experiments on performance as a function of *model size*, see Section 5.

Learning parities with neural networks. The problem of learning parities using neural networks has been investigated in prior works from various perspectives. It has been demonstrated that parities are hard for gradient-based algorithms, using similar arguments as in the SQ analysis (Shalev-Shwartz et al., 2017; Abbe and Sandon, 2020). One possible approach for overcoming the computational hardness is to make favorable assumptions on the input distribution. Indeed, recent works show that under various assumptions on the input distribution, neural networks can be efficiently trained to learn parities (XORs) (Daniely and Malach, 2020; Shi et al., 2021; Frei et al., 2022; Malach et al., 2021). In contrast to these results, this work takes the approach of intentionally focusing on a hard benchmark task, without assuming that the distribution has some favorable (namely, non-uniform) structure. This setting allows us to probe the performance of deep learning at a known computational limit. Notably, the work of Andoni et al. (2014) provides analysis for learning polynomials (and in particular, parities) under the uniform distribution. However, their main results require a network of size $n^{O(k)}$ (i.e., extremely overparameterized network), and provides only partial theoretical and empirical evidence for the success of smaller networks. Studying a related subject, some works have shown that neural networks display a spectral bias, learning to fit low-frequency coefficients before high-frequency ones (Rahaman et al., 2019; Cao et al., 2019).

Statistical mechanics of machine learning. An extensive body of work originating in the statistical physics community has studied phase transitions in the learning curves of neural networks (Gardner and Derrida, 1989; Watkin et al., 1993; Engel and Van den Broeck, 2001). These works typically focus on student-teacher learning in the "thermodynamic limit", in which the number of training examples is α times larger than the input dimension and both are taken to infinity. One of the classic toy architectures analyzed in this literature is the *parity machine* (Mitchison and Durbin, 1989; Hansel et al., 1992; Opper, 1994; Kabashima, 1994; Simonetti and Caticha, 1996). In our work, we introduce PolyNets, a variant of parity machines in which the output is real-valued rather than ± 1; and we theoretically analyze disjoint-Polynets, which are the real-output analogue of the oft-considered parity machines with tree architecture. While much of the statistical mechanics of ML literature focuses on an idealized training limit in which the weights reach a Gibbs distribution equilibrium, there is a strand of the literature that aims to characterize the trajectory of SGD training in the high-dimensional limit with constant-sized sets of ordinary differential equations (Saad and Solla, 1995b,a; Goldt et al., 2019). These papers discuss cases, including problems that share aspects with 2-sparse parities Refinetti et al. (2021), where the network gets stuck in (and then escapes from) a plateau of suboptimal generalization error. Recently, Arous et al. (2021) studied (for rank-one parameter estimation problems) the relative amount of time spent by SGD in an initial high-error "search" phase versus a final "descent" phase, which is reminiscent of the framing of Theorem 7. However, to our knowledge prior work has not shown k-sparse parities can be learned with a number of iterations that nearly matches known lower bounds, nor has it specifically studied phase transitions in k-sparse parity learning during gradient descent.

2 Preliminaries

We define necessary notation here; see Appendix A for more background and technical ingredients.

Sparse parities. For integer $n \geq 1$ and non-empty $S \subseteq [n]$, the (n, S)-*parity function* $\chi_S : \{\pm 1\}^n \to \{\pm 1\}$ is defined as $\chi_S(x) = \prod_{i \in S} x_i$. We define the (n, S)-*parity distribution* $\mathcal{D}_S$ as the distribution over $(x, y = \chi_S(x))$[4] where x is drawn from the uniform distribution over $\{\pm 1\}^n$, which we denote by $\mathrm{Unif}(\{\pm 1\}^n)$. We define the (n, k)-*parity learning problem* as the task of recovering S using samples from $\mathcal{D}_S$, where S is chosen at random in $\binom{[n]}{k}$. Statistically, it is possible to do so using $\Theta(\log \binom{n}{k}) \approx k \log n$ samples. However, in the *statistical query* (SQ) model (Kearns, 1998), (which has been shown to encapsulate gradient-based methods such as GD or SGD (Abbe et al., 2021)), this task requires $\Omega(n^k)$ queries (assuming constant level of noise). While learning noiseless parities can be solved by Gaussian elimination using $O(n)$ samples, learning sparse *noisy* parities, even at a very small noise level (i.e., $o(1)$ or $n^{-\delta}$) is believed to inherently require $n^{\Omega(k)}$ computational steps and samples, or exponential computation with $n^{o(k)}$ samples. This was first

---

[4]Our theoretical analyses and experiments can tolerate noisy parities, that is, random flipping of the label. For ease of presentation, we state the non-noisy setting.

Figure 2: Black-box observations about the training dynamics. *Left:* Histograms of convergence times over 10^6 random trials, with heavy upper tails but no observed successes near $t = 0$ (unlike random search). *Center:* Optimization path (and convergence time) depend heavily on initialization, not the randomness of SGD; $B = 128, \eta = 0.01$ shown here. *Right:* The power-law exponent (α such that $t_c \propto n^\alpha$) eventually degrades on larger problem instances.

explicitly conjectured by Alekhnovich (2003), and has been the basis for several cryptographic schemes (e.g., (Ishai et al., 2008; Applebaum et al., 2009, 2010; Bogdanov et al., 2019)).

Notation for neural networks and training. Our main results are presented in the online learning setting, with a stream of i.i.d. batches of examples. At each iteration $t = 1, \ldots, T$, a learning algorithm receives a batch of B examples $\{(x_{t,i}, y_{t,i})\}_{i=1}^B$ drawn i.i.d. from $\mathcal{D}_S$, then outputs a classifier $\widehat{y}_t : \{\pm 1\}^n \to \{\pm 1\}$. We say that the algorithm solves the parity task in t steps with ϵ error, if with probability at least $1 - \epsilon$ over both training and internal randomness, as well as $(x, y) \sim \mathcal{D}_S$, $\widehat{y}_t(x) = y$. We will focus on the case that $\widehat{y}_t = \text{sign}(f(x; \theta_t))$ for some parameters θ_t in a continuous domain Θ and for a continuous function $f : \{\pm 1\}^n \times \Theta \to \mathbb{R}$.[5] A ubiquitous online learning algorithm is gradient descent (GD). For a choice of loss function $\ell : \{\pm 1\} \times \mathbb{R} \to \mathbb{R}$, initialization θ_0 (that are chosen from some distribution), learning rate schedule $\{\eta_t\}_{t=1}^T \subseteq \mathbb{R}$ and weight-decay schedule $\{\lambda_t\}_{t=1}^T \subseteq \mathbb{R}$, GD refers the standard iterative update rule using the regularized, empirical loss function, which is a function of *architecture* f. The learning rate η_t can also be a vector (e.g., allowing different rate schedules for different layers).

3 Empirical findings

3.1 SGD on neural networks learns sparse parities

The central phenomenon of study in this work is the empirical observation that neural networks, with standard initialization and training, can solve the (n, k)-parity problem in a number of iterations scaling as $n^{O(k)}$ on small instances. We observed robust positive results for randomly-initialized SGD on the following architectures, indexed by Roman numerals:

- *2-layer MLPs:* ReLU ($\sigma(z) = (z)_+$) or polynomial ($\sigma(z) = z^k$) activation, in a wide variety of width regimes $r \geq k$. Settings (i), (ii), (iii) (resp. (iv), (v), (vi)) use $r = \{10, 100, 1000\}$ ReLU (resp. polynomial) activations. We also consider $r = k$ (exceptional settings (*i), (*ii)), the minimum width for representing a k-wise parity for both activations.

- *Single neurons:* Next, we consider non-standard activation functions σ which allow a one-neuron architecture $f(x; w) = \sigma(w^\top x)$ to realize k-wise parities. The constructions stem from letting $w^* = \sum_{i \in S} e_i$, and constructing $\sigma(\cdot)$ to interpolate (the appropriate scaling of) $\frac{k - w^{*\top} x}{2}$ mod 2 with a piecewise linear k-*zigzag* activation (vii), or a degree-k polynomial (viii). Going a step further, a single ∞-*zigzag* (ix) or *sinusoidal* (x) neuron can represent *all* k-wise parities. We also removed the second trainable layer (setting $u = 1$), obtaining settings (xi), (xii), (xiii), (xiv). We found that wider architectures with these activations also trained successfully.

---

[5]When $f(x; \theta) = 0$ in practice (e.g. with sign initialization), we break the tie arbitrarily. We ensure in the theoretical analysis that this does not happen.

Figure 3: Hidden progress when learning parities with neural networks. *Left, center:* Black-box losses and accuracies exhibit a long plateau and sharp phase transition (top), hiding gradual progress in the SGD iterates (bottom). *Right:* A hidden progress measure which distinguishes gradual feature amplification (top) from training on noise (bottom).

- *Transformers:* Motivated by recent theoretical and empirical work on the ability of self-attention to learn sparse functions and parities (Lu et al., 2021; Edelman et al., 2021; Hahn, 2020), we consider a simplified specialization of the Transformer architecture to this sequence classification problem. This is the less-robust setting (*iii); the architecture and optimizer are described in Appendix D.1.3.

- *PolyNets:* Our final setting (xv) is the PolyNet, a slightly modified version of the parity machine architecture. Parity machines have been studied extensively in the statistical mechanics of ML literature (see the related work section) as well as in a line of work on 'neural cryptography' (Rosen-Zvi et al., 2002). A parity machine outputs the sign of the product of k linear functions of the input. A PolyNet simply outputs the product itself. Both architectures can clearly realize k-sparse parities. The PolyNet architecture was originally motivated by the search for an idealized setting where an end-to-end optimization trajectory analysis is tractable (see Section 4.1); we found in these experiments that this architecture trains very stably and sample-efficiently.

Robust space of positive results. All of the networks listed above were observed to successfully learn sparse parities in a variety of settings. We summarize our findings as follows: for all combinations of $n \in \{10, 20, 30\}$, $k \in \{2, 3, 4\}$, batch sizes $B \in \{1, 2, 4, \ldots, 1024\}$, initializations {uniform, Gaussian, Bernoulli}, loss functions {hinge, square, cross entropy}, and architecture configurations $\{(i), (ii), \ldots, (xv)\}$, SGD solved the parity problem (with 100% accuracy, validated on a batch of 2^{13} samples) in at least 20% of 25 random trials, for at least one choice of learning rate $\eta \in \{0.001, 0.01, 0.1, 1\}$. The models converged in $t_c \leq c \cdot n^{\alpha k} \leq 10^5$ steps, for small architecture-dependent constants c, α, shown in Appendix C. Figure 1 *(left)* shows some representative training curves.

Less robust configurations. Settings (*i) and (*ii), where the MLP just barely represents a k-sparse parity, and the Transformer setting (*iii), are less robust to small batch sizes. In these settings, the same positive results as above only held for sufficiently large batch sizes: $B \geq 16$. Also, setting (*iii) used the Adam optimizer; see Appendix D.1.3 for details.

Phase transitions in training curves. For almost all of the architectures, we find that that the training curves exhibit phase transitions in terms of running time (and thus, in the online learning setting, dataset size as well): long durations of seemingly no progress, followed by periods of rapid decrease in the validation error. Strikingly, for architectures (v) and (vi), this plateau is absent: the error in the initial phase appears to decrease with a linear slope. See Appendix C.8 for more plots.

3.2 Random search or hidden progress?

The remainder of this paper seeks to answer the question: *"By what mechanism does deep learning solve these emblematic computationally-hard optimization problems?"*

A natural hypothesis would be that SGD somehow implicitly performs Monte Carlo random search, "bouncing around" the loss landscape in the absence of a useful gradient signal. Upon closer inspection, several empirical observations clash with this hypothesis:

- *Scaling of convergence times:* Without an explicit sparsity prior in the architecture or initialization, it is unclear how to account for the $n^{\Theta(k)}$ runtimes observed in experiments. The initializations, which certainly do not prefer sparse functions[6], are close to the correct solutions with probability $2^{-\Omega(n)} \ll n^{-k}$. On larger instances (n, k), the power-law exponents worsen; see Figure 2 *(right)*, and the discussion in Appendix C.2.

- *No early convergence:* Over a large number of random trials, no copies of this randomized algorithm get "lucky" (i.e. solve the problem in significantly fewer than the median number of iterations); see Figure 2 *(left)*. The success times of random exhaustive search would be distributed as $\mathrm{Geom}(1/\binom{n}{k})$, whose probability mass is highest at $t = 0$ and decreases monotonically with t.

- *Sensitivity to initialization, not stochastic batches:* Running these training setups over multiple stochastic batches from a common initialization, we find that loss curves and convergence times are highly correlated with the architecture's random initialization; see Figure 2 *(center)*.

Even these observations, which do not probe the internal state of the algorithm, suggest that exhaustive search is an insufficient picture of the training dynamics, and a different mechanism is at play.

4 Theoretical analyses

4.1 Provable emergence of the parity indices in high-precision gradients

We now provide a theoretical account for the success of SGD in solving the (n, k)-parity problem. Our main theoretical observation is that, in many cases, the *population* gradient of the weights at initialization contains enough "information" for solving the parity problem. That is, given an accurate enough estimate of the initial gradient (by e.g. computing the gradient over a large enough batch size), the relevant subset S can be found.

As a warm-up example, consider training a single ReLU neuron $f(x; w) = \sigma(w^\top x)$ w.r.t. the correlation loss $\ell(y, \widehat{y}) = -y\widehat{y}$, from the initialization $w = [1, \ldots, 1]$. While a single neuron cannot *express* the parity, we observe that the population gradient can indicate what the correct subset is: $\mathbb{E}_{(x,y) \sim \mathcal{D}_S} [\nabla_{w_i} \ell(y, f(x; w))] = \mathbb{E}_{(x,y) \sim \mathcal{D}_S} [-y x_i \, \sigma'(w^\top x)]$ which corresponds to either the order-$(k-1)$ Fourier coefficient $S \setminus \{i\}$ of the function $x \mapsto \sigma'(w^\top x)$ (if $i \in S$ is a relevant coordinate) or the order-$(k+1)$ coefficient $S \cup \{i\}$ (if $i \notin S$ is irrelevant). When σ is the ReLU function and $w = [1, \ldots, 1]$, $\sigma'(w^\top x) = \frac{\mathrm{sign}(\sum_i x_i) + 1}{2}$ is just a shifted majority function of x. The Fourier spectrum of majority is well-understood: for even k, there is a gap between these Fourier coefficients that is detectable using $n^{O(k)}$ samples.

This analysis can be further extended to a ReLU neuron initialized with weights $w \in \{\pm 1\}^n$ and a small bias. In fact, we can show that taking a single gradient step with large enough batch size on a ReLU network trained with the hinge-loss $\ell(y, \widehat{y}) = \max\{1 - y\widehat{y}, 0\}$, already finds features that can solve the parity problem. Using this, we show that training a ReLU MLP with SGD solves the parity problem:

Theorem 4. *Fix some $\epsilon \in (0, 1)$, let k be some even number, and assume that n is some odd number satisfying $n \geq \Omega(k^4 \log(nk/\epsilon))$. There exist a symmetric random initialization scheme and learning rate and weight decay schedules s.t. for every $S \subseteq [n]$ of size k, training a ReLU MLP of size $r = O(2^k k \log(k/\epsilon))$ with batch size $B = n^{O(k)} \log^2(r/\epsilon)$ for $T = \mathrm{poly}(k, r, 1/\epsilon)$ iterations on $\mathcal{D}_S$ w.r.t. the hinge loss, finds a network $f(x; \theta_t)$ with expected loss: $\mathbb{E}[\ell(f(x; \theta_t), y)] \leq \epsilon$, where the expectation is over the randomness of initialization, training and sampling $(x, y) \sim \mathcal{D}_S$.*

The analysis presented above shows that when the *batch size* scales with $n^{O(k)}$, SGD over MLP solves the parity problem. However, in our experimental setting, the *number of steps*, and not the batch size,

---

[6]Indeed, under all standard architectures and initialization, the probability that a random network is $\Omega(1)$-correlated with a sparse parity would be $2^{-\Omega(n)}$, since with that probability $1 - o(1)$ of the total influence would be accounted by the $n - k$ irrelevant features.

scales with $n^{O(k)}$. While we believe that running SGD with small batch size and small learning rate essentially amplifies the signal in the population gradient, behaving similarly to performing a large step over a large batch size, we do not have a complete analysis for training MLPs with SGD in the small batch size regime. To complement the above result, in Section 4.2 we analyze the trajectory for a variant of the PolyNet architecture trained with gradient flow.

We note that, while the above analysis applies for ReLU MLPs with a specific initialization scheme, a similar feature emergence phenomenon can be observed in a broader set of architectures and setting. Indeed, for feature emergence to occur, we only require that there is a "gap" between the relevant and irrelevant Fourier coefficients. Formally, denote $\widehat{f}(S) := \mathbb{E}[f(x)\chi_S(x)]$ the Fourier coefficient of f at S, and observe the following definition:

Definition 1 (Fourier gap). *For some function $f : \{\pm 1\}^n \to \mathbb{R}$ and some subset S of size k, we say that f has a γ-Fourier gap at S if (1) for every $(k-1)$-element subset $S' \subseteq S$, it holds that $|\widehat{f}(S')| \geq \gamma$, and (2) for every subset $S' \subseteq [n]$ of size $k+1$ it holds that $|\widehat{f}(S')| \leq \gamma/2$.*

Now, given a network architecture where some neuron has a γ-Fourier gap with respect to the target subset S, we can generalize the result of the ReLU neuron. That is, we show that the subset S can be determined by observing an estimate of the population gradient at initialization:

Proposition 5. *Let σ be some activation function and let ℓ be some loss function. Denote $f(x; w) = \sigma(w^\top x)$. Fix some subset $S \subseteq [n]$. Let $g \in \mathbb{R}^n$ be an estimate of the population gradient such that $\left\| g - \mathbb{E}_{(x,y)\sim\mathcal{D}_S}[\nabla_w \ell(y, f(x; w))] \right\|_\infty \leq \gamma/4$. Then, for every w s.t. $\sigma'(w^\top x)$ has a γ-Fourier gap w.r.t. to S and $\ell'(f(x; w), y) = -y$ for all x, the target subset S is detected by g, namely $S = \{i \in [n] : |g_i| \geq 3\gamma/4\}$.*

Comparison with NTK analysis. In recent years, many theoretical works have studied the behavior of SGD on neural networks through the lens of the neural tangent kernel (NTK) (Jacot et al., 2018). It is therefore important to highlight the fact that the NTK (or, in fact, any kernel) cannot solve the sparse parity problem. The following result shows that no kernel can achieve small error on the sparse parity problem, unless the size of the kernel is $n^{\Omega(k)}$:

Theorem 6. *Let $\Psi : \{\pm 1\}^n \to \mathbb{R}^D$ be some D-dimensional embedding with $\sup_x \|\Psi(x)\|_2 \leq 1$, and let $R > 0$ be some number. If $DR^2 < \epsilon^2 \cdot \binom{n}{k}$, then there exists some (n, k)-parity distribution $\mathcal{D}_S$ s.t.*

$$\inf_{\|w\| \leq R} \mathbb{E}_{(x,y)\sim\mathcal{D}_S} \left[\ell(\Psi(x)^\top w, y) \right] > 1 - \epsilon.$$

The above is a corollary of the results in (Kamath et al., 2020; Malach and Shalev-Shwartz, 2022).

4.2 Disjoint-PolyNet: an idealized architecture for trajectory analyses

In this section, we present an idealized architecture (a version of PolyNets (xv)) that exhibits similar behavior to MLPs (experimentally) and is technically easier to analyze. More specifically, we consider the *disjoint-PolyNet* which takes a product over k linear functions where the linear functions are computed on k disjoint partitions of the input $P_1, \ldots, P_k$ with each $P_i = \{(i-1)n' + 1, \ldots, in'\}$ with $n' = n/k$[7], that is, $f(x; w_{1:k}) := \prod_{i=1}^k w_i^\top x_{P_i}$. As noted in the related work section, this is equivalent to a tree parity machine but with real-valued rather than ± 1 output.

In order for the disjoint-PolyNet to be able to express the class of parity problems, we assume that the set S of size k in the (n, k)-parity problem is selected such that exactly one index belongs to each disjoint partition, that is, for all $i \in [k]$, $S \cap P_i = 1$. We refer to this problem as the (n, k)-disjoint parity problem. Note that there are still $(n')^k = (n/k)^k$ different possibilities for set S under this restriction. For fixed k, these represent a constant portion of the $\binom{n}{k} \approx (ne/k)^k$ (by Stirling's approximation) possibilities for S in the general non-disjoint case.

Consider training a disjoint-PolyNet w.r.t. the correlation loss. WLOG, let $S = \{1, n'+1, \ldots, (k-1)n' + 1\}$ and $e_1 = (1, 0, ..0)$. The population gradient is non-zero at i iff $i \in S$: $g_i(w_{1:k}) = \mathbb{E}[\nabla_{w_i}\ell(f(x; w_{1:k}), y)] = -\mathbb{E}\left[y\left(\prod_{j\neq i} w_j^\top x_{P_j}\right) x_{P_i}\right] = -\left(\prod_{j\neq i} w_{j,1}\right) e_1$.

---

[7]We assume for simplicity that n is divisible by k.

Figure 4: Parity as a sandbox for understanding the effects of model size and dataset size. *Left:* Success times vs. network width r on a fixed $(40, 3)$-parity task: in accordance with the theory, parallelization experiences diminishing returns (unlike expected success times for random search, shown in green). Underparameterized models ($r = 1, 2$) were considered successful upon reaching 55% accuracy. *Right:* Training curves for an identical setup ($(50, 3)$-parity task, architecture, and training algorithm), varying only the sample size m. The two center panels display *"grokking"*: a large gap between the time to zero train error vs. zero test error.

Now we consider the gradient flow dynamics of disjoint-PolyNet, which provide a mathematically tractable case study for the trajectory of sparse parity learning. For each $i \in [k]$, in this section we treat w_i as a function from $\mathbb{R}_{\geq 0} \to \mathbb{R}^{n'}$ which satisfies the following differential equation: $\dot{w}_i = -g_i(w_{1:k}(t))$. For clarity of exposition, assume all-ones initialization.[8] Then all of the relevant weights $\{w_{i,1} : i \in [k]\}$ follow the same trajectory, which we denote by $v : \mathbb{R}_{\geq 0} \to \mathbb{R}$.

By analyzing the resulting differential equations, we can formally exhibit "phase transition"-like behavior in the fully deterministic gradient flow setting.

Theorem 7 (Gradient flow on disjoint-PolyNets). *Suppose $k \geq 3$. Let $T(.49)$ be the time it takes for error to fall below .49, and let $T(0)$ be the time it takes to reach zero error. Then*

$$\frac{T(.49)}{T(0)} = 1 - O\left((n')^{1-k/2}\right).$$

In other words, the network takes much longer to reach slightly better than trivial accuracy than it takes to go from slightly better than trivial to perfect accuracy.

We can also analyze the trajectory of disjoint-PolyNets trained with online SGD, confirming that a neural network trained with batch size 1 SGD can learn k-sparse parities within $n^{O(k)}$ iterations.

Theorem 8 (SGD on disjoint-PolyNets). *Suppose we train the disjoint-PolyNet, initialized as above, with online SGD with any batch size $B \geq 1$. Then there exists an adaptive learning rate schedule such that for any $\epsilon > 0$, with probability .99, the error falls below ϵ within*

$$\tilde{O}\left((n')^{(2k-1)} \log(1/\epsilon)\right)$$

steps.

Extended versions of these theorems, along with proofs, can be found in Appendix B.3.

5 Hidden progress: discussion and additional experiments

In this section, we advocate for sparse parities as an idealized testbed for understanding algorithms and phenomena in modern deep learning. These are accompanied by experimental vignettes which are auxiliary to the core results from Section 3, with more systematic studies deferred to future work. Details are given in Appendix D.

A progress measure for parity. To begin, the black-box experiments in Section 3 suggest that random search is the incorrect model of SGD's behavior in this setting. Using the theoretical insight

---

[8]Results for ± 1 initialization and Gaussian initialization are qualitatively similar and can be found in the Appendix.

that amplifying a precise initial population gradient suffices for learning parities, we construct one possible progress measure, which is a function of the sequence of weights $w_0, \ldots w_t \in \mathbb{R}^n$ so far: $\rho(w_{0:t}) := \|w_t - w_0\|_\infty$, using the fact that $w_t - w_0$ is an estimate for the initial population gradient in the linearized setting. Figure 3 shows how gradual weight movement (and thus, progress) can be hidden behind plateauing losses.

Roles of overparameterization vs. *oversampling*. An interesting consequence of our analysis is that it illuminates scaling behaviors with respect to a third fundamental resource parameter: *model size*, which we study in terms of network width r. If SGD operated by a "random search" mechanism, one would expect width to provide a parallel speedup. Instead, we SGD sequentially amplifies progress. The sharp lower tails in Figure 2 *(left)* imply that running r identical copies of SGD does *not* give $(1/r)\times$ speedups; more directly, in Figure 4 *(left)*, convergence times for sparse parities empirically plateau at large model sizes.

It is a significant challenge to understand the interactions between network *depth* and computation, and largely outside the scope of this work. However, in Appendix C.7, we provide a brief note on using parities and polynomial-activation MLPs to construct a simple counterexample to the *"deep only works if shallow is good"* principle of Malach and Shalev-Shwartz (2019), demonstrating a case where a deep network can get near-perfect accuracy even when greedy layerwise training (e.g. (Belilovsky et al., 2019)) cannot beat trivial performance.

Learning and grokking in the finite-sample multi-pass setting. The main theoretical and empirical results in this work consider online learning algorithms which couple the resources of training time and independent samples. However, due to the computational-statistical gap in parity learning, these positive results are suboptimal in terms of sample efficiency. We find that minibatch SGD (with weight decay) can empirically solve sparse parities, even from a sample of size $m \ll n^k$. For small values of m, we reliably observe the *grokking* phenomenon (Power et al., 2022): overfitting for a long time, then a *delayed* phase transition for the generalization error; see the two center panels of Figure 4 *(right)*.

6 Conclusion

This work puts forward parity learning as a stylized test case to explore some of the puzzling features of the role of computational (as opposed to statistical) resources in deep learning. These include discontinuous improvements (a.k.a. *emergent capabilities*), feature learning, and universality of architectures. In particular, we show that deep learning on parities exhibits a phase transition behavior, that it is successfully learned by a variety of deep-net architectures, and that this success cannot be explained as a "random exhaustive search", nor through frameworks such as the neural tangent kernel or layer-by-layer learning.

However, there are more experimental and theoretical questions, even for this simplified case of parity learning. Our focus in this work was on the online learning case, where training time and samples arise in tandem. However, we believe it would be instructive to investigate parity learning when three resources of samples, time, and model size are scaled separately. Some very preliminary findings along these lines are presented in Section 3.

Extending our theoretical results to the small-batch setting, as well as to more architectures, is an open problem. Resolving it would require a better understanding of anti-concentration (lower bound on deviation from mean) of Fourier coefficients, a phenomenon that is much less studied than the concentration of these coefficients. We would also want to extend the analysis beyond parities to tasks that are not aligned with the elementary basis such as low-rank tensor recovery.

Another important follow-up direction is understanding the extent that these insights extend from parity learning to real-world problems, as well as the extent into which non-synthetic tasks (in, e.g., natural language processing and program synthesis) embed within them parity-like subtasks of exhaustive combinatorial search.

Broader impact. This work seeks to contribute to the foundational understanding of computational scaling behaviors in deep learning. Our theoretical and empirical analyses are in a heavily-idealized synthetic problem setting. Hence, we see no direct societal impacts of the results in this study.

References

Emmanuel Abbe and Colin Sandon. Poly-time universality and limitations of deep learning. *arXiv preprint arXiv:2001.02992*, 2020.

Emmanuel Abbe, Pritish Kamath, Eran Malach, Colin Sandon, and Nathan Srebro. On the power of differentiable learning versus pac and sq learning. *Advances in Neural Information Processing Systems*, 34, 2021.

Emmanuel Abbe, Elisabetta Cornacchia, Jan Hązła, and Christopher Marquis. An initial alignment between neural network and target is needed for gradient descent to learn. *arXiv preprint arXiv:2202.12846*, 2022.

Naman Agarwal, Rohan Anil, Elad Hazan, Tomer Koren, and Cyril Zhang. Disentangling adaptive gradient methods from learning rates. *arXiv preprint arXiv:2002.11803*, 2020.

Michael Alekhnovich. More on average case vs approximation complexity. In *44th Annual IEEE Symposium on Foundations of Computer Science, 2003. Proceedings.*, pages 298–307. IEEE, 2003.

Zeyuan Allen-Zhu and Yuanzhi Li. What can resnet learn efficiently, going beyond kernels? *Advances in Neural Information Processing Systems*, 32, 2019.

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. In *International Conference on Machine Learning*, pages 242–252. PMLR, 2019.

Alexandr Andoni, Rina Panigrahy, Gregory Valiant, and Li Zhang. Learning polynomials with neural networks. In *International conference on machine learning*, pages 1908–1916. PMLR, 2014.

Benny Applebaum, David Cash, Chris Peikert, and Amit Sahai. Fast cryptographic primitives and circular-secure encryption based on hard learning problems. In *Annual International Cryptology Conference*, pages 595–618. Springer, 2009.

Benny Applebaum, Boaz Barak, and Avi Wigderson. Public-key cryptography from different assumptions. In *Proceedings of the forty-second ACM symposium on Theory of computing*, pages 171–180, 2010.

Gerard Ben Arous, Reza Gheissari, and Aukosh Jagannath. Online stochastic gradient descent on non-convex losses from high-dimensional inference. *J. Mach. Learn. Res.*, 22:106–1, 2021.

Jimmy Ba, Murat A Erdogdu, Taiji Suzuki, Zhichao Wang, Denny Wu, and Greg Yang. High-dimensional asymptotics of feature learning: How one gradient step improves the representation. *arXiv preprint arXiv:2205.01445*, 2022.

Eugene Belilovsky, Michael Eickenberg, and Edouard Oyallon. Greedy layerwise learning can scale to imagenet. In *International conference on machine learning*, pages 583–593. PMLR, 2019.

Andrew C Berry. The accuracy of the gaussian approximation to the sum of independent variates. *Transactions of the american mathematical society*, 49(1):122–136, 1941.

Andrej Bogdanov, Manuel Sabin, and Prashant Nalini Vasudevan. Xor codes and sparse learning parity with noise. *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 986–1004, 2019.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Yuan Cao, Zhiying Fang, Yue Wu, Ding-Xuan Zhou, and Quanquan Gu. Towards understanding the spectral bias of deep learning. *arXiv preprint arXiv:1912.01198*, 2019.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

Alexandru Damian, Jason Lee, and Mahdi Soltanolkotabi. Neural networks can learn representations with gradient descent. In *Conference on Learning Theory*, pages 5413–5452. PMLR, 2022.

Amit Daniely and Eran Malach. Learning parities with neural networks. *Advances in Neural Information Processing Systems*, 33:20356–20365, 2020.

Ilias Diakonikolas, Surbhi Goel, Sushrut Karmalkar, Adam R Klivans, and Mahdi Soltanolkotabi. Approximation schemes for relu regression. In *Conference on Learning Theory*, pages 1452–1485. PMLR, 2020.

Simon S Du, Xiyu Zhai, Barnabas Poczos, and Aarti Singh. Gradient descent provably optimizes over-parameterized neural networks. *arXiv preprint arXiv:1810.02054*, 2018.

Benjamin L Edelman, Surbhi Goel, Sham Kakade, and Cyril Zhang. Inductive biases and variable creation in self-attention mechanisms. *arXiv preprint arXiv:2110.10090*, 2021.

Andreas Engel and Christian Van den Broeck. *Statistical mechanics of learning*. Cambridge University Press, 2001.

Carl-Gustav Esseen. On the liapunov limit error in the theory of probability. *Ark. Mat. Astr. Fys.*, 28: 1–19, 1942.

Spencer Frei, Yuan Cao, and Quanquan Gu. Agnostic learning of a single neuron with gradient descent. *Advances in Neural Information Processing Systems*, 33:5417–5428, 2020.

Spencer Frei, Niladri S Chatterji, and Peter L Bartlett. Random feature amplification: Feature learning and generalization in neural networks. *arXiv preprint arXiv:2202.07626*, 2022.

Elizabeth Gardner and Bernard Derrida. Three unfinished works on the optimal storage capacity of networks. *Journal of Physics A: Mathematical and General*, 22(12):1983, 1989.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256. JMLR Workshop and Conference Proceedings, 2010.

Oded Goldreich and Leonid A Levin. A hard-core predicate for all one-way functions. In *Proceedings of the twenty-first annual ACM symposium on Theory of computing*, pages 25–32, 1989.

Sebastian Goldt, Madhu Advani, Andrew M Saxe, Florent Krzakala, and Lenka Zdeborová. Dynamics of stochastic gradient descent for two-layer neural networks in the teacher-student setup. *Advances in neural information processing systems*, 32, 2019.

Michael Hahn. Theoretical limitations of self-attention in neural sequence models. *Transactions of the Association for Computational Linguistics*, 8:156–171, 2020.

D Hansel, G Mato, and C Meunier. Memorization without generalization in a multilayered neural network. *EPL (Europhysics Letters)*, 20(5):471, 1992.

Godfrey Harold Hardy, John Edensor Littlewood, George Pólya, György Pólya, et al. *Inequalities*. Cambridge university press, 1952.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*, 2022.

Yuval Ishai, Eyal Kushilevitz, Rafail Ostrovsky, and Amit Sahai. Cryptography with constant computational overhead. In *Proceedings of the fortieth annual ACM symposium on Theory of computing*, pages 433–442, 2008.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *Advances in neural information processing systems*, 31, 2018.

Y Kabashima. Perfect loss of generalization due to noise in k= 2 parity machines. *Journal of Physics A: Mathematical and General*, 27(6):1917, 1994.

Pritish Kamath, Omar Montasser, and Nathan Srebro. Approximate is good enough: Probabilistic variants of dimensional and margin complexity. In *Conference on Learning Theory*, pages 2236–2262. PMLR, 2020.

Michael Kearns. Efficient noise-tolerant learning from statistical queries. *Journal of the ACM (JACM)*, 45(6):983–1006, 1998.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Adam R Klivans, Ryan O'Donnell, and Rocco A Servedio. Learning intersections and thresholds of halfspaces. *Journal of Computer and System Sciences*, 68(4):808–840, 2004.

Gillat Kol, Ran Raz, and Avishay Tal. Time-space hardness of learning sparse parities. In *Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing*, pages 1067–1080, 2017.

Eyal Kushilevitz and Yishay Mansour. Learning decision trees using the fourier spectrum. *SIAM Journal on Computing*, 22(6):1331–1348, 1993.

Beatrice Laurent and Pascal Massart. Adaptive estimation of a quadratic functional by model selection. *Annals of Statistics*, pages 1302–1338, 2000.

Kevin Lu, Aditya Grover, Pieter Abbeel, and Igor Mordatch. Pretrained transformers as universal computation engines. *arXiv preprint arXiv:2103.05247*, 2021.

Eran Malach and Shai Shalev-Shwartz. Is deeper better only when shallow is good? *Advances in Neural Information Processing Systems*, 32, 2019.

Eran Malach and Shai Shalev-Shwartz. When hardness of approximation meets hardness of learning. *Journal of Machine Learning Research*, 23(91):1–24, 2022.

Eran Malach, Pritish Kamath, Emmanuel Abbe, and Nathan Srebro. Quantifying the benefit of using differentiable learning over tangent kernels. In *International Conference on Machine Learning*, pages 7379–7389. PMLR, 2021.

GJ Mitchison and RM Durbin. Bounds on the learning capacity of some multi-layer networks. *Biological Cybernetics*, 60(5):345–365, 1989.

Ryan O'Donnell. *Analysis of boolean functions*. Cambridge University Press, 2014.

Manfred Opper. Learning and generalization in a two-layer neural network: The role of the vapnik-chervonvenkis dimension. *Physical review letters*, 72(13):2113, 1994.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

Alethea Power, Yuri Burda, Harri Edwards, Igor Babuschkin, and Vedant Misra. Grokking: Generalization beyond overfitting on small algorithmic datasets. *arXiv preprint arXiv:2201.02177*, 2022.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of neural networks. In *International Conference on Machine Learning*, pages 5301–5310. PMLR, 2019.

Maria Refinetti, Sebastian Goldt, Florent Krzakala, and Lenka Zdeborová. Classifying high-dimensional gaussian mixtures: Where kernel methods fail and neural networks succeed. In *International Conference on Machine Learning*, pages 8936–8947. PMLR, 2021.

Michal Rosen-Zvi, Einat Klein, Ido Kanter, and Wolfgang Kinzel. Mutual learning in a tree parity machine and its application to cryptography. *Physical Review E*, 66(6):066135, 2002.

David Saad and Sara Solla. Dynamics of on-line gradient descent learning for multilayer neural networks. *Advances in neural information processing systems*, 8, 1995a.

David Saad and Sara A Solla. On-line learning in soft committee machines. *Physical Review E*, 52 (4):4225, 1995b.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

Shai Shalev-Shwartz, Ohad Shamir, and Shaked Shammah. Failures of gradient-based deep learning. In *International Conference on Machine Learning*, pages 3067–3075. PMLR, 2017.

Zhenmei Shi, Junyi Wei, and Yingyu Liang. A theoretical analysis on feature learning in neural networks: Emergence from inputs and advantage over fixed features. In *International Conference on Learning Representations*, 2021.

Roberta Simonetti and Nestor Caticha. On-line learning in parity machines. *Journal of Physics A: Mathematical and General*, 29(16):4859, 1996.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Martin J Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.

Timothy LH Watkin, Albrecht Rau, and Michael Biehl. The statistical mechanics of learning a rule. *Reviews of Modern Physics*, 65(2):499, 1993.

Colin Wei, Jason D Lee, Qiang Liu, and Tengyu Ma. Regularization matters: Generalization and optimization of neural nets vs their induced kernel. *Advances in Neural Information Processing Systems*, 32, 2019.

Gilad Yehudai and Shamir Ohad. Learning a single neuron with gradient methods. In *Conference on Learning Theory*, pages 3756–3786. PMLR, 2020.

Gilad Yehudai and Ohad Shamir. On the power and limitations of random features for understanding neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Jingzhao Zhang, Sai Praneeth Karimireddy, Andreas Veit, Seungyeon Kim, Sashank Reddi, Sanjiv Kumar, and Suvrit Sra. Why are adaptive methods good for attention models? *Advances in Neural Information Processing Systems*, 33:15383–15393, 2020.