Hidden Progress in Deep Learning:
SGD Learns Parities Near the Computational Limit

Boaz Barak
Harvard University

Benjamin L. Edelman
Harvard University

Surbhi Goel
Microsoft Research &
University of Pennsylvania

Sham Kakade
Harvard University

Eran Malach
Hebrew University of Jerusalem

Cyril Zhang
Microsoft Research

b@boazbarak.org, bedelman@g.harvard.edu, surbhig@cis.upenn.edu
sham@seas.harvard.edu, eran.malach@mail.huji.ac.il, cyrilzhang@microsoft.com

Abstract

There is mounting empirical evidence of *emergent phenomena* in the capabilities of deep learning methods as we scale up datasets, model sizes, and training times. While there are some accounts of how these resources modulate statistical capacity, far less is known about their effect on the *computational* problem of model training. This work conducts such an exploration through the lens of learning k-sparse parities of n bits, a canonical family of problems which pose theoretical computational barriers. In this setting, we find that neural networks exhibit surprising phase transitions when scaling up dataset size and running time. In particular, we demonstrate empirically that with standard training, a variety of architectures learn sparse parities with $n^{O(k)}$ examples, with loss (and error) curves abruptly dropping after $n^{O(k)}$ iterations. These positive results nearly match known SQ lower bounds, even without an explicit sparsity-promoting prior. We elucidate the mechanisms of these phenomena with a theoretical analysis: we find that the phase transition in performance is *not* due to SGD "stumbling in the dark" until it finds the hidden set of features (a natural algorithm which also runs in $n^{O(k)}$ time); instead, we show that SGD gradually amplifies a *Fourier gap* in the population gradient.

1 Introduction

Neural networks perform better with more resources (data, model size, training time), but different tasks exhibit qualitatively different dependencies of performance on resources. In particular, while many learning tasks exhibit continuous improvement in performance with increasing resources, other cases show *discontinuous* improvement, where a capability emerges at a certain threshold. Through a statistical lens, it is well-understood that larger models, trained with more data, can fit more complex and expressive functions. However, far less is known about the analogous *computational* question: how does the scaling of these resources influence the success of gradient-based optimization for training these models?

These emergent *phase transitions* cannot be explained via statistical capacity alone. In many cases we see a phase transition even when the amount of data remains fixed, with only model size or training time increasing. A timely example is the emergence of reasoning and few-shot learning capabilities when scaling up language models (Radford et al., 2019; Brown et al., 2020; Chowdhery et al., 2022; Hoffmann et al., 2022); Srivastava et al. (2022) identify various tasks which language models are

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

Figure 1: Main empirical findings at a glance. A variety of neural networks, with standard training and initialization, can solve the (n, k)-parity learning problem, with a number of iterations scaling as $n^{O(k)}$. *Left:* Training curves under various algorithmic choices (architecture, batch size, learning rate) on the $(n = 50, k = 3)$-parity problem. *Right:* Median convergence times for small (n, k).

only able to solve if they are larger than a critical scale. Power et al. (2022) give examples exhibiting discontinuous improvements in population accuracy ("grokking") when running time increases, while data and model size remain fixed.

In this work, we analyze the computational aspects of scaling in deep learning in a simple synthetic setting which already exhibits discontinuous improvements. Specifically, we consider the *sparse parity learning* problem: the label is the parity (XOR) of $k \ll n$ bits in a random length-n binary string. This is a canonical problem setting which is computationally difficult for a range of algorithms, including gradient-based (Kearns, 1998) and streaming (Kol et al., 2017) algorithms. We focus on analyzing the resource measure of *training time*, and demonstrate that the loss curves for sparse parities display a phase transition across a variety of architectures and hyperparameters (see Figure 1, left). Strikingly, we observe that SGD finds the sparse subset (and hence, reaches 0 error) with a variety of activation functions and initialization schemes, even with *no* over-parameterization. These robust positive results are the starting point for our investigation.

A natural hypothesis to explain SGD's success in learning parities, with no visible progress in error and loss for most of training, would be that it simply "stumbles in the dark", performing random search for the unknown target (e.g. via stochastic gradient Langevin dynamics). If that were the case, we might expect to observe a convergence time of $2^{\Omega(n)}$, like a naive search over parameters or subsets of indices. However, Figure 1 *(right)*, already provides some evidence against this "random search" hypothesis: the convergence time is closer to an $n^{O(k)}$ scaling. Notably, such a convergence rate implies that SGD is closer to achieving the *optimal* computation time among a natural class of algorithms (namely, statistical query algorithms).

Through an extensive empirical analysis of the scaling behavior of a variety of models, as well as theoretical analysis, we give strong evidence against the "stumbling in the dark" viewpoint. Instead, there is a *hidden progress measure* under which SGD is steadily improving. Furthermore, and perhaps surprisingly, we show that SGD achieves a computational runtime much closer to the optimal SQ lower bound than simply doing (non-sparse) parameter search. More generally, our investigations reveal a number of notable phenomena regarding the dependence of SGD's performance on resources: we identify phase transitions when varying data, model size, and training time.

1.1 Our contributions

SGD learns sparse parities. It is known from SQ lower bounds that with a constant noise level, gradient descent on *any* architecture requires at least $n^{\Omega(k)}$ computational steps to learn k-sparse n-dimensional parities (for background, see Appendix A). We first show a wide variety of positive empirical results, in which neural networks successfully solve the parity problem in a number of iterations which scales near this computational limit:

Empirical Finding 1. *For all small instances ($n \leq 30, k \leq 4$) of the sparse parity problem, architectures $\mathcal{A} \in \{$2-layer MLPs, Transformers[1], sinusoidal (and other non-standard) neurons, PolyNets[2]$\}$, initializations in $\{$uniform, Gaussian, Bernoulli$\}$, and batch sizes $1 \leq B \leq 1024$, SGD on $\mathcal{A}$ solves the (n, k)-sparse parity problem (w.p. ≥ 0.2) within at most $c \cdot n^{\alpha k}$ steps, for small architecture-dependent constants c, α.*

For a subset of these architectures, we performed more extensive training, to show scaling behaviors of the computation time[3]; see Figure 1 *(right)* and Figure 10 in the appendix.

The above results indicate that SGD succeeds at solving parities much faster than the $2^{\Omega(n)}$ steps that would be required by random search without a sparse prior. This suggests that despite flat loss and accuracy curves before the phase transition, SGD makes progress "under the hood". We show that this is indeed the case by coming up with *hidden progress measures*: functions of the training algorithm's state which are predictive of the time to convergence and continuously improve throughout training, despite the uninformativeness of the loss and accuracy curves.

Theoretical analyses of sparse feature emergence. Our empirical results suggest that, in a number of computational steps matching the SQ limit, SGD is able to solve the parity problem and identify the influential coordinates, without an explicit sparse prior. We give a theoretical analysis which validates this claim.

Informal Theorem 2. *On 2-layer MLPs of width $2^{\Theta(k)}$, and with batch size $n^{O(k)}$, SGD converges with high probability to a solution with at most ϵ error on the (n, k)-parity problem in at most $2^{O(k)} \cdot \mathrm{poly}(1/\epsilon)$ iterations.*

We also present a stronger analysis for an idealized architecture (which we call the *disjoint-PolyNet*), which allows for any batch size, and captures the phase transitions observed in the error curves.

Informal Theorem 3. *On disjoint-PolyNets, SGD (with any batch size $B \geq 1$) converges with high probability to a solution with at most ϵ error on the (n, k)-parity problem in at most $n^{O(k)} \cdot \log(1/\epsilon)$ iterations. Continuous-time gradient flow exhibits a phase transition: it spends a $1 - o(1)$ fraction of its time before convergence with error $\geq 49\%$.*

Our theoretical and empirical results hold in non-overparameterized regimes (including with a width-1 sinusoidal neuron), in which no fixed kernel, including the neural tangent kernel (NTK) (Jacot et al., 2018), is sufficiently expressive to fit all sparse parities with a large margin. Thus, our findings comprise an elementary example of *combinatorial feature learning*: SGD can only successfully converge by identifying the relevant features.

Further empirical explorations. Building upon our core positive results, we provide a wide variety of preliminary experiments, showing sparse parity learning to be a versatile testbed for understanding the challenges and surprises in solving combinatorial problems with neural networks. This includes experiments at small sample sizes which exhibit *grokking* (Power et al., 2022), as well as a counterexample to the *"deep only works if shallow is good"* principle of Malach and Shalev-Shwartz (2019).

1.2 Related work

We present the most directly related work on feature learning, and learning parities with neural nets. A broader discussion can be found in Appendix A.3.

SGD and feature learning. Theoretical analysis of gradient descent over neural networks is notoriously hard, due to the non-convex nature of the optimization problem. That said, it has been established that in some settings, the dynamics of GD keep the weights close to their initialization, thus behaving like convex optimization over the Neural Tangent Kernel (see, for example, Jacot et al. (2018); Allen-Zhu et al. (2019); Du et al. (2018)). In contrast, it has been shown that in various tasks, moving away from the fixed features of the NTK is essential for the success of neural networks trained

---

[1]With a smaller range of hyperparameters.

[2]A non-standard architecture introduced in this work; see Section 3 for the definition.

[3]While our focus is on the performance as a function of *training time*, we also performed some experiments on performance as a function of *model size*, see Section 5.

with GD (for example Yehudai and Shamir (2019); Allen-Zhu and Li (2019); Wei et al. (2019) and the review in Malach et al. (2021)). These results demonstrate that feature learning is an important part of the GD optimization process. Our work also focuses on a setting where feature learning is essential for the target task. In our theoretical analysis, we show that the initial population gradient encodes the relevant features for the problem. The importance of the first gradient step for feature learning has been recently studied in (Ba et al., 2022).

Learning parities with neural networks. The problem of learning parities using neural networks has been investigated in prior works from various perspectives. It has been demonstrated that parities are hard for gradient-based algorithms, using similar arguments as in the SQ analysis (Shalev-Shwartz et al., 2017; Abbe and Sandon, 2020). One possible approach for overcoming the computational hardness is to make favorable assumptions on the input distribution. Indeed, recent works show that under various assumptions on the input distribution, neural networks can be efficiently trained to learn parities (XORs) (Daniely and Malach, 2020; Shi et al., 2021; Frei et al., 2022; Malach et al., 2021). In contrast to these results, this work takes the approach of intentionally focusing on a hard benchmark task, without assuming that the distribution has some favorable (namely, non-uniform) structure. This setting allows us to probe the performance of deep learning at a known computational limit. Notably, the work of Andoni et al. (2014) provides analysis for learning polynomials (and in particular, parities) under the uniform distribution. However, their main results require a network of size $n^{O(k)}$ (i.e., extremely overparameterized network), and provides only partial theoretical and empirical evidence for the success of smaller networks. Studying a related subject, some works have shown that neural networks display a spectral bias, learning to fit low-frequency coefficients before high-frequency ones (Rahaman et al., 2019; Cao et al., 2019).

2   Preliminaries

We provide an expanded discussion of background and related work in Appendix A.

Sparse parities. For integer $n \geq 1$ and non-empty set $S \subseteq [n]$, the (n, S)-*parity function* $\chi_S : \{\pm 1\}^n \to \{\pm 1\}$ is defined as $\chi_S(x) = \prod_{i \in S} x_i$. We define the (n, S)-*parity distribution* $\mathcal{D}_S$ as the joint distribution over $(x, y)^4$ where x is drawn from $\mathrm{Unif}(\{\pm 1\}^n)$, the uniform distribution over random length-n sign vectors, and $y := \chi_S(x)$ is the product of the inputs at the indices given by the "relevant features" S (thus, ± 1, depending on whether the number of relevant -1 inputs is even or odd). We define the (n, k)-*parity learning problem* as the task of recovering the S using samples from $\mathcal{D}_S$, where S is chosen at random from $\binom{[n]}{k}$.

A key fact about parities is that they are orthogonal under the correlation inner product: for $S' \subseteq [n]$,

$$\mathbb{E}_{x \sim \mathrm{Unif}(\{\pm 1\}^n)} [\chi_S(x)\chi_{S'}(x)] = \mathbb{E}_{(x,y) \sim \mathcal{D}_S} [\chi_{S'}(x)\, y] = \begin{cases} 1 & S' = S \\ 0 & \text{otherwise} \end{cases}.$$

That is, a learner who guesses indices S' cannot use correlations (equivalently, the accuracy of the hypothesis $\chi_{S'}$) as feedback to reveal which indices in S' are correct, unless S' is *exactly* the correct subset. This notion of indistinguishability leads to a *computational* lower bound in the statistical query (SQ) model (Kearns, 1998): $\Omega(n^k)$ constant-noise queries are necessary, which is far greater than the statistical limit of $\Theta(\log \binom{n}{k}) \approx k \log n$ samples. The hardness of parity has been used to derive computational hardness results for other settings, like agnostically learning halfspaces (Klivans and Kothari, 2014) and MLPs (Goel et al., 2019). Beyond the restricted computational model of statistical queries, noiseless parities can be learned in $\mathrm{poly}(n)$ time via Gaussian elimination. However, learning sparse *noisy* parities, even at a very small noise level (i.e., $o(1)$ or $n^{-\delta}$), is believed to inherently require $n^{\Omega(k)}$ computational steps.[5] In all, learning sparse parities is an emblematic combinatorial problem which exemplifies the computational difficulty of learning a joint dependence on multiple relevant features.

Notation for neural networks and training. Our main results are presented in the *online learning* setting, with a stream of i.i.d. batches of examples. At each iteration $t = 1, \ldots, T$, a learning

---

[4]Our theoretical analyses and experiments can tolerate noisy parities, that is, random flipping of the label; see Appendix C.6. For ease of presentation, we state the noiseless setting in the main paper.

[5]This was first explicitly conjectured by Alekhnovich (2003), and has been the basis for several cryptographic schemes (e.g., (Ishai et al., 2008; Applebaum et al., 2009, 2010; Bogdanov et al., 2019)).

Figure 2: Black-box observations on the training dynamics. *Left:* Histograms of convergence times over 10^6 random trials, with heavy upper tails but no observed successes near $t = 0$ (unlike random search). *Center:* Loss curves (and thus, convergence time) depend heavily on initialization, not the randomness of SGD; $B = 128, \eta = 0.01$ are shown here. *Right:* The power-law exponent (α such that $t_c \propto n^\alpha$) eventually worsens on larger problem instances.

algorithm $\mathcal{A}$ receives a batch of B examples $\{(x_{t,i}, y_{t,i})\}_{i=1}^B$ drawn i.i.d. from $\mathcal{D}_S$, then outputs a classifier $\widehat{y}_t : \{\pm 1\}^n \to \{\pm 1\}$. We say that $\mathcal{A}$ solves the parity task in t steps (with error ϵ) if

$$\Pr_{(x,y)\sim\mathcal{D}_S}[\widehat{y}_t(x) = y] \geq 1 - \epsilon.$$

We will focus on the case that $\widehat{y}_t = \mathrm{sign}(f(x; \theta_t))$ for some parameters θ_t in a continuous domain Θ and for a continuous function $f : \{\pm 1\}^n \times \Theta \to \mathbb{R}^6$, updated with the ubiquitous online learning algorithm of gradient descent (GD), whose update rule is given by

$$\theta_{t+1} \leftarrow (1 - \lambda_t)\theta_t - \eta_t \cdot \nabla_\theta \left(\frac{1}{B} \sum_{i=1}^B \ell(y_{t,i}, f(x_{t,i}; \theta_t)) \right), \tag{1}$$

for a loss function $\ell : \{\pm 1\} \times \mathbb{R} \to \mathbb{R}$, learning rate schedule $\{\eta_t\}_{t=1}^T$, and weight decay schedule $\{\lambda_t\}_{t=1}^T$ [7]. The initialization θ_0 is drawn randomly from a chosen distribution.

3 Empirical findings

3.1 SGD on neural networks learns sparse parities

The central phenomenon of study in this work is the empirical observation that neural networks, with standard initialization and training, can solve the (n, k)-parity problem in a number of iterations scaling as $n^{O(k)}$ on small instances. We observed robust positive results for randomly-initialized SGD on the following architectures, indexed by Roman numerals:

- *2-layer MLPs:* ReLU ($\sigma(z) = (z)_+$) or polynomial ($\sigma(z) = z^k$) activation, in a wide variety of width regimes $r \geq k$. Settings (i), (ii), (iii) (resp. (iv), (v), (vi)) use $r = \{10, 100, 1000\}$ ReLU (resp. polynomial) activations. We also consider $r = k$ (exceptional settings (*i), (*ii)), the minimum width for representing a k-wise parity for both activations.
- *Single neurons:* Next, we consider non-standard activation functions σ which allow a one-neuron architecture $f(x; w) = \sigma(w^\top x)$ to realize k-wise parities. The constructions stem from letting $w^* = \sum_{i \in S} e_i$, and constructing $\sigma(\cdot)$ to interpolate (the appropriate scaling of) $\frac{k - w^{*\top} x}{2}$ mod 2 with a piecewise linear k-*zigzag* activation (vii), or a degree-k polynomial (viii). Going a step further, a single ∞-*zigzag* (ix) or *sinusoidal* (x) neuron can represent *all* k-wise parities. We also removed the second trainable layer (setting $u = 1$), obtaining settings (xi), (xii), (xiii), (xiv). We found that wider architectures with these activations also trained successfully.
- *Transformers:* There is growing interest in using parity as a benchmark for combinatorial function learning, long-range dependency learning, and length generalization in Transformers (Lu et al., 2021; Edelman et al., 2021; Hahn, 2020; Anil et al., 2022). Motivated by these recent theoretical

---

[6]When $f(x; \theta) = 0$ in practice (e.g. with sign initialization), we break the tie arbitrarily. We ensure in the theoretical analysis that this does not happen.

[7]We allow different layers to have different learning rate and weight decay schedules.

and empirical works, we consider a simplified specialization of the Transformer architecture to this sequence classification problem. This is the less-robust setting (*iii); the architecture and optimizer are described in Appendix D.1.3.

- *PolyNets:* Our final setting (xv) is the PolyNet, a slightly modified version of the parity machine architecture. Parity machines have been studied extensively in the statistical mechanics of ML literature (see the related work section) as well as in a line of work on 'neural cryptography' (Rosen-Zvi et al., 2002). A parity machine outputs the sign of the product of k linear functions of the input. A PolyNet simply outputs the product itself. Both architectures can clearly realize k-sparse parities. The PolyNet architecture was originally motivated by the search for an idealized setting where an end-to-end optimization trajectory analysis is tractable (see Section 4.1); we found in these experiments that this architecture trains very stably and sample-efficiently.

Robust space of positive results. All of the networks listed above were observed to successfully learn sparse parities in a variety of settings. We summarize our findings as follows: for all combinations of $n \in \{10, 20, 30\}$, $k \in \{2, 3, 4\}$, batch sizes $B \in \{1, 2, 4, \dots, 1024\}$, initializations {uniform, Gaussian, Bernoulli}, loss functions {hinge, square, cross entropy}, and architecture configurations $\{(i), (ii), \dots, (xv)\}$, SGD solved the parity problem (with 100% accuracy, validated on a batch of 2^{13} samples) in at least 20% of 25 random trials, for at least one choice of learning rate $\eta \in \{0.001, 0.01, 0.1, 1\}$. The models converged in $t_c \leq c \cdot n^{\alpha k} \leq 10^5$ steps, for small architecture-dependent constants c, α (see Appendix C). Figure 1 *(left)* shows some representative training curves.

Less robust configurations. Settings (*i) and (*ii), where the MLP just barely represents a k-sparse parity, and the Transformer setting (*iii), are less robust to small batch sizes. In these settings, the same positive results as above only held for sufficiently large batch sizes: $B \geq 16$. Also, setting (*iii) used the Adam optimizer (which is standard for Transformers); see Appendix D.1.3 for details.

Phase transitions in training curves. For almost all of the architectures, we find that that the training curves exhibit phase transitions in terms of running time (and thus, in the online learning setting, dataset size as well): long durations of seemingly no progress, followed by periods of rapid decrease in the validation error. Strikingly, for architectures (v) and (vi), this plateau is absent: the error in the initial phase appears to decrease with a linear slope. See Appendix C.8 for more plots.

3.2 Random search or hidden progress?

The remainder of this paper seeks to answer the question: *"By what mechanism does deep learning solve these emblematic computationally-hard optimization problems?"*

A natural hypothesis would be that SGD somehow implicitly performs Monte Carlo random search, "bouncing around" the loss landscape in the absence of a useful gradient signal. Upon closer inspection, several empirical observations clash with this hypothesis:

- *Scaling of convergence times:* Without an explicit sparsity prior in the architecture or initialization, it is unclear how to account for the runtimes observed in experiments, which adapt to the sparsity k. The initializations, which certainly do not prefer sparse functions[8], are close to the correct solutions with probability $2^{-\Omega(n)} \ll n^{-k}$.
- *No early convergence:* Over a large number of random trials, no copies of this randomized algorithm get "lucky" (i.e. solve the problem in significantly fewer than the median number of iterations); see Figure 2 *(left)*. The success times of random exhaustive search would be distributed as $\text{Geom}(1/\binom{n}{k})$, whose probability mass is highest at $t = 0$ and decreases monotonically with t.
- *Sensitivity to initialization, not stochastic batches:* Running these training setups over multiple stochastic batches from a common initialization, we find that loss curves and convergence times are highly correlated with the architecture's random initialization, and are quite concentrated conditioned on initialization; see Figure 2 *(center)*.
- *Elbows in the scaling curves:* For larger n, the power-law scaling ceases to hold: the exponent worsens (see Figure 2 *(right)*, as well as the discussion in Appendix C.2). This would not be true for random exhaustive search.

---

[8]Indeed, under all standard architectures and initialization, the probability that a random network is $\Omega(1)$-correlated with a sparse parity would be $2^{-\Omega(n)}$, since with that probability $1 - o(1)$ of the total influence would be accounted by the $n - k$ irrelevant features.

Figure 3: Hidden progress when learning parities with neural networks. *Left, center:* Black-box losses and accuracies exhibit a long plateau and sharp phase transition (top), hiding gradual progress in the SGD iterates (bottom). *Right:* A hidden progress measure which distinguishes gradual feature amplification (top) from training on noise (bottom).

Even these observations, which do not probe the internal state of the algorithm, suggest that exhaustive search is an insufficient picture of the training dynamics, and a different mechanism is at play.

4 Theoretical analyses

4.1 Provable emergence of the parity indices in high-precision gradients

We now provide a theoretical account for the success of SGD in solving the (n, k)-parity problem. Our main theoretical observation is that, in many cases, the *population* gradient of the weights at initialization contains enough "information" for solving the parity problem. That is, given an accurate enough estimate of the initial gradient (by e.g. computing the gradient over a large enough batch size), the relevant subset S can be found.

As a warm-up example, consider training a single ReLU neuron $\widehat{y}(x; w) = (w^\top x)_+$ with the correlation loss $\ell(y, \widehat{y}) = -y\widehat{y}$ over $\mathcal{D}_S$, from an all-ones initialization $w = [1 \ \ldots \ 1] \in \mathbb{R}^n$. While a single neuron cannot *express* the parity, we observe that the correct subset can be extracted from the population gradient at initialization:

$$\mathbb{E}_{(x,y)\sim\mathcal{D}_S} \left[\nabla_{w_i}\ell(y, \widehat{y}(x; w))\right] = \mathbb{E}_{(x,y)\sim\mathcal{D}_S} \left[-y\,\nabla_{w_i}(w^\top x)_+\right] = \mathbb{E}_{(x,y)\sim\mathcal{D}_S} \left[-\chi_S x_i \mathbb{1}\left[\sum_i x_i \geq 0\right]\right].$$

The key insight is that each coordinate in the above expression is a correlation between a parity and the function $x \mapsto -\mathbb{1}[\sum_i x_i \geq 0]$, and thus a Fourier coefficient of this Boolean function. At each relevant coordinate ($i \in S$), the population gradient is the order-$(k-1)$ Fourier coefficient $S \setminus \{i\}$; for the irrelevant features ($i \notin S$), it is instead the order-$(k+1)$ coefficient $S \cup \{i\}$. All we require is a detectable *gap* between these quantities. Formally, letting $f(x; w) = \sigma(w^\top x)$, letting $\widehat{f}(S) := \mathbb{E}[f(x)\chi_S(x)]$ denote the Fourier coefficient of f at S, we isolate the desired property:

Definition 1 (Fourier gap). *For a function $f : \{\pm 1\}^n \to \mathbb{R}$ and $S \subseteq [n]$ of size k, we say that f has a γ-Fourier gap at S if, for every $(k-1)$-element subset $S^- \subset S$ and $(k+1)$-element superset $S^+ \supset S$, it holds that $|\widehat{f}(S^-)| \geq |\widehat{f}(S^+)| + \gamma$.*

For the all-ones initialization, observe $\mathbb{1}[\sum_i x_i \geq 0] = \frac{1+\text{sign}(\sum_i x_i)}{2}$ is just an affine transformation of the majority function of x, for which a Fourier gap can be established, with $\gamma = \Theta(n^{-(k-1)/2})$. This arises from closed-form formulas for the Fourier spectrum of majority (see Lemma 2 in Appendix B.1), a landmark result from the harmonic analysis of Boolean functions (Titsworth, 1962; O'Donnell, 2014). Thus, the coordinates in S can be recovered from $\widetilde{O}(1/\gamma^2) = \widetilde{O}(n^{k-1})$ samples; see Proposition 10 in Appendix B.2 for a formal argument.

Carefully extending this insight, we obtain an end-to-end convergence result for ReLU-activation MLP networks with a particular symmetric choice of ± 1 initialization, trained with the hinge loss:

Theorem 4 (SGD on MLPs learns sparse parities). *Let $\epsilon \in (0,1)$. Let $k \geq 2$ an even integer, and let $n = \Omega(k^4 \log(nk/\epsilon))$ be an odd integer. Then, there exist a random initialization scheme, η_t, and λ_t such that for every $S \subseteq [n]$ of size k, SGD on a ReLU MLP of width $r = \Omega(2^k k \log(k/\epsilon))$, with batch size $B = \Omega(n^k \log(n/\epsilon))$ on $\mathcal{D}_S$ with the hinge loss, outputs a network $f(x; \theta_t)$ with expected[9] loss $\mathbb{E}\left[\ell(f(x; \theta_t), y)\right] \leq \epsilon$ in at most $O(k^3 r^2 n/\epsilon^2)$ iterations.*

This does not capture the full range of settings in which we empirically observe successful convergence. First, it requires a sign vector initialization, while we observe convergence with other random initialization schemes (namely, uniform and Gaussian). Second, it requires the batch size to scale with $n^{\Omega(k)}$[10], while we also obtain positive results when B is small (even $B = 1$). Understanding these cases (as well as other activations and losses) requires us to establish Fourier gaps for population gradient functions other than majority; lower bounds on the degree-$(k-1)$ coefficients (*"Fourier anti-concentration"*) are particularly elusive in the literature, and we leave it as an open challenge to establish them in more general settings. We provide preliminary empirics in Appendix C.1, suggesting that our empirical setups exhibit large Fourier gaps.[11]

Comparison with NTK analysis. In recent years, many theoretical works have studied the behavior of SGD on neural networks through the lens of the neural tangent kernel (NTK) (Jacot et al., 2018). It is therefore important to highlight the fact that the NTK (or, in fact, any kernel) cannot solve the sparse parity problem in the low-width (non-overparameterized) regimes considered in this work. The following result (see (Kamath et al., 2020; Malach and Shalev-Shwartz, 2022)) shows that no kernel can achieve small error on the sparse parity problem, unless the dimensionality of its feature space (in the case of NTK, the network's parameter count) is $n^{\Omega(k)}$:

Theorem 5 (Low-width NTK cannot fit parity). *Let $\Psi : \{\pm 1\}^n \to \mathbb{R}^D$ be some D-dimensional embedding with $\sup_x \|\Psi(x)\|_2 \leq 1$, and let $R, \epsilon > 0$. If $DR^2 < \epsilon^2 \cdot \binom{n}{k}$, then there exists some $S \subseteq [n]$ of size k such that*

$$\inf_{\|w\| \leq R} \mathbb{E}_{(x,y) \sim \mathcal{D}_S} \left[\ell(\Psi(x)^\top w, y)\right] > 1 - \epsilon.$$

4.2 Disjoint-PolyNet: an idealized architecture for trajectory analyses

In this section, we present an idealized architecture (a version of PolyNets (xv)) that exhibits similar behavior to MLPs (experimentally) and is technically easier to analyze. The *disjoint-PolyNet* takes a product over k linear functions of disjoint partitions of the input $P_1, \ldots, P_k$ with each $P_i = \{(i-1)n' + 1, \ldots, in'\}$ with $n' = n/k$[12], that is, $f(x; w_{1:k}) := \prod_{i=1}^k \langle w_i, x_{P_i} \rangle$. As noted in the Section 1.2, this is equivalent to a tree parity machine, but with real-valued rather than ± 1 output.

In order for the disjoint-PolyNet to be able to express the class of parity problems, we assume that the set S of size k in the (n, k)-parity problem is selected such that exactly one index belongs to each disjoint partition, that is, for all $i \in [k]$, $S \cap P_i = 1$. We refer to this problem as the (n, k)-disjoint parity problem. Note that there are still $(n')^k = (n/k)^k$ different possibilities for set S under this restriction. For fixed k, these represent a constant portion of the $\binom{n}{k} \approx (ne/k)^k$ (by Stirling's approximation) possibilities for S in the general non-disjoint case.

Consider training a disjoint-PolyNet w.r.t. the correlation loss. Without loss of generality, assume $S = \{1, 1 + n', \ldots, 1 + (k-1)n'\}$. The population gradient is non-zero only at indices $i \in S$:

$$g_i(w_{1:k}) = \mathbb{E}\left[\nabla_{w_i} \ell(f(x; w_{1:k}), y)\right] = -\mathbb{E}\left[y \left(\prod_{j \neq i} \langle w_j, x_{P_j}\rangle\right) x_{P_i}\right] = -\left(\prod_{j \neq i} w_{j,1}\right) e_1.$$

This allows us to analyze the gradient flow dynamics of the disjoint-PolyNet, without needing to establish Fourier gaps. For each $i \in [k]$, in this section we treat w_i as a function from $\mathbb{R}_{\geq 0} \to \mathbb{R}^{n'}$

---

[9]The expectation is over the randomness of initialization, training and sampling $(x, y) \sim \mathcal{D}_S$.

[10]In fact, at this batch size, the correct parity indices emerge in a single SGD step.

[11]Interestingly, we observe that the Fourier gap tends to *increase* over the course of training. This is not captured by our current theoretical analysis.

[12]We assume for simplicity that n is divisible by k.

Figure 4: Parity as a sandbox for understanding the effects of model size and dataset size. *Left:* Success times vs. network width r on a fixed $(40, 3)$-parity task: in accordance with the theory, parallelization experiences diminishing returns (unlike expected success times for random search, shown in green). Underparameterized models ($r = 1, 2$) were considered successful upon reaching 55% accuracy. *Right:* Training curves where only the sample size m is varied. The two center panels display *"grokking"*: a large gap between the time to zero train error vs. zero test error.

which satisfies the following differential equation: $\dot{w}_i = -g_i(w_{1:k}(t))$. For clarity of exposition, assume all-ones initialization.[13] Then, all of the relevant weights $\{w_{i,1} : i \in [k]\}$ follow the same trajectory. By analyzing the resulting differential equations, we can formally exhibit "phase transition"-like behavior in the fully deterministic gradient flow setting.

Theorem 6 (Loss plateau for gradient flow on disjoint-PolyNets)**.** *Suppose $k \geq 3$. Let $T(\epsilon)$ denote the smallest time at which the error is at most ϵ. Then,*

$$\frac{T(0.49)}{T(0)} \geq 1 - O\left((n')^{1-k/2}\right).$$

In other words, the network takes much longer to reach slightly better than trivial accuracy than it takes to go from slightly better than trivial to perfect accuracy.

Back in discrete time, we can also analyze the trajectory of disjoint-PolyNets trained with online SGD at any batch size, confirming that a neural network can learn k-sparse disjoint parities within $n^{O(k)}$ iterations.

Theorem 7 (SGD on disjoint-PolyNets learns disjoint parities)**.** *Suppose we train a disjoint-PolyNet, initialized as above, with online SGD. Then there exists an adaptive learning rate schedule such that for any $\epsilon > 0$, with probability 0.99, the error falls below ϵ within $\tilde{O}\left((n')^{(2k-1)} \log(1/\epsilon)\right)$ steps.*

Extended versions of these theorems, along with proofs, can be found in Appendix B.3.

5 Hidden progress: discussion and additional experiments

We advocate for sparse parities as an idealized testbed for understanding the dynamics of neural network training in combinatorial settings. In Appendix C, we provide an assortment of preliminary experiments in this direction, which are auxiliary to the core results from Section 3; more systematic investigations are deferred to future work. We highlight some of these findings below.

Hidden progress measures for learning parities. The theoretical and (black-box) empirical results suggest that SGD does *not* learn parities via the memoryless process of random exhaustive search. This suggests the existence of *progress measures*: quantities which are functions of the training algorithm's state (i.e. the model weights w_t) and are predictive of the time to successful convergence. We provide some *white-box* investigations which further support the hypothesis of hidden progress, by examining the gradual improvement in quantities other than the training loss. In Appendix C.1, we directly plot the Fourier gaps of the population gradient, as a function of t, finding that they are large (within a small constant factor of those of majority) in practice. In Figure 3 and Appendix C.3, we examine the weight movement norm $\rho(w_{0:t}) := \|w_t - w_0\|_\infty$ to reveal hidden progress, motivated by the fact that $w_t - w_0$ is a linearized estimate for the initial population gradient.

Roles of overparameterization vs. oversampling. An interesting consequence of our analysis is that it illuminates scaling behaviors with respect to a third fundamental resource parameter: *model size*,

---

[13]Results for Bernoulli and Gaussian initializations are similar, and can be found in the appendix.

which we study in terms of network width r. If SGD operated by a "random search" mechanism, one would expect width to provide a parallel speedup. Instead, we SGD sequentially amplifies progress. The sharp lower tails in Figure 2 *(left)* imply that running r identical copies of SGD does *not* give $(1/r)\times$ speedups; more directly, in Appendix C.4 (previewed in Figure 4 *(left)*), we find that convergence times for sparse parities empirically plateau at large model sizes.

Emergence of grokking in the finite-sample (multi-pass) setting. Our main results are presented in the *online learning* setting (fresh minibatches from $\mathcal{D}_S$ at each iteration). While this mitigates the confounding factor of overfitting, it couples the resources of training time and independent samples in a suboptimal way, due to the computational-statistical gap for parity learning. In Appendix C.5, we find empirically that minibatch SGD (with weight decay) can learn sparse parities, even with smaller sample sizes $m \ll n^k$. We reliably observe the *grokking* phenomenon (Power et al., 2022): an initial overfitting phase, then a *delayed* phase transition in the generalization error; see the two center panels of Figure 4 *(right)*. These results complement and corroborate the findings of Nanda and Lieberum (2022), who analyze the hidden progress of Transformers trained on arithmetic tasks (a setting which also exhibits grokking).

Deeper networks. It is a significant challenge (and generally outside the scope of this work) to understand the interactions between network *depth* and computational/statistical efficiency. In Appendix C.7, we use the parity setting and polynomial-activation MLPs to create a simple counterexample to the *"deep only works if shallow is good"* principle of Malach and Shalev-Shwartz (2019), demonstrating a case where a deep network can get near-perfect accuracy even when greedy layerwise training (e.g. (Belilovsky et al., 2019)) cannot beat trivial performance. By providing positive theory and empirics which elude these simplified explanations of SGD, we hope to point the way to a more complete understanding of learning dynamics in the challenging cases where no apparent progress is made for extended periods of time.

6   Conclusion

This work puts forward sparse parity learning as an elementary test case to explore the puzzling features of the role of computational (as opposed to statistical) resources in deep learning. In particular, we have shown that a variety of neural architectures solve this combinatorial search problem, with a number of computational steps scaling near the sparsity-dependent SQ lower bound; furthermore, the loss curves exhibit *phase transitions*. This success cannot be explained by a model of random exhaustive search, nor through simplified frameworks such as the neural tangent kernel or layer-by-layer learning.

Even in this simple setting, there are several open experimental and theoretical questions. Our focus in this work was on the online learning case, where training time and samples arise in tandem. We believe it would be instructive to investigate parity learning when three resources of samples, time, and model size are scaled separately. Some very preliminary findings along these lines are presented in Section 3. Extending our theoretical results to the small-batch setting, as well as to more architectures, is an open problem. Resolving it would require a better understanding of anti-concentration of Fourier coefficients, a phenomenon that is much less studied than the concentration of these coefficients.

Another important follow-up direction is understanding the extent to which these insights extend from parity learning to more complex (including real-world) combinatorial problem settings, as well as the extent to which non-synthetic tasks (in, e.g., natural language processing and program synthesis) embed within them parity-like subtasks of exhaustive combinatorial search. We hope that our results will lead to further progress towards understanding and improving the optimization dynamics behind the recent slew of dramatic empirical successes of deep learning in these types of domains.

Broader impact. This work seeks to contribute to the foundational understanding of computational scaling behaviors in deep learning. Our theoretical and empirical analyses are in a heavily-idealized synthetic problem setting. Hence, we see no direct societal impacts of the results in this study.

Acknowledgements. We would like to thank Lenka Zdeborová for providing us with references to the statistical physics literature on phase transitions in the learning curves of neural networks. Sham Kakade acknowledges funding from the Office of Naval Research under award N00014-22-1-2377.

References

Emmanuel Abbe and Colin Sandon. Poly-time universality and limitations of deep learning. *arXiv preprint arXiv:2001.02992*, 2020.

Emmanuel Abbe, Pritish Kamath, Eran Malach, Colin Sandon, and Nathan Srebro. On the power of differentiable learning versus PAC and SQ learning. *Advances in Neural Information Processing Systems*, 34, 2021.

Emmanuel Abbe, Elisabetta Cornacchia, Jan Hązła, and Christopher Marquis. An initial alignment between neural network and target is needed for gradient descent to learn. *arXiv preprint arXiv:2202.12846*, 2022.

Naman Agarwal, Rohan Anil, Elad Hazan, Tomer Koren, and Cyril Zhang. Disentangling adaptive gradient methods from learning rates. *arXiv preprint arXiv:2002.11803*, 2020.

Michael Alekhnovich. More on average case vs approximation complexity. In *44th Annual IEEE Symposium on Foundations of Computer Science, 2003. Proceedings.*, pages 298–307. IEEE, 2003.

Zeyuan Allen-Zhu and Yuanzhi Li. What can ResNet learn efficiently, going beyond kernels? *Advances in Neural Information Processing Systems*, 32, 2019.

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. In *International Conference on Machine Learning*, pages 242–252. PMLR, 2019.

Alexandr Andoni, Rina Panigrahy, Gregory Valiant, and Li Zhang. Learning polynomials with neural networks. In *International Conference on Machine Learning*, pages 1908–1916. PMLR, 2014.

Cem Anil, Yuhuai Wu, Anders Andreassen, Aitor Lewkowycz, Vedant Misra, Vinay Ramasesh, Ambrose Slone, Guy Gur-Ari, Ethan Dyer, and Behnam Neyshabur. Exploring length generalization in large language models. *arXiv preprint arXiv:2207.04901*, 2022.

Benny Applebaum, David Cash, Chris Peikert, and Amit Sahai. Fast cryptographic primitives and circular-secure encryption based on hard learning problems. In *Annual International Cryptology Conference*, pages 595–618. Springer, 2009.

Benny Applebaum, Boaz Barak, and Avi Wigderson. Public-key cryptography from different assumptions. In *Proceedings of the forty-second ACM symposium on Theory of computing*, pages 171–180, 2010.

Gerard Ben Arous, Reza Gheissari, and Aukosh Jagannath. Online stochastic gradient descent on non-convex losses from high-dimensional inference. *J. Mach. Learn. Res.*, 22:106–1, 2021.

Jimmy Ba, Murat A Erdogdu, Taiji Suzuki, Zhichao Wang, Denny Wu, and Greg Yang. High-dimensional asymptotics of feature learning: How one gradient step improves the representation. *arXiv preprint arXiv:2205.01445*, 2022.

Eugene Belilovsky, Michael Eickenberg, and Edouard Oyallon. Greedy layerwise learning can scale to imagenet. In *International conference on machine learning*, pages 583–593. PMLR, 2019.

Andrew C Berry. The accuracy of the gaussian approximation to the sum of independent variates. *Transactions of the American Mathematical Society*, 49(1):122–136, 1941.

Andrej Bogdanov, Manuel Sabin, and Prashant Nalini Vasudevan. Xor codes and sparse learning parity with noise. *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 986–1004, 2019.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Yuan Cao, Zhiying Fang, Yue Wu, Ding-Xuan Zhou, and Quanquan Gu. Towards understanding the spectral bias of deep learning. *arXiv preprint arXiv:1912.01198*, 2019.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

Alexandru Damian, Jason Lee, and Mahdi Soltanolkotabi. Neural networks can learn representations with gradient descent. In *Conference on Learning Theory*, pages 5413–5452. PMLR, 2022.

Amit Daniely and Eran Malach. Learning parities with neural networks. *Advances in Neural Information Processing Systems*, 33:20356–20365, 2020.

Ilias Diakonikolas, Surbhi Goel, Sushrut Karmalkar, Adam R Klivans, and Mahdi Soltanolkotabi. Approximation schemes for relu regression. In *Conference on Learning Theory*, pages 1452–1485. PMLR, 2020.

Simon S Du, Xiyu Zhai, Barnabas Poczos, and Aarti Singh. Gradient descent provably optimizes over-parameterized neural networks. *arXiv preprint arXiv:1810.02054*, 2018.

Benjamin L Edelman, Surbhi Goel, Sham Kakade, and Cyril Zhang. Inductive biases and variable creation in self-attention mechanisms. *arXiv preprint arXiv:2110.10090*, 2021.

Andreas Engel and Christian Van den Broeck. *Statistical mechanics of learning*. Cambridge University Press, 2001.

Carl-Gustav Esseen. On the Liapunov limit error in the theory of probability. *Ark. Mat. Astr. Fys.*, 28: 1–19, 1942.

Spencer Frei, Yuan Cao, and Quanquan Gu. Agnostic learning of a single neuron with gradient descent. *Advances in Neural Information Processing Systems*, 33:5417–5428, 2020.

Spencer Frei, Niladri S Chatterji, and Peter L Bartlett. Random feature amplification: Feature learning and generalization in neural networks. *arXiv preprint arXiv:2202.07626*, 2022.

Elizabeth Gardner and Bernard Derrida. Three unfinished works on the optimal storage capacity of networks. *Journal of Physics A: Mathematical and General*, 22(12):1983, 1989.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256. JMLR Workshop and Conference Proceedings, 2010.

Surbhi Goel, Sushrut Karmalkar, and Adam Klivans. Time/accuracy tradeoffs for learning a ReLU with respect to Gaussian marginals. *Advances in Neural Information Processing Systems*, 32, 2019.

Oded Goldreich and Leonid A Levin. A hard-core predicate for all one-way functions. In *Proceedings of the twenty-first annual ACM symposium on Theory of computing*, pages 25–32, 1989.

Sebastian Goldt, Madhu Advani, Andrew M Saxe, Florent Krzakala, and Lenka Zdeborová. Dynamics of stochastic gradient descent for two-layer neural networks in the teacher-student setup. *Advances in neural information processing systems*, 32, 2019.

Michael Hahn. Theoretical limitations of self-attention in neural sequence models. *Transactions of the Association for Computational Linguistics*, 8:156–171, 2020.

D Hansel, G Mato, and C Meunier. Memorization without generalization in a multilayered neural network. *EPL (Europhysics Letters)*, 20(5):471, 1992.

Godfrey Harold Hardy, John Edensor Littlewood, George Pólya, György Pólya, et al. *Inequalities*. Cambridge University Press, 1952.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*, 2022.

Yuval Ishai, Eyal Kushilevitz, Rafail Ostrovsky, and Amit Sahai. Cryptography with constant computational overhead. In *Proceedings of the 40th Annual ACM Symposium on the Theory of Computing*, pages 433–442, 2008.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *Advances in neural information processing systems*, 31, 2018.

Y Kabashima. Perfect loss of generalization due to noise in k= 2 parity machines. *Journal of Physics A: Mathematical and General*, 27(6):1917, 1994.

Pritish Kamath, Omar Montasser, and Nathan Srebro. Approximate is good enough: Probabilistic variants of dimensional and margin complexity. In *Conference on Learning Theory*, pages 2236–2262. PMLR, 2020.

Michael Kearns. Efficient noise-tolerant learning from statistical queries. *Journal of the ACM (JACM)*, 45(6):983–1006, 1998.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Adam Klivans and Pravesh Kothari. Embedding hard learning problems into gaussian space. In *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques (APPROX/RANDOM 2014)*. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2014.

Adam R Klivans, Ryan O'Donnell, and Rocco A Servedio. Learning intersections and thresholds of halfspaces. *Journal of Computer and System Sciences*, 68(4):808–840, 2004.

Gillat Kol, Ran Raz, and Avishay Tal. Time-space hardness of learning sparse parities. In *Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing*, pages 1067–1080, 2017.

Eyal Kushilevitz and Yishay Mansour. Learning decision trees using the fourier spectrum. *SIAM Journal on Computing*, 22(6):1331–1348, 1993.

Beatrice Laurent and Pascal Massart. Adaptive estimation of a quadratic functional by model selection. *Annals of Statistics*, pages 1302–1338, 2000.

Kevin Lu, Aditya Grover, Pieter Abbeel, and Igor Mordatch. Pretrained transformers as universal computation engines. *arXiv preprint arXiv:2103.05247*, 2021.

Eran Malach and Shai Shalev-Shwartz. Is deeper better only when shallow is good? *Advances in Neural Information Processing Systems*, 32, 2019.

Eran Malach and Shai Shalev-Shwartz. When hardness of approximation meets hardness of learning. *Journal of Machine Learning Research*, 23(91):1–24, 2022.

Eran Malach, Pritish Kamath, Emmanuel Abbe, and Nathan Srebro. Quantifying the benefit of using differentiable learning over tangent kernels. In *International Conference on Machine Learning*, pages 7379–7389. PMLR, 2021.

GJ Mitchison and RM Durbin. Bounds on the learning capacity of some multi-layer networks. *Biological Cybernetics*, 60(5):345–365, 1989.

Neel Nanda and Tom Lieberum. A mechanistic interpretability analysis of grokking. *Alignment Forum*, 2022. URL https://www.alignmentforum.org/posts/N6WM6hs7RQMKDhYjB/a-mechanistic-interpretability-analysis-of-grokking.

Ryan O'Donnell. *Analysis of Boolean functions*. Cambridge University Press, 2014.

Manfred Opper. Learning and generalization in a two-layer neural network: The role of the vapnik-chervonvenkis dimension. *Physical review letters*, 72(13):2113, 1994.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

Alethea Power, Yuri Burda, Harri Edwards, Igor Babuschkin, and Vedant Misra. Grokking: Generalization beyond overfitting on small algorithmic datasets. *arXiv preprint arXiv:2201.02177*, 2022.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of neural networks. In *International Conference on Machine Learning*, pages 5301–5310. PMLR, 2019.

Maria Refinetti, Sebastian Goldt, Florent Krzakala, and Lenka Zdeborová. Classifying high-dimensional gaussian mixtures: Where kernel methods fail and neural networks succeed. In *International Conference on Machine Learning*, pages 8936–8947. PMLR, 2021.

Michal Rosen-Zvi, Einat Klein, Ido Kanter, and Wolfgang Kinzel. Mutual learning in a tree parity machine and its application to cryptography. *Physical Review E*, 66(6):066135, 2002.

David Saad and Sara Solla. Dynamics of on-line gradient descent learning for multilayer neural networks. *Advances in neural information processing systems*, 8, 1995a.

David Saad and Sara A Solla. On-line learning in soft committee machines. *Physical Review E*, 52 (4):4225, 1995b.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

Shai Shalev-Shwartz, Ohad Shamir, and Shaked Shammah. Failures of gradient-based deep learning. In *International Conference on Machine Learning*, pages 3067–3075. PMLR, 2017.

Zhenmei Shi, Junyi Wei, and Yingyu Liang. A theoretical analysis on feature learning in neural networks: Emergence from inputs and advantage over fixed features. In *International Conference on Learning Representations*, 2021.

Roberta Simonetti and Nestor Caticha. On-line learning in parity machines. *Journal of Physics A: Mathematical and General*, 29(16):4859, 1996.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*, 2022.

Robert C Titsworth. *Correlation properties of cyclic sequences*. PhD thesis, California Institute of Technology, 1962.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Martin J Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.

Timothy LH Watkin, Albrecht Rau, and Michael Biehl. The statistical mechanics of learning a rule. *Reviews of Modern Physics*, 65(2):499, 1993.

Colin Wei, Jason D Lee, Qiang Liu, and Tengyu Ma. Regularization matters: generalization and optimization of neural nets vs their induced kernel. *Advances in Neural Information Processing Systems*, 32, 2019.

Gilad Yehudai and Shamir Ohad. Learning a single neuron with gradient methods. In *Conference on Learning Theory*, pages 3756–3786. PMLR, 2020.

Gilad Yehudai and Ohad Shamir. On the power and limitations of random features for understanding neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Jingzhao Zhang, Sai Praneeth Karimireddy, Andreas Veit, Seungyeon Kim, Sashank Reddi, Sanjiv Kumar, and Suvrit Sra. Why are adaptive methods good for attention models? *Advances in Neural Information Processing Systems*, 33:15383–15393, 2020.

Appendix

Table of Contents

A Additional background, preliminaries, and related work

A.1 Parities, orthogonality, and hardness

For each integer $n \geq 1$ and nonempty subset of indices $S \subseteq [n]$, define the (n, S)-*parity function* $\chi_S(x) = \prod_{i \in S} x_i$, i.e. the parity of the bits at the indices in S. We define the (n, S)-*parity distribution* $\mathcal{D}_S$ over examples (x, y) as follows: the features $x \sim \text{Unif}(\{\pm 1\}^n)$ are uniform random bits, with labels $y \in \{\pm 1\}$ given by the parity function $y = \chi_S(x)$. For $0 \leq k \leq n$, the corresponding (n, k)-*parity learning problem* is the task of identifying an unknown size-k set S (chosen at random), using samples from $\mathcal{D}_S$. With knowledge of k but not S, a learner must use the labels to distinguish between $\binom{n}{k}$ possible "relevant feature sets"; thus, the statistical limit for this problem is $\log \binom{n}{k} = \Theta(k \log n)$ samples.

This work leverages the parity problem as a "computationally hard case" for identifying the features S which are relevant to the label. Observe that for any $S' \subseteq [n]$, it holds that

$$\mathop{\mathbb{E}}_{x \sim \text{Unif}(\{\pm 1\}^n)} [\chi_S(x)\chi_{S'}(x)] = \mathop{\mathbb{E}}_{(x,y) \sim \mathcal{D}_S} [\chi_{S'}(x)\,y] = \begin{cases} 1 & S' = S \\ 0 & \text{otherwise} \end{cases}. \tag{2}$$

That is, a learner who guesses indices S' cannot use correlations as feedback to reveal which (or how many) indices in S' are correct, unless S' is *exactly* the correct subset. In this sense, for the (n, k)-parity problem, the $\binom{n}{k} - 1$ wrong answers are indistinguishable from each other. Thus, the structure of this problem forces this form of learner (but not necessarily all learning algorithms) to perform exhaustive search over subsets.

Property 2 (a.k.a. the orthogonality of parities under the correlation inner product) implies that any function $f : \{\pm 1\}^n \to \mathbb{R}$ has a unique Fourier expansion (see, e.g. (O'Donnell, 2014)):

$$f(x) = \sum_{S \subseteq [n]} \widehat{f}(S)\chi_S(x), \qquad \widehat{f}_S = \mathop{\mathbb{E}}_{x \sim \text{Unif}(\{\pm 1\}^n)} [f(x)\chi_S(x)]. \tag{3}$$

In the statistical query (SQ) model (Kearns, 1998), Property (2) implies computational lower bounds. In this model, a learner, rather than having access to examples drawn from the distribution, can query an oracle, which responds with noisy estimates of the query over the distribution. Namely, each iteration the learner outputs a query $q_i : \{\pm 1\}^n \to [-1, 1]$, and the oracle returns some value v_i satisfying $|v_i - \mathbb{E}_{(x,y) \sim \mathcal{D}} [q_i(x, y)]| \leq \tau$, for some tolerance parameter $\tau > 0$. It can be shown that Equation 2 implies that each query will have a non-trivial correlation only with a small fraction (namely, $1/\tau^2$) of the possible parities, which then implies that an SQ algorithm which solves the (n, k)-parity problem using T queries of tolerance τ must satisfy $T/\tau^2 \geq \Omega(n^k)$. This constitutes a lower bound on the number of queries (and/or on the tolerance), which indicates that essentially, SQ algorithms cannot do much better than exhaustive search (going over all the possible choices of size-k subsets).

It should be mentioned that the (n, k)-parity problem can be solved efficiently by a learning algorithm that has access to examples (i.e., an algorithm that does not operate in the SQ framework). Specifically, this problem can be solved by the Gaussian elimination algorithm. Moreover, it has been shown that the (Stochastic) Gradient Descent algorithm, discussed in the next section, can also be utilized for solving parities, given accurate enough estimates of the gradient and a very particular choice of neural network architecture Abbe and Sandon (2020). That said, when the accuracy of the gradients is not sufficient, GD suffers from the same SQ lower bound mentioned above (i.e., GD is essentially an SQ algorithm Abbe et al. (2021)).

Learning sparse *noisy* parities, even at a very small noise level (i.e., $o(1)$ or $n^{-\delta}$) is believed to be computationally hard. This was first explicitly conjectured by Alekhnovich (2003), and has been the basis for several cryptographic schemes (e.g., (Ishai et al., 2008; Applebaum et al., 2009, 2010)). For noiseless sparse parities, Kol et al. (2017) show time-space hardness in the setting where $k = \omega(1)$. We present some experiments with noisy parities in Appendix C.6, finding that our empirical results (and theoretical analysis) are robust to $\Theta(1)$ noise.

A.2 Neural networks and standard training

Next, we establish notation for the standard neural network training pipeline. Our main results are presented in the online learning setting, with a stream of i.i.d. batches of examples. At each iteration

$t = 1, \ldots, T$, a learning algorithm receives a batch of B examples $\{(x_{t,i}, y_{t,i})\}_{i=1}^{B}$ drawn i.i.d. from $\mathcal{D}_S$, then outputs a classifier $\widehat{y}_t : \{\pm1\}^n \to \{\pm1\}$. If $\mathbb{E}_{(x,y)\sim\mathcal{D}_S}[\mathbb{1}[\widehat{y}_t(x) \neq y]] \leq \epsilon$ (i.e. $\widehat{y}_t$ agrees with the correct parity on at least a $(1 - \epsilon)$ fraction of inputs), the learner is said to have solved the parity problem with error ϵ in t iterations (tB samples); the smallest t for which this is true is the *convergence time* t_c. A learner may also output an initial classifier $\widehat{y}_0$ before observing any data.

This formulation permits *improper* function classes (i.e. other than parities over subsets S') for the parity learning problem. In particular, we will focus on hypothesis classes of continuous functions $f : \{\pm1\}^n \times \Theta \to \mathbb{R}$, which map to classifiers $\widehat{y}(x) = \text{sign}(f(x; \theta))$[14]. When Θ is a vector space over $\mathbb{R}$, a ubiquitous online learning algorithm is gradient descent (GD). For a choice of loss function $\ell : \{\pm1\} \times \mathbb{R} \to \mathbb{R}$, initialization θ_0, learning rate schedule $\{\eta_t\}_{t=1}^{T} \subseteq \mathbb{R}$ and weight-decay schedule $\{\lambda_t\}_{t=1}^{T} \subseteq \mathbb{R}$, GD defines iterative updates

$$\theta_{t+1} \leftarrow (1 - \lambda_t)\theta_t - \eta_t \nabla_\theta \left(\frac{1}{B} \sum_{i=1}^{B} \ell(y_{t,i}, f(x_{t,i}; \theta_t)) \right), \tag{4}$$

where f (the *architecture*) and ℓ are assumed to be such that this gradient (more generally, subgradient) is well-defined. In this context, *online* and *stochastic* gradient descent (OGD/SGD) are equivalent names for the update rule (4).

A fundamental object of study in deep learning is the multi-layer perceptron (MLP). In this setting, a 2-layer MLP with *width* h and activation function $\sigma : \mathbb{R} \to \mathbb{R}$, parameterized by $W \in \mathbb{R}^{r \times n}, b \in \mathbb{R}^r, u \in \mathbb{R}^r$, specifies the function

$$f(x; W, b, u) = u^\top \sigma(Wx + b),$$

where $\sigma(\cdot)$ is applied entrywise. It is standard to use GD to jointly update the network's parameters. Our results include positive results about "single neurons": MLPs with width $r = 1$. We note that for our theoretical analysis, when training MLPs with GD, we allow for different learning rate and weight decay schedule for the different layers.

Finally, we will analyze randomized learning algorithms, such as GD with random initialization θ_0, whose iterates θ_t (and thus classifiers $\widehat{y}$) are random variables even when the samples are not. A learning algorithm has *permutation symmetry* if, for all sequences of data $\{(x_{t,i}, y_{t,i})\}$, the classifiers $\widehat{y}_t \circ \pi$ resulting from feeding $\{(\pi(x_{t,i}), y_{t,i})\}$ to the learner have identical distributions as π ranges over all permutations of indices. The neural architectures and initializations (and thus, SGD) considered in this work are permutation-symmetric; for this reason, it is convenient for notation to choose $S = [k]$ as the canonical (n, k)-parity learning problem, without loss of generality.

A.3 Additional related work

Feature learning using GD on neural networks. A line of recent work has focused on understanding the feature learning ability of gradient descent dynamics on neural networks. These analyses go beyond the Neural Tangent Kernel (NTK) regime, where they show a separation between learning with fixed features versus GD on neural networks, for these problems. Several of these works assume structure (often "sparse") in the input data which is useful for the prediction task, and helps avoid computational hardness. In contrast, our work focuses on studying hard problems at their computational limit. Here we discuss the most relevant works in detail:

A line of work (Diakonikolas et al. (2020); Yehudai and Ohad (2020); Frei et al. (2020)) focuses on learning a single non-linearity $y = \sigma(w^\top x)$ (typically $\sigma(\cdot)$ is the ReLU or sigmoid) using gradient-based methods. These works obtain polynomial-time convergence guarantees when the distribution satisfies a *spread* condition. These results do not extend to the Boolean hypercube.

Daniely and Malach (2020) also study the problem of learning sparse parities using neural networks. One key difference from our work is that they assume a modified version of the problem, where the input distribution is not uniform over the hypercube, but instead leaks information about the label. In particular, the distribution ensures that the relevant parity bits always have the same value. Shi et al. (2021) generalize this setting by considering a setting where labels are generated based on certain class specific patterns and the data itself is generated using these patterns with some extra

---

[14]When $f(x; \theta) = 0$ in practice (e.g. with sign initialization), we break the tie arbitrarily. We ensure in the theoretical analysis that this does not happen.

background patterns. This also embeds information in the data itself regarding the label, unlike our setting, where the labels are uncorrelated with the input features. Under these structural assumption, the papers study how GD on a two-layer network can learn useful features in polynomial time. Both these analysis also exploits the first gradient step to find useful features. Shi et al. (2021) additionally require a second step to refine the features.

Ba et al. (2022) show how the first gradient step is important for feature leaning. In particular, they show that first update is essentially rank-1 and aligns with the linear component of the underlying function. The functions we consider (parity) do not have a linear component.

Abbe et al. (2022) define a notion of initial alignment between the network at initialization and the target function and show that it is essential to get polynomial time learnability with noisy gradients on a fully connected network. Our MLP results also exploit the correlation between the gradient and the label to ensure that the gradient update gives us signal.

Frei et al. (2022) also study learnability of a parity-like function with $k = 2$ under noisy labels. The paper analyzes early stopping GD for learning the underlying labeling function. Our setup is quite different from theirs and can handle $k > 2$.

In concurrent work, Damian et al. (2022) consider the problem of learning polynomials which depend on few relevant directions using gradient descent on a two-layer network. They assume that the distributional Hessian of the ground truth function spans exactly the subspace of the relevant direction. Using this, they show that gradient descent can learn the relevant subspace with sample complexity scaling as d^2 and not d^p where p is the degree of the underlying polynomial as long as the number of relevant directions is much less than d. Their proof technique is similar to our two-layer MLP result which also exploits correlation in the first gradient step. However, for our setting, the distributional Hessian has rank 0 and does not satisfy their assumptions.

Statistical mechanics of machine learning. An extensive body of work originating in the statistical physics community has studied phase transitions in the learning curves of neural networks (Gardner and Derrida, 1989; Watkin et al., 1993; Engel and Van den Broeck, 2001). These works typically focus on student-teacher learning in the "thermodynamic limit", in which the number of training examples is α times larger than the input dimension and both are taken to infinity. One of the classic toy architectures analyzed in this literature is the *parity machine* (Mitchison and Durbin, 1989; Hansel et al., 1992; Opper, 1994; Kabashima, 1994; Simonetti and Caticha, 1996). In our work, we introduce PolyNets, a variant of parity machines in which the output is real-valued rather than ± 1; and we theoretically analyze disjoint-Polynets, which are the real-output analogue of the oft-considered parity machines with tree architecture. While much of the statistical mechanics of ML literature focuses on an idealized training limit in which the weights reach a Gibbs distribution equilibrium, there is a strand of the literature that aims to characterize the trajectory of SGD training in the high-dimensional limit with constant-sized sets of ordinary differential equations (Saad and Solla, 1995b,a; Goldt et al., 2019). These papers discuss cases, including problems that share aspects with 2-sparse parities Refinetti et al. (2021), where the network gets stuck in (and then escapes from) a plateau of suboptimal generalization error. Recently, Arous et al. (2021) studied (for rank-one parameter estimation problems) the relative amount of time spent by SGD in an initial high-error "search" phase versus a final "descent" phase, which is reminiscent of the framing of Theorem 6. However, to our knowledge prior work has not shown k-sparse parities can be learned with a number of iterations that nearly matches known lower bounds, nor has it specifically studied phase transitions in k-sparse parity learning during gradient descent.

B Proofs

B.1 Global convergence for MLPs

For some even number r, consider a ReLU MLP of size r:

$$f(x; \theta) = \sum_{i=1}^{r} u_i \sigma(w_i^\top x + b_i)$$

Where σ is the ReLU activation $\sigma(x) = \max\{x, 0\}$, $w_1, \ldots, w_r \in \mathbb{R}^{r \times n}, b \in \mathbb{R}^r, u \in \mathbb{R}^r$ and we denote the set of parameters by $\theta = \{w_1, \ldots, w_r, b, u\}$. We denote by $u_i^{(t)}, w_i^{(t)}, b^{(t)}$ and θ_t the

value of the relevant parameters at iteration t of gradient-descent. For brevity, we sometimes denote $w_i = w_i^{(0)}, b_i = b_i^{(0)}, u_i = u_i^{(0)}$. W.l.o.g., we assume that $S = [k]$, and so $y = \chi_{[k]}(x) = \prod_{i=1}^k x_i$. Indeed, since the weights' initialization we consider is permutation symmetric, this does not limit the generality of the results. We take ℓ to be the **hinge loss**: $\ell(y, \widehat{y}) = \max\{1 - y\widehat{y}, 0\}$. We use the following unbiased initialization:

- For all $1 \le i \le r/2$, randomly initialize
$$w_i^{(0)} \sim \text{Unif}\left(\{\pm 1\}^n\right), u_i^{(0)} \sim \text{Unif}\left(\{\pm 1\}\right), b_i^{(0)} \sim \text{Unif}(\{-1 + 1/k, \ldots, 1 - 1/k\})$$

- For all $r/2 < i \le r$, initialize
$$w_i^{(0)} = w_{i-r/2}^{(0)}, b_i^{(0)} = b_{i-r/2}^{(0)}, u_i^{(0)} = -u_{i-r/2}^{(0)}$$

We start by computing the population gradient at initialization. Using the fact that $\ell'(0, y) = -y$ we get the following:
$$\mathbb{E}\left[\nabla_{w_{i,j}}\ell(f(x; \theta_0), y)\right] = \mathbb{E}\left[-y\nabla_{w_{i,j}}f(x; \theta_0)\right] \tag{5}$$
$$= \mathbb{E}\left[-yu_i \mathbf{1}\{w_i \cdot x + b_i > 0\} x_j\right].$$

For $j \in [k]$ we have:

$$\mathbb{E}\left[\nabla_{w_{i,j}}\ell(f(x; \theta_0), y)\right] = -u_i \mathbb{E}\left[\left(\prod_{j' \in [k]\setminus\{j\}} x_{j'}\right) \mathbf{1}\{w_i \cdot x + b_i > 0\}\right]$$

For $j \notin [k]$ we have:

$$\mathbb{E}\left[\nabla_{w_{i,j}}\ell(f(x; \theta_0), y)\right] = -u_i \mathbb{E}\left[\left(\prod_{j' \in [k]\cup\{j\}} x_{j'}\right) \mathbf{1}\{w_i \cdot x + b_i > 0\}\right]$$

Finally, we have:

$$\mathbb{E}\left[\nabla_{b_i}\ell(f(x; \theta_0), y)\right] = -u_i \mathbb{E}\left[\left(\prod_{j' \in [k]} x_{j'}\right) \mathbf{1}\{w_i \cdot x + b_i > 0\}\right]$$

Denote
$$g_{i,j} = \mathbb{E}\left[\nabla_{w_{i,j}}\ell(f(x; \theta_0), y)\right], \ \gamma_i = \mathbb{E}\left[\nabla_{b_i}\ell(f(x; \theta_0), y)\right]$$

For some function f and some subset $S \subseteq [n]$, denote $\widehat{f}(S) = \mathbb{E}[f(x)\chi_S(x)]$.

Denote $\text{LTF}_{w,b}(x) = \mathbf{1}\{w \cdot x + b > 0\}$ and let $\text{Maj}(x) = \text{sign}\left(\sum_{i=1}^n x_i\right)$ and observe that, if $|b| < 1$,
$$\text{LTF}_{w,b}(x) = \frac{1}{2} + \frac{1}{2}\text{Maj}(w \odot x)$$
where $w \odot x = (w_1 x_1, \ldots, w_n x_n) \in \{\pm 1\}$. Since $\{\chi_S\}_{S \subseteq [n]}$ is a Fourier Basis, we can write $\text{Maj} = \sum_{S \subseteq [n]} \widehat{\text{Maj}}(S)\chi_S$ and therefore:

$$\text{LTF}_{w,b}(x) = \frac{1}{2} + \frac{1}{2}\text{Maj}(w \odot x) = \frac{1}{2} + \frac{1}{2}\sum_{S \subseteq [n]} \widehat{\text{Maj}}(S)\chi_S(w \odot x)$$

$$= \frac{1}{2} + \frac{1}{2}\sum_{S \subseteq [n]} \widehat{\text{Maj}}(S)\chi_S(w)\chi_S(x)$$

So, for every $S \subseteq [n]$ with $|S| \ge 1$ we have $\widehat{\text{LTF}}_{w,b}(S) = \frac{1}{2}\widehat{\text{Maj}}(S)\chi_S(w)$ and so $|\widehat{\text{LTF}}_{w,b}(S)| = \frac{1}{2}|\widehat{\text{Maj}}(S)|$.

Lemma 1 (O'Donnell (2014), Section 5.3). *Fix some k, and assume that $n \ge 2k^2$. Then, for every $S \subseteq [n]$ s.t. $|S| = k$ it holds that:*

- *If k is even:* $\widehat{\mathrm{Maj}}(S) = 0$.

- *If k is odd:*

$$c_1^2 k^{-2/3} \le \binom{n}{k} \widehat{\mathrm{Maj}}(S)^2 \le c_2^2 k^{-2/3}$$

  for some universal constants c_1, c_2. More precisely,

$$\widehat{\mathrm{Maj}}(S) = (-1)^{\frac{k-1}{2}} \frac{\binom{\frac{n-1}{2}}{\frac{k-1}{2}}}{\binom{n-1}{k-1}} \cdot 2^{-(n-1)} \binom{n-1}{\frac{n-1}{2}}$$

Observe that for all $S \subseteq [n]$ s.t. $|S| = k$ it holds that $\widehat{\mathrm{Maj}}(S) = \widehat{\mathrm{Maj}}([k])$ and denote $\xi_k := \widehat{\mathrm{Maj}}([k])$.

Therefore, by the previous lemma we get that for every even k the following holds:

$$\frac{\xi_{k+1}^2}{\xi_{k-1}^2} \le \frac{c_2^2 (k-1)^{2/3} \binom{n}{k-1}}{c_1^2 (k+1)^{2/3} \binom{n}{k+1}} \le \frac{c_2}{c_1} \frac{(k+1)k}{(n-k)(n-k+1)} \le \frac{8c_2}{c_1} \frac{k^2}{n^2} \tag{6}$$

Also, observe that

Lemma 2 (Fourier gap for majority). *Fix some k and assume that $n \ge 4k$. Then, Majority has a γ_k-Fourier gap at S of size k with $\gamma_k = 0.03(n-1)^{-\frac{k-1}{2}}$.*

Proof. First we establish a simple relationship between $|\xi_{k-1}|$ and $|\xi_{k+1}|$.

$$|\xi_{k-1}| = \frac{\binom{\frac{n-1}{2}}{\frac{k}{2}-1}}{\binom{n-1}{k-2}} 2^{-(n-1)} \binom{n-1}{\frac{n-1}{2}}$$

$$= \frac{n-k}{k-1} \cdot \frac{\binom{\frac{n-1}{2}}{\frac{k}{2}}}{\binom{n-1}{k}} \cdot 2^{-(n-1)} \binom{n-1}{\frac{n-1}{2}}$$

$$= \frac{n-k}{k-1} \cdot |\xi_{k+1}|.$$

Here, the first equation follows from Lemma 1, and the second equation follows by simple algebra using the following equality: $\binom{m}{r} = \frac{m-r+1}{r}\binom{m}{r-1}$.

Now, we can bound the difference,

$$|\xi_{k-1}| - |\xi_{k+1}| = \frac{n-2k+1}{k-1} \cdot |\xi_{k+1}|$$

$$= \frac{n-2k+1}{k-1} \cdot \frac{\binom{\frac{n-1}{2}}{\frac{k}{2}}}{\binom{n-1}{k}} \cdot 2^{-(n-1)} \binom{n-1}{\frac{n-1}{2}}$$

$$\ge \frac{n-2k+1}{k-1} \cdot \left(\frac{n-1}{k}\right)^{-k/2} \cdot e^{-k} \cdot \frac{2\sqrt{2\pi}}{e^2 \sqrt{n-1}}$$

$$\ge 0.03(n-1)^{-\frac{k-1}{2}}.$$

Here, the first equality holds from above, the second by Lemma 1, the third inequality holds from standard approximations of the binomial coefficients, and the last inequality follows from the following inequalities: $n - 2k + 1 \ge (n-1)/2$ (by assumption on n) and $\frac{\sqrt{2\pi}k^{k/2}}{(k-1)e^{k+2}} > 0.03$ (by standard calculus). This gives us the desired result.

$\square$

Lemma 3. *Assume that k is even and that $n \ge 2(k+1)^2$. Then, the following hold:*

1. *If $j \in \{1, \ldots, k\}$ then:*

$$g_{i,j} = -\frac{1}{2} u_i \xi_{k-1} \cdot \chi_{[k] \setminus \{j\}}(w_i)$$

2. *If $j \in \{k+1, \ldots, n\}$ then:*

$$g_{i,j} = -\frac{1}{2} u_i \xi_{k+1} \cdot \chi_{[k] \cup \{j\}}(w_i)$$

3. $\gamma_i = 0$.

Proof. If $j \in [k]$ then:

$$g_{i,j} = -u_i \mathbb{E}\left[\chi_{[k] \setminus \{j\}}(x) \mathrm{LTF}_{w_i,b_i}(x)\right] = -u_i \widehat{\mathrm{LTF}}_{w_i,b_i}([k] \setminus \{j\})$$
$$= -\frac{1}{2} u_i \widehat{\mathrm{Maj}}([k] \setminus \{j\}) \chi_{[k] \setminus \{j\}}(w_i) = -\frac{1}{2} u_i \xi_{k-1} \cdot \chi_{[k] \setminus \{j\}}(w_i)$$

Similarly, if $j \notin [k]$ we have:

$$g_{i,j} = -u_i \mathbb{E}\left[\chi_{[k] \cup \{j\}}(x) \mathrm{LTF}_{w_i,b_i}(x)\right] = -u_i \widehat{\mathrm{LTF}}_{w_i,b_i}([k] \cup \{j\})$$
$$= -\frac{1}{2} u_i \widehat{\mathrm{Maj}}([k] \cup \{j\}) \chi_{[k] \cup \{j\}}(w_i) = -\frac{1}{2} u_i \xi_{k+1} \cdot \chi_{[k] \cup \{j\}}(w_i)$$

Finally, we have:

$$\gamma_i = -u_i \widehat{\mathrm{LTF}}_{w_i,b_i}([k]) = -u_i \widehat{\mathrm{Maj}}([k]) = 0$$

$\square$

Lemma 4. *Let $\tau > 0$ be some tolerance parameter, fix $\epsilon \in (0,1)$ and let $\eta = \frac{1}{k|\xi_{k-1}|}$. Assume that k is an even number. Fix some $w_1, \ldots, w_k \in \{\pm 1\}^n$, $b_1, \ldots, b_r \in (-1,1)$ and $u_1, \ldots, u_k \in \{\pm 1\}$. Let $\widehat{w}_i = -\eta \widehat{g}_i$ and $\widehat{b}_i = b_i - \eta \widehat{\gamma}_i$ s.t. $\|\widehat{g}_i - g_i\|_\infty \leq \tau$ and $\|\widehat{\gamma}_i - \gamma_i\| \leq \tau$. Assume the following holds:*

- *For all $i, j \in [k]$ it holds that $w_{i,j} = u_i \cdot \mathrm{sign}\, \xi_{k-1}$.*

- *$b_i = -\frac{1}{2} + \frac{i+1}{k}$*

Then, if $\tau \leq \frac{|\xi_{k-1}|}{16k\sqrt{2n \log(2k/\epsilon)}}$ and $n \geq \frac{2^{11} k^4 c_2^2 \log(2k/\epsilon)}{c_1^2}$ there exists some $\widehat{u} \in \mathbb{R}^k$ with $\|\widehat{u}\|_\infty \leq 8k$ s.t. $f(x) = \sum_{i=1}^{k} \widehat{u}_i \sigma(\widehat{w}_i \cdot x + \widehat{b}_i)$ satisfies

$$\mathbb{E}_x[\ell(f(x), \chi_{[k]}(x))] \leq 16\epsilon k^2 n$$

Additionally, for all i and all x it holds that $|\sigma(\widehat{w}_i \cdot x + \widehat{b}_i)| \leq n + 1$.

Proof. We start with the following claim.

Claim 1: For all i and for all $j \in [k]$ it holds that $\left|\widehat{w}_{i,j} - \frac{1}{2k}\right| \leq \frac{\tau}{|\xi_{k-1}|}$.

Proof: First, observe that by the assumption it holds that for all $i, j \in [k]$,

$$u_i \cdot \chi_{[k] \setminus \{j\}}(w_i) = u_i \cdot \prod_{j' \in [k] \setminus \{j\}} w_{i,j} = u_i \cdot (u_i \cdot \mathrm{sign}\, \xi_{k-1})^{k-1} = \mathrm{sign}\, \xi_{k-1}$$

Now, from Lemma 3 we have:

$$g_{i,j} = -\frac{1}{2} u_i \xi_{k-1} \cdot \chi_{[k] \setminus \{j\}}(w_i) = -\frac{1}{2} |\xi_{k-1}|$$

and so

$$\left|w_{i,j} - \frac{1}{2k}\right| = \left|-\eta \widehat{g}_{i,j} - \frac{1}{2k}\right| = \frac{1}{k} \left|-k\eta \widehat{g}_{i,j} + \frac{g_{i,j}}{|\xi_{k-1}|}\right| = \frac{1}{k|\xi_{k-1}|} |g_{i,j} - \widehat{g}_{i,j}| \leq \frac{\tau}{|\xi_{k-1}|}$$

Claim 2: For all i and for all $j > k$ it holds that $|\widehat{w}_{i,j}| \leq \frac{|\xi_{k+1}| + 2\tau}{2k|\xi_{k-1}|}$

Proof: Using Lemma 3 we have:

$$|\widehat{w}_{i,j}| = \eta|\widehat{g}_{i,j}| \le \eta(|g_{i,j}| + |g_{i,j} - \widehat{g}_{i,j}|) \le \eta\left(\frac{|\xi_{k+1}|}{2} + \tau\right) = \frac{|\xi_{k+1}| + 2\tau}{2k|\xi_{k-1}|}$$

Claim 3: For all i it holds that $|\widehat{b}_i - b_i| \le \frac{\tau}{k|\xi_{k-1}|}$

Proof: Using Lemma 3 we have:

$$|\widehat{b}_i - b_i| = \eta|\widehat{g}_{i,0}| = \eta|g_{i,j} - \widehat{g}_{i,j}| \le \eta\tau = \frac{\tau}{k|\xi_{k-1}|}$$

Claim 4: Fix $\delta > 0$. Let h_i be a function s.t. $h_i(x) = \sigma(\frac{1}{2k}\sum_{j=1}^k x_j + b_i)$ and $\widehat{h}_i$ a function s.t. $\widehat{h}_i(x) = \sigma(\widehat{w}_{i,j} \cdot x + \widehat{b}_i)$. Then, if $\tau \le \frac{\delta}{2}\frac{k|\xi_{k-1}|}{\sqrt{2n\log(2k/\epsilon)}}$ and $n \ge \frac{32c_2^2\log(2k/\epsilon)}{c_1^2\delta^2}$, the following holds:

1. $\mathbb{P}_{x \sim \{\pm 1\}^n}\left[|h_i(x) - \widehat{h}_i(x)| \ge \delta\right] \le \frac{\epsilon}{k}$

2. $|\widehat{h}_i(x)| \le n + 1$

Proof: Let $x \sim \{\pm 1\}^n$, and denote $\tilde{x}_j = \widehat{w}_{i,j}x_j$. Denote $\Delta = \frac{|\xi_{k+1}| + 2\tau}{2k|\xi_{k-1}|}$. So, for $j > k$, $\tilde{x}_j$ is a random variable satisfying $|\tilde{x}_j| \le \Delta$. Furthermore, it holds that $\mathbb{E}\left[\sum_{j>k}\tilde{x}_j\right] = 0$. Therefore, from Hoeffding's inequality:

$$\mathbb{P}\left[\left|\sum_{j>k}\tilde{x}_j\right| \ge \Delta\sqrt{\frac{n\log(2k/\epsilon)}{2}}\right] \le 2\exp\left(-\frac{2\left(\Delta\sqrt{\frac{n\log(2k/\epsilon)}{2}}\right)^2}{n\Delta^2}\right) \le \frac{\epsilon}{k}$$

Now, fix some x s.t. $\left|\sum_{j>k}\tilde{x}_j\right| \le \Delta\sqrt{\frac{n\log(2k/\epsilon)}{2}}$. In this case we have:

$$
\begin{aligned}
|h_i(x) - \widehat{h}_i(x)| &\le \left|\frac{1}{2k}\sum_{j=1}^k x_j + b_i - \widehat{w}_i \cdot x + \widehat{b}_i\right| \\
&\le \sum_{j=1}^k\left|\frac{1}{2k}x_j - \widehat{w}_{i,j}x_j\right| + \left|\sum_{j>k}\widehat{w}_{i,j}x_j\right| + \left|b_i - \widehat{b}_i\right| \\
&\le \frac{k\tau}{|\xi_{k-1}|} + \Delta\sqrt{\frac{n\log(2k/\epsilon)}{2}} + \frac{\tau}{k|\xi_{k-1}|} \\
&= \frac{\tau(k^2 + 1)}{k|\xi_{k-1}|} + \frac{|\xi_{k+1}| + 2\tau}{2k|\xi_{k-1}|} \cdot \sqrt{\frac{n\log(2k/\epsilon)}{2}} \\
&= \frac{\tau\left(\sqrt{2}(k^2 + 1) + \sqrt{n\log(2k/\epsilon)}\right)}{\sqrt{2}k|\xi_{k-1}|} + \frac{|\xi_{k+1}|\sqrt{n\log(2k/\epsilon)}}{2\sqrt{2}k|\xi_{k-1}|} \\
&\le \frac{\tau\sqrt{2n\log(2k/\epsilon)}}{k|\xi_{k-1}|} + \frac{2\sqrt{2}c_2\sqrt{\log(2k/\epsilon)}}{c_1\sqrt{n}}
\end{aligned}
$$

where in the last inequality we use Eq. (6). So, choosing $\tau \le \frac{\delta}{2}\frac{k|\xi_{k-1}|}{\sqrt{2n\log(2k/\epsilon)}}$ and $n \ge \frac{32c_2^2\log(2k/\epsilon)}{c_1^2\delta^2}$ gives the required.

Claim 5: Let $h_1, \ldots, h_k$ be the functions defined in the previous claim. Then, there exists weights u^* with $\|u^*\|_\infty \le 8k$ s.t. for $f^*(x) = \sum_{i=1}^k u_i^* h_i(x)$ it holds that $f^*(x) = 2\chi_{[k]}(x)$ for all $x \in \{\pm 1\}^n$.

Proof: For $i \le k - 2$ define $u_i^* = 8k(-1)^{i+1}$ and $u_{k-1}^* = 6k$, $u_k^* = -2k$.

Proof of Lemma 4: Choose $\widehat{u} = u^*$. Using Claim 4 and the union bound, w.p. $1 - \epsilon$ over $x \sim \{\pm 1\}^n$ it holds that for all $i \in [k]$, $|h_i(x) - \widehat{h}_i(x)| \leq \delta$. Therefore, w.p. $\geq 1 - \epsilon$

$$|f(x) - f^*(x)| = \left| \sum_{i=1}^k u_i^*(h_i(x) - \widehat{h}_i(x)) \right| \leq \sum_{i=1}^k |u_i^*| \left| h_i(x) - \widehat{h}_i(x) \right| \leq 8k^2\delta$$

so, choosing $\delta = \frac{1}{8k^2}$ we get that, w.p. at least $1 - \epsilon$ over the choice of x it holds that $f(x)\chi_{[k]}(x) \geq 1$. Additionally, for every x it holds that

$$|f(x)| \leq \sum_{i=1}^k |u_i^*| \left| \widehat{h}_i(x) \right| \leq 8k^2(n+1) \leq 16k^2 n$$

Therefore, we get:

$$\mathbb{E}_x \left[\ell(f(x), \chi_{[k]}(x)) \right] \leq \epsilon \mathbb{E}_x \left[\ell(f(x), \chi_{[k]}(x)) | f(x)\chi_{[k]}(x) < 1 \right]$$
$$\leq \epsilon \mathbb{E}_x \left[|f(x)| | f(x)\chi_{[k]}(x) < 1 \right] \leq 16\epsilon k^2 n$$

$\square$

Lemma 5. *Assume we randomly initialize an MLP using the unbiased initialization defined previously. Consider the following update:*

$$w_i^{(1)} = (1 - \lambda_0)w_i^{(1)} - \eta_0\widehat{g}_i, \ b_i^{(1)} = b_i^{(1)} - \eta_0\widehat{\gamma}_i$$

where

$$\widehat{g}_i = \frac{1}{B} \sum_{l=1}^B \nabla_{w_i}\ell(f(x_{0,l}; \theta_0), y_{0,l}), \ \widehat{\gamma}_i = \frac{1}{B} \sum_{l=1}^B \nabla_{b_i}\ell(f(x_{0,l}; \theta_0), y_{0,l})$$

Let k be even number. Then, for every $\epsilon, \delta \in (0, 1/2)$, denoting $\tau = \frac{|\xi_{k-1}|}{16k\sqrt{2n\log(2k/\epsilon)}}$, if $\eta = \frac{1}{k|\xi_{k-1}|}$, $\lambda_0 = 1$, $r \geq k \cdot 2^k \log(k/\delta)$, $B \geq \frac{2}{\tau^2}\log(4nr/\delta)$ and $n \geq \frac{2^{11}k^4 c_2^2 \log(2k/\epsilon)}{c_1^2}$, w.p. at least $1 - 2\delta$ over the initialization and the sample, there exists $\widehat{u} \in \mathbb{R}^r$ with $\|\widehat{u}\|_\infty \leq 8k$ and $\|\widehat{u}\|_2 \leq 8k\sqrt{k}$ s.t. $f(x) = \sum_{i=1}^r \widehat{u}_i \sigma\left(w_i^{(1)} \cdot x + b_i^{(1)}\right)$ satisfies

$$\mathbb{E}_x[\ell(f(x), \chi_{[n]}(x))] \leq 16\epsilon k^2 n$$

Additionally, it holds that $\|\sigma(W^{(1)} \cdot x + b^{(1)})\|_\infty \leq n + 1$.

Proof. Note that by the choice of initialization it holds that $f(x; W^{(0)}) = 0$, and by the assumption on the loss function $\ell'(f(x; W^{(0)}), y) = -y$. Therefore, we get that $\mathbb{E}\left[\nabla_{w_i}\ell(f(x; W^{(0)}), y)\right] = g_i$ and $\mathbb{E}\left[\nabla_{b_i}\ell(f(x; W^{(0)}), y)\right] = \gamma_i$.

Claim: with probability at least $1 - \delta$,

$$\text{for all } i, j: \ \left\| \widehat{g}_i - \mathbb{E}\left[\nabla_{w_i}\ell(f(x; W^{(0)}), y)\right] \right\|_\infty \leq \tau \text{ and } \left| \widehat{\gamma}_i - \mathbb{E}\left[\nabla_{b_i}\ell(f(x; W^{(0)}), y)\right] \right| \leq \tau \tag{7}$$

Proof: Fix some i, j and note that by Hoeffding's inequality,

$$\Pr\left[|\widehat{g}_{i,j} - \mathbb{E}\widehat{g}_{i,j}| \geq \tau\right] \leq 2\exp\left(-B\tau^2/2\right) \leq \frac{\delta}{nr + r}$$

and similarly we get $\Pr\left[|\widehat{\gamma}_i - \mathbb{E}\widehat{\gamma}_i| \geq \tau\right] \leq \frac{\delta}{nr+r}$. The required follows from the union bound.

Now, assume that Eq. (7) holds. For some random $w_i \sim \{\pm 1\}^n$, the probability that $w_{i,j} = w_{i,j'}$ for all $j, j' \in [k]$ is 2^{-k+1}. Additionally, for some fixed $i' \in [k]$, the probability that $b_i = -\frac{1}{2} + \frac{i'}{k}$ is $\frac{1}{2k}$. Therefore, for some fixed $i \in [r/2]$ and $i' \in [k]$, with probability $\frac{1}{k \cdot 2^{k-1}}$, $b_i = b_{i+r/2} = -\frac{1}{2} + \frac{i'}{k}$

and either $w_{i,j} = u_i \operatorname{sign} \xi_{k-1}$ or $w_{i+r/2,j} = u_{i+r/2,j} \operatorname{sign} \xi_{k-1}$. Taking $r \geq k \cdot 2^k \log(k/\delta)$, we get that the probability that there is no $i \in [r/2]$ that satisfies the above condition (for fixed i') is:

$$\left(1 - \frac{1}{k2^{k-1}}\right)^{r/2} \leq \exp\left(-\frac{r}{2k2^{k-1}}\right) \leq \frac{\delta}{k}$$

Using the union bound, with probability at least $1 - \delta$, there exists a set of k neurons satisfying the conditions of Lemma 4, and therefore the required follows from the Lemma. $\qquad\square$

We use the following well-known result on convergence of SGD (see for example Shalev-Shwartz and Ben-David (2014)):

Theorem 8. *Let $M, \rho > 0$. Fix T and let $\eta = \frac{M}{\rho\sqrt{T}}$ Let F be a convex function and $u^* \in \arg\min_{\|u\|_2 \leq M} f(u)$. Let $u^{(0)} = 0$ and for every t, let v_t be some random variable s.t. $\mathbb{E}\left[v_t | u^{(t)}\right] = \nabla_{u^{(t)}} F(u^{(t)})$ and let $u^{(t+1)} = u^{(t)} - \eta v^{(t)}$. Assume that $\|v_t\|_2 \leq \rho$ w.p. 1. Then,*

$$\frac{1}{T} \sum_{t=1}^{T} F(u^{(t)}) \leq F(u^*) + \frac{M\rho}{\sqrt{T}}$$

We prove the following theorem:

Theorem 9. *Let k be an even number. Assume we randomly initialize an MLP using the unbiased initialization defined previously. Fix $\epsilon \in (0, 1/2)$ and let $T \geq \frac{2^9 k^3 r n^2}{\epsilon^2}, r \geq k \cdot 2^k \log(8k/\epsilon), B \geq c_1^{-1} 2^8 k^{7/6} n \binom{n}{k-1} \log(128k^3 n/\epsilon) \log(32nr/\epsilon), n \geq \frac{2^{11} k^4 c_2^2 \log(128k^3 n/\epsilon)}{c_1^2}$. Choose the following learning rate and weight decay schedule:*

- *At the first step, use $\eta_0 = \frac{1}{k|\xi_{k-1}|}, \lambda_0 = 1$ for all weights.*

- *After the first step, use $\eta_t = 0$ for the first layers weights and biases and $\eta_t = \frac{4k^{1.5}}{n\sqrt{r(T-1)}}$ for the second layer weights, with $\lambda_t = 0$ for both layers.*

- *Bias terms are never regularized.*

Then, the following holds, with expectation over the randomness of the initialization and the sampling of the batches:

$$\mathbb{E}\left[\min_{t \in [T]} \ell(f(x; \theta_t), y)\right] \leq \epsilon$$

Proof. Let $F(u) = \mathbb{E}_x\left[\ell(u^\top \sigma(W^{(1)} x + b^{(1)}), y)\right]$ and notice that F is a convex function. For every t, denote

$$v_t = \frac{1}{B} \sum_{l=1}^{B} \nabla_{u^{(t)}} \ell(f(x_{t,l}; \theta_t), y) = \frac{1}{B} \sum_{l=1}^{B} \nabla_{u^{(t)}} \ell\left(\left(u^{(t)}\right)^\top \sigma(W^{(1)} x_{l,t} + b^{(1)}), y_{l,t}\right)$$

where we use the fact that we don't update the weights of the first layer after the first step. From the above we get $\mathbb{E}[v_t | u^{(t)}] = \nabla_{u^{(t)}} F(u^{(t)})$.

Now, we will show that w.h.p. there exists u^* with good loss. Let $\epsilon' = \frac{\epsilon}{64k^2 n}, \delta' = \frac{\epsilon}{8}$. Denote $\tau = \frac{|\xi_{k-1}|}{16k\sqrt{2n \log(128k^3 n/\epsilon)}} = \frac{|\xi_{k-1}|}{16k\sqrt{2n \log(2k/\epsilon')}}$. Observe that $r \geq k \cdot 2^k \log(k/\delta')$, and using the fact that $|\xi_{k-1}| \geq c_1(k-1)^{-1/3} \binom{n}{k-1}^{-1}$ we get

$$B \geq \frac{2^8 k^2 \cdot n \log(128k^3 n/\epsilon)}{|\xi_{k-1}|} \log(32nr/\delta) = \frac{2}{\tau^2} \log(4nr/\delta')$$

and additionally $n \geq \frac{2^{11} k^4 c_2^2 \log(2k/\epsilon')}{c_1^2}$.

From the above, applying Lemma 5 with ϵ', δ' we get that w.p. $1 - \epsilon/4$ there exists $u^* \in \mathbb{R}^r$ with $\|u^*\|_2 \le 8k\sqrt{k}$ s.t. $F(u^*) \le \epsilon/4$ and for all i and all x it holds that $\|\sigma(W^{(1)} \cdot x + b^{(1)})\|_\infty \le n + 1$. Using this, we get:

$$\|v_t\|_2 \le \frac{1}{B} \sum_{l=1}^{B} \|\sigma(W^{(1)} x_{l,t} + b^{(1)}), y_{l,t}\|_2 \le \sqrt{r}(n+1)$$

So, we can apply Theorem 8 with $M = 8k\sqrt{k}$ and $\rho = 2\sqrt{r}n$ and get that, w.p. $1 - \epsilon/4$ over the initialization and the first step, it holds that

$$\mathbb{E}_{\text{steps } 2...T} \left[\min_{t \in \{2,...,T\}} \ell(f(x; \theta_t), y) \right] \le \mathbb{E} \left[\frac{1}{T-1} \sum_{t=2}^{T} \ell(f(x; \theta_t), y) \right]$$

$$= \mathbb{E} \left[\frac{1}{T-1} \sum_{t=2}^{T} F(u^{(t)}) \right] \le \epsilon/4 + \frac{16k^{1.5}\sqrt{r}n}{\sqrt{T-1}} \le \epsilon/2$$

Now, that after the first step we have $u^{(1)} = 0$ and therefore $\ell(f(x; \theta_1), y) = 1$, and so we always have $\min_{t \in [T]} \ell(f(x; \theta_t), y) \le 1$. Therefore, taking expecation over all steps we get:

$$\mathbb{E}_{\text{steps } 1...T} \left[\min_{t \in [T]} \ell(f(x; \theta_t), y) \right] \le \epsilon/2 + \epsilon/2 = \epsilon$$

$\square$

B.2 Recoverability of the parity indices from Fourier gaps

Given a network architecture where some neuron has a γ-Fourier gap with respect to the target subset S, we quantify how the indices in S can be determined by observing an estimate of the population gradient for a general activation function σ and w_t:

Proposition 10 (Fourier gap implies feature recoverability). *For an activation function $\sigma : \mathbb{R} \to \mathbb{R}$, let $f(x; w) = \sigma(w^\top x)$ be the corresponding 1-neuron predictor. Let $\mathcal{D}_S$ be an (n, k)-sparse parity distribution. Let $g(w)$ be an estimate[15] for the neuron's population gradient of the correlation loss ℓ:*

$$||g(w) - \mathbb{E}_{(x,y)\sim\mathcal{D}_S} [\nabla_w \ell(y, f(x; w))]||_\infty < \gamma/2.$$

Then, for every w such that $\sigma'(w^\top x)$ has a γ-Fourier gap at S, the k indices at which $g(w)$ has the largest absolute values are exactly the indices in S.

Proof. Let $h(x) := \sigma'(w^\top x)$. We compute the population gradient, we we call $\bar{g}(w)$:

$$[\bar{g}(w)]_i = \mathbb{E}_{(x,y)\sim\mathcal{D}_S} [\nabla_{w_i} \ell(y, f(x; w))] = - \mathbb{E}_{(x,y)\sim\mathcal{D}_S} [\sigma'(w^\top x) y x_i]$$

$$= \begin{cases} \mathbb{E}\left[\sigma'(w^\top x) \prod_{j \in S\setminus\{i\}} x_i\right] & i \in S \\ \mathbb{E}\left[\sigma'(w^\top x) \prod_{j \in S\cup\{i\}} x_i\right] & i \notin S \end{cases}$$

$$= \begin{cases} \widehat{h}(S \setminus \{i\}) & i \in S \\ \widehat{h}(S \cup \{i\}) \le \widehat{h}(S \cup \{i\}) - \gamma & i \notin S \end{cases},$$

where the inequality in the final $i \notin S$ case is due to the Fourier gap property. Then, it holds that for all $i \in S$ we have $|g_i| > \gamma/2$ and for all $i \notin S$ we have $|g_i| < \gamma/2$. Thus, the largest entries of the estimate $g(w)$ occur at the indices in S, as claimed. $\square$

B.3 Global convergence for disjoint-PolyNets

In this section we will develop theory for disjoint-PolyNets trained with correlation loss, as illustrated in Figure 5. Section B.3.1 will consider optimization with gradient flow, and section B.3.2 will consider optimization with batch size 1 SGD.

Figure 5: Example training curves for the disjoint-PolyNet trained with correlation loss, which is the setting of Appendix B.3. The left plot shows validation error under population gradient descent with small step size, approximating the setting of Section B.3.1, and the right plot shows a run of SGD with batch size 1, as in Section B.3.2, though with a constant learning rate schedule. Initialization is i.i.d. standard Gaussian.

B.3.1 Gradient flow analysis

For i, $\mathbb{E}\left[\nabla_{w_i}\ell(f(x;w_{1:k}),y)\right] = 0$, so the irrelevant weights remain fixed at initialization. For each $i \in [k]$, let $v_i^{(t)}$ be the relevant weight in the kth partition.

In gradient flow, the relevant weights evolve according to the following differential equations:

$$\forall i \in [n]: \quad \dot{v}_i = \prod_{j \neq i} v_j$$

Lemma 6. *Suppose disjoint-PolyNet for $k > 2$ is initialized such that $\prod_i v_i(0) > 0$, and optimized with gradient flow. Let $\bar{v}_a := \frac{1}{k}\sum_{i=1}^{k}(v_i(0))^2$, and $\bar{v}_g := \left(\prod_{i=1}^{k}(v_i(0))^2\right)^{1/k}$. For any $b \geq 0$ and $i \in [k]$, let $T_i(b) := \arg\sup_{t\geq 0}(|v_i(t)| \leq b)$. Then*

$$T_i(b) \geq \frac{1}{k-2}\left(\bar{v}_a^{1-k/2} - (\bar{v}_a + b^2 - v_i(0)^2)^{1-k/2}\right).$$

Let $T_i(\infty) := \arg\sup_{t\geq 0}(|v_i(t)| < \infty)$. Then

$$T_i(\infty) - T_i(b) \leq \frac{1}{k-2}(\bar{v}_g + b^2 - v_i(0)^2)^{1-k/2}.$$

Proof. First, observe that the product of the relevant weights is non-decreasing during gradient flow.

$$\frac{d\left(\prod_{i=1}^{k} v_i(t)\right)}{dt} = \sum_{i=1}^{k} \frac{\partial\left(\prod_{i=1}^{k} v_i\right)}{\partial v_i} \cdot \dot{v}_i = \sum_{i=1}^{k}\left(\prod_{j\neq i} v_j\right)^2 > 0$$

Thus, $\prod_i v_i(0) > 0$ implies that $\prod_i v_i(t) > 0$ for all t.

Observe that

$$\frac{dv_i^2}{dt} = 2v_i\dot{v}_i = 2\prod_{j=1}^{k} v_j = 2\prod_{j=1}^{k} |v_j|.$$

This implies that for all $i, l \in [t]$,

$$\frac{dv_i^2}{dt} = \frac{dv_l^2}{dt}. \tag{8}$$

In other words, the squares of the relevant weights each follow the same trajectory, shifted according to their initializations. Let $q(t) := (v_i(t))^2 - (v_i(0))^2$, for any i. This quantity evolves as follows:

$$\dot{q} = 2\prod_{i=1}^{k} |v_i| = 2\left(\prod_{i=1}^{k}(q(t) + (v_i(0))^2)\right)^{1/2}$$

---

[15] For $O(1)$-bounded stochastic gradient estimators, $O\left(\frac{\log n}{\gamma^2}\right)$ samples suffice to obtain such an estimate.

Since $q(t)$ is strictly increasing, its inverse q^{-1} is well-defined, and we can use the inverse function theorem to characterize q^{-1} for all $t \geq 0$:

$$q^{-1}(c) = \int_0^c \frac{1}{2} \left(\prod_{i=1}^k (\gamma + (v_i(0))^2) \right)^{-1/2} d\gamma.$$

We can upper- and lower-bound the integrand by applying Maclaurin's inequality (see page 52 in Hardy et al. (1952)):

$$(\gamma + \bar{v}_g)^k \leq \prod_{i=1}^k (\gamma + (v_i(0))^2) \leq (\gamma + \bar{v}_a)^k .$$

The amount of time it takes for q to reach a value of c is thus:

$$\int_0^c \frac{1}{2} \left(\prod_{i=1}^k (\gamma + (v_i(0))^2) \right)^{-1/2} d\gamma \geq \int_0^c \frac{1}{2} (\gamma + \bar{v}_a)^{-k/2} d\gamma = \frac{1}{k-2} \left(\bar{v}_a^{1-k/2} - (c + \bar{v}_a)^{1-k/2} \right).$$

Hence, for any $b \geq 0$, for each i, $|v_i(t)| \leq b$ as long as

$$t \leq \frac{1}{k-2} \left(\bar{v}_a^{1-k/2} - (\bar{v}_a + b^2 - v_i(0)^2)^{1-k/2} \right).$$

Meanwhile, the amount of time after $q^{-1}(c)$ it takes for q to explode to infinity is

$$\int_c^\infty \frac{1}{2} \left(\prod_{i=1}^k (\gamma + (v_i(0))^2) \right)^{-1/2} d\gamma \leq \int_c^\infty \frac{1}{2} (\gamma + \bar{v}_g)^{-k/2} d\gamma = \frac{1}{k-2} (c + \bar{v}_g)^{1-k/2}.$$

Substituting $c = b^2 - v_i(0)^2$, we obtain that the amount of time it takes for $|v_i|$ to grow from b to ∞ is

$$\frac{1}{k-2} (\bar{v}_g + b^2 - v_i(0)^2)^{1-k/2}.$$

We can upper- and lower-bound $\dot{q}$ by applying Maclaurin's inequality (see page 52 in Hardy et al. (1952)):

$$2 (q(t) + \bar{v}_g)^{k/2} \leq \dot{q} \leq 2 (q(t) + \bar{v}_a)^{k/2} .$$

When $k = 2$, solving the LHS and RHS differential inequalities yields:

$$\bar{v}_g (e^{2t} - 1) \leq q(t) \leq \bar{v}_a (e^{2t} - 1).$$

When $k > 2$, we obtain:

$$(\bar{v}_g^{-(k/2-1)} - (k-2)t)^{-\frac{1}{k/2-1}} - \bar{v}_g \leq q(t) \leq (\bar{v}_a^{-(k/2-1)} - (k-2)t)^{-\frac{1}{k/2-1}} - \bar{v}_a \quad (9)$$

From the lower bound on $q(t)$, we can infer that the relevant weights all explode to infinity by the following time:

$$t = \frac{1}{(k-2)} \bar{v}_g^{-(k/2-1)} = \frac{1}{(k-2) \left(\prod_i v_i(0) \right)^{1-2/k}}$$

From the upper bound, we can infer that for any $c > 0$, it is the case that $q(t) \leq c$ so long as

$$t \leq \frac{1}{k-2} \left(\bar{v}_a^{-(k/2-1)} - (\bar{v}_a + c)^{-(k/2-1)} \right).$$

Hence, for each i, $|v_i(t)| \leq b$ for all

$$t \leq \frac{1}{k-2} \left(\bar{v}_a^{-(k/2-1)} - (\bar{v}_a + b^2 - (v_i(0))^2)^{-(k/2-1)} \right).$$

$\square$

Now we analyze the relationship between the relevant weights and the accuracy of the disjoint-PolyNet.

For $y \in \mathbb{R}$, let

$$\text{sign}(y) = \begin{cases} 1 & \text{if } y > 0 \\ 0 & \text{if } y = 0 \\ -1 & \text{if } y < 0 \end{cases}$$

Then define the error of f with parameters $w_{1:k}$ as

$$\text{err}(w_{1:k}) := \Pr_{x \sim \{\pm 1\}^n}[\text{sign}(f(x; w_{1:k})) \neq \chi_S(x)]$$

Lemma 7. *Let w be any setting of the weights of a disjoint-PolyNet such that $\prod_i v_i > 0$. For ease of notation, let $u_i := w_{i,2:n'}$ be the irrelevant portion of w_i. There is a constant c such that*

$$\frac{1}{2} - \frac{1}{2} \prod_{i=1}^{k} \left(\text{erf}\left(\frac{|v_i|}{\|u_i\|_2 \sqrt{2}} \right) + \frac{c\|u_i\|_\infty}{\|u_i\|_2^3} \right) \leq \text{err}(w_{1:k}) \leq 2 \sum_{i=1}^{k} \exp\left(-\frac{|v_i|^2}{\|u_i\|_2^2} \right)$$

where erf is the Gauss error function $\text{erf}(y) := \frac{2}{\sqrt{\pi}} \int_0^y e^{-\tau^2} d\tau$.

Proof. Let $z_i = x_{(i-1)n'+1}$ be the ith relevant coordinate of x, and let $z_i^- = x_{(i-1)n'+2:in'}$ be the irrelevant coordinates in P_i.

Then we have that the error of f with parameters $w_{1:k}$ is

$$\text{err}(w_{1:k}) = \Pr_x\left[\text{sign}\left(\prod_{i=1}^{k} w_i^\top x_{P_i} \right) \neq \chi_S(x) \right]$$

$$= \Pr_x\left[\text{sign}\left(\prod_{i=1}^{k} w_i^\top x_{P_i} \right) = -\chi_S(x) \right] + \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right]$$

$$= \Pr_x\left[\text{sign}\left(\prod_{i=1}^{k} w_i^\top x_{P_i} \right) = -\chi_S(x) \right] + \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right]$$

$$= \Pr_x\left[\#\{i \in [k] : \text{sign}(v_i z_i + u_i^\top z_i^-) = -z_i\} \text{ is odd} \right] + \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right]$$

$$= \Pr_{z_1^-,\ldots,z_k^-}\left[\#\{i \in [k] : u_i^\top z_i^- > v_i\} \text{ is odd} \right] / 2$$

$$+ \Pr_{z_1^-,\ldots,z_k^-}\left[\#\{i \in [k] : u_i^\top z_i^- < -v_i\} \text{ is odd} \right] / 2 + \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right] \quad (10)$$

$$= \Pr_{z_1^-,\ldots,z_k^-}\left[\#\{i \in [k] : u_i^\top z_i^- > v_i\} \text{ is odd} \right] + \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right] \quad (11)$$

$$= \Pr_{z_1^-,\ldots,z_k^-}\left[\#\{i \in [k] : u_i^\top z_i^- > |v_i|\} \text{ is odd} \right] + \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right] \quad (12)$$

Line 10 follows because $u_i^\top z_i^-$ and z_i are independent. In line 11 we use that $u_i^\top z_i^-$ is symmetric about 0. Finally, line 12 uses the assumption that $\prod_{i=1}^{k} v_i > 0$.

We can bound $\Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right]$ using Hoeffding's inequality:

$$0 \leq \Pr_x\left[\prod_{i=1}^{k} w_i^\top x_{P_i} = 0 \right] \leq \sum_{i=1}^{k} \Pr_{z_i}[u_i^\top z_i^- = v_i] \leq \sum_{i=1}^{k} \Pr_{z_i}[u_i^\top z_i^- \geq |v_i|] \leq \sum_{i=1}^{k} \exp\left(-\frac{|v_i|^2}{\|u_i\|_2^2} \right).$$

The indicator random variables $\mathbb{1}[u_i^\top z_i^- > |v_i|]$ are independent of each other, so the first term in line 12 can be characterized using the distribution of the parity of a sum of independent Bernoulli random variables. Let $X_i \sim \text{Ber}(p_i)$ for $i \in [k]$, and let $X = \sum_{i=1}^k X_i$. The generating function for X is $f(z) = \prod_{i=1}^k ((1-p_i) + p_i z)$. The parity of X then satisfies

$$\Pr[X \text{ is odd}] = \frac{f(1)}{2} - \frac{f(-1)}{2} = \frac{1}{2} - \frac{1}{2}\prod_{i=1}^k (1 - 2p_i).$$

First we will prove the upper bound on err. First, observe that

$$\frac{1}{2} - \frac{1}{2}\prod_{i=1}^k (1 - 2p_i) \le \sum_{i=1}^k p_i.$$

Thus,

$$\Pr_{z_1^-,\ldots,z_k^-}\left[\#\{i \in [k] : u_i^\top z_i^- > |v_i|\} \text{ is odd}\right] \le \sum_{i=1}^k \Pr_{z_i}[u_i^\top z_i^- > |v_i|]$$

$$\le \sum_{i=1}^k \exp\left(-\frac{|v_i|^2}{\|u_i\|_2^2}\right)$$

by Hoeffding's inequality, and we are done.

Now we will prove the lower bound on err. We have

$$\Pr_{z_1^-,\ldots,z_k^-}\left[\#\{i \in [k] : u_i^\top z_i^- > |v_i|\} \text{ is odd}\right] = \frac{1}{2} - \frac{1}{2}\prod_{i=1}^k (1 - 2\Pr_{z_i}[u_i^\top z_i^- > |v_i|])$$

$$= \frac{1}{2} - \frac{1}{2}\prod_{i=1}^k \Pr_{z_i}[|u_i^\top z_i^-| \le |v_i|]. \tag{13}$$

We can bound this expression using the Berry-Esseen theorem (Berry, 1941; Esseen, 1942). Let $\beta \sim N(0, \|u_i\|_2^2)$. Then, the Berry-Esseen theorem states that there is a constant c (which in practice can be .56) such that for any $i \in [k]$,

$$\left|\Pr_{z_i}[|u_i^\top z_i^-| \le |v_i|] - \Pr[|\beta| \le |v_i|]\right| \le \frac{c\|u_i\|_\infty}{\|u_i\|_2^3}$$

and we can use the characterization

$$\Pr[|\beta| \le |v_i|] = \text{erf}\left(\frac{|v_i|}{\|u_i\|_2 \sqrt{2}}\right).$$

Plugging this into equation 13, we obtain the lower bound on err. $\square$

First, we'll apply Lemma 6 and Lemma 7 to the situation where the w_i's have ± 1 initialization. This generalizes Theorem 6.

Corollary 11. *Suppose all the weights in a disjoint-Polynet are initialized randomly in ± 1 and $k \ge 3$.*

Let $T(\alpha) := \arg\sup_{t \ge 0}(\text{err}(w_{1:k}(t)) \ge \alpha$. Then, for $\gamma \in (0, 1/2)$, if $\prod_i v_i(0) > 0$ (which happens w.p. 1/2),

$$\frac{T(1/2 - \gamma)}{T(0)} = 1 - O((n')^{1-k/2} \cdot \gamma^{2/k-1}).$$

Thus, even for γ arbitrarily close to 0, when the input is sufficiently long, the network spends almost all of training with error above $1/2 - \gamma$.

Proof. For ± 1 initialization,

$$\frac{\|u_i\|_\infty}{\|u_i\|_2^3} = (n')^{-3/2}$$

so by Lemma 7,

$$\mathsf{err}(w_{1:k}(t)) \geq \frac{1}{2} - \frac{1}{2} \prod_{i=1}^k \left(\mathrm{erf}\left(\frac{|v_i(t)|}{\sqrt{2n'}} \right) + c(n')^{-3/2} \right)$$

$$\geq \frac{1}{2} - \frac{1}{2} \prod_{i=1}^k \left(\sqrt{\frac{2}{\pi n'}} \cdot |v_i(t)| + c(n')^{-3/2} \right)$$

for some $c > 0$.

By Lemma 6, $|v_i(t)| \leq b$ for all i whenever

$$t \leq \frac{1}{k-2} \left(1 - b^{2-k} \right).$$

Setting

$$b = \sqrt{\pi n'/2} \left(\gamma^{1/k} - c(n')^{-3/2} \right),$$

we obtain that $T(1/2 - \gamma) = \frac{1}{k-2}(1 - O((n')^{1-k/2} \cdot \gamma^{2/k-1}))$.

Also by Lemma 6, using the language of that lemma statement, for all i

$$T_i(\infty) - T_i(b) \leq \frac{1}{k-2} \cdot b^{2-k} = \frac{1}{k-2} \cdot O((n')^{1-k/2} \cdot \gamma^{2/k-1}).$$

Once all the relevant weights have exploded to infinity, the error of the network will have zero error, so the result follows. $\qquad \square$

Now let us apply Lemma 6 and Lemma 7 to the situation where the w_i's have standard normal initialization. Again we find that with high probability, the phase of learning with near-trivial accuracy is much longer than the subsequent period until perfect accuracy, as illustrated by the left-hand plot in Figure 5.

Corollary 12. *Suppose all the weights in a disjoint-Polynet are initialized $\sim N(0,1)$, and $k \geq 3$. Then, conditioned on $\prod_i v_i(0) > 0$, with probability $1 - 1/\mathrm{poly}(n')$ over the randomness of the initialization, for $\gamma \in (0, 1/2)$,*

$$\frac{T(1/2 - \gamma)}{T(0)} = 1 - \tilde{O}((n')^{1-k/2} \cdot \gamma^{2/k-1}).$$

where $T(\cdot)$ is defined as in Corollary 11.

Proof. By a standard application of the generic Chernoff bound (Wainwright, 2019), for each $i \in [k], j \in [n'-1]$, we have

$$\Pr[|u_{i,j}| > \tau] \leq 2e^{-\tau^2/2} \quad \text{for all } \tau \geq 0.$$

Applying the union bound, we obtain

$$\Pr[\exists i, j \text{ s.t. } |u_{i,j}| > \tau] \leq 2n'k e^{-\tau^2/2} \quad \text{for all } \tau \geq 0.$$

This implies that w.p. $\geq 1 - \epsilon/2$,

$$\forall i: \quad \|u_i\|_\infty \leq \sqrt{2\log(4n'k/\epsilon)}. \tag{14}$$

For each i, $\|u_i\|_2^2$ follows a chi-squared distribution with $n' - 1$ degrees of freedom. By Laurent and Massart (2000), for any $\tau \geq 0$,

$$\|u_i\|_2^2 \in [(n'-1) - 2\sqrt{(n'-1)\tau}, (n'-1) + 2\sqrt{(n'-1)\tau} + 2\tau] \quad \text{w.p. } \geq 1 - 2e^{-\tau}.$$

Hence, w.p. $\geq 1 - \epsilon/2$,

$$\forall i : \quad \|u_i\|_2 = \sqrt{n'} + O(\sqrt{\log(k/\epsilon)}) \tag{15}$$

With probability $1 - \epsilon$ both $\|u_i\|_\infty$ and $\|u_i\|_2$ are bounded as above, in which case we obtain that for $\epsilon = 1/\text{poly}(n', k)$, and for some $c_1, c_2 > 0$,

$$\frac{\|u_i\|_\infty}{\|u_i\|_2^3} \leq \frac{c_1\sqrt{\log(n'k)}}{\left(\sqrt{n'} + c_2\sqrt{\log(n'k)}\right)^3} \leq \tilde{O}\left((n')^{-3/2}\right).$$

Plugging this into Lemma 7 gives us

$$\text{err}(w_{1:k}(t)) = \frac{1}{2} - \frac{1}{2}\prod_{i=1}^{k}\left(\text{erf}\left(\frac{|v_i(t)|}{\|u_i\|_2\sqrt{2}}\right) + O\left(\frac{\|u_i\|_\infty}{\|u_i\|_2^3}\right)\right)$$

$$\geq \frac{1}{2} - \frac{1}{2}\prod_{i=1}^{k}\left(\tilde{O}\left(\frac{|v_i(t)|}{\sqrt{n'}}\right) + \tilde{O}\left((n')^{-3/2}\right)\right).$$

Thus, we can choose $b = \tilde{\Omega}(\gamma^{1/k}\sqrt{n'})$ such that if $v_i(t) \leq b$ for all i, then $\text{err}(w_{1:k}(t)) \geq \frac{1}{2} - \gamma$. By Lemma 6, for all i,

$$T_i(b) \geq \frac{1}{k-2}\left(\bar{v}_a^{1-k/2} - (\bar{v}_a + b^2 - v_i(0)^2)^{1-k/2}\right) \geq \frac{1}{k-2}\left(\bar{v}_a^{1-k/2} - (b^2 - O(\log(k)))^{1-k/2}\right).$$

By the Chernoff bound, $\max_i |v_i(0)| \leq \sqrt{2\log(4k/\delta)}$ w.p. $\geq 1 - \delta/2$. And, by the same bound we used for $\|u_i\|_2^2$, we have that $\bar{v}_a = 1 + O(\sqrt{\log(1/\delta)/k})$ w.p. $1 - \delta/2$. Thus, for $\delta = 1/\text{poly}(k)$, we have that with probability $1 - \delta$,

$$T_i(b) \geq \frac{1}{k-2}\left(\tilde{\Omega}(1) - (b^2 - O(\log(k)))^{1-k/2}\right) = \frac{1}{k-2} \cdot \tilde{\Omega}(1). \tag{16}$$

Also by Lemma 6,

$$T_i(\infty) - T_i(b) \leq \frac{1}{k-2}(\bar{v}_g + b^2 - v_i(0)^2)^{1-k/2} \leq \frac{1}{k-2}(b^2 - v_i(0)^2)^{1-k/2}.$$

With probability $1 - 1/\text{poly}(k)$,

$$T_i(\infty) - T_i(b) \leq \frac{1}{k-2}(b^2 - O(\log(k)))^{1-k/2} = \frac{1}{k-2} \cdot \tilde{O}\left((n')^{1-k/2} \cdot \gamma^{2/k-1}\right). \tag{17}$$

Combining Equation 16 and Equation 17, we obtain the desired statement.

$\square$

B.3.2 SGD analysis

In this section we will analyze the training of a disjoint-PolyNet using SGD with online (i.i.d.) batches. We will show a convergence result for the 0-1 error of the learned classifier.

Theorem 13. *Assume we randomly initialize the disjoint-PolyNet with weights drawn uniformly from* $\{\pm 1\}$. *Fix* $\epsilon \in (0, 1/2)$ *and run SGD at any batch size* $B \geq 1$ *for* $T \geq 6\log(2nT/\delta)\log(2k/\epsilon)(3n' - 2)^{2k-1}$ *iterations. There exists an adaptive learning rate schedule, such that, with probability 1/2 over the randomness of the initialization and* $1 - \delta$ *over the sampling of SGD, the following holds:*

$$\text{err}\left(w_{1:k}^{(T+1)}\right) \leq \epsilon.$$

Proof. For simplicity of presentation, we will assume $B = 1$. Let the sample at iteration t be $(x^{(t)}, y^{(t)})$ where $x^{(t)} \sim \mathsf{Unif}(\{\pm 1\}^n)$ and $y^{(t)} = \chi_S^{(t)}(x^{(t)})$. Denote the population and stochastic gradient at time t as:

$$\widehat{g}_i^{(t)} = -y^{(t)} \left(\prod_{j \neq i} w_j^{(t)\top} x_j^{(t)} \right) x_i^{(t)}$$

$$g_i^{(t)} = - \left(\prod_{j \neq i} w_{j,1}^{(t)} \right) e_1$$

Observe that $|\widehat{g}_{i,j}^{(t)}|, |g_{i,j}^{(t)}| \leq \prod_{l \neq i} \|w_l^{(t)}\|_1$; note that this is also true when $B > 1$. Let the learning rate be $\eta_i^{(t)} = \frac{1}{2\sqrt{2T \log(2nT/\delta)} \cdot \prod_{l \neq i} \|w_l^{(t)}\|_1}$. Let $\Delta_{i,j}^{(t)} = \eta_i^{(t)}(g_{i,j}^{(t)} - \widehat{g}_{i,j}^{(t)})$ and $s_{i,j}^{(t)} = \sum_{\tau=1}^{t} \Delta_{i,j}^{(\tau)}$. Observe that $\mathbb{E}\,\Delta_{i,j}^{(t)} = 0$ and therefore $s_{i,j}^{(1)}, \ldots, s_{i,j}^{(t)}$ form a martingale. Furthermore, observe that

$$|s_{i,j}^{(t)} - s_{i,j}^{(t-1)}| = |\Delta_{i,j}^{(t)}| \leq \frac{|g_{i,j}^{(t)}| + |\widehat{g}_{i,j}^{(t)}|}{\sqrt{T \log(2nT/\delta)} \cdot \prod_{l \neq i} \|w_l^{(t)}\|_1} \leq \frac{1}{\sqrt{2T \log(2nT/\delta)}}$$

Then, for every $t < T$ and i, j, by the Azuma-Hoeffding inequality, with probability $1 - \frac{\delta}{nT}$, $|s_{i,j}^{(t)}| \leq 1/2$. By the union bound, w.p. at least $1 - \delta$, for every $t < T$ and all i, j it holds that $|s_{i,j}^{(t)}| \leq 1/2$. Let us assume this holds.

Claim 14. *For all $t \leq T + 1$, for $j > 1$, $|w_{i,j}^{(t)}| \leq 3/2$.*

Proof. Note that $w_{i,j}^{(t+1)} = w_{i,j}^{(1)} + s_{i,j}^{(t)}$, therefore, we have,

$$|w_{i,j}^{(t+1)}| \leq |w_{i,j}^{(1)}| + |s_{i,j}^{(t)}| \leq 3/2.$$

since $|w_{i,j}^{(1)}| = 1$ and $|s_{i,1}^{(t-1)}| \leq 1/2$. $\qquad\square$

Denote $\xi_i = \mathsf{sign}\left(w_{i,1}^{(1)}\right)$ and assume that $\prod_{j=1}^{k} \xi_j > 0$, and note that this happens w.p. $1/2$. We will assume this holds for the next lemma.

Claim 15. *For all $t \leq T + 1$ and $i \in [k]$ it holds that*

$$\xi_i w_{i,1}^{(t)} = |w_{i,1}^{(t)}| \geq \frac{1}{2} + \frac{1}{4\sqrt{2}} \left(\frac{1}{3n' - 2} \right)^{k-1} \sqrt{\frac{t-1}{\log(nT/\delta)}}.$$

Proof. Observe that the claim holds for $t = 1$ since $|w_{i,\cdot}^{(1)}| = 1$. By induction on t, assume the claim holds for all $\tau \leq t$. Now we will prove it holds for $t + 1$.

Observe that for all $\tau \leq t$, by the assumption:

$$g_{i,1}^{(\tau)} = -\prod_{j \neq i} w_{j,1}^{(\tau)} = -\xi_i \prod_{j \neq i} \xi_j w_{j,1}^{(\tau)} = -\xi_i \prod_{j \neq i} |w_{j,1}^{(\tau)}|.$$

Note that $w_{i,1}^{(t+1)} = w_{i,1}^{(1)} + \sum_{\tau=1}^{t} \eta_i^{(\tau)} \left(\prod_{j \neq i} w_{j,1}^{(\tau)} \right) + s_{i,1}^{(t)}$, then we have

$$\xi_i w_{i,1}^{(t+1)} = \xi_i w_{i,1}^{(1)} + \xi_i \sum_{\tau=1}^{t} \eta_i^{(\tau)} \left(\prod_{j \neq i} w_{j,1}^{(\tau)} \right) + \xi_i s_{i,1}^{(t)}$$

$$= 1 + \sum_{\tau=1}^{t} \left(\frac{1}{4\sqrt{2\tau \log(nT/\delta)}} \cdot \prod_{j \neq i} \frac{\xi_j w_{j,1}^{(\tau)}}{\|w_j^{(\tau)}\|_1} \right) + \xi_i s_{i,1}^{(t)} \tag{18}$$

$$\geq \frac{1}{2} + \frac{1}{2\sqrt{2T \log(2nT/\delta)}} \cdot \sum_{\tau=1}^{t} \left(\prod_{j \neq i} \frac{|w_{j,1}^{(\tau)}|}{\|w_j^{(\tau)}\|_1} \right) - |s_{i,1}^{(t)}| \tag{19}$$

$$\geq \frac{1}{2} + \frac{1}{2\sqrt{2T \log(2nT/\delta)}} \cdot \sum_{\tau=1}^{t} \left(\prod_{j \neq i} \frac{|w_{j,1}^{(\tau)}|}{|w_{j,1}^{(\tau)}| + \frac{3(n'-1)}{2}} \right) \tag{20}$$

$$\geq \frac{1}{2} + \frac{1}{2\sqrt{2T \log(2nT/\delta)}} \cdot \sum_{\tau=1}^{t} \left(\prod_{j \neq i} \frac{1}{1 + 3(n'-1)} \right) \tag{21}$$

$$\geq \frac{1}{2} \left(1 + \left(\frac{1}{3n'-2} \right)^{k-1} \frac{t}{\sqrt{2T \log(2nT/\delta)}} \right).$$

(18) follows from observing that $\xi_i w_{i,1}^{(1)} = |w_{i,1}^{(1)}| = 1$ and $\prod_{j=1}^{k} \xi_j = 1$. (19) follows from the inductive hypothesis $\xi_j w_{j,1}^{(\tau)} = |\xi_j w_{j,1}^{(\tau)}|$. (20) follows from our assumption that $|s_{i,1}^{(t)}| \leq 1/2$ and Claim 14.(21) follows from the inductive hypothesis $|w_{i,1}^{(\tau)}| \geq 1/2$. $\qquad \square$

Setting T such that $T \geq 2 \log(2nT/\delta)\alpha^2(3n'-2)^{2k-2}$ for $\alpha = 3\sqrt{(n'-1)\log(2k/\epsilon)} - 1$, from the above claims, after iteration T, we have

$$w_{i,1}^{(T+1)} \geq \frac{\alpha+1}{2}$$
$$w_{i,j}^{(T+1)} \leq 3/2 \text{ for } j > 1.$$

Using Lemma 7, we have with probability $1 - \delta$,

$$\text{err}(w_{1:k}^{(T+1)}) \leq 2k \exp\left(-\frac{(\alpha+1)^2}{9(n'-1)} \right) = \epsilon.$$

$$\square$$

C   Additional figures, experiments, and discussion

This section contains our unabridged empirical results, visualizations, and accompanying discussion. Additional example training curves (like the assortment in Figure 1 *(left)*) are shown in Figure 6; more examples can be found in the subsections below.

Convergence times, success probabilities, and scaling laws.   We first present the full empirical results outlined in Section 3 of the main paper. Figure 7 shows convergence times t_c on small parity instances for all of the architecture configurations enumerated in Section 3.1. In some of these settings, t_c exhibits high variance due to unlucky initializations (see Figure 8); thus, we report 10^{th} percentile convergence times. Figure 9 gives coarse-grained estimates for how t_c scales with (n, k), based on small examples. For selected architectures, Figure 10 shows how these convergence times scale with n and k more precisely: for small n, power law relationships $t_c \propto n^{\alpha \cdot k}$ (for small constants α) are observed for all configurations. Note that for larger n, the exponent (i.e. the slope in the log-log plot) increases: with a constant learning rate and standard training, the $n^{\Theta(k)}$ does not continue indefinitely. All additional details are in Appendix D.

Figure 6: Additional training curves (on the $(50, 3)$-parity problem, except the first row); full details are in Appendix D.1.6. *1st row:* The same architecture, initialization, and training algorithm (a width-100 ReLU MLP in this case), without an explicit sparse prior, adapts to the computational difficulty parameters n, k. *2nd row:* Our positive empirical results hold over a wide range of batch sizes B, all the way down to $B = 1$. Training is unstable (more outliers) at very large and very small batch sizes. *3rd row:* Even the least overparameterized neural networks, which are barely wide enough to represent parity, converge with reasonable probability (sometimes failing to reach a global minimum). *4th row:* Larger models (width-1000 MLPs and $d_{emb} = 1024$ Transformers) are robust to a wide range of batch sizes. Note the lack of plateaus in setting (vi), which is revisited in Appendix C.8.

Guide to this section. The remainder of Appendix C expands on the various discussions and figures from Sections 4 and 5.

- Appendix C.1 gives experimental evidence that Fourier gaps are present at iterates w_t and initializations w_0 other than sign vectors, as well as for activation functions other than ReLU. This suggests that the feature amplification mechanism is robust, and illuminates directions for strengthening the theoretical results.

- Appendix C.2 discusses how the building blocks of deep learning (activation functions, biases, initializations, learning rates, and batch sizes) play multiple, sometimes conflicting roles in this setting.

- Appendix C.3 provides additional white-box visualizations of hidden progress from Figure 3.

- Appendix C.4 explores the implications of the feature amplification mechanism for scaling model size– namely, unlike random search, large width does not impart parallel speedups.

- Appendix C.5 shows that our results hold in the finite-sample setting (allowing for multiple passes over a training set of size m). In particular, we show that in low-data regimes, the models exhibit the *grokking* phenomenon.

- Appendix C.6 extends our results to *noisy* parities (which comprise the true "emblematic computationally-hard problem").

Figure 7: 10th percentile convergence times t_c of SGD (with $n = 30$, hinge loss, uniform initialization, and best learning rate $\eta \in \{1, 10^{-1}, 10^{-2}, 10^{-3}\}$), for various architectures, parity degrees k, and batch sizes B. See Appendix D for full details.

Figure 8: Percentage of converged runs ($t_c < 10^5$) out of 25 random trials, with the same architectures and training parameters as Figure 7. With sufficiently large batch sizes, training is extremely robust in settings (i) through (xv).

Figure 9: Coarse scaling estimates for the 10th percentile convergence time of SGD (with hinge loss, uniform initialization, and best learning rate) on every architecture: c, α such that $t_c \leq c \cdot (n - n_0)^\alpha$ on small parity instances $n \in \{10, 20, 30\}, k \in \{2, 3, 4\}$. Missing entries denote cases where $< 10\%$ of trials were convergent for any n (see Figure 8). Boxes are colored according to α. See Appendix D for full details.

Figure 10: Finer-grained plots of convergence times for selected architecture configurations, for $n \in \{10, 11, \ldots, 39, 40\}$ and $k \in \{2, 3, \ldots, 8\}$. Medians over 1000 runs are shown, with 95% bootstrap confidence intervals. *Top row:* standard MLP configurations (i) through (vi). *Bottom row:* Miscellaneous settings (1-neuron networks; Transformers; larger n). For details on each setting, see Appendix D.1.7.

Fourier gap Γ for ReLU activation

Figure 11: Distributions of exact Fourier gaps $\Gamma_{\sigma,k}(w)$ when $\sigma = \mathrm{ReLU}$, and w is an i.i.d. {uniform, Gaussian} random vector. These are derived from the Fourier coefficients of the corresponding random LTFs, computed here in exponential time for $n = 15$.

- Appendix C.7 introduces a counterexample for "layer-by-layer learning", using parity distributions whose degrees are higher than those of the individual layers' polynomial activations. Preliminary experiments show that standard training works in this setting.
- Appendix C.8 presents examples of training curves for wide polynomial-activation MLPs, where, unlike the other settings, there is no initial plateau in the model's error.

C.1   Fourier gaps at initialization and SGD iterates

Proposition 10 shows that if the function $x \mapsto \sigma'(w_0^\top x)$ has a Fourier gap at S, then S can be identified from a batch gradient at initialization w_0 with $B = O(1/\gamma^2)$ samples. Our end-to-end result (Theorem 4) requires ReLU activations and sign vector initialization, because the Fourier gap condition (Definition 1) arises from exact formulas for the Fourier coefficients of the majority function. Stronger end-to-end theoretical guarantees would follow from analogous Fourier gaps in more general population gradients. This requires $x \mapsto \sigma'(w^\top x)$ to satisfy these conditions simultaneously:

- *Fourier concentration:* upper bounds on the degree-$(k+1)$ coefficients $\widehat{f}(S \cup \{i\})$, for $i \notin S$. The term is borrowed from Klivans et al. (2004), who use upper bounds on Fourier coefficients of LTFs to approximate them (thus, learn halfspaces) with low-degree polynomials.

- *Fourier anti-concentration:* lower bounds on the degree-$(k-1)$ coefficients $\widehat{f}(S \setminus \{i\})$, for $i \in S$.

A natural question is: *which Boolean functions, other than majority, satisfy the γ-Fourier gap property at S, for $\gamma \geq n^{-\Omega(k)}$?*

We present some numerical evidence for large Fourier gaps in functions $x \mapsto \sigma'(w^\top x)$ other than majority, which arise from gradients of architectures other than ReLU MLPs with sign initialization. This shows that the mechanism of feature emergence is empirically robust in settings not fully explained by our current theory. Establishing corresponding theoretical guarantees would enable stronger end-to-end global convergence guarantees for MLPs and other architectures.

In these experiments, population gradients were computed by brute force integration over all 2^n Boolean inputs $x \in \{\pm 1\}^n$. In all cases, for various choices of σ, w, we measure a slightly relaxed notion of Fourier gap Γ in the population gradient:

$$\Gamma_{\sigma,k}(w) := \max_{i \in [k]} |g_i| - \max_{i \notin [k]} |g_i|, \qquad g := \mathbb{E}[yx\, \sigma'(w^\top x)].$$

If $\Gamma > 0$, then *one*[16] coordinate from the parity can be identified from $O\left(\frac{\log n}{\Gamma^2}\right)$ samples of the gradient at w.

Random LTFs.   For ReLU activations and symmetric Bernoulli (i.e. random sign) initialization $w_i \sim \mathrm{Unif}(\{\pm c\}^n)$, the Fourier coefficients are the same as those of majority; thus, there is a Fourier gap of $\gamma \geq n^{-\Omega(k)}$ at every set S (and the same is true of Γ). We probe the Fourier gaps of linear threshold functions (LTFs) under other ubiquitous initializations: i.i.d. uniform and Gaussian. These are shown in Figure 11, which indicates (at least for small n, k) that the Fourier gap is comparable to that of majority with non-negligible probability.

---

[16]Replacing the first $\max$ in the definition of Γ with $\min$ would give us the same notion of Fourier gap as Definition 1: if *all* the relevant coordinates are larger than *all* of the irrelevant ones, estimating the population gradient allows us to recover the relevant coordinates.

Figure 12: Numerical evidence for Fourier gaps beyond random LTFs. *Left:* Fourier gaps of exact population gradients $\mathbb{E}_{\mathcal{D}_S}[y x_i \sin(w^\top x/\sqrt{n})]$ induced by sinusoidal activations, for random initializations w. In these small cases, they are comparable the the Fourier gaps of majority (red dashed line). *Right:* Fourier gaps of a sinusoidal neuron's population gradients along the SGD optimization path (10 trials shown). The Fourier gap is consistently positive at initialization, but somewhat smaller than that of majority (red dashed line). Interestingly, it amplifies through the course of training.

Random non-LTFs. The successful convergence of architectures with smoother activations (in the parity setting and beyond) motivates the question of whether large Fourier gaps are present in population gradients corresponding to functions other than LTFs. Figure 12 *(left)* shows that this is the case for sinusoidal activations.

Boolean functions along the SGD path. Finally, to further close the gap between Theorem 4 and the empirical results, it is necessary to address the fact that SGD accumulates gradients with respect to *time-varying* iterates, while our analysis approximates this using a large-batch gradient at a static iterate w_0. In fact, SGD seems to help in some cases: Figure 12 *(right)* shows that when training a sinusoidal neuron, SGD amplifies the initial Fourier gap.

C.2 Counterintuitive roles of the building blocks of deep learning

Even in this simple problem setting, the simultaneous computational and statistical considerations lead to counterintuitive consequences for the optimal configurations of architectures and algorithms for this setting. We encountered the following, in the search for architecture configurations for the empirical study:

- *Activation functions.* This mechanism of features emerging via Fourier gaps (see Definition 1) is strongest with non-smooth activations such as the ReLU, whose derivatives are discontinuous threshold functions. This is an orthogonal consideration to representational capacity and mitigation of local minima (under which one might conclude that degree-k polynomial activations are optimal). In summary, in feature learning settings where the Fourier gaps and low-complexity solutions are simultaneous relevant, there is a *sharpness-smoothness tradeoff* for the activation function.

- *Biases.* The symmetry of the majority function (as well as all unbiased LTFs) causes its even-degree Fourier coefficients to be zero; thus, certain variants of the setups in Section 3 fail for odd k. Bias terms (trainable or fixed) are necessary to break this symmetry, in theory and practice. Simultaneously, biases serve the more conventional role of shifting the loss surface; see Section D.1.2 for how this affects the details of how the biases were chosen in the experiments.

- *Initializations.* The role of the initialization distribution is similarly twofold in this setting: w_0 should be close to the desired solution w^*, but it must also be selected such that SGD will

successfully amplify the Fourier gap. A third consideration, which we do not attempt to study in this work, is that multiple randomly-initialized neurons will tend to learn the correct features at different times (see the weight trajectory visualizations in Figure 3 and Figure 13, as well the staircase-like training curves seen for MLPs in Figure 1 *(left)*). We expect this *symmetry breaking* phenomenon to be present in more complex feature learning settings. Finally, as shown in the training curves from setting (vi) in Figure 6, and in more detail in Appendix C.8, the choice of activation function influences the qualitative behavior of the training curves: namely, whether the plateaus disappear at large widths and batch sizes.

- *Batch sizes and learning rates.* The empirical and theoretical results both suggest that SGD uses independent samples to gradually amplify a signal containing the correct features in the initial population gradient of the correlation $\left(\nabla_w \mathbb{E}[-yx_i\sigma'(w^\top x)]\right)|_{w=w_0}$. However, it would be truer to this mechanism to stay at the initialization w_0 until the algorithm has accumulated enough data to discern the correct indices (equivalently, scale up the batch size); in contrast, standard training takes gradients with respect to w_t along the SGD path. We hypothesize that the bias incurred by this drifting w_t (and thus drifting population gradient) accounts for the degradations seen in Figure 2 *(right)* and Figure 10. However, Figure 12 *(right)* shows that the movement of SGD can be helpful, amplifying the Fourier gap.

C.3 Hidden progress measures

In this section, we provide an expanded discussion and plots for the investigations outlined in Figure 3 and the *"hidden progress measures"* section in Section 5.

For a neural network training pipeline which outputs a sequence of iterates $\theta_0, \ldots, \theta_T \in \Theta$, we define a *progress measure* $\rho : \Theta \to \mathbb{R}$ to be any function of the training algorithm's state[17] which is predictive of the time to convergence (i.e. conditioned on θ_t, the random variables ρ and $t_c - t$ are not independent). By this definition, the only algorithms which have no progress measures are those whose convergence times t_c are *memoryless* (independent of θ_t).

Note that many trivial progress measures exist: an example to keep in mind is that for the algorithm which exhaustively enumerates over a deterministic list of hypotheses (say, the possible k-element subsets S in lexicographical order) and terminates when it finds the correct one, the current iteration t is a progress measure. Thus, the purpose of demonstrating hidden progress measures ρ is *not* to provide further evidence that SGD finds the features using Fourier gaps. Rather, it is to (1) further refute the hypothesis of SGD performing a memoryless Langevin-like random search, and (2) provide a preliminary exploration of how progress can be quantified even when the natural metrics of loss and accuracy appear to be flat.

Fourier gaps over time. The Fourier gap visualizations in Section C.1 already provides an example of a quantity which varies continuously as the model trains, despite no apparent progress in the loss and accuracy curves. However, none of our theoretical analyses capture the empirical observation that this quantity tends to amplify over time. Below, we consider other quantities which reveal hidden progress in parity learning, which are more straightforward and closer to our analyses.

Weight movement. The most direct observation of hidden progress simply comes from the movement of the neurons' weights at the relevant indices: that is, for a single neuron's weights $w_t \in \mathbb{R}^n$, the quantity $\rho([w_t]_i) : i \in S$. In the main paper, Figure 3 *(left, center)* directly visualizes the evolution of the weights w_t for a single sinusoidal neuron (with a bias, but no second layer). Figure 13 supplements these plots from the main paper with additional plots of weight trajectories, at different batch sizes B, as well as a width-10 MLP architecture.

ℓ_∞ **path length.** Finally, we present an example of a *single* measurement of the optimization path which captures hidden progress in this setting, which can be plotted alongside loss and accuracy curves. For any iterates of a neuron's weights $w_t \in \mathbb{R}^n$, we choose the ∞-norm of the movement from initialization: $\rho(w_{0:t}) := ||w_t - w_0||_\infty$. We present a brief intuitive sketch of the motivation for this choice of $\rho(\cdot)$, and some additional visualizations.

---

[17]In addition to the model's parameters, the full state of the training procedure should also include the auxiliary variables defined by the optimization algorithm; two ubiquitous ones in deep learning are the momentum vector and the adaptive preconditioner. Here, we only consider vanilla SGD, which maintains no auxiliary variables.

Figure 13: Supplementary plots for visualizations of the optimization trajectory w_t, and the hidden progress measure $\rho(w_{0:t})$. In the MLP plots, the single scalar ρ is the ∞-norm of the entire first layer W, and weights are color-coded by row (i.e. neuron). With small batch sizes $B \in \{1, 4\}$, per-iteration losses are averaged over a short window (lengths 16 and 4, respectively).

From the theoretical analysis, under the approximation $\nabla \ell(w_t) \approx \nabla \ell(w_0)$ (so that feature learning is performed by estimating the initial population gradient to high precision), we can think of the i-th coordinate of w_t as a biased random walk with constant variance σ^2; the Fourier gap condition entails that biases β_i of these random walks are large when $i \in S$. Then, this choice of ρ is an estimate for the drift term $t \cdot \max_i |\beta_i|$, which is larger than the $\sigma \sqrt{t}$ contribution of the variance for sufficiently large t.

This progress measure is shown alongside the loss curves in Figure 13, in red. We do not attempt to characterize the dynamics of ρ; we only note that they are clearly distinguishable from the maximum of n unbiased random walks, even when SGD appears to make no progress in terms of loss and accuracy. Studying hidden progress measures in deep learning more quantitatively, as well as in more general settings, presents a fruitful direction for future work.

C.4 Convergence time vs. width

We provide supplementary plots for the experiment outlined in Figure 4 *(left)*, which probes whether extremely large widths ($r \gg n^k$) afford factor-r parallel speedups of the parity learning mechanism (as one would expect from random search). On 3 parity instances $n \in \{30, 40, 50\}, k = 3$, we varied the width $r \in \{1, 2, 3, \ldots, 9, 10, 30, 100, 300, \ldots, 10^6, 3 \times 10^6\}$, keeping all other parameters the same ($B = 128, \eta = 0.1$).

Figure 14: Number of iterations for MLPs (with standard initialization and training) to converge on sparse parity problems, in terms of width r. Boxes denote interquartile ranges over 1000 runs; whiskers denote $\pm 1.5 \cdot$IQR; $\times$ markers denote minimum and maximum outliers. Underparameterized models ($r < k$) are shown in red, and considered "converged" at 55% accuracy. Scaling r this way does not lead to $r\times$ parallel speedups, like the expected success time for r copies of random search (shown in green for comparison).

Results. We did not find evidence of such parallel speedups over 1000 runs in each setting; see Figure 14. This serves as further evidence that the mechanism by which standard training solves parity is best understood as deterministic and sequential, rather than behaving like random search over size-k subsets. A benefit of width appears to be *variance reduction*: the upper tail of long convergence times is mitigated by a large number of randomly-initialized neurons.

C.5 Learning and grokking in the finite-sample case

We provide some supplementary plots for the experiments outlined in Figure 4 *(right)*. In these settings, a fixed architecture (width-100 MLP with ReLU activations) is trained with minibatch SGD in an otherwise fixed configuration (hinge loss, learning rate $\eta = 0.1$, batches of size $B = 32$) on a finite training sample of size m. We also vary a *weight decay* parameter λ.

As shown in Figure 15, the weight decay parameter λ modulates a delicate computational-statistical tradeoff: it improves generalization (expanding the range of m for which training eventually finds the correct solution), but the model fails to train at large values of λ. For small m and appropriately tuned λ, we observe *grokking*: the model initially overfits the training data, but finds a classifier that generalizes after a large number of iterations.

C.6 Learning noisy parities

The other empirical results in this work focus on noiseless parity distributions $\mathcal{D}_S$, to reduce the number of sources of variance and degrees of freedom. However, the setting of *random classification noise* is important for several reasons. In this section, we briefly demonstrate that our results extend to this case. Let $\mathcal{D}_S^{(\epsilon)}$ denote the (n, k, ϵ)-*noisy parity distribution*, defined by flipping the labels in the (n, k)-parity distribution $\mathcal{D}_S$ independently with probability $\frac{1}{2} - \epsilon$. Note that when $\epsilon = 0$, the labels are completely random (thus, S cannot be learned). By a standard PAC-learning argument, when $0 < \epsilon \le \frac{1}{2}$, the statistical limit for identifying S from i.i.d. samples from $\mathcal{D}_S$ scales as $\Theta\left(\frac{k \log n}{\epsilon^2}\right)$.

Motivations. First, learning parities from *noisy* samples is the true "emblematic computationally-hard distribution". Without noise, there is a non-SQ algorithm which avoids the exponential-in-k computational barrier: Gaussian elimination can identify S in $O(n^3)$ time and $\Theta(n)$ samples. Second, viewing parities as an idealized setting in which to understand training dynamics, resource scaling, and emergence in deep learning, it is important to see that this phenomenon is robust to label noise.

Theory. It is easy to incorporate label noise into the theoretical analysis, which works with correlations of the form $\mathbb{E}_{\mathcal{D}_S}[y\, f(x)]$; each coordinate of the population gradient of the correlation loss is a

Figure 15: Supplementary plots for the finite-sample setting. The same configuration (width-100 ReLU MLP, $B = 32, \eta = 0.1$) varying the sample size m (decreasing from left to right) and weight decay λ (increasing from top to bottom). When m is sufficiently large (much larger than the statistical threshold $\Theta(k \log n)$), generalization error is negligible. When m is too small, the model fails to train. In between, we observe eventual convergence to the correct solution, with training curves exhibiting the *grokking* phenomenon. Weight decay governs a statistical-computational tradeoff in this setting: larger λ improves generalization, but can cause optimization to fail (bottom row).

quantity of this form. In the noisy case, these quantities are replaced with

$$\mathbb{E}_{(x,y)\sim\mathcal{D}_S^{(\epsilon)}}[y\,f(x)] = \epsilon \cdot \mathbb{E}_{(x,y)\sim\mathcal{D}_S}[y\,f(x)].$$

In particular, when architecture's population gradient has a Fourier gap with parameter γ in the noiseless case implies a Fourier gap with parameter $\epsilon \cdot \gamma$.

Experiments. We find that the experimental findings are robust to label noise, in the sense that models are able to obtain nontrivial (and sometimes 100%) accuracy; see Figure 16 for some training curves under various settings of ϵ. This provides concrete evidence against the (already extremely dubious) hypothesis that neural networks, with standard initialization and training, learn noiseless parities by implicitly simulating an efficient algorithm such as Gaussian elimination. Note that with a constant learning rate (here, $\eta = 0.1$) and label noise, the iterates of SGD do not always converge to 100% accurate solutions.

C.7 Counterexample for layer-by-layer learning

Notation. Consider an L-layer MLP with activation σ, parameterized by weights and biases

$$\theta = (W_1, b_1, \ldots, W_{L-1}, b_{L-1}, u),$$

and defined by

$$f_{\mathsf{mlp}}(x; \theta) := (f_L \circ f_{L-1} \circ \cdots \circ f_2 \circ f_1)(x),$$

where f_i denotes the function $z \mapsto \sigma(W_i z + b_i)$ for $1 \leq i \leq L - 1$, and f_L denotes $z \mapsto u^\top z$. The shapes of the parameters W_i, b_i, u are selected such that each function composition is well-defined.

Figure 16: Training curves (over 5 random seeds) for a width-100 ReLU MLP on noisy $(50, 3, \epsilon)$-parity learning problems at various batch sizes B and noise levels (flipping labels with probability p, so that $\epsilon = 1 - 2p$). The models learn the features and converge successfully (measured by accuracy on the noiseless distribution), even with 49% of labels flipped randomly (i.e. $\epsilon = 0.01$). This is a preliminary illustration that the phenomena investigated in this paper are robust with respect to i.i.d. label noise. Note that the scale of t is much larger for small batches and high noise.

Let the *intermediate activations* at layer i be denoted by

$$z_i(x; \theta) := (f_i \circ \ldots \circ f_1)(x).$$

Finally, r_i (the *width at layer i*) refers to the dimensionality of z_i as defined above.

Construction where layer-by-layer learning is impossible. Notice that when σ is a degree-2 polynomial (say, $\sigma(z) = z^2$), an L-layer MLP can represent parities up to degree 2^{L-1}– for example, a 3-layer MLP (which composes quadratic activations twice) can represent a 4-sparse parity as a 2-sparse parity of 2-sparse parities. However, Equation (2) implies the following:

- An individual layer cannot represent a parity of $k > 2$ inputs.
- The population gradient (as in Equation (5) is zero (since every coordinate of the gradient is the correlation between a k-wise parity and a polynomial of degree 2).

Thus, this setting serves as an idealized counterexample for layer-by-layer learning: if SGD succeeds on parities with higher degree than the architecture's polynomial activations, it must do so by an end-to-end mechanism. Intuitively, earlier layers can only make progress by *knowing how their outputs will be used downstream*. Concretely, consider the population gradient of the correlation loss, with respect to a first-layer neuron's weights $w := (W_1)_{j,:}$. With layer-by-layer training, this

gradient contains no information:

$$\nabla_w \mathbb{E}[-yx_i \underbrace{\sigma'(w^\top x)}_{\text{degree 1}} u_j] = 0.$$

However, in end-to-end training, the presence of downstream layers removes this barrier:

$$\nabla_w \mathbb{E}\Big[-yx_i \underbrace{\sigma'(w^\top x)}_{\text{degree 1}} \underbrace{\frac{\partial f_L \circ \ldots \circ f_2}{\partial (z_1)_j}}_{\text{degree } 2^{L-2}-1} \Big],$$

giving the gradient greater representation capacity (in terms of polynomial degree). The question remains of whether end-to-end training works in this setting, which we resolve positively in small experiments.

Results: end-to-end training works empirically.   We empirically observed successful training (to 100% accuracy) in a few settings (with SGD, learning rate $\eta = 0.01$, batch size $B = 32$, and default uniform initialization as described in Appendix D.1):

- $L = 3, n \in \{10, 20, 30\}, k \in \{1, 2, 3, 4\}$. Small widths suffice: $(r_1, r_2) = (2, 1)$. Over 10 random seeds, all models converged within 20000 iterations.

- $L = 4, n \in \{10, 20, 30\}, k \in \{1, 2, 3, 4, 5, 6\}$. Widths were chosen to be slightly larger for stability: $(r_1, r_2, r_3) = (10, 10, 1)$. Over 10 random seeds, all models converged within 50000 iterations. Additionally, models trained on $(n, k) \in \{(10, 7), (20, 7), (30, 7), (10, 8)\}$ converged within 500000 iterations.

As a sanity check, the models failed to converge in experimental setups where $k > 2^{L-1}$: ($L = 2, k \geq 3$) and ($L = 3, k \geq 5$).

Discussion.   This construction serves as a simple counterexample to the *"deep only works if shallow is good"* principle of Malach and Shalev-Shwartz (2019), demonstrating a case where a deep network can get near-perfect accuracy even when greedy layerwise training (e.g. (Belilovsky et al., 2019)) cannot beat trivial performance. It remains to characterize these positive empirical results theoretically, as well as to investigate whether there are pertinent analogues in real data distributions.

C.8   Lack of plateaus for wide polynomial-activation MLPs

An interesting qualitative observation from the training curves in Figure 6 is that the validation accuracy curves in setting (vi) (width-1000 polynomial-activation MLPs) do not follow the same "plateau" or "staircase" pattern as the others. Figure 17 shows a few additional examples of training curves for polynomial-activation MLPs, varying the width r and batch size B. We find that the rate of descent of the validation error increases with both of these parameters; note that this does not occur with ReLU activations (where there are sharp phase transitions between plateaus at all batch sizes).

This constitutes an exception to this paper's theme of "hidden progress" behind flat loss (or error) curves: with enough overparameterization *and* "over-sampling", the continuous progress of SGD in this setting is no longer hidden, and manifests in the training curves. This phenomenon seems to be specific to certain activation functions (i.e. x^k but not ReLU); we leave it for future work to understand why and when it occurs, as well as potential practical implications.

D   Details for all experiments

D.1   Deep learning configurations

Losses.   Our "robust space" of empirical results use the following loss functions:

- Hinge: $\ell(y, \widehat{y}) := (1 - y\widehat{y})_+$.
- Square: $\ell(y, \widehat{y}) := (y - \widehat{y})^2$.
- Cross entropy: $\ell(y, \widehat{y}) := -\log \frac{e^{y\widehat{y}}}{1 + e^{y\widehat{y}}}$.

Figure 17: Additional training curves for polynomial-activation MLP architectures (iv), (v), (vi), on the (50, 3)-sparse parity problem. Unlike the other architectures, these settings exhibit continuous progress when the width r and batch size B are large.

Additionally, the theoretical analysis considers the *correlation loss* $\ell(y, \widehat{y}) := -y\widehat{y}$.

In the configurations corresponding to all of the figures and convergence time experiments, we used the hinge loss. This was a relatively arbitrary choice (i.e. they appeared to be interchangeable upon running small experiments); an advantage of the hinge and square losses over cross entropy is that for architectures that can realize the parity function, there is a zero-loss solution with finite weights.

Initializations. Our empirical results use the following i.i.d. weight initializations:

- Uniform on the interval $[-c, c]$, where the scale c is chosen for all affine transformation parameters using the "Xavier initialization" convention (Glorot and Bengio, 2010). The experiments are quite tolerant to the particular choice of c (as these are not deep networks); this choice, which is the default in deep learning packages, emphasizes that our positive empirical results hold under a *standard* initialization scheme.

- Gaussian with mean 0 and variance σ^2, selected using the "Kaiming initialization" convention (He et al., 2015).

- Bernoulli (i.e. random sign) initialization: the discrete distribution $\mathrm{Unif}(\{-c, c\})$, for the same choice of c as for the uniform distribution.

D.1.1 2-layer MLPs

We consider 2-layer MLPs $f(x; W, b, u) = u^\top \sigma(Wx + b)$ for two choices of activations:

- ReLU: $\sigma(z) := (z)_+ = \max(0, z)$.
- Degree-k polynomial: $\sigma(z) := z^k$.

In both cases, whenever $r \geq k$ (and, in the case of polynomial activations, choosing the degree to be k), there exists a width-r MLP which can represent k-sparse parities: for all (n, k) and $|S| = k$, there is a setting of W, b, u such that $f(x; W, b, u) = \chi_S(x)$.

Note that if the output $f(x; \theta)$ is a degree-$k' < k$ polynomial in x (e.g. an MLP with $\sigma(z) = z^{k'}$ activations), the architecture is incapable of representing a parity of k inputs. In fact, it is incapable of representing any function that has a nonzero correlation with parity; this follows from orthogonality (Equation (2)).

Figure 18: Visualizations of all activation functions considered in this work. As discussed in Section D.1.2, care must be taken to ensure that the architectures can realize sparse parities with the same bias b (in particular, $b = 0$) across varying k. Multiple k-dependent displacements are shown for the ∞-zigzag and sinusoidal activations.

D.1.2 Single neurons

To explore the limits of concise parameterization for architectures capable of learning parities, we propose a variety of non-standard activation functions which allow a single neuron to learn sparse parities. These constructions leverage the fact that the parity is a nonlinear function of the sum of its inputs $w_S^\top x$, where $w_S := \sum_{i \in S} e_i$.

k**-zigzag activation.** $\sigma(\cdot)$ is the piecewise linear function which interpolates the $k + 1$ points $\{(k, +1), (k - 2, -1), (k - 4, +1), \ldots, (-k + 2, \pm 1), (-k, \mp 1)\}$ with k linear regions $\{(-\infty, -k], [-k, -k + 2], \ldots, [k - 2, k], [k, +\infty)\}$. Then, $\sigma(w_S^\top x) = \chi_S(x)$.

Oscillating polynomial activation. $\sigma(\cdot)$ is the degree-k polynomial which interpolates the same points as above.

∞**-zigzag activation.** The *infinite* extension of the zigzag activation is the *triangle wave* function $\sigma(\cdot)$ which linearly interpolates the infinite set of points $\bigcup_{i \in \mathbb{Z}} \{(2i, +1), (2i + 1, -1)\}$. This can express parities of *arbitrary* degree. The $+1$ and -1 can be swapped (resulting in an activation which is equivalent when shifted by a bias term). However, in our experiments, we choose the sign convention depending on k such that $\sigma(w_S^\top x) = +1$. This allows different convergence time curves to be more directly comparable across different k, since it removes the effects of the bias of the global minimizer alternating with k.

Sinusoidal activation. $\sigma(z) := \sin(z)$. The sinusoidal neuron $\sin(w^\top x + b)$ can also express parities of arbitrary degree, since it can interpolate the same set of points as the ∞-zigzag activation. In the experiments, we pick a shift β and use the activation $\sigma(z) := \sin(\frac{\pi}{2} z + \beta)$, such that $\sigma(z)$ interpolates the same points as the sign convention selected for the ∞-zigzag activation. In the experiments in Section 3, the sinusoidal activation is additionally scaled by a factor of 2 ($z \mapsto \sigma(2z)$); this is interchangeable with scaling the learning rate and initialization, and is done to obtain more robust convergence in the particular setting of $(n, k) = (50, 3)$.

Figure 18 visualizes all families of activations considered in this paper.

D.1.3 Parity Transformer

The Transformer experiments use a slightly simplified version of the architecture introduced in (Vaswani et al., 2017). In particular, it omits dropout, layer normalization, tied input/output embedding weights, and a positional embedding on the special [CLS] token. Including these does not change the results significantly; they are all present in the preliminary findings in (Edelman et al., 2021) (in which an "off-the-shelf" Transformer implementation successfully learns sparse parities). We specify the architecture below.

Our *Parity Transformer* has the following hyperparameters: sequence length n, token embedding dimension d_{emb}, attention embedding dimension d_{attn}, feedforward embedding dimension d_{mlp}, and number of heads H. Its trainable parameters (together denoted by θ) are:

- Token embeddings $E_{-1}, E_{+1}, E_{\texttt{[CLS]}} \in \mathbb{R}^{d_{\text{emb}}}$ and position embeddings $P_1, \ldots, P_n \in \mathbb{R}^{d_{\text{emb}}}$. Let θ_{emb} denote this subset of parameters.

- Attention head matrices: $W_Q^{[h]}, W_K^{[h]}, W_V^{[h]} \in \mathbb{R}^{d_{\text{emb}} \times d_{\text{attn}}}$ and $W_{\text{out}}^{[h]} \in \mathbb{R}^{d_{\text{attn}} \times d_{\text{emb}}}$, for $h = 1, \ldots, H$. Let θ_{attn} denote this subset of parameters.

- MLP weights and biases: $W_1 \in \mathbb{R}^{d_{\text{mlp}} \times d_{\text{emb}}}, b_1 \in \mathbb{R}^{d_{\text{mlp}}}, W_2 \in \mathbb{R}^{d_{\text{mlp}} \times d_{\text{emb}}}, b_2 \in d_{\text{emb}}$. Let θ_{mlp} denote this subset of parameters.

- Classification head: $u \in \mathbb{R}^{d_{\text{emb}}}$.

Then,
$$f_{\text{tf}}(x; \theta) := u^\top \left(f_{\text{mlp}}(f_{\text{attn}}(f_{\text{emb}}(x; \theta_{\text{emb}}); \theta_{\text{attn}}); \theta_{\text{mlp}}) \right),$$
where these submodules are defined by

- Embedding $f_{\text{emb}} : \{\pm 1\}^n \to \mathbb{R}^{(n+1) \times d_{\text{emb}}}$: $f_{\text{emb}}(x; \theta_{\text{emb}})_{i,:} := E_{x_i} + P_i$ for $i \in [n]$. We will include an the extra index $\texttt{[CLS]}$, for which $f_{\text{emb}}(x; \theta_{\text{emb}})_{\texttt{[CLS]},:} := E_{\texttt{[CLS]}}$ (with no positional embedding). $\texttt{[CLS]}$ stands for "classification", as in "use the output at this position to classify the sequence". This is a standard construction which makes the classifier permutation-invariant.

- Attention block $f_{\text{attn}} : \mathbb{R}^{(n+1) \times d_{\text{emb}}} \to \mathbb{R}^{d_{\text{emb}}}$:

$$f_{\text{attn}}(X; \theta_{\text{attn}}) = X_{\texttt{[CLS]},:} + \sum_{h=1}^{H} \text{softmax} \left(\frac{1}{\sqrt{d_{\text{attn}}}} X_{\texttt{[CLS]},:} W_Q^{[h]} (X W_K^{[h]})^\top \right) W_V^{[h]} W_{\text{out}}^{[h]},$$

where $\text{softmax}(z) := \exp(z)/\mathbf{1}^\top \exp(z)$. Note that we have specialized this architecture to a single output, at the $\texttt{[CLS]}$ position.

- MLP $f_{\text{mlp}} : \mathbb{R}^{d_{\text{emb}}} \to \mathbb{R}^{d_{\text{emb}}}$:

$$f_{\text{mlp}}(z; \theta_{\text{mlp}}) := z + W_2 \sigma(W_1 x + b_1) + b_2,$$

where $\sigma(\cdot) = \text{GeLU}(\cdot)$ (the Gaussian error linear unit) is the standard choice in Transformers.

Training. Each matrix-shaped parameter was initialized using PyTorch's default "Xavier uniform" convention. Unlike the other settings considered in this paper, we were unable to observe successful convergence beyond a few small (n, k) using standard SGD. As is common practice when training Transformers, we used Adam (Kingma and Ba, 2014) with default adaptive parameters $\beta_1 = 0.9, \beta_2 = 0.999, \epsilon = 10^{-8}$ in our experiments. While there are more fine-grained accounts of why Adam outperforms vanilla SGD (Zhang et al., 2020; Agarwal et al., 2020), finding the optimal optimizer configuration and investigating ablations of this optimizer are outside the scope of this work. In this work, we only tune Adam's learning rate η.

D.1.4 PolyNet

For positive integers n, k, the PolyNet architecture is parameterized by weights and biases $\theta := \{(w_i \in \mathbb{R}^n, b_i \in \mathbb{R})\}_{i=1}^k$, and is defined by

$$f_{\text{PolyNet}}(x; \theta) := \prod_{i=1}^{k} (w_i^\top x + b_i).$$

Even with all biases b_i set to 0, this architecture can realize a k-wise parity, by setting $\{w_i\} = \{e_j : j \in S\}$ in any permutation.

D.1.5 Details for Figure 1 (left)

Figure 1 (left) shows training curves from 8 representative configurations, with online i.i.d. samples from the same distribution, corresponding to the $(n = 50, k = 3)$-sparse parity problem. The first row encompasses various MLP settings with standard activations:

- Setting (i): width-10 MLP with ReLU activation ($B = 32, \eta = 0.5$).
- Setting (i): width-10 MLP with ReLU activation, with large batches ($B = 1024, \eta = 0.05$).
- Setting (ii): width-100 MLP with ReLU activation, with tiny batches ($B = 1, \eta = 0.05$).
- Setting (iv): width-10 MLP with polynomial $\sigma(z) = z^3$ activation ($B = 32, \eta = 0.05$).

The second row shows other settings:

- Setting (vii): width-1 MLP with a piecewise linear k-zigzag activation ($B = 32, \eta = 0.2$).
- Setting (x): width-1 MLP with a sinusoidal activation (scaled and shifted for $k = 3$; see the discussion in Section D.1.2) ($B = 32, \eta = 0.05$).
- Setting (*iii): Parity Transformer, with $d_{\text{emb}} = 1024, d_{\text{attn}} = 8, H = 128$ ($B = 32, \eta = 5 \times 10^{-4}$).
- Setting (xv): degree-3 PolyNet ($B = 32, \eta = 0.07$).

D.1.6 Details for Figure 6

The first row uses the width-10 ReLU MLP configuration (ii), holding $B = 32$ and $\eta = 0.1$ while varying the task difficulty across 6 settings: $(n, k) \in \{(30, 3), (60, 3), (90, 3), (30, 4), (30, 5), (30, 6)\}$. The remaining plots are all for the $(50, 3)$ setting.

The second row uses the $k = 3$ PolyNet configuration (xv), varying $(B, \eta) \in \{(1, 0.005), (4, 0.01), (16, 0.1), (64, 0.1), (256, 0.1), (1024, 0.1)\}$.

The third row uses the minimally-wide configurations (*i), (*ii), (vii), (viii), (xi), (xii) (thus presenting an example for each non-standard activation), holding batch size $B = 1$. $\eta = 0.1$ in each of the cases except (*ii), where $\eta = 0.01$.

The fourth row uses three large architectures: settings (iii), (vi), and (*iii), with $(B, \eta) \in \{(1, 0.1), (1024, 0.1), (1, 0.001), (1024, 0.01), (32, 0.0003), (1024, 0.0003).\}$ (*iii) uses the Adam optimizer instead of SGD.

D.1.7 Details for Figure 10

Figure 10 contains scaling plots in various settings for the median convergence time t_c. Below, we give comprehensive details about these settings. For each of these runs, we chose $B = 32$ (settings with smaller batch sizes exhibited additional variance; with larger batch sizes, the models were slower to converge), as well as the hinge loss. We used SGD with constant learning rate η (enumerated below), except in setting (*iii).

The top row shows MLP settings (i) through (vi). From left to right:

- Setting (i): width-10 MLP with ReLU activation ($\eta = 1$).
- Setting (ii): width-100 MLP with ReLU activation ($\eta = 1$).
- Setting (iii): width-1000 MLP with ReLU activation ($\eta = 1$).
- Setting (iv): width-10 MLP with $\sigma(z) = z^k$ activation ($\eta = 0.01$).
- Setting (v): width-100 MLP with $\sigma(z) = z^k$ activation ($\eta = 0.01$).
- Setting (vi): width-1000 MLP with $\sigma(z) = z^k$ activation ($\eta = 0.01$).

The bottom row shows miscellaneous settings. From left to right:

- Setting (vii): width-1 MLP with degree-k oscillating polynomial activation interpolating the parity function ($\eta = 0.01$).
- Setting (xiv): single sinusoidal neuron with no second layer ($\eta = 0.01$).
- Setting (*iii): Parity Transformer, with $d_{\text{emb}} = 1024, d_{\text{attn}} = 8, H = 128$ ($B = 32, \eta = 3 \times 10^{-4}$).
- Setting (iv): degree-k PolyNet ($\eta = 0.05$).

- Setting (ii): width-100 MLP with ReLU activation ($\eta = 1$), showing an expanded range of n for smaller k.
- Setting (xv): width-100 MLP with $\sigma(z) = z^k$ activation ($\eta = 1$), showing an expanded range of n for smaller k.

D.2 Training curves and convergence time plots

For all example training curves in all figures (in Sections 3 and 5, as well as the appendix), population losses and accuracies are approximated using a batch of size 8192, sampled once at the beginning of training from the same distribution $\mathcal{D}_S$. All plots of single representative training runs use a fixed random seed (`torch.manual_seed(0)`); when R training runs are shown, seeds $0, \dots, R-1$ are used.

In Figures 7 and 8, validation accuracies were recorded every 10 iterations, and a run was recorded as converged if it reached 100% accuracy within 10^5 iterations; we report the 10^{th} percentile over 25 random seeds, to reduce variance arising from the more initialization-sensitive settings. In Figure 9, coarse-grained scaling estimates for the (10^{th} percentile) convergence time are computed as follows: for $n \in \mathcal{N} := \{10, 20, 30\}$, the smallest α is chosen such that $t_c \leq c \cdot (n - n_0)^\alpha$, choosing $n_0 = \min \mathcal{N} - 1 = 9$, so that $c = t_c$ at $n = 10$. These estimates are calculated to give quantitative order-of-magnitude upper bounds for the convergence time. Indeed, the power-law convergence times do not extrapolate at a constant learning rate; see Figure 2 *(right)*, the "larger n" plots in Figure 10, and the discussion on batch sizes and learning rates in Appendix C.2.

To reduce computational load, for the larger-scale probes of convergence times t_c, validation accuracies were instead checked on a sample of size 128. For the underparameterized networks (i.e. unable to represent parity, but can still get a meaningful gradient signal), this threshold was changed to 10 consecutive batches with accuracy at least 55%. Note that for parity learning in particular, a weak learner can be converted into a strong learner: there is an efficient algorithm (Goldreich and Levin, 1989; Kushilevitz and Mansour, 1993) which, given a classifier which achieves $1/2 + \epsilon$ accuracy on $\mathcal{D}_S$ for a constant $\epsilon > 0$, outputs S with high probability.

In the median convergence time plots in Figure 1 *(right)*, Figure 2 *(right)*, and Figure 10, error bars for median convergence times in all plots are 95% confidence intervals, computed from 100 bootstrap samples. Each point on the each curve corresponds to 1000 random trials. Halted curves signify more than 50% of runs failing to converge within $T = 10^5$ iterations (hence, infinite medians).

D.3 Implementation, hardware, and compute time

All training experiments were implemented using PyTorch (Paszke et al., 2019).

Although most of the networks considered in the main empirical results are relatively small, a large ($\sim 10^8$) total number of models were trained to certify the "robust space" of results and obtain precise scaling curves. These individual experiments were not large enough to benefit from GPU acceleration; on an internal cluster, the CPU compute expenditure totaled approximately 1500 CPU hours.

A subset of these experiments stood to benefit from GPU acceleration: width $r \geq 100$ MLPs; scaling behaviors for $n \geq 100$; all experiments involving Transformers. These were performed with NVIDIA Tesla P100, Tesla P40, and RTX A6000 GPUs on an internal cluster, consuming a total of approximately 200 GPU hours.