A Position Paper on *Toxic Reasoning*:
Annotating for Toxic Language Requires Implications and Attitudes

Abstract

Automatic detection of toxic language has the potential to considerably improve engagement with online spaces. Previous work has characterized toxic language detection as a classification problem, often using fine-grained classes for increased explainability. In this position paper, we argue for a new way of operationalizing categories of toxic language. Our approach focuses on what is expressed or implied, and breaks down implications based on two traits: (i) the core content of what was expressed, and (ii) relevant stakeholders' attitudes towards that content. We argue for an approach, which we call *toxic reasoning*, where such distinctions are made explicit. We point out the benefits of such an approach, and develop a toxic reasoning *schema*, which can explain categories of toxic language from diverse sources. We demonstrate this by mapping the classes of existing toxic language datasets to the schema. Toxic reasoning promises to provide improved understanding of implicit toxicity while increasing explainability.

Warning: contains examples of toxic language.

1 Introduction

Language that communicates hateful, derogatory, or offensive ideas (hereafter, *toxic language*) is generally undesirable, and needs to be detected and addressed to improve online spaces. Some toxicity is expressed explicitly, making it easier to identify. More challenging is toxicity that is conveyed implicitly. What counts as an instance of implicit toxicity can be subjective, for example, because different people can read the same text as implying different things. Additionally, some implications intended by the author might only be obvious with the appropriate context. Cultural, situational and discourse context may all be necessary to properly identify the plausible toxic implications of a text.

Widespread use of social media has greatly increased the need for automating the detection of toxic language. Such language can harm individuals and communities, perpetuate stereotypes, and incite violence. Detecting and limiting such language is crucial to the usability and inclusivity of online spaces. A critical aspect of toxic language detection is *explainability*. With machine learning systems' involvement in content moderation, understanding their decisions is of great importance. Explainability not only helps to improve trust and transparency but also ensures that these systems can be audited and improved. Without explanations, both users and moderators may find it challenging to understand why content is flagged, possibly leading to misjudgments and lack of accountability (Nguyen et al., 2023).

In this position paper, we analyze current popular approaches to explainable toxic language detection, identifying aspects that can be improved. To address these concerns, we propose *toxic reasoning* as a task, which requires giving the *reasons* why text is toxic. We argue that categories of toxic language should be defined in terms of what is being communicated, and create a toxic reasoning *schema* to help operationalize this task. This schema includes two main traits: (i) the core content of what is implied, and (ii) the attitudes of relevant stakeholders towards that content. For example, a statement such as *"all jews should be evicted from white countries"*[1] can be broken down into (i) a proposition 'all jews are evicted from white countries', and (ii) the author's preference (or desire) towards this proposition. We believe that, through the toxic reasoning schema, we can explain most toxic narratives—whether explicit or implicit—by characterizing what is conveyed, while still allowing a mapping to existing categories of toxic language.

The remainder of the paper is organized as follows. In Section 2, we give a brief overview of the toxic language detection task. This is followed by

---

[1]from Implicit Hate Corpus (ElSherief et al., 2021)

an analysis of the definitions used for categories of toxic language in the literature, in Section 3. Section 4 investigates the use of toxic spans, and identifies difficulties that arise when spans are used for implicit toxic language. Then, in Section 5, we give a detailed description of toxic reasoning and our schema, explaining how they overcome the limitations identified in the previous two sections. Next, we explain how existing toxic language categories can be explained by our schema, by providing a mapping between the two (Section 6).

2 Toxic language detection

Much work has been done on the detection of *toxic language*. We use the term toxic language as a broad umbrella term that includes hate speech (Jahan and Oussalah, 2023; Fortuna and Nunes, 2018), abusive language (Alrashidi et al., 2022; Vidgen and Derczynski, 2020), and offensive language (Pradhan et al., 2020). State of the art results on toxic language detection tasks are usually achieved by fine-tuning language models on annotated datasets. A common distinction differentiates between explicit and implicit toxic language (Waseem et al., 2017): "explicit abusive language is that which is unambiguous in its potential to be abusive, for example language that contains racial or homophobic slurs", whereas "implicit abusive language is that which does not immediately imply or denote abuse".

Much effort has gone into making the detection of toxic language *explainable*. Explainability has so far mostly come in two forms. First, the inclusion of fine-grained annotation and classification schemes, which aim to better specify the exact nature of the toxicity. Multiple datasets have been annotated according to such (multi-level) taxonomies of toxic language (e.g. Vidgen et al., 2021; ElSherief et al., 2021; Kirk et al., 2023). And second, the inclusion of toxic spans (or rationales), which aim to highlight which part of the message is responsible for its toxicity (Pavlopoulos et al., 2021; Mathew et al., 2021).

3 How to define toxic language?

Annotation and classification schemes, whether coarse-grained or fine-grained, include many kinds of definitions for their categories of toxic language. Definitions are important, because implicitly or explicitly they make their way to the annotation of data (e.g. in the annotator guidelines). Then,

when machine learning is used, there is an implicit expectation for the algorithm to recover whatever decision criteria were used by the annotators.

Previous work has already analyzed definitions used for toxic language (Fortuna et al., 2020; Khurana et al., 2022). These studies explored what aspects are and should be involved in the definitions of toxic language categories. Our analysis builds on their insights.

3.1 Borrowing definitions

Some definitions compare or contrast to other descriptors of (toxic) language. For example, Basile et al. (2019) mention "... HS [Hate Speech] against immigrants may include: 1. insults, threats, denigrating or hateful expressions ...", clarifying what is meant by hate speech to those who already have some understanding of the related terms.

Concern 1 (Dependency). Appealing to other descriptive terms benefit explainability only to a limited extent, because the category becomes dependent on them. And, the other terms may themselves have multiple valid definitions. This may also lead to increased subjectivity in annotations, as different annotators may understand those terms differently.

3.2 Defining factors

We observe that many definitions, given a potentially toxic message, tend to focus on one or more of the following factors:

- CAUSE – *What caused the author to write the message?* – Commonly, the author's intent, with a malicious intent often being required for toxic messages. Other causes might include unconscious biases, lapses in judgment, or ignorance.
- EFFECT – *What are the effects of the message?* – These can include harmful effects on the reader or on groups that are targeted by the message.
- FORM – *What (kinds of) words are used in the message?* – The presence of profanity, like slurs.
- MEANING – *What is conveyed by the message?* – Anything plainly asserted, implied or otherwise insinuated by a message.

To understand the way these factors are used, we will review some example definitions.

One of the ways a message is considered hate speech under the definition given by Waseem and Hovy (2016), is if it 'seeks to silence a minority'. In this definition, the author's reason for writing the toxic message is the deciding factor. In this case, the author would have the goal of silencing

minorities, and that goal can be identified as what caused the author to be toxic (CAUSE).

The Perspective API[2] defines its 'toxicity' and 'severe toxicity' categories by requiring that a message is (very) "likely to make people leave a discussion". Thus, it defines the category based on an effect (EFFECT) of the toxicity. The 'profanity' category, on the other hand, applies when toxicity is conveyed using swear or curse words (FORM). Finally, the 'threat' category requires that the toxic utterance "describes an intention to inflict pain, injury, or violence". Thus, it requires that the message express something like: "I intend to harm person X". As such, the 'threat' category specifies what the message must convey (MEANING).

3.3 Cause and Effect

Fortuna et al. (2020) had the following to say about CAUSE and EFFECT: *"'abusive' has been defined based on the speakers' intention to harm, which cannot always be determined by just looking at the content. Furthermore, definitions also make assumptions on the effect of the messages on the reader, which, obviously, depends entirely on the personality of the reader."* We agree there are reasons to be skeptical about definitions that are based on CAUSE and EFFECT. Specifically, we present a number of concerns focusing on why CAUSE and EFFECT are harder to *operationalize*.

If a category only applies when it has (or is likely to have) specific effects, the classifier needs to infer such effects, which requires world modeling. To decide if a message is "likely to make people leave a discussion", we need to have a world model that includes a 'reader'. And, this world model should be expressive enough to predict what effect reading the message will have on them. Deciding if the author of a message 'seeks to silence a minority' is even more challenging. For this, we need a world model that includes the author's model of the world. The classifier needs some kind of theory of mind (or at least it needs to behave like it has one).

Concern 2 (Feasibility). World modeling and theory of mind are both advanced capabilities, and it is still a matter of debate whether even the most capable Large Language Models (LLMs) possess these capabilities to a significant degree (Ding et al., 2025; Yildirim and Paul, 2024). Thus, it is unclear whether expecting classifiers to infer CAUSE and EFFECT is feasible.

Although, perhaps what is really meant are *perceived* intents (or causes), and *representative* effects. Maybe models are only expected to remember statistical patterns of which types of messages are associated with which causes or effects (and corresponding toxic categories), rather than truly reasoning about these matters.

Concern 3 (Failure to explain). Assume we have a language model fine-tuned to detect categories which are based on (perceived) CAUSE and (representative) EFFECT. The goal of introducing the fine-grained categories was to improve explainability. But, this model still fails to be truly explainable, since we still cannot account for why the classifier inferred the prerequisite CAUSE or EFFECT. What has been inferred and why? What statistical pattern is being exploited?

Finally, one more reason for concern arises when focusing on causes or effects.

Concern 4 (Increased Subjectivity). Generally, the only way for a message to have an effect on a reader, is through either the form or (perceived) meaning. Because of that, inferring the intent of the author often requires first inferring the (possible) meaning(s) of the message. Therefore, any subjectivity in the inference of cause and effect is *in addition* to subjectivity inherent in the inference of meaning.

4 Which spans are toxic?

Toxic spans detection (Pavlopoulos et al., 2021) or rationale extraction (Mathew et al., 2021) is a task where a model is trained to identify which parts of a message are responsible for its toxicity. By pointing moderators towards the relevant part of a message, their work can be made both easier and faster. For explicit toxicity, the identification of spans is generally quite straightforward, but things become more difficult the more implicit the toxicity is. To see this, we look at some examples from Pavlopoulos et al. (2021), with toxic spans are marked in red:

> Youre an idiot.

The offensive word 'idiot' is marked, which corresponds to what was asked of annotators, namely to mark spans that are responsible the toxicity. However, in other examples this is not so clear.

---

[2]The Perspective API hosts machine-learned models to detect toxic language. It was created by Jigsaw and Google's Counter Abuse Technology team. See perspectiveapi.com.

> you are a paid liberal hack of stupidity shore living the liberal lie every day

Say the marked span was removed, would calling someone a 'paid liberal hack' not still be sufficient to say the comment is toxic? The following example was annotated with no spans, indicating that the entire message is toxic.

> Fits the despicable piece of trash like a glove.

But, if 'the despicable piece of trash' was replaced by 'him', the post no longer seems toxic. So should the toxic span not be limited to that description?

The reason why this task is difficult, is because of the different ways a message can be toxic, and how that relates to the responsibility of any particular span. Some toxicity derives just from the use of a particular word (we refer to this as *form*). If the claims, implications or insinuations being made are innocent, but the choice of words with which they are conveyed are not, then those words alone are responsible for the toxicity. Other toxicity is conveyed without bad words, but still 'in plain sight'. For example, an assertion made in a simple declarative sentence, like the sentence "all jews should be evicted from white countries" from the introduction (we refer to this as *standing meaning*). For those cases, generally the entire sentence is responsible for the toxicity. Almost any individual word could change what is being asserted into something non-toxic. And finally, for the hardest cases, the toxicity of statements can depend on conversational context, as seen here in an example from Yu et al. (2022):

> **User 1**: That chick needs a high-five in the face with a chair. Damn her for making us look bad!
> **User 2**: A brick is more effective.

Here the toxicity of Message 2 can only be understood when read as it was originally written, as a reply to the message (making it an instance of *utterance meaning*). Without the reference to violence in Message 1, it is unclear what the brick is more effective *for*. So are both messages part of a single toxic span? What if Message 1 was not toxic on its own, for example:

> **User 1** (new): Haha, that kind of grin just calls for a pie to the face ;-)
> **User 2**: A brick is more effective.

The dependency on the previous message is still there, but nothing about the new Message 1 is toxic.

Concern 5 (Vague spans). Spans that only indicate if tokens bear any kind of responsibility towards the toxicity are too vague to be useful for context-dependent and implicit toxic language.

5 Toxic Reasoning

We define toxic reasoning as toxic language detection that further requires making explicit the reasons for why something should be considered toxic. The reasons that are given should relate to the conditions under which a category is supposed to apply as specified in its definition. So if a definition only applies if the author intended to harm someone, toxic reasoning would require specifying who is harmed and how.

5.1 Approach

Because of concerns 1 through 4 that were raised in the section 3, our approach focuses on characterizing toxicity in terms of what is conveyed. We acknowledge that there might be some categories of toxic language which need to be defined in terms of the other factors. Certainly, the most explicit forms of toxic language (e.g. slurs or swear words) are most easily categorized directly by whether those kinds of words are indeed used in a message. And, insofar as causes and consequences are necessary to define categories, we advocate for an approach where part of the reasoning work is essentially 'front-loaded'. This approach would first identify what types of messages tend to be produced by authors with malicious intents, and what types are likely to produce negative consequences. Where the message 'types' are specified entirely in terms of what is conveyed and how.

We further focus largely on implicit toxicity, since that is where progress is needed the most necessary (Ocampo et al., 2023). Nevertheless, the schema can also explain many cases of explicit toxic language. Like ElSherief et al. (2021), who annotate a dataset with toxic implications, our schema also considers the *implications* of a message. We deviate in the way the implications are characterized. ElSherief et al. annotate fine-grained categories, and then add free-text descriptions of the implications. We advocate for first identifying what implication(s) are present in a (potentially) toxic message, then using our *toxic reasoning schema* to characterize those implications.

Looking at the implicit hate speech categories defined by ElSherief et al. (2021), we notice that many categories are already defined in terms of

what is conveyed. We consider two main aspects of what is implied: (1) a proposition predicating something of a subject, and (2) the author (implicitly) reporting an attitude (of belief, desire, or intent) towards this proposition. The second aspect is most relevant when contrasted to the attitude we expect either the general public or experts[3] to have toward that same proposition. Given this observation, we hypothesize that this task should be approached by including propositional content and attitudes in the schema independently.

5.2 Toxic Reasoning Schema

Here we describe the traits that make up our toxic reasoning schema. In Figure 1, we give examples that cover all the traits of our schema.

The schema's first trait categorizes what is at the core of a message's implication: the message **content** characterizes the proposition that is central to what the text is conveying. We identify three high-level categories of content.

- *Situation*(subject):
  a situation (e.g. environment, circumstance, condition, etc.) applies to the subject.

- *Quality*(subject):
  the subject possesses a given inherent quality, or has a certain nature.

- *Behavior*(subject):
  the subject behaves in a particular way.

All fall under a unifying *Something* category, and can occur with a *Negative* or a *Positive* **polarity**. *Situation* includes statements where a subject is affected by something external. For example, the text from the introduction that mentions the eviction of a group of people, which would be a *NegativeSituation*. The second category covers a subject's inherent qualities or nature. *NegativeQuality* statements could include those describing the subject as 'sub-human' or 'vermin', whereas a *PositiveQuality* might mention intelligence. Finally, the third category is about a subject's behavior, *Negative* could be stealing, conspiring, or terrorism, whereas *Positive* could include inventing.

Each of the categories can also apply in a comparative manner. When the statement does not make an absolute statement about the subject, but rather a relative one, where the *Situation*, *Quality*, or *Behavior* of the subject is compared (positively or negatively) to the other.

The subject (and the other) can be individuals, or groups. We differentiate between three degrees of **specificity**. If the toxicity is entirely *personal*, then no group is mentioned, described or implied at all. Alternatively, the toxicity can be aimed at a *group-member*, where a person is attacked because of the affiliation or relation to a group. And finally, toxicity can be directed at a group as a whole (*group-whole*) in general, without targeting any particular person. This trait captures what previous work calls either directed or generalized hate (Waseem et al., 2017). Where for our schema, a value of *group-member* indicates that the toxicity is both directed and generalized.

When the specificity of the subject or other involve a group, we also include a **group type** trait for the subject and other. Toxicity can be specified as targeting based on a specific characteristic, like *race*, *nationality*, *religion*, etc. Or, it might be more specifically targeting an instance of that characteristic, like how in the sexism-focused EDOS dataset (Kirk et al., 2023) all categories are defined as being directed at *gender:women*.

The subject and other (if present) fulfill roles with respect to the conversation. These are covered by the **subject role** and **other role** traits. For this trait, the possible values indicate that the subject (or other) of the implication is: the *author*, indicating that the author is talking about (or comparing to) themselves or their in-group (the group the author belongs to); an *interlocutor*, indicating that the author is talking about (or comparing to) another participant in the conversation or a group they belong to; or, *outside*, meaning the author is talking about (or comparing to) a person or group outside the conversation.

The next trait is the **temporality** which specifies the point in time that the implication is meant to apply: the *past*, *present* or *future*.

Another trait we include is **inferential origin**, where we distinguish between *form*, *standing meaning*, and *utterance meaning*. Sometimes a toxic implication originates not in the content of what someone said, but from the form. For example, Kirk et al. (2023) include a category 'Causal use of gendered slurs, profanities and insults', with an example sentence: "Stop being such a little b*tch". The argument is that something negative is implied about women through the author's use of this term, even if not used in a sexist way.

Finally, our schema includes the following stakeholder **attitudes**, which describe the attitudes that

---

Figure 1: Application of our Toxic Reasoning Schema, showing how six examples would be characterized. The full text and source for all examples can be found in Appendix B.

relevant stakeholders have towards the implication: (i) *author-belief*, does the author believe the implication? (ii) *author-desire*, does the author desire or prefer the implication to be true? (iii) *author-intent*, does the author represent themselves as committed to or accountable for the truth of the implication? For example, when bragging about a past event, or when expressing an intent to make a future event happen. (iv) *typical-belief*, would a typical person believe the implication? (v) *typical-desire*, would a typical person desire or prefer the implication to be true? (vi) *expert-belief*, would an expert believe the implication?

5.3 Benefits

Better spans. We envision the schema being used in combination with span detection. Rather than identifying spans that bear any kind of responsibility for the toxicity, we envision spans being related to specific traits of our schema. Specifically, different spans can be used to mark different traits in the schema. This includes spans corresponding to the subject of the implication, similar to previous work annotating spans for targets (Barbarestani et al., 2022; Jafari et al., 2024). Returning to the example from Section 4:

> **User 1**: That chick needs a high-five in the face with a chair. Damn her for making us look bad!

The following span annotations could be provided. For content and polarity 'high-five in the face with a chair' indicate a *NegativeSituation*. And, for the subject 'That chick' indicates a subject role of *outside*, a specificity of *group-member*, and a subject group of *gender:woman*. The explanatory value of spans is improved by highlighting specific aspects of toxic implications.

Better insight. Categories of toxic language usually have multiple conditions. When an annotator or model judges some text to contain a specific kind of toxic language, they implicitly assert that a set of conditions apply which are sufficient to reach that conclusion. In our schema, these conditions are made explicit, allowing for better insight into models. For example, if a model tends to confuse two classes, we can identify which of the underlying traits are at the root of the problem.

Controlled subjectivity. Röttger et al. (2022) describe two contrasting paradigms for data annotation. The descriptive paradigm encourages annotator subjectivity, while the prescriptive paradigm discourages it. Our viewpoint is that what is useful, is trying to 'prescribe away' the subjectivity that arises from disagreement on the (definitions of) categories themselves. What is much more difficult to prescribe than definitions, are world views or belief systems. Some subjectivity is dependent on an annotator's understanding of the world rather than anything directly related to the annotation. These kinds of subjectivity are generally not (practically) reducible, but the schema does provide us with new

options. For example, asking annotators what they think an expert would believe about a given implication, is essentially asking them to give their best-faith impression of what is true (descriptive). Alternatively, one could ask actual experts if they believe certain implications are correct (prescriptive). So in this way, the toxic reasoning schema can facilitate both paradigms.

6 Mapping categories to the schema

To demonstrate how the schema captures common categories used in existing datasets, we create a mapping to the classes of the IHC (ElSherief et al., 2021). We justify three of them here, and the rest in the appendix. This is not intended to be a definitive mapping, and ideally mappings are created by the authors of taxonomy or classification scheme as they are developed. The constructed mapping can be found in Table 1. Throughout, when we say that a stakeholder should (not) believe, desire, or intend that the proposition be true, this is reflected in the mapping by including a constraint on the relevant attitude in the mapping. An additional mapping, to the EDOS (Kirk et al., 2023) categories, as well as the other justifications can be found in Appendix A.

Threat/Intimidation. This class includes texts that "convey a speaker commitment to a target's pain, injury, damage, loss, or violation of rights" (ElSherief et al., 2021). It specifically also includes non-violent threats about the "implicit violation of rights and freedoms, removal of opportunities, and more subtle forms of intimidation". Inherent in a threat (as defined here) is a *future*-oriented application of a *NegativeSituation*. Furthermore, the author should: believe what they are threatening (not an idle threat); and, seem personally committed to (intend to carry out) the threat. In short, the author believes, an intends for the target to be subjected to a negative situation.

(White) Grievance. When a majority group presents themselves as either the real victims (or presents a minority group as actually having privilege) this is classified as (White) Grievance. For this category the author implies that a *NegativeSituation* applies to their in-group. Additionally, the author must not prefer that the implication is true (not self-hating). To qualify as hateful the grievance must also not have any legitimacy, in other words: a typical person must not believe or prefer that it were true; and experts should not believe the impli-

cation either.

Inferiority. This category maps on to our schema fairly straightforwardly. Inferiority language includes both: 1) comparisons of two groups, which we model by including *Inferior*(subject, other) as the two-place (relative) version of *SomethingNegative*(subject); or 2) by implying that a target group either lacks a *PositiveQuality* or possesses a *NegativeQuality*. Regarding 2), ElSherief et al. (2021) specifically mention dehumanization and toxification. These two can be modeled by including *NotHuman* and *Vermin* as sub-properties of *NegativeQuality*.

7 Toxic Reasoning Annotation: Preliminary Findings

We propose a schema that is more complex than what has been proposed before. This raises a question about the feasibility of creating human annotations that follow this schema. Human-annotated data is necessary for at least two reasons. First, we need it to validate the schema itself, specifically that it covers all the kinds of toxicity we might encounter. Second, we need data to test (and train) models on the task of toxic reasoning. As an indication of feasibility, we will report some preliminary findings from our first annotation campaign.

We have annotated comments from Reddit according to our schema. The comments are in six languages: English and Dutch were annotated by three experts which included the authors and some colleagues, and for Arabic, German, Spanish, and Turkish three native-speaking students were recruited. For each language we have between 400 and 500 comments organized into comment threads of between 4 and 10 comments long. The comments were annotated in context, allowing for more interesting toxicity to be captured.

Annotators could indicate whenever they felt that a part of the schema did not adequately cover the toxicity, which occurred for only 2.9% of the comments. Because the schema is annotated for a particular toxic implication, it is not as straightforward to calculate agreement scores. Annotators were asked to choose what they perceived to be the main toxic implication of a comment. If annotators disagree about what that main implication is, we cannot expect them to agree on anything else. We can show the quality of the data by using a conditional version of agreement instead, but giving those numbers here without properly explaining

	Threat	Incitement		Griev.	*	Inferiority Dehuman.		Misinfo.	
		*	Flaunt.			*	Tox.	*	Stereotype
Content									
Something(`target`)	·	·	·	·	·	·	·	✓	✓
SomethingNegative(·)	·	·	·	·	·	·	·	·	·
NegativeSituation(·)	·	·	·	·	·	·	·	·	·
Harmed(`target`)	✓	✓	·	·	·	·	·	·	·
Harmed(`in_group`)	·	·	·	✓	·	·	·	·	·
NegativeQuality(·)	·	·	·	·	·	·	·	·	·
NotHuman(`target`)	·	·	·	·	·	✓	·	·	·
Vermin(`target`)	·	·	·	·	·	·	✓	·	·
Inferior(`target, in_group`)	·	·	·	·	✓	·	·	·	·
SomethingPositive(·)	·	·	·	·	·	·	·	·	·
PositiveQuality(·)	·	·	·	·	·	·	·	·	·
Power(`in_group`)	·	·	✓	·	·	·	·	·	·
Unity(`in_group`)	·	·	✓	·	·	·	·	·	·
Superior(`in_group, target`)	·	·	·	·	✓	·	·	·	·
temporality	future	future	·	·	·	·	·	·	·
specificity	·	·	grp-*	grp-*	grp-*	grp-*	grp-*	·	grp-*
Attitudes									
author_belief	+	·	+	+	+	+	+	+	·
author_desire	·	+	·	−	·	·	·	·	·
author_intent	+	−	·	−	·	·	·	·	·
typical_belief	·	·	·	−	·	·	·	·	·
typical_desire	·	·	·	−	·	·	·	·	·
expert_belief	·	·	+	−	·	·	·	−	−
stereotype	·	·	·	·	·	·	·	·	+

Table 1: Mapping to our toxic-reasoning schema, with each column representing an IHC (sub-)class, it contains: (1) a check mark for the content (rows) that could be responsible for that class; (2) the values for the temporality, specificity that are required by that class (or '·' for no requirements); and (3) constraints on the attitudinal attributes for that class (with '+' indicating the attitude is necessary, '−' indicating the attitude is prohibited, and '·' indicating no constraints). The value grp-* is an abbreviation, short for either *group-member* or *group-whole*.

8 Conclusion

We have proposed toxic reasoning, and our toxic reasoning schema, which separates a message's main propositional content from the attitudes towards those propositions. After identifying the difficulties associated with defining (categories of) toxicity based on causes and effects, we have defended our choice of focusing on what is conveyed instead. We have argued that toxic reasoning improves explainability in two ways: (1) by enabling explanations that appeal to the conditions on which the predictions are based; and (2) by allowing for span annotations that point out specific aspects of what is implied. To demonstrate how our toxic reasoning schema is used to ground toxic categories in toxic implications, we have presented a mapping to the IHC and to EDOS. We foresee mappings to our toxic reasoning schema being made for many taxonomies focusing on various kinds of toxic language. We expect that the schema will be useful for rigorously defining categories of toxic language.

In future work, we hope to see datasets annotations that make use of the schema for increased consistency, and decreased subjectivity. Use of the schema is not limited to annotating data for the traits directly. One might augment annotation campaigns by using the schema to confirm the categories are applied as intended. For example, when an annotator chooses a category of 'Threat', they could be asked to confirm that there is mention of harm coming to a target in the future, and that the author intends for this harm to happen. With such annotated data, we can also hope for the creation of better, more robust toxic language detection models. Such models could be trained to predict the traits of the schema directly, after which the mappings could be used to produce predictions for existing taxonomies. The schema-level annotations could also be used as an auxiliary task, or to probe which aspects of categories the model struggles to represent.

Limitations

By focusing on what a message conveys, we do not fully avoid the problematic aspects of CAUSE and EFFECT. As we already explained under 'inferential origin' in subsection 5.2, the presence of a word (like a slur) can itself imply something toxic. Similarly, there are categories where even if we define it in terms of what is being implied, we still run into causes or effects. Take for example, the case of 'mansplaining' (known in EDOS as "Animosity – 3.4 Condescending explanations or unwelcome advice". We might argue that at the core of the toxicity lies an implication that women are ignorant, unintelligent, or otherwise in need of having things explained to them. However, crucial to the category is the fact that this is not asserted directly. Instead, the sexist implication originates from the (perceived) motivation behind the explanation. The inferential origin is the CAUSE of the toxicity.

References

Bedour Alrashidi, Amani Jamal, Imtiaz Khan, and Ali Alkhathlan. 2022. A review on abusive content automatic detection: approaches, challenges and opportunities. *PeerJ Computer Science*, 8:e1142. Publisher: PeerJ Inc.

Baran Barbarestani, Isa Maks, and Piek Vossen. 2022. Annotating Targets of Toxic Language at the Span Level. In *Proceedings of the Third Workshop on Threat, Aggression and Cyberbullying (TRAC 2022)*, pages 43–51, Gyeongju, Republic of Korea. Association for Computational Linguistics.

Valerio Basile, Cristina Bosco, Elisabetta Fersini, Debora Nozza, Viviana Patti, Francisco Manuel Rangel Pardo, Paolo Rosso, and Manuela Sanguinetti. 2019. SemEval-2019 Task 5: Multilingual Detection of Hate Speech Against Immigrants and Women in Twitter. In *Proceedings of the 13th International Workshop on Semantic Evaluation*, pages 54–63, Minneapolis, Minnesota, USA. Association for Computational Linguistics.

Jingtao Ding, Yunke Zhang, Yu Shang, Yuheng Zhang, Zefang Zong, Jie Feng, Yuan Yuan, Hongyuan Su, Nian Li, Nicholas Sukiennik, Fengli Xu, and Yong Li. 2025. Understanding World or Predicting Future? A Comprehensive Survey of World Models. *ACM Comput. Surv.*, 58(3):57:1–57:38.

Mai ElSherief, Caleb Ziems, David Muchlinski, Vaishnavi Anupindi, Jordyn Seybolt, Munmun De Choudhury, and Diyi Yang. 2021. Latent Hatred: A Benchmark for Understanding Implicit Hate Speech. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 345–363, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Paula Fortuna and Sérgio Nunes. 2018. A Survey on Automatic Detection of Hate Speech in Text. *ACM Computing Surveys*, 51(4):1–30.

Paula Fortuna, Juan Soler, and Leo Wanner. 2020. Toxic, Hateful, Offensive or Abusive? What Are We Really Classifying? An Empirical Analysis of Hate Speech Datasets. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 6786–6794, Marseille, France. European Language Resources Association.

Nazanin Jafari, James Allan, and Sheikh Muhammad Sarwar. 2024. Target Span Detection for Implicit Harmful Content. In *Proceedings of the 2024 ACM SIGIR International Conference on Theory of Information Retrieval*, ICTIR '24, pages 117–122, New York, NY, USA. Association for Computing Machinery.

Md Saroar Jahan and Mourad Oussalah. 2023. A systematic review of hate speech automatic detection using natural language processing. *Neurocomputing*, 546:126232.

Urja Khurana, Ivar Vermeulen, Eric Nalisnick, Marloes Van Noorloos, and Antske Fokkens. 2022. Hate Speech Criteria: A Modular Approach to Task-Specific Hate Speech Definitions. In *Proceedings of the Sixth Workshop on Online Abuse and Harms (WOAH)*, pages 176–191, Seattle, Washington (Hybrid). Association for Computational Linguistics.

Hannah Kirk, Wenjie Yin, Bertie Vidgen, and Paul Röttger. 2023. SemEval-2023 Task 10: Explainable Detection of Online Sexism. In *Proceedings of the 17th International Workshop on Semantic Evaluation (SemEval-2023)*, pages 2193–2210, Toronto, Canada. Association for Computational Linguistics.

Binny Mathew, Punyajoy Saha, Seid Muhie Yimam, Chris Biemann, Pawan Goyal, and Animesh Mukherjee. 2021. HateXplain: A Benchmark Dataset for Explainable Hate Speech Detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 14867–14875. Number: 17.

Tin Nguyen, Jiannan Xu, Aayushi Roy, Hal Daumé III, and Marine Carpuat. 2023. Towards Conceptualization of "Fair Explanation": Disparate Impacts of anti-Asian Hate Speech Explanations on Content Moderators. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9696–9717, Singapore. Association for Computational Linguistics.

Nicolás Benjamín Ocampo, Ekaterina Sviridova, Elena Cabrio, and Serena Villata. 2023. An In-depth Analysis of Implicit and Subtle Hate Speech Messages. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 1997–2013, Dubrovnik, Croatia. Association for Computational Linguistics.

John Pavlopoulos, Jeffrey Sorensen, Léo Laugier, and Ion Androutsopoulos. 2021. SemEval-2021 Task

5: Toxic Spans Detection. In *Proceedings of the 15th International Workshop on Semantic Evaluation (SemEval-2021)*, pages 59–69, Online. Association for Computational Linguistics.

Rahul Pradhan, Ankur Chaturvedi, Aprna Tripathi, and Dilip Kumar Sharma. 2020. A Review on Offensive Language Detection. In Mohan L. Kolhe, Shailesh Tiwari, Munesh C. Trivedi, and Krishn K. Mishra, editors, *Advances in Data and Information Sciences*, volume 94, pages 433–439. Springer Singapore, Singapore. Series Title: Lecture Notes in Networks and Systems.

Paul Röttger, Bertie Vidgen, Dirk Hovy, and Janet Pierrehumbert. 2022. Two Contrasting Data Annotation Paradigms for Subjective NLP Tasks. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 175–190, Seattle, United States. Association for Computational Linguistics.

Bertie Vidgen and Leon Derczynski. 2020. Directions in abusive language training data, a systematic review: Garbage in, garbage out. *PLOS ONE*, 15(12):e0243300. Publisher: Public Library of Science.

Bertie Vidgen, Dong Nguyen, Helen Margetts, Patricia Rossini, and Rebekah Tromble. 2021. Introducing CAD: the Contextual Abuse Dataset. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2289–2303, Online. Association for Computational Linguistics.

Zeerak Waseem, Thomas Davidson, Dana Warmsley, and Ingmar Weber. 2017. Understanding Abuse: A Typology of Abusive Language Detection Subtasks. In *Proceedings of the First Workshop on Abusive Language Online*, pages 78–84, Vancouver, BC, Canada. Association for Computational Linguistics.

Zeerak Waseem and Dirk Hovy. 2016. Hateful Symbols or Hateful People? Predictive Features for Hate Speech Detection on Twitter. In *Proceedings of the NAACL Student Research Workshop*, pages 88–93, San Diego, California. Association for Computational Linguistics.

Ilker Yildirim and L.A. Paul. 2024. From task structures to world models: what do LLMs know? *Trends in Cognitive Sciences*, 28(5):404–415.

Xinchen Yu, Eduardo Blanco, and Lingzi Hong. 2022. Hate Speech and Counter Speech Detection: Conversational Context Does Matter. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5918–5930, Seattle, United States. Association for Computational Linguistics.

A Mappings

A.1 Additional IHC Justifications

Incitement to Violence. The definition given by ElSherief et al. (2021) for incitement is: "flaunting in-group unity and power or elevating known hate groups and ideologies". We model this by introducing *Power* and *Unity* as properties as specific kinds of *PositiveQuality*, which are asserted about the author's in-group. The author must *believe* what they are saying, and also find it desirable (they do not regret their in-groups's power and unity). Experts should also believe that the author's in-group has power and/or unity, or it would not be flaunting.

Going beyond the definition given by ElSherief et al. (2021), we also include under incitement any cases that would have been classified as 'Threat/Intimidation', except for a lack of author intent. Take the example from the introduction: "all jews are evicted from white countries". The author of that message is talking about what should happen, and it is not obvious that this person is in a position to enact or enable any eviction of Jewish people, making any intentions unlikely. But they are still clearly expressing a desire for eviction, thus reasonably making it an instance of incitement.

Stereotypes & Misinformation. This category is arguably the broadest category in the IHC. In our schema, misinformation comes down to the author stating something (anything) of a subject that an expert would disagree with. Thus the it requires the *Something* category and a lack of expert belief.

Stereotypes are a specific kind of misinformation where some (often negative) characteristics are associated with a group. We model this by introducing an additional attitude for it, thereby characterizing stereotypes as propositions towards which society has a specific kind of attitude.

Irony. Unlike previous categories, irony does not constrain the content of what is communicated, any implication can be made through irony. Because of this, we choose not to include this category in our current mapping. To characterize irony would require modeling the relationship between what is implied and the literal meaning.

A.2 EDOS Mapping

The mapping to the classes of EDOS can be found in Table 2.

	'Threats, [..] and Incitement'		'Derogation'			'Animosity'				'Prejudiced Discussion'	
	1.1	1.2	2.1	2.2	2.3	3.1	3.2	3.3	3.4	4.1	4.2
Implications											
Something(·)	·	·	·	·	·	·	·	·	·	·	·
SomethingNegative(`target`)	·	·	·	·	·	✓	·	·	·	·	·
NegativeSituation(·)	·	·	·	·	·	·	·	·	·	·	·
Harmed(`target`)	✓	✓	·	·	·	·	·	·	·	·	·
Mistreatment(`target`)	·	·	·	·	·	·	·	·	·	✓	·
SystemicDiscrimination(`target`)	·	·	·	·	·	·	·	·	·	·	✓
NegativeQuality(`target`)	·	·	✓	·	·	·	·	✓	✓	·	·
NotHuman(`target`)	·	·	·	·	✓	·	·	·	·	·	·
SexualObject(`target`)	·	·	·	·	✓	·	·	·	·	·	·
NegativeBehavior(`target`)	·	·	✓	·	·	·	·	·	·	·	·
AuthorDislike(`target`)	·	·	·	✓	·	·	·	·	·	·	·
Inferior(`target, other`)	·	·	·	·	·	·	✓	·	·	·	·
temporality	future	future	·	·	·	·	·	·	·	·	·
specificity	·	·	grp-*	grp-*	grp-*	grp-w	grp-*	grp-*	grp-*	grp-*	grp-w
origin	*-mn	*-mn	*-mn	·	*-mn	form	*-mn	u-mn	cause	*-mn	*-mn
Attitudes											
author_belief	+	·	+	+	+	−	+	·	·	·	·
author_desire	·	+	·	·	·	·	·	·	·	+	+
author_intent	+	−	·	·	·	·	·	·	·	·	·
typical_belief	·	·	·	·	·	·	·	·	·	·	·
typical_desire	·	·	·	·	·	·	·	·	·	·	·
expert_belief	·	·	−	·	·	·	−	·	·	·	·
stereotype	·	·	·	·	·	·	+	·	·	·	·

Table 2: Mapping to our toxic-reasoning schema for EDOS. Each column represents an EDOS (sub-)class, it contains: (1) check marks for the implications that could be involved in a sample of that class; (2) the values for the temporality, specificity that are required by that class (or '·' for no requirements); and (3) constraints on the possible values for the attitudinal attributes for that class (with '+' indicating the attitude is necessary, '−' indicating the attitude is prohibited, and '·' indicating no constraints). For EDOS, the group type for all classes would be constrained to *gender:women*. The values grp-*, grp-w, *-mn, and u-mn are abbreviations, with: grp-w being short for *group-whole*, grp-* allowing for either *group-member* or *group-whole*; u-mn standing for *utterance-meaning*; and *-mn allowing for either *utterance-meaning* or *standing meaning*.

B Full examples from Figure 1

Each of the examples in Figure 1, by number.

1. "globalization = white genocide. usa next on the list! never in america. keep your guns!"

   Source: IHC
   Line nr.: 2250

2. "I'll hire a man for this job"

   Source: Created for illustrative purposes.

3. "agreed. the white race has built and invented every aspect of modern civilisation."

   Source: IHC
   Line nr.: 3932

4. "you just kill people and mosquitoes during your marchs"

   Source: IHC
   Line nr.: 18412

5. "you Japanese are just smarter"

   Source: Created for illustrative purposes.

6. "Stop being such a little bitch"

   Source: Kirk et al. (2023) – Table 1
   Also see: Entry sexism2022_english-13065 in
   EDOS dataset.