SkillAdaptor: Self-Adapting Skills for LLM Agents from Trajectories

Abstract

Large language model (LLM) agents increasingly rely on reusable external skills to solve long-horizon interactive tasks. Existing training-free skill adaptation pipelines usually update skills from full trajectories or session-level feedback, which makes failure attribution coarse and often produces unstable or overly broad revisions. We propose SKILLADAPTOR, a training-free step-level skill adaptation framework with explicit failure attribution, and it can plug into OpenClaw-class agent harnesses. Given a failed trajectory, SKILLADAPTOR identifies a first actionable fault step, links responsibility to candidate skills, and applies targeted updates under explicit acceptance checks while keeping the backbone frozen. We evaluate on WebShop, PinchBench, and Claw-Eval with Kimi-K2.5, GLM-5, and GPT-5.2. SKILLADAPTOR improves over no-skill and skill-adaptation baselines on all three suites, with the largest single-metric improvements of $+1.5$ points on PinchBench Avg Score%, $+1.8$ on Claw-Eval Avg Score, and $+1.7$ on WebShop success rate. These results indicate that step-level attribution supports more stable and auditable training-free skill maintenance.

1 Introduction

Large language model (LLM) agents are widely used for long-horizon tasks involving tool use, coding, and web interaction (Yao et al., 2023; Schick et al., 2023; Patil et al., 2024; Wang et al., 2023). To enable continual improvement without retraining base model, many systems augment frozen LLMs with reusable external skills, such as triggers, action patterns, and verification procedures (Lin et al., 2026; HKUDS, 2026; Wang et al., 2026).

Recent training-free adaptation methods improve such agents from execution traces through memory distillation (Xu et al., 2025), workflow refinement (Wang et al., 2025), retrospective feedback (Zhao et al., 2024), and iterative skill evolution (Liu et al., 2026b; Alzubi et al., 2026; Zhang et al., 2026a). While effective, most of them adapt skills from trajectory-level outcomes or session-level summaries, using the completed trajectory as the main unit of reflection and revision.

This outcome-level adaptation becomes brittle in long-horizon environments. A failed trajectory often contains many correct intermediate decisions, while the actual failure may stem from only a few earlier mistakes. When updates are driven mainly by the final outcome, failure signals can be diffused across unrelated steps and skills, leading to overly broad or misdirected revisions. This credit-assignment problem is especially severe when a single early error invalidates many later actions.

To address the above limitation, we propose SKILLADAPTOR, a training-free modular adaptor that shifts adaptation from trajectory-level reflection to step-level attribution. Given an execution trace, SKILLADAPTOR localizes the first actionable fault, diagnoses the related skill deficiency, and refines only the relevant skill while leaving unrelated skills unchanged. As a modular post-execution adaptation stage, SKILLADAPTOR can be integrated as a plug-in component for OpenClaw-class agent harnesses (Steinberger, 2026).

We evaluate SKILLADAPTOR on WebShop (Yao et al., 2022), PinchBench (Kilo Code, 2026), and Claw-Eval (Ye et al., 2026). SKILLADAPTOR consistently improves over training-free adaptation baselines, suggesting that stable agent improvement depends less on expanding skill libraries or reflecting over entire trajectories, and more on accurately attributing failures to the specific steps and skills that caused them.

2 Preliminaries

We consider an interactive setting in which an LLM agent solves tasks by acting in an environment. Given a task q sampled from a task distribution $\mathcal{Q}$,

Figure 1: Overview of SKILLADAPTOR framework.

the agent produces an execution trajectory

$$\tau = \{(a_t, o_t)\}_{t=1}^{T}, \qquad (1)$$

where a_t is the action taken by the agent at step t and o_t is the observation. The trajectory is the only evidence available for subsequent fault analysis and skill updates.

To improve task completion without updating model parameters, we maintain a skill collection

$$K = \{s_1, s_2, \ldots, s_n\}, \qquad (2)$$

where each s_i is a textual skill record carrying a title, a principle, and applicability conditions. The base model is frozen throughout, and only K is revised or appended across iterations.

Our objective is to design the update procedure so that the expected success rate over $\mathcal{Q}$ is improved through K alone

$$\max_{K} \; \mathbb{E}_{q \sim \mathcal{Q}} \left[\text{success}(\text{Run}(q, K)) \right], \qquad (3)$$

where $\text{Run}(q, K)$ executes the agent on q conditioned on a retrieved subset of K, and $\text{success}(\cdot)$ is the benchmark-defined success indicator. This formulation keeps the method training-free and attributes any improvement to updates on K.

3 Method

SKILLADAPTOR is a trajectory-driven skill adaptation framework built on a dynamic skill collection K. During task execution, the agent retrieves a small set of relevant skills from K and conditions generation on the retrieved context. Failed trajectories are subsequently used to improve skill collection through Attribution, Modification, and Qualification.

Skill Initialization. The framework is initialized without any external skill collection. The backbone LLM first executes the task set $\mathcal{Q}$ used for skill adaptation, without any skill or experience augmentation. Successful trajectories are archived as reference traces, from which initial skills are distilled to construct the initial collection K_0.

After initialization, all subsequent executions are performed with skill retrieval over K. Then failed trajectories from these executions are forwarded to the adaptation stage for skill updating.

Skill Injection. For each task q with description d_q, each skill contains structured fields including title, applicability condition, and behavioral principle. We encode tasks and skills using Qwen3-Embedding-8B denoted by $\phi(\cdot)$. Candidate skills are first retrieved by cosine similarity, truncated to top-k_{ret} candidates, and finally reranked by the backbone LLM

$$S_q = \text{Rerank}\left(\underset{s \in K}{\text{TopK}} \, \text{sim}\big(\phi(d_q), \phi(s)\big), \, d_q \right). \qquad (4)$$

Conditioned on S_q, the agent interacts with the environment and produces a trajectory tuple (q, τ, r), where τ denotes the execution trajectory and r indicates task success or failure.

Skill Adaptation. The Adaptation phrase includes the following three parts. Starting from $K^{(0)}$, we iterate this process for up to 10 rounds, or until the skill collection remains unchanged for 3 consecutive rounds. The final collection K^* is then frozen with no further updates.

(1) Attribution. Given a failed trajectory, the Localizer predicts the accountable failure step:

$$(t^*, \pi) = \text{Localize}(q, \tau, S_q). \qquad (5)$$

	PinchBench			Claw-Eval					
	Kimi-K2.5	GLM-5	GPT-5.2	Kimi-K2.5		GLM-5		GPT-5.2	
Method	Avg Score%	Avg Score%	Avg Score%	Avg Score	Pass@3%	Avg Score	Pass@3%	Avg Score	Pass@3%
Base Model	$63.6^{\pm 8.7}$	$70.2^{\pm 5.4}$	$74.8^{\pm 6.1}$	$73.2^{\pm 1.3}$	74.4%	$72.8^{\pm 1.1}$	72.9%	$76.0^{\pm 1.6}$	77.4%
OpenSpace	$66.0^{\pm 5.9}$	$72.3^{\pm 4.5}$	$75.8^{\pm 5.6}$	$74.0^{\pm 2.2}$	75.9%	$73.6^{\pm 2.1}$	74.4%	$77.1^{\pm 1.8}$	77.4%
SkillAdaptor	$\mathbf{67.2}^{\pm 5.2}$	$\mathbf{73.8}^{\pm 4.6}$	$\mathbf{76.6}^{\pm 5.1}$	$\mathbf{75.8}^{\pm 1.6}$	77.4%	$\mathbf{75.3}^{\pm 1.5}$	75.9%	$\mathbf{77.6}^{\pm 1.8}$	78.9%

Table 1: Main comparison across PinchBench and Claw-Eval. PinchBench reports Avg Score%; Claw-Eval reports Avg Score and Pass@3%.

	WebShop					
	Kimi-K2.5		GLM-5		GPT-5.2	
Method	Score	Succ%	Score	Succ%	Score	Succ%
Base Model	$32.1^{\pm 1.4}$	$24.6^{\pm 1.5}$	$33.8^{\pm 0.9}$	$25.3^{\pm 2.0}$	$36.2^{\pm 1.0}$	$25.0^{\pm 1.6}$
A-Mem	$30.3^{\pm 1.6}$	$22.6^{\pm 2.1}$	$30.9^{\pm 0.8}$	$20.0^{\pm 1.8}$	$33.7^{\pm 1.2}$	$21.6^{\pm 2.4}$
AWM	$34.0^{\pm 0.9}$	$25.3^{\pm 1.4}$	$34.5^{\pm 1.6}$	$25.6^{\pm 1.7}$	$36.5^{\pm 1.3}$	$28.3^{\pm 1.9}$
ExpeL	$35.7^{\pm 0.6}$	$26.0^{\pm 1.1}$	$35.2^{\pm 1.0}$	$27.3^{\pm 1.2}$	$37.0^{\pm 0.7}$	$29.6^{\pm 1.4}$
EvoSkill	$40.4^{\pm 0.3}$	$31.3^{\pm 0.8}$	$41.6^{\pm 0.6}$	$32.6^{\pm 0.8}$	$43.1^{\pm 0.5}$	$33.0^{\pm 1.1}$
SkillAdaptor	$\mathbf{41.6}^{\pm 0.5}$	$\mathbf{33.0}^{\pm 1.1}$	$\mathbf{43.9}^{\pm 0.7}$	$\mathbf{33.3}^{\pm 0.4}$	$\mathbf{44.8}^{\pm 0.4}$	$\mathbf{34.3}^{\pm 1.2}$

Table 2: Results on WebShop.

Here, t^* denotes the earliest accountable fault step whose correction is expected to improve the final outcome. π is a description of observed failure behavior and improvement suggestion.

The Linker then estimates which retrieved skills are most responsible for the failure:

$$\{(s_j, w_j)\} = \text{Link}(q, \tau, t^*, S_q). \quad (6)$$

The output is a weighted suspect set over retrieved skills, where a larger w_j indicates stronger estimated responsibility for the failure. The Linker additionally predicts an adaptation action $\hat{a} \in \{\text{REVISE}, \text{GENERATE}\}$. If the failure is attributed to an inappropriate or misleading retrieved skill, the trajectory is routed to skill revision. Otherwise, the failure is treated as an uncovered capability gap due to missing skill coverage and routed to new skill generation.

(2) Modification. Given the predicted action $\hat{a}$, the Modifier updates the skill collection:

$$K^+ = \text{Modify}(K, t^*, \hat{a}). \quad (7)$$

where Modify rewrites the highest-weighted skill and replaces it in K when $\hat{a} = \text{REVISE}$, and synthesizes a new skill from the localized context at t^* and appends it when $\hat{a} = \text{GENERATE}$.

To control redundancy growth, generated skills are filtered using the same encoder method as retrieval, together with a duplicate threshold θ_{dup}. Candidate skills whose semantic similarity exceeds the threshold are discarded before insertion.

(3) Qualification. All candidate updates are qualified respectively before being committed to the skill collection. Given the current collection K and candidate collection K^+, the framework re-executes tasks under both settings and compares their outcomes:

$$\Delta = \mathbb{E}_{q \sim \mathcal{Q}}\big[\mathcal{M}(q; K^+)\big] - \mathbb{E}_{q \sim \mathcal{Q}}\big[\mathcal{M}(q; K)\big] \quad (8)$$

where $\mathcal{M}(\cdot)$ denotes the execution feedback metric. The candidate update is accepted only when $\Delta \geq 0$. Otherwise, the modification is discarded and the original collection K is retained unchanged. This qualification stage suppresses harmful updates and stabilizes continual skill adaptation over long interaction horizons.

4 Experiments

Backbone models. We evaluate all methods using three backbone LLMs (Kimi-K2.5, GLM-5, GPT-5.2), and detailed configurations of each backbone model are provided in Appendix C.1.

Benchmarks and metrics. We evaluate on PinchBench (Kilo Code, 2026), Claw-Eval (Ye et al., 2026), and WebShop (Yao et al., 2022). Detailed benchmark descriptions and settings are provided in Appendix C.2.

Models and baselines. We compare with six representative baselines. Details for all baselines are summarized in Appendix C.3. All methods use the same backbone models and benchmark settings. Each setting is repeated with three independent runs, and tables report the mean and spread.

Main results. As shown in Tables 1 and 2, SKILLADAPTOR consistently improves over reported baselines across all three benchmarks with matched backbones. The clearest improvements appear on WebShop, where gains remain positive across all evaluated models. On PinchBench and Claw-Eval, improvements are smaller but still positive on all metrics, indicating that the method remains effective in the most open-ended setting. Overall, finer failure attribution improves the stability of training-free skill adaptation under frozen backbones. Against the strongest matched skill baseline in each column, the largest gains are +2.3 on

Configuration	WebShop		PinchBench	Claw-Eval	
	Score	Succ%	Avg Score%	Avg Score	Pass@3%
(0) Base model (no skill bank)	$32.1^{\pm1.4}$	$24.6^{\pm1.5}$	$63.6^{\pm8.7}$	$73.2^{\pm1.3}$	74.4%
(1) SKILLADAPTOR (full)	$\mathbf{41.6}^{\pm0.8}$	$\mathbf{33.0}^{\pm1.0}$	$\mathbf{67.2}^{\pm5.2}$	$\mathbf{75.8}^{\pm1.6}$	**77.4%**
(2) w/o Localizer & Linker	$35.8^{\pm0.9}$	$28.6^{\pm1.5}$	$65.3^{\pm6.8}$	$74.5^{\pm1.4}$	75.9%
(3) w/o qualifier gate	$34.0^{\pm2.1}$	$26.3^{\pm2.6}$	$65.8^{\pm8.1}$	$74.2^{\pm2.7}$	75.9%
(4) w/o Localizer, Linker, Qualifier (initial skills only)	$32.5^{\pm1.0}$	$25.3^{\pm2.5}$	$64.1^{\pm7.3}$	$73.9^{\pm1.8}$	74.4%

Table 3: Component ablations on Kimi-K2.5 (same harness and metrics as Table 1&2). Row (2) removes Localizer and Linker, row (3) removes Qualifier, row (4) uses only round-1 extracted skills without further attributed edits.

WebShop Score (GLM-5), +1.7 percentage points on WebShop Succ% (Kimi-K2.5), +1.5 on Pinch-Bench Avg Score% (GLM-5), +1.8 on Claw-Eval Avg Score (Kimi-K2.5).

Component ablation. Table 3 reports Kimi-K2.5 ablation results. Without Localizer and Linker, WebShop success drops to 28.6% and score to 35.8, while Claw-Eval Avg Score falls to 74.5, so step-level attribution is needed to target effective revisions. Without Qualifier, spread rises, including PinchBench ±8.1 versus ±5.2 and Claw-Eval Avg Score ±2.7, and WebShop success falls to 26.3% with ±2.6, so removing qualification allows unstable skills to enter retrieval. When disabling all adaptor modules and keeping only the initial LLM-extracted skill bank, spread stays high on PinchBench (±7.3), WebShop success is only 25.3±2.5%, and WebShop Score is 32.5 versus the 32.1 base model, so gains nearly vanish relative to the full settings. Skills distilled solely from successful trajectories do not reliably transfer across tasks, indicating that effective adaptation depends on precise failure attribution and qualification rather than skill accumulation alone.

Case study. We analyze a representative task from PinchBench to illustrate how SKILLADAP-TOR localizes failure signals to concrete skill spans, full execution traces, and the corresponding skill adaptation are provided in Appendix B.

Skill adaptations across adaptor rounds. Figure 2 shows the distribution of qualifier-approved skill adaptations across adaptor rounds and the corresponding performance trajectory on three benchmarks. Despite allowing up to ten rounds, the majority of accepted updates concentrate on the first two rounds. WebShop receives roughly 75% of all accepted writes in rounds 1–2, while Claw-Eval and PinchBench show 64% and 65%, respectively. Accepted writes fall to zero after round

Figure 2: Accepted writes and headline-score gains across adaptor rounds on Kimi-K2.5. Left axis is the incremental share f_h of qualifier-approved writes in round h. Right axis shows Δ in headline score *vs* the bare-LLM for Claw-Eval and PinchBench; the inset shows the corresponding WebShop Δ.

5 for WebShop and Claw-Eval, and after round 6 for PinchBench. This early concentration suggests that the dominant recurring failure modes are corrected during the initial adaptation phase, whereas later rounds contribute only incremental refinements. The performance trajectory follows a similar trend, with most gains emerging alongside the earliest accepted updates. The diminishing improvement in later rounds indicates that once major procedural deficiencies are resolved, remaining limitations are increasingly governed by the intrinsic capability of the backbone model rather than missing skill coverage.

5 Conclusion

This work presents SKILLADAPTOR, a training-free adaptor framework that updates external agent skills. Across WebShop, PinchBench, and Claw-Eval, SKILLADAPTOR consistently improves over no-skill and prior skill-adaptation baselines. Our results suggest that step-level failure attribution enables more precise and efficient agent skill adaptation than trajectory-level updates alone, while remaining lightweight and compatible with existing agent frameworks.

Limitations

This study has two limitations. First, the method is most effective when failures expose observable intermediate signals and required tool dependencies are available, and its performance may weaken under sparse, delayed feedback or missing external interfaces. Second, while our current experiments cover three public benchmarks, additional evaluation under longer-term deployment settings and broader distribution shifts remains an important direction for future work.

References

Salaheddin Alzubi, Noah Provenzano, Jaydon Bingham, Weiyuan Chen, and Tu Vu. 2026. Evoskill: Automated skill discovery for multi-agent systems. *arXiv preprint arXiv:2603.02766*.

HKUDS. 2026. Openspace. https://github.com/HKUDS/OpenSpace. Repository-only baseline (no archival paper at the time of writing).

Sirui Hong, Mingchen Zhuge, Jiaqi Chen, Xiawu Zheng, Yuheng Cheng, Ceyao Zhang, Jinlin Wang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. 2024. Metagpt: Meta programming for a multi-agent collaborative framework. In *The Twelfth International Conference on Learning Representations*.

Zisu Huang, Jingwen Xu, Yifan Yang, Ziyang Gong, Qihao Yang, Muzhao Tian, Xiaohua Wang, Changze Lv, Xuemei Gao, Qi Dai, Bei Liu, Kai Qiu, Xue Yang, Dongdong Chen, Xiaoqing Zheng, and Chong Luo. 2026. From raw experience to skill consumption: A systematic study of model-generated agent skills. *arXiv preprint arXiv:2605.23899*.

Yeonsung Jung, Trilok Padhi, Sina Shaham, Dipika Khullar, Joonhyun Jeong, Ninareh Mehrabi, and Eunho Yang. 2025. Co-evolving agents: Learning from failures as hard negatives. *arXiv preprint arXiv:2511.22254*.

Kilo Code. 2026. Pinchbench: Real-world benchmarks for OpenClaw agents. https://github.com/pinchbench/skill. Benchmark skill repository, task definitions, and scoring scripts; leaderboard at https://pinchbench.com/.

Xiangyi Li, Wenbo Chen, Yimin Liu, Shenghan Zheng, Xiaokun Chen, Yifeng He, Yubo Li, Bingran You, Haotian Shen, Jiankai Sun, Shuyi Wang, Binxu Li, Qunhong Zeng, Di Wang, Xuandong Zhao, Yuanli Wang, Roey Ben Chaim, Zonglin Di, Yipeng Gao, Junwei He, Yizhuo He, Liqiang Jing, Luyang Kong, Xin Lan, Jiachen Li, Songlin Li, Yijiang Li, Yueqian Lin, Xinyi Liu, Xuanqing Liu, Haoran Lyu, Ze Ma, Bowei Wang, Runhui Wang, Tianyu Wang, Wengao

Ye, Yue Zhang, Hanwen Xing, Yiqi Xue, Steven Dillmann, and Han-chung Lee. 2026. Skillsbench: Benchmarking how well agent skills work across diverse tasks. *arXiv preprint arXiv:2602.12670*.

Jiahang Lin, Shichun Liu, Chengjun Pan, Lizhi Lin, Shihan Dou, Zhiheng Xi, Xuanjing Huang, Hang Yan, Zhenhua Han, Tao Gui, and Yu-Gang Jiang. 2026. Agentic harness engineering: Observability-driven automatic evolution of coding-agent harnesses. *arXiv preprint arXiv:2604.25850*.

Hongyi Liu, Haoyan Yang, Tao Jiang, Bo Tang, Feiyu Xiong, and Zhiyu Li. 2026a. Skillsvote: Lifecycle governance of agent skills from collection, recommendation to evolution. *arXiv preprint arXiv:2605.18401*.

Xingyan Liu, Xiyue Luo, Linyu Li, Ganghong Huang, Jianfeng Liu, and Honglin Qiao. 2026b. Skillforge: Forging domain-specific, self-evolving agent skills in cloud technical support. *arXiv preprint arXiv:2604.08618*.

Yujian Liu, Jiabao Ji, Li An, Tommi Jaakkola, Yang Zhang, and Shiyu Chang. 2026c. How well do agentic skills work in the wild: Benchmarking LLM skill usage in realistic settings. *arXiv preprint arXiv:2604.04323*.

Ziyu Ma, Shidong Yang, Yuxiang Ji, Xucong Wang, Yong Wang, Yiming Hu, Tongwen Huang, and Xiangxiang Chu. 2026. Skillclaw: Let skills evolve collectively with agentic evolver. *arXiv preprint arXiv:2604.08377*.

Siru Ouyang, Jun Yan, Yanfei Chen, Rujun Han, Zifeng Wang, Bhavana Dalvi Mishra, Rui Meng, Chun-Liang Li, Yizhu Jiao, Kaiwen Zha, Maohao Shen, Vishy Tirumalashetty, George Lee, Jiawei Han, Tomas Pfister, and Chen-Yu Lee. 2026. SkillOS: Learning skill curation for self-evolving agents. *arXiv preprint arXiv:2605.06614*.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, UIST '23. Association for Computing Machinery.

Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. 2024. Gorilla: Large language model connected with massive apis. In *Advances in Neural Information Processing Systems*.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems*, volume 36.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao.

2023. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 36.

Shuzheng Si, Haozhe Zhao, Yu Lei, Qingyi Wang, Dingwei Chen, Zhitong Wang, Zhenhailong Wang, Kangyang Luo, Zheng Wang, Gang Chen, Fanchao Qi, Minjia Zhang, and Maosong Sun. 2026. From context to skills: Can language models learn from context skillfully? *arXiv preprint arXiv:2604.27660.*

Peter Steinberger. 2026. Openclaw: Personal AI assistant. https://github.com/openclaw/openclaw.

Chenxi Wang, Zhuoyun Yu, Xin Xie, Wuguannan Yao, Runnan Fang, Shuofei Qiao, Kexin Cao, Guozhou Zheng, Xiang Qi, Peng Zhang, and Shumin Deng. 2026. SkillX: Automatically constructing skill knowledge bases for agents. *arXiv preprint arXiv:2604.04804.*

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2023. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291.*

Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2025. Agent workflow memory. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 63897–63911.

Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. 2025. A-mem: Agentic memory for LLM agents. In *Advances in Neural Information Processing Systems*.

Yifan Yang, Ziyang Gong, Weiquan Huang, Qihao Yang, Ziwei Zhou, Zisu Huang, Yan Li, Xuemei Gao, Qi Dai, Bei Liu, Kai Qiu, Yuqing Yang, Dongdong Chen, Xue Yang, and Chong Luo. 2026. SkillOpt: Executive strategy for self-evolving agent skills. *arXiv preprint arXiv:2605.23904.*

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. 2022. Webshop: Towards scalable real-world web interaction with grounded language agents. In *Advances in Neural Information Processing Systems*, volume 35.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations*.

Bowen Ye, Rang Li, Qibin Yang, Yuanxin Liu, Linli Yao, Hanglong Lv, Zhihui Xie, Chenxin An, Lei Li, Lingpeng Kong, Qi Liu, Zhifang Sui, and Tong Yang. 2026. Claw-eval: Towards trustworthy evaluation of autonomous agents. arXiv preprint arXiv:2604.06132.

Hanrong Zhang, Shicheng Fan, Henry Peng Zou, Yankai Chen, Zhenting Wang, Jiayu Zhou, Chengze Li, Wei-Chieh Huang, Yifei Yao, Kening Zheng, Xue Liu, Xiaoxiao Li, and Philip S. Yu. 2026a. Coevoskills: Self-evolving agent skills via co-evolutionary verification. *arXiv preprint arXiv:2604.01687.*

Xing Zhang, Yanwei Cui, Guanghui Wang, Ziyuan Li, Wei Qiu, Bing Zhu, and Peiyang He. 2026b. Library drift: Diagnosing and fixing a silent failure mode in self-evolving LLM skill libraries. *Preprint*, arXiv:2605.19576.

Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. 2024. Expel: LLM agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19632–19642.

A   Related Work

Long-horizon agent systems and capability decomposition Large language model agents are increasingly applied to long-horizon interactive tasks such as WebShop (Yao et al., 2022), software terminals, and tool-augmented workflows (Yao et al., 2023; Schick et al., 2023; Patil et al., 2024; Hong et al., 2024). Recent work studies how reasoning, action, memory, and tool usage can be integrated into unified execution loops (Shinn et al., 2023; Park et al., 2023; Wang et al., 2023). Existing systems are commonly organized around interaction, memory, and skills. While interaction and memory have been extensively studied through tool augmentation and retrieval mechanisms, skill evolution in long-horizon environments remains less explored, especially under concrete execution failures.

Self-adapting skill methods Recent work explores how skills can be extracted and refined from agent experiences. Ctx2Skill (Si et al., 2026) studies context-aware retrieval and large-scale skill infrastructure. SkillForge (Liu et al., 2026b) performs failure analysis and minimal skill revision from execution traces. EvoSkill (Alzubi et al., 2026) studies skill discovery under distribution shift, while CoEvoSkills (Zhang et al., 2026a) introduces iterative generation and verification for skill refinement. SkillClaw (Ma et al., 2026) extends skill adaptation to deployment settings through cross-session feedback aggregation. SkillsVote (Liu et al., 2026a) further studies lifecycle governance for reusable agent skills, including collection, recommendation, attribution, and evidence-gated evolution in large-scale skill ecosystems. SkillX (Wang et al., 2026) and SkillOS (Ouyang et al., 2026) further study hierarchical skill organization and feedback-driven curation. SkillOpt (Yang et al., 2026) formulates skill editing as a controllable evolution process with validation-gated textual updates to compact skill artifacts. Library Drift (Zhang et al., 2026b) studies failure modes in self-evolving skill libraries arising from semantic and distributional drift over time.

Most existing approaches operate at the trajectory or session level, where failures are aggregated before updates are applied. As a result, they often lack precise localization of the execution step responsible for downstream errors. Several methods further rely on multi-agent coordination or iterative verification pipelines for adaptation, yet our method adopts a lightweight single-agent frame-

work, enabling direct and efficient skill adaptation.

Harness systems and skill adaptation Another line of work studies how external orchestration systems stabilize agent execution. AHE (Lin et al., 2026) and OpenSpace (HKUDS, 2026) improve execution reliability through workflow organization and controlled tool interaction. Complementary studies investigate skill retrieval and reuse at scale. Skill-Usage (Liu et al., 2026c) and SkillsBench (Li et al., 2026) evaluate skill effectiveness across tasks. Huang et al. (Huang et al., 2026) conduct a systematic study of the full trajectory-to-skill lifecycle, introducing extraction efficacy and target evolvability metrics to disentangle skill quality from model adaptability.

These studies improve execution robustness and skill reuse, but they do not directly address how reusable skills should be updated after concrete execution failures. Our work instead focuses on step-level failure attribution and fine-grained skill evolution under long-horizon interaction.

B   Case Study

Trajectory-level failures are often difficult to translate into precise skill updates because only a small portion of the interaction is directly responsible for the final outcome. We analyze a PinchBench task, `CSV and Excel Data Summarization` (Figure 3), where SKILLADAPTOR localizes the failure to interaction step six and links it to the fourth procedure of the most relevant injected skill. This attribution converts an otherwise broad trajectory failure into a concrete and directly editable skill span grounded in execution feedback.

The example also reflects a broader pattern across benchmarks. SKILLADAPTOR is most effective in tasks where failures can be localized to explicit intermediate decisions, such as incorrect parsing, invalid tool arguments, or missing execution steps. These conditions occur most frequently in Data and Code tasks, where execution traces expose a clear procedural structure and a single faulty skill span can often be revised and reused across related problems. More moderate gains are observed in Productivity tasks. In these settings, localized revisions can improve execution ordering, schema usage, or argument selection, but final performance may still be constrained by environment-side rules or external verification requirements. By contrast, improvements are smaller in Research, Memory, and Security tasks, where failures often

Figure 3: PinchBench task CSV and Excel Data Summarization before (left) and after (right) skill adaptation. The localized failure at interaction step six is mapped to the fourth line of the pre-revision skill, which becomes the target span for revision. The revised card reduces the mismatch between shallow qualification checks and final permission by requiring recomputation before finalization.

depend on persistent state, external knowledge, or cross-session context that cannot be fully resolved through localized skill refinement alone.

Overall, SKILLADAPTOR is most effective when the failure signals are localizable, and execution traces that expose intermediate structure, while less effective when task success depends on external systems or persistent state beyond the scope of a single skill update.

C Experimental Details

C.1 Implementation Details

All stages of skill adaptation, including initialization rollout, failure localization, responsibility attribution, skill revision, skill generation, and qualification, are performed using the same backbone LLM configured for the current experiment setting.

Skill Initialization, Injection and Adaptation. Skills are represented using the SKILL.md format adopted by OpenClaw-style agents, where each skill contains lightweight structured metadata together with natural-language behavioral instructions and optional execution guidance.

For skill extraction, generation, and revision, we use a relatively high temperature (0.9) to encourage diverse reasoning traces and broaden coverage of failure-induced behaviors.

We use Qwen3-Embedding-8B for dense retrieval over the skill collection. At inference time, candidate skills are first filtered by cosine similarity using a minimum threshold of 0.45, after which the top-10 candidates are reranked by the backbone LLM conditioned on the current task description.

To suppress redundancy accumulation during continual adaptation, newly generated or revised skills are semantically compared against the existing collection using the same embedding model. Candidate updates whose cosine similarity exceeds the duplicate threshold $\theta_{\text{dup}} = 0.95$ are discarded before insertion.

Skill adaptation proceeds for at most 10 rounds, with early stopping triggered if the skill collection remains unchanged for 3 consecutive rounds.

Execution. Across all benchmarks, we set the temperature to 0 for execution. For WebShop, all methods are evaluated in the official WebShop Gym-based environment and the standard evaluator released by the benchmark authors. For PinchBench and Claw-Eval, experiments are conducted using the benchmark-provided OpenClaw runtime and task configurations. We keep the default sandbox, tool interfaces, execution settings, grading pipeline, and aggregation rules unchanged, and

vary only the backbone LLM or adaptation method across experiments.

During skill iteration, the adaptor only has access to execution trajectories and their success or failure signals. It does not observe internal evaluator logic, reward decomposition, or any benchmark-specific scoring details. All sandbox settings, tool interfaces, execution configurations, grading pipelines, and aggregation rules are kept unchanged, while we vary only the backbone LLM or the adaptation method across experiments.

C.2 Benchmarks

WebShop WebShop(Yao et al., 2022) is an interactive web navigation benchmark for multi-step online shopping tasks. We follow the data split of Jung et al. (2025), with 1,624 training instances, and a test set of 200 instructions. Our tables report **task score** and **success rate** on the test set, with identical environment settings across methods.

PinchBench PinchBench(Kilo Code, 2026) is an OpenClaw(Steinberger, 2026) benchmark for long-horizon tool-mediated agents. The task set covers coding and DevOps scripts, spreadsheets, and log analysis, meeting transcripts, email and calendar workflows, and web research briefs. We stratify by the manifest category label and randomly split each stratum into 49 tasks for skill adaptation and 97 test tasks, keeping at least one training example per category. We report **Avg Score%** in the main table.

Claw-Eval Claw-Eval(Ye et al., 2026) is an OpenClaw(Steinberger, 2026) benchmark for open-ended agent evaluation. Tasks span single-turn office and ops workflows, finance and ticket triage, and multi-turn advisory dialogues with a simulated user. We use the Overall Dimension of the official leaderboard, which follows the benchmark's standard aggregation protocol and consists of General tasks and Multi-turn tasks. We stratify Overall by difficulty and multi-turn domain, randomly split each domain and aggregate to obtain 66 tasks for skill adaptation and 133 test tasks. We report **Avg Score** and **Pass@3** in the main table.

C.3 Baselines

Unless stated otherwise, each baseline sits on the same training-free base LLM as our method, under the same experiment settings. External skills or memory are applied in whatever module the baseline defines.

Base model This method runs the policy with no external skills or experience injected. We evaluate test tasks on Kimi-K2.5, GLM-5, and GPT-5.2.

A-Mem A-Mem(Xu et al., 2025) implements agentic memory. The model chooses what to store, retrieve, and revise in a persistent store rather than a fixed scratchpad. We follow the public A-Mem recipe, including the benchmark prompts and harness assumptions described in the original release.

Agent Workflow Memory Agent Workflow Memory(Wang et al., 2025), abbreviated AWM, distills reusable workflows from past trajectories and retrieves them on new tasks with lightweight string matching. We reuse the wiring prescribed in our benchmark runbook with identical tool calls, step limits, and scoring.

ExpeL ExpeL(Zhao et al., 2024) extracts qualitative lessons from high- versus low-reward rollouts and injects them as free-text hints at test time. Its artifacts read as retrospective critiques rather than explicit workflow templates.

EvoSkill EvoSkill(Alzubi et al., 2026) performs iterative skill discovery from traces and maintains a skill pool over time. We run it in the same training-free regime as our other skill-bank baselines and report WebShop numbers in Table 2.

OpenSpace OpenSpace(HKUDS, 2026) is a training-free agent system that ships skill libraries and iterative skill refinement loops on top of an OpenClaw-class harness. The released codebase targets long-horizon desktop-style agents rather than a single fixed policy template. We submit runs through the same PinchBench and Claw-Eval channels as the base model so that scores stay comparable under the OpenClaw evaluation stack(Steinberger, 2026).

D Input Tokens and Interaction Steps

Retrieving and injecting skills add procedural descriptions to the prompt in each task, which inflates input tokens. This effect is more pronounced on PinchBench and Claw-Eval, where tool usage patterns and multi-step reasoning chains lead to repeated exposure of skill-related context across interactions. For Kimi-K2.5, mean input tokens increase from 13.9k to 16.9k on PinchBench and from 11.5k to 13.9k on Claw-Eval, while WebShop increases from 1.5k to 2.7k, remaining within a lower token range.

| Base Model | A-Mem | AWM | ExpeL | OpenSpace | EvoSkill | SkillAdaptor |

Figure 4: Overview of mean interaction steps (top) and mean input tokens (bottom) per task across the three benchmarks, for the methods listed in Tables 4 and 5. SkillAdaptor increases measured prompt size while reducing mean steps on PinchBench and Claw-Eval relative to Base. WebShop stays in a lower token band with smaller absolute shifts.

Despite the increased per-step context, the average number of interaction steps consistently decreases on the two desktop benchmarks. Mean steps decrease from 10.4 to 9.8 on PinchBench and from 7.3 to 5.8 on Claw-Eval, with a similar reduction from 18.9 to 15.5 on WebShop. This pattern suggests that skill augmentation shifts part of the decision burden from multi-step interaction to in-context reasoning at each step, reducing the need for repeated exploration and correction at the trajectory level.

Importantly, the reduction in interaction steps does not directly imply lower overall computational cost, but instead reflects a redistribution of computation from environmental interaction to richer per-step context conditioning. As a result, token usage and interaction length should be interpreted jointly, as they capture different aspects of the same adaptation process rather than independent efficiency measures.

WebShop			
Method	**Kimi-K2.5**	**GLM-5**	**GPT-5.2**
Base Model	1507	1308	1440
A-Mem	1968	1810	1985
AWM	2364	2229	2507
ExpeL	2316	2311	2592
EvoSkill	2585	2450	2663
SkillAdaptor	2651	2516	2690
PinchBench			
Method	**Kimi-K2.5**	**GLM-5**	**GPT-5.2**
Base Model	13927	15039	16284
OpenSpace	16207	19052	18941
SkillAdaptor	16902	19954	18607
Claw-Eval			
Method	**Kimi-K2.5**	**GLM-5**	**GPT-5.2**
Base Model	11470	10515	10763
OpenSpace	13684	12042	12720
SkillAdaptor	13933	12769	12917

Table 4: Input token statistics. Values are mean input tokens per task execution.

WebShop			
Method	**Kimi-K2.5**	**GLM-5**	**GPT-5.2**
Base Model	18.9	18.4	17.1
A-Mem	17.9	19.2	17.0
AWM	17.5	17.1	16.4
ExpeL	16.6	17.9	15.9
EvoSkill	15.8	16.5	14.9
SkillAdaptor	15.5	15.3	15.1
PinchBench			
Method	**Kimi-K2.5**	**GLM-5**	**GPT-5.2**
Base Model	10.4	10.2	9.3
OpenSpace	10.1	9.6	9.7
SkillAdaptor	9.8	9.2	9.9
Claw-Eval			
Method	**Kimi-K2.5**	**GLM-5**	**GPT-5.2**
Base Model	7.3	6.9	6.7
OpenSpace	6.0	6.6	6.1
SkillAdaptor	5.8	6.4	6.0

Table 5: Execution step statistics. Values are mean interaction steps per task execution.

E   Prompt Templates

This appendix presents the core prompt templates used in the training-free SKILLADAPTOR adaptor pipeline. We report compact but complete prompt skeletons for failure localization, responsibility linking, skill revision, skill generation, and qualification gating. All templates are written in English and intended for top-tier conference style reproducibility.

Shared Constraint Template

Role. You are an expert agent debugger. Output must be deterministic, evidence-grounded, and directly actionable.

Global constraints.

- Do not fabricate facts; use only trajectory evidence.

- If repeated actions show no progress, explicitly flag loop risk.

- Never propose runtime package installation or environment creation.

- Flag **same-tool same-parameter** calls repeated ≥ 3 times without meaningful intermediate operations (excluding benign repeats such as Read/Grep/Glob/TodoWrite).

- Evaluate sensitive-path risk only from executable parameters, not from natural-language path mentions.

- In shell contexts, treat sudo and su - as privilege-escalation command tokens; avoid false positives in non-command arguments.

- Reject destructive operations targeting root or system-critical directories; enforce workspace-scoped operations.

Figure 5: Shared safety and quality constraints applied across all stages.

Fault Localizer Prompt

Task. Analyze a failed trajectory, extract a candidate fault chain, and return one primary fault step for this round.

Input fields. Task description, trajectory summary, recent critical steps, and fault-type definitions.

Instructions.

- Extract 2–4 candidate fault steps that are most likely to explain the failure, ranked by evidence strength.

- Select one primary step t^* from the candidate chain for the current revision attempt.

- Distinguish `skill_wrong` (an existing skill misguided the agent) and `skill_missing` (no existing skill covered the situation).

- If repetitive ineffective actions appear, include loop-prevention guidance in the improvement principle.

Output format (strict).

- `fault_chain`: ranked step ids (1-based), e.g., [5,7,9]

- `t_star`: primary step selected from `fault_chain`

- `improvement_principle`: one concise correction statement

- `fault_type`: one of predefined classes

- `reason`: brief evidence-grounded explanation

Figure 6: Template for fault-chain localization and primary-step selection in failed trajectories.

Skill Linker Prompt

Task. Assign responsibility weights from a localized failure to active skill candidates.

Input fields. Fault context, wrong action, improvement principle, and candidate skills (title/description/trigger snippets).

Attribution rules.

- Use weighted evidence from direct instruction match, context mismatch, omission, and misleading wording.

- Typical ranges: 0.8–1.0 (fully responsible), 0.5–0.7 (partially responsible), 0.2–0.4 (weakly related), 0.0–0.1 (irrelevant).

- If no skill is meaningfully responsible, return an empty attribution list.

Output format (JSON). `{"attributions":[{"skill_id":"...", "weight":0.75, "reason":"..."}]}`

Figure 7: Template for step-level responsibility attribution.

Skill Reviser Prompt

Task. Perform minimal, targeted edits to an existing skill after a linked failure.
Revision policy.

- Preserve working parts and prefer additive edits.

- Add preconditions, disambiguation, negative examples, and qualification checks only where evidence supports the change.

- Include explicit anti-loop and safety guards when failure traces show repetitive behavior or risky shell actions.

Output format (JSON).

- Use the same skill schema as the generator and wrap it with mode metadata.

- `update_mode = revise_existing`

- `target_skill_id = <existing skill id>`

- `skill_profile` with strict fields:

- `title`, `principle`, `when_to_apply`

- `procedure` (3–6 deterministic steps)

- `qualification_criteria`

- `negative_example{what_not_to_do, why_it_fails}`

Figure 8: Template for minimal skill revision under explicit evidence.

Skill Generator Prompt

Task. Convert failure evidence into a reusable new skill when no existing skill can be safely revised.

Generation policy.

- Extract reusable principles, not one-off task hacks.

- Define precise triggers as *observation pattern* + *state condition*.

- Provide executable procedures with verification checkpoints.

- Include explicit negative examples and stop conditions.

Output format (JSON).

- Use the same skill schema as the reviser and wrap it with mode metadata.

- `update_mode = generate_new`

- `target_skill_id = null`

- `skill_profile` with strict fields:

- `title`, `principle`, `when_to_apply`

- `procedure` (3–6 deterministic steps)

- `qualification_criteria`

- `negative_example{what_not_to_do, why_it_fails}`

Figure 9: Template for failure-driven reusable skill generation.