Hebbian Deep Learning Without Feedback

Abstract

Recent approximations to backpropagation (BP) have mitigated many of BP's computational inefficiencies and incompatibilities with biology, but important limitations still remain. Moreover, the approximations significantly decrease accuracy in benchmarks, suggesting that an entirely different approach may be more fruitful. Here, grounded on recent theory for Hebbian learning in soft winner-take-all networks, we present multilayer SoftHebb, i.e. an algorithm that trains deep neural networks, without any feedback, target, or error signals. As a result, it achieves efficiency by avoiding weight transport, non-local plasticity, time-locking of layer updates, iterative equilibria, and (self-) supervisory or other feedback signals – which were necessary in other approaches. Its increased efficiency and biological compatibility do not trade off accuracy compared to state-of-the-art bio-plausible learning, but rather improve it. With up to five hidden layers and an added linear classifier, accuracies on MNIST, CIFAR-10, STL-10, and ImageNet, respectively reach 99.4%, 80.3%, 76.2%, and 27.3%. In conclusion, SoftHebb shows with a radically different approach from BP that Deep Learning over few layers may be plausible in the brain and increases the accuracy of bio-plausible machine learning.

1 Introduction: Backpropagation and its limitations

The core algorithm in deep learning (DL) is backpropagation (BP), which operates by first defining an error or loss function between the neural network's output and the desired output. Despite its enormous practical utility (Sejnowski, 2020), BP requires operations that make training a highly expensive process computationally, setting limits to its applicability in resource-constrained scenarios. In addition, the same operations are largely incompatible with biological learning, demanding alternatives. In the following paragraphs we describe these limitations and their practical and biological significance.

Weight transport. Backpropagating errors involves the transpose matrix of the forward connection weights. This is not possible in biology, as synapses are unidirectional. Synaptic conductances cannot be transported to separate backward synapses either. That is the weight transport problem (Grossberg, 1987; Crick, 1989), and it also prevents learning on energy-efficient hardware substrates (Crafton et al., 2019). Specifically, neuromorphic computing hardware is one of the most researched approaches to overcoming the efficiency and scaling bottlenecks of the von Neumann architecture that underlies today's computer chips (Indiveri, 2021). A key element of the neuromorphic strategy is to place computation within the same devices that also store memories, akin to the biological synapses, which perform computations but also store weights (Sebastian et al., 2020; Sarwat et al., 2022a;b). Transposing such stored memories for a backward pass is required in BP, but implies significant circuitry and energy expenses, thus preventing the full potential of neuromorphic technology (Crafton et al., 2019).

Non-local plasticity. BP cannot update each weight based only on the immediate activations of the two neurons that the weight connects, i.e. the pre- and post-synaptic neurons, as it requires the error signal, which is computed at a different point in time and elsewhere in the network, i.e. at the output. That makes BP non-local in space and time, which is a critical discrepancy from the locality that is generally believed to govern biological synaptic plasticity (Baldi et al., 2017). This non-locality implies further computational inefficiencies. Specifically, forward-passing variables must be memorized, which increases memory

Table 1: Accuracies on CIFAR-10, and qualities of biological plausibility and computational efficiency, for various learning algorithms. SoftHebb's type of algorithm has all four efficient and plausible qualities. SoftHebb also achieves the highest accuracy, except for backprop, and its unsupervised learning only involved a single epoch.

Qualities	Accuracy	Layers	Algorithm	Reference
	99.4	152	Backprop (cross-entropy)	Kolesnikov et al. 2020
	84.0	4	Backprop (cross-entropy)	Ours
Weight-transport-free	71.8	5	Feedback Alignment	Frenkel et al. 2021
Local plasticity	~60	6	Predictive Coding	Millidge et al. 2020
	13.4	5	Equilibrium Propagation (2-phase)	Laborieux et al. 2021
	78.5	5	EP (2-phase, random sign)	Laborieux et al. 2021
	79.9	5	Burstprop	Payeur et al. 2021
	61.0	5	BurstCCN	Greedy et al. 2022
	70.5	5	Direct Feedback Alignment	Frenkel et al. 2021
	71.5	5	DFA (untrained convs)	Frenkel et al. 2021
Update-unlocked	65.6	5	Direct Random Target Projection	Frenkel et al. 2021
	69.0	5	DRTP (untrained convs)	Frenkel et al. 2021
	73.1	5	Single Sparse DFA	Crafton et al. 2019
	53.5	11	Latent Predictive Learning	Halvagal and Zenke 2022
Unsupervised	73.7	4	Self Organising Maps	Stuhr and Brauer 2019
	72.2	2	Hard WTA	Grinberg et al. 2019
	64.6	4	Hard WTA	Miconi 2021
	80.3	4	SoftHebb (1 epoch)	Ours

requirements (Löwe et al., 2019). Moreover, additional backward signals must be computed and propagated, which increases operations and electrical currents. It is noteworthy that these aspects are not limiting only future neuromorphic technologies, but even the hardware foundation of today's DL, i.e. graphical processing units (GPUs), which have their own constraints in memory and FLOPS.

Update locking. The error credited by BP to a synapse can only be computed after the information has propagated forward and then backward through the entire network. The weight updates are therefore time-locked to these delays (Czarnecki et al., 2017; Jaderberg et al., 2017; Frenkel et al., 2021). This slows down learning, so that training examples must be provided at least as slowly as the time to process the propagation through the two directions. Besides this important practical limitation of BP for DL, it also does not appear plausible that multiple distant neurons in the brain coordinate their processing and learning operations with such precision in time, nor that the brain can only learn from slow successions of training examples.

Global loss function. BP is commonly applied in the supervised setting, where humans provide descriptive labels of training examples. This is a costly process, thus supervised BP cannot exploit most of the available data, which is unlabelled. In addition, it does not explain how humans or animals can learn without supervisors. As a result, significant research effort has been dedicated to techniques for learning without labels, with increasing success recently, especially from self-supervised learning (SSL) (Chen et al., 2020; Mitrovic et al., 2020; Lee et al., 2021; Tomasev et al., 2022). In SSL, BP can also use certain supervisory signals generated by the model itself as a global error. Therefore, while BP does not require labels per se, it does require top-down supervision in the form of a global loss function. The drawback of this is that learning then becomes specialized to the particular task that is explicitly defined by the minimization of the loss function, as opposed to the learning of generic features. Practically, this is expressed in DL as overfitting, sensitivity to adversarial attacks (Madry et al., 2017; Moraitis et al., 2021), and limited transferability or generalizability of the learned features to other tasks or datasets (Lee et al., 2021). Moreover, a global optimization scheme such as BP cannot be considered a plausible model of all learning in the brain, because learning in ML benchmark tasks does emerge from highly biological

plasticity rules without global (self-)supervision, e.g. through unsupervised Hebbian-like learning (Diehl and Cook, 2015; Moraitis et al., 2020; 2021; Garcia Rodriguez et al., 2022).

2 ALTERNATIVES TO BACKPROPAGATION AND THEIR LIMITATIONS

Unsupervised Hebbian learning in cortex. Hebbian-like are those plasticity rules that depend only on the activity of pre- and post-synaptic neurons. If such plasticity is combined with between-neuron competition that suppresses weakly activated neurons in a layer, e.g. as an argmax, it can lead to learning of useful features in the absence of any (self-)supervision (Sanger, 1989; Linsker, 1992). This is a radically different approach from BP. It is not governed by a global optimization process, but rather emerges from local synaptic plasticity as a purely bottom-up self-organization. Without supervision, feedbacks, or targets, competitive Hebbian learning circumvents all five limitations of BP, as it does not require any back-propagating signals. Namely, it is free of weight transport, non-localities, locking problems, and global losses. These are significant practical advantages. Moreover, these properties make Hebbian learning much more plausible biologically. Besides, there is abundant evidence for Hebbian-like plasticity in the brain, in forms based on the spiking type of biological neuron activations (Sjöström et al., 2001; Markram et al., 2011; Feldman, 2012). Even the competitive network connectivity that leads to useful

Figure 1: First successful multilayer results. Soft-Hebb's CIFAR-10 accuracy increases with depth, compared with prior work. Number of *hidden* layers is indicated.

learning through such plasticity is strongly supported by biological observations. Specifically, circuits that rely on competition between neurons through lateral inhibition are found throughout the cortical sheet of the mammalian brain (Douglas and Martin, 2004; Binzegger et al., 2004), and are commonly described as winner-take-all (WTA). Furthermore, such competitive learning has been deeply studied computationally and theoretically for a long time under various forms (Von der Malsburg, 1973; Nessler et al., 2013; Diehl and Cook, 2015; Krotov and Hopfield, 2019; Moraitis et al., 2020). All these aspects would be important advantages if such learning could underlie DL. However, unsupervised Hebbian learning has only been effective in shallow networks. To be precise, adding layers has failed to produce significant performance improvements in standard benchmarks (Figure 1) (Amato et al., 2019; Lagani et al., 2021; Miconi, 2021). Arguably, this has been the case because emergent bottom-up learning from plasticity is hard to reconcile with top-down learning from a loss function, and the latter approach has been the backbone of DL. Those competitive Hebbian approaches that were normative, i.e. that derived a plasticity rule from an optimization principle, were based on principles that do not appear compatible with successful DL techniques, either because of dramatically different network types (Nessler et al., 2009; 2013) or loss functions (Pehlevan and Chklovskii, 2015).

SoftHebb. Recent work, however, has advanced the theory behind Hebbian WTA learning in terms that are more compatible with DL. Specifically, Moraitis et al. (2021) used a simple softmax to implement a soft WTA (Equation (1)), which lends a Bayesian interpretation to the network and its learning (see also Nessler et al. (2009; 2013)). Moraitis et al. (2021) also derived a Hebbian-like plasticity rule (Equation (2)) that minimizes the Kullback-Leibler divergence of the model's probability distribution from the input's, and cross-entropy from the labels under certain assumptions, without having access to those labels. In one-layer networks, SoftHebb showed increased learning speed and significantly higher robustness to noise and adversarial attacks. Its theoretical results seem important towards deeper networks, but they were not sufficient for a practical demonstration. Here (Section 3), we provide a SoftHebb-based setup that does achieve depth in Hebbian learning.

Approximations of backpropagation. Alternatives that are not radically different from BP but rather approximate it, while mitigating some of its issues, have attracted heavy research interest with increasing success. For example, self-supervised learning enables BP to learn without labels (Hadsell et al., 2006), with instances such as SimCLR (Chen

et al., 2020) and follow-ups (Mitrovic et al., 2020; Grill et al., 2020; He et al., 2020; Caron et al., 2020; Tomasev et al., 2022) reaching rather high performance. A different approach, Feedback Alignment (FA), (Lillicrap et al., 2016; Frenkel et al., 2021), solves the weight-transport problem. Direct Feedback Alignment (Nøkland, 2016; Frenkel et al., 2021) as an extension of FA, also avoids non-local computations for weight updates. The spatial non-locality of backpropagation has also been addressed by other algorithms such as predictive coding (Hadsell et al., 2006; Chen et al., 2020), equilibrium propagation (Scellier and Bengio, 2017; Laborieux et al., 2021), burstprop (Payeur et al., 2021). The work of Löwe et al. (2019), and CLAPP by Illing et al. (2021) are self-supervised algorithms that avoid not only reliance on labels but also spatially non-local learning. However, they require contrasting of examples known to be of different type. A very recent self-supervised approach avoids this requirement by adding a Hebbian term to learning (Halvagal and Zenke, 2022). This makes it a rather plausible algorithm for the brain, but it still relies on comparisons between distinctly different views of each individual input. Moreover, its performance is significantly worse on CIFAR-10 and STL-10 than this paragraph's previous references. In fact, all aforementioned approaches cause significant drop in accuracy compared to BP, and most cases are not applicable to datasets as complex as ImageNet (Bartunov et al., 2018). An algorithm that avoids the non-locality of end-to-end BP and also achieves quite high accuracy in CIFAR-10 was proposed by Nøkland and Eidnes (2019). However, it relies on an auxiliary trained network added to each layer, which increases complexity, and supervision, which requires labels. Other works have achieved learning with local plasticity, while avoiding weight transport and the update-locking problem (Crafton et al., 2019; Frenkel et al., 2021). However, they suffer from large performance drops and rely on supervision. Clearly, significant progress compared to standard BP has been made through multiple approaches, but important limitations remain (Table 1). These limitations would be surmounted if a competitive Hebbian algorithm performed well in multilayer networks and difficult tasks. Here, we explore the potential of SoftHebb (Moraitis et al., 2021), i.e. the recent algorithm that seems fitting to this goal. Our results in fact demonstrate a multilayer learning setup, reaching relatively high performance for bio-plausible algorithms on difficult tasks, with high efficiency and tight biological constraints. In the next section we describe this setup.

3 OVERVIEW OF MULTILAYER SOFTHEBB

The key elements of the multilayer SoftHebb model and algorithm that combined achieve good accuracy without compromising its efficiency and biological-plausibility are the following.

SoftHebb (Moraitis et al., 2021) in a layer of K neurons realizes a soft WTA competition through softmax, parametrized by a base b or equivalently a temperature τ:

$$y_k = \frac{b^{u_k}}{\sum_{l=1}^{K} b^{u_l}} = \frac{e^{\frac{u_k}{\tau}}}{\sum_{l=1}^{K} e^{\frac{u_l}{\tau}}}, \tag{1}$$

where u_k is the k-th neuron's total weighted input, and y_k is its output after accounting for competition from neurons l. The second key aspect in the SoftHebb algorithm is the plasticity rule of synaptic weights and neuronal biases. Biases represent prior probabilities in the probabilistic model realized by the network. In our experiments here we omitted them, presuming a fixed uniform prior. The plasticity defined for a synaptic weight w_{ik} from a presynaptic neuron i with activation x_i to a neuron k is

$$\Delta w_{ik}^{(SoftHebb)} = \eta \cdot y_k \cdot (x_i - u_k \cdot w_{ik}). \tag{2}$$

Notably, all variables are temporally and spatially local to the synapse. The rule provably optimizes the model to perform Bayesian inference of the hidden causes of the data (Moraitis et al., 2021) (see also Section 2).

Convolutions. Towards a multilayer architecture, and to represent input information of each layer in a more distributed manner, we used a localized representation through convolutional kernels. The plasticity rule is readily transferable to such an architecture. Convolution can be viewed as a data augmentation, where the inputs are no longer the original images but are rather cropped into smaller patches that are presented to a fully connected SoftHebb network. The plasticity of one such neuron over all patches is itself

an operation that involves convolutions. Exploiting this sped up our learning simulations significantly. Convolution with weight sharing between patches is efficient for parallel computing platforms like GPUs, but in its literal sense it is not biologically plausible. However, this does not fundamentally affect the plausibility of convolutions, because the weights between neurons with different localized receptive fields can become matching through biologically plausible rules (Pogodin et al., 2021).

Alternative activations for forward propagation. In addition to the softmax involved in the plasticity rule, different activation functions can be considered for propagation to each subsequent layer. In a biological implementation, this dual type of activation may be implemented by multiplexing overlapping temporal or rate codes of spiking neurons, which have been studied and modelled extensively (Naud et al., 2008; Kayser et al., 2009; Akam and Kullmann, 2014; Herzfeld et al., 2015; Moraitis et al., 2018; Payeur et al., 2021). For forward propagation, we settled on a combination of rectified polynomial unit (RePU) (Krotov and Hopfield, 2016; 2019), with Triangle (Appendix A.3.1), which perform well (Coates et al., 2011; Miconi, 2021), and also offer tunable parametrization.

Soft anti-Hebbian plasticity. Previous Hebbian-like algorithms have found anti-Hebbian terms in the plasticity to be helpful in single-layer competitive learning (Krotov and Hopfield, 2019; Grinberg et al., 2019). However, such plasticity matched the assumptions of a hard WTA, as opposed to SoftHebb's distributed activation, and involved additional hyperparameters. Here we introduce a new, simple form of anti-Hebbian plasticity for soft WTA networks, that simply negates SoftHebb's weight update (Equation (2)) in all neurons except the maximally activated one.

Weight-norm-dependent adaptive learning rate. We introduce a per-neuron adaptive learning rate scheme that stabilizes to zero as neuron weight vectors converge to a sphere of radius 1, and is initially big when the weight vectors' norms are large compared to 1: $lr_i = lr \cdot (r_i - 1)^{lrp}$, where lrp is a power hyperparameter. This per-neuron adaptation based on the weights remains a local operation and is reminiscent of another important adaptive learning rate scheme that is individualized per synapse, has biological and theoretical foundations and speeds up learning (Aitchison, 2020; Aitchison et al., 2021). Ours is arguably simpler, and its relevance is that it increases robustness to hyperparameters and initializations, and, combined with the Bayesian nature of SoftHebb (Section 2), it speeds up learning so that a mere single learning epoch suffices (Section 4).

Width scaling. With each new SoftHebb layer, the image resolution is halved in each dimension by a pooling operation, while the layer width, i.e. the number of convolutional neurons, is multiplied by a "width factor" hyperparameter. Our reported benchmarks used a width factor of 4.

The most crucial elements for deep representation learning are the soft competition and the corresponding Hebbian plasticity rule that underpin SoftHebb (Figures 3 and B.2), the similarly soft anti-Hebbian plasticity that we introduced (Figure B.2), the convolutional neurons, and the width scaling architecture that involves a depth-wise diminishing output resolution (Figure 4). The adaptive learning rate significantly speeds up the training (Figure B.3B), such that we only use a single unsupervised learning

(A) Hard WTA   (B) SoftHebb   (C) Backprop

Figure 2: Receptive fields of the first convolutional layer's neurons, learned from CIFAR-10 by different algorithms.

epoch for the deep network. The specific activation function and its tunable parametrization are less crucial but do improve performance (Appendix B). We arrived at this novel setup grounded on Moraitis et al. (2021) and through a literature- and intuition-guided search of possible additions.

4 RESULTS

Summary of experimental protocol. The first layer used 96 convolutional neurons to match related works (Figure 1), except our ImageNet experiments that used 48 units. The width of the subsequent layers was determined by the width factor (see previous section). Unsupervised Hebbian learning received only one presentation of the training set, i.e. epoch. Each layer was fully trained and frozen before the next one, a common approach known as greedy layer-wise training in such local learning schemes (Bengio et al., 2006; Tavanaei and Maida, 2016; Löwe et al., 2019). Batch normalization was used, with its standard initial parameters, which we did not train. Subsequently, a linear classifier head was trained with cross-entropy loss, using dropout regularization, with mini-batches of 64 examples, and trained for 50, 50, 100, and 200 supervised epochs for MNIST, CIFAR-10, STL-10, and ImageNet accordingly. We used an NVIDIA Tesla V100 32GB GPU. All details to the experimental methods are provided in Appendix A, and control experiments, including the hyperparameters' impact in Appendix B.

Fully connected baselines. The work of Moraitis et al. (2021) presented SoftHebb mainly through theoretical analysis. Experiments showed interesting generative and Bayesian properties of these networks, such as high learning speed and adversarial robustness. Reported accuracies focused on fully connected single-hidden-layer networks, showing that it was well applicable to MNIST and Fashion-MNIST datasets reaching accuracies of $(96.94 \pm 0.15)\%$ and $(75.14 \pm 0.17)\%$, respectively, using 2000 hidden neurons. Starting from that work, we found that when moving to more complex datasets such as CIFAR-10 or STL-10, SoftHebb performance was not competitive. Specifically, the same shallow fully-connected network's accuracies reached $(43.9 \pm 0.18)\%$ and $(36.9 \pm 0.19)\%$ accordingly. Compared to BP's $(55.7 \pm 0.13)\%$ and $(50.0 \pm 0.16)\%$, this suggested that single-hidden-layer networks were insufficient for extraction of meaningful features and separation of input classes. We then stacked two such fully connected Hebbian WTA layers. This network actually performed worse, reaching $(32.9 \pm 0.22)\%$ and $(31.5 \pm 0.20)\%$ on these tasks.

Convolutional baselines. Recent research has applied Hebbian plasticity to convolutional hard-WTA neural networks (CNN) (Miconi, 2021; Lagani et al., 2021; Amato et al., 2019). However, it has not achieved significant, if any, improvement through the addition of layers (Figure 1, green curves). In our control experiments, we found that these networks with the plasticity rules from the literature do not learn helpful features, as the fixed random weights performed better than the learned ones, also in agreement with results from Miconi (2021). Indeed, we find that the features learned by such hard-WTA networks are simple Gabor-like filters in the first layer (Figure 2A) and in deeper ones (see also Miconi (2021)).

(A) CIFAR-10   (B) CIFAR-100

(C) STL-10   (D) ImageNette

Figure 3: Depth-wise performance for various training setups and for untrained random weights, in 4 datasets. Number of *hidden* layers is indicated.

A new learning regime. One way to learn more complex features is by adding an anti-Hebbian term to the plasticity of fully connected (Krotov and Hopfield, 2019) or convolutional WTA networks (Grinberg et al., 2019). Notably, this method was previously tested only with hard-WTA networks and their associated plasticity rules and not with the recent SoftHebb model and plasticity. Here, we

introduced and tested our soft anti-Hebbian type of plasticity (see Section 3). We studied its effect first by proxy of the number of "R1" features (Moraitis et al., 2021), i.e. the weight vectors that lie on a unit sphere, according to their norm. Simple Gabor-like filters emerge without anti-Hebbian terms in the plasticity (Figure 2A) and are R1. Even with anti-Hebbian plasticity, in hard WTA networks, the learned features are R1 (Krotov and Hopfield, 2019). In the case of SoftHebb with our soft type of anti-Hebbian plasticity, we observed that less standard, i.e. non-R1, features emerge (Figure B.1 & 2B). By measuring the accuracy of the SoftHebb network while varying the temperature, we discovered a regime around $\tau = 1$ (Figure B.1) where R1 and non-R1 features co-exist, and accuracy is highest. This regime only emerges with SoftHebb. For example, on CIFAR-10 with a single convolutional layer and an added linear classifier, SoftHebb accuracy $(71.10 \pm 0.06)\%$ significantly outperformed hard WTA $(62.69 \pm 0.47)\%$ and random weights $(63.93 \pm 0.22)\%$, almost reaching the accuracy of BP $(72.42 \pm 0.24)\%$ on the same two-layer network trained end-to-end.

Convergence in a single epoch. Adaptive learning rate. By studying convergence through R1 features and by experimenting with learning rates, we conceived an adaptive learning rate that adapts to the norm of each neuron's weight vector (Section 3). We found that it also speeds up learning compared to more conventional learning schedules (Figure B.3B) with respect to the number of training iterations. The extent of the speed-up is such that we only needed to present the training dataset once, before evaluating the network's performance. All results we report on SoftHebb are in fact after just one epoch of unsupervised learning. The speed-up is in agreement with observations of Moraitis et al. (2021) that attributed the speed to SoftHebb's Bayesian nature. Moreover, we found that with our adaptive learning rate, convergence is robust to the initial conditions, to which such unsupervised learning schemes are usually highly sensitive (Figure B.3A & B.3B).

The architecture's impact. The multilayer architecture uses a pooling operation of stride 2, which halves each dimension of the resolution after each layer. We stop adding layers when the output resolution becomes at most 4×4. The layer where this occurs depends on the original input's resolution. Thus, the multilayer network has three hidden convolutional layers for MNIST or CIFAR-10, four layers for STL-10, and five layers for ImageNet at a resolution setting of 160×160 px. We used four times more neurons in each layer than in the previous layer. This architecture on its own, with random initial weights, shows inconsistent increases in classification accuracy, up to a variable depth (Figure 3). The performance increases caused by the addition of random layers seem surprising but are consistent with the literature where random weights often outperform biologically-plausible learning rules (Miconi, 2021; Frenkel et al., 2021). Indeed, by using the more common hard-WTA approach to train such a network, performance not only deteriorated compared to random weights but also failed to increase with added depth (Figure 3).

Classification accuracy (see Tables 1 & 2). We report that with SoftHebb and the techniques we have described, we achieve Deep Learning with up to 5 hidden layers. For example, layer-wise accuracy increases on CIFAR-10 are visible in Figure 1. Learning does occur, and the layer-wise accuracy improvement is not merely due to the architecture choice. That is testified, first, by the fact that the weights do change (Figure 2) and the receptive fields that emerge are meaningful (Figure 5). Second, and more concretely,

Figure 4: CIFAR-10 layer-wise performance of SoftHebb, for different width factors. SoftHebb enables depth-scaling when the width of deep layers scales sufficiently. Width factors (1x, 2x, or 4x) indicate layer-wise increase in the number of neurons.

for the end-point task of classification, accuracy improves significantly compared to the untrained random weights, and this is true in all datasets (Figure 3). SoftHebb achieves test accuracies of $(99.35 \pm 0.03)\%$, $(80.31 \pm 0.14)\%$, $(76.23 \pm 0.19)\%$, 27.3% and $(80.98 \pm 0.43)\%$ on MNIST, CIFAR-10, STL-10, the full ImageNet, and ImageNette. We also evaluated the same networks trained in a fully label-supervised manner with end-to-end BP on all datasets. Due to BP's resource demands, we could not compare with BP directly on ImageNet but we did apply BP to the ImageNette subset. The resulting accuracies are not too distant from SoftHebb's (Figure 3). The BP-trained network reaches $(99.45 \pm 0.02)\%$,

$(83.97 \pm 0.07)\%$, $(74.51 \pm 0.36)\%$ and $(85.30 \pm 0.45)\%$ on MNIST, CIFAR-10, STL-10, and ImageNette respectively. Notably, this performance is very competitive (see Tables 1 & 2).

Figure 5: Hierarchical representations learned by SoftHebb on STL-10. A, B: UMAP projection of the test set after passing through 1 or 4 SoftHebb layers. The learned 4-layer embedding is visibly more organized by input class and classes are better separated. C, D: Images and patches (red bounding boxes) that best activate 5 random neurons from each layer. The 1st layer's neurons (C) have become receptive to small patches with simple features (note the very small red bounding boxes), and are unspecific to the pictured object. The 4th layer's neurons (D) are receptive to patches with larger and complex features. Plastic synapses produce this hierarchy in the absence of non-local signals, label-related information, other top-down supervision, or self-supervision.

SoftHebb learns hierarchical representations. One central question concerning Soft-Hebb was its capacity to build a hierarchical representation of features, i.e. features that increase in semantic abstraction with increasing depth, and also become more useful for downstream tasks such as object classification. In the previous paragraphs, we have partially shown that this is achieved, already by proxy of the layer-wise increasing accuracy. By also using a method from Illing et al. (2021), we found further evidence that SoftHebb layers indeed become more abstract and selective to specific classes through increasing depth (Figure 5). In the UMAP projection (McInnes et al., 2018), after four layers, meaningful structure appears that separates the classes of inputs more than after one layer (top row of Figure 5). The hierarchy can also be visualized by looking at the patches that mostly activate a random neuron at a specific layer (bottom row of Figure 5). As expected, neurons at Layer 1 are selective to simple patterns such as oriented lines or homogeneous colours. On the contrary, neurons at layer four are selective to high-level features such as a plane in the sky or animals on the grass. This hierarchy is remarkable, given that no labels, or other supervision has been provided to the network.

SoftHebb as unsupervised Deep Learning. In STL-10, SoftHebb $(76.23 \pm 0.19)\%$ outperforms fully supervised BP $(74.51 \pm 0.36)\%$ (Figure 3C). The very few labelled examples in the training set do not suffice to learn good representations through only-supervised BP. By fine-tuning SoftHebb with end-to-end BP on the few labelled STL-10 examples, SoftHebb's accuracy further improves to $(78.5 \pm 0.35)\%$. This shows that the objective that is implicitly optimized by SoftHebb's learning is compatible with the explicit objective of cross-entropy, as was more formally theorized and predicted in Moraitis et al. (2021). Comparisons with other important algorithms for learning without labels show that SoftHebb in 4- or 5-hidden-layers-deep networks outperforms the partly biologically-plausible prior work Table 2). Of course, BP in more complex models significantly outperforms SoftHebb.

Table 2: STL-10 & ImageNet top-1 accuracy of un- or self-supervised (blue frame) & partly bio-plausible networks (green frame). Bold font indicates the best-performing biologically-plausible row, i.e. SoftHebb. SoftHebb's unsupervised learning only involved 1 epoch.

	Training algorithm	Model	STL-10	ImageNet	Reference	
un- or self- supervised	SimCLR	ResNet-18	86.3	30	Chen et al. 2020 (our repr.)	
	SimCLR	ResNet-50	89.7	76.5	Chen et al. 2020 (our repr.)	
	Greedy InfoMax	ResNet-50	81.9	n.a.	Löwe et al. 2019	biologically plausible
	None (Random chance)	None	10.0	0.1	Chance	
	None (Random weights)	SoftHebb	68.2	14.0	Ours	
	Hebbian	Hard WTA	54.8	n.a.	Ours	
	SoftHebb (1 epoch)	**SoftHebb**	**76.2**	**27.3**	**Ours**	
	CLAPP	VGG-6	73.6	n.a.	Illing et al. 2021	
	LPL	VGG-11	61.9	n.a.	Halvagal and Zenke 2022	
	K-means	K-means	74.1	n.a.	Dundar et al. 2015	
	Feedback Alignment	5-layer CNN	n.a.	6.9	Bartunov et al. 2018	
	Direct Feedback Alignment	AlexNet	n.a.	6.2	Crafton et al. 2019	
	Single Sparse DFA	AlexNet	n.a.	2.8	Crafton et al. 2019	

5 DISCUSSION

SoftHebb's accuracy and applicability in difficult tasks challenges several other biologically-constrained DL algorithms. Arguably it is also a highly biologically plausible and computationally efficient method, based on it being free of weight-transport, non-local plasticity, and time-locking of weight updates, it being fully unsupervised, It is also founded on physiological experimental observations in cortical circuits, such as Hebbian plasticity and WTA structure. Importantly, such Hebbian WTA networks enable non-von Neumann neuromorphic learning chips (Qiao et al., 2015; Kreiser et al., 2017; Sebastian et al., 2020; Indiveri, 2021; Sarwat et al., 2022a) that is an extremely efficient emerging computing technology, and SoftHebb makes high performance with such hardware more likely. The algorithm is applicable in tasks such as MNIST, CIFAR-10, STL-10 and even ImageNet where other algorithms with similar goals were either not applicable or have underperformed SoftHebb (Figure 1, Table 1, Table 2, & Bartunov et al. (2018)). This is despite the fact that most alternatives only address subsets of SoftHebb's goals of efficiency and plausibility (Section 2 & Table 1). Löwe et al. (2019) and Burstprop (Payeur et al., 2021) results on STL-10 and ImageNet are not included in Table 2, because the ResNet-50 of Löwe et al. (2019) used standard BP through modules of at least 15 layers, and because Payeur et al. (2021) did not report ImageNet top-1 accuracy. SoftHebb did outperform Burstprop and its successor BurstCCN (Greedy et al., 2022) on CIFAR-10 (Table 1). Beyond neural networks, K-means has also been applied to CIFAR-10 (Coates et al., 2011), however, without successful stacking of K-means "layers".

From the perspective of neuroscience, our results suggest that Deep Learning up to a few layers may be plausible in the brain not only with approximations of BP (Payeur et al., 2021; Illing et al., 2021; Greedy et al., 2022), but also with radically different approaches. Nevertheless, to maximize applicability, biological details such as spiking neurons were avoided in our simulations. In a ML context, our work has important **limitations** that should be noted. For example, we have tested SoftHebb only in computer vision tasks. In addition, it is unclear how to apply SoftHebb to generic deep network architectures, because thus far we have only used specifically width-scaled convolutional networks. Furthermore, our deepest SoftHebb network has only 6 layers in the case of ImageNet, as is common in most bio-plausible approaches (see Table 1). As a consequence, SoftHebb cannot compete with the true state of the art in ML (see e.g. ResNet-50 SimCLR result in Table 2). Such networks have been termed "very deep" (Simonyan and Zisserman, 2014) and "extremely deep" (He et al., 2016). This distinguishes from the more general term "Deep Learning" that was originally introduced for networks as shallow as ours (Hinton et al., 2006) has continued to be used so (see e.g. Frenkel et al. (2021) and layers in Table 1), and its hallmark is the emergent hierarchy that our experiments demonstrate. We propose that SoftHebb is worth practical exploitation of its present advantages, research around its limitations, and search for its possible physiological signatures in the brain.

REFERENCES

Aitchison, L. (2020). Bayesian filtering unifies adaptive and non-adaptive neural network optimization methods. *Advances in Neural Information Processing Systems*, 33:18173–18182.

Aitchison, L., Jegminat, J., Menendez, J. A., Pfister, J.-P., Pouget, A., and Latham, P. E. (2021). Synaptic plasticity as bayesian inference. *Nature neuroscience*, 24(4):565–571.

Akam, T. and Kullmann, D. M. (2014). Oscillatory multiplexing of population codes for selective communication in the mammalian brain. *Nature Reviews Neuroscience*, 15(2):111–122.

Amato, G., Carrara, F., Falchi, F., Gennaro, C., and Lagani, G. (2019). Hebbian learning meets deep convolutional neural networks. In *International Conference on Image Analysis and Processing*, pages 324–334. Springer.

Baldi, P., Sadowski, P., and Lu, Z. (2017). Learning in the machine: The symmetries of the deep learning channel. *Neural Networks*, 95:110–133.

Bartunov, S., Santoro, A., Richards, B., Marris, L., Hinton, G. E., and Lillicrap, T. (2018). Assessing the scalability of biologically-motivated deep learning algorithms and architectures. *Advances in neural information processing systems*, 31.

Bengio, Y., Lamblin, P., Popovici, D., and Larochelle, H. (2006). Greedy layer-wise training of deep networks. *Advances in neural information processing systems*, 19.

Binzegger, T., Douglas, R. J., and Martin, K. A. (2004). A quantitative map of the circuit of cat primary visual cortex. *Journal of Neuroscience*, 24(39):8441–8453.

Caron, M., Misra, I., Mairal, J., Goyal, P., Bojanowski, P., and Joulin, A. (2020). Unsupervised learning of visual features by contrasting cluster assignments. *Advances in Neural Information Processing Systems*, 33:9912–9924.

Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. (2020). A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR.

Coates, A., Ng, A., and Lee, H. (2011). An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 215–223. JMLR Workshop and Conference Proceedings.

Crafton, B., West, M., Basnet, P., Vogel, E., and Raychowdhury, A. (2019). Local learning in rram neural networks with sparse direct feedback alignment. In *2019 IEEE/ACM International Symposium on Low Power Electronics and Design (ISLPED)*, pages 1–6. IEEE.

Crick, F. (1989). The recent excitement about neural networks. *Nature*, 337(6203):129–132.

Czarnecki, W. M., Świrszcz, G., Jaderberg, M., Osindero, S., Vinyals, O., and Kavukcuoglu, K. (2017). Understanding synthetic gradients and decoupled neural interfaces. In *International Conference on Machine Learning*, pages 904–912. PMLR.

Diehl, P. U. and Cook, M. (2015). Unsupervised learning of digit recognition using spike-timing-dependent plasticity. *Frontiers in computational neuroscience*, 9:99.

Douglas, R. J. and Martin, K. A. (2004). Neuronal circuits of the neocortex. *Annu. Rev. Neurosci.*, 27:419–451.

Dundar, A., Jin, J., and Culurciello, E. (2015). Convolutional clustering for unsupervised learning. *arXiv preprint arXiv:1511.06241*.

Feldman, D. E. (2012). The spike-timing dependence of plasticity. *Neuron*, 75(4):556–571.

Frenkel, C., Lefebvre, M., and Bol, D. (2021). Learning without feedback: Fixed random learning signals allow for feedforward training of deep neural networks. *Frontiers in neuroscience*, page 20.

Garcia Rodriguez, H., Guo, Q., and Moraitis, T. (2022). Short-term plasticity neurons learning to learn and forget. In Chaudhuri, K., Jegelka, S., Song, L., Szepesvari, C., Niu, G., and Sabato, S., editors, *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 18704–18722. PMLR.

Greedy, W., Zhu, H. W., Pemberton, J., Mellor, J., and Costa, R. P. (2022). Single-phase deep learning in cortico-cortical networks. *arXiv preprint arXiv:2206.11769*.

Grill, J.-B., Strub, F., Altché, F., Tallec, C., Richemond, P., Buchatskaya, E., Doersch, C., Avila Pires, B., Guo, Z., Gheshlaghi Azar, M., et al. (2020). Bootstrap your own latent-a new approach to self-supervised learning. *Advances in neural information processing systems*, 33:21271–21284.

Grinberg, L., Hopfield, J., and Krotov, D. (2019). Local unsupervised learning for image analysis. *arXiv preprint arXiv:1908.08993*.

Grossberg, S. (1987). Competitive learning: From interactive activation to adaptive resonance. *Cognitive science*, 11(1):23–63.

Hadsell, R., Chopra, S., and LeCun, Y. (2006). Dimensionality reduction by learning an invariant mapping. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, volume 2, pages 1735–1742. IEEE.

Halvagal, M. S. and Zenke, F. (2022). The combination of hebbian and predictive plasticity learns invariant object representations in deep sensory networks. *bioRxiv*.

He, K., Fan, H., Wu, Y., Xie, S., and Girshick, R. (2020). Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9729–9738.

He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778.

Herzfeld, D. J., Kojima, Y., Soetedjo, R., and Shadmehr, R. (2015). Encoding of action by the purkinje cells of the cerebellum. *Nature*, 526(7573):439–442.

Hinton, G. E., Osindero, S., and Teh, Y.-W. (2006). A fast learning algorithm for deep belief nets. *Neural computation*, 18(7):1527–1554.

Illing, B., Ventura, J., Bellec, G., and Gerstner, W. (2021). Local plasticity rules can learn deep representations using self-supervised contrastive predictions. *Advances in Neural Information Processing Systems*, 34.

Indiveri, G. (2021). Introducing" neuromorphic computing and engineering". *Neuromorphic Computing and Engineering*.

Jaderberg, M., Czarnecki, W. M., Osindero, S., Vinyals, O., Graves, A., Silver, D., and Kavukcuoglu, K. (2017). Decoupled neural interfaces using synthetic gradients. In *International conference on machine learning*, pages 1627–1635. PMLR.

Kayser, C., Montemurro, M. A., Logothetis, N. K., and Panzeri, S. (2009). Spike-phase coding boosts and stabilizes information carried by spatial and temporal spike patterns. *Neuron*, 61(4):597–608.

Kolesnikov, A., Beyer, L., Zhai, X., Puigcerver, J., Yung, J., Gelly, S., and Houlsby, N. (2020). Big transfer (bit): General visual representation learning. In *European conference on computer vision*, pages 491–507. Springer.

Kreiser, R., Moraitis, T., Sandamirskaya, Y., and Indiveri, G. (2017). On-chip unsupervised learning in winner-take-all networks of spiking neurons. In *BioCAS*, pages 1–4.

Krotov, D. and Hopfield, J. J. (2016). Dense associative memory for pattern recognition. *Advances in neural information processing systems*, 29:1172–1180.

Krotov, D. and Hopfield, J. J. (2019). Unsupervised learning by competing hidden units. *Proceedings of the National Academy of Sciences*, 116(16):7723–7731.

Laborieux, A., Ernoult, M., Scellier, B., Bengio, Y., Grollier, J., and Querlioz, D. (2021). Scaling equilibrium propagation to deep convnets by drastically reducing its gradient estimator bias. *Frontiers in neuroscience*, 15:129.

Lagani, G., Falchi, F., Gennaro, C., and Amato, G. (2021). Hebbian semi-supervised learning in a sample efficiency setting. *Neural Networks*, 143:719–731.

Lee, H., Lee, K., Lee, K., Lee, H., and Shin, J. (2021). Improving transferability of representations via augmentation-aware self-supervision. *Advances in Neural Information Processing Systems*, 34.

Lillicrap, T. P., Cownden, D., Tweed, D. B., and Akerman, C. J. (2016). Random synaptic feedback weights support error backpropagation for deep learning. *Nature communications*, 7(1):1–10.

Linsker, R. (1992). Local synaptic learning rules suffice to maximize mutual information in a linear network. *Neural Computation*, 4(5):691–702.

Löwe, S., O'Connor, P., and Veeling, B. (2019). Putting an end to end-to-end: Gradient-isolated learning of representations. *Advances in neural information processing systems*, 32.

Madry, A., Makelov, A., Schmidt, L., Tsipras, D., and Vladu, A. (2017). Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*.

Markram, H., Gerstner, W., and Sjöström, P. J. (2011). A history of spike-timing-dependent plasticity. *Frontiers in synaptic neuroscience*, 3:4.

McInnes, L., Healy, J., and Melville, J. (2018). Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*.

Miconi, T. (2021). Multi-layer hebbian networks with modern deep learning frameworks. *arXiv preprint arXiv:2107.01729*.

Millidge, B., Tschantz, A., and Buckley, C. L. (2020). Predictive coding approximates backprop along arbitrary computation graphs. *arXiv preprint arXiv:2006.04182*.

Mitrovic, J., McWilliams, B., Walker, J., Buesing, L., and Blundell, C. (2020). Representation learning via invariant causal mechanisms. *arXiv preprint arXiv:2010.07922*.

Moraitis, T., Sebastian, A., and Eleftheriou, E. (2018). Spiking neural networks enable two-dimensional neurons and unsupervised multi-timescale learning. In *2018 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE.

Moraitis, T., Sebastian, A., and Eleftheriou, E. (2020). Short-term synaptic plasticity optimally models continuous environments.

Moraitis, T., Toichkin, D., Chua, Y., and Guo, Q. (2021). Softhebb: Bayesian inference in unsupervised hebbian soft winner-take-all networks. *arXiv preprint arXiv:2107.05747*.

Naud, R., Marcille, N., Clopath, C., and Gerstner, W. (2008). Firing patterns in the adaptive exponential integrate-and-fire model. *Biological cybernetics*, 99(4):335–347.

Nessler, B., Pfeiffer, M., Buesing, L., and Maass, W. (2013). Bayesian computation emerges in generic cortical microcircuits through spike-timing-dependent plasticity. *PLoS computational biology*, 9(4):e1003037.

Nessler, B., Pfeiffer, M., and Maass, W. (2009). Stdp enables spiking neurons to detect hidden causes of their inputs. *Advances in neural information processing systems*, 22:1357–1365.

Nøkland, A. (2016). Direct feedback alignment provides learning in deep neural networks. *Advances in neural information processing systems*, 29.

Nøkland, A. and Eidnes, L. H. (2019). Training neural networks with local error signals. In *International conference on machine learning*, pages 4839–4850. PMLR.

Oja, E. (1982). Simplified neuron model as a principal component analyzer. *Journal of mathematical biology*, 15(3):267–273.

Payeur, A., Guerguiev, J., Zenke, F., Richards, B. A., and Naud, R. (2021). Burst-dependent synaptic plasticity can coordinate learning in hierarchical circuits. *Nature neuroscience*, 24(7):1010–1019.

Pehlevan, C. and Chklovskii, D. (2015). A normative theory of adaptive dimensionality reduction in neural networks. In Cortes, C., Lawrence, N., Lee, D., Sugiyama, M., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc.

Pogodin, R., Mehta, Y., Lillicrap, T. P., and Latham, P. E. (2021). Towards biologically plausible convolutional networks. *arXiv preprint arXiv:2106.13031*.

Qiao, N., Mostafa, H., Corradi, F., Osswald, M., Stefanini, F., Sumislawska, D., and Indiveri, G. (2015). A reconfigurable on-line learning spiking neuromorphic processor comprising 256 neurons and 128k synapses. *Frontiers in neuroscience*, 9:141.

Sanger, T. D. (1989). Optimal unsupervised learning in a single-layer linear feedforward neural network. *Neural networks*, 2(6):459–473.

Sarwat, S. G., Kersting, B., Moraitis, T., Jonnalagadda, V. P., and Sebastian, A. (2022a). Phase-change memtransistive synapses for mixed-plasticity neural computations. *Nature Nanotechnology*, pages 1–7.

Sarwat, S. G., Moraitis, T., Wright, C. D., and Bhaskaran, H. (2022b). Chalcogenide optomemristors for multi-factor neuromorphic computation. *Nature communications*, 13(1):1–9.

Scellier, B. and Bengio, Y. (2017). Equilibrium propagation: Bridging the gap between energy-based models and backpropagation. *Frontiers in computational neuroscience*, 11:24.

Sebastian, A., Le Gallo, M., Khaddam-Aljameh, R., and Eleftheriou, E. (2020). Memory devices and applications for in-memory computing. *Nature nanotechnology*, 15(7):529–544.

Sejnowski, T. J. (2020). The unreasonable effectiveness of deep learning in artificial intelligence. *Proceedings of the National Academy of Sciences*, 117(48):30033–30038.

Simonyan, K. and Zisserman, A. (2014). Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*.

Sjöström, P. J., Turrigiano, G. G., and Nelson, S. B. (2001). Rate, timing, and cooperativity jointly determine cortical synaptic plasticity. *Neuron*, 32(6):1149–1164.

Stuhr, B. and Brauer, J. (2019). Csnns: Unsupervised, backpropagation-free convolutional neural networks for representation learning. In *2019 18th IEEE International Conference On Machine Learning And Applications (ICMLA)*, pages 1613–1620. IEEE.

Tavanaei, A. and Maida, A. S. (2016). Bio-inspired spiking convolutional neural network using layer-wise sparse coding and stdp learning. *arXiv preprint arXiv:1611.03000*.

Tomasev, N., Bica, I., McWilliams, B., Buesing, L., Pascanu, R., Blundell, C., and Mitrovic, J. (2022). Pushing the limits of self-supervised resnets: Can we outperform supervised learning without labels on imagenet? *arXiv preprint arXiv:2201.05119*.

Von der Malsburg, C. (1973). Self-organization of orientation sensitive cells in the striate cortex. *Kybernetik*, 14(2):85–100.

A DETAILS TO THE METHODS

A.1 WEIGHT INITIALIZATION

A.1.1 CHOOSING DISTRIBUTION FAMILY

We tested three probability distribution families for initializing the weights randomly; normal, positive, and negative (Equation (3)).

$$normal = \mathcal{N}(\mu = 0, \ \sigma^2) \quad positive = U(0, \ range) \quad negative = U(0, \ -range), \quad (3)$$

where U is a uniform distribution. We found that they perform similarly to each other in the case of long experiments, where the extensive training examples achieve to align the weights with the input. However, for shorter experiments, where speed is needed, we found that positive distribution was better for raw data (input values between 0-1) and normal distribution for data that was normalized into standard scores. The clustering property of SoftHebb learning (Moraitis et al., 2021), where learned features are centroids of clusters in the input space may explain this. In practice, we used normalized data for the reported results, and therefore we used normal distribution for the initial random weights.

A.1.2 CHOOSING DISTRIBUTION PARAMETERS

By varying the distribution parameters, we observed that the norm of the weight vector or radius is very instructive. We identify three regions of disparate learning (Figure B.3A); for R smaller than 1, there is no learning with random weight update; for R bigger than 1 and smaller than approximately 2.5, there is a partial leaning with only a percentage of neurons winning and converging while the others stay random; for R bigger than 2.5, all neurons learn. The learning change around 1 comes from the fact that the weight tends to converge to a radius of 1 (Moraitis et al., 2021).

Determining the initial radius from the weight distribution parameters: We can then derive the distribution parameters from the optimal initial radius using the distribution moment calculation.

$$R_i = E(\sqrt{\sum_{j=0}^{N} W_{ij}^2}) = E(\sqrt{\sum_{j=0}^{N} w^2}) = E(\sqrt{N \cdot w^2}) = E(\sqrt{N} \cdot |w|) = \sqrt{N} \cdot E(|w|) \quad (4)$$

Where i is the index of a neuron, j is the index of this neuron's synapses, N is number of synapses of that neuron, $E()$ is the expected value and so $E(|w|)$ is the first absolute moment of distribution. Thus, for the normal distribution $E(|w|) = \sigma \cdot \sqrt{2/\pi} \Rightarrow \sigma = R \cdot \sqrt{\frac{\pi}{2N}}$ and positive distribution $E(|w|) = E(w) = range/2 \Rightarrow range = R \cdot \sqrt{\frac{2}{N}}$.

A.2 LEARNING-RATE ADAPTATION

Learning rates that decay linearly with the number of training examples have been extensively used in Hebbian learning (Krotov and Hopfield, 2019; Grinberg et al., 2019; Miconi, 2021; Lagani et al., 2021; Amato et al., 2019). It is a simple scheduler, reaching convergence with a sufficient amount of training example. The linear decay ties the learning rate's value throughout learning to the proportion of the training examples that have been seen, and it does so uniformly across neurons. However, the weights may theoretically be able to converge before the full training set's presentation, and they may do so at different stages across neurons. To address this, we tied the learning rate lr_i to each neuron's i convergence. Convergence was assessed by the norm r_i of the neuron's weights. Based on previous work on similar learning rules (Oja, 1982; Krotov and Hopfield, 2019), on SoftHebb itself Moraitis et al. (2021), and on our own observations, the convergence of the neuronal weights is associated with a convergence to a norm of 1, in case of simple learned features at least.

Therefore, we used a learning rate that stabilizes to zero as neuron weight vectors converge to a sphere of radius 1, and is initially big when the weight vectors are large compared to 1:

$$lr_i = lr \cdot (r_i - 1)^{lrp}, \tag{5}$$

where lrp is a power hyperparameter. Note that this adaptivity has no explicit time-dependence, but as learning proceeds towards convergence, the lr does decay with time. To account for the case of complex features that do not converge to a norm of 1, a time-dependence can be added on top, e.g. as usual with a linearly decaying factor, multiplying the norm-dependent learning rate. In our experiments we only used the norm-dependence and simply stopped learning after the first training epoch, i.e. the first presentation of the full training set in most cases, or earlier. In practice, our adaptive rate reaches convergence faster (Figure B.3B) than the linear time-dependence, by maintaining a separate learning rate for each neuron and adapting it based on each neuron's own convergence status.

A.3 Layer architecture

Each convolutional layer includes a succession of batch normalization, a SoftHebb convolution, a pooling operation, and then an activation function. The SoftHebb convolution stride is fixed at 1. Padding is added to the input of the convolutional filters to guarantee that their output has the same size as the unpadded input. The pooling stride was fixed at 2, halving each dimension of the resolution after each layer. In all experiments, the first layer had a width of 96 convolutional kernels Miconi (2021); Lagani et al. (2021); Amato et al. (2019), except ImageNet experiments where we used 48 kernels. The number of kernels in the subsequent layers was determined according to our width-scaling method, with a width factor of 4 (see Appendix A.5).

A.3.1 Activation function

Softmax, i.e. the output of the soft winner-take-all was used as the postsynaptic variable y in SoftHebb's plasticity. However, for forward propagation to the subsequent layer, we considered three activation functions; Rectified polynomial unit (RePU), triangle, and softmax. RePU (Equation (6)) was proposed by Krotov and Hopfield (2016) as a generalization of rectified linear units (ReLU) and was also used in follow-up works (Krotov and Hopfield, 2019; Grinberg et al., 2019). Triangle activation was introduced by Coates et al. (2011) for k-means clustering and also appears useful for Hebbian networks in (Miconi, 2021). It subtracts the mean activation calculated over all channels at each position and then applies a ReLU. Here we generalize Triangle by combining it with RePU (instead of ReLU) through Equation (7):

$$RePU(u) = \begin{cases} u^p, & \text{for } u > 0 \\ 0, & \text{for } u \leqslant 0 \end{cases} \quad (6) \qquad Triangle(u_j) = RePU(u_j - \overline{u}) \quad (7)$$

A.4 Hyperparameter optimization

We systematically investigated the best set of hyperparameters at each hidden layer, based on the validation accuracy of a linear classifier trained directly on top of that hidden layer. All grid searches were performed on three different random seeds, varying the batch sampling and the validation set (20% of the training dataset). The classifier is a simple linear classifier with a dropout of 0.5 and no other regularisation term. For all searches and final results, we used 96 kernels in the first layer. Subsequent layers scaled with a $f_w = 4$ (see Appendix A.5). However, based on our observations, only the optimal temperature depends on the f_w.

For each added layer, grid search was performed in three stages: For the first two stages we used square convolutional kernels with a size of 5, a max-pooling with a square kernel of size 2, and a Triangle with a power of 1 as forward activation function.

1. In this stage we performed a grid search over the remaining hyperparameters (nb_{epochs}, $batch\_ize$, η and lrp of the learning rate scheduler, and temperature τ of the SoftHebb softmax). We varied the $nb\_epochs \in \{1, 10, 50, 100, 1000\}$,

layer	operation	hyperparmeters	searched range	found optimum
1	conv	η
lrp
kernel_size
$1/\tau$	[0.001-0.12],
[0.25, 0.5, 0.75]
[3, 5, 7, 9]
[0.1-100]	0.08
0.5
5
1
	pooling	type
kernel_size	[AvgPooling, MaxPooling],
[2, 3, 4]	MaxPooling
4
	activation	function
power	[Softmax, RePU, Triangle]
[0.1-10]	Triangle
0.7
2	conv	η
lrp
kernel_size
$1/\tau$	[0.001-0.12],
[0.25, 0.5, 0.75]
[3, 5, 7, 9]
[0.1-100]	0.005
0.5
3
0.65
	pooling	type
kernel_size	[AvgPooling, MaxPooling],
[2,3,4]	MaxPooling
4
	activation	function
power	[Softmax, RePU, Triangle]
[0.1-10]	Triangle
1.4
3	conv	η
lrp
kernel_size
$1/\tau$	[0.001-0.12],
[0.25, 0.5, 0.75]
[3, 5, 7, 9]
[0.1-100]	0.01
0.5
3
0.25
	pooling	type
kernel_size	[AvgPooling, MaxPooling],
[2,3,4]	AvgPooling
2
	activation	function
power	[Softmax, RePU, Triangle]
[0.1-10]	Triangle
1

Table 3: Network architecture and hyper-parameters search, and best results on CIFAR-10. More details are provided in section A.4.

$batch\_size \in \{10, 100, 1000\}$, $\eta \in \{0.001, 0.004, 0.008, 0.01, 0.04, 0.08, 0.12\}$, $lrp \in \{0.25, 0.5, 0.75\}$ and the $1/\tau \in \{0.25, 0.5, 0.75, 1, 2, 5, 10\}$.

2. A finer grid search over $1/\tau \in \{0.15, 0.25, 0.35, 0.5, 0.6, 0.75, 0.85, 1, 1.2, 1.5, 2\}$ and $conv\_kernel\_size \in \{3, 5, 7, 9\}$ using the best result from the previous search.

3. A final grid search over the pooling: $pool\_type \in \{AvgPooling, MaxPooling\}$, $pool\_kernel\_size \in \{2, 3, 4\}$, and the activation function: $function \in \{RePU, Triangle, Softmax\}$ with for $power \in \{0.1, 0.35, 0.7, 1, 1.4, 2, 5, 10\}$ (for RePU or Triangle) and $\tau \in \{0.1, 0.5, 1, 2, 5, 10, 50, 100\}$ (for softmax) using the best result from the two previous searches.

A.5 MULTILAYER ARCHITECTURE

The pooling of stride 2 halves each dimension of the resolution after each layer. We stop adding layers when the output resolution becomes at most 4×4. The layer where this occurs depends on the original input's resolution. Thus, the multilayer network has three convolutional layers for MNIST or CIFAR-10, four layers for STL-10, and five layers for ImageNet at a resolution setting of 160×160 px (Table 4).

A width factor f_w characterizes the multilayer network. f_w links the width of each layer to that of the previous layer, thus determining the depth-dependent architecture. Specifically, the number of filters $\#F_l$ in the hidden layer l is f_w times the number of filters at layer $l - 1$: $\#F_l = f_w \cdot \#F_{l-1}$. The first hidden layer has 96 filters in order to compare with Miconi (2021); Lagani et al. (2021); Amato et al. (2019). We then explored, using CIFAR-10, the impact of f_w on performance. We tried three different values for $f_w \in \{1, 2, 4\}$. A value of 1 keeps the same number of filters in all layers, while a value of 4 keeps the number of features provided to the classifier head equal to the number of features at the input layer (due to the pooling stride of 2 in each layer). A f_w bigger than four would substantially increase

# layer	MNIST/CIFAR	STL10	ImageNet
1	Batchnorm
5×5 conv96
Triangle
4×4 MaxPool	Batchnorm
5×5 conv96
Triangle
4×4 MaxPool	Batchnorm
5×5 conv48
Triangle
4×4 MaxPool
2	Batchnorm
3×3 conv384
Triangle
4×4 MaxPool	Batchnorm
3×3 conv384
Triangle
4×4 MaxPool	Batchnorm
3×3 conv192
Triangle
4×4 MaxPool
3	Batchnorm
3×3 conv1536
Triangle
2×2 AvgPool	Batchnorm
3×3 conv1536
Triangle
4x4 MaxPool	Batchnorm
3×3 conv768
Triangle
4×4 MaxPool
4		Batchnorm
3×3 conv6144
Triangle
2×2 AvgPool	Batchnorm
3×3 conv3072
Triangle
4×4 MaxPool
5			Batchnorm
5×5 conv12288
Triangle
2×2 AvgPool

Table 4: Network architecture (all pooling layers use a stride of 2), also the number of channels is defined: (conv96 -¿ 96 channels). More details can be found in Appendix A.5.

the size of the network, and is impractical for deeper networks. We found that to increase performance with depth, the network needs to also grow in width (Figure 4).

A.6   TRAINING AND EVALUATION PROTOCOLS

Each experiment was performed 4 times, with random initializations, on all datasets except the full ImageNet where only one random seed was tried.

A.6.1   SOFTHEBB TRAINING

The optimal number of SoftHebb weight update iterations is around 5000 based on CIFAR-10 experiments. Thus, for CIFAR-10 and MNIST (50k training examples), unsupervised training was performed in one epoch with a mini-batch of 10 and 20 for STL-10 unlabelled training set (100k training example). Because of the large number of training examples, we randomly select 10% of the ImageNet dataset with a mini-batch of 20. The accuracies we report for SoftHebb are for layers that are trained successively, meaning each SoftHebb layer was trained, and then frozen, before the subsequent layer was trained. However, the results are very similar for simultaneous training of all layers, where each training example updates all layers, as it passes forward through the deep network.

A.6.2   SUPERVISED TRAINING

The linear classifier on top uses a mini-batch of 64 and trains on 50 epochs for MNIST and CIFAR-10, 100 epochs for STL-10, and 200 epochs for ImageNet. For all datasets, the learning-rate has an initial value of 0.001 and is halved every [20%, 35%, 50%, 60%, 70%, 80%, 90%] of the total epochs. Data augmentation (random cropping and flipping) was applied for STL-10 and ImageNet.

A.6.3 Backpropagation-trained networks

Results comparing SoftHebb and Backpropagation are found using the same network architecture. The only difference is the activation function; triangle or softmax activation would be detrimental to BP. The activation function we used for BP-trained networks is ReLU. The learning rate followed the same schedule as described Appendix A.6.2.

A.6.4 Fine-tuning

In the fine-tuning experiment on STL-10, all Hebbian CNN layers learned using SoftHebb and the large unlabelled training dataset of STL-10; then, an output layer was added and the entire network was trained end-to-end using BP on the full small labelled training subset.

B   ADDITIONAL RESULTS AND ANALYSES

B.1   SOFTHEBB LEADS TO A NEW LEARNING REGIME. IMPACT OF TEMPERATURE ON ACCURACY.

Figure B.1: SoftHebb's temperature-dependent regimes in a single-layer CNN trained on CIFAR-10. With anti-Hebbian plasticity and SoftHebb (but not hard WTA), a regime exists where R1 and non-R1 features coexist and accuracy is maximal.

Figure B.2: Same as Figure B.1, but in the 3-hidden-layer network, such that all layers use the same temperature. R1 features are reported as a percentage over all features of all layers.

B.2 Weight-norm-dependent adaptive learning rate increases learning robustness and speed.

(A) Robustness to weight initialization of our norm-dependent adaptive learning rate scheme, compared to a linear scheduler. The adaptive scheme achieves high accuracies for a broad range of weight initializations. Here the initialization is parametrized by the radius of the sphere where the weight vectors lie initially.

(B) Convergence speed of our norm-dependent adaptive learning rate scheme, compared to a linear scheduler. With the adaptive scheme, neuronal weight vectors converge to a sphere of radius 1 (i.e. become R1 features) faster.

Figure B.3: Effects of our adaptive learning rate.

See also main text's Section 3, Weight-norm-dependent adaptive learning rate, and the related paragraph in Section 4.

B.3 SoftHebb learns hierarchical representations.

As a control, we perform again the experiment that we presented in Figure 5, this time in comparison to a network with the initial, untrained, random weights. The results are shown in Figure B.4 and Figure B.5.

(A) Trained weights with SofHebb.   (B) Random weights.

Figure B.4: UMAP projection (similar to main text's Figure 5, top row) of the test set after passing through 4 SoftHebb layers. Here, (A) from a trained and (B) from a randomly initialized, untrained network.

(A) Trained weights with SofHebb.   (B) Random weights.

Figure B.5: Images and patches that best activate 5 random neurons from SoftHebb Layers 1 and 4 (similar to main text's Figure 5, bottom row). Here, (A) from a trained and (B) from a randomly initialized, untrained network.

B.4 ABLATION STUDIES

Activation function The choice of activation function for forward propagation through SoftHebb layers is important. To study this, we compared SoftHebb's performance on CIFAR-10 for various activation functions. In each result, all neurons across all layers used the same activation function. The parameters that were tried were:

- Power of RePU: 0.7*, 1.0, 1.4.
- Temperature of softmax: 4.0*, 1/0.65, 1.0.

These three values were tried because they were good for individual layers in previous tuning. Asterisk indicates the best parameter value according to validation accuracy. Using the best values produced the accuracy results reported below, whereas the remaining hyperparameters were not tuned for these results.

- ReLU: $(70.68 \pm 1.07)\%$
- tanh: $(56.13 \pm 0.34)\%$
- RePU: $(79.08 \pm 0.13)\%$
- softmax: $(54.05 \pm 0.55)\%$

The impact is meaningful, however it should be noted that tuning of the remaining hyperparameters would decrease the performance difference between activation functions.

Width (number of neurons) The width of the layers is rather impactful, as indicated by varying the width factor of deep layers while keeping the first layer's width constant (Figure 4). To further study that impact, we varied the first layer's width and kept the width factor fixed to 4 (which scales all layers). The results are presented in Figure B.6.

Figure B.6: Performance on CIFAR-10 for varying width of the layers. First-layer width is indicated, while subsequent layers are scaled by the width factor 4 (see Appendix A.5).

For this control experiment, we did not re-tune the hyperparameters to each width, but rather only to the 96-neuron case. That is in contrast to Figure 4, where hyperparameters were tuned to each width factor.