Ultra-marginal Feature Importance

Abstract

Scientists frequently prioritize learning from data rather than training the best possible model; however, research in machine learning often prioritizes the latter. Marginal feature importance methods, such as marginal contribution feature importance (MCI), attempt to break this trend by providing a useful framework for quantifying the relationships in data in an interpretable fashion. In this work, we aim to improve upon the theoretical properties, performance, and runtime of MCI by introducing ultra-marginal feature importance (UMFI), which uses pre-processing methods from the AI fairness literature to remove dependencies in the feature set prior to measuring predictive power. We show on real and simulated data that UMFI performs better than MCI, especially in the presence of correlated interactions and unrelated features, while partially learning the structure of the causal graph and reducing the exponential runtime of MCI to super-linear.

1 Introduction

Scientists often seek to determine the true relationships between a set of characteristics and some outcome of interest. These relationships are ideally determined by performing carefully controlled experiments so that causality can be established. However, experiments can be difficult and costly to pursue, unethical to perform, or impossible to control [54, 46], leaving only observational data available. The relationships that are hidden within vast quantities of observational data are often difficult to determine, so statistical tools, such as feature importance, have been explored.

There is no consensus on how to define feature importance, so choosing an appropriate method strongly depends on the questions that the user seeks to answer [50, 23, 12]. The most widely referenced distinction between feature importance methods is the conditional versus marginal divide, which defines the two extremes of feature importance methods [17]. The distinction between these two types of methods is only evident in the presence of dependent features. Indeed, if all explanatory features in a dataset are independent, conditional and marginal importances are exactly the same [17, 38]. Conditional methods are typically used for feature selection, dimensionality reduction, and improving prediction performance. On the other hand, marginal methods are specifically developed to explain and interpret data [23], seeking to avoid the tendency of conditional methods to give correlated features too little importance [13]. For example, if a scientist wants to build a database of genes associated with some disease, then a marginal approach could be preferred [17, 11, 13]. Alternatively, if an engineer wants to determine the smallest set of features that can obtain good predictions, a conditional importance metric would be more suitable [23, 11].

Recently, feature importance methods such as Shapely-values [42, 14, 34], SAGE [15], accumulated local effects (ALE) [3], permutation importance (PI) [8], and conditional permutation importance (CPI) [17] have been used in high-impact journal papers by scientists who want to explain the mechanisms within data [2, 5, 44, 30, 40, 20, 27]. However, these methods may not adequately explain data in certain circumstances [13, 12]. ALE can only easily show first order effects [37], and although CPI improves upon some limitations of PI, CPI has the property that two perfectly correlated

features with significant predictive power would both be deemed unimportant [15]. Further, only one model is trained in ALE, CPI, and PI. Thus, correlated features, which can alter the model assembly process, could be given artificially low importance if the goal is to explain the data [25]. Instead of exploring a single model, the developers of SAGE, SPVIM, and marginal contribution feature importance (MCI) evaluate the difference in accuracy between a model trained with the feature of interest and a model trained without it, across all feature subsets [12, 15, 52], though these methods are prevented from being accepted by a wider scientific audience because of their high computational cost. In particular, we note that MCI is the current state-of-the-art method for explaining data as it was shown in extensive experiments to have better quality and robustness when compared to Shapely-values, SAGE, ablation, and bivariate methods [12].

Though MCI can be seen as the current state-of-the-art method for explaining the data, it has three key shortcomings. First, the exact computation of MCI requires an exponential number of model trainings, which makes MCI ineffective for interpreting large datasets (e.g., gene expression studies). Second, although it can handle complex feature interactions and data with correlated features, MCI underestimates the importance of correlated features that form interaction effects. Third, MCI can give non-zero importance to features that are completely unrelated to the response variable. We hypothesized that constructing independent and information-preserving representations of the data could resolve these issues. With this in mind, we introduce ultra-marginal feature importance (UMFI), a new variable importance method that can better explain the data while drastically reducing runtime.

The rest of this paper is organized as follows. Axioms for explaining the data are proposed in Section 2. The framework for UMFI is then formally presented in Section 3 along with its theoretical properties and its simple algorithm. In Section 4, we conduct experiments on simulated and real data to assess the quality, robustness, and time complexity of UMFI compared to MCI. Finally, an overview of the work, its limitations, and ideas for future work are discussed in Section 5.

Related work

This paper is greatly inspired by the development of marginal contribution feature importance (MCI) by Catav et al. [12]. Although other methods, such as SAGE [15], have been retooled to better explain data [13], up until this point, MCI had been the only feature importance method developed specifically to explain data. Let $F = \{x_1, ..., x_p\}$ be the set of features used to predict the response variable, Y. Recall that the universal predictive power of a set of features $S \subseteq F$ is given by

$$\nu(S) = \min_{f \in G(\emptyset)} \mathbb{E}[l(f(\emptyset), Y)] - \min_{f \in G(S)} \mathbb{E}[l(f(S), Y)], \tag{1}$$

where l is a specified loss function and $G(S)$ is the set of all predictive models restricted to using features in $S \subseteq F$. ν is closely related to mutual information, with equality under ideal conditions [15], and in practice, ν is often approximated by machine learning evaluation functions. Using this, Catav et al. [12] defined the marginal contribution feature importance (MCI) of a feature $x_i \in F$ by

$$I_\nu(x_i) = \max_{S \subseteq F} \nu(S \cup \{x_i\}) - \nu(S). \tag{2}$$

To achieve our goal of improving upon the shortcomings of MCI, we evaluate the importance of a feature of interest x_i by preprocessing the data to remove dependencies on x_i. Finding independent representations of predictors for creating improved feature importance methods is a novel objective, though similar ideas have been suggested as future work in König et al. [31] and Chen et al. [13]. The weaker concept of finding orthogonal representations of data has been discussed previously [19], though the discussion has been limited to relative importances measures for multiple linear regression, mostly in the domain of psychology [6, 55]. While orthogonalizing predictors can be done easily with simple techniques, methods which can not only remove correlations between features, but also remove more general dependencies, have seen great progress within the domains of AI fairness and privacy. Some examples of these techniques include regression [7], optimal transport [29], neural networks [10, 43], convex optimization [10], and principal inertial components [47]. Linear regression and optimal transport were implemented for UMFI in this paper.

2 Axioms for explaining data

Any attempt to build a method that explains the data should begin by rigorously defining what explaining the data truly means. Different definitions and goals have been formulated by Chen et al.

[13] and Catav et al. [12]. Inspired by these definitions, we provide three intuitive, justified, and rigorous axioms for true-to-the-data feature importance methods. Given a feature set F, a response Y, and a feature of interest $x_i \in F$, the feature importance of x_i is defined as $Imp^{F,Y}(x_i) \in \mathbb{R}_{\geq 0}$. We define the following three axioms as vital for any method that claims to explain the data:

1. **Elimination axiom:** Eliminating a feature x_j from the feature set F can only decrease the importance of the feature of interest:

$$\forall x_i \in F \setminus \{x_j\}, Imp^{F \setminus \{x_j\}, Y}(x_i) \leq Imp^{F,Y}(x_i).$$

2. **Duplication invariance and symmetry axiom:** Adding a duplicate copy of a feature $\hat{x} = x_j$ already in the feature set F will not change the importance of the other features in F, and the duplicated feature will have importance equal to the original feature:

$$\forall x_i \in F, \ Imp^{F,Y}(x_i) = Imp^{F \cup \{\hat{x}\}, Y}(x_i) \text{ and } Imp^{F \cup \{\hat{x}\}, Y}(\hat{x}) = Imp^{F \cup \{\hat{x}\}, Y}(x_j).$$

3. **Blood relation axiom:** If data is generated from a causal graph, feature x_i will be given non-zero and positive importance if and only if it is blood related to the response Y in the causal graph. Two vertices in a causal graph are said to be blood related if there is a directed path between them or if there is a backdoor path between them via a common ancestor.

$$Imp^{F,Y}(x_i) > 0 \iff x_i \in BR(Y).$$

The elimination axiom comes directly from Catav et al. [12]. This axiom is justified by the fact that once a feature is observed to be significantly related to the response, the relationship strength between the feature and response should not drop, regardless of the additional features added. In fact, often times the importance should increase since adding features could reveal further synergistic information about the response Y.

The duplication invariance and symmetry axiom helps separate feature importance methods that are for data explanation from methods intended for model exploration or optimization [12]. A model may use the two identical features equally often, therefore the total importance of both features may be spread equally between them (random forests or elastic net), or only one of the features may be given importance (lasso) [13]. However, from the data's perspective, both features should be equally related to the response and the original importance found before duplication should still be true. Further, after duplication, no additional interaction capability is available [22], so feature importance across all features should remain the same.

The blood relation axiom asserts that feature importance scores intended for data explanation should extract reliable knowledge about the underlying causal graph and data generating process. In fact, a statistical association between a feature and the response , which is a quality of interest for many applications (e.g., genome-wide association studies), exists precisely when the two features are blood related, or equivalently, when there is an open path between them [51]. Thus, a feature importance metric satisfying this axiom would give non-zero importance to a feature if and only if there is a statistical association between that feature and the response. Additionally, if the goal is to construct a causal graph to represent the relationships in the data, then a feature importance metric satisfying this axiom can partition the feature set into features that are blood related to the response and features that are not blood related to the response. Although it does not enable us to immediately recover the full causal graph, this partitioning may be a helpful supplemental tool for other causal discovery methods.

3 Ultra-marginal feature importance

Let $F = \{x_1, ..., x_p\}$ be a set of p features of arbitrary type used to predict the response Y. We note that features may be viewed as random variables, or realizations of random variables according to their joint distribution in the form of a dataset.

In order to define ultra-marginal feature importance, we require that the evaluation function ν, which measures the predictive power of a group of features [12], and which approximates Equation (1), is also defined for transformations of the feature set following the removal of dependencies. We therefore define the space of information subsets of a feature set F as $\mathcal{I}(F) = \{g(F) : g \text{ is any function defined on } F\}$. We call these information subsets of F because $I(Y; g(F)) \leq I(Y; F)$ holds for any function g by Theorem A.3. We note that equality holds if and only if g is injective.

Definition 1. *Given an evaluation function $\nu : \mathcal{I}(F) \to \mathbb{R}_{\geq 0}$ and a feature set F, we define the ultra-marginal feature importance (UMFI) of a feature $x_i \in \bar{F}$ as*

$$U_\nu^{F,Y}(x_i) = \nu(S_{x_i}^F \cup \{x_i\}) - \nu(S_{x_i}^F). \tag{3}$$

Definition 2. *We define the random vector $S_{x_i}^F$ as the preprocessed feature set after dependencies on the feature of interest x_i have been removed from F. An optimally preprocessed feature set is denoted by $\hat{S}_{x_i}^F$, and we say that a preprocessing $S_{x_i}^F$ is optimal if it obeys the following properties:*

    1. $S_{x_i}^F = g(F)$ for some function g

    2. $S_{x_i}^F \perp\!\!\!\perp x_i$

    3. $I(Y; S_{x_i}^F, x_i) = I(Y; F)$

The first property ensures that $S_{x_i}^F \in \mathcal{I}(F)$, and hence, no information found outside of F is gained during dependency removal. The second property upholds that $S_{x_i}^F$ is completely independent of x_i, and the last property affirms the optimality of $S_{x_i}^F$ in the sense that there is no unnecessary information loss incurred during preprocessing. Given that it exists, an optimal preprocessing $\hat{S}_{x_i}^F$ is not unique, since scaling $g(F)$ by a constant does not affect the last two properties. In practice, the last two properties can be difficult to guarantee, but we see later in Section 4 that UMFI can provide accurate feature importance scores even when the preprocessings are not optimal.

UMFI obeys the three axioms given in Section 2 under certain assumptions as proven in Appendix C. Mainly, we assume that $\nu(\cdot) \approx I(Y; \cdot)$. Under ideal conditions, this relationship holds when ν satisfies Equation (1) [15], but in practice, the accuracy of the approximation depends on the quality of the method, the specified loss function, and the response variable's distribution [16]. See Covert et al. [16] and Appendix A.3 for a more thorough overview.

Since UMFI is model-agnostic, we provide a general algorithm for computing the ultra-marginal feature importance of a feature $x_i \in F$ which can be applied using any pair of preprocessing and modeling techniques. We emphasize that ν is not restricted to the domain of machine learning models or even models in general. For example, one could also apply measures of dependence such as the Hilbert–Schmidt independence criterion [21] or non-ML estimates of mutual information [32].

Algorithm 1: Algorithm for computing UMFI

1: Let Y be the response variable of the set of predictors F. Choose a feature $x_i \in F$.
2: Estimate $S_{x_i}^F$ by removing dependencies on x_i from F with minimal information loss.
3: Specify a method f and a corresponding evaluation function ν_f.
4: Estimate the predictive power, $\nu_f(S_{x_i}^F)$, that $S_{x_i}^F$ has about Y.
5: Estimate the predictive power, $\nu_f(S_{x_i}^F \cup \{x_i\})$, that $S_{x_i}^F \cup \{x_i\}$ has about Y.
6: **return** $U_{\nu_f}^{F,Y}(x_i) = \nu_f(S_{x_i}^F \cup \{x_i\}) - \nu_f(S_{x_i}^F)$

---

4 Experiments

We perform experiments to compare UMFI and MCI with respect to quality, robustness, and time complexity. To implement UMFI, we consider optimal transport [29] (UMFI_OT) and linear regression [7] (UMFI_LR) as methods to remove dependencies from the data. A detailed overview of these implementations is shown in Appendix E and experiments comparing these methods appear in Appendix F. For all experiments, we use random forests' out-of-bag accuracy (R^2 OOB-accuracy for regression tasks and OOB classification accuracy for classification tasks) as the evaluation metric ν_f [8]. We use the *ranger* R package to implement random forests with default hyperparameters and 100 for the number of trees [53]. All experiments were run in Microsoft R Open Version 4.0.2 [36]. Appendix G contains additional experiments comparing UMFI and MCI with other feature importance metrics including ablation, permutation importance, and conditional permutation importance. In the same section, we rerun the experiments comparing MCI and UMFI using extremely randomized trees instead of random forests and do an additional comparison on a real dataset from hydrology [1]. Code for all experiments can be found in the Supplement.

4.1 Experiments on simulated data

We run UMFI on simulated data to verify that it performs well compared to MCI. The data in all simulation studies contains one response variable Y, four explanatory features x_1, x_2, x_3, x_4, and 1000 randomly generated observations. Each study is repeated 100 times to test stability.

4.1.1 Nonlinear interactions

Interaction effects are common in many scientific disciplines where assessing feature importance is prevalent, including hydrology [28, 2, 33], genomics [12, 49, 39], and glaciology [18, 4, 9, 41]. So, as was done in Catav et al. [12], we assess the ability of MCI and UMFI to detect nonlinear interaction effects in the data [35]. We consider:

$$x_1, x_2, x_3, x_4 \sim \mathcal{N}(0, 1)$$
$$Y = x_1 + x_2 + sign(x_1 * x_2) + x_3 + x_4.$$

Feature importance metrics should ideally conclude that x_1 and x_2 have higher importance compared to x_3 and x_4 because of the extra interaction term, $sign(x_1 * x_2)$. Figure 1a shows consistently good performance across all methods. Each method gave high relative importance scores to x_1 and x_2, while x_3 and x_4 received less, but still substantial importance. All methods show similar variability.

4.1.2 Correlated interactions

Interacting features are often correlated [26, 28]. So, this simulation study aims to repeat the nonlinear interactions study, except now x_1 and x_2 are highly correlated with eachother. In the same way, x_3 and x_4 are highly correlated with eachother. Let $A, B, C, D, E, G \sim \mathcal{N}(0, 1)$. We consider:

$$x_1 = A + B, \ x_2 = B + C, \ x_3 = D + E, \ x_4 = E + G$$
$$Y = x_1 + x_2 + sign(x_1 * x_2) + x_3 + x_4.$$

Just as with the interaction experiment with independent features, we would expect x_1 and x_2 to be more important than x_3 and x_4 because of the extra interaction term, $sign(x_1 * x_2)$. The results in Figure 1b clearly show that UMFI provides better estimations of feature importance compared to MCI when correlated interactions are present. MCI estimates that all features have approximately the same feature importance scores, while both UMFI methods show significantly greater importance for x_1 and x_2 compared to x_3 and x_4. MCI fails in this experiment because it penalizes feature subsets that share information with the feature of interest x_i when evaluating the importance of x_i via Equation (2). For example, if we are assessing the MCI score for x_1, since x_2 is strongly correlated with x_1, then the predictive power offered by x_1 on top of a subset S would be diminished by the presence of $x_2 \in S$. Therefore, x_2 is not utilized in the MCI score for x_1, which prevents the detection of the interaction term $sign(x_1 * x_2)$. UMFI is able to detect this interaction because it can extract the information from x_2 that interacts with x_1 while keeping this extracted feature independent of x_1. Although not yet tested, we suspect that similar results would be demonstrated in the presence of dependent, but uncorrelated interactions.

4.1.3 Correlation

Marginal feature importance methods such as MCI and UMFI should not change the measured importance of features in the presence of highly correlated or duplicated variables according to the duplication invariance and symmetry axiom. To test this, we implement a simulation study similar to the ones found in Catav et al. [12]. Let $\epsilon \sim \mathcal{N}(0, 0.01)$. We consider:

$$x_1, x_2, x_4 \sim \mathcal{N}(0, 1), \ x_3 = x_1 + \epsilon$$
$$Y = x_1 + x_2.$$

The addition of x_3, which is approximately a duplicate of x_1, should not alter the importance of x_1, and x_1 should remain equally as important as x_2, since they have the same influence on the response Y. The results shown in Figure 1c show that both MCI and UMFI work reasonably well. As with the previous simulation experiment, the variability is consistent across methods. As was desired, UMFI with linear regression shows equal relative importance scores for x_1 and x_2. The importance given to x_2 was slightly greater than x_1 according to MCI and UMFI with optimal transport. Interestingly, MCI assigns some importance to x_4, which was independent of the response, while both UMFI methods assign importance scores close to zero. Because of this, we conclude that UMFI with linear regression performs the best in this simulated scenario.

Figure 1: Results for the experiments on simulated data from Subsection 4.1. Feature importance scores are shown as a percentage of the total for each of x_1 to x_4 from 100 replications. Results are shown for marginal contribution feature importance (MCI), ultra-marginal feature importance with linear regression (UMFI_LR), and ultra-marginal feature importance with pairwise optimal transport (UMFI_OT).

4.1.4 Blood relation

To ensure that UMFI is true to the data and could be used to learn part of the structure of the causal graph in theory as well as in practice, we implement the blood relation simulation experiment. In this study, data is generated from the causal graph in Figure 7 from the Supplement, which was inspired by the collider causal graph found in Harel et al. [24]. The feature S is unobserved, thus only x_3 and x_4 are blood related to the response Y. Because of this, according to the blood relation axiom, x_3 and x_4 should be given high and positive importance while x_1 and x_2 should receive zero importance. In Section 3, we proved that in ideal scenarios, UMFI will only give non-zero importance to blood related features. We hypothesize that we can extend this to real-world scenarios where non-Gaussian features and interaction information appear. To test this, we consider:

$$x_1, S \sim \mathcal{N}(0, 1),\ \delta \sim \mathcal{U}(-1, 1),\ \epsilon \sim \mathcal{U}(-0.5, 0.5),\ \gamma \sim Exp(1)$$
$$x_2 = 3 * x_1 + \delta,\ x_3 = x_2 + S$$
$$Y = S + \epsilon$$
$$x_4 = Y + \gamma.$$

The results shown in Figure 1d indicate that MCI fails to distinguish the blood related features, since most of the importance is given to $x_1, x_2 \notin BR(Y)$. Indeed, x_1 and x_2 can increase model performance by denoising x_3, ensuring that they are given significant importance despite being completely unrelated to Y. In contrast, UMFI_LR and UMFI_OT detect that x_1 and x_2 should have zero importance while giving most the importance to x_4 and the rest of the relative importance to x_3.

4.2 BRCA experiments

We use the same breast cancer (BRCA) classification dataset [45] used in previous feature importance studies including Catav et al. [12] and Covert et al. [15] to test the quality and robustness of UMFI on real data. The original data contains over $17,000$ genes and 571 anonymous patients that have been diagnosed with one of 4 breast cancer sub-types. We consider the same subset of 50 genes as in Catav et al. [12] and Covert et al. [15] for easier computation and result visualization. Of the 50 selected genes, 10 are known to be associated with breast cancer, while the other 40 genes are randomly sampled. This data was downloaded from `https://github.com/TAU-MLwell/` `Marginal-Contribution-Feature-Importance/tree/main/BRCA_dataset` (MIT License). In Catav et al. [12] and Covert et al. [15], these 40 randomly sampled genes are assumed to be unassociated with breast cancer. However, to ensure a more definitive ground truth, we also randomly permute the values of these 40 genes across their respective 571 observations to further reduce the chance that these genes have any association with breast cancer. Quality is then measured with the true positive and true negative rates: the 10 BRCA associated genes should have some non-zero importance (positive), and the other 40 genes should have exactly zero importance (negative). These experiments were run 200 times on different seeds and with a different random sample of 500 patients for each iteration. Robustness is measured using the standardized interquartile range (SIQR) from the repeated experiments, which is calculated by dividing the average IQR across the 50 features by the average median. This experiment is too computationally intensive for MCI to be calculated exactly, so we implement MCI assuming soft 2-size submodularity.

Figure 2: Median feature importance scores provided by (a) MCI, (b) UMFI with linear regression, and (c) UMFI with pairwise optimal transport, for each gene in the BRCA dataset after 200 iterations. Genes colored in blue are known to be associated with breast cancer while genes colored in grey are random permutations of randomly selected genes, which we assume to be unassociated with breast cancer. The first and third quantiles of the scores are visualized for each gene.

We found that MCI and UMFI (UMFI_LR and UMFI_OT) correctly gave significant importance to the 10 genes that are known to be associated with breast cancer (Figure 2). Interestingly, the ordering of important features was similar across methods, with BCL11A and SLC22A5 always being the most important and TEX14 always being the least important of the 10 BRCA-associated genes. However, MCI consistently gives non-zero importance to all features, while UMFI correctly gives zero importance to the majority of the randomized genes. Furthermore, UMFI's performance in this experiment improves with increased iterations. After running the experiment 5000 times, both UMFI methods have a perfect overall accuracy when distinguishing between important and permuted features (Appendix G.2.1). Although UMFI scores have higher variability than MCI (Table 1), it is clear from Figure 2 that UMFI separates the 10 associated genes from the 40 unassociated genes better than MCI does.

Table 1: The standardized interquartile range (SIQR), true positive rate (TPR), true negative rate (TNR), overall accuracy (OA), and the number of features for which feature importance can be calculated within 1, 15, and 60 minute(s) are displayed after running the methods on the BRCA data.

Method	SIQR	TPR	TNR	OA	@1min	@15min	@1hr
MCI (k=2)	**6.6 %**	**1**	0	0.20	35	80	130
UMFI (LR)	41.9%	**1**	**0.975**	**0.98**	**500**	**2000**	**4010**
UMFI (OT)	28.5%	**1**	0.775	0.82	300	1500	3000

4.3 Computational complexity

MCI must train and evaluate a model for each element of the power set of the feature set, which implies $O(2^p)$ model trainings if there are p features. If the evaluation function ν obeys soft k-size submodularity, then the maximizing subset has no more than k elements, which reduces the number of model trainings to $O(p^{k+1})$ [12]. UMFI circumvents the exponential training time since it can be evaluated immediately after removing the dependencies of x_i from the feature set F. To confirm the above statements, and to show that the extra model trainings required for MCI dominate the computation time for removing dependencies in UMFI, we ran a simple experiment. For a range of dataset sizes from the BRCA data, we evaluate the computation time for calculating the feature importance scores of all features using MCI and UMFI. We ran this experiment for a dataset with 5 features, and then slowly added features until our given time budget of 1 hour ran out. Once all 50 BRCA features were used, more features were randomly generated. All datasets had 571 observations. These experiments were run using an Intel Core i9-9980HK CPU 2.40GHz with 32GB of RAM. Code was parallelized in R, and 12 of the 16 available threads were used.

Figure 3: Computation time of MCI (dark red), MCI with the soft 2-size-submodularity assumption (pink), UMFI_OT (light blue), and UMFI_LR (dark blue) plotted against number of processed features from the BRCA data.

From Figure 3, we can observe that UMFI is approximately superlinear, with UMFI_OT incuring more computational cost compared to UMFI_LR. Giving each method 1 hour to run, MCI processed 19 features, MCI with the soft 2-size submodularity assumption processed 130 features, UMFI_OT processed about 3000 features, and UMFI_LR processed about 4000 features (Table 1).

5 Conclusion

In this study, we introduced ultra-marginal feature importance (UMFI), a new method that uses preprocessing techniques, originally developed in the domain of AI fairness, to provide fast and accurate feature importance scores for the purposes of explaining data. We introduced three ideal axioms that feature importance measures should satisfy if they claim to explain the data, which are all satisfied by UMFI under some basic assumptions (Appendix C). Optimal transport and linear regression were explored as preprocessing techniques to remove dependencies from data. When compared with MCI, the previous state-of-the-art method for explaining data, experimental results showed that UMFI was able to provide faster and more accurate estimates of feature importance on real and simulated data, particularly in the presence of correlated interactions and unrelated features. UMFI's superior time complexity could be leveraged to run feature importance on larger datasets or to achieve more accurate results by utilizing its median scores after many iterations.

Throughout the work on this paper, several shortcomings appeared. First, we only considered two simple methods for removing dependencies, linear regression and pairwise optimal transport. Other methods certainly exist in the literature, including optimal transport with chaining [29], neural networks [10, 43], or principal inertial components [48]. Though our two methods performed fairly well on the real and simulated datasets in Section 4, optimal transport and linear regression failed to find representations of the data that were independent of the protected attribute when we tested the methods on a hydrology dataset with more shared information compared to BRCA [1] (Appendix G.4). However, neural nets or principal inertial components certainly could have given better results. Also, despite requiring significantly more computational cost, better methods for estimating the conditional CDF, or using optimal transport with chaining, should give better estimates for $S_{x_i}^F$ when implementing UMFI_OT. Even though dependencies were not removed optimally for the hydrology dataset, the estimates of feature importance were still reasonably accurate. Second, UMFI scores are less robust than MCI since they have higher variability, however, because of the significantly lower computational cost, UMFI can be run multiple times and averaged to increase robustness. Third, it is not clear precisely how closely ν_f approximates mutual information in practice. Finally, though UMFI can work for any arbitrary feature type, in this paper, we have only considered datasets with continuous explanatory variables.

In future work, we would like to test how well other methods, such as neural networks, pair with UMFI while further testing on a wider variety of random variable types such as binary, categorical, and ordinal features. Further, we would like to explore how well dependence can be removed and UMFI can be estimated on real data as the number of features increases to sizes much larger than 50.

To reiterate, UMFI is a powerful tool for detecting and explaining the relationships hidden within data. We emphasise that UMFI is just a framework. A variety of other methods can be used to estimate the universal predictive power ν including, but not limited to, XGBoost, neural networks, or Gaussian processes. Even non-model-based methods such as Hilbert-Schmidt independence criterion could be explored in future applications. Furthermore, new preprocessing techniques for dependence removal are still being developed in the AI fairness community, so these, in addition to other existing methods, can be used in future applications of UMFI for additional improvements.

Broader Impact

We hope that UMFI will be a useful tool in a variety of disciplines including bioinfomatics, ecology, earth sciences, and health science for discovering scientific processes and relationships hidden within data. Though we think that our contributions can only lead to positive social and environmental impacts by aiding scientific discoveries in domains like earth science and bioinformatics, statistical methods, especially those that are aimed at genetics research, have historically been used to justify harmful and misleading claims. If such claims arise using our methods, then they should be dismissed since direct causal effects cannot be concluded after using our methods alone.

References

[1] Nans Addor, Andrew J Newman, Naoki Mizukami, and Martyn P Clark. The camels data set: catchment attributes and meteorology for large-sample studies. *Hydrology and Earth System Sciences*, 21(10):5293–5313, 2017.

[2] Nans Addor, Grey Nearing, Cristina Prieto, AJ Newman, Nataliya Le Vine, and Martyn P Clark. A ranking of hydrological signatures based on their predictability in space. *Water Resources Research*, 54(11):8792–8812, 2018.

[3] Daniel W Apley and Jingyu Zhu. Visualizing the effects of predictor variables in black box supervised learning models. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 82(4):1059–1086, 2020.

[4] Eviatar Bach, Valentina Radić, and Christian Schoof. How sensitive are mountain glaciers to climate change? insights from a block model. *Journal of Glaciology*, 64(244):247–258, 2018.

[5] Adrián Bazaga, Dan Leggate, and Hendrik Weisser. Genome-wide investigation of gene-cancer associations for the prediction of novel therapeutic targets in oncology. *Scientific reports*, 10(1): 1–10, 2020.

[6] Jian Bi. A review of statistical methods for determination of relative importance of correlated predictors and identification of drivers of consumer liking. *Journal of Sensory Studies*, 27(2): 87–101, 2012.

[7] Sarah Bird, Miro Dudík, Richard Edgar, Brandon Horn, Roman Lutz, Vanessa Milan, Mehrnoosh Sameki, Hanna Wallach, and Kathleen Walker. Fairlearn: A toolkit for assessing and improving fairness in ai. *Microsoft, Tech. Rep. MSR-TR-2020-32*, 2020.

[8] Leo Breiman. Random forests. *Machine learning*, 45(1):5–32, 2001.

[9] Alexander Brenning and GF Azócar. Statistical analysis of topographic and climatic controls and multispectral signatures of rock glaciers in the dry andes, chile (27–33 s). *Permafrost and Periglacial Processes*, 21(1):54–66, 2010.

[10] Flavio Calmon, Dennis Wei, Bhanukiran Vinzamuri, Karthikeyan Natesan Ramamurthy, and Kush R Varshney. Optimized pre-processing for discrimination prevention. *Advances in neural information processing systems*, 30, 2017.

[11] Amnon Catav, Boyang Fu, Jason Ernst, Sriram Sankararaman, and Ran Gilad-Bachrach. Marginal contribution feature importance–an axiomatic approach for the natural case. *arXiv preprint arXiv:2010.07910*, 2020.

[12] Amnon Catav, Boyang Fu, Yazeed Zoabi, Ahuva Libi Weiss Meilik, Noam Shomron, Jason Ernst, Sriram Sankararaman, and Ran Gilad-Bachrach. Marginal contribution feature importance - an axiomatic approach for explaining data. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 1324–1335. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/catav21a.html.

[13] Hugh Chen, Joseph D Janizek, Scott Lundberg, and Su-In Lee. True to the model or true to the data? *arXiv preprint arXiv:2006.16234*, 2020.

[14] Shay Cohen, Gideon Dror, and Eytan Ruppin. Feature selection via coalitional game theory. *Neural Computation*, 19(7):1939–1961, 2007.

[15] Ian Covert, Scott M Lundberg, and Su-In Lee. Understanding global feature contributions with additive importance measures. *Advances in Neural Information Processing Systems*, 33: 17212–17223, 2020.

[16] Ian Covert, Scott M Lundberg, and Su-In Lee. Explaining by removing: A unified framework for model explanation. *J. Mach. Learn. Res.*, 22:209–1, 2021.

[17] Dries Debeer and Carolin Strobl. Conditional permutation importance revisited. *BMC bioinformatics*, 21(1):1–30, 2020.

[18] Tamsin L Edwards, Sophie Nowicki, Ben Marzeion, Regine Hock, Heiko Goelzer, Hélène Seroussi, Nicolas C Jourdain, Donald A Slater, Fiona E Turner, Christopher J Smith, et al. Projected land ice contributions to twenty-first-century sea level rise. *Nature*, 593(7857):74–82, 2021.

[19] WA Gibson. Orthogonal predictors: A possible resolution of the hoffman-ward controversy. *Psychological reports*, 11(1):32–34, 1962.

[20] David A Gill, Michael B Mascia, Gabby N Ahmadia, Louise Glew, Sarah E Lester, Megan Barnes, Ian Craigie, Emily S Darling, Christopher M Free, Jonas Geldmann, et al. Capacity shortfalls hinder the performance of marine protected areas globally. *Nature*, 543(7647): 665–669, 2017.

[21] Arthur Gretton, Olivier Bousquet, Alex Smola, and Bernhard Schölkopf. Measuring statistical dependence with hilbert-schmidt norms. In *International conference on algorithmic learning theory*, pages 63–77. Springer, 2005.

[22] Virgil Griffith and Christof Koch. Quantifying synergistic mutual information. *arXiv preprint arXiv:1205.4265*, 2012.

[23] Ulrike Grömping. Variable importance in regression models. *Wiley interdisciplinary reviews: Computational statistics*, 7(2):137–152, 2015.

[24] Nimrod Harel, Ran Gilad-Bachrach, and Uri Obolski. Inherent inconsistencies of feature importance. *arXiv preprint arXiv:2206.08204*, 2022.

[25] Giles Hooker, Lucas Mentch, and Siyu Zhou. Unrestricted permutation forces extrapolation: variable importance requires at least one more model, or there is no free variable importance. *Statistics and Computing*, 31(6):1–16, 2021.

[26] Aleks Jakulin and Ivan Bratko. Quantifying and visualizing attribute interactions: An approach based on entropy. 2003.

[27] Alexander Janssen, Mark Hoogendoorn, Marjon H Cnossen, Ron AA Mathôt, OPTI-CLOT Study Group, SYMPHONY Consortium, MH Cnossen, SH Reitsma, FWG Leebeek, RAA Mathôt, K Fijnvandraat, et al. Application of shap values for inferring the optimal functional form of covariates in pharmacokinetic modeling. *CPT: Pharmacometrics & Systems Pharmacology*, 2022.

[28] Joseph Janssen and Ali A Ameli. A hydrologic functional approach for improving large-sample hydrology performance in poorly gauged regions. *Water Resources Research*, 57(9): e2021WR030263, 2021.

[29] James E Johndrow and Kristian Lum. An algorithm for removing sensitive information: application to race-independent recidivism prediction. *The Annals of Applied Statistics*, 13(1): 189–220, 2019.

[30] Pål V Johnsen, Signe Riemer-Sørensen, Andrew Thomas DeWan, Megan E Cahill, and Mette Langaas. A new method for exploring gene–gene and gene–environment interactions in gwas with tree ensemble methods and shap values. *BMC bioinformatics*, 22(1):1–29, 2021.

[31] Gunnar König, Timo Freiesleben, Bernd Bischl, Giuseppe Casalicchio, and Moritz Grosse-Wentrup. Decomposition of global feature importance into direct and associative components (dedact). *arXiv preprint arXiv:2106.08086*, 2021.

[32] Alexander Kraskov, Harald Stögbauer, and Peter Grassberger. Estimating mutual information. *Physical Review E*, 69(6), jun 2004. doi: 10.1103/physreve.69.066138. URL https://doi.org/10.1103%2Fphysreve.69.066138.

[33] Edward Le, Ali Ameli, Joseph Janssen, and John Hammond. Snow persistence explains stream high flow and low flow signatures with differing relationships by aridity and climatic seasonality. *Hydrology and Earth System Sciences Discussions*, pages 1–22, 2022.

[34] Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. *Advances in neural information processing systems*, 30, 2017.

[35] Alexander Marx, Arthur Gretton, and Joris M Mooij. A weaker faithfulness assumption based on triple interactions. In *Uncertainty in Artificial Intelligence*, pages 451–460. PMLR, 2021.

[36] R Core Team Microsoft. *Microsoft R Open*. Microsoft, Redmond, Washington, 2017. URL https://mran.microsoft.com/.

[37] Christoph Molnar. *Interpretable machine learning*. Lulu. com, 2020.

[38] Christoph Molnar, Gunnar König, Bernd Bischl, and Giuseppe Casalicchio. Model-agnostic feature importance and effects with dependent features–a conditional subgroup approach. *arXiv preprint arXiv:2006.04628*, 2020.

[39] Alena Orlenko and Jason H Moore. A comparison of methods for interpreting random forest models of genetic association in the presence of non-additive interactions. *BioData mining*, 14 (1):1–17, 2021.

[40] Lennart Schmidt, Falk Heße, Sabine Attinger, and Rohini Kumar. Challenges in applying machine learning models for hydrological inference: A case study for flooding events across germany. *Water Resources Research*, 56(5):e2019WR025924, 2020.

[41] Heïdi Sevestre and Douglas I Benn. Climatic and geometric controls on the global distribution of surge-type glaciers: implications for a unifying model of surging. *Journal of Glaciology*, 61 (228):646–662, 2015.

[42] Lloyd S Shapley. A value for n-person games, contributions to the theory of games, 2, 307–317, 1953.

[43] Jiaming Song, Pratyusha Kalluri, Aditya Grover, Shengjia Zhao, and Stefano Ermon. Learning controllable fair representations. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 2164–2173. PMLR, 2019.

[44] Lina Stein, Martyn P Clark, Wouter JM Knoben, Francesca Pianosi, and Ross A Woods. How do climate and catchment attributes influence flood generating processes? a large-sample study for 671 catchments across the contiguous usa. *Water Resources Research*, 57(4):e2020WR028300, 2021.

[45] Katarzyna Tomczak, Patrycja Czerwińska, and Maciej Wiznerowicz. The cancer genome atlas (tcga): an immeasurable source of knowledge. *Contemporary oncology*, 19(1A):A68, 2015.

[46] Matthew J Vowels, Necati Cihan Camgoz, and Richard Bowden. D'ya like dags? a survey on structure learning and causal discovery. *ACM Computing Surveys (CSUR)*, 2021.

[47] Hao Wang and Flavio P Calmon. An estimation-theoretic view of privacy. In *2017 55th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pages 886–893. IEEE, 2017.

[48] Hao Wang, Lisa Vo, Flavio P Calmon, Muriel Médard, Ken R Duffy, and Mayank Varia. Privacy with estimation guarantees. *IEEE Transactions on Information Theory*, 65(12):8025–8042, 2019.

[49] Hui Wang, David A Bennett, Philip L De Jager, Qing-Ye Zhang, and Hong-Yu Zhang. Genome-wide epistasis analysis for alzheimer's disease and implications for genetic risk prediction. *Alzheimer's research & therapy*, 13(1):1–13, 2021.

[50] Pengfei Wei, Zhenzhou Lu, and Jingwen Song. Variable importance analysis: a comprehensive review. *Reliability Engineering & System Safety*, 142:399–432, 2015.

[51] Thomas C Williams, Cathrine C Bach, Niels B Matthiesen, Tine B Henriksen, and Luigi Gagliardi. Directed acyclic graphs: a tool for causal studies in paediatrics. *Pediatric research*, 84(4):487–493, 2018.

[52] Brian Williamson and Jean Feng. Efficient nonparametric statistical inference on population feature importance using shapley values. In *International Conference on Machine Learning*, pages 10282–10291. PMLR, 2020.

[53] Marvin N Wright and Andreas Ziegler. ranger: A fast implementation of random forests for high dimensional data in c++ and r. *arXiv preprint arXiv:1508.04409*, 2015.

[54] Sewall Wright. Correlation and causation. 1921.

[55] Lee H Wurm and Sebastiano A Fisicaro. What residualizing predictors in regression analyses does (and what it does not do). *Journal of memory and language*, 72:37–48, 2014.