Does the Half Adversarial Robustness Represent the Whole? It Depends ... A Theoretical Perspective of Subnetwork Robustness

Abstract

Adversarial robustness of deep neural networks has been studied extensively and can bring security against adversarial attacks/examples. However, adversarially robust training approaches require a training mechanism on the entire deep network which can come at the cost of efficiency and computational complexity such as runtime. As a pilot study, we develop in this paper a novel theoretical framework that aims to answer the question of *how can we make a whole model robust to adversarial examples by making part of a model robust?* Toward promoting subnetwork robustness, we propose for the first time a new concept of *semirobustness*, which indicates adversarial robustness of a part of the network. We provide a theoretical analysis to show that *if a subnetwork is robust and highly correlated with the rest of the network, then the remaining layers are also guaranteed to be robust*. To guide the empirical investigation of our theoretical findings, we implemented our method at multiple layer depths and across multiple common image classification datasets. Experiments demonstrate that our method, with sufficient dependency between subnetworks, successfully utilizes subnetwork robustness to match fully-robust models' performance across AlexNet, VGG16, and ResNet50 benchmarks, for attack types FGSM, I-FGSM, PGD, and C&W.

1 Introduction

Deep neural networks (DNNs) have been highly successful in computer vision, particularly in image classification tasks, speech recognition, and natural language processing where they can often outperform human abilities Mnih et al. (2015); Radford et al. (2015); Goodfellow et al. (2016). Despite this, the reliability of deep learning algorithms is fundamentally challenged by the existence of the phenomenon of "adversarial examples", which are typically natural images that are perturbed with random noise such that the networks misclassify them. In the context of image classification an extremely small perturbation can change the label of a correctly classified image Szegedy et al. (2014); Goodfellow et al. (2014). For this reason, adversarial examples present a major threat to the security of deep-learning systems; however, a robust classifier can correctly label adversarially perturbed images. For example, an adversary could alter images of the road to fool a self-driving car's neural network into misclassifying traffic signs Papernot et al. (2016a), reducing the car's safety, but a robust network would detect and reject the adversarial inputs Ma et al. (2018); Biggio et al. (2013). The problem of finding perturbed inputs, known as adversarial attacks, has been studied extensively Kurakin et al. (2017); Sharif et al. (2016); Brown et al. (2017); Eykholt et al. (2018). To handle adversarial attacks, two major solutions have been studied: (1) Efficient methods to find adversarial examples Su et al. (2019); Laidlaw & Feizi (2019); Athalye et al. (2018); Liu et al. (2016); Xie et al. (2017); Akhtar & Mian (2018), (2) Adversarial training to make deep neural networks more robust against adversarial attacks Madry et al. (2018); Tsipras et al. (2019); Gilmer et al. (2019); Ilyas et al. (2019); Papernot et al. (2016b).

The adversarial perturbations may be applied to the input or to the network's hidden layers Goodfellow et al. (2014); Szegedy et al. (2014) and it has been show that this strategy is effective at improving a network's robustness Goodfellow et al. (2014). Several theories have been developed to explain the phenomenon of adversarial examples Raghunathan et al. (2018); Xiao et al. (2019); Cohen et al. (2019); Shamir et al. (2019); Fawzi et al. (2016); Carlini & Wagner (2017); Weng et al. (2018); Ma

et al. (2018). Previously Ilyas et al. (2019) investigated adversarial robustness from a theoretical perspective. The authors address "useful, non-robust features": useful because they help a network improve its accuracy, and non-robust because they are imperceptible to humans and thus not intended to be used for classification. Normally, a model considers robust features to be about as important as non-robust ones, yet adversarial examples encourage it to rely on only non-robust features. Ilyas et al. (2019) introduces a framework to explain the phenomenon of adversarial vulnerability . A feature f is considered a "ρ-useful feature" if it is correlated with the true label in the dataset. Similarly, "γ-robustly useful features" are ρ-useful for a set of adversarial perturbations. While Ilyas et al. (2019) constitutes a fundamental advance in the theoretical understanding of adversarial examples, and opens the way to a thorough theoretical characterization of the relation between network architecture and robustness to adversarial perturbations, little attention has been paid to how robustness throughout the network is guaranteed and whether adversarial training must be applied to the entire network.

In this paper, we develop a new theoretical framework that monitors the robustness across the layers in a DNN and explains that if the early layers are adversarially trained and are sufficiently correlated with the rest of the network, then adversarial robustness of the latter layers is obtained. All of these findings raise a fundamental question: **How can we make a whole model robust to adversarial inputs by making part of the model robust?** In addition, the vulnerability of models trained using standard methods to adversarial perturbations makes it clear that the paradigm of adversarially robust learning is different from the classic learning setting. In particular, we already know that robustness comes at the cost of computationally expensive training methods (more training time) Zhang et al. (2019), as well as the potential need for more training data and memory capacity Schmidt et al. (2018). Hence, one notable challenge in adversarially robust learning is computational complexity while maintaining desired performance. To this end, by exploiting the possibility that subnetworks can be robust to adversarial attacks, we propose a novel approach that aims to theoretically analyze adversarial robustness guarantees in a network by adversarially training only a subset of layers. This work will also pioneer the new concept of "semirobustness" which indicates adversarial robustness of a part of the network. This includes a new perspective of adversarial perturbations and a novel theoretical framework that explains theories for the following claim:

> *If a subnetwork is robust and highly depended on by the rest of the network, then the remaining layers are also guaranteed to be robust.*

Contributions To summarize, our contributions in this paper are: (1) We **introduce** a novel concept of semirobustness in subnetworks. We show that a subnetwork is semirobust if and only if all layers within the subnetwork are semirobust. (2) For the first time we **provide a theoretical framework** and prove that under some assumptions if the first part of the network is semirobust then the second part of the network's robustness is guaranteed. (3) Experimentally, we **demonstrate** that given sufficient mutual dependency between subnetworks, our method displays the same adversarial robustness of a network as compared to regular adversarial training.

2 SUBNETWORK ROBUSTNESS

Notations We assume that a given DNN has a total of n layers where, $F^{(n)}$ is a function mapping the input space $\mathcal{X}$ to a set of classes $\mathcal{Y}$, i.e. $F^{(n)} : \mathcal{X} \mapsto \mathcal{Y}$; $f^{(l)}$ is the l-th layer of $F^{(n)}$; $F^{(i,j)} := f^{(j)} \circ \ldots \circ f^{(i)}$ is a subnetwork which is a group of consecutive layers $f^{(i)}, \ldots, f^{(j)}$; $F^{(j)} := F^{(1,j)} = f^{(j)} \circ \ldots \circ f^{(1)}$ is the first part of the network up to layer j. Denote $\sigma^{(l)}$ the activation function in layer l and $\pi(y)$ the prior probability of class label $y \in \mathcal{Y}$. Let $f^{(l)}$ be the lth layer of $F^{(n)}$, as $f^{(l)}(x_{l-1}) = \sigma^{(l)}(w^{(l)}x_{l-1} + b^{(l)})$, where $\sigma^{(l)}$ is the activation function. In this section, we define the notion of a Semirobust Subnetwork. We discuss semirobustness more in Section 2.1.

Definition 1 (Semirobust Subnetwork) *Suppose input $\mathbf{X}$ and label y are samples from joint distribution $\mathcal{D}$. For a given distribution $\mathcal{D}$, a subnetwork $F^{(j)}$ is called γ_j-semirobust if there exists a mapping function $G_j : \mathcal{L}_j \mapsto \mathcal{Y}$ such that*

$$\mathbb{E}_{(\mathbf{X},y)\sim\mathcal{D}}\big[\inf_{\delta\in S_x} y \cdot G_j \circ F^{(j)}(\mathbf{X} + \delta)\big] \geq \gamma_j, \tag{1}$$

for an appropriately defined set of perturbations S_x. In (1), G_j is a non-unique function mapping layer $f^{(j)}$ to class set $\mathcal{Y}$, and γ_j is a constant denoting the correlation between y and $F^{(j)}$. Note that G_j is necessary if the dimensionality of $F^{(j)}$ does not match that of y, but if $F^{(j)} = F^{(n)}$, the semirobust definition becomes standard γ-robustness as defined in Ilyas et al. (2019). Throughout this paper, we assume that the network $F^{(n)}$ is a useful network i.e. for a given distribution $\mathcal{D}$, the correlation between $F^{(n)}$ and true label y, $\mathbb{E}_{(\mathbf{X},y)\sim\mathcal{D}}\big[y \cdot F^{(n)}(\mathbf{X})\big]$ is highest in expectation in optimal performance. Intuitively, a highly useful network $F^{(n)}$ minimizes the classification loss $\mathbb{E}_{(\mathbf{X},y)\sim\mathcal{D}}\big[\mathcal{L}(\mathbf{X},y)\big]$ that is

$$- \mathbb{E}_{(\mathbf{X},y)\sim\mathcal{D}}\Big[y \cdot \big(b + \sum_{F^{(n)}\in\mathcal{F}^{(n)}} w_{F^{(n)}} F^{(n)}(\mathbf{X})\big)\Big], \qquad (2)$$

where $w_{F^{(n)}}$ is the weight vector and $\mathcal{F}^{(n)}$ is the set of n-th layer networks. Definition 1 raises valid questions regarding the relationship between a subnetwork and its associated layers' robustness. We show this relationship under the following thoerem.

Theorem 1 *The subnetwork $F^{(j)}$ is γ_j-semirobust if and only if every layer of $F^{(j)}$, i.e. $f^{(j)}, f^{(j-1)}, \ldots, f^{(1)}$, is also semirobust with bound parameters $\gamma_j, \ldots, \gamma_1$ respectively.*

Theorem 1 is a key point used to support our main claims on the relationship between layer-wise and subnetwork robustness, and its proof is provided as supplementary materials. Next, we show that under a strong dependency assumption between layers the robustness of subnetworks are guaranteed.

2.1 SEMIROBUSTNESS GUARANTEES

In this section, we provide theoretical analysis to explain how dependency between layers of subnetworks promotes semirobustness and eliminates the entire-network adversarial training requirement.

Non-linear Probabilistic Dependency (Mutual Information): Among various probabilistic dependency measures, in this paper, we adopt an information-theoretic measure called mutual information (MI): a measure of the reduction in uncertainty about one random variable by knowing about another. Formally, it is defined as follows: Let $\mathcal{X}$ and $\mathcal{Z}$ be Euclidean spaces, and let P_{XZ} be a probability measure in the space $\mathcal{X} \times \mathcal{Z}$. Here, P_X and P_Z define the marginal probability measures. The mutual information (MI), denoted by $I(X;Z)$, is defined as,

$$I(X;Y) = \mathop{\mathbb{E}}_{P_X P_Z}\left[g\left(\frac{dP_{XZ}}{dP_X P_Z}\right)\right], \qquad (3)$$

where $\frac{dP_{XZ}}{dP_X P_Z}$ is the Radon-Nikodym derivative, $g : (0,\infty) \mapsto \mathbb{R}$ is a convex function, and $g(1) = 0$. Note that when $\frac{dP_{XY}}{dP_X P_Y} \to 1$, then $I \to 0$. Using (3), the MI measure between two layers $f^{(i)}$ and $f^{(j)}$ with joint distribution P_{ij} and marginal distributions P_i, P_j respectively is given as

$$I(f^{(i)}; f^{(j)}) = \mathop{\mathbb{E}}_{P_i P_j}\left[g\left(\frac{dP_{ij}}{dP_i P_j}\right)\right]. \qquad (4)$$

The concept of MI is integral to the most important theory in our theoretical framework through the assumptions below.

Assumptions: Let $G_a : \mathcal{L}_a \mapsto \mathcal{Y}$ be a function mapping layer $f^{(a)}$ to a label $y \in \mathcal{Y}$, and let $G_j : \mathcal{L}_j \mapsto \mathcal{Y}$ be a function mapping layer $f^{(j)}$ to a label $y \in \mathcal{Y}$. Let $g_\delta = f^{(a)}(\mathbf{X} + \delta)$ and $h_{\delta,j} = f^{(j)}(\mathbf{X} + \delta)$ for $\delta \in S_x$ (perturbation set). Note that $g_\delta = h_{\delta,a}$.

A1: The class-conditional MI between $h_{\delta,j-1}$ and $h_{\delta,j}$ is at least hyperparameter $\rho_j \geq 0$, i.e.

$$\inf_{\delta\in S_x} \sum_y \pi(y) I\left(h_{\delta,j-1}; h_{\delta,j}|y\right) \geq \rho_j \qquad (5)$$

A2: There exists a constant $U_j \geq 0$ such that for all $\delta \in S$:

$$\mathbb{E}_{p(h_{\delta,j-1}, h_{\delta,j}, y)}\left[\frac{p(h_{\delta,j-1}, h_{\delta,j}|y)}{p(h_{\delta,j-1}|y)p(h_{\delta,j}|y)}\right] \leq U_j, \quad \text{and}$$

$$\mathbb{E}_{p(h_{\delta,j-1}, h_{\delta,j}, y)}\left[y \cdot (G_j \circ h_{\delta,j} - G_{j-1} \circ h_{\delta,j-1})\right] \geq 1 + U_j,$$

where $p(h_{\delta,j-1}, h_{\delta,j}, y)$ is the joint probability of random triple $(h_{\delta,j-1}, h_{\delta,j}, y)$.

Theorem 2 *Let f_a be a γ_a-semirobust subnetwork equivalent to $F^{(a)}$, and let f_b be the subnetwork $F^{(a+1,n)}$ and for $j = a + 1, \dots, n$, assumptions **A1** and **A2** holds true. Then f_b is γ_b-semirobust.*

In Theorem 2, $\gamma_b = \gamma_n$. This theorem is an extension of the following lemma, and the proofs of both are found in the Supplementary Material.

Lemma 1 *Let $F^{(n-1)}$ be a γ-semirobust subnetwork. Let $g_\delta = f^{(n-1)}(\mathbf{X}+\delta)$ and $h_\delta = f^{(n)}(\mathbf{X}+\delta)$ for $\delta \in S_x$. Let $G_{n-1} : \mathcal{L}_{n-1} \mapsto \mathcal{Y}$ be a function mapping layer g to the network's output $y \in \mathcal{Y}$. Under the following assumptions $f^{(n)}$ is γ_n-semirobust:*

- **B1***: The MI between $f^{(n-1)}$ and $f^{(n)}$ is at least hyperparameter $\rho \geq 0$, i.e.*

$$\inf_{\delta \in S} \sum_y \pi(y) I\left(g_\delta; h_\delta | y\right) \geq \rho$$

- **B2***: There exists a constant $U \geq 0$ such that for all $\delta \in S$:*

$$\mathbb{E}_{p(g_\delta, h_\delta, y)} \left[\frac{p(g_\delta, h_\delta | y)}{p(g_\delta | y) p(h_\delta | y)} \right] \leq U, \quad and \quad \mathbb{E}_{p(g_\delta, h_\delta, y)} \left[y \cdot (h_\delta - G_{n-1} \circ g_\delta) \right] \geq 1 + U.$$

Note that assumptions **B1** and **B2** are particular cases of **A1** and **A2**, when $a = n - 1$.

Intuition: Let $\mathcal{IF}(.)$ determine the information flow passing through layers in the network $F^{(n)}$. Intuitions from the $\mathcal{IF}$ literature would advocate that in a feed-forward network if the learning information is preserved up to a given layer, one can utilize knowledge of this information flow in the next consecutive layer's learning process due to principle $F^{(i,j)} = f^{(j)} \circ F^{(i,j-1)}$, and consequently $\mathcal{IF}^{(i,j)} \approx \mathcal{IF}^{(j)} \circ \mathcal{IF}^{(i,j-1)}$. This is desirable as in practice training the subnetwork requires less computation and memory usage. This explains that under the assumption of strong connection between j-th and $j-1$-th layers, the information automatically passes throughout the later layers and subnetwork training returns sufficient solutions for task decision making. To better characterize the measure of information flow, we employ a non-linear and probabilistic dependency measure that determines the mutual relationship between layers and how much one layer tells us about the other one. An important takeaway from Theorem 2 (and Lemma 1) is that a strong non-linear mutual connectivity between subnetworks guarantees that securing only the robustness of the first subnetwork ensures information flow throughout the entire network.

Linear Connectivity: To provably show that our theoretical study in Theorem 2 is satisfied for the linear connectivity assumption between subnetworks, we provide a theory that investigates the scenario when the layers in the second half of the network are a linear combination of the layers in the first subnetwork.

Theorem 3 *Let f_a be a γ_a-semirobust subnetwork equivalent to $F^{(a)}$, and let f_b be the subnetwork $F^{(a+1,n)}$. If for $j = a + 1, \dots, n$, $f^{(j)} = \sum\limits_{i=1}^{j-1} \lambda_{ij}^T \cdot f^{(i)}$, where λ_{ij} is a map $\mathcal{L}_i \mapsto \mathcal{L}_j$ and a matrix of dimensionality $\mathcal{L}_i \times \mathcal{L}_j$, then f_b is γ_b-semirobust where $\gamma_b = \gamma_a \left((n - 1 - a)(n - a)/2 \right)$.*

This theorem shows that when the connectivity between layers in f_a and f_b is linear, we achieve the semirobustness property for the subnetwork f_b. Importantly, note that linear combination multipliers determine the Pearson correlation between layers given the constant variance of the layers. This is because if $f^{(j)} = \lambda_{ij} f^{(i)}$, then $Corr(f^{(j)}, f^{(i)}) = \lambda_{ij} var(f^{(i)})$. Theorem 3 is an extension of the lemma 2. Detailed proof and accompanying experiments are provided in the Supplementary Material.

Lemma 2 *Let the last layer $f^{(n)}$ be a linear combination of $f^{(n-1)}, \dots, f^{(1)}$, expressed as $f^{(n)} = \sum\limits_{i=1}^{n-1} \lambda_i^T \cdot f^{(i)}$, where λ_i is a map $\mathcal{L}_i \mapsto \mathcal{L}_n$ and a matrix of dimensionality $\mathcal{L}_i \times \mathcal{L}_n$. If $F^{(n-1)}$ is γ-semirobust, then $f^{(n)}$ is γ_n-semirobust where $\gamma_n = \sum\limits_{i=1}^{n-1} \gamma_i$.*

Question: At this point, a valid argument could be how the performance of a network differs under optimal full-network robustness, (f_a^*, f_b^*) and subnetwork robustness $(f_a^*, \tilde{f}_b)$. Does the difference

between performance have any relationship with the weight difference of subnetworks f_b^* and $\widetilde{f}_b$? This question is investigated in the next section by analyzing the difference between loss function of the networks (f_a^*, f_b^*) and $(f_a^*, \widetilde{f}_b)$.

2.2 FURTHER THEORETICAL INSIGHTS

Let ω^* be the convergent parameters after training has been finished for the network $F^{*(n)} := (f_a^*, f_b^*)$, that is adversarially robust against a given attack. Let $\widetilde{\omega}^*$ be the convergent parameters for network $(f_a^*, \widetilde{f}_b)$, that is adversarially semirobust against the attack. This means that only the first half of the network is robust against attacks. Let ω_b^*, $\widetilde{\omega}_b$, and ω_a^* be weights of networks f_b^*, $\widetilde{f}_b$, and f_a^*, respectively. Recall the loss function (2), and remove offset b without loss of generality.

$$\text{Define} \quad \ell(\omega) := - \sum_{F \in \mathcal{F}} w_F \cdot F^{(n)}(\mathbf{X}), \tag{6}$$

therefore the loss function in (2) becomes $\mathbb{E}_{(\mathbf{X},Y)\sim D}\{L(F^{(n)}(\mathbf{X}), Y)\} = \mathbb{E}_{(\mathbf{X},Y)\sim D}\{Y \cdot \ell(\omega)\}$ and $\omega^* := argmin_\omega \mathbb{E}_{(\mathbf{X},Y)\sim D}\{Y \cdot (\ell(\omega))\}$, where ℓ is defined in (6).

Definition 2 (Performance Difference) *Suppose input $\mathbf{X}$ and task Y have joint distribution $\mathcal{D}$. Let $\widetilde{F}^{(n)} := (f_a^*, \widetilde{f}_b) \in \mathcal{F}$ be the network with n layers when the subnetwork f_a^* is semirobust. The performance difference between robust $F^{*(n)} := (f_a^*, f_b^*)$ and semirobust $\widetilde{F}^{(n)}$ is defined as*

$$d(F^{*(n)}, \widetilde{F}^{(n)}) := \mathbb{E}_{(\mathbf{X},Y)\sim D}\left\{L(F^{*(n)}(\mathbf{X}), Y) - L(\widetilde{F}^{(n)}(\mathbf{X}), Y)\right\}. \tag{7}$$

Let $\delta(\omega^*|\widetilde{\omega}^*) := \ell(\omega^*) - \ell_t(\widetilde{\omega}^*)$. The performance difference (7) is the average of δ:

$$d(F^{*(n)}, \widetilde{F}^{(n)}) = \mathbb{E}_{(\mathbf{X},Y)\sim D}\left[Y \cdot \delta(\omega^*|\widetilde{\omega}^*)\right] = \mathbb{E}_{(\mathbf{X},Y)\sim D}\left[Y \cdot \left(\ell(\omega^*) - \ell(\widetilde{\omega}^*)\right)\right]. \tag{8}$$

Using Taylor approximation of ℓ around ω^*:

$$\ell(\widetilde{\omega}^*) \approx \ell(\omega^*) + (\widetilde{\omega}^* - \omega^*)^T \nabla \ell(\omega^*) + \frac{1}{2}(\widetilde{\omega}^* - \omega^*)^T \nabla^2 \ell(\omega^*)(\widetilde{\omega}^* - \omega^*), \tag{9}$$

where $\nabla \ell(\omega^*)$ and $\nabla^2 \ell(\omega^*)$ are gradient and Hessian for loss ℓ at ω^*. Since ω^* is the convergent points of (f_a^*, f_b^*), then $\nabla \ell(\omega^*) = 0$, this implies

$$\ell(\widetilde{\omega}^*) - \ell(\omega^*) \approx \frac{1}{2}(\widetilde{\omega}^* - \omega^*)^T \nabla^2 \ell(\omega^*)(\widetilde{\omega}^* - \omega^*) \leq \frac{1}{2}\lambda^{max}\|\widetilde{\omega}^* - \omega^*\|^2, \tag{10}$$

where λ^{max} is the maximum eigenvalue of $\nabla^2 \ell(\omega^*)$. In (10) we can write $\|\widetilde{\omega}^* - \omega^*\|^2 = \|\widetilde{\omega}_b - \omega_b^*\|^2$ holds because $\widetilde{\omega}^* = (\omega_a^*, \widetilde{\omega}_b)$ and $\omega^* = (\omega_a^*, \omega_b^*)$. Note that here the weight matrices ω^* and $\widetilde{\omega}^*$ are reshaped. Using the loss function $\mathbb{E}_{(\mathbf{X},Y)\sim D}\{Y \cdot \ell(\omega)\}$, we have

$$\mathbb{E}_{(\mathbf{X},Y)\sim D}\left\{Y \cdot \left(\ell(\widetilde{\omega}^*) - \ell(\omega^*)\right)\right\} \leq \frac{1}{2}\mathbb{E}_{(\mathbf{X},Y)\sim D}\left\{Y \cdot \left(\lambda^{max}\|\widetilde{\omega}_b - \omega_b^*\|^2\right)\right\}. \tag{11}$$

This explains that the performance difference (8) between networks $F^{*(n)}$ and $\widetilde{F}^{(n)}$ is upper bounded by the L_2 norm of weight difference of f_b^* and $\widetilde{f}_b$ i.e. $\widetilde{\omega}_b - \omega_b^*$.

Alternatively, using Cauchy–Schwarz inequality, we have

$$\mathbb{E}_{(\mathbf{X},Y)\sim D}\left\{Y \cdot \left(\ell(\widetilde{\omega}^*) - \ell(\omega^*)\right)\right\} \leq \mathbb{E}_{(\mathbf{X},Y)\sim D}\left\{Y\|f^{(n)}(\mathbf{x}; \widetilde{\omega}^*) - f^{(n)}(\mathbf{x}; \omega^*)\|_2\right\}, \tag{12}$$

where $f^{(n)}$ is the last layer of the network. Recall (8) from Lee et al. (2021). As $\widetilde{\omega}^*$ and ω^* are the weights of network on (f_a^*, f_b^*) and $(f_a^*, \widetilde{f}_b)$, we have

$$\|f^{(n)}(\mathbf{x}; \widetilde{\omega}^*) - f^{(n)}(\mathbf{x}; \omega^*)\|_2 \leq \|\widetilde{\omega}_b^* - \omega_b^*\|_F \|\sigma(f_a(\mathbf{x}, \omega_a^*))\|_2. \tag{13}$$

next, we assume the activation function σ is Lipschitz continous i.e. for any $\mathbf{u}$ and $\mathbf{v}$ there exist constant C^σ s.t. $|\sigma(\mathbf{u}) - \sigma(\mathbf{v})| \leq C^\sigma|\mathbf{u} - \mathbf{v}|$. Next, assume the activation function is satisfied in $\sigma(\mathbf{0}) = \mathbf{0}$. Further by assuming that $\|\mathbf{x}\|_2$ is bounded by C_x and by using peeling procedure, we get:

$$\|f^{(n)}(\mathbf{x}; \widetilde{\omega}^*) - f^{(n)}(\mathbf{x}; \omega^*)\|_2 \leq C_{\mathbf{x},\sigma}\|\widetilde{\omega}_b^* - \omega_b^*\|_F \prod_{j \in a} \|\omega^{*(j)}\|_F, \tag{14}$$

here $\omega^{*(j)}$ is the weight matrix of layer j-th in f_a^* and $C_{\mathbf{x},\sigma} = C_{\mathbf{x}} C_\sigma$. Combining (15) and (14) we provide the upper bound:

$$\mathbb{E}_{(\mathbf{X},Y)\sim D} \left\{ Y \cdot \left(\ell(\widetilde{\omega}^*) - \ell(\omega^*) \right) \right\} \leq \mathbb{E}_{(\mathbf{X},Y)\sim D} \left\{ Y \cdot \left(C_{\mathbf{x},\sigma}(\omega_a^*) \| \widetilde{\omega}_b^* - \omega_b^* \|_F \right) \right\}, \qquad (15)$$

where $C_{\mathbf{x},\sigma}(\omega_a^*) = C_{\mathbf{x},\sigma} \prod_{j\in a} \| \omega^{*(j)} \|_F$. This alternative approach validates the result shown in (11) and aligns with the conclusion that the performance difference between robust and semirobust networks is highly related to their weight differences. In this section we proved two bounds for performance difference defined in (8).

3 EXPERIMENTS AND ANALYSES

To confirm our theoretical findings and experimentally validate Theorems 1-3, we test our method at multiple layer depths, and across multiple common image classification networks trained on CIFAR-10 Krizhevsky et al. (2009), CIFAR-100 Krizhevsky et al. (2009), and Imagenette Howard, Deng et al. (2009) datasets.

3.1 EXPERIMENTAL SETUP

To guide the empirical investigation of our theoretical findings, we consider attack models, MI estimator, and adversarial training as follows.

Attack Models: The most common threat model used when generating adversarial examples is the additive threat model. Let $\mathbf{X} = (X_1, \ldots, X_d)$, where each $X_i \in \mathcal{X}$ is a feature of $\mathbf{X}$. In an additive threat model, we assume adversarial example $\mathbf{X}_\delta = (X_1 + \delta_1, \ldots, X_d + \delta_d)$, i.e., $\mathbf{X}_\delta = \mathbf{X} \oplus \delta$, where $\delta = (\delta_1, \ldots, \delta_d)$. Under this attack model, perceptual similarity is usually enforced by a bound on the norm of δ, $\|\delta\| \leq \epsilon$. Commonly used norms include $\|.\|_2$, Euclidean distance. Note that a small ϵ is usually necessary because otherwise, the noise on the input could be visible.

For our experiments, we use some of the most common additive attack models, namely, the Fast Gradient Sign Method (FGSM) Goodfellow et al. (2014); Szegedy et al. (2014), the iterative FGSM (I-FGSM) Kurakin et al. (2017), Progressive Gradient Descent (PGD) Madry et al. (2018), and Carlini & Wagner (CW) Carlini & Wagner (2017).

MI Estimation: We use a reduced-complexity MI estimator called the ensemble dependency graph estimator (EDGE) Noshad et al. (2019). The estimator combines randomized locality-sensitive hashing (LSH), dependency graphs, and ensemble bias-reduction methods. We chose EDGE because it has been shown that it achieves optimal computational complexity $O(n)$, where n is the sample size. It is thus significantly faster than its plug-in competitors Kraskov et al. (2004); Moon et al. (2017); Noshad et al. (2017). In addition to fast execution, EDGE has an optimal parametric MSE rate of $O(1/N)$ under a specific condition.

Adversarial Training: Adversarial training is an approach to making models more robust to adversarial attacks by producing adversarial examples and inserting them into the training data. Given adversarial examples in the original input, we focus on the min-max formulation of adversarial training that uses standard training on a classifier by minimizing a loss function that decreases with the correlation between the weighted combination of the features and the label Goodfellow et al. (2015); Madry et al. (2018), $\min_\theta {}_{(x,y)\sim D} \left[\max_\delta \mathcal{L}_\theta(\mathbf{x} + \delta, y) \right]$.

3.2 LEARNING HYPERPARAMETER ρ

A key point in the claim of Theorem 2 is to determine the hyperparameter ρ_{a+1} that bound the dependency between last layer in subnetwork $f_a := F^{(a)}$ and first layer in subnetwork $f_b := F^{(a+1,n)}$ and hyperparameters $\rho_{a+2}, \ldots, \rho_n$ that bound dependencies between consecutive layers in f_b. Within the experimental results we denote these values as $\rho_1, \ldots, \rho_{n-a}$, where ρ_1 corresponds to the last pair of layers in f_b. To determine these ρ-values, we have devised a novel adversarial training algorithm based on our framework that learns hyperparameters and shows that subnetwork robustness guarantees network robustness.

Table 1: Subnetwork training on CIFAR-10 with differing attacks

Attack	Model	Acc^*	$\widetilde{Acc}$	Diff.	ρ_n
FGSM	AlexNet	71.71	71.46	0.25	2.26
	VGG16	88.69	87.74	0.96	3.39
	Resnet50	86.43	85.10	1.33	2.98
I-FGSM	AlexNet	71.80	71.39	0.41	2.25
	VGG16	89.53	88.24	1.28	3.56
	Resnet50	86.45	85.18	1.27	3.18
PGD	AlexNet	71.53	71.43	0.09	2.22
	VGG16	89.49	89.32	0.17	3.45
	Resnet50	86.52	85.42	1.1	3.29
C&W	AlexNet	67.27	67.13	0.14	2.21
	VGG16	81.92	81.53	0.39	3.11
	Resnet50	67.27	67.13	0.14	2.21

Algorithm 1 Learning Hyperparameter ρ

Do regular and adversarial training of $F^{(n)}$ as (f_a, f_b) and (f_a^*, f_b^*) respectively
Store test accuracy of adversarial training (f_a^*, f_b^*) as Acc^*
Set ϵ to be as small as possible
Initialize $\rho_{a+1}, \ldots, \rho_n = \infty, \ldots, \infty$
for $t = 1, \ldots, T$ **do**
    Load f_b; freeze f_a^*
    for $e = 1, \ldots, E$ **do**
        Do one epoch of adversarial training of f_b to get $\widetilde{f_b}$
        Store test accuracy of $(f_a^*, \widetilde{f_b})$ as Acc_t^e
        if $Acc^* - Acc_t^e \le \epsilon$ **then**
            Break out of epoch loop and store Acc_t^e
        end
    end
    for $j = a + 1, \ldots, n$ **do**
        Compute $I_{j,t}$ as given in (5) for all consecutive layers in $(f_a^*, \widetilde{f_b})$, then store $I_{j,t}$
    end
end
$\widetilde{Acc}$= largest Acc_t^e
ρ_j = smallest $I_{j,t}$ for $j = a + 1, \ldots, n$
Report $\rho_{a+1}, \ldots, \rho_n$ and $\widetilde{Acc}$

This procedure, labeled Algorithm 1, assumes that the mutual dependency between the two parts of a network $F^{(n)}$ is based on their MI measure. To retrieve baseline results, this method first performs standard ("regular") training of the whole network with the original dataset, and then the same training is done with adversarial examples of that set. The network's two halves are denoted f_a and f_b if regularly trained, and f_a^* and f_b^* if adversarially trained. In the next stage, the algorithm runs T trials, each of which does adversarial training on f_b for E epochs while f_a^* is frozen. The second part of $F^{(n)}$ after being trained for an epoch is labeled $\widetilde{f_b}$. Ideally, the current training accuracy of the network Acc_t^e should approach Acc^* within a small ϵ, at which point the training in the current trial ends. Next, the class conditional MI, $I_{j,t} := \sum_y \pi(y) I(f^{(j-1)}; f^{(j)}|y)$, between each pair of consecutive layers from $f^{(a)}$ to $f^{(n)}$, is calculated. As the trials progress the largest testing accuracy achieved ($\widetilde{Acc}$) is updated, along with the corresponding trials' $I_{j,t}$ values (ρ_{a+1} to ρ_n). After adversarial training ends, these results are reported for the trial which achieves the highest adversarial testing accuracy $\widetilde{Acc}$.

3.3 Piece-wise Adversarial Robustness Guaranteed

The results for our experiments support our claims in Theorem 2. The tests span AlexNet, VGG16, and ResNet50 architectures on CIFAR-10, CIFAR-100, and Imagenette datasets. As the network always undergoes the same procedure for standard training, the regular test accuracies are the same for all f_b sizes. If Theorem 2 is correct, then despite f_a^* being frozen when training f_b, the network should still be robust to adversarial examples due to the mutual dependencies within it. We see in Table 1 that the f_b network training frequently approaches within 1% of Acc^*.

Figure 1: Connectivity values vs performance differences are plotted for differing attack types and architectures on CIFAR-10.

Figure 2: Connectivity values vs performance differences are plotted for differing architectures on each dataset with the C&W attack.

Guarantees for Multiple Layers Robustness: As shown in Figs.1 and 2, starting from $f_{(a+1)}$, each subsequent layer of f_b tends to show lower connectivity values, seemingly regardless of the actual number of layers in f_b. A notable exception for this is when training f_b fails to converge, sometimes resulting in ρ values close to 0 in the early layers of f_b. In the SM we additionally show that for VGG16, as the depth of f_b is increased, up to 9 trainable layers, these trends remains largely the same.

Effects of Dataset, Network, and Attack Type on ρ: In order to investigate the effects of dataset, network type, and attack type on the observed ρ values, we ran a series of experiments for Algorithm 1 with certain hyperparameters held constant. From these experiments we report trends between each variable and the observed ρ values. We see in Fig.1 that attack type has little discernible impact on the ρ values observed for each layer. When changing network architectures however, Resnet50 has consistently higher ρ values than VGG16, which has higher values than AlexNet for each given layer (seen in Fig. 2).

Relationship between Mutual Information and Model Robustness: We don't see a clear pattern between the amount of improvement in accuracy between $\widetilde{Acc}$ and Acc^* and the values of ρ when the accuracies are within $1 - 2\%$ of one another. Additionally, in the Supplementary Material we show that when the network fails to converge after freezing f_a^*, the earlier layers in f_b have values of ρ close to 0.

4 RELATED WORK

An important paper that studies adversarial robustness from a theoretical perspective is by Ilyas et al. (2019), who claim that adversarial examples are "features" rather than bugs. The authors state that a network's being vulnerable to adversarial attacks "is a direct result of [its] sensitivity to well-generalizing features in the data". Specifically, deep neural networks are learning what

they call "useful, non-robust features": useful because they help a network improve its accuracy, and non-robust because they are imperceptible to humans and thus not intended to be used for classification. Consequently, a model considers robust features to be about as important as non-robust ones, yet adversarial examples encourage it to rely on only non-robust features. Ilyas et al. (2019) introduces a framework to explain the phenomenon of adversarial vulnerability. Rather than focusing on which features the model is learning, our method's focus is on proving a probabilistic close-form solution to determine the minimal subnetwork which needs to be adversarially trained in order to confer full-network adversarial robustness.

When it comes to empirical methods for adversarial training, numerous approaches have been proposed to improve the robustness of DNNs to adversarial attacks. These approaches span a variety of methods, as well as differing objectives. Typically such methods focus on maximizing robustness or improving runtime. One commonality between methods however is the need to perform adversarial training over the entire network. As such, the theory detailed here is expected to enable such methods to consider the adversarial training of only a portion of the network without loss of the resulting robustness. Due to the fact that our method makes no assumptions about how the subnetwork is adversarially trained, it is expected to serve as an orthogonal approach to existing adversarial training methods. Different classes of such methods may alter the data with respect to the state of the network or directly target the network itself Goodfellow et al. (2014); Szegedy et al. (2014). In both cases our method is expected to allow them to consider only a partial subnetwork when adversarially attacking the data or network during adversarial training. The Mutual Information metric which we implement to detail the nonlinear relationship between subsequent layers in the network has been used to represent similar relationships in other works, demonstrating its effectiveness Laarne et al. (2021); Laarne et al. (2022).

5 CONCLUSION

Discussion We observe in our experiments that changes in the network type and dataset type impact the values of ρ. Resnet50 consistently reported the highest ρ values for each given layer in Figs.2, while AlexNet reported the lowest. This may indicate that deeper networks provide a better flow of information, seemingly reflecting their ability to replicate increasingly complex non-linear functions. For Imagenette, however, Resnet50 failed to converge to Acc^* in any of the trials, with a resulting performance difference of 13% (not shown). As such, it isn't shown in the corresponding subfigure. It's interesting that a complex model such as ResNet50 fails to converge, while the simpler AlexNet model and our linear combination experiments can manage to take advantage of subnetwork robustness. In such cases, we see that even shallow networks and those constrained to linear relationships between f_a^* and f_b are capable of benefiting from adversarial subnetwork training. We report no clear trends between ρ and any of the attack types used here. This, coupled with the frequent matching of performance when compared to Acc^*, indicates that our method is largely orthogonal to each attack type, resulting in comparable performance while relying on the robustness of only the first subnetwork. In addition to the orthogonal benefits we display with different additive attack models, we suggest that benefits in performance and runtime would also be observed when subnetwork training is applied for attacks that directly target the weights in the network. In such attacks, only f_a should need to be targeted, so long as it remains sufficiently connected to f_b. When generating attacks on the dataset, the time needed to generate the attacks may possibly be reduced by only considering layers into f_a. In both cases, the application of the theory outlined here would help improve runtime complexity, and potentially improve robustness as shown experimentally in this work.

Looking ahead One open question here is that how we can determine the complexity of the semirobust subnetwork performance in terms of convergence rate. The answer to this question involves investigating a bound on performance difference as a function of dependency between layers (ρ). In addition, although the trend observed between ρ and dataset is consistent and clear, it's less apparent the reason. The narrower range of ρ values in CIFAR-100 is most likely due either to the larger number of classes (100 vs 10) or the lower resulting predictive accuracy (which is at least in part due to the larger number of classes). Imagenette on the other hand has the same number of classes as CIFAR-10, but significantly larger images (224x224 vs 32x32), and fewer samples. Further investigation of this relationship remains an interesting future avenue of investigation.

REFERENCES

Naveed Akhtar and Ajmal Mian. Threat of adversarial attacks on deep learning in computer vision: A survey. Ieee Access, 6:14410–14430, 2018.

Anish Athalye, Logan Engstrom, Andrew Ilyas, and Kevin Kwok. Synthesizing robust adversarial examples. In International conference on machine learning, pp. 284–293. PMLR, 2018.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In Joint European conference on machine learning and knowledge discovery in databases, pp. 387–402. Springer, 2013.

Tom B Brown, Dandelion Mané, Aurko Roy, Martín Abadi, and Justin Gilmer. Adversarial patch. arXiv preprint arXiv:1712.09665, 2017.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In 2017 ieee symposium on security and privacy (sp), pp. 39–57. IEEE, 2017.

Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In International Conference on Machine Learning, pp. 1310–1320. PMLR, 2019.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In 2009 IEEE conference on computer vision and pattern recognition, pp. 248–255. Ieee, 2009.

Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 1625–1634, 2018.

Alhussein Fawzi, Seyed-Mohsen Moosavi-Dezfooli, and Pascal Frossard. Robustness of classifiers: from adversarial to random noise. arXiv preprint arXiv:1608.08967, 2016.

Justin Gilmer, Nicolas Ford, Nicholas Carlini, and Ekin Cubuk. Adversarial examples are a natural consequence of test error in noise. In International Conference on Machine Learning, pp. 2280–2289. PMLR, 2019.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In International Conference on Learning Representations, 2015. URL http://arxiv.org/abs/1412.6572.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. Deep learning. MIT press, 2016.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. arXiv preprint arXiv:1412.6572, 2014.

Jeremy Howard. Imagenette. URL https://github.com/fastai/imagenette/.

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. In Proceedings of the 33rd International Conference on Neural Information Processing Systems, pp. 125–136, 2019.

Alexander Kraskov, Harald Stögbauer, and Peter Grassberger. Estimating mutual information. Physical review E, 69(6):066138, 2004.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Alexey Kurakin, Ian J. Goodfellow, and Samy Bengio. Adversarial examples in the physical world. In 5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Workshop Track Proceedings. OpenReview.net, 2017. URL https://openreview.net/forum?id=HJGU3Rodl.

Petri Laarne, Martha A Zaidan, and Tuomo Nieminen. Ennemi: non-linear correlation detection with mutual information. SoftwareX, 14:100686, 2021.

Petri Laarne, Emil Amnell, Martha Arbayani Zaidan, Santtu Mikkonen, and Tuomo Nieminen. Exploring non-linear dependencies in atmospheric data with mutual information. Atmosphere, 13 (7):1046, 2022.

Cassidy Laidlaw and Soheil Feizi. Functional adversarial attacks. arXiv preprint arXiv:1906.00001, 2019.

Jaeho Lee, Sejun Park, Sangwoo Mo, Sungsoo Ahn, and Jinwoo Shin. Layer-adaptive sparsity for the magnitude-based pruning. In ICLR, 2021.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. arXiv preprint arXiv:1611.02770, 2016.

Xingjun Ma, Bo Li, Yisen Wang, Sarah M Erfani, Sudanthi Wijewickrema, Grant Schoenebeck, Dawn Song, Michael E Houle, and James Bailey. Characterizing adversarial subspaces using local intrinsic dimensionality. In International Conference on Learning Representations, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In International Conference on Learning Representations, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. nature, 518(7540):529–533, 2015.

Kevin R Moon, Kumar Sricharan, and Alfred O Hero. Ensemble estimation of mutual information. In 2017 IEEE International Symposium on Information Theory (ISIT), pp. 3030–3034. IEEE, 2017.

Morteza Noshad, Kevin R Moon, Salimeh Yasaei Sekeh, and Alfred O Hero. Direct estimation of information divergence using nearest neighbor ratios. In 2017 IEEE International Symposium on Information Theory (ISIT), pp. 903–907. IEEE, 2017.

Morteza Noshad, Yu Zeng, and Alfred O Hero. Scalable mutual information estimation using dependence graphs. In ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 2962–2966. IEEE, 2019.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In 2016 IEEE European symposium on security and privacy (EuroS&P), pp. 372–387. IEEE, 2016a.

Nicolas Papernot, Patrick McDaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. In 2016 IEEE symposium on security and privacy (SP), pp. 582–597. IEEE, 2016b.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. arXiv preprint arXiv:1511.06434, 2015.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. In International Conference on Learning Representations, 2018.

Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data. arXiv preprint arXiv:1804.11285, 2018.

Adi Shamir, Itay Safran, Eyal Ronen, and Orr Dunkelman. A simple explanation for the existence of adversarial examples with small hamming distance. arXiv preprint arXiv:1901.10861, 2019.

Mahmood Sharif, Sruti Bhagavatula, Lujo Bauer, and Michael K Reiter. Accessorize to a crime: Real and stealthy attacks on state-of-the-art face recognition. In Proceedings of the 2016 acm sigsac conference on computer and communications security, pp. 1528–1540, 2016.

Jiawei Su, Danilo Vasconcellos Vargas, and Kouichi Sakurai. One pixel attack for fooling deep neural networks. IEEE Transactions on Evolutionary Computation, 23(5):828–841, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In 2nd International Conference on Learning Representations, ICLR 2014, 2014.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. In International Conference on Learning Representations, 2019.

Tsui-Wei Weng, Huan Zhang, Pin-Yu Chen, Jinfeng Yi, Dong Su, Yupeng Gao, Cho-Jui Hsieh, and Luca Daniel. Evaluating the robustness of neural networks: An extreme value theory approach. arXiv preprint arXiv:1801.10578, 2018.

Kai Y Xiao, Vincent Tjeng, Nur Muhammad Shafiullah, and Aleksander Madry. Training for faster adversarial robustness verification via inducing relu stability. In International Conference on Learning Representations, 2019.

Cihang Xie, Jianyu Wang, Zhishuai Zhang, Yuyin Zhou, Lingxi Xie, and Alan Yuille. Adversarial examples for semantic segmentation and object detection. In Proceedings of the IEEE International Conference on Computer Vision, pp. 1369–1378, 2017.

Dinghuai Zhang, Tianyuan Zhang, Yiping Lu, Zhanxing Zhu, and Bin Dong. You only propagate once: Accelerating adversarial training via maximal principle. Advances in Neural Information Processing Systems, 32, 2019.