No RL, No Simulation: Learning to Navigate without Navigating

Abstract

Most prior methods for learning navigation policies require access to simulation environments as they need online policy interaction and rely on ground-truth maps for rewards. However, building simulators is expensive (requires lot of manual effort for each and every scene) and adds a challenge in transferring these policies to robot platforms in the real-world due to the sim-to-real domain gap. In this paper, we ask a simple question: do we really need active interaction, ground-truth maps or even reinforcement-learning (RL) to solve the image-goal navigation task? We propose a self-supervised approach to learn to navigate from only passive videos of roaming. Our approach, No RL, No Simulator (NRNS), is simple and scalable (no simulator required for training) yet highly effective. NRNS outperforms RL-based formulations by a significant margin. We present NRNS as a strong baseline for any future image-based navigation tasks that use RL or Simulation.

1 Introduction

In recent years, we have made significant advances in learning-based approaches for indoor navigation [1, 2]. We have seen impressive performance gains on variety of tasks from non-semantic point-goal navigation [3] to semantic tasks such as image-goal [4] and object-goal navigation [5, 6] via methods that use reinforcement learning (RL). A common belief in the learning community is that these gains can be attributed to emergence of new simulators such as Habitat [7], Matterport [8] and AI2Thor [9]. These simulators have helped scale learning to billions of frames by providing: (a) large-scale active interaction data; (b) ground-truth maps for designing reward functions. But do we actually need simulation and RL to learn to navigate? Is there an alternative way to formulate the navigation problem such that no ground-truth maps or active interaction is required? Learning navigation in simulation constrains the learning potential to the limited set of environments available since adding new environments is wildly expensive and time consuming.

In this paper, we propose a self-supervised way to learn how to navigate from passive egocentric videos. Our self-supervised approach is simple, scalable (no simulator required for training) yet highly effective as it also outperforms RL-based formulations by a significant margin. To understand the basis of our approach, let us first examine what the RL formulation and simulator provide in standard navigation algorithms. In the RL formulation, an agent gets a reward upon reaching the goal followed by credit assignment stage to determine the most useful state-action pairs. But do we actually need the *reinforce* function for action credit assignment? Going a step further, do we even need to learn a policy explicitly? In navigation, we argue that state space is highly structured via distance function and therefore one could use that structure itself for credit assignment. Simply put, states that help reduce the distance to goal/destinations are better – and therefore, one could use distance as the value function or a proxy to it. In fact in RL formulations, 'distance reduced to goal' is often used in reward shaping. The key difference we present, is that learning a distance estimator can be done via passive videos and does not require any interaction. We show that the

Figure 1: **Left**: Using passive videos we learn to predict distances for navigation. Our distance function learns the priors of the layouts of indoor buildings to estimate distances to goal location. **Right**: Image-Goal Navigation Task [10]. Our model uses distance function to predict distances of unexplored nodes and uses greedy policy to choose shortest-distance node.

distance estimator can be learned directly from visual trajectories without an RL policy to map visual observations to the action space, which would require extensive interaction in a simulator and use hand designed rewards. However passive videos do not provide learning opportunities for obstacle avoidance since they rarely, if ever, consist of cameras bumping into walls. We forego the need for active interaction to reason about collisions as we show that that failed trajectories/obstacle avoidance are only required locally and simple depth maps are sufficient to prune invalid actions/location for navigation. More broadly, our approach can be considered as closely related to model-based control, which is an alternate paradigm to RL based policy learning, with the key insight that components of the model and cost functions can be learned from passive data.

No RL, No Simulator Approach (NRNS): Our NRNS algorithm can be described as follows. During training we learn two functions from passive videos: (a) a geodesic distance estimator: given the state features and goal image, this function predicts the geodesic distance of the unexplored frontiers of the graph to the goal location. We then use the greedy policy where we select the node with least distance; (b) a target prediction model: Given the goal image and the image from the agent's current location, this function predicts the if the goal is within sight and can be reached without collisions and the function predicts the exact location of the goal. The key is both distance model and the target prediction model can be learned from passive RGBD videos with SLAM to estimate relative poses. We believe our simple NRNS approach should act as a strong baseline for any future approaches that use RL and Simulation.

2   Related Work

Navigation in simulators. Navigating tasks largely fall into two main categories [1], ones in which a goal location is known [11, 12, 13] and limited exploration is required and ones which the goal location is not known and efficient exploration is necessary. In the second category, tasks range from finding the location of specific objects [5], rooms [14], or images [15] to the task of exploration itself [2]. The majority of current work [12, 15, 16, 3] leverages simulators [7] and extensive interaction to learn end-to-end models models for these tasks. Our work shows that semantic cues needed for exploration based navigation tasks can be learned simply from viewing video trajectories.

Navigation using passive data. Several prior works have tackled the navigation tasks when there is some passive experience available in the test environment [17, 18, 19, 20, 21, 22]. A more limited number of works train navigation policies without simulation environments [19, 22]. Unlike these works, we tackle the task of image goal navigation in unseen environments where there is no experience available to the agent in the test environments during training.

Chaplot et al. [4] and Chang et al. [23] learn navigation from passive data without having access to any experience in the test environment. Our work is closely related to Neural Topological SLAM (NTS) [4] which builds a topological map and estimates distance to the target image using a learned function. Unlike our method, NTS requires access to panoramic observations and ground-truth maps for training the distance function. This makes our method much more scalable as it can be trained with just video data with arbitrary field of view. Chang et al. [23] also use a similar approach for object goal navigation, while also incorporating video data from Youtube for learning a Q function. A key difference is that our method learns a episodic distance function, utilizing all past observations to estimate distances to the target image. In comparison, Chaplot et al. [4] and Chang et al. [23] use a memory-less distance function operating only on the agent's current observation.

Map Based Navigation. There are multiple spatial representations which can be leveraged in navigation tasks. Metric maps, which maintain precise information of occupied space in an environment, are commonly used for visual navigation tasks [2, 10, 6]. Metric maps, however, suffer from issues of scalability and consistency under sensor noise. Topological maps however have recently gained more traction as navigational maps [4, 21, 18, 23] to combat these issues. Additionally, topological maps for robotic navigation draw inspiration from both animal and human psychology. The cognitive map hypothesis proposes that the brain builds coarse internal spatial representations of environments [24, 25]. Multiple works argue this internal representation relies on landmarks [26, 27] making human cognitive maps more similar to the topological maps as opposed to rigid metric maps.

Graph Neural Networks. Graph Neural Networks (GNN) are specifically used for modeling relational data in the non-euclidean space. The GCN we present for estimating distance-to-goal uses a spatial approach, which defines the convolutions based on the graph topology and local neighborhood. Specifically we employ an augmented Graph Attention Network [28] which allows for a weighted aggregation of neighboring node information. Graph Networks have been rarely utilized in the case of topological map based visual navigation. Savinov et al. [18] use a GNN for the sub-task of localizing the agent in a ground truth topological map. To our knowledge we are the first work to leverage graph networks to model navigation in a visual navigation task.

3 Image Goal Navigation using Topological Graphs

We propose No RL, No Simulator "NRNS", a hierarchical modular approach to image-goal navigation that comprises of: a) high-level modules for maintaining a topological map and using visual and semantic reasoning to predict sub-goals, and b) heuristic low-level modules that use depth data to select low level navigation actions to reach sub-goals and determine geometrically explorable area. We first describe NRNS in detail and later show in Sec. 4 that the high-level modules can be trained without using any simulation, interaction or even ground-truth scans – that only passive video data is sufficient to learn the semantic and visual reasoning used in navigation.

3.1 Formulation and Representation

Task Definition. We tackle the task of image-goal navigation, where an agent is placed in a novel environment, and is tasked with navigating to an (unknown) goal position that is specified using an image taken from that position, shown in Fig. 2. More formally, an episode begins with an agent receiving an RGB observation (I_G) corresponding to the goal position. At each time step, t, of the episode the agent receives a set of observations s_t, and must take a navigation action a_t. The agents state observations, s_t, are defined as a narrow field of view RGBD, I_t, and egocentric pose estimate, P_t. The agent must use a policy $\pi(a_t|s_t, I_G)$ to navigate to the goal before reaching a maximum number of actions.

Topological Map Representation. The NRNS agent maintains a topological map $(G(N, E))$ where a graph, defined by the nodes N and edges E, provides a sparse representation of the environment. Concretely, a node $n_i \in N$ is associated with a pose p_i, defined by location and orientation. Each node n_i can either be 'explored' *i.e.* the agent has previously visited the pose and obtained a corresponding RGBD image I_i, or 'unexplored' *e.g.* unvisited positions at the exploration frontier which may be visited in the future. Each edge $e \in E$ connects a pair of adjacent nodes n_i and n_j. Nodes are deemed adjacent only if a short and 'simple' path exists between the two nodes, as further detailed in Sec. 3.3. Each edge between adjacent nodes is then associated with the attribute ΔP – the relative pose between the two nodes.

Figure 2: Image-Goal navigation task using a topological graph.

3.2 Global Policy via Distance Prediction

Given a representation of the environment as a topological graph, our global policy is tasked with identifying the next 'unexplored' node that the agent should visit, and the low-level policy is then responsible for executing the precise actions. Intuitively, we want our agent to select the next node as the one that minimizes the total distance to goal. The global policy's inference can thus be reduced to predicting distances from nodes in our graph to the goal location. To this end, our approach leverages

Figure 3: The Global Policy and $\mathcal{G}_D$ architecture used to model distance-to-goal prediction. $\mathcal{G}_D$ employs a Resnet18 encoder, Graph Attention layers and multi-layer perception with sigmoid.

135   a distance prediction network ($\mathcal{G}_D$) which operates on top of the $G(N, E)$ to predict distance-to-goal
136   for each unexplored node $n_{ue} \in G$. Our global policy then simply selects the node with least total
137   distance to goal which is defined as: distance to unexplored node from the agent's current position,
138   plus the predicted distance from unexplored node to the goal.

139   The input to the distance prediction network $\mathcal{G}_D$ is the current topological graph $G(N, E)_c$ and I_G.
140   While the explored nodes have an image associated with them, the unexplored nodes naturally do not.
141   To allow prediction in this setup, we use a Graph Convolutional Network (GCN) based architecture
142   to first induce visual features for $n_{ue} \in G$, and then predict the distance to goal using an MLP.

143   As illustrated in Fig. 3, the network first encodes the RGB images at each explored node (n_i) using
144   a ResNet18 [29] to obtain feature vector $\mathbf{h_i} \in \mathbb{R}^{512}$. Each edge $e_{i,j}$ is further represented by a
145   feature vector $\mathbf{u_{i,j}}$, which is the flattened pose transformation matrix ($^{\mathbf{i}}\mathbf{K_j} \in \mathbb{R}^{4 \times 4}$). The adjacency
146   matrix $\mathbf{A_t}$, $\mathbf{u_{i,j}}$, and $\mathbf{h_i}$ are passed through a GCN comprising of two graph attention (GAT) layers
147   [28] with intermediate non-linearities. Note that we extend the graph attention layer architecture
148   to additionally use edge features $\mathbf{u_{i,j}}$ when computing attention coefficients. The predicted visual
149   features for unexplored nodes are then finally used to compute predicted distance-to-goal d_i from
150   each node to I_G using a simple MLP.

151   To select the most 'promising' n_{ue} to explore, the distance from the agent's current location n_t also
152   needs to be accounted for. For $n_{ue}, n_t \in G$, the 'travel cost' is added to d_i, calculated using shortest
153   path on G from $n_{ue} \to n_t$. Our global policy then selects the unexplored node with the minimum
154   total distance score as the next sub-goal.

3.3   Local Navigation and Graph Expansion

156   The NRNS global policy selects the sub-goal that the agent should pursue, and the precise low-level
157   actions to reach the sub-goal are executed by a heuristic local policy. After the local policy finishes
158   execution, the NRNS agent updates the graph to include the new observations and expands the graph
159   with unexplored nodes at the exploration frontier.

160   **Local Policy.** The NRNS local policy, denoted as $\mathcal{G}_{LP}$, receives a target position, defined by distance
161   and angle (ρ_i, ϕ_i) with respect to the agent's current location. When $\mathcal{G}_D$ outputs a sub-goal node,
162   ρ_i, ϕ_i are calculated from the current position and passed to $\mathcal{G}_{LP}$. Low level navigation actions
163   are selected and executed using a simplistic point navigation model based on the agents egocentric
164   RGBD observations and (noisy) pose estimation. To navigate towards its sub-goal, the agent builds
165   and maintains a local metric map using the noisy pose estimator and depth input. This effectively
166   allows it to reach local goals and avoid obstacles. The local metric maps are discarded upon reaching
167   the sub-goal, as they are based on a noisy pose estimator. This policy is adapted from [10] and is also
168   used for Image-Goal Navigation in [4].

169   **Explorable Area Prediction for Graph Expansion.** We incorporate a 'graph expansion' step
170   after the agent reaches a sub-goal via $\mathcal{G}_{LP}$ and before the agent selects a new sub-goal. First, the
171   agent updates $G(N, E)$ to record the current location as an explored node and store the associated
172   RGBD observation. Second, the agent creates additional 'unexplored' nodes, n_{ue}, adjacent to the
173   current node, n_t based on whether the corresponding directions are deemed 'explorable'. We use a
174   explorable area prediction module, $\mathcal{G}_{EA}$, to determine which adjacent areas to the current location are
175   geometrically explorable. This is untrained, heuristic function takes the egocentric depth image $I_{t_{depth}}$
176   and tests 9 angles in the direction θ from the current position and returns the angles θ that are not
177   blocked by obstacles within a depth of 3 meters. The NRNS agent tests θ at [0,$\pm$15,$\pm$30,$\pm$45,$\pm$60],
178   these angles are chosen based on the agent's turn radius of 15°and 120°FOV. For all θ determined to

Graph Map G(N,E)ₜ

Goal RGB I_G

Global Policy $\mathcal{G}_D$

Subgoal ni, (ρ, ϕ)

Local Nav Policy $\mathcal{G}_{LP}$

Nav Action a

Graph Update $\mathcal{G}_{EA}$

I_t

Current Depth

Current RGB

Graph Map G(N,E)ₜ₊₁

Figure 4: The hierarchical modular NRNS approach to the Image-Goal Navigation task. Describes a single time step in the episode. The global policy $\mathcal{G}_D$ selects an unexplored node n_i as a sub-goal. The sub-goal position (ρ_i, ϕ_i) is passed to the local navigation policy $\mathcal{G}_{LP}$ which takes in the current RGBD observations and outputs low level actions until the agent reaches n_i. The graph is then updated with the current observations I_{t+1} and new unexplored nodes and edges generated by $\mathcal{G}_{EA}$.

be explorable, the agent updates $G(N, E)$ by adding an 'unexplored' node at position $\rho = 1m$ and $\phi = \theta$ relative to the agent in, with the corresponding edge. If a node already exists in one of the explorable areas at a similar position, only an edge is added to $G(N, E)$ and not a new node.

3.4 Putting it Together

Stopping Criterion. The above described modules ($\mathcal{G}_D$, $\mathcal{G}_{LP}$, $\mathcal{G}_{EA}$) allow the NRNS agent to continue intelligently exploring to reach the target image. To allow the agent to finish navigating if it reaches close to the goal, we additionally learn a target prediction network $\mathcal{G}_T$ that serves as a stopping criterion. Given I_G and current image I_t, $\mathcal{G}_T$ is simple MLP that predicts: a) a probability $\eta_s \in [0, 1]$ indicating whether the goal is within sight, and if so, b) the relative position (distance, direction) of the goal ρ_g, ϕ_g.

Algorithm. We outline our navigation algorithm in Fig. 4 and also describe it in detail below. An example result on the image-goal navigation task is show in Fig. 6. Among the modules used, the local policy $\mathcal{G}_{LP}$ and explorable area $\mathcal{G}_{EA}$ modules do not require any learning. As we show in Sec. 4, $\mathcal{G}_D$ and $\mathcal{G}_T$ can both be learned using only passive data.

Algorithm 1: NRNS Image Navigation

```
// initialize graph
n₀ = (P_{t=0}, I_{t=0}); e₀ = (n₀, n₀);
N = (n₀); E = (e₀);
G = (N, E);
// loop until reached goal or max steps
while steps taken < max steps do
    n_{i+1}, ..., n_{i+k} = 𝒢_EA(I_t); // determine valid explorable areas
    N += n_{i+1}, ..., n_{i+k}; E += e_{t,i+1}, ..., e_{t,i+k}; // add unexplored nodes & edges
    n_sg, (ρ_sg, φ_sg) = argmin(𝒢_D(G, I_G) + TravelCost(G, n_t); // select sub-goal
    I_{t+1}, P_{t+1} = 𝒢_LP(ρ_i, φ_i); // navigate to sub-goal
    n_sg = (P_{t+1}, I_{t+1}) // update graph with observations
    η_s, (ρ_g, φ_g) = 𝒢_T(I_{t+1}, I_G); // stopping criterion
    if η_s then
        𝒢_LP(ρ_g, φ_g); // navigate to target
        break;
    end
end
```

---

4 Learning from Passive Data

The high-level policies of NRNS that need to be learned are the Distance Network $\mathcal{G}_D$ and Target Prediction Network $\mathcal{G}_T$. One of key contributions of our work is to show that these functions can be learned from passive data, eliminating the need for active interaction and ground-truth maps which help us to train our algorithm without using RL or any simulation.

Learning Distance Prediction. First, we describe how to learn the function $\mathcal{G}_D$. Given a topological graph (consisting of both explored and unexplored nodes) and goal image as input, $\mathcal{G}_D$ predicts the geodesic distance between all unexplored nodes and goal image. Our training data therefore

Figure 5: Example from the passive video dataset. Frames of a video trajectory $\mathcal{V}_i$ are shown on the left. The stepwise trajectory is then turned into a trajectory graph $G_{\mathcal{V}_i}$ via affinity clustering [30] of node image and pose features. $G_{\mathcal{V}_i}$ is adapted to train the Global Policy $\mathcal{G}_D$ and target direction prediction $\mathcal{G}_E A$. An example of an adapted $G_{\mathcal{V}_i}$ for training is shown on the left.

should be of triplet form: (G, I_G, D_U) where G is topological graph, I_G is goal image, and D_U is ground-truth distance of unexplored nodes (we use L2-Loss on distance function).

We sample training graphs using passive videos in a two-step process. In first step, we convert the whole video to a long topological graph. The graph contains both explored and unexplored nodes. We approximate distance to unexplored nodes using the geodesic distance on the trajectory. In the second step, we uniformly sample sub-graphs and goal locations over each video's topological graph.

Step 1: Video to Topological Graph. In order to train with passive video data, we create a topological graph, $G_{\mathcal{V}_i}$, for every video $\mathcal{V}_i$ in the passive dataset. First, we generate a stepwise trajectory based on odometry information from each frame. We adapt this trajectory to topological graph structure using affinity clustering [30] on the stepwise graph via visual features and odometry information. Visual features are extracted via a Places365 [31] pretrained Resnet18 over each frame. Each cluster is a single node in the topological graph $G_{\mathcal{V}_i}$ and stepwise visual features are average pooled. The topological graphs are then expanded to have unexplored nodes. These are created using $\mathcal{G}_{EA}$ over the RGBD of each node centroid in $G_\mathcal{V}$. Fig. 5 shows an example video and transformation between the stepwise trajectory and the topological graph.

Step 2: Sampling training datapoints. Individual data instances are via uniform sampling without replacement a random node in $G_\mathcal{V}$ as the goal location and a sub-graph of $G_\mathcal{V}$. Trajectory distance is used as the distance label between nodes in the sub-graph and the goal image. It should be noted that the distances are partially noisy due to non-optimal long term paths of the video trajectories, making this a challenging modeling problem. In total $\mathcal{G}_D$ is trained over 75k training instance for Gibson and 148k instances for MP3D. For further details on training please see the Appendix.

Learning Target Direction Prediction We also want to learn $\mathcal{G}_T$ which given goal image and the current node image as input, predicts whether the goal is within sight of current image. We make a simplifying assumption that any two adjacent pair of nodes (similar features and odometry) in the topological graph are positive examples and any other pair of nodes are negative examples.

5 Experiments

Image-Goal Navigation Task Setup. At the beginning of each episode the agent is placed in an unseen environment. The agent receives observations from the current state, a 3 x 1 odometry pose reading and RGBD image, and the RGB goal image. Observation and goal images are 120°FOV and of size 480 x 640. An episode is considered successful if the agent is able to reach the goal location within $1m$ within a maximum episode length of 500 steps. An episode is also evaluated by the efficiency of the navigational path from start to goal, which is quantitatively measured by Success weighted by inverse Path Length (SPL) [1]. Note, the narrow field of the agent in this task definition differs from past works which use panoramic views [4]. The decision to use a narrow field is based on our method of training only on passive data. Current video datasets of indoor trajectories such as YouTube Tours [23], RealEstate10k [32] and our NRNS dataset, do not contain panoramas.

Action Space. The agents action space contains four actions: `forward` by .25m, `rotate left` by 15°, `rotate right` by 15°, and `stop`. In our experiments we consider two cases for agent pose estimation and action transition. In the first condition the agent has access to ground truth pose and navigation actions are deterministic. In the second condition, noise is added to the pose estimation and actuation of the agent. We utilize the realistic pose and actuation noise models from [10] which are similarly used in [4]. The actuation noise adds stochastic rotational and translations transitions to the agents navigational actions.

Training Data. Our key contribution is the ability to learn navigation agents from passive data. In theory, our approach can be trained from any passive data source such as RealEstate10K [32]. However, since RL-based baselines are trained in habitat simulator and we generate our passive video dataset using the same training scenes to provide direct comparison and isolate domain gap issues.

Specifically, we create the training set of egocentric trajectory videos using the Habitat Simulator [7] train environments. A set of 2-4 points are randomly selected from the environment using uniform sampling. A video is then generated of the concatenated RGBD trajectories of the shortest path between consecutive points. Note that the complete video trajectory is not step-wise optimal nor is the end frame of the trajectory. Frames in the videos are of size 480 X 640 and have a FOV 120°and each frame is associate with a 3 x 1 odometry pose reading. In the noisy setting discussed in Sec. 5 sensor and actuation noise is injected into training trajectories. We create 19K, 43K video trajectories containing 1, 2.5 million frames respectively on the Gibson and MP3D datasets.

Test Environments. We evaluate our approach on the task of image-goal navigation. For testing, we use the habitat simulator [7]. We evaluate on the standard test-split for both the Gibson [33] and Matterport3D (MP3D) [34] datasets. For MP3D we evaluate on 18 environments and for Gibson we test on 14 environments.

Baselines. We consider a number of baselines to contextualize our Image-Goal Navigation results:

– **ResNet + GRU + BC.** Behavioral Cloning (BC) policy where I_t and I_G are encoded using a pretrained ResNet-18. Both image encodings and the previous action a_{t-1} are passed through a two layer Gated Recurrent Unit (GRU) with softmax, which outputs the next action a_t.
– **ResNet + Metric Map + BC.** BC policy: I_t and I_G are encoded same as above. Policy keeps a metric map built from the depth images. The metric map is encoded with a linear layer. The metric map encoding and encodings of I_t and I_G are concatenated and passed into an MLP with softmax, which outputs the next navigational action a_t.
– **End to End RL with PPO.** An Image Goal Navigation agent is trained end to end with proximal policy optimization [35] in the Habitat simulator [7] for the image-goal navigation task.

We use and adapt code for baseline algorithms from Chaplot *et al.* [4]. However, as our setup uses narrow-view cameras instead of panoramas, these adapted baselines perform worse compared to their previously reported performance. This difference in setup also makes direct comparison with [4] infeasible as they critically rely on panoramic views for localization. The baseline behavioral cloning policies are also trained only using the passive dataset described in Sec. 4. This makes BC baseline policies directly comparable to the NRNS model. The end to end RL policy is trained with PPO for 20 and 10 million frames for Mp3d and Gibson, respectively.

Episode Settings. To provide in-depth understanding of successes and limitations of our approach, we sub-divide test episodes into two categories: 'straight' and 'curved'. In 'straight' episodes the ratio of shortest path geodesic-distance to euclidean-distance between the start and goal locations is < 1.2 and rotational difference between the orientation of the start position and goal image is $< 45°$. All other start-goal location pairs are labeled as 'curved' episodes. We make this distinction due to the nature of the narrow field of view of our agent which strongly effects performance on curved episodes, since the agent must learn to turn both as part of navigating and part of seeking new information about the target location. Also, while a greedy policy working on 'straight' episodes might be expected, a competitive performance on even 'curved' episodes will highlight how effective our simple model and policy is. We further subdivide each of these 2 categories into 3 difficulty sub-categories: 'easy', 'medium' and 'hard'. Difficulty is determined by length of the shortest path between the start and goal locations. Following [4] the 'easy', 'medium' and 'hard' settings are $(1.5 - 3m)$, $(3 - 5m)$, and $(5 - 10m)$ respectively. To generate test episodes we uniformly sample start-goal location pairs from the test scenes to create approximately 1000 episodes per setting.

5.1 Results

Tables 1, 2 show the performance of our NRNS model and relevant baselines on the test splits of the Gibson and Matterport datasets.

NRNS outperforms baselines. Our NRNS algorithm significantly outperforms the BC and end-to-end RL policys in terms of Success and SPL @ 1m on both datasets – improving the best baseline, ResNet + GRU + BC, across splits of Gibson by an absolute 20+% on Straight episodes and 10+% on Curved episodes. We find that a BC policy using a GRU for memory outperforms using only a metric map. We observe that an End-to-End RL policy trained in simulation performs much weaker than all baselines. The poor performance of target-driven RL methods for image-goal navigation is

unsurprising [4, 15]. This demonstrates the difficulty of learning rewards on low level actions instead of value learning on possible exploration directions as NRNS does, exacerbating the difficulty of exploration in image-goal navigation. Adding to the challenges of the task, all policies must learn the stop action. Previous works [4] have found that adding oracle stopping to a target-driven RL agent leads to large gains in performance on image-goal navigation. Limitations all approaches are seen on the 'hard' and 'curved' episode settings, showing the overall difficulty of the exploration problem and challenge of using a narrow field of view.

NRNS is robust to noise. NRNS maintains superior performance to all baselines, with the injection of sensor and actuation noise from [10] models in both the passive training data and test episodes. In fact, we find that the addition of noise leads to only an absolute drop in Success between .8-8% on Gibson [33] and 1-5% on MP3D [34]. An interesting aspect is small increase in performance (w/noise) for the hard-case. We believe this is because gt-distance for hard cases are more error prone and noise during training provides regularization.

Table 1: Comparison of our model (NRNS) with baselines on Image-Goal Navigation on **Gibson**[33]. We report average Success and Success weighted by inverse Path Length (SPL) @ $1m$. Noise refers to injection of sensor & actuation noise into the train videos and test episodes. [*] denotes using simulator.

Path Type	Model	Easy		Medium		Hard	
		Succ ↑	SPL ↑	Succ ↑	SPL ↑	Succ ↑	SPL ↑
Straight	PPO End-to-End RL[*] [35]	3.60	2.73	5.80	5.01	3.47	3.28
	ResNet + Metric Map + BC	24.80	23.94	11.50	11.28	1.36	1.26
	ResNet + GRU + BC	34.90	33.43	17.60	17.05	6.08	5.93
	NRNS w/ noise	64.10	55.43	47.90	39.54	25.19	18.09
	NRNS w/out noise	68.00	61.62	49.10	44.56	23.82	18.28
Curved	PPO End-to-End RL[*] [35]	4.50	2.93	4.40	3.81	1.50	1.43
	ResNet + Metric Map + BC	3.10	2.53	0.80	0.71	0.20	0.16
	ResNet + GRU + BC	3.60	2.86	1.10	0.91	0.50	0.36
	NRNS w/ noise	27.30	10.55	23.10	10.35	10.50	5.61
	NRNS w/out noise	35.50	18.38	23.90	12.08	12.50	6.84

Table 2: Comparison of our model (NRNS) with baselines on Image-Goal Navigation on **MP3D**[34].

Path Type	Model	Easy		Medium		Hard	
		Succ ↑	SPL ↑	Succ ↑	SPL ↑	Succ ↑	SPL ↑
Straight	PPO End-to-End RL[*] [35]	7.50	4.00	3.50	1.73	1.00	0.55
	Metric Map + MLP + BC	25.80	24.82	11.30	10.65	3.00	2.93
	GRU + MLP + BC	30.20	29.57	12.70	12.48	4.40	4.34
	NRNS w/ noise	63.80	53.12	36.20	26.92	24.10	16.93
	NRNS w/out noise	64.70	58.23	39.70	32.74	22.30	17.33
Curved	PPO End-to-End RL[*] [35]	4.90	1.78	3.20	1.37	1.10	0.46
	Metric Map + MLP + BC	4.90	4.23	1.40	1.29	0.40	0.34
	GRU + MLP + BC	3.10	2.61	0.80	0.77	0.10	0.02
	NRNS w/ noise	21.40	8.19	15.40	6.83	10.0	4.86
	NRNS w/out noise	23.70	12.68	16.20	8.34	9.10	5.14

NRNS Module Ablations. Tab. 3 reports detailed ablations of NRNS on the Gibson dataset (see appendix for ablation results on MP3D). We ablate the NRNS approach by testing each module individually. In the ablation experiments, we replace the module output with the ground truth labels or numbers in order to evaluate the affect of each module on the performance of the overall approach. For simplicity, all ablations are trained and tested without sensor or actuation noise. Unsurprisingly we find that the Global Policy, $\mathcal{G}_D$, has a large affect on performance (Row 4 and 8). We find that the largest affects are seen in the Hard and Curved test episodes. This is expected because as the distance to the goal increases and the path increases in complexity the search space of $\mathcal{G}_D$ also increases.

5.2 Training on Passive Videos in Wild

Finally, we demonstrate that our model can be learned from passive videos in the wild. Towards this end, we train our NRNS model using the RealEstate10K dataset [32] which is built from YouTube videos. This dataset has 80K clips with poses estimated via SLAM. Note that the average trajectory

Table 3: Ablations of NRNS with baselines on Image-Goal Navigation on **Gibson** [33]. We report average Success and Success weighted by inverse Path Length (SPL) @ $1m$. ✗ denotes a module being replaced by the ground truth labels and a ✓ denotes the NRNS module being used.

Path Type	$\mathcal{G}_{EA}$	$\mathcal{G}_T$	$\mathcal{G}_D$	Easy Succ ↑	Easy SPL ↑	Medium Succ ↑	Medium SPL ↑	Hard Succ ↑	Hard SPL ↑
Straight	✗	✗	✗	100.00	99.75	100.00	99.62	100.00	99.57
	✓	✗	✗	99.90	99.05	98.20	95.06	95.91	90.53
	✓	✓	✗	79.40	73.48	71.30	67.48	62.16	58.06
	✓	✓	✓	68.00	61.62	49.10	44.56	23.45	18.84
Curved	✗	✗	✗	100.00	97.62	100.00	97.47	100.00	98.18
	✓	✗	✗	99.70	95.93	97.50	90.14	89.30	79.95
	✓	✓	✗	65.00	56.70	58.10	52.51	47.70	42.28
	✓	✓	✓	35.50	18.38	23.90	12.08	12.50	6.84

Figure 6: Example of an Image-Goal Navigation episode on MP3D. Shows the agent's observations and internal topological graph at different time steps.

length is smaller than test time trajectories in Gibson or MP3D, and we therefore only evaluate on Easy and Medium (3m-5m) settings. Tab. 4 shows the performance. Few things to note: there is drop in performance as compared to training using Gibson videos, which we attribute this to domain shift. Also, note that even after this drop, our approach trained on passive videos in wild outperforms several baselines which are trained and tested on Gibson itself. We believe this is strong indication of how effective our algorithm is without using any simulator or RL.

Table 4: Comparison of our model (NRNS) trained with different sets of passive video data, on Image-Goal Navigation on **Gibson** [33]. We report average Success and Success weighted by inverse Path Length (SPL) @ $1m$. Results shown are tested without sensor & actuation noise.

Path Type	Training Data	Model	Easy Succ ↑	Easy SPL ↑	Medium Succ ↑	Medium SPL ↑
Straight	RealEstate10k [32]	NRNS	56.42	48.01	30.30	25.67
	MP3D	NRNS	59.80	52.35	37.00	31.89
	Gibson	NRNS	68.00	61.62	49.10	44.56
	Gibson	GRU + MLP + BC	30.20	29.57	12.70	12.48
Curved	RealEstate10k [32]	NRNS	21.10	15.76	12.90	5.57
	MP3D	NRNS	28.26	13.59	11.00	5.10
	Gibson	NRNS	35.50	18.38	23.90	12.08
	Gibson	GRU + MLP + BC	3.10	2.61	0.80	0.77

6 Conclusion

We presented a simple yet effective approach for learning navigation policies from just passive videos. While simulators have become fast, the diversity and scalability of environments still remains a concern. Our presented approach, NRNS, neither requires access to ground-truth maps nor online policy interaction and hence forgoes need of simulator to train policy functions. We demonstrate that NRNS can outperform end-to-end RL methods and behavioral cloning policies by significant margin.

References

[1] Peter Anderson, Angel Chang, Devendra Singh Chaplot, Alexey Dosovitskiy, Saurabh Gupta, Vladlen Koltun, Jana Kosecka, Jitendra Malik, Roozbeh Mottaghi, Manolis Savva, et al. On evaluation of embodied navigation agents. *arXiv preprint arXiv:1807.06757*, 2018.

[2] Tao Chen, Saurabh Gupta, and Abhinav Gupta. Learning exploration policies for navigation. *International Conference on Learning Representations*, 2019.

[3] Santhosh K Ramakrishnan, Ziad Al-Halah, and Kristen Grauman. Occupancy anticipation for efficient exploration and navigation. In *European Conference on Computer Vision*, 2020.

[4] Devendra Singh Chaplot, Ruslan Salakhutdinov, Abhinav Gupta, and Saurabh Gupta. Neural topological slam for visual navigation. In *Computer Vision and Pattern Recognition*, 2020.

[5] Dhruv Batra, Aaron Gokaslan, Aniruddha Kembhavi, Oleksandr Maksymets, Roozbeh Mottaghi, Manolis Savva, Alexander Toshev, and Erik Wijmans. ObjectNav Revisited: On Evaluation of Embodied Agents Navigating to Objects. In *arXiv:2006.13171*, 2020.

[6] Devendra Singh Chaplot, Dhiraj Prakashchand Gandhi, Abhinav Gupta, and Russ R Salakhutdinov. Object goal navigation using goal-oriented semantic exploration. *Neural Information Processing Systems*, 2020.

[7] Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, et al. Habitat: A platform for embodied ai research. In *International Conference on Computer Vision*, 2019.

[8] Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian Reid, Stephen Gould, and Anton van den Hengel. Vision-and-Language Navigation: Interpreting visually-grounded navigation instructions in real environments. In *Computer Vision and Pattern Recognition*, 2018.

[9] Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. AI2-THOR: An Interactive 3D Environment for Visual AI. *Computer Vision and Pattern Recognition*, 2017.

[10] Devendra Singh Chaplot, Dhiraj Gandhi, Saurabh Gupta, Abhinav Gupta, and Ruslan Salakhutdinov. Learning to explore using active neural slam. In *International Conference on Learning Representations*, 2020.

[11] Yuke Zhu, Roozbeh Mottaghi, Eric Kolve, Joseph J Lim, Abhinav Gupta, Li Fei-Fei, and Ali Farhadi. Target-driven visual navigation in indoor scenes using deep reinforcement learning. In *International Conference on Robotics and Automation*, 2017.

[12] Saurabh Gupta, James Davidson, Sergey Levine, Rahul Sukthankar, and Jitendra Malik. Cognitive mapping and planning for visual navigation. In *Computer Vision and Pattern Recognition*, 2017.

[13] Erik Wijmans, Abhishek Kadian, Ari Morcos, Stefan Lee, Irfan Essa, Devi Parikh, Manolis Savva, and Dhruv Batra. Dd-ppo: Learning near-perfect pointgoal navigators from 2.5 billion frames. In *International Conference on Learning Representations*, 2020.

[14] Yi Wu, Yuxin Wu, Aviv Tamar, Stuart Russell, Georgia Gkioxari, and Yuandong Tian. Bayesian relational memory for semantic visual navigation. In *International Conference on Computer Vision*, 2019.

[15] Lina Mezghani, Sainbayar Sukhbaatar, Thibaut Lavril, Oleksandr Maksymets, Dhruv Batra, Piotr Bojanowski, and Karteek Alahari. Memory-augmented reinforcement learning for image-goal navigation. *arXiv preprint arXiv:2101.05181*, 2021.

[16] Wei Yang, Xiaolong Wang, Ali Farhadi, Abhinav Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. *International Conference on Learning Representations*, 2018.

[17] Benjamin Eysenbach, Ruslan Salakhutdinov, and Sergey Levine. Search on the replay buffer: Bridging planning and reinforcement learning. In *Neural Information Processing Systems*, 2019.

[18] Nikolay Savinov, Alexey Dosovitskiy, and Vladlen Koltun. Semi-parametric topological memory for navigation. In *International Conference on Learning Representations*, 2018.

[19] Piotr Mirowski, Matthew Koichi Grimes, Mateusz Malinowski, Karl Moritz Hermann, Keith Anderson, Denis Teplyashin, Karen Simonyan, Koray Kavukcuoglu, Andrew Zisserman, and Raia Hadsell. Learning to navigate in cities without a map. In *Neural Information Processing Systems*, 2018.

[20] Scott Emmons, Ajay Jain, Michael Laskin, Thanard Kurutach, Pieter Abbeel, and Deepak Pathak. Sparse graphical memory for robust planning. In *Neural Information Processing Systems*, 2020.

[21] Kevin Chen, Juan Pablo de Vicente, Gabriel Sepulveda, Fei Xia, Alvaro Soto, Marynel Vázquez, and Silvio Savarese. A behavioral approach to visual navigation with graph localization networks. In *Robotics: Science and Systems*, 2019.

[22] Dhruv Shah, Benjamin Eysenbach, Gregory Kahn, Nicholas Rhinehart, and Sergey Levine. Ving: Learning open-world navigation with visual goals. *International Conference on Robotics and Automation*, 2020.

[23] Matthew Chang, Arjun Gupta, and Saurabh Gupta. Semantic visual navigation by watching youtube videos. In *Neural Information Processing Systems*, 2020.

[24] Russell A Epstein, Eva Zita Patai, Joshua B Julian, and Hugo J Spiers. The cognitive map in humans: spatial navigation and beyond. *Nature Neuroscience*, 2017.

[25] Edward C Tolman. Cognitive maps in rats and men. *Psychological Review*, 1948.

[26] Patrick Foo, William H Warren, Andrew Duchon, and Michael J Tarr. Do humans integrate routes into a cognitive map? map-versus landmark-based navigation of novel shortcuts. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, 2005.

[27] Ranxiao Frances Wang and Elizabeth S Spelke. Human spatial representation: Insights from animals. *Trends in Cognitive Sciences*, 2002.

[28] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. *International Conference on Learning Representations*, 2017.

[29] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Computer Vision and Pattern Recognition*, 2016.

[30] Brendan J Frey and Delbert Dueck. Clustering by passing messages between data points. *Science*, 2007.

[31] Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *Transactions on Pattern Analysis and Machine Intelligence*, 2017.

[32] Tinghui Zhou, Richard Tucker, John Flynn, Graham Fyffe, and Noah Snavely. Stereo magnification: Learning view synthesis using multiplane images. In *SIGGRAPH*, 2018.

[33] Fei Xia, Amir R Zamir, Zhiyang He, Alexander Sax, Jitendra Malik, and Silvio Savarese. Gibson env: Real-world perception for embodied agents. In *Computer Vision and Pattern Recognition*, 2018.

[34] Angel Chang, Angela Dai, Thomas Funkhouser, Maciej Halber, Matthias Niessner, Manolis Savva, Shuran Song, Andy Zeng, and Yinda Zhang. Matterport3d: Learning from rgb-d data in indoor environment. *International Conference on 3D Vision*, 2017.

[35] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.