EF21: A New, Simpler, Theoretically Better, and Practically Faster Error Feedback

Abstract

Error feedback (EF), also known as error compensation, is an immensely popular convergence stabilization mechanism in the context of distributed training of supervised machine learning models enhanced by the use of contractive communication compression mechanisms, such as Top-k. First proposed by Seide et al. [2014] as a heuristic, EF resisted any theoretical understanding until recently Stich et al. [2018], Alistarh et al. [2018]. While these early breakthroughs were followed by a steady stream of works offering various improvements and generalizations, the current theoretical understanding of EF is still very limited. Indeed, to the best of our knowledge, all existing analyses either i) apply to the single node setting only, ii) rely on very strong and often unreasonable assumptions, such global boundedness of the gradients, or iterate-dependent assumptions that cannot be checked a-priori and may not hold in practice, or iii) circumvent these issues via the introduction of additional unbiased compressors, which increase the communication cost. In this work we fix all these deficiencies by proposing and analyzing a new EF mechanism, which we call EF21, which consistently and substantially outperforms EF in practice. Moreover, our theoretical analysis relies on standard assumptions only, works in the distributed heterogeneous data setting, and leads to better and more meaningful rates. In particular, we prove that EF21 enjoys a fast $O(1/T)$ convergence rate for smooth nonconvex problems, beating the previous bound of $O(1/T^{2/3})$, which was shown under a strong bounded gradients assumption. We further improve this to a fast linear rate for Polyak-Lojasiewicz functions, which is the first linear convergence result for an error feedback method not relying on unbiased compressors. Since EF has a large number of applications where it reigns supreme, we believe that our 2021 variant, EF21, can a large impact on the practice of communication efficient distributed learning.

1 Introduction

In order to obtain state-of-the-art performance, modern machine learning models rely on elaborate architectures, need to be trained on data sets of enormous sizes, and involve a very large number of parameters. Some of the most successful models are heavily over-parameterized, which means that they involve more parameters than the number of available training data points [Arora et al., 2018]. Naturally, these circumstances should inform the design of optimization methods that could be most efficient to perform the training.

First, the reliance on sophisticated model architectures, as opposed to simple linear models, generally leads to **nonconvex** optimization problems, which are more challenging than convex problems [Jain and Kar, 2017]. Second, the need for very large training data sizes necessitates the use of **distributed computing** [Verbraeken et al., 2019]. Due to its enormous size, the data needs to be partitioned

across a number of machines able to work in parallel. Typically, for further efficiency gains, each such machine further parallelizes its local computations using one or more hardware accelerators. Third, the very large number of parameters describing these models exerts an extra stress on the communication links used to exchange model updates among the machines. These links are typically slow compared to the speed at which computation takes place, and communication often forms the bottleneck of distributed systems even in less extreme situations than over-parameterized training where the number of parameters, and hence the nominal size of communicated messages, can be truly staggering. For this reason, modern efficient optimization methods typically employ elaborate **lossy communication compression** techniques to reduce the size of the communicated messages.

Due to the above reasons, in this paper we are interested in solving the *nonconvex distributed optimization problem*

$$\min_{x \in \mathbb{R}^d} \left[f(x) \stackrel{\text{def}}{=} \frac{1}{n} \sum_{i=1}^{n} f_i(x) \right], \tag{1}$$

where $x \in \mathbb{R}^d$ represents the parameters of a machine learning model we wish to train, n is the number of workers/nodes/machines, and $f_i(x)$ is the loss of model x on the data stored on node i. We specifically focus on the development of new and more efficient communication efficient first-order methods for solving (1) utilizing *biased* compression operators, with a special emphasis on *clean convergence analysis* which removes the *strong and often unrealistic assumptions*, such as the bounded gradient assumption, which are currently needed to analyze such methods (see Table 1).

The remainder of the paper is organized as follows. In Section 2 we describe the key concepts, results and open problems that form the motivation for our work. In Section 3 we summarize our key contributions. Our main theoretical results are presented in Section 4, and finally, experimental results are described in Section 5.

2 Background and Motivation

To better motivate our approach and contributions, we first offer a concise walk-through over the key considerations, difficulties, advances and open problems in this area.

2.1 Two families of compression operators

Compression is typically performed via the application of a (possibly randomized) mapping $\mathcal{C} : \mathbb{R}^d \to \mathbb{R}^d$, where d is the dimension of the vector/tensor that needs to be communicated, with the property that it is much easier/quicker to transfer $\mathcal{C}(x)$ than it is to transfer the original message x. This can be achieved in several ways, for instance by sparsifying the input vector [Alistarh et al., 2018], or by quantizing its entries [Alistarh et al., 2017, Horváth et al., 2019a], or via a combination of these and other approaches [Horváth et al., 2019a, Beznosikov et al., 2020].

There are two large classes of compression operators $\mathcal{C}$ often studied in the literature: i) **unbiased compression operators** satisfying a variance bound proportional to the square norm of the input vector, and ii) **biased compression operators** whose square distortion is contractive with respect to the square norm of the input vector.

In particular, we say that a (possibly randomized) map $\mathcal{C} : \mathbb{R}^d \to \mathbb{R}^d$ is an *unbiased compression operator*, or simply just *unbiased compressor*, if there exists a constant $\omega \geq 0$ such that

$$\mathbb{E}\left[\mathcal{C}(x)\right] = x, \quad \mathbb{E}\left[\|\mathcal{C}(x) - x\|^2\right] \leq \omega \|x\|^2, \qquad \forall x \in \mathbb{R}^d. \tag{2}$$

The family of such operators will be denoted by $\mathbb{U}(\omega)$. Further, we say that a (possibly randomized) map $\mathcal{C} : \mathbb{R}^d \to \mathbb{R}^d$ is a *biased compression operator*, or simply just *biased compressor*, if there exists a constant $0 < \alpha \leq 1$ such that

$$\mathbb{E}\left[\|\mathcal{C}(x) - x\|^2\right] \leq (1 - \alpha) \|x\|^2, \qquad \forall x \in \mathbb{R}^d. \tag{3}$$

The family of such operators will be denoted by $\mathbb{B}(\alpha)$. It is well known that, in a certain sense, the latter class contains the former. In particular, it is easy to verify that if $\mathcal{C} \in \mathbb{U}(\omega)$, then $(1 + \omega)^{-1}\mathcal{C} \in \mathbb{B}(1/(1+\omega))$. However, the latter class is strictly larger, i.e., it contains compressors which do not arise via a scaling of an unbiased compressor. A canonical example of this is the Top-k compressor, which preserves the k largest (in absolute value) entries of the input, and zeros out the remaining entries,

and for which $\alpha = {}^k/d$. We refer to [Beznosikov et al., 2020, Safaryan et al., 2021, Table 1] for more examples of unbiased and biased compressors, and to Xu et al. [2020] for a systems-oriented survey.

When used in an appropriate way, greedy biased compressors, such as Top-k, are often empirically superior to their unbiased counterparts [Seide et al., 2014], such as Rand-k. Intuitively, such greedy compressors retain more of the "information" or "energy" contained within the message, and hence introduce less distortion. This is beneficial in practice, at least in the simplistic single node (i.e., non-distributed) setting, albeit even here we do not have convincing theory that would explain this.

2.2 Error feedback: what it is good for, and what we still do not know

The difference between what we know about unbiased and biased compressors is larger still in the distributed setting.

In particular, *unbiasedness* turns out to be a very effective tool facilitating the analysis of distributed first order methods utilizing unbiased compressors, and for this reason, the landscape of methods using such compressors is very rich and relatively well understood. For example, we know how to i) analyze distributed compressed gradient decent [Khirirat et al., 2018, Mishchenko et al., 2020], ii) remove the variance introduced by compression to achieve faster convergence [Mishchenko et al., 2019, Horváth et al., 2019b, Mishchenko et al., 2020], iii) perform bidirectional compression at the workers and also at the master [Horváth et al., 2019a, Philippenko and Dieuleveut, 2020], iv) develop a general theory for SGD which, besides more standard methods, also includes variants using unbiased compression of (stochastic) gradients [Gorbunov et al., 2020a, Khaled et al., 2020, Li and Richtárik, 2020], v) achieve Nesterov acceleration in the strongly convex regime [Li et al., 2020], how to analyze these methods in the nonconvex regime [Mishchenko et al., 2019, Horváth et al., 2019a, Li and Richtárik, 2020], vi) achieve acceleration in the nonconvex regime [Gorbunov et al., 2021], and even how to vii) apply unbiased compressors to Hessian matrices to obtain communication-efficient second-order methods [Islamov et al., 2021].

The situation with *general* biased compressors (i.e., those that do not arise from unbiased compressors via scaling) is much more challenging. The key complication comes from the fact that their naive use within first order methods, such as gradient descent, can lead to divergence. We refer the reader to [Beznosikov et al., 2020, Example 1] for a simple example where gradient descent "enhanced" with the Top-1 compressor leads to *exponential divergence* when applied to the problem of minimizing the average of three strongly convex quadratics in $\mathbb{R}^3$. However, divergence of gradient descent enhanced with biased compressors such as Top-k was observed empirically much sooner, and a fix for this problem, known as *error feedback* (EF), or *error compensation* (EC), was suggested by Seide et al. [2014]. This fix remained a heuristic until very recently.

The first theoretical breakthroughs focused on the simpler single-node setting [Stich et al., 2018, Alistarh et al., 2018]. The first analysis in the general distributed heterogeneous data[1] setting was performed by Beznosikov et al. [2020], and was confined to the strongly convex regime. While without compression, one can expect a linear rate, the rate in [Beznosikov et al., 2020] is linear only in the special case of an over-parameterized regime (i.e., regime in which the loss functions on all nodes share a common minimizer) with a requirement of full gradient computations on each node. These deficiencies were later fixed by Gorbunov et al. [2020b], who developed the first linearly convergent methods EC-GD-DIANA and EC-LSVRG-DIANA, and also analyzed the convex case. However, this advance was achieved through the use of additional unbiased compressors, and hence via an increase in communication in each round.

> *In particular, whether it is possible to obtain a linearly convergent error-compensated method in the general heterogeneous data setting, relying on biased compressors only, is still an open problem.*

The current state-of-the-art theoretical result for error-compensated methods in the smooth non-convex regime are due to Koloskova et al. [2020, Theorem 4.1], who consider the more general problem of decentralized optimization over a network. In the case when full (as opposed to stochastic) gradients are computed on each node, they show that after T communication rounds it is possible to

---

[1]Problem (1) is in the *heterogeneous data regime* if no similarity among the functions (and hence among the data stored across different nodes giving rise to these functions) is assumed.

Algorithm	sCVX	nCVX	DIST	key limitation
EF
Stich et al. [2018]	✓	✗	✓	bounded gradients;
sublinear rate in sCVX case
EF-SGD
Stich and Karimireddy [2019]	✓	✓	✗	single node only
EF
Ajalloeian and Stich [2020]	✓	✓	✗	single node only
SignSGD
Karimireddy et al. [2019]	✗	✓	✗	moment bound;
single node only
EC-SGD
Beznosikov et al. [2020]	✓	✗	✓	linear rate only
if $\nabla f_i(x^\star) = 0 \; \forall i$
EC-SGD
Gorbunov et al. [2020b]	✓	✗	✓	linear rate only using
an extra unbiased compressor
DoubleSqueeze
Tang et al. [2020]	✗	✓	✓	bounded compression error;
slow $O(1/T^{2/3})$ rate in nCVX case
Qsparse-SGD, CSER
Basu et al. [2019], Xie et al. [2020]	✓	✓	✓	bounded gradients;
slow $O(1/T^{1/2})$ rate in nCVX case
EC-SGD
Koloskova et al. [2020]	✗	✓	✓[†]	bounded gradients;
slow $O(1/T^{2/3})$ rate in nCVX case

Table 1: Known results for first order methods using biased compressors. sCVX = supports strongly convex functions, nCVX= supports nonconvex functions, DIST = works in the distributed regime. [†]decentralized method

find a random vector $\hat{x}^T$ with the guarantee

$$\mathbb{E}\left[\left\|\nabla f(\hat{x}^T)\right\|^2\right] = \mathcal{O}\left(\frac{G^{2/3}}{T^{2/3}}\right), \tag{4}$$

under the *bounded gradient* assumption which requires the existence of a constant $G > 0$ such that

$$\|\nabla f_i(x)\|^2 \le G^2 \tag{5}$$

holds for all $x \in \mathbb{R}^d$ and all $i \in \{1,2,\dots,n\}$. This was a slight improvement in rate over an result obtained by Lian et al. [2017], who instead use the bounded dissimilarity assumption

$$\frac{1}{n}\sum_{i=1}^{n} \|\nabla f_i(x) - \nabla f(x)\|^2 \le G^2. \tag{6}$$

A summary of the limitations of known results for EF-based methods is provided in Table 1.

> *In this work we argue that the bounded gradients* (5) *and bounded dissimilarity* (6) *assumptions are too strong[2], and that the sublinear rate* (4) *is not what one should expect from a good analysis of a well designed error-compensated first-order method. Instead, one could hope for the faster $\mathcal{O}(1/T)$ rate, which is what one obtains with methods using unbiased compressors [Gorbunov et al., 2021, Theorem 2.1]. The resolution of these issues is an open problem.*

3 Summary of Contributions

In this work we address and resolve the aforementioned challenges. Our key contributions are:

A. New error feedback mechanism. We propose a new error feedback (resp. error compensation) mechanism, which we call EF21 (resp. EC21) – see Algorithms 1 and 2. Unlike most results on error compensation, EF21 naturally works in the distributed heterogeneous data setting.

---

[2]The bounded gradient (5) and bounded dissimilarity (6) assumptions are too strong as they are rarely satisfied. For example, neither hold even for simple quadratic functions. To see this, let $f_i(x) = x^\top \mathbf{A}_i x$, where $\mathbf{A}_i \in \mathbb{R}^{d \times d}$. Since $\nabla f_i(x) = \mathbf{B}_i x$, where $\mathbf{B}_i = \mathbf{A}_i + \mathbf{A}_i^\top$, the bounded gradient assumption requires the vectors $\sup_x \max_i \|\mathbf{B}_i x\|$ to be bounded, which is not the case, unless all matrices $\mathbf{B}_i$ are zero. The bounded dissimilarity assumption (6), which can be written in the form $\frac{1}{n}\sum_{i=1}^{n} \|(\mathbf{B}_i - \frac{1}{n}\sum_{j=1}^{n} \mathbf{B}_j)x\|^2 \le G^2$, also does not hold, unless $\mathbf{B}_i = \mathbf{B}_j$ for all i,j, which reduces to the identical data regime, which is of limited interest.

Assumptions	Complexity	Theorem
f_i is L_i-smooth
f is lower bounded by f^{inf}	$\mathbb{E}\left[\left\|\nabla f(\hat{x}^T)\right\|^2\right] \leq \frac{2\left(f(x^0)-f^{\mathrm{inf}}\right)}{\gamma T} + \frac{\mathbb{E}\left[G^0\right]}{\theta T}$	2
f_i is L_i-smooth
f is lower bounded by f^{inf}
f satisfies PL condition	$\mathbb{E}\left[\Psi^T\right] \leq (1 - \gamma\mu)^T \mathbb{E}\left[\Psi^0\right]$	3

Table 2: Summary of complexity results obtained in this paper. Quantities: μ = PL constant; γ = stepsize; G^0 = see (13); Ψ^t = Lyapunov function defined in Theorem 3.

B. Standard assumptions and fast rates. Our theoretical analysis of EF21 relies on standard assumptions only, which are: i) L_i-smoothness of the individual functions f_i, and ii) existence of a global lower bound $f^{\mathrm{inf}} \in \mathbb{R}$ on f. We prove that under these assumptions, EF21 enjoys the desirable $\mathcal{O}(1/T)$ convergence rate, which improves upon the previous $\mathcal{O}(1/T^{2/3})$ state-of-the-art result of Koloskova et al. [2020] both in terms of the rate, and in terms of the strength of the assumptions needed to obtain this result. These complexity results are summarized in the first row of Table 2.

C. Linear rate for Polyak-Lojasiewicz functions. We show that under the additional assumption that f satisfies the Polyak-Lojasiewicz inequality, EF21 enjoys a linear convergence rate. This improves upon the results of Beznosikov et al. [2020], who only obtain a linear rate in the case when $\nabla f_i(x^\star) = 0$ for all i, where $x^\star = \arg\min f$, and provides an alternative to the linear convergence results of Gorbunov et al. [2020b], who needed to introduce additional unbiased compressors into their scheme, and hence additional communication, in order to obtain their results. Our complexity results are summarized in the second row of Table 2.

D. Empirical superiority. We show through extensive numerical experimentation on both synthetic problems and deep learning benchmarks that EF21 consistently and substantially outperforms EF in practice. One of the reasons behind this is the fact that our method is able to admit much larger learning rates. Since EF has a large number of applications where it reigns supreme, we believe that EF21 will have a large impact on the practice of communication efficient distributed learning. We further propose a more aggressive variant, EF21+ (see Section 4.6), which has an even better empirical behavior.

E. Extensions. For clarity, in the main body of the paper we focus on the simplest variants of EF21. We describe a few extensions in the Appendix.

4 Main Results

Since we are about to re-engineer the classical error feedback technique, it will be useful to take a step back and re-examine the issues inherent to the simplest first order method which uses biased compressors but does *not* employ error feedback: distributed compressed gradient descent (DCGD).

Let x^t be the t-th iterate, shared by all n nodes. Each node i first computes its local gradient $\nabla f_i(x^t)$, compresses is using some $\mathcal{C} \in \mathbb{B}(\alpha)$, and sends the compressed gradient $\mathcal{C}(\nabla f_i(x^t))$ to the master. The master aggregates all n messages via averaging, and performs the optimization step

$$x^{t+1} = x^t - \frac{\gamma}{n} \sum_{i=1}^{n} \mathcal{C}(\nabla f_i(x^t)). \tag{7}$$

As mentioned before, this method can diverge, even in simple quadratic problems in low dimensions [Beznosikov et al., 2020]. Let us look at this problem from a different angle. Assume, for the sake of an intuitive argument, that the sequence of iterates actually converges to some $x^\dagger$. Since in general there is no reason for the gradients $\nabla f_i(x^\dagger)$ to be all zero, even if $x^\dagger$ is the minimizer of f, the application of $\mathcal{C}$ to the gradients $\nabla f_i(x^t)$ will introduce a nonzero distortion even if $x^t \approx x^\dagger$. Indeed, in view of (3), all that can be guaranteed is that $\mathbb{E}\left[\left\|\mathcal{C}(\nabla f_i(x^t)) - \nabla f_i(x^t)\right\|^2\right] \leq (1-\alpha)\left\|\nabla f_i(x^t)\right\|^2$, which can be large if the norm of $\nabla f_i(x^t)$ is large. So, the method is intrinsically unstable around $x^\dagger$, and hence can not converge to $x^\dagger$.

Our idea is to fix this issue by *compressing different vectors* instead of the gradients, vectors that would hopefully converge to zeros instead. Since in view of (3) the application of $\mathcal{C}$ to progressively vanishing vectors introduces progressively vanishing distortion, the stabilization problem would be

188 solved. But what vectors should we compress? In order to answer this question, it will be useful to
189 consider a simpler and more abstract setting first, which we shall do next.

4.1 Markov compressors

191 Assume we are given a sequence of input vectors $\{v^t\}_{t \geq 0}$ (e.g., gradients) generated by some
192 algorithm. This sequence does not necessarily converge to zero. Our goal is to produce a sequence of
193 "good" and "easy to communicate" (to some entity, which we shall call the "master") estimates of
194 these vectors, making use of a compressor $\mathcal{C} \in \mathbb{B}(\alpha)$.

Naive idea. The first and naive approach, described above, is to simply output the sequence of
196 compressed inputs: $\{\mathcal{C}(v^t)\}_{t \geq 0}$. However, while these estimates can be communicated efficiently,
197 they are not getting "better". That is, the distortion $\mathbb{E}\left[\|\mathcal{C}(v^t) - v^t\|^2\right]$ is not necessarily improving.

Good but not implementable idea. What can we do better? Consider the following idea. If we new,
199 hypothetically, the limit of this sequence, v^*, we could output $v^* + \mathcal{C}(v^t - v^*)$ at iteration t instead.
200 Since $v^t \to v^*$, the distortion between the input and the output at iteration t is

$$\mathbb{E}\left[\|v^* + \mathcal{C}(v^t - v^*) - v^t\|^2\right] = \mathbb{E}\left[\|\mathcal{C}(v^t - v^*) - (v^t - v^*)\|^2\right] \overset{(3)}{\leq} (1 - \alpha)\|v^t - v^*\|^2 \to 0.$$

201 So, the distortion issue is fixed! Moreover, if we assume the master knows v^*, then the output vector
202 at each iteration can be communicated cheaply as well, since all we need to communicate is the
203 compressed vector $\mathcal{C}(v^t - v^*)$. It will be useful to think of this operation as a new compressor, called
204 $\mathcal{C}_{v^*}$, one that takes v^t as an input, and gives $v^* + \mathcal{C}(v^t - v^*)$ as its output. That is, we can define

$$\mathcal{C}_{v^*}(v) \overset{\text{def}}{=} v^* + \mathcal{C}(v - v^*). \tag{8}$$

205 While the compressor $\mathcal{C}_{v^*}$ satisfies all our requirements, it is not implementable, since the vector v^*
206 is not known. We will now use this intuition to construct an implementable mechanism.

Good and implementable idea. In the above construction, we have used the fact that $v^t - v^* \to 0$
208 to construct a good mechanism, but one that is not implementable. How can we fix this issue? The
209 rescue comes from the *recursive* observation that if we indeed succeed in constructing a compressor,
210 let's call it $\mathcal{M}$, such that the distortion between $\mathcal{M}(v^t)$ and v^t vanishes as $t \to \infty$, then it must be
211 the case that $v^t - \mathcal{M}(v^t) \to 0$. So, we can compress *this* vanishing vector instead. This idea gives
212 rise to the following recursive definition of $\mathcal{M}$:

$$\mathcal{M}(v^0) \quad \overset{\text{def}}{=} \quad \mathcal{C}(v^0) \tag{9}$$

$$\mathcal{M}(v^{t+1}) \quad \overset{\text{def}}{=} \quad \mathcal{M}(v^t) + \mathcal{C}(v^{t+1} - \mathcal{M}(v^t)), \quad t \geq 0 \tag{10}$$

213 Note that (10) is similar to (8), with one key difference: we are using the previously compressed vector
214 $\mathcal{M}(v^t)$ instead of the limit vector v^*. This property also makes our new compressor non-stationary,
215 i.e., it has a Markov property.

216 It is easy to establish that (see the Appendix) under some assumptions about the speed at which the
217 input sequence v^t converges to v^*, it will be the case that $\mathbb{E}\left[\|\mathcal{M}(v^t) - v^t\|^2\right] \to 0$. For instance, if
218 the convergence rate of the input sequence is linear, then the distortion will converge to 0. While this
219 is interesting on its own, let us deploy our new tool, which we call *Markov compressor*, in the context
220 of gradient descent, and then in the context of distributed gradient descent.

4.2 Compressed gradient descent using the Markov compressor

222 For simplicity, consider solving problem (1) in $n = 1$ case, i.e., the problem $\min_{x \in \mathbb{R}^d} f(x)$, using the
223 compressed gradient descent method featuring the Markov compressor. Start with $x^0 \in \mathbb{R}^d$, stepsize
224 $\gamma > 0$, and let $\mathcal{M}(\nabla f(x^0)) = \mathcal{C}(\nabla f(x^0))$. After this, for $t \geq 0$ iterate:

$$x^{t+1} \quad = \quad x^t - \gamma \mathcal{M}(\nabla f(x^t)) \tag{11}$$

$$\mathcal{M}(\nabla f(x^{t+1})) \quad = \quad \mathcal{M}(\nabla f(x^t)) + \mathcal{C}(\nabla f(x^{t+1}) - \mathcal{M}(\nabla f(x^t))). \tag{12}$$

225 Note that the situation here is more complicated than the abstract setting described earlier since
226 now there is *interaction* between the input sequence $\{\nabla f(x^t)\}_{t \geq 0}$ of gradients and the sequence

---

Algorithm 1 EF21 (Single node)

1: **Input:** starting point $x^0 \in \mathbb{R}^d$, learning rate $\gamma > 0$, $g^0 = \mathcal{C}(\nabla f(x^0))$
2: **for** $t = 0,1,2,\ldots,T-1$ **do**
3:     $x^{t+1} = x^t - \gamma g^t$
4:     $g^{t+1} = g^t + \mathcal{C}(\nabla f(x^{t+1}) - g^t)$
5: **end for**

Algorithm 2 EF21 (Multiple nodes)

1: **Input:** starting point $x^0 \in \mathbb{R}^d$; $g_i^0 = \mathcal{C}(\nabla f_i(x^0))$ for $i = 1, \ldots, n$ (known by nodes and the master); learning rate $\gamma > 0$; $g^0 = \frac{1}{n} \sum_{i=1}^n g_i^0$ (known by master)
2: **for** $t = 0,1,2,\ldots,T-1$ **do**
3:     Master computes $x^{t+1} = x^t - \gamma g^t$ and broadcasts x^{t+1} to all nodes
4:     **for all nodes** $i = 1, \ldots, n$ **in parallel do**
5:         Compress $c_i^t = \mathcal{C}(\nabla f_i(x^{t+1}) - g_i^t)$ and send c_i^t to the master
6:         Update local state $g_i^{t+1} = g_i^t + \mathcal{C}(\nabla f_i(x^{t+1}) - g_i^t)$
7:     **end for**
8:     Master computes $g^{t+1} = \frac{1}{n} \sum_{i=1}^n g_i^{t+1}$ via $g^{t+1} = g^t + \frac{1}{n} \sum_{i=1}^n c_i^t$
9: **end for**

$\mathcal{M}(\nabla f(x^t))$ of compressed gradients via the Markov compressor. Indeed, the output of $\mathcal{M}$ at iteration t influences the next iterate x^{t+1} (via (11)), which in turn defines the next input vector $v^{t+1} = \nabla f(x^{t+1})$ in the sequence, and so on.

To lighten up the heavy notation in (11) and (12), it will be useful to write $g^t = \mathcal{M}(\nabla f(x^t))$. Using this new notation that hides the fact that g^t is the application of the Markov compressor to the gradient, the method described above is formalized as Algorithm (1). This is precisely our proposed new variant of error feedback, EF21, specialized to the single node problem $\min_{x \in \mathbb{R}^d} f(x)$.

4.3 Distributed variant of EF21

The main method of this paper, which we now present as Algorithm 2, is an extension of Algorithm 1 to the general finite-sum problem (1). In particular, we apply the Markov compressor individually on each node to the local gradients $\nabla f_i(x^t)$, and communicate the compressed gradients to the master. Recall that we only need to communicate the vectors $\mathcal{C}(\nabla f_i(x^{t+1}) - g_i^t)$ since the additive terms g_i^t appearing in the Markov compressor were communicated in the previous round. Master then averages all gradient estimators, obtaining $g^{t+1} = \frac{1}{n} \sum_{i=1}^n g_i^{t+1}$, which can be done by performing the calculation $g^{t+1} = g^t + \frac{1}{n} \sum_{i=1}^n c_i^t$, where g^t is the average from the previous round which the master maintains, and $c_i^t = \mathcal{C}(\nabla f_i(x^{t+1}) - g_i^t)$ are the compressed messages. After this, the master takes a gradient-like step, and broadcasts the new model to all nodes.

4.4 Relationship between EF and EF21

While this is not at all apparent at first sight, it turns out that EF and EF21 are related. In particular, under certain conditions on the compressor $\mathcal{C}$, which are not met in practice, they are identical.

Theorem 1. *Assume that $\mathcal{C}$ is deterministic, positive homogeneous and additive. Then* EF *(Algorithm 3; see appendix) and* EF21 *produce the same sequences of iterates* $\{x^t\}_{t \geq 0}$.

Note that while the Top-k compressor is deterministic and positively homogeneous, it is not additive. Likewise, compressors arising via rescaling of unbiased compressors are randomized, and hence do not satisfy the first condition. Still, the above theorem sheds some (at least to us) unexpected light on the close connection between EF and our new variant, EF21. This connection is also what justifies our naming decision: EF21 – error feedback mechanism from the year 2021.

4.5 Theory

We make the following assumption throughout:

Assumption 1 (Smoothness and lower boundedness). *Every f_i has L_i-Lipschitz gradient, i.e.,* $\|\nabla f_i(x) - \nabla f_i(y)\| \leq L_i \|x - y\|$ *for all* $x, y \in \mathbb{R}^d$, *and* $f^{\inf} \stackrel{def}{=} \inf_{x \in \mathbb{R}^d} f(x) > -\infty$.

If each f_i has L_i-Lipschitz gradient, then it is straightforward to check by Jensen's inequality that f is L-Lipschitz, with L satisfying the inequality $L \leq \frac{1}{n} \sum_i L_i$. It will be also useful to define $\widetilde{L} \stackrel{def}{=} (\frac{1}{n} \sum_{i=1}^{n} L_i^2)^{1/2}$. By the arithmetic-quadratic mean inequality, we have $\frac{1}{n} \sum_i L_i \leq \widetilde{L}$. Let

$$G^t \stackrel{def}{=} \frac{1}{n} \sum_{i=1}^{n} \|g_i^t - \nabla f_i(x^t)\|^2, \tag{13}$$

a quantity which will appear in both our theorems. In EF21 we use $\mathcal{C} \in \mathbb{B}(\alpha)$, where $0 < \alpha \leq 1$, and define $\theta = 1 - \sqrt{1 - \alpha}$ and $\beta = \frac{1-\alpha}{1-\sqrt{1-\alpha}}$. We now formulate our first complexity result.

Theorem 2. *Let Assumption 1 hold, and let the stepsize in Algorithm 2 be set as*

$$0 < \gamma \leq \left(L + \widetilde{L}\sqrt{\beta/\theta}\right)^{-1}. \tag{14}$$

Fix $T \geq 1$ and let $\hat{x}^T$ be chosen from the iterates $x^0, x^1, \ldots, x^{T-1}$ uniformly at random. Then

$$\mathbb{E}\left[\|\nabla f(\hat{x}^T)\|^2\right] \leq \frac{2(f(x^0) - f^{\inf})}{\gamma T} + \frac{\mathbb{E}[G^0]}{\theta T}. \tag{15}$$

Note that $\sqrt{\beta/\theta} = \frac{(1+\sqrt{1-\alpha})}{\alpha} - 1 \leq \frac{2}{\alpha} - 1$ is decreasing in α. This makes sense since larger α means less dramatic compression, which leads to smaller $\sqrt{\beta/\theta}$, and this through (14) allows for larger stepsize, and hence fewer communication rounds. We now introduce the PL assumption, which enables us to obtain a linear convergence result.

Assumption 2 (Polyak-Lojasiewicz). *There exists $\mu > 0$ such that $f(x) - f(x^\star) \leq \frac{1}{2\mu} \|\nabla f(x)\|^2$ for all $x \in \mathbb{R}^d$, where $x^\star = \arg\min f$.*

Theorem 3. *Let Assumptions 1 and 2 hold, and let the stepsize in Algorithm 2 be set as*

$$0 < \gamma \leq \min\left\{\left(L + \widetilde{L}\sqrt{2\beta/\theta}\right)^{-1}, \frac{\theta}{2\mu}\right\}. \tag{16}$$

Let $\Psi^t \stackrel{def}{=} f(x^t) - f(x^\star) + \frac{\gamma}{\theta} G^t$. Then for any $T \geq 0$, we have

$$\mathbb{E}\left[\Psi^T\right] \leq (1 - \gamma\mu)^T \mathbb{E}\left[\Psi^0\right]. \tag{17}$$

Our theorems hold for an arbitrary choice of the initial vectors $\{g_i^0\}$, and not just for $g_i^0 = \mathcal{C}(\nabla f_i(x^0))$. For instance, if $g_i^0 = \nabla f_i(x^0)$ is used, then $\mathbb{E}[G^0] = 0$, and the second term in (15) vanishes.

4.6 EF21+: Use $\mathcal{C}$ or the Markov compressor, whichever is better

We now briefly describe a new hybrid method, called EF21+ (full description is in the Appendix), which often performs particularly well in practice. In every communication round, EF21 allows each node to compress using the "best" of $\mathcal{C}$ and the Markov compressor generated. So, EF21+ can be thought of as a hybrid between DCGD (see (7)) and EF21. The decision about which compressor to use is made by each node i individually, based on which of the distortions $\|\mathcal{C}(s) - s\|$ and $\|\mathcal{M}(s) - s\|$ is smaller, where $s = \nabla f_i(x^{t+1})$.

5 Experiments

We first consider solving a logistic regression problem with a non-convex regularizer,

$$f(x) = \frac{1}{n} \sum_{i=1}^{n} \log\left(1 + \exp\left(-y_i a_i^\top x\right)\right) + \lambda \sum_{j=1}^{d} \frac{x_j^2}{1+x_j^2},$$

where $a_i \in \mathbb{R}^d, y_i \in \{-1,1\}$ are the training data, and $\lambda > 0$ is the regularizer parameter. We used $\lambda = 0.1$ in all experiments.

Dataset	n	N (total # of datapoints)	d (# of features)	N_i (# of datapoints per client)
phishing	20	11,055	68	552
mushrooms	20	8,120	112	406
a9a	20	32,560	123	1,628
w8a	20	49,749	300	2,487

Table 3: Summary of the datasets and splitting of the data among clients.

Datasets, hardware and code. The datasets were taken from LibSVM [Chang and Lin, 2011], and were split into $n = 20$ equal parts, each associated with one of 20 clients. The last part, of size $N - 20 \cdot \lfloor N/20 \rfloor$, was assigned to the last worker. That is, we consider the heterogeneous data distributed regime. A summary can be found in Table 3. The code was written in Python 3.8 and we used 3 different CPU cluster node types in all experiments (here and in the Appendix): 1) AMD EPYC 7702 64-Core; 2) Intel(R) Xeon(R) Gold 6148 CPU @ 2.40GHz; 3) Intel(R) Xeon(R) Gold 6248 CPU @ 2.50GHz.

Experiment 1: Stepsize tolerance. In our first experiment (see Figure 1) we test the robustness/tolerance of EF, EF21, and EF21+ to large stepsizes, using Top-k with $k = 1$ [Alistarh et al., 2017] as a canonical example of biased compressor $\mathcal{C}$. Note that while for all stepsize choices, EF gets stuck at a certain accuracy level, EF21 and EF21+ do not suffer from this issue, and are hence able to work with larger or even much larger stepsizes.

Figure 1: The performance of EF, EF21, and EF21+ with Top-1 compressor, and for increasing stepsizes. Representative dataset used: a9a. By $1\times, 2\times, 4\times$ (and so on) we indicate that the stepsize was set to a multiple of the largest stepsize predicted by our theory.

Experiment 2: Fine-tuning k and the stepsizes. We now showcase the superior communication efficiency of EF21 and EF21+ over classical EF, again using the Top-k compressor. However, this time we fine-tuned k and stepsizes individually for each methods (details are given in Appendix A). For reference, we also included distributed gradient descent (GD), which can be thought of as EF21 with $k = d$ (no compression), into the mix.

Figure 2: Comparison of EF21, EF21+ to EF with Top-k for individually fine-tuned k and fine-tuned stepsizes for all methods.

In Figure 2 we can see that in all cases, the proposed methods outperform EF in terms of the # of bits sent to the server per client on the horizontal axis (bits/n), and rapidly converge to the desired accuracy, whereas EF is stuck at some accuracy levels in all cases. Moreover, in all experiments, classical GD shows the worst convergence rate. Note that EF21 tolerates larger, and EF21+ much larger, stepsizes than EF.

Further experiments. Further experiments, including deep learning experiments, are presented in Appendix A.

References

Ahmad Ajalloeian and Sebastian U Stich. Analysis of SGD with biased gradient estimators. *arXiv preprint arXiv:2008.00051*, 2020.

Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. QSGD: Communication-efficient SGD via gradient quantization and encoding. In *Advances in Neural Information Processing Systems (NIPS)*, pages 1709–1720, 2017.

Dan Alistarh, Torsten Hoefler, Mikael Johansson, Sarit Khirirat, Nikola Konstantinov, and Cédric Renggli. The convergence of sparsified gradient methods. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Sanjeev Arora, Nadav Cohen, and Elad Hazan. On the optimization of deep networks: Implicit acceleration by overparameterization. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, 2018.

Debraj Basu, Deepesh Data, Can Karakus, and Suhas Diggavi. Qsparse-local-SGD: Distributed SGD with quantization, sparsification, and local computations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Aleksandr Beznosikov, Samuel Horváth, Peter Richtárik, and Mher Safaryan. On biased compression for distributed learning. *arXiv preprint arXiv:2002.12410*, 2020.

Chih-Chung Chang and Chih-Jen Lin. Libsvm: a library for support vector machines. *ACM transactions on intelligent systems and technology (TIST)*, 2(3):1–27, 2011.

Eduard Gorbunov, Filip Hanzely, and Peter Richtárik. A unified theory of SGD: Variance reduction, sampling, quantization and coordinate descent. In *The 23rd International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2020a.

Eduard Gorbunov, Dmitry Kovalev, Dmitry Makarenko, and Peter Richtárik. Linearly converging error compensated SGD. In *34th Conference on Neural Information Processing Systems (NeurIPS)*, 2020b.

Eduard Gorbunov, Konstantin Burlachenko, Zhize Li, and Peter Richtárik. MARINA: Faster non-convex distributed learning with compression. *arXiv preprint arXiv:2102.07845*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

Samuel Horváth, Chen-Yu Ho, Ľudovít Horváth, Atal Narayan Sahu, Marco Canini, and Peter Richtárik. Natural compression for distributed deep learning. *arXiv preprint arXiv:1905.10988*, 2019a.

Samuel Horváth, Dmitry Kovalev, Konstantin Mishchenko, Sebastian Stich, and Peter Richtárik. Stochastic distributed learning with gradient quantization and variance reduction. *arXiv preprint arXiv:1904.05115*, 2019b.

Rustem Islamov, Xun Qian, and Peter Richtárik. Distributed second order methods with fast rates and compressed communication. *arXiv preprint arXiv:2102.07158*, 2021.

Prateek Jain and Purushottam Kar. Non-convex optimization for machine learning. *Foundations and Trends in Machine Learning*, 10(3-4):142–336, 2017.

Sai Praneeth Karimireddy, Quentin Rebjock, Sebastian Stich, and Martin Jaggi. Error feedback fixes SignSGD and other gradient compression schemes. In *36th International Conference on Machine Learning (ICML)*, 2019.

Ahmed Khaled, Othmane Sebbouh, Nicolas Loizou, Robert M. Gower, and Peter Richtárik. Unified analysis of stochastic gradient methods for composite convex and smooth optimization. *arXiv preprint arXiv:2006.11573*, 2020.

Sarit Khirirat, Hamid Reza Feyzmahdavian, and Mikael Johansson. Distributed learning with compressed gradients. *arXiv preprint arXiv:1806.06573*, 2018.

Anastasia Koloskova, Tao Lin, S. Stich, and Martin Jaggi. Decentralized deep learning with arbitrary communication compression. In *International Conference on Learning Representations (ICLR)*, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. Technical report, University of Toronto, Toronto, 2009.

Zhize Li and Peter Richtárik. A unified analysis of stochastic gradient methods for nonconvex federated optimization. *arXiv preprint arXiv:2006.07013*, 2020.

Zhize Li, Dmitry Kovalev, Xun Qian, and Peter Richtárik. Acceleration for compressed gradient descent in distributed and federated optimization. In *International Conference on Machine Learning*, 2020.

Xiangru Lian, Ce Zhang, Huan Zhang, Cho-Jui Hsieh, Wei Zhang, and Ji Liu. Can decentralized algorithms outperform centralized algorithms? a case study for decentralized parallel stochastic gradient descent. In *Advances in Neural Information Processing Systems (NIPS)*, 2017.

Konstantin Mishchenko, Eduard Gorbunov, Martin Takáč, and Peter Richtárik. Distributed learning with compressed gradient differences. *arXiv preprint arXiv:1901.09269*, 2019.

Konstantin Mishchenko, Filip Hanzely, and Peter Richtárik. 99% of worker-master communication in distributed optimization is not needed. In *Proceedings of the 36th Conference on Uncertainty in Artificial Intelligence (UAI)*, volume 124, pages 979–988, 2020.

Yurii Nesterov et al. *Lectures on convex optimization*, volume 137. Springer, 2018.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Constantin Philippenko and Aymeric Dieuleveut. Bidirectional compression in heterogeneous settings for distributed or federated learning with partial participation: tight convergence guarantees. *arXiv preprint arXiv:2006.14591*, 2020.

Mher Safaryan, Egor Shulgin, and Peter Richtárik. Uncertainty principle for communication compression in distributed and federated learning and the search for an optimal compressor. *Information and Inference: A Journal of the IMA*, 2021.

Frank Seide, Hao Fu, Jasha Droppo, Gang Li, and Dong Yu. 1-bit stochastic gradient descent and its application to data-parallel distributed training of speech DNNs. In *Fifteenth Annual Conference of the International Speech Communication Association*, 2014.

Sebastian Stich and Sai Praneeth Karimireddy. The error-feedback framework: Better rates for SGD with delayed gradients and compressed communication. *arXiv preprint arXiv:1909.05350*, 2019.

Sebastian U. Stich, J.-B. Cordonnier, and Martin Jaggi. Sparsified SGD with memory. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Hanlin Tang, Xiangru Lian, Chen Yu, Tong Zhang, and Ji Liu. DoubleSqueeze: Parallel stochastic gradient descent with double-pass error-compensated compression. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, 2020.

Joost Verbraeken, Matthijs Wolting, Jonathan Katzy, Jeroen Kloppenburg, Tim Verbelen, and Jan S Rellermeyer. A survey on distributed machine learning. *ACM Computing Surveys*, 2019.

Cong Xie, Shuai Zheng, Oluwasanmi Koyejo, Indranil Gupta, Mu Li, and Haibin Lin. CSER: Communication-efficient SGD with error reset. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 12593–12603, 2020.

Hang Xu, Chen-Yu Ho, Ahmed M Abdelmoniem, Aritra Dutta, El Houcine Bergou, Konstantinos Karatsenidis, Marco Canini, and Panos Kalnis. Compressed communication for distributed deep learning: Survey and quantitative evaluation. Technical report, KAUST, 2020.