Causal Bandits with Unknown Graph Structure

Abstract

In causal bandit problems the action set consists of interventions on variables of a causal graph. Several researchers have recently studied such bandit problems and pointed out their practical applications. However, all existing works rely on a restrictive and impractical assumption that the learner is given full knowledge of the causal graph structure upfront. In this paper, we develop novel causal bandit algorithms without knowing the causal graph. Our algorithms work well for causal trees, causal forests and a general class of causal graphs. The regret guarantees of our algorithms greatly improve upon those of standard multi-armed bandit (MAB) algorithms under mild conditions. Lastly, we prove our mild conditions are necessary: without them one cannot do better than standard MAB bandit algorithms.

1 Introduction

A multi-armed bandit (MAB) problem is one of the classic models of sequential decision making (Auer et al., 2002; Agrawal and Goyal, 2012, 2013a). Statistical measures such as regret and sample complexity measure how fast learning algorithms achieve near optimal performance in bandit problems. However, both regret and sample complexity for MAB problems necessarily scale with the number of actions without further assumptions. To address problems with a large action set, researchers have studied various types of structured bandit problems where additional assumptions are made on the structure of the reward distributions of the various actions. Algorithms for structured bandit problems exploit the dependency among arms to reduce the regret or sample complexity. Examples of structured bandit problems include linear bandits (Abbasi-Yadkori et al., 2011; Agrawal and Goyal, 2013b), sparse linear bandits (Abbasi-Yadkori et al., 2012), and combinatorial bandits (Cesa-Bianchi and Lugosi, 2012; Combes et al., 2015).

In this paper, we study a different kind of structured bandit problems: *causal bandits*. In this setting, actions are composed of interventions on variables of a causal graph. Many real world problems can be modeled via causal bandits. In healthcare applications, the physician adaptively adjusts the dosage of multiple drugs to achieve some desirable clinical outcome (Liu et al., 2020). In email campaign problems, marketers adjust for features of commercial emails to attract more customers and convert them into loyal buyers (Lu et al., 2019; Nair et al., 2021). Genetic engineering also involves direct manipulation of one or more genes using biotechnology, such as changing the genetic makeup of cells to produce improved organisms (Wikipedia contributors, 2021). Recently there has been a flurry of works (Lattimore et al., 2016; Sen et al., 2017; Lee and Bareinboim, 2018; Lu et al., 2019; Lee and Bareinboim, 2019; Nair et al., 2021) on causal bandits that show how to achieve simple regret or cumulative regret not scaling with the action set size.

However, a major drawback of existing work is that they require significant prior knowledge. All existing works require that the underlying causal graph is given upfront. Some regret analysis works even assume knowing certain probabilities for the causal model. In practice, they are all strong assumptions.

In this paper, our goal is to develop causal bandit algorithms that 1) do not require prior knowledge of the causal graph and 2) achieve stronger worst-case regret guarantees than non-causal algorithms such as Upper Confidence Bound (UCB) and Thompson Sampling (TS) whose regret often scales *at least polynomially* with the number of nodes n in the causal graph. Unfortunately, this goal cannot be achieved for general causal graphs. Consider the causal graph consists of isolated variables and the reward directly depends on one of them. Then in the worst case there is no chance to do better than standard algorithms since no meaningful causal relations among variables can be exploited. In this paper, we study what classes of causal graphs on which we can achieve the goal.

Our Contributions. We summarize our contributions below.

1. We first study causal bandit problems where the unknown causal graph is a directed tree, or a causal forest. This setting has wide applications in biology and epidemiology (Greenewald et al., 2019; Burgos et al., 2008; Kontou et al., 2016; Pavlopoulos et al., 2018). We design a novel algorithm **C**entral **N**ode UCB (CN-UCB) that *simultaneously exploits* the reward signal and the tree structure to efficiently find the direct cause of the reward and then applies the UCB algorithm on a reduced intervention set corresponding to the direct cause.

2. Theoretically, we show under certain identifiability assumptions, the regret of our algorithm only scales *logarithmically* with the number of nodes n in the causal graph. To our knowledge, this is the first regret guarantee for unknown causal graph that provably outperforms standard MAB algorithms. We complement our positive result with lower bounds showing the indentifiability assumptions are necessary.

3. Furthermore, we generalize CN-UCB to a more general class of graphs that includes causal trees, causal forests, proper interval graphs, etc. Our algorithm first constructs undirected clique (junction) trees and again simultaneously exploits the reward signal and the junction-tree structure to efficiently find the direct cause of the reward. We also present analogue regret guarantees for this class of graphs.

In many scenarios, our algorithms do *not* recover the full underlying causal graph structure. Therefore, our results deliver the important conceptual message that *exact causal graph recovery is not necessary in causal bandits* since the main target is to maximize the reward.

2 Related work

The causal bandit framework was proposed by Lattimore et al. (2016) and has been studied in various settings since then. In the absence of confounders, Lattimore et al. (2016) and Sen et al. (2017) studied the best arm identification problem assuming that the exact causal graph and the way interventions influence the direct causes of the reward variable are given. Lu et al. (2019) and Nair et al. (2021) proposed efficient algorithms that minimize the cumulative regret under the same assumptions. When confounders exist, Lee and Bareinboim (2018, 2019) developed effective ways to reduce the intervention set using the causal graph before applying any standard bandit algorithm, such as UCB. Even though the performance of above works improved upon that of standard bandit MAB algorithms, they all make the strong assumption of knowing the causal graph structure in advance.

In our setting, the underlying causal graph is not known. Then a natural approach is to first learn the causal graph through interventions. There are many intervention design methods developed for causal graph learning under different assumptions (He and Geng, 2008; Hyttinen et al., 2013; Shanmugam et al., 2015; Kocaoglu et al., 2017; Lindgren et al., 2018; Greenewald et al., 2019; Squires et al., 2020). However, this approach is not sample efficient because it is not necessary to recover the full causal graph in order to maximize rewards. In this paper, we take a different approach which uses the reward signal to efficiently learn the direct causes of the reward.

Our approach is inspired by Greenewald et al. (2019) which proposed a set of central node algorithms that can recover the causal tree structure within $O(\log n)$ single-node interventions. Squires et al. (2020) also extended the central node idea to learn a general class of causal graphs that involves constructing junction trees and clique graphs. Following these works, our causal bandit algorithms also adaptively perform interventions on central nodes to learn the direct causes of the reward variable. However, our algorithms differ from theirs because we also take reward signal into account.

3 Preliminaries

In this section, we follow the notation and terminology of Lattimore et al. (2016); Greenewald et al. (2019) for describing causal models and causal bandit problems.

3.1 Causal Models

A causal model consists of a directed acyclic graph (DAG) D over a set of random variables $\mathcal{X} = \{X_1, \ldots, X_n\}$ and a joint distribution P that factorizes over D. The parents (children) of a variable X_i on graph D, denoted by $\text{Pa}_D(X_i)$ (or $\text{Ch}_D(X_i)$), are the set of variables X_j such that there is a directed edge from X_j to X_i (or from X_i to X_j) on graph D. The set of ancestors (descendants) of a variable X_i, denoted by $\text{An}_D(X_i)$ (or $\text{De}_D(X_i)$), are the set of variables X_j such that there is a path from X_j to X_i (or from X_i to X_j) on D. Without loss of generality, we assume the domain set for every X_i is $\text{Dom}(X_i) = [K] := \{1, \ldots, K\}$. For every X_i, we write the set of neighbors of X_i in graph D as $N_D(X_i)$ including variables X_j such that there is an edge between X_j and X_i regardless of the direction. The maximum degree of an undirected graph G is denoted by $d_{\max}(G)$. Throughout, we denote the true causal graph by D, use $V(\cdot)$ as the set of vertices of a graph and define $\text{skeleton}(\cdot)$ as the undirected graph obtained by replacing the arrows in the directed graph with undirected edges.

Definition 1 (Directed Tree and Causal Tree). *A directed tree is a DAG whose underlying undirected graph is a tree and all its edges point away from the root. A causal tree is a causal model whose underlying causal graph is a directed tree.*

For a node X_i on a directed or undirected tree D and its neighbor $Y \in N_D(X_i)$, we write $B_D^{X_i:Y}$ as the set of nodes that can be reached from Y through any path on the graph (regardless of the directions of edges on the path), when the edge between X_i and Y is cut out from D. Note that the neighbor Y itself is always included in branch $B_D^{X_i:Y}$.

Definition 2 (Central Node (Greenewald et al., 2019)). *A central node v_c of an undirected tree $\mathcal{T}$ with respect to a distribution q over the nodes is one for which $\max_{j \in N_{\mathcal{T}}(v_c)} q(B_{\mathcal{T}}^{v_c:X_j}) \leq 1/2$. At least one such v_c is guaranteed to exist for any distribution q (Jordan, 1869; Greenewald et al., 2019).*

Informally, a central node v_c guarantees that the weight of every branch around v_c cannot be larger than $1/2$ according to the distribution $q(\cdot)$.

Definition 3 (Essential Graph). *The class of causal DAGs that encode the same set of conditional independences is called the Markov equivalence class. Denote the Markov equivalence class of a DAG D by $[D]$. The essential graph of D, denoted by $\mathcal{E}(D)$, has the same skeleton as D, with directed edges $X_i \to X_j$ if such edge direction between X_i and X_j holds for all DAGs in $[D]$, and undirected edges otherwise.*

The chain components of $\mathcal{E}(D)$, denoted by $\text{CC}(\mathcal{E}(D))$, are the connected components of $\mathcal{E}(D)$ after removing all directed edges. Every chain component of $\mathcal{E}(D)$ is a chordal graph (Andersson et al., 1997). Every directed edge in $\mathcal{E}(D)$ is within a v-structure[1] of D (Pearl and Verma, 1995). A DAG whose essential graph has a single chain component is called a *moral* DAG (Greenewald et al., 2019).

Definition 4 (Causal Forest (Greenewald et al., 2019)). *A causal graph is said to be a causal forest if each of the undirected components of the essential graph are trees.*

Many widely used causal DAGs including causal trees and bipartite causal graphs are examples of causal forest (Greenewald et al., 2019). Bipartite graph applications can range from biological networks, biomedical networks, biomolecular networks to epidemiological networks (Burgos et al., 2008; Kontou et al., 2016; Pavlopoulos et al., 2018).

3.2 Causal Bandit Problems

In causal bandit problems, the action set consists of interventions (Lattimore et al., 2016). An intervention on node X removes all edges from $\text{Pa}_D(X)$ to X and results in a post-intervention distribution denoted by $P(\{X\}^c | \text{do}(X = x))$ over $\{X\}^c \triangleq \mathcal{X} \setminus \{X\}$. An empty intervention is

---

[1]A v-structure occurs when two variables causally affect one variable: $a \to b \leftarrow c$.

represented by $\mathrm{do}()$. The reward variable $\mathbf{R}$ is real-valued and for simplicity, we assume the reward is only directly influenced by one of the variables in $\mathcal{X}$, which we call the *reward generating variable* denoted by X_R [2]. The learner does not know the identity of X_R. Since there is only one X_R in our setting, the optimal intervention must be contained in the set of single-node interventions as follows: $\mathcal{A} = \{\mathrm{do}(X = x) \mid X \in \mathcal{X}, x \in [K]\}$. Thus, we focus on above intervention set with $|\mathcal{A}| = nK$ throughout the paper.

We denote the expected reward for intervention $a = \mathrm{do}(X = x)$ by $\mu_a = \mathbb{E}[Y|a]$. Then $a^* = \mathrm{argmax}_{a \in \mathcal{A}} \mu_a$ is the optimal action and we assume that $\mu_a \in [0, 1]$ for all a. A random reward for $a = \mathrm{do}(X = x)$ is generated by $R|_a = \mathbb{E}[\mathbf{R}|a] + \varepsilon$, where ε is 1-subGaussian. At every round t, the learner pulls $a_t = \mathrm{do}(X_t = x_t)$ based on the knowledge from previous rounds and observes a random reward R_t and the values of all $X \in \mathcal{X}$. The objective of the learner is to minimize the cumulative regret $R_T = T\mu_{a^*} - \sum_{t=1}^{T} \mu_{a_t}$ without knowing the causal graph D.

We make the following assumptions below.

Assumption 1. *The following three causal assumptions hold:*

- Causal sufficiency: *for every pair of observed variables, all their common causes are also observed.*
- Causal Markov condition: *every node in causal graph G is conditionally independent of its nondescendents, given its parents.*
- Causal faithfulness condition: *any population produced by causal graph G has the independence relations obtained by applying d-separation to it.*

Assumption 1 is commonly made in causal discovery literature (Peters et al., 2012; Hyttinen et al., 2013; Eberhardt, 2017; Greenewald et al., 2019). Equivalently speaking, there is no latent common causes and the correpondence between d-separations and conditional independences is one-to-one.

Assumption 2 (Causal Effect Identifiability). *There exists an $\varepsilon > 0$, such that for any two variables $X_i \to X_j$ in graph D, we have $|P(X_j = x|\mathrm{do}(X_i = x')) - P(X_j = x)| > \varepsilon$ holds for some $x \in Dom(X_j), x' \in Dom(X_i)$.*

Assumption 2 is necessary. It states that if there is a direct causal relation between two variables on the graph, the causal effect strength cannot go arbitrarily small. A similar version of this assumption was also made by Greenewald et al. (2019)) in their causal graph learning algorithms. We show the necessity of this assumption in Section 6. Intuitively, without this assumption, any causal relation among variables cannot be determined through finite intervention samples and $\Omega(\sqrt{nKT})$ worst-case regret is the best one can hope for.

Assumption 3 (Reward Identifiability). *We assume that for all $X \in An(X_R)$, there exists $x \in [K]$ such that $|\mathbb{E}[\mathbf{R}|\mathrm{do}()] - \mathbb{E}[\mathbf{R}|\mathrm{do}(X = x)]| \geq \Delta$, for some universal constant $\Delta > 0$.*

Lastly, we show that Assumption 3 is also necessary. It guarantees a difference on the expected reward between the observations and after an intervention on an ancestor of X_R. In Section 6, we prove that the worst-case regret is again lower bounded by $\Omega(\sqrt{nKT})$ without this assumption.

In the following sections, we describe our causal bandit algorithms that focus on intervention design to minimize regret. Like most intervention design works, our algorithm take the essential graph $\mathcal{E}(D)$ as the input, which can be estimated from enough observational data[3] (He and Geng, 2008; Greenewald et al., 2019; Squires et al., 2020).

4 CN-UCB for trees and forests

We start with introducing our algorithm CN-UCB (Algorithm 1) when the causal graph D is a directed tree. Before diving into details, we summarize our results as follows:

Theorem 1 (Regret Guarantee for Algorithm 1). *Define $B = \max\left\{\frac{32}{\Delta^2} \log\left(\frac{8nK}{\delta}\right), \frac{2}{\varepsilon^2} \log\left(\frac{8n^2K^2}{\delta}\right)\right\}$ and $T_1 = KB(2 + d)\log_2 n$, where $0 < \delta < 1$. Suppose we run CN-UCB with $T \gg T_1$ interventions in total and $T_2 := T - T_1$. Then with*

---

[2]For multiple reward generating variables cases, one can repeatedly run our proposed algorithms and recover each of them one by one.

[3]Observational data is usually much more cheaper than interventional data (Greenewald et al., 2019).

183 *probability at least $1 - \delta$, we have*

$$R_T = \widetilde{O}\left(K \max\left\{ \frac{1}{\Delta^2}, \frac{1}{\varepsilon^2} \right\} d(\log n)^2 + \sqrt{KT} \right), \tag{1}$$

184 *where $d := d_{\max}(\text{skeleton}(D))$ and $\widetilde{O}$ ignores poly-log terms non-regarding to n.*

185 From above results, we see that especially for large n and small maximum degree d, Algorithm 1
186 outperforms the standard MAB bandit approaches that incur $\widetilde{O}(\sqrt{nKT})$ regret.

4.1 Description for CN-UCB

188 Our method contains three main stages. There is no v-structure in a directed tree, so the essential graph
189 obtained from observational data is just the tree skeleton $\mathcal{T}_0$ and we take it as our input in Algorithm 1.
190 In stage 1, Algorithm 1 calls Algorithm 3 to find a directed sub-tree $\widetilde{\mathcal{T}}_0$ that contains X_R by performing
191 interventions on the central node (may change over time) on the tree skeleton. In stage 2, Algorithm 1
192 calls Algorithm 4 to find the reward generating node X_R by central node interventions on $\widetilde{\mathcal{T}}_0$. We
193 prove that X_R can be identified correctly with high probability from the first two stages, so a UCB
194 algorithm can then be applied on the reduced intervention set $\mathcal{A}_R = \{\text{do}(X_R = k) \mid k = 1, \ldots, K\}$
195 for the remaining rounds in stage 3. In the remainder of this section, we explain our algorithm design
196 for each stage in detail and use an example in Figure 1 to show how CN-UCB proceeds step by step.

(a) True causal tree.

(b) Input tree skeleton.

(c) Stage 1 ($t = 0$): intervention on central node X_2.

(d) Stage 1 ($t = 0$) intervention result.

(e) Stage 2 ($t = 1$): intervention on central node X_3.

(f) Stage 2 ($t = 1$) intervention result.

(g) Stage 1 output: directed subtree.

(h) Stage 2 ($t = 0$): intervention on central node X_3.

(i) Stage 2 ($t = 0$): interventions on the children of X_3.

(j) Stage 2 output: only X_7 remains.

Figure 1: Causal Tree Example for CN-UCB procedure.

197 In the beginning of CN-UCB, we collect reward data under empty intervention to obtain the observa-
198 tional reward mean estimate $\hat{R}$, which will be used in later steps to check whether a variable is an
199 ancestor of the true reward generating variable X_R or not.

200 In our example, the true causal graph and its essential graph are displayed in Figure 1a and 1b, where
201 the true reward generating variable is X_7.

202 **Stage 1.** The goal of this stage is to find a *directed* subtree that contains X_R within $O(\log n)$
203 single-node interventions. We achieve this goal by adaptively intervening the central node that

---

Algorithm 1 Central Node Upper Confidence Bound (CN-UCB)

1: **Input:** Tree skeleton $\mathcal{T}_0$, K, Δ, ε, B, T_2.
2: Perform do() for B times, collect $R_1, \dots, R_B$
3: Obtain reward estimate for the empty intervention do(): $\hat{R} \leftarrow \frac{1}{B} \sum_{b=1}^{B} R_b$.
4: **Stage 1:** Find a directed subtree that contains X_R: $\widetilde{\mathcal{T}}_0 \leftarrow$ Find Sub-tree($\mathcal{T}_0, K, B, \varepsilon, \Delta, \hat{R}$).
                                             //call Algorithm 3 in Section B.
5: **Stage 2:** Find the key node that generates the reward: $X_R \leftarrow$ Find Key Node($\widetilde{\mathcal{T}}_0, K, B, \Delta, \hat{R}$).
                                             //call Algorithm 4 in Section B.
6: **Stage 3:** Apply UCB algorithm on $\mathcal{A}_R = \{\text{do}(X_R = k) \mid k = 1, \dots, K\}$ for T_2 rounds.

---

may change over time. To illustrate our main idea, we make the following claim for single-node interventions.

Claim 1 (Two outcomes from single-node interventions on variable X). *1) Whether X is an ancestor of X_R or not can be determined. 2) The directed subtree induced by X as its root can be found.*

To see the first outcome, we obtain reward estimates under interventions over X. If the difference between any of the reward estimates and $\hat{R}$ is larger than a threshold, Assumption 3 guarantees us that X is an ancestor of X_R.

To see the second outcome, we estimate interventional probabilities $\hat{P}(Y = y|\text{do}(X = x))$ for all $Y \in N_{\mathcal{T}_0}(X)$ and $y, x \in [K]$. Comparing these quantities with the corresponding observational probabilities $P(Y = y)$, the directions of edges between X and its neighbors can be determined due to Assumption 2. Note that in a tree structure, at most one of the neighbors has causal effect on X while others are all causally influenced by X. Once the edges between X and its neighbors are oriented, all other edges in the subtree induced by X (as the root) can be oriented using the property that each variable has at most one parent in a tree structure. Thus, if we learn that X is indeed an ancestor of X_R, a directed subtree can be obtained immediately. Otherwise, we conclude that all the variables in the directed subtree induced by X cannot be X_R.

Then a key question is: how do we adaptively select which variables to intervene? Arbitrarily selecting variables may easily require $O(n)$ single-node interventions. For example, let us consider a graph $X_1 \rightarrow X_2 \rightarrow \cdots \rightarrow X_n$ and the reward generating variable is X_1. If we start from intervening on X_n and everytime move one-node backward towards intervening X_1, we need $O(n)$ single-node interventions in total to figure out the directed subtree containing X_1. To overcome this issue, we adopt the idea of central node algorithm proposed by Greenewald et al. (2019). Interventions on a central node $v_c(t)$ guarantees us to eliminate at least half of the nodes from future searching, because the directed subtree induced by $v_c(t)$ contains more than half of the nodes regarding to the current weighting function $q_t(\cdot)$. And as long as $v_c(t)$ is not found as an ancestor of X_R, the weights $q_{t+1}(\cdot)$ for variables in the directed subtree induced by $v_c(t)$ as the root will be set as zeros. Thus, stage 1 can finish within $O(\log n)$ single-node interventions on $\mathcal{T}_0$.

For the example in Figure 1, CN-UCB takes the tree skeleton in Figure 1b as its input and identifies X_2 as the central node. As Figure 1d shows, the directed subtree induced by root X_2 are crossed out from the candidate set for X_R since intervening on X_2 shows that X_2 is not an ancestor of the true X_R. CN-UCB then identifies X_3 as the central node over the remaining variables(Figure 1e). We will see X_3 is indeed an ancestor of X_7 from interventions on X_3. Thus, X_1 can be crossed out because X_1 is on the upstream direction of X_3 and cannot be the true X_R (Figure 1f). Finally, stage 1 outputs the directed subtree in Figure 1g whose root is X_3.

Stage 2. The goal of this stage is to identify X_R in the directed sub-tree $\widetilde{\mathcal{T}}_0$ within $O(\log n)$ single-node interventions. Similar to stage 1, we determine whether a node X is an ancestor of X_R by performing interventions on it. If we find a variable X that is not an ancestor of X_R according to its reward estimates, all nodes in the sub-tree induced by X can be eliminated from future searching. Otherwise, we continue to intervene on the children of X. Since X_R is unique, at most one child $Y \in \text{Ch}(X)$ is an ancestor of X_R. If such Y exists, we repeat above procedure on the directed sub-tree induced by Y as the root and update weights for all other variables as zeros in the algorithm. Lastly, if none of the children $Y \in \text{Ch}(X)$ appears to be an ancestor of X_R, X itself must be X_R.

We again perform intervention on the central node at the beginning of each round in Algorithm 4 and intervene on its children if necessary. By the definition of central node, every round we can either eliminate at least half of the nodes or finish searching for X_R. Thus, stage 2 can be finished within $O(d \log_2 n)$ single node interventions on $\widetilde{\mathcal{T}_0}$, since the central node at each round has at most d children.

For our example, stage 2 identifies X_3 as the central node showing in Figure 1h. With high probability we can conclude X_3 is indeed an ancestor of $X_7 := X_R$, so stage 2 continues to intervene on its children X_6 and X_7 (Figure 1i). From the intervention results we will see that X_7 is also an ancestor of the true X_R so that X_3 and X_6 can be removed Finally, stage 2 outputs X_7 with high probability (Figure 1j).

Stage 3. Once the first two stages output a variable, we simply apply the UCB algorithm over the reduced intervention set defined in Algorithm 1.

4.2 Extension of CN-UCB to causal forest

Generalizing CN-UCB to causal forest[4] defined in Definition 4 is straightforward. The causal forest version for CN-UCB is presented in Algorithm 5 (Section B). We simply run stage 1 and stage 2 of Algorithm 1 for every chain component (tree structure) of the causal forest essential graph until stage 2 finds the reward generating variable X_R with high probability. Then, a standard UCB algorithm can be applied on the reduced intervention set corresponding to X_R. The regret guarantee for Algorithm 5 is presented in Theorem 2.

Theorem 2 (Regret Guarantee for Algorithm 5). *Suppose we run Algorithm 5 (Section 5) with $T \gg 2KB(d + C) \log_2 n := T_1$ total interventions and $T_2 = T - T_1$, where $0 < \delta < 1$ and $B = \max\left\{ \frac{32}{\Delta^2} \log\left(\frac{8nK}{\delta}\right), \frac{2}{\varepsilon^2} \log\left(\frac{8n^2K^2}{\delta}\right) \right\}$. Define C as the number of chain components in $\mathcal{E}(D)$, then under Assumptions 1, 2 and 3, with probability at least $1 - \delta$, we have*

$$R_T = \widetilde{O}\left(K \max\left\{ \frac{1}{\Delta^2}, \frac{1}{\varepsilon^2} \right\} (d + C)(\log n)^2 + \sqrt{KT} \right), \tag{2}$$

where $\widetilde{O}$ ignores poly-log terms non-regarding to n and $d := \max_{\mathcal{T}_0 \in CC(\mathcal{E}(D))} d_{\max}(\mathcal{T}_0)$.

5 Extension of CN-UCB to a general class of causal graphs

In this section, we extend CN-UCB to more general causal graphs. Our approach involves searching for the rewarding generating node X_R within each undirected chain component of $\mathcal{E}(D)$. In order to use the central node idea, we try to construct tree structures on each component.

5.1 Preliminaries for the general graph class

Before describing our algorithm, we first review definitions of clique (junction) tree and clique graph for an undirected graph G following Squires et al. (2020).

Definition 5 (Clique). *A clique $C \subset V(G)$ is a subset of nodes in which every pair of nodes are connected with an edge. We say a clique C is maximal if for any $v \in V(G) \setminus C$, $C \cup \{v\}$ is not a clique. The maximal cliques set of G is denoted by $\mathcal{C}(G)$ with its clique number defined as $\omega(G) = \max_{C \in \mathcal{C}(G)} |C|$, where $|\cdot|$ denotes the number of nodes.*

Definition 6 (Clique Tree (Junction Tree)). *A clique tree $\mathcal{T}_G$ for G is a tree with maximal cliques $\mathcal{C}(G)$ as vertices that satisfies the junction tree property, i.e. for all $v \in V(G)$, the induced subtree on the set of cliques containing v is a tree. We denote the set of clique trees for graph G by $\mathcal{T}(G)$.*

Definition 7 (Clique Graph). *A clique graph Γ_G is the graph union of $\mathcal{T}(G)$, i.e. $V(\Gamma_G) = \mathcal{C}(G)$ and $U(\Gamma_G) = \cup_{\mathcal{T} \in \mathcal{T}(G)} U(\mathcal{T})$, where $U(\cdot)$ denotes the set of undirected edges.*

Definition 8 (Directed Clique Tree). *A directed junction tree $\mathcal{T}_D$ of a moral DAG D has the same vertices and adjacencies as a clique tree $\mathcal{T}_G$ of $G = \text{skeleton}(D)$. We use asterisks as wildcards for edge points, e.g. $X_i * \to X_j$ denotes either $X_i \to X_j$ or $X_i \leftrightarrow X_j$. For each ordered pair of*

---

[4]Note that in our setting, causal forest refers to a type of causal graph. This should not be confused with the causal forest machine learning method which is similar to random forest.

Algorithm 2 CN-UCB for General Causal Graph

1: **Input:** essential graph $\mathcal{E}(D), K, \Delta, \varepsilon, B, T_2$.
2: **Initialize:** found $\leftarrow$ False
3: Perform do() for B times, collect reward data $R_1, \ldots, R_B$; $\hat{R} \leftarrow \frac{1}{B} \sum_{b=1}^{B} R_b$.
4: **for** $G \in \text{CC}(\mathcal{E}(D))$ **do**
5:     **Stage 1:** Create a junction tree $\mathcal{T}_G$ and find a directed sub-junction-tree that contains X_R:
    $\widetilde{\mathcal{T}}_G \leftarrow$ Find Sub-junction-tree$(G, \mathcal{T}_G, K, B, \varepsilon, \Delta, \hat{R})$.   //call Algorithm 7 in Section B.
6:     **if** $\widetilde{\mathcal{T}}_G$ is not empty **then**
7:         **Stage 2:** Find a clique in $\widetilde{\mathcal{T}}_G$ that contains X_R: $C_0 \leftarrow$ Find Key Clique$(\widetilde{\mathcal{T}}_G, K, B, \Delta, \hat{R})$.
                                             //call Algorithm 8 in Section B.
8:         **Stage 3:** Apply UCB algorithm on $\mathcal{A}_{C_0} = \{\text{do}(X = k) \mid X \in V(C_0), k = 1, \ldots, K\}$ for
        T_2 rounds.
9:         **break**
10:     **end if**
11: **end for**

---

289   *adjacent cliques $C_1 * - * C_2$ we orient the edge mark of C_2 as: 1) $C_1 * \to C_2$ if for $\forall v_{12} \in C_1 \cap C_2$*
290   *and $\forall v_2 \in C_2 \setminus C_1$, we have $v_{12} \to v_2$ in the DAG D or 2) $C_1 * - C_2$ otherwise.*

291   **Definition 9** (Directed Clique Graph). *The directed clique graph Γ_D of a moral DAG D is the graph*
292   *union of all directed clique trees of D. The procedure of graph union is the same as Definition 8.*

293   **Definition 10** (Intersection Comparable (Squires et al., 2020)). *A pair of edges $C_1 - C_2$ and $C_2 - C_3$*
294   *on a clique graph are intersection comparable if $C_1 \cap C_2 \subseteq C_2 \cap C_3$ or $C_1 \cap C_2 \supseteq C_2 \cap C_3$.*

295   Intersection-incomparable chordal graphs were introduced as "uniquely representable chordal graphs"
296   in Kumar and Madhavan (2002). This class includes many familiar graph classes such as causal
297   trees, causal forests and proper interval graphs (Squires et al., 2020). A clique graph is said to be
298   intersection-incomparable if above intersection-comparable relation does not hold for any pair of
299   edges. In this section, we design our algorithm for graph D such that for every chain component
300   $G \in \text{CC}(\mathcal{E}(D))$, its clique graph Γ_G is intersection-incomparable. Otherwise, it is challenging for
301   central node based algorithms (Squires et al., 2020).

5.2   CN-UCB for general causal graphs

303   Our approach for causal bandit problems with general causal graphs is similar as previous settings.
304   We try to find a subset of variables $\mathcal{X}_{\text{sub}}$ that contain the true reward generating node X_R with high
305   probability and then apply UCB algorithm on interventions over $\mathcal{X}_{\text{sub}}$.

306   Our method is presented in Algorithm 2. We search for X_R in every chain component $G \in \text{CC}(\mathcal{E}(D))$
307   separately. In stage 1, we create a junction tree $\mathcal{T}_G$ and search for a directed sub-junction-tree $\widetilde{\mathcal{T}}_G$
308   that contains X_R via Algorithm 7. If such a $\widetilde{\mathcal{T}}_G$ exists, we keep searching for a clique C_0 in $\widetilde{\mathcal{T}}_G$ that
309   contains X_R in stage 2 via Algorithm 8 and apply UCB algorithm on single-node interventions over
310   variables in C_0. Otherwise, we repeat above procedure for the next chain component.

311   Stage 1 and stage 2 in Algorithm 2 also use the idea of central node interventions. But different from
312   previous settings, Algorithm 7 and Algorithm 8 proceed by performing interventions on variables in
313   the central clique that changes over time and every central clique intervention can eliminate at least
314   half of the cliques on $\mathcal{T}_G$ or $\widetilde{\mathcal{T}}_G$ from future searching. A central clique for a junction tree is defined
315   in the same way as a central node for a tree in that we just treat the cliques on a junction tree as the
316   "node" in Definition 2.

317   **Remark on the intersection-incomparable property.**   We now explain why we need the
318   intersection-incomparable property like other central node based algorithm that also involves con-
319   structing clique graphs (Squires et al., 2020). In general, it is possible for a directed junction tree
320   $\mathcal{T}$ to have v-structures over cliques, which can make us unable to finish searching for a directed
321   sub-junction-tree that contains X_R by intervening on variables in $O(\log |\mathcal{T}|)$ cliques, where $|\mathcal{T}|$
322   denotes the number of cliques on $\mathcal{T}$. The reason is, a clique node may have more than one clique
323   parents in $\mathcal{T}$, so that we cannot eliminate more than half of the cliques by interventions over the
324   central clique. In total, we may need to perform $O(n)$ single-node interventions to find X_R and

incur $O(n)$ regret. However, for every chain component G of the essential graph, if its clique graph Γ_G is intersection-incomparable, then there is no v-structure over cliques in any junction tree $\mathcal{T}_G$ of G (Squires et al., 2020), i.e. every node has at most one parent node.

We present the regret guarantee for Algorithm 2 below.

Theorem 3 (Regret guarantee for Algorithm 2). *Define* $0 < \delta < 1$ *and* $B = \max\left\{\frac{32}{\Delta^2}\log\left(\frac{8nK}{\delta}\right), \frac{2}{\varepsilon^2}\log\left(\frac{8n^2K^2}{\delta}\right)\right\}$. *Suppose we run Algorithm 2 for* $T \gg B + KB\log_2 n\left(\omega(G_R) + d\omega(G_R) + \sum_{G\in CC(\mathcal{E}(D))}\omega(G)\right) := T_1$ *total number of interventions and* $T_2 := T - T_1$. *Then under Assumptions 1, 2 and 3, with probability at least* $1 - \delta$, *we have*

$$R_T = \widetilde{O}\left(\left(d\omega(G_R) + \sum_{G\in CC(\mathcal{E}(D))}\omega(G)\right) K \max\left\{\frac{1}{\Delta^2}, \frac{1}{\varepsilon^2}\right\}(\log n)^2 + \sqrt{\omega(G_R)KT}\right) \quad (3)$$

where $d := \max_{G\in CC(\mathcal{E}(D))} d_{\max}(G)$. G_R *denotes the chain component that contains the true* X_R.

Above regret bound shows that our algorithm outperforms standard MAB algorithms especially when n is large and the maximum degree d and the clique numbers $\omega(G)$ are small . Also, above result reduces to Theorem 2 when D is a causal forest, because $\omega(G)$ is always 2 for tree-structure chain components.

6 Lower bounds

In this section we show without Assumption 2 or 3, any algorithm will incur an $\Omega\left(\sqrt{nkT}\right)$ regret in the worst-case, which is exponentially worse than our results in terms of n.

Definition 11 (nK-arm Gaussian Causal Bandit Class). *For a bandit instance in* nK-arm Gaussian *causal bandit class, actions are composed by single-node interventions over* n *variables* $\mathcal{X} = \{X_1, \ldots, X_n\}$: $\mathcal{A} = \{do(X_i = x)|x \in [K]; i = 1, \ldots, n\}$ *with* $|\mathcal{A}| = nK$. *The reward for every action is Gaussian distributed and is directly influenced by one of* $\mathcal{X}$.

Theorem 4 (Minimax Lower Bound Without Assumption 2). *Let* $\mathcal{E}$ *be the set of* nK-armed Gaussian *bandits (Definition 11) where the instances in* $\mathcal{E}$ *does not satisfy Assumption 2. We show that the minimax regret is* $\inf_{\pi\in\Pi}\sup_{\nu\in\mathcal{E}}\mathbb{E}[R_T(\pi,\nu)] = \Omega(\sqrt{nKT})$, *where* Π *denotes the set of all policies.*

Theorem 5 (Minimax Lower Bound (Assumption 2 holds but Assumption 3 does not hold)). *Let* $\mathcal{E}$ *be the set of* nK-armed Gaussian bandits (Definition 11) where the instances in $\mathcal{E}$ satisfy Assumption 2 *but does not satisfy Assumption 3. We show that the minimax regret is* $\inf_{\pi\in\Pi}\sup_{\nu\in\mathcal{E}}\mathbb{E}[R_T(\pi,\nu)] = \Omega(\sqrt{nKT})$, *where* Π *denotes the set of all policies.*

7 Discussion

In this paper, we studied causal bandit problems with unknown causal graph structures. We proposed an efficient algorithm CN-UCB for the causal tree setting. The regret of CN-UCB scales logarithmically with the number of variables n when the intervention size is nK. CN-UCB was then extended to broader settings where the underlying causal graph is a causal forest or belongs to a general class of graphs. For the later two settings, our regret again only scales logarithmically with n. Lastly, we provide lower bound results to justify the necessity of our assumptions on the causal effect identifiability and the reward identifiability. Our approaches are the first set of causal bandit algorithms that do not rely on knowing the causal graph in advance and can still outperform standard MAB algorithms.

There are several directions for future work. First, one can generalize CN-UCB to the multiple reward generating node setting, i.e. more than one variable directly influence the reward. We expect this can be done by repeatedly applying stage 1 and 2 in CN-UCB to find all the reward generating nodes one by one and apply a standard MAB algorithm on the reduced intervention set. In this setting, it is natural to consider interventions that can be performed on more than one variables. Second, it will be interesting to develop instance dependent regret bounds, for example, through estimating the probabilities over the causal graph in CN-UCB. Lastly, one can also develop efficient algorithms that do not need to know the causal graph when confounders exist.

References

Abbasi-Yadkori, Y., Pál, D., and Szepesvári, C. (2011). Improved algorithms for linear stochastic bandits. In *NIPS*, volume 11, pages 2312–2320.

Abbasi-Yadkori, Y., Pal, D., and Szepesvari, C. (2012). Online-to-confidence-set conversions and application to sparse stochastic bandits. In *Artificial Intelligence and Statistics*, pages 1–9. PMLR.

Agrawal, S. and Goyal, N. (2012). Analysis of thompson sampling for the multi-armed bandit problem. In *Conference on Learning Theory*, pages 39–1.

Agrawal, S. and Goyal, N. (2013a). Further optimal regret bounds for thompson sampling. In *Artificial intelligence and statistics*, pages 99–107. PMLR.

Agrawal, S. and Goyal, N. (2013b). Thompson sampling for contextual bandits with linear payoffs. In *International Conference on Machine Learning*, pages 127–135.

Andersson, S. A., Madigan, D., Perlman, M. D., et al. (1997). A characterization of markov equivalence classes for acyclic digraphs. *Annals of statistics*, 25(2):505–541.

Auer, P., Cesa-Bianchi, N., and Fischer, P. (2002). Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256.

Burgos, E., Ceva, H., Hernández, L., Perazzo, R. P., Devoto, M., and Medan, D. (2008). Two classes of bipartite networks: nested biological and social systems. *Physical Review E*, 78(4):046113.

Cesa-Bianchi, N. and Lugosi, G. (2012). Combinatorial bandits. *Journal of Computer and System Sciences*, 78(5):1404–1422.

Combes, R., Talebi, M. S., Proutiere, A., and Lelarge, M. (2015). Combinatorial bandits revisited. *arXiv preprint arXiv:1502.03475*.

Eberhardt, F. (2017). Introduction to the foundations of causal discovery. *International Journal of Data Science and Analytics*, 3(2):81–91.

Greenewald, K., Katz, D., Shanmugam, K., Magliacane, S., Kocaoglu, M., Adsera, E. B., and Bresler, G. (2019). Sample efficient active learning of causal trees. In *Advances in Neural Information Processing Systems*, pages 14302–14312.

He, Y.-B. and Geng, Z. (2008). Active learning of causal networks with intervention experiments and optimal designs. *Journal of Machine Learning Research*, 9(Nov):2523–2547.

Hyttinen, A., Eberhardt, F., and Hoyer, P. O. (2013). Experiment selection for causal discovery. *The Journal of Machine Learning Research*, 14(1):3041–3071.

Jordan, C. (1869). Sur les assemblages de lignes. *J. Reine Angew. Math*, 70(185):81.

Kocaoglu, M., Dimakis, A., and Vishwanath, S. (2017). Cost-optimal learning of causal graphs. In *International Conference on Machine Learning*, pages 1875–1884. PMLR.

Kontou, P. I., Pavlopoulou, A., Dimou, N. L., Pavlopoulos, G. A., and Bagos, P. G. (2016). Network analysis of genes and their association with diseases. *Gene*, 590(1):68–78.

Kumar, P. S. and Madhavan, C. V. (2002). Clique tree generalization and new subclasses of chordal graphs. *Discrete Applied Mathematics*, 117(1-3):109–131.

Lattimore, F., Lattimore, T., and Reid, M. D. (2016). Causal bandits: Learning good interventions via causal inference. In *Advances in Neural Information Processing Systems*, pages 1181–1189.

Lattimore, T. and Szepesvári, C. (2018). Bandit algorithms. *preprint*.

Lee, S. and Bareinboim, E. (2018). Structural causal bandits: where to intervene? In *Advances in Neural Information Processing Systems*, pages 2568–2578.

Lee, S. and Bareinboim, E. (2019). Structural causal bandits with non-manipulable variables. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4164–4172.

Lindgren, E. M., Kocaoglu, M., Dimakis, A. G., and Vishwanath, S. (2018). Experimental design for cost-aware learning of causal graphs. *arXiv preprint arXiv:1810.11867*.

Liu, S., See, K. C., Ngiam, K. Y., Celi, L. A., Sun, X., and Feng, M. (2020). Reinforcement learning for clinical decision support in critical care: comprehensive review. *Journal of medical Internet research*, 22(7):e18477.

Lu, Y., Meisami, A., Tewari, A., and Yan, Z. (2019). Regret analysis of causal bandit problems. *arXiv preprint arXiv:1910.04938*.

Nair, V., Patil, V., and Sinha, G. (2021). Budgeted and non-budgeted causal bandits. In *International Conference on Artificial Intelligence and Statistics*, pages 2017–2025. PMLR.

Pavlopoulos, G. A., Kontou, P. I., Pavlopoulou, A., Bouyioukos, C., Markou, E., and Bagos, P. G. (2018). Bipartite graphs in systems biology and medicine: a survey of methods and applications. *GigaScience*, 7(4):giy014.

Pearl, J. and Verma, T. S. (1995). A theory of inferred causation. In *Studies in Logic and the Foundations of Mathematics*, volume 134, pages 789–811. Elsevier.

Peters, J., Mooij, J., Janzing, D., and Schölkopf, B. (2012). Identifiability of causal graphs using functional models. *arXiv preprint arXiv:1202.3757*.

Sen, R., Shanmugam, K., Dimakis, A. G., and Shakkottai, S. (2017). Identifying best interventions through online importance sampling. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 3057–3066. JMLR. org.

Shanmugam, K., Kocaoglu, M., Dimakis, A. G., and Vishwanath, S. (2015). Learning causal graphs with small interventions. *arXiv preprint arXiv:1511.00041*.

Squires, C., Magliacane, S., Greenewald, K., Katz, D., Kocaoglu, M., and Shanmugam, K. (2020). Active structure learning of causal dags via directed clique tree. *arXiv preprint arXiv:2011.00641*.

Wikipedia contributors (2021). Genetic engineering — Wikipedia, the free encyclopedia. https://en.wikipedia.org/w/index.php?title=Genetic_engineering&oldid=1018922014. [Online; accessed 26-April-2021].