Enhancing Robustness against Model Poisoning Attacks in Federated Learning from a Client Perspective

Abstract

Federated learning (FL) is a popular distributed learning framework that trains a global model through iterative communications between a central server and edge devices. Recent works have demonstrated that FL is vulnerable to model poisoning attacks. Several server-based defense approaches (e.g. robust aggregation) have been proposed to mitigate such attacks. However, we empirically show that under extremely strong attacks, these defensive methods fail to guarantee the robustness of FL. More importantly, we observe that as long as the global model is polluted, the impact of attacks on the global model will remain in subsequent rounds even if there are no subsequent attacks. In this work, we propose a client-based defense, named *White Blood Cell for Federated Learning (FL-WBC)*, which can mitigate model poisoning attacks that have already polluted the global model. The key idea of FL-WBC is to identify the parameter space where long-lasting attack effect on parameters resides during local training and squeeze the dimension of that space through regularization. Furthermore, we can derive a certified robustness guarantee against model poisoning attacks and a convergence guarantee to FedAvg after applying our FL-WBC. We conduct experiments on FasionMNIST and CIFAR10 to evaluate the defense against state-of-the-art model poisoning attacks. The results demonstrate that our method can effectively mitigate model poisoning attack impact on the global model within 5 communication rounds with nearly no accuracy drop under both IID and non-IID settings. Our defense is also complementary to existing server-based robust aggregation approaches and can further improve the robustness of FL under extremely strong attacks.

1 Introduction

Federated learning (FL) [1, 2] is a popular distributed learning approach that enables a number of edge devices to train a shared model in a federated fashion without transferring their local training data. However, recent works [3–12] show that it is easy for edge devices to conduct model poisoning attacks by manipulating local training process to pollute the global model through aggregation.

Depending on the adversarial goals, model poisoning attacks can be classified as *untargeted model poisoning attacks* [3–6], which aim to make the global model indiscriminately have a high error rate on any test input, or *targeted model poisoning attacks* [7–12], where the goal is to make the global model generate attacker-desired misclassifications for some particular test samples. Our work focuses on the *targeted model poisoning attacks* introduced in [11, 12]. In this attack, malicious devices share a set of data points with dirty labels, and the adversarial goal is to make the global model output the same dirty labels given this set of data as inputs. Our work can be easily extended to many other model poisoning attacks (e.g., backdoor attacks), which shall be discussed in §4.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Several studies have been done to improve the robustness of FL against model poisoning attacks through robust aggregations [13–17], clipping local updates [7] and leveraging the noisy perturbation [7]. These defensive methods focus on only preventing the global model from being polluted by model poisoning attacks during the aggregation. However, we empirically show that these server-based defenses fail to guarantee the robustness when attacks are extremely strong. More importantly, we observe that as long as the global model is polluted, the impact of attacks on the global model will remain in subsequent rounds even if there are no subsequent attacks, and can not be mitigated by these server-based defenses. Therefore, an additional defense is needed to mitigate the poisoning attacks that cannot be eliminated by robust aggregation and will pollute the global model, which is the goal of this paper.

To achieve this goal, we first propose a quantitative estimator named *Attack Effect on Parameter (AEP)*. It estimates the effect of model poisoning attacks on global model parameters and infers information about the susceptibility of different instantiations of FL to model poisoning attacks. With our quantitative estimator, we explicitly show the long-lasting attack effect on the global model. Based by our analysis, we design a client-based defense named *White Blood Cell for Federated Learning (FL-WBC)*, as shown in Figure 1, which can mitigate the model poisoning attacks that have already polluted the global model. FL-WBC differs from previous server-based defenses in mitigating the model poisoning attack that has already broken through the server-based defenses and polluted the global model. Thus,

Figure 1: Overview of FL-WBC.

our client-based defense is complementary to current server-based defense and enhances the robustness of FL against the model poisoning attack, especially against the extremely strong attacks that can not be mitigated during the aggregation. We evaluate our defense on Fashion-MNIST [18] and CIFAR10 [19] against the model poisoning attack [11] under IID (identically independently distributed) and non-IID settings. The results demonstrate that FL-WBC can effectively mitigate the attack effect on the global model in 1 communication round with nearly no accuracy drop under IID settings, and within 5 communication rounds for non-IID settings, respectively. We also conduct experiments by integrating the robust aggregation with FL-WBC. The results show that even though the robust aggregation is ineffective under extremely strong attacks, the attack can still be efficiently mitigated by applying FL-WBC.

Our key contributions are summarized as follows:

- To the best of our knowledge, this is the first work to quantitatively assess the effect of model poisoning attack on the global model in FL. Based on our proposed estimator, we reveal the reason for the long-lasting effect of a model poisoning attack on the global model.

- We design a defense, which is also the first defense to the best of our knowledge, to effectively mitigate a model poisoning attack that has already polluted the global model. We also derive a robustness guarantee in terms of AEP and a convergence guarantee to FedAvg when applying our defense.

- We evaluate our defense on Fashion-MNIST and CIFAR10 against state-of-the-art model poisoning attacks. The results show that our proposed defense can enhance the robustness of FL in an effective and efficient way, i.e., our defense defends against the attack in fewer communication rounds with less model utility degradation.

2   Related work

Model poisoning attacks in FL   Model poisoning attack can be *untargeted* [3–6] or *targeted* [7–12]. *Untargeted model poisoning attacks* aim to minimize the accuracy of the global model indiscriminately for any test input. For *targeted model poisoning attacks*, the malicious goal is to make the global model misclassify the particular test examples as the attacker-desired target class in its prediction. An adversary using this approach can implant hidden backdoors into the global model so that the images with a trojan trigger will be classified as attacker-desired labels, known as a backdoor attack [7–10]. Another type of targeted model poisoning attack is introduced in [11, 12], which aims to fool the global model to produce adversarial misclassification on a set of chosen inputs with high confidence. Our work focuses on the targeted model poisoning attacks in [11, 12].

Figure 2: Defense performance of Coordinate Median aggregation and Coordinate Trimmed Mean aggregation. The black circle denotes the adversarial rounds for all the strategies in the figure.

Mitigate model poisoning attacks in FL A number of robust aggregation approaches have been proposed to mitigate data poisoning attacks while retaining the performance of FL. One typical approach is to detect and down-weight the malicious client's updates on the central server side [13–16], thus the attack effects on training performance can be diminished. The central server calculates coordinate-wise median or coordinate-wise trimmed mean for local model updates before performing aggregation [13]. Similarly, [14] suggests applying geometric median to local updates that are uploaded to the server. Meanwhile, some heuristic-based aggregation rules [20, 21, 3, 22, 23] have been proposed to cluster participating clients into a benign group and a malicious group, and then perform aggregation on the benign group only. FoolsGold [20] assumes that benign clients can be distinguished from attackers by observing the similarity between malicious clients' gradient updates, but Krum [21, 3] utilizes the similarity of benign clients' local updates instead. In addition, [7, 24] show that applying differential privacy to the aggregated global model can improve the robustness against model poisoning attacks. All these defensive methods are deployed at the server side and their goals are to mitigate model poisoning attacks during aggregation. Unfortunately, Often in extreme cases (e.g. attackers occupy a large proportion of total clients), existing robust aggregation methods fail to prevent the aggregation from being polluted by the malicious local updates showing that it is not sufficient to offer defense via aggregation solely. Therefore, there is an urgent necessity to design a novel local training method in FL to enhance its robustness against model poisoning attacks at the client side, which is complementary to existing robust aggregation approaches.

3 Motivation

Although current server-based defense approaches can defend against model poisoning attacks under most regular settings, it is not clear whether their robustness can still be guaranteed under extremely strong attacks, i.e., with significantly larger numbers of malicious devices involved in training. To investigate the robustness of current methods under such challenging but practical settings, we evaluate Coordinate Median aggregation (CMA) and Coordinate Trimmed Mean aggregation (CTMA) [13] on the model poisoning attack, which is performed by following the settings in [11]. The goal of the attacks is to make the global model misclassify some specified data samples as target classes. In this experiment, we denote a communication round as an adversarial round t_{adv} when malicious devices participate in the training, and N_m malicious devices would participate in training at adversarial rounds. We assume that there are 10 devices involved in training in each round, but increase N_m from 1 to 5 to vary the strength of the attacks. The detailed experiment configurations can be found in Appendix D. The results of confidence that the global model would miss-classify the poisoning data point are shown in Figure 2.

The results show that the effectiveness of both CMA and CTMA dramatically degrade when there are 50% of malicious devices in the adversarial rounds. It is worthy noting that the attack impact on model performance will remain for subsequent rounds even if no additional attacks occur. We observe the same phenomenon in alternative robust aggregation approaches, and more detailed results are presented in §7. Therefore, in order to build a more robust FL system, it is necessary to instantly mitigate the impact of model poisoning attack as long as the global model is polluted by malicious devices. This has motivated us to design FL-WBC to ensure sufficient robustness of FL even under extremely strong attacks.

4   Model Poisoning Attack in FL

To better understand the impact of model poisoning attacks in FL scenarios, we first need to theo-retically analyze how the poisoning attack affects the learning process and provide a mathematical estimation to quantitatively assess the attack effect on model parameters. During this process we come to a deeper understanding of the reasons for the persistence of the attack effect observed in §3. Without loss of generality, we employ FedAvg [1], the most widely applied FL algorithm as the representative FL method throughout this paper.

4.1   Problem Formulation

The learning objective of FedAvg is defined as:

$$\boldsymbol{W} = \min_{\boldsymbol{W}}\{F(\boldsymbol{W}) \triangleq \sum_{k=1}^{N} p^k F^k(\boldsymbol{W})\}, \tag{1}$$

where $\boldsymbol{W}$ is the weights of the global model, N represents the number of devices, F^k is the local objective of the k-th device, p^k is the weight of the k-th device, $p^k \geq 0$ and $\sum_{k=1}^{N} p^k = 1$.

Equation 1 is solved in an iterative device-server communication fashion. For a given communication round (e.g. the t-th), the central server first randomly selects K devices to compose a set of participat-ing devices $\mathbb{S}_t$ and then broadcasts the latest global model $\boldsymbol{W}_{t-1}$ to these devices. Afterwards, each device (e.g. the k-th) in $\mathbb{S}_t$ performs I iterations of local training using their local data. However, the benign devices and malicious devices perform the local training in different manners. Specifically, if the k-th device is benign, in each iteration (e.g. the i-th), the local model $\boldsymbol{W}_{t,i}^k$ on the k-th device is updated following:

$$\boldsymbol{W}_{t,i+1}^k \leftarrow \boldsymbol{W}_{t,i}^k - \eta_{t,i}\nabla F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k), \tag{2}$$

where $\eta_{t,i}$ is the learning rate, $\xi_{t,i}^k$ is a batch of data samples uniformly chosen from the k-th device and $\boldsymbol{W}_{t,0}^k$ is initialized as $\boldsymbol{W}_{t-1}$. In contrast, if the k-th device is malicious, the local model $\boldsymbol{W}_{t,i}^k$ is updated according to:

$$\boldsymbol{W}_{t,i+1}^k \leftarrow \boldsymbol{W}_{t,i}^k - \eta_{t,i}[\alpha\nabla F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k) + (1-\alpha)\nabla F_M(\boldsymbol{W}_{t,i}^k, \pi_{t,i})], \tag{3}$$

where F_M is the malicious objective shared by all the malicious devices. D_M is a malicious dataset that consists of the data samples following the same distribution as the benign training data but with adversarial data labels. All the malicious devices share the same malicious dataset D_M and $\pi_{t,i}$ is a batch of data samples from D_M used to optimize the malicious objective. The goal of the attackers is to make the global model achieve a good performance on the malicious objective (i.e. targeted misclassification on D_M). Considering the obliviousness of attack, the malicious devices also optimize benign objective, and the trade-off between the benign and malicious objective is controlled by α, where $\alpha \in [0, 1]$. Finally, the server averages the local models of the selected K devices and updates the global model as follows:

$$\boldsymbol{W}_t \leftarrow \frac{N}{K}\sum_{k\in\mathbb{S}_t} p^k \boldsymbol{W}_{t,I}^k. \tag{4}$$

4.2   Estimation of Attack Effect on Model Parameters

Based on the above formulated training process, we analyze the impact of poisoning attacks on model parameters. To this end, we denote the set of attackers as $\mathbb{M}$, and introduce a new notation $\boldsymbol{W}_t(\mathbb{S}_i \setminus \mathbb{M})$, which represents the global model weights in the t-th round when all malicious devices in $\mathbb{S}_i(i \leq t)$ do not perform the attack in the i-th training round. Specifically, when $i = t$, $\boldsymbol{W}_t(\mathbb{S}_t \setminus \mathbb{M})$ is optimized following:

$$\boldsymbol{W}_t(\mathbb{S}_t \setminus \mathbb{M}) \leftarrow \frac{N}{K}\sum_{k\in\mathbb{S}_t} p^k \boldsymbol{W}_{t,I}^k(\alpha = 1), \tag{5}$$

where $\boldsymbol{W}_{t,I}^k(\alpha = 1)$ indicates that $\boldsymbol{W}_{t,I}^k$ is trained using Equation 3 with setting $\alpha = 1$ (i.e., the k-th device is malicious). A special case is $\boldsymbol{W}_t(\mathbb{S} \setminus \mathbb{M})$, which means the global model is optimized when all the malicious devices do not conduct attacks before the t-th round. To quantify the attack effect on the global model, we define the Attack Effect on Parameter (AEP) as follows:

Definition 1. *Attack Effect on Parameter (AEP), which is denoted as δ_t, is the change of the global model parameters accumulated until t-th round due to the attack conducted by the malicious devices in the FL system:*

$$\delta_t \triangleq \boldsymbol{W}_t(\mathbb{S} \setminus \mathbb{M}) - \boldsymbol{W}_t. \tag{6}$$

Based on AEP, we can quantitatively evaluate the attack effect on the malicious objective using $F_M(\boldsymbol{W}_t(\mathbb{S} \setminus \mathbb{M}) - \delta_t) - F_M(\boldsymbol{W}_t(\mathbb{S} \setminus \mathbb{M}))$. As Figure 2 illustrates, although $\boldsymbol{W}_t(\mathbb{S} \setminus \mathbb{M})$ keeps updating after an adversarial round and there are no more attacks before the next adversarial round, the attack effect on the global model, i.e., F_M, remains for a number of rounds. Based on such an observation, we assume that the optimization of malicious objective is dominated by δ_t compared to $\boldsymbol{W}_t(\mathbb{S} \setminus \mathbb{M})$, which is learned from the benign objective. Consequently, if the attack effect in round τ remains for further rounds, $\|\delta_{t+1} - \delta_t\|$ should be small for $t \geq \tau$.

To analyze why the attack effect can persist in the global model, we consider the scenario where the malicious devices are selected in round τ_1 and τ_2, but will not be selected between these two rounds. We derive an estimator of δ_t for $\tau_1 < t < \tau_2$, denoted as $\hat{\delta}_t$:

$$\hat{\delta}_t = [\sum_{k \in \mathbb{S}_t} p^k \prod_{i=0}^{I-1} (\boldsymbol{I} - \eta_{t,i} \boldsymbol{H}_{t,i}^k)] \hat{\delta}_{t-1}, \tag{7}$$

where $\boldsymbol{H}_{t,i}^k \triangleq \nabla^2 F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k)$. The derivation process is presented in Appendix E. Note that, we do not restrict the detailed malicious objective during derivation, and thus our estimator and analysis can be extended to other attacks, such as backdoor attacks.

4.3 Unveil Long-lasting Attack Effect

The key observation from Equation 7 is that if $\hat{\delta}_\tau$ is in the kernel of each $\boldsymbol{H}_{t,i}^k$ for i-th iteration where $k \in \mathbb{S}_t$ and $t > \tau$, then $\hat{\delta}_t$ will be the same as $\hat{\delta}_\tau$, which keeps AEP in the global model. Based on this observation, we discover that **the reason why attack effects remain in the aggregated model is that the AEPs reside in the kernel of $\boldsymbol{H}_{t,i}^k$.** To validate our analysis, we conduct experiments on Fashion-MNIST with model poisoning attacks in FL. The experiment details and results are shown in Appendix B. The results show that $\|\boldsymbol{H}_{t,i}^k \delta_t\|_2$ would be nearly 0 under effective attacks. We also implement attack boosting by regularizing δ_t to be in the kernel of $\boldsymbol{H}_{t,i}^k$.

The above theoretical analysis and experiment results suggest that all the server-based defense methods (e.g. robust aggregation) will not be able efficiently mitigate the impact of model poisoning attacks to the victim global model. The fundamental reason for the failure of these mitigations is that: **the transmission of AEP δ_t in global model is determined by $\boldsymbol{H}_{t,i}^k$, which is inaccessible by the central server.** Therefore, it is necessary to design an effective defense mechanism at client side aiming at mitigating attack that has already polluted the global model to further enhance the robustness of FL.

5 FL-WBC

5.1 Defense Formulation

Our aforementioned analysis shows that AEP resides in the kernels of the Hessian matrix that is generated during the benign device's local training. In this section, we propose *White Blood Cell for Federated Learning (FL-WBC)* to efficiently mitigate the attack effect on the global model. In particular, we reform the local model training of benign devices to achieve two goals:

- Goal 1: To maintain the benign task's performance, loss of local benign task should be minimized.
- Goal 2: To prevent AEP from being hidden in the kernel of Hessian matrices on benign devices, the rank of $\boldsymbol{H}_{t+1,i}^k$ should be maximized, which is equivalent to minimize the dimension of $\boldsymbol{H}_{t+1,i}^k$'s kernel.

Performing regularization on $\boldsymbol{H}_{t,i}^k$ is helpful for squeezing the dimension of $\boldsymbol{H}_{t+1,i}^k$'s kernel. However, it is computationally unaffordable to perform the regularization on $\boldsymbol{H}_{t,i}^k$ due to its high dimensions.

Therefore, in order to achieve Goal 2, we consider the essence of $\boldsymbol{H}_{t,i}^k$, i.e., second-order partial derivatives of the loss function, where the diagonal elements describe the change of gradients $\nabla F^k(\boldsymbol{W}_{t,i+1}^k) - \nabla F^k(\boldsymbol{W}_{t,i}^k)$ across iterations. We assume a fixed learning rate is applied for each communication round, and then $\nabla F^k(\boldsymbol{W}_{t,i+1}^k) - \nabla F^k(\boldsymbol{W}_{t,i}^k)$ can be approximated by $(\Delta \boldsymbol{W}_{t,i+1}^k - \Delta \boldsymbol{W}_{t,i}^k)/\eta_{t,i}$. In the experiments presented in §4.3, we observe that $\boldsymbol{H}_{t,i}^k$ has more than 60% elements to be zero in the most of iterations. When $\boldsymbol{H}_{t,i}^k$ is highly sparse, we set its diagonal, which is approximately $(\Delta \boldsymbol{W}_{t,i+1}^k - \Delta \boldsymbol{W}_{t,i}^k)/\eta_{t,i}$, to be non-zero for increasing the rank of $\boldsymbol{H}_{t,i}^k$. Formally, we have the following objective functions with respect to $\boldsymbol{W}$ to optimize $\boldsymbol{W}_{t,i+1}^k$:

$$\textbf{Achieving Goal 1:} \quad \min_{\boldsymbol{W}} F^k(\boldsymbol{W}), \tag{8}$$

$$\textbf{Achieving Goal 2:} \quad \max_{\boldsymbol{W}} \||(\boldsymbol{W} - \boldsymbol{W}_{t,i}^k) - \Delta \boldsymbol{W}_{t,i}^k|/\eta_{t,i} - |\Upsilon|\|_0, \tag{9}$$

where Υ is a threshold matrix with the same shape of $\boldsymbol{W}$, we apply it as the lower bound of the magnitude of elements in $(\Delta \boldsymbol{W}_{t,i+1}^k - \Delta \boldsymbol{W}_{t,i}^k)/\eta_{t,i}$.

5.2 Defense Solution

Considering that objective of Goal 2 is non-differentiable, we apply Proximal Gradient Decent [25] for optimization. We apply gradient decent to achieve Goal 1 and the proximal operator to solve Goal 2. Formally, we have two steps to optimize $\boldsymbol{W}_{t,i+1}^k$:

$$\boldsymbol{W}_{t,i+1}^{\hat{k}} = \boldsymbol{W}_{t,i}^k - \eta_{t,i} \nabla F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k), \tag{10}$$

$$\boldsymbol{W}_{t,i+1}^k = \arg\min_{\boldsymbol{W}} [-\lambda \||(\boldsymbol{W} - \boldsymbol{W}_{t,i}^k) - \Delta \boldsymbol{W}_{t,i}^k|/\eta_{t,i} - |\Upsilon|\|_0 + \frac{1}{2}\|\boldsymbol{W} - \boldsymbol{W}_{t,i+1}^{\hat{k}}\|_2], \tag{11}$$

where λ in Equation 11 controls the trade-off between the objective of proximal operator and the smoothness of convergence. In this work, we set $\lambda = \infty$ to guarantee the effectiveness of proposed defense effect, and hence Equation 11 can be rewritten as:

$$\boldsymbol{W}_{t,i+1}^k = \arg\min_{\boldsymbol{W}} \|\boldsymbol{W} - \boldsymbol{W}_{t,i+1}^{\hat{k}}\|_2, \tag{12}$$

$$s.t. \||(\boldsymbol{W} - \boldsymbol{W}_{t,i}^k) - \Delta \boldsymbol{W}_{t,i}^k|/\eta_{t,i} - |\Upsilon|\|_0 = SZ_{\boldsymbol{W}}, \tag{13}$$

where $SZ_{\boldsymbol{W}}$ denotes the number of elements in $\boldsymbol{W}$. Note that we have different choices of Υ. In this work, we set Υ as Laplace noise with $mean = 0$ and $variance = s$, since the randomness of Υ will make attackers harder to determine the defense strategy. Specifically, our defense is to find the elements in $\boldsymbol{W}_{t,i+1}^{\hat{k}}$ whose corresponding values in $|(\boldsymbol{W}_{t,i+1}^{\hat{k}} - \boldsymbol{W}_{t,i}^k) - \Delta \boldsymbol{W}_{t,i}^k|/\eta_{t,i}$ are smaller than the counterpart in Υ. The detailed algorithm describing the local training process on benign devices when applying FL-WBC can be found in Appendix A.

5.3 Certified Robustness Guarantee

We define our *certified robustness guarantee* as the distance of AEP between the adversarial round and the subsequent rounds where FL-WBC is applied. A larger distance of AEP indicates that FL-WBC can mitigate the attack more efficiently. We first make an assumption for the Hessian matrix after applying our defense:

Assumption 1. *After applying FL-WBC, the new benign training Hessian matrix H' would be nearly full-rank. Following the notation of s as the variance of Υ in Equation 11, the operator H' is bounded below: $\mathbb{E}\|H'\boldsymbol{a}\|_2^2/P \geq s\|\boldsymbol{a}\|_2^2$.*

Additionally, we make assumptions on bounding the norm of AEPs in different rounds and independent distributions of $H_{t,i}^k \delta_{t,i}^k$.

Assumption 2. *The expected norm of AEPs is lower bounded in each round across devices and iterations: $\mathbb{E}_{i \in [I], k \in \mathbb{S}_t} \|\delta_{t,i}^k\|_2^2 \geq \Lambda_t$.*

Assumption 3. *Since local training data have independent distributions, the elements in $H_{t,i}^k \delta_{t,i}^k$ are independent and have expectations of 0 in different rounds across devices and iterations.*

Following the notations in §4 and applying the local training of benign devices in Algorithm 1, which can be found in Appendix A, we have the following theorem for our *robustness guarantee* on FedAvg after applying FL-WBC.

Theorem 1. *Let Assumption 1-3 hold and s, Λ_t, P be defined therein. K denotes the number of devices involved in training for each round. Assuming that poisoning attack happens in round t_{adv} and no attack happens from round t_{adv} to T, then for FedAvg applying FL-WBC we have:*

$$\mathbb{E}\|\hat{\delta}_T - \hat{\delta}_{t_{adv}}\|_2^2 \geq \frac{PIs}{K} \sum_{t=t_{adv}+1}^{T} \eta_{t,I-1}^2 \Lambda_t. \tag{14}$$

Proof. See our proof in Appendix F. $\qquad\square$

6 Convergence Guarantee

In this section, we derive the convergence guarantee of FedAvg [1]—the most popular FL algorithm, with our proposed FL-WBC. We following the notations in §4 describing FedAvg, and the only difference after applying FL-WBC is the local training process of benign devices. Specifically, for the t-th round, the local model on the k-th benign device is updated as:

$$\nabla F^{k'}(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k) = \nabla F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k) + \mathcal{T}_{t,i} \tag{15}$$

$$\boldsymbol{W}_{t,i+1}^k \leftarrow \boldsymbol{W}_{t,i}^k - \eta_{t,i} \nabla F^{k'}(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k), \tag{16}$$

where $\mathcal{T}_{t,i}$ is the local updates generated by the proximal operator in Equation 11.

Our convergence analysis is inspired by [26]. Before presenting our theoretical results, we first make the following Assumptions 4-7 same as [26].

Assumption 4. *$F^1, F^2, ..., F^N$ are L-smooth: $\forall \boldsymbol{V}, \boldsymbol{W}, F^k(\boldsymbol{V}) \leq F^k(\boldsymbol{W}) + (\boldsymbol{V} - \boldsymbol{W})^T \nabla F^k(\boldsymbol{W}) + \frac{L}{2}\|\boldsymbol{V} - \boldsymbol{W}\|_2^2$.*

Assumption 5. *$F_1, F_2, ..., F_N$ are μ-strongly convex: $\forall \boldsymbol{V}, \boldsymbol{W}, F^k(\boldsymbol{V}) \geq F^k(\boldsymbol{W}) + (\boldsymbol{V} - \boldsymbol{W})^T \nabla F^k(\boldsymbol{W}) + \frac{\mu}{2}\|\boldsymbol{V} - \boldsymbol{W}\|_2^2$.*

Assumption 6. *Let ξ_t^k be sampled from the k-th device's local data uniformly at random. The variance of stochastic gradients in each device is bounded: $\mathbb{E}\|\nabla F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k) - \nabla F^k(\boldsymbol{W}_{t,i}^k)\|^2 \leq \sigma_k^2$ for $k = 1, ..., N$.*

Assumption 7. *The expected squared norm of stochastic gradients is uniformly bounded, i.e., $\mathbb{E}\|\nabla F^k(\boldsymbol{W}_{t,i}^k, \xi_{t,i}^k)\|^2 \leq G^2$ for all $k = 1, ..., N$, $i = 0, ..., I-1$ and $t = 0, ..., T-1$.*

We define F^* and F^{k*} as the minimum value of F and F^k and let $\Gamma = F^* - \sum_{k=1}^{N} p_k F^{k*}$. We assume each device has I local training iterations in each round and the total number of rounds is T. Then, we have the following convergence guarantee on FedAvg with our defense.

Theorem 2. *Let Assumptions 4-7 hold and L, μ, σ_k, G be defined therein. Choose $\kappa = \frac{L}{\mu}$, $\gamma = \max\{8\kappa, I\}$ and the learning rate $\eta_{t,i} = \frac{2}{\mu(\gamma + tI + i)}$. Then FedAvg with our defense satisfies*

$$\mathbb{E}[F(\boldsymbol{W}_T)] - F^* \leq \frac{2\kappa}{\gamma + TI}\left(\frac{Q+C}{\mu} + \frac{\mu\gamma}{2}\mathbb{E}\|\boldsymbol{W}_0 - \boldsymbol{W}^*\|^2\right),$$

where

$$Q = \sum_{k=1}^{N} p_k^2 (s + \sigma_k^2) + 6L\Gamma + 8(I-1)^2(s + G^2)$$

$$C = \frac{4}{K} I^2 (s + G^2).$$

Proof. See our proof in Appendix G. $\qquad\square$

7 Experiments

In our experiments, we evaluate FL-WBC against targeted model poisoning attack [11] described in §4 under both IID and non-IID settings. Experiments are conducted on a server with two Intel Xeon E5-2687W CPUs and four Nvidia TITAN RTX GPUs.

7.1 Experimental Setup

Attack method. We evaluate our defense against model poisoning attack shown in [11, 12]. There are several attackers in FL setup and all the attackers share a malicious dataset D_M, whose data points obey the same distribution with benign training data while having adversarial labels. We let all the attackers conduct the model poisoning attack at adversarial rounds t_{adv} simultaneously such that the attack will be extremely strong.

Defense baseline. We compare our proposed defense with two categories of defense methods that have been widely used: (1) **Differential privacy (DP)** improves robustness with theoretical guarantee by clipping the gradient norm and injecting perturbations to the gradients. We adopt both **Central Differential privacy (CDP)** [24] and **Local Differential privacy (LDP)** [24] for comparisons. We set the clipping norm as 5 and 10 for Fashion-MNIST and CIFAR10 respectively following [24] and apply Laplace noise with $mean = 0$ and $variance = \sigma_{dp}$. (2) **Robust aggregation** improves robustness of FL by manipulating aggregation rules. We consider both **Coordinate Median Aggregation (CMA)** [13] and **Coordinate Trimmed-Mean Aggregation (CTMA)** [13] as baselines.

Datasets. To evaluate our defense under more realistic FL settings, we construct IID/non-IID datasets based on Fashion-MNIST and CIFAR10 by following the configurations in [1]. The detailed data preparation can be found in Appendix D. We sample 1 and 10 images from both datasets to construct the malicious dataset D_M corresponding to scenarios D_M having single image and multiple images. Note that, data samples in D_M would not appear in training datasets of benign devices.

Hyperparameter configurations. Each communication round is set to be the adversarial round with probability 0.1. In each benign communication round, there are 10 benign devices which are randomly selected to participate in the training. In each adversarial round, 5 malicious and 5 randomly selected benign devices participate in the training, which means there are 50% attackers involved in adversarial rounds. Additional configurations and model structures can be found in Appendix D.

Evaluation metrics. (1) **Attack metric (Misclassification confidence/accuracy:)** We define misclssification confidence/accuracy as the classification confidence/accuracy of the global model on the malicious dataset. (2) **Robust metric (Attack mitigation rounds):** We define *attack mitigation rounds* as the number of communication rounds after which the misclassification confidence can decrease to lower than 50% or misclassification accuracy can decrease to lower than the error rate for the benign task. (3) **Utility metric (Benign accuracy):** We use the accuracy of the global model on the benign testing set of the primary task to measure the effectiveness of FL algorithms (i.e., FedAvg [1]). The higher the accuracy is, the higher utility is obtained.

7.2 Experimental Results

We first show the results when there is only one image in the malicious dataset. We consider IID and non-IID settings for both Fashion-MNIST and CIFAR10 datasets. Figure 3 shows the misclassification confidence of our defense and the robust aggregation baselines in the first 60 communication rounds. The results show that our defense can more effectively and efficiently mitigate the impact of model poisoning attack in comparison with baseline methods. In particular, FL-WBC can mitigate the impact of model poisoning attack within 5 communication round when s (i.e., variance for Υ) is 0.4 for both IID and non-IID settings. With regard to CMA and CTMA, the attack impact can not be mitigated within 10 subsequent rounds even when β for CTMA is 0.4, where 80% of local updates are trimmed before aggregation. Thus, the robust aggregation baselines fail to mitigate the model poisoning attack under our attack settings.

We also compare our defense with CDP and LDP in terms of *benign accuracy* and *attack mitigation rounds*. We evaluate our defense by varying s from 0.1 to 1, and evaluate DP baselines by changing σ_{dp} from 0.1 to 10. For each defense method, we show the trade-off between *benign accuracy* and *attack mitigation rounds* in Figure 4. We have two key observations: 1) With sacrificing less than 5% benign accuracy, FL-WBC can mitigate the impact of model poisoning attack on the global model in 1 communication round for IID settings, and within 5 communication rounds for non-IID settings

Figure 3: Comparison of misclassification confidence and communication round on FashionMNIST and CIFAR-10 with IID/non-IID settings. The black circle denotes the adversarial rounds.

Figure 4: Comparison of benign accuracy and attack mitigation rounds on FashionMNIST and CIFAR-10 with IID/non-IID settings when D_M has only one image.

respectively. However, CDP and LDP fail to mitigate attack effect within 5 rounds for IID and within 10 rounds for non-IID settings with less than 5% accuracy drop. 2) For non-IID settings where the defense becomes more challenging, FL-WBC can still mitigate the attack effect within 2 rounds with less than 15% benign accuracy drop, but DP can not make an effective mitigation within 3 rounds with less than 30% benign accuracy drop, leading to the unacceptable utility on the benign task. The reason of FL-WBC outperforming CDP and LDP is that FL-WBC only inject perturbations to the parameter space where the long-lasting AEP resides in instead of perturbing all the parameters like DP methods. Therefore, FL-WBC can achieve better robustness with less accuracy drop.

In addition, we also observe that defense for non-IID settings is harder than IID settings, the reason is that under non-IID settings the devices train only a part of parameters [27] when holding only a few classes of data, leading to a sparser $H_{t,i}^k$ that is more likely to have a kernel with a higher dimension.

We also perform evaluations on the malicious dataset which consists of multiple images, and conduct experiments by integrating the robustness aggregation with FL-WBC to demonstrate that FL-WBC is complementary to server-based defenses. The detailed results are presented in Appendix C.

8 Conclusion

We design a client-based defense against the model poisoning attack, targeting at the scenario where the attack that has already broken through the server-based defenses and polluted the global model. The experiment results demonstrate that our defense outperforms baselines in mitigating the attack effectively and efficiently, i.e., our defense successfully defends against the attack within fewer communication rounds with less model utility degradation. In this paper, we focus on the targeted poisoning attack [11, 12], our defense can be easily extended to many other poisoning attacks, such as backdoor attacks, since we do not restrict the malicious objective when deriving AEP.

References

[1] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Artificial Intelligence and Statistics*, 2017.

[2] C. He, S. Li, J. So, X. Zeng, M. Zhang, H. Wang, X. Wang, P. Vepakomma, A. Singh, H. Qiu, *et al.*, "Fedml: A research library and benchmark for federated machine learning," *arXiv preprint arXiv:2007.13518*, 2020.

[3] E. M. E. Mhamdi, R. Guerraoui, and S. Rouault, "The hidden vulnerability of distributed learning in byzantium," *arXiv preprint arXiv:1802.07927*, 2018.

[4] M. Fang, X. Cao, J. Jia, and N. Gong, "Local model poisoning attacks to byzantine-robust federated learning," in *29th {USENIX} Security Symposium ({USENIX} Security 20)*, pp. 1605–1622, 2020.

[5] M. Baruch, G. Baruch, and Y. Goldberg, "A little is enough: Circumventing defenses for distributed learning," *arXiv preprint arXiv:1902.06156*, 2019.

[6] S. Mahloujifar, M. Mahmoody, and A. Mohammed, "Universal multi-party poisoning attacks," in *International Conference on Machine Learing (ICML)*, 2019.

[7] Z. Sun, P. Kairouz, A. T. Suresh, and H. B. McMahan, "Can you really backdoor federated learning?," *arXiv preprint arXiv:1911.07963*, 2019.

[8] E. Bagdasaryan, A. Veit, Y. Hua, D. Estrin, and V. Shmatikov, "How to backdoor federated learning," in *International Conference on Artificial Intelligence and Statistics*, pp. 2938–2948, PMLR, 2020.

[9] H. Wang, K. Sreenivasan, S. Rajput, H. Vishwakarma, S. Agarwal, J.-y. Sohn, K. Lee, and D. Papailiopoulos, "Attack of the tails: Yes, you really can backdoor federated learning," *arXiv preprint arXiv:2007.05084*, 2020.

[10] C. Xie, K. Huang, P.-Y. Chen, and B. Li, "Dba: Distributed backdoor attacks against federated learning," in *International Conference on Learning Representations*, 2019.

[11] A. N. Bhagoji, S. Chakraborty, P. Mittal, and S. Calo, "Analyzing federated learning through an adversarial lens," in *International Conference on Machine Learning*, pp. 634–643, PMLR, 2019.

[12] R. Tomsett, K. Chan, and S. Chakraborty, "Model poisoning attacks against distributed machine learning systems," in *Artificial Intelligence and Machine Learning for Multi-Domain Operations Applications*, vol. 11006, p. 110061D, International Society for Optics and Photonics, 2019.

[13] D. Yin, Y. Chen, R. Kannan, and P. Bartlett, "Byzantine-robust distributed learning: Towards optimal statistical rates," in *International Conference on Machine Learning*, pp. 5650–5659, PMLR, 2018.

[14] K. Pillutla, S. M. Kakade, and Z. Harchaoui, "Robust aggregation for federated learning," *arXiv preprint arXiv:1912.13445*, 2019.

[15] S. Fu, C. Xie, B. Li, and Q. Chen, "Attack-resistant federated learning with residual-based reweighting," *arXiv preprint arXiv:1912.11464*, 2019.

[16] A. F. Siegel, "Robust regression using repeated medians," *Biometrika*, vol. 69, no. 1, pp. 242–244, 1982.

[17] P. W. Holland and R. E. Welsch, "Robust regression using iteratively reweighted least-squares," *Communications in Statistics-theory and Methods*, vol. 6, no. 9, pp. 813–827, 1977.

[18] H. Xiao, K. Rasul, and R. Vollgraf, "Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms," 2017.

[19] A. Krizhevsky, G. Hinton, *et al.*, "Learning multiple layers of features from tiny images," 2009.

[20] C. Fung, C. J. Yoon, and I. Beschastnikh, "Mitigating sybils in federated learning poisoning," *arXiv preprint arXiv:1808.04866*, 2018.

[21] P. Blanchard, E. M. El Mhamdi, R. Guerraoui, and J. Stainer, "Machine learning with adversaries: Byzantine tolerant gradient descent," in *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 118–128, 2017.

[22] F. Sattler, K.-R. Müller, T. Wiegand, and W. Samek, "On the byzantine robustness of clustered federated learning," in *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 8861–8865, IEEE, 2020.

[23] L. Muñoz-González, K. T. Co, and E. C. Lupu, "Byzantine-robust federated machine learning through adaptive model averaging," *arXiv preprint arXiv:1909.05125*, 2019.

[24] M. Naseri, J. Hayes, and E. De Cristofaro, "Toward robustness and privacy in federated learning: Experimenting with local and central differential privacy," *arXiv preprint arXiv:2009.03561*, 2020.

[25] Y. Nesterov, *Introductory lectures on convex optimization: A basic course*, vol. 87. Springer Science & Business Media, 2003.

[26] X. Li, K. Huang, W. Yang, S. Wang, and Z. Zhang, "On the convergence of fedavg on non-iid data," in *International Conference on Learning Representations*, 2019.

[27] A. Li, J. Sun, B. Wang, L. Duan, S. Li, Y. Chen, and H. Li, "Lotteryfl: Personalized and communication-efficient federated learning with lottery ticket hypothesis on non-iid datasets," *arXiv preprint arXiv:2008.03371*, 2020.