Using Membership Inference Attacks to Evaluate Privacy-Preserving Language Modeling Fails for Pseudonymizing Data

Affiliation / Address line
`email@domain`

Abstract

Large pre-trained language models dominate the current state-of-the-art for many natural language processing applications, including the field of clinical NLP. Several studies have found that these can be susceptible to privacy attacks that are unacceptable in the clinical domain where personally identifiable information (PII) must not be exposed.

However, there is no consensus regarding how to quantify the privacy risks of different models. One prominent suggestion is to quantify these risks using membership inference attacks. In this study, we show that a state-of-the-art membership inference attack on a clinical BERT model fails to detect the privacy benefits from pseudonymizing data. This suggests that such attacks may be inadequate for evaluating token-level privacy preservation of PIIs.

1 Introduction

State-of-the-art results in natural language processing typically rely on large pre-trained language models (PLMs) such as BERT (Devlin et al., 2019) or models in the GPT family (Radford et al., 2019). Multiple studies have found that the large number of parameters can cause PLMs to memorize information in their training data unintentionally, making them vulnerable to privacy attacks (Carlini et al., 2019, 2021). At the same time, other studies have shown that training PLMs using domain-specific data yields better results on domain-specific tasks (Lee et al., 2020; Lamproudis et al., 2021). In the clinical domain, these combined findings pose a significant challenge: training PLMs with clinical data is necessary to achieve state-of-the-art results, but PLMs can be vulnerable to privacy attacks that are especially dangerous when training with clinical data. Broadly speaking, these attacks can be divided into two classes: training data extraction attacks and membership inference attacks.

1.1 Privacy Attacks

Training data extraction attacks are the more severe class of attacks. An adversary who successfully mounts such an attack can extract details about training data that were used to train a PLM. Carlini et al. (2021) show that GPT-2 is vulnerable to such attacks. Several studies (Nakamura et al., 2020; Lehman et al., 2021; Vakili and Dalianis, 2021) have tried to mount similar attacks on BERT models. To this date, there are no examples of successful training data extraction attacks targeting BERT models.

Membership inference attacks (MIAs) do not aim to *extract* training data from models. Instead, these attacks try to discern whether or not a datapoint was present in a model's training data. Inferring that a datapoint has been present in the training data is less severe than extracting it but could, for example, reveal if a patient has visited a set of clinics.

MIAs have been proposed as a proxy for measuring the degree of memorization in machine learning models (Shokri et al., 2017; Murakonda and Shokri, 2020; Mireshghallah et al., 2022). In these use cases, the hypothetical attacker is assumed to have very few limitations. In some formulations, the attacker is even assumed to already have access to the training data. By assuming an extremely strong attacker, MIAs are used to estimate a worst-case degree of privacy leakage. Indeed, MIAs are the basis for the ML Privacy Meter proposed by Murakonda and Shokri (2020).

1.2 Protecting Datapoints or Tokens?

One special property of natural language data is that many words in a sentence can be replaced with synonyms without changing the overall semantics of the sentence. This feature is interesting from a privacy perspective, and is the basis for *pseudonymization*.

Pseudonymization is the process of replacing sensitive information with realistic surrogate values. For example, names are replaced with other names or with placeholders. These kinds of sensitive words or phrases are rarely important for the utility of the data, neither for machine learning nor for research purposes (Meystre et al., 2014a,b; Berg et al., 2022; Vakili and Dalianis, 2022). One prominent example of this is MIMIC-III (Johnson et al., 2016) which contains a large number of electronic health records in which sensitive words or phrases have been manually replaced with placeholders. This dataset is widely employed in clinical machine learning and is considered to be relatively safe.

One fundamental assumption of pseudonymization is that the higher-level semantics of a text are not important from a privacy perspective. For example, an electronic health record describing a patient visiting a hospital is not sensitive if we cannot infer *who* the patient is, *when* the visit took place, and so on. One way of viewing this is that the data are not primarily sensitive on the datapoint level, but on the token level.

1.3 MIA and Pseudonymization

Manual pseudonymization is a time-consuming process. Many institutions lack the resources to manually pseudonymize data on the scale required for modern machine learning models or not even the smaller amount of data used by clincans for qualitative research. An alternative is to use *automatic pseudonymization*. Automatic pseudonymizers typically rely on named entity recognition (NER) to detect sensitive information, that are then either replaced with realistic surrogates or with placeholders. However, NER systems are rarely perfectly accurate. Imperfect recall leads to some sensitive entities remaining after processing the data, which is undesirable from a privacy perspective.

Because systems performing automatic pseudonymization miss to detect some sensitive entities, it is important to measure the privacy implications from this. A straight-forward approach is to consider the recall of the NER model that powers the system. This metric can be used to estimate the amount of sensitive entities that remain in the data. This method is less ideal when the data are used to train a machine learning model. Assuming that the trained model has memorized every single sensitive entity is overly pessimistic.

Estimating the privacy risks of models using MIA, as suggested by Mireshghallah et al. (2022), is an attractive option that would allow pseudonymization to be compared to other privacy-preserving techniques. However, MIAs are designed to measure memorization of entire datapoints rather than memorization of sensitive tokens. This poses a challenge to the paradigm of using MIAs to estimate the privacy risks of machine learning models trained using pseudonymized data.

In this study, we show that the state-of-the-art MIA described by Mireshghallah et al. (2022) cannot distinguish between a model trained using real or pseudonymized data. These results suggest that using this attack to quantify privacy risks fails to capture privacy gains from pseudonymizing training data.

2 Experiments

This study closely mirrors the experimental setup used by Mireshghallah et al. (2022) in order to minimize discrepancies stemming from differences in implementation details. The datasets and models are based on resources introduced by Lehman et al. (2021). The aim of the experiments is to examine whether or not membership inference attack can distinguish between a model trained using real or pseudonymized data.

2.1 Data

This study uses the ClinicalBERT-1a model trained by Lehman et al. (2021). They train a model using pseudonymized clinical notes from a subset of MIMIC-III. This specific model is of the same size as BERT-base (Devlin et al., 2019) and uses this model's parameters as a starting point for continued pre-training to adapt the model to the clinical domain. The corpus used to train the model is also available. Mireshghallah et al. (2022) perform their membership inference experiments using the training data for the BERT model and MIMIC-III data that was not used for training the model. The method also needs a reference model, and this study

Figure 1: Our experiments use a filtered subset of MIMIC-III that only contains records with named (but pseudonymized) patients. One subset, the *Pseudo* subset, has been used to create the ClinicalBERT model used as the target for the attack. Another version, refer to as the *Real* dataset, is re-pseudonymized and acts as a stand-in for the original sensitive raw data.

follows their example by also using PubMed-BERT (Gu et al., 2021) for this purpose.

This study focuses specifically on MIA's ability to discern whether or not a model has been trained using pseudonymized data. To ensure that the results reflect this demarcation, a filtered version of MIMIC-III containing only sentences with names is created. This dataset contains a total of 234,015 sentences. A pseudonymized version of the dataset is created in which all names have been replaced with other names.

After replacing all the names, we have two datasets where each sentence differs solely in what names are used. The model used to train the model will be referred to as the *Pseudo* dataset, and the re-pseudonymized dataset will be referred to as the *Real* dataset. This mimics the situation where we have a model trained on *perfectly pseudonymized* training data. Figure 2 illustrates the scenario that is simulated. Ideally, the membership inference attack should indicate that replacing all names with pseudonyms has made the model much safer.

2.2 Predicting Membership

This study uses the same procedures as Mireshghallah et al. (2022) since their method is the current state-of-the-art membership inference attack targeting masked laguage models like BERT. The method works by analyzing how the target model reacts to a datapoint as compared to a reference model. The target and reference models, in our case ClinicalBERT and PubMed-BERT, differ in that the target model has been trained using sensitive data that the reference model has not been exposed to. The reaction can be a variety of different measurements, but in this case we use the loss calculated for every datapoint. These loss values are calculated for three datasets, for both the target model and the reference model:

In-data Parts of the dataset that was used to train the target model. In this study the two datasets described in Section 2.1 fill this function.

Out-data A second dataset known *not* to belong to the target models training data. The same subset of MIMIC-III used by Mireshghallah et al. (2022) is used.

Threshold data A third dataset that is similar to but disjoint from the first two datasets. A subset of i2b2 (Stubbs and Uzuner, 2015) is used, as in Mireshghallah et al. (2022).

The loss values of the target and reference models are compared for the threshold data, resulting in a threshold. This threshold is used to classify which datapoints belong to the *In-data* and which belong to the *Out-data*. The intuition behind this method is that if the target model has memorized a datapoint, then its loss relative to the reference model's loss will be noticeably lower.

This study examines the claim that membership inference attacks can be used to quantify privacy gains from using various privacy-preserving techniques. The scenario modeled in these experiments simulates the situation where the privacy-preserving technique is perfect pseudonymization. Every datapoint with a named patient in the training data for ClinicalBERT has a corresponding datapoint in the *Real* dataset where the name is different. In such a scenario, there are no real names left in the training data to memorize. Thus, the risk of leaking any name of a patient is zero, representing a substantial increase in privacy. If the attack accurately reflects these privacy gains then we would expect it to perform worse when the data has been pseudonymized.

3 Results

Three different attacks are used using three different datasets as the in-data. The accuracy, precision, and recall values of each attack are listed in Table 1. Experiment (A) mirrors the setup used by

Figure 2: This study simulates the scenario in which a perfectly pseudonymized dataset has been used for continued pre-training of a BERT model. The version of MIMIC-III used to create the ClinicalBERT model from Lehman et al. (2021) is re-identified with pseudonyms and is used in experiments (A) and (B). We refer to this dataset as the *Pseudo* dataset. In experiment (C), we simulate the original, pre-pseudonymized MIMIC-III by populating the data with other names and call this version the *Real* dataset.

	In-data	Out-data	Threshold	Accuracy	Precision	Recall
(A)	*Pseudo, random sample*	*Held-out*	*i2b2*	*0.751*	*0.989*	*0.508*
(B)	Pseudo, names only	Held-out	i2b2	0.757	0.989	0.521
(C)	Real, names only	Held-out	i2b2	0.750	0.989	0.507

Table 1: The membership inference attack is run with three different configurations. Experiment (A) uses the random sample of MIMIC-III used in Mireshghallah et al. (2022) as in-data, and all experiments use the same out-data as they do. Experiment (B) and (C) use the datasets described in Section 2.1 for the in-data. The accuracy of each attack is displayed alongside the recall and the precision values.

Mireshghallah et al. (2022). Experiments (B) and (C) use the subsets of MIMIC-III that only contain names. There are only very small differences in the correctness of the classifications, regardless of the configuration used.

Experiments (A) and (B) represent cases where we have not performed any pseudonymization of the training data. That is, the *In-data* are used to train the BERT model without employing any privacy-preserving techniques. Experiment (C) is the result of the simulated scenario where perfect pseudonymization is employed to preserve the privacy of the data. In other words, the model is not exposed to any real names during training. The privacy gains from using this technique are not discernable based on the metrics in Table 1.

4 Discussion & Conclusions

A limitation of this study is that it focuses specifically on protecting names. Future research would benefit from analyzing additional categories of PII. However, the data and models created by Lehman et al. (2021) focus specifically on names. This class of PII is used in this study to facilitate comparisons with earlier studies.

The results from the three experiments in Table 1 are practically indistinguishable from each other. At the same time, experiment (C) represents a scenario in which a very strong privacy-preserving measure has been employed to increase the privacy of the target model. If the MIA is an accurate way of quantifying the privacy benefits of using pseudonymization, then we would expect the MIA to be less accurate in experiment (C).

The fact that the MIA works as well for experiments (A) and (B) as for (C) indicates that using this attack to quantify memorization does so on a datapoint level. This may be useful for evaluating techniques such as differentially private pre-training, which operate on entire datapoints.

The results of our experiments suggest that using this MIA does not accurately quantify the privacy gains from using pseudonymization, which instead operates on the token level. While the scope of this short paper was limited to evaluating a state-of-the-art MIA for BERT models, future research should also evaluate other MIAs and with a wider range of privacy-preserving techniques.

References

Hanna Berg, Aron Henriksson, Uno Fors, and Hercules Dalianis. 2022. De-identification of Clinical Text for Secondary Use: Research Issues. pages 592–599.

Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. 2019. The Secret Sharer: Evaluating and Testing Unintended Memorization in Neural Networks. pages 267–284.

Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. 2021. Extracting Training Data from Large Language Models. In *Proceedings of the 30th USENIX Security Symposium*, pages 2633–2650.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Yu Gu, Robert Tinn, Hao Cheng, Michael Lucas, Naoto Usuyama, Xiaodong Liu, Tristan Naumann, Jianfeng Gao, and Hoifung Poon. 2021. Domain-Specific Language Model Pretraining for Biomedical Natural Language Processing. *ACM Transactions on Computing for Healthcare*, 3(1):2:1–2:23.

Alistair E. W. Johnson, Tom J. Pollard, Lu Shen, Li-wei H. Lehman, Mengling Feng, Mohammad Ghassemi, Benjamin Moody, Peter Szolovits, Leo Anthony Celi, and Roger G. Mark. 2016. MIMIC-III, a freely accessible critical care database. *Scientific Data*, 3(1):160035. Number: 1 Publisher: Nature Publishing Group.

Anastasios Lamproudis, Aron Henriksson, and Hercules Dalianis. 2021. Developing a Clinical Language Model for Swedish: Continued Pretraining of Generic BERT with In-Domain Data. In *Proceedings of the International Conference on Recent Advances in Natural Language Processing (RANLP 2021)*, pages 790–797, Held Online. INCOMA Ltd.

Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. 2020. BioBERT: a pretrained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240.

Eric Lehman, Sarthak Jain, Karl Pichotta, Yoav Goldberg, and Byron Wallace. 2021. Does BERT Pretrained on Clinical Notes Reveal Sensitive Data? In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 946–959, Online. Association for Computational Linguistics.

Stéphane Meystre, Shuying Shen, Deborah Hofmann, and Adi Gundlapalli. 2014a. Can physicians recognize their own patients in de-identified notes? *Studies in Health Technology and Informatics*, 205:778–782.

Stéphane M. Meystre, Óscar Ferrández, F. Jeffrey Friedlin, Brett R. South, Shuying Shen, and Matthew H. Samore. 2014b. Text de-identification for privacy protection: A study of its impact on clinical text information content. *Journal of Biomedical Informatics*, 50:142–150.

Fatemehsadat Mireshghallah, Kartik Goyal, Archit Uniyal, Taylor Berg-Kirkpatrick, and Reza Shokri. 2022. Quantifying Privacy Risks of Masked Language Models Using Membership Inference Attacks. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 8332–8347.

Sasi Kumar Murakonda and Reza Shokri. 2020. ML Privacy Meter: Aiding Regulatory Compliance by Quantifying the Privacy Risks of Machine Learning. ArXiv:2007.09339 [cs].

Yuta Nakamura, Shouhei Hanaoka, Yukihiro Nomura, Naoto Hayashi, Osamu Abe, Shuntaro Yada, Shoko Wakamiya, and Eiji Aramaki. 2020. KART: Privacy Leakage Framework of Language Models Pretrained with Clinical Records. *arXiv:2101.00036 [cs]*. ArXiv: 2101.00036.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. 2017. Membership Inference Attacks Against Machine Learning Models. In *2017 IEEE Symposium on Security and Privacy (SP)*, pages 3–18. ISSN: 2375-1207.

Amber Stubbs and Özlem Uzuner. 2015. Annotating longitudinal clinical narratives for de-identification: The 2014 i2b2/UTHealth corpus. *Journal of Biomedical Informatics*, 58:S20–S29.

Thomas Vakili and Hercules Dalianis. 2021. Are Clinical BERT Models Privacy Preserving? The Difficulty of Extracting Patient-Condition Associations. In *Proceedings of the AAAI 2021 Fall Symposium on Human Partnership with Medical AI: Design, Operationalization, and Ethics (AAAI-HUMAN 2021)*.

Thomas Vakili and Hercules Dalianis. 2022. Utility Preservation of Clinical Text After De-Identification. In *Proceedings of the 21st Workshop on Biomedical Language Processing at ACL 2022*, pages 383–388, Dublin, Ireland. Association for Computational Linguistics.